

0611-52-6,
1903


MANUFACTURING METHOD FOR AROMATIC CARBONATES

The present invention concerns a manufacturing method for aromatic carbonates; more specifically it concerns a manufacturing method for aromatic carbonates in which aromatic carbonates can be continuously and efficiently manufactured from dialkyl carbonate and an aromatic hydroxy compound.

Diphenyl carbonate (DPC) is an industrially useful compound that is used as a raw material in the manufacture of polycarbonate and the like, and the ability to manufacture diphenyl carbonate productively is an industrially useful skill.

It is known in the prior art to obtain diaryl carbonates such as the above-mentioned diphenyl carbonate by reacting dialkyl carbonate and an aromatic hydroxy compound.

For example, methyl phenyl carbonate, diphenyl carbonate, or mixtures of them can be obtained as follows by reacting dimethyl carbonate and phenol.




However, the problem with such reactions is that they are all equilibrium reactions that tend to lead back to the original systems and they have slow reaction rates.

5 In an attempt to solve these problems, various catalysts for raising the reaction rate have been proposed.

It is also known to use reactors equipped with distilling columns in an attempt to distill off alcoholic by-products of the reaction (e.g., methyl alcohol) from the raw materials, product, solvent, and the like and promote a more
10 productive reaction.

Japanese Unexamined Patent Application Disclosure Kokai No. Hei 3-291257 discloses a method for continuously manufacturing aromatic carbonates in which alcohols and other by-products are continuously distilled off with a multistage distillation column to promote the productivity of the
15 reaction, as the reaction product is continuously removed.

It is also known that reactions such as those hereinabove produce alkyl aromatic ether by-products as well as the desired aromatic carbonates. For example, anisole is a by-product of the reaction of dimethyl carbonate and phenol.



20 This anisole by-product apparently results from the decarboxylation of methyl phenyl carbonate, the intended product of the reaction. Thus, reacting dimethyl carbonate and phenol at high temperatures generally increases the

efficiency with which aromatic carbonates are produced, but it also raises the rate at which anisole is produced.

For example, it was reported in a comparative example of Kokai No. Hei 4-9358 that when the reaction was conducted at 195°C in a reaction vessel
5 equipped with a distilling column, the selectivity for anisole was 5 percent, based on the raw material methyl phenyl carbonate. This disclosure also taught that the selectivity for anisole was 0.7 percent, based on the raw material methyl phenyl carbonate, when a multistage distilling column was used at the same temperature. And a working example of Kokai Hei 3-291257 showed that the
10 selectivity for anisole was 0.8 percent, based on the raw material phenol, when the reaction was conducted in a multistage distilling column with a temperature of 204°C at the base.

Kokai Hei 3-291257 and other disclosure documents indicate that high reaction temperatures ranging from 50 to 350°C can be used, but a closer
15 examination of these documents reveals that the highest reaction temperature used in the working examples was 205°C. There are simply no working examples in which dimethyl carbonate and phenol are reacted at higher temperatures, and the higher temperatures are not used because more anisole by-product will be produced, as described hereinabove.

20 In continuous manufacturing methods for aromatic carbonates such as those mentioned hereinabove, unreacted raw materials, catalysts, solvents, and the like are recovered from the reaction column, also referred to as a reactive distillation column, in addition to the reaction product and alcoholic by-products. As a result, aromatic carbonates can be manufactured very efficiently
25 by returning these materials, especially the unreacted raw materials, to the reaction system.

However, in their research, the present inventors discovered that, when attempting to manufacture aromatic carbonates continuously by reacting dialkyl carbonate and an aromatic hydroxy compound, alkyl aromatic ether by-

products such as anisole accumulated in the reactor (where they are produced) when unreacted raw materials were returned to the reaction system. This accumulation of by-product progressively decreases the effective capacity of the reactor and lowers the efficiency with which aromatic carbonates are produced.

- 5 As a result, there is a pressing need to further lower the amount of alkyl aromatic ether by-products resulting from continuous processes for manufacturing aromatic carbonates.

As the present inventors studied the prior art mentioned hereinabove, they discovered that it is possible to manufacture aromatic carbonates at good
10 rates of productivity, while producing little alkyl aromatic ether by-product, by conducting the reaction of dialkyl carbonate and an aromatic hydroxy compound under specific conditions. In particular, they discovered that it is possible to manufacture aromatic carbonates at good rates of productivity while keeping the selectivity for anisole low by selecting specific conditions
15 such as reaction time, amount of catalyst, and fractions of the various components and by conducting the reaction at high temperatures not seen in the working examples of the prior art, thereby completing the invention.

The object of the present invention is to provide a method by which it is possible to manufacture aromatic carbonates from dialkyl carbonate and an
20 aromatic hydroxy compound at good rates of efficiency with low production of alkyl aromatic ether by-product.

The manufacturing method for aromatic carbonates of the invention is characterized by the fact that

the method for manufacturing aromatic carbonates comprising alkyl aryl
25 carbonates, diaryl carbonates, or mixtures of them by reacting dialkyl carbonate and an aromatic hydroxy compound in the presence of a catalyst is improved by conducting the reaction under conditions that satisfy (1) through (4) hereinbelow:

(1) the catalyst used has a catalytic activity such that methyl phenyl carbonate is produced at a rate of at least 0.005 L/mole/h when the reaction temperature is 200°C, the dialkyl carbonate is dimethyl carbonate, the aromatic hydroxy compound is phenol, dimethyl carbonate/phenol = 1 (molar ratio) in the reaction system, and 0.01 molar percent of catalyst is used, based on the amount of phenol used;

(2) the reaction is conducted with
 amount of catalyst c : 0.01 to 5 molar percent based on the aromatic hydroxy compound
 10 reaction time r : 0.05 to 2 h,
 reaction temperature t : 206 to 280°C, and
 molar ratio d of dialkyl carbonate/aromatic hydroxy compound in the reaction system: 0.5 to 2;

(3) the reaction is conducted under conditions satisfying the following
 15 relational expressions

$$g(r,t) \leq 2 \text{ and}$$

$$f(c,r,t,d) \leq 0.02$$

where c is the amount of catalyst used (a molar percentage of the aromatic hydroxy compound), r is reaction time (h), t is reaction temperature (°C), and d is a molar ratio

and

$$g(r,t) = (r) \cdot \exp[36-17 \cdot \{1000/(273 + t)\}]$$

$$f(c,r,t,d) = (c) \cdot (r) \cdot \exp[36-17 \cdot \{1000/(273 + t)\}] \cdot d/(1 + d)^2;$$

and

(4) the selectivity for alkyl aromatic ethers is less than one percent, based
 25 on the amount of aromatic hydroxy compound fed to the reaction.

The preferred dialkyl carbonate in the present invention is dimethyl carbonate or diethyl carbonate.

The preferred aromatic hydroxy compound(s) in the invention are phenol, *m*-, and/or *p*-cresol.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED


A typical example of an alkyl aromatic ether is anisole.

The manufacturing method for aromatic carbonates of the invention is described in concrete terms hereinbelow.

The following specific conditions are used to manufacture aromatic carbonates consisting of alkyl aryl carbonates, diaryl carbonates, or mixtures of them by reacting dialkyl carbonate and an aromatic hydroxy compound in the presence of a catalyst.

First to be described are the dialkyl carbonate, aromatic hydroxy compound, and catalyst used to manufacture aromatic carbonates in the present invention.

Dialkyl carbonates described by general formula (i) hereinbelow are used in the invention.



where R^1 and R^2 are alkyl groups, alkenyl groups, alicyclic groups, or aralkyl groups, R^1 and R^2 may be the same or different, and they may form a ring.

Specific examples of R^1 and R^2 include alkyl groups such as methyl groups, ethyl groups, propyl groups, butyl groups, pentyl groups, hexyl groups, heptyl groups, octyl groups, nonyl groups, and decyl groups;

alkenyl groups, allyl groups, and butenyl groups;

alicyclic groups such as cyclopropyl groups, cyclobutyl groups, cyclopentyl groups, cyclohexyl groups, and cycloheptyl groups;

alkyl groups containing alicyclic groups such as cyclohexylmethyl groups; and

aralkyl groups such as benzyl groups, phenethyl groups, phenylpropyl groups, phenylbutyl groups, and methylbenzyl groups.

These groups may be substituted with lower alkyl groups, lower alkoxy groups, cyano groups, and halogen, and they may contain unsaturated bonds.

Examples of dialkyl carbonate described by formula (i) include dimethyl carbonate, diethyl carbonate, dipropyl carbonate, diallyl carbonate, dibutenyl carbonate, dibutyl carbonate, dipentyl carbonate, dihexyl carbonate, diheptyl carbonate, dioctyl carbonate, dinonyl carbonate, didecyl carbonate, methyl ethyl carbonate, methyl propyl carbonate, methyl butyl carbonate, ethyl propyl carbonate, ethyl butyl carbonate, ethylene carbonate, propylene carbonate, di(methoxymethyl) carbonate, di(methoxyethyl) carbonate, di(chloroethyl) carbonate, di(cyanoethyl) carbonate, dicyclopentyl carbonate, dicyclohexyl carbonate, dicycloheptyl carbonate, dibenzyl carbonate, diphenethyl carbonate, di(phenylpropyl) carbonate, di(phenylbutyl) carbonate, di(chlorobenzyl) carbonate, and di(methoxybenzyl) carbonate.

These dialkyl carbonates may be used in combinations of two or more.

Preferred among these is dialkyl carbonate where each R^1 and R^2 is an alkyl group with no more than four carbon atoms, with dimethyl carbonate and diethyl carbonate more preferred and dimethyl carbonate especially preferred.

The aromatic hydroxy compound used to manufacture aromatic carbonates is described by general formula (ii) hereinbelow.




Ar^1 is a monovalent aromatic group which may have a substituent.

Examples of such aromatic monohydroxy compounds include alkylphenols such as phenol, cresol, xlenol, trimethylphenol, tetramethylphenol, ethylphenol, propylphenol, butylphenol, diethylphenol, methylethylphenol, methylpropylphenol, dipropylphenol, methylbutylphenol, pentylphenol, hexylphenol, and cyclohexylphenol; alkoxyphenols such as methoxyphenol and ethoxyphenol;

naphthols and substituted naphthols;


and substituted phenols described by the formula

5



where A is -O-, -S-, -CO-, SO₂;

10 a substituted alkylene such as



a divalent group such as cycloalkylene, for example



15

or simply a bond.

In these formulas, each R⁴, R⁵, R⁶, and R⁷ is a hydrogen atom, lower alkyl group, cycloalkyl group, aryl group, or aralkyl group, which may be substituted with a halogen atom or alkoxy group. k is an integer ranging in value from 3 to 11, and the hydrogen atoms may be replaced by lower alkyl groups, aryl groups, halogen atoms, or the like.

20


Furthermore, alicyclic groups may be substituted with substituents such as lower alkyl groups, lower alkoxy groups, ester groups, hydroxyl groups, nitro groups, halogen, and cyano groups.

25

Heteroaromatic hydroxy compounds such as hydroxypyridine, hydroxycoumarin, and hydroxyquinoline can also be cited as examples of the aromatic hydroxy compound.

Aromatic dihydroxy compounds can also be used, examples including hydroquinone, resorcinol, catechol, dihydroxynaphthalene,

dihydroxyanthracene, and alkylated forms of them. Aromatic dihydroxy compounds described by the following formula can also be used.






where A is identical to A hereinabove, and the alicyclic may be substituted with a substituent such as a lower alkyl group, lower alkoxy group, ester group, hydroxyl group, nitro group, halogen, or cyano group.

10 In the present invention, aromatic monohydroxy compounds in which Ar^1 in the above-mentioned formula (ii) is an aromatic group with six to 10 carbon atoms are preferred, with phenol, *m*-cresol, and/or *p*-cresol being more preferred, and phenol being especially preferred. Aromatic hydroxy compounds may be used in combinations of two or more.

15 Alkyl aryl carbonates and diallyl carbonates are produced from the above-described dialkyl carbonates and aromatic hydroxy compounds by reactions such as the following. The following examples are reactions using dialkyl carbonates in which R^1 and R^2 in formula (i) are the same.

Specific examples of alkyl aryl carbonates that can be obtained by means
 20 of reaction (1) include methyl phenyl carbonate, ethyl phenyl carbonate, propyl phenyl carbonate, allyl phenyl carbonate, butyl phenyl carbonate, pentyl phenyl carbonate, hexyl phenyl carbonate, heptyl phenyl carbonate, octyl tolyl carbonate, nonyl (ethylphenyl) carbonate, decyl (butylphenyl) carbonate, methyl tolyl carbonate, ethyl tolyl carbonate, propyl tolyl carbonate, butyl tolyl
 25 carbonate, allyl tolyl carbonate, ethyl xylyl carbonate, methyl (trimethylphenyl) carbonate, methyl (chlorophenyl) carbonate, methyl (nitrophenyl) carbonate, methyl (methoxyphenyl) carbonate, methyl cumyl carbonate, methyl (naphthyl) carbonate, methyl (pyridyl) carbonate, ethyl cumyl carbonate, methyl (benzoylphenyl) carbonate, ethyl xylyl carbonate, benzyl xylyl



carbonate, methyl (hydroxyphenyl) carbonate, ethyl (hydroxyphenyl) carbonate, methoxycarbonyloxybiphenyl, methyl (hydroxybiphenyl) carbonate, methyl 2-(hydroxyphenyl)propylphenyl carbonate, and ethyl 2-(hydroxyphenyl)propylphenyl carbonate.

Specific examples of diaryl compounds that can be obtained in reactions (2) and (3) include diphenyl carbonate, ditolyl carbonate, phenyl tolyl carbonate, di(ethylphenyl) carbonate, phenyl (ethylphenyl) carbonate, dinaphthyl carbonate, di(hydroxyphenyl) carbonate, and di[2-(hydroxyphenylpropyl)phenyl] carbonate.

Products obtained using an aromatic dihydroxy compound as the aromatic hydroxy compound are also included in the above-cited examples.

The aromatic carbonates manufactured in the present invention are alkyl aryl carbonates, diaryl carbonates, or mixtures of them, as mentioned hereinabove.

In the present invention, it is preferred to use raw materials that produce alcoholic by-products with lower boiling points than the aromatic carbonate reaction products in the above-described reactions, allowing the aromatic carbonate to be removed from the bottom of the column and the alcoholic by-products to be removed from the top of the column. It is specifically preferred to use methyl phenyl carbonate as the alkyl aryl carbonate and diphenyl carbonate as the diaryl carbonate in the above-described reactions.

It is preferred to manufacture diaryl carbonates as the final aromatic carbonate product.

The above-described reaction of dialkyl carbonate and an aromatic hydroxy compound is conducted in the conventional liquid state in the presence of a catalyst, which must have the following type of catalytic activity.

Namely, the catalytic activity is such that methyl phenyl carbonate (PMC) is produced at a rate of at least 0.005 L/mole/h, preferably at least 0.01 L/mole/h, when the reaction temperature is 200°C, the dialkyl carbonate is dimethyl carbonate (DMC), the aromatic hydroxy compound is phenol (PhOH), dimethyl carbonate/phenol = 1 (molar ratio) in the reaction system, and the amount of catalyst used is 0.01 molar percent, based on the phenol. The production rate for PMC is calculated with the following formula, using k_1 as the rate constant.

$$d[\text{PMC}]/dt = k_1[\text{PhOH}][\text{DMC}] - k_2[\text{PMC}][\text{MeOH}]$$

$$k_1/k_2 = k_{eq} \text{ (equilibrium constant)} = 2.3 \cdot 10^{-3}$$

Catalysts used in the present invention, such as those described hereinabove, may be soluble (homogeneous) or insoluble (heterogeneous) in the reaction fluid.

Examples of the catalyst include Lewis acids, organotin compounds, lead compounds, compounds of the copper family metals, alkali metal complexes, zinc complexes, compounds of the iron family metals, zirconium complexes, and solid catalysts. More specific examples include the following.

Examples of Lewis acids include Lewis acids and transition metal compounds producing Lewis acids such as AlX_3 , TiX_3 , TiX_4 , VOX_3 , VX_5 , ZnX_2 , FeX_3 , and SnX_4 (where X is a halogen, acetoxy group, alkoxy group, or aryloxy group). More specific examples include titanium tetrachloride,

- 5 tetraphenoxytitanium $(Ti(OPh)_4)$, tetracresyloxytitanium, tetramethoxytitanium $(Ti(OMe)_4)$, tetraethoxytitanium, tetraisopropoxytitanium, tetradodecyloxytitanium, tetraisooctyloxytin, and triisopropoxyaluminum.

- Examples of tin compounds include organotin compounds such as
 10 trimethyltin acetate, triethyltin acetate, tributyltin acetate, triphenyltin acetate, dibutyltin diacetate, dibutyltin dilaurate, dioctyltin dilaurate, dibutyltin adipate, dibutyldimethoxytin, dibutyldiphenoxytin, $[(Bu_2Sn(OPh)]_2O$, dimethyltin glycolate, dibutyldiethoxytin, triethyltin hydroxide, hexaethylstannoxane, hexabutylstannoxane, dibutyltin oxide (Bu_2SnO) ,
 15 dioctyltin oxide, butyltin triisooctylate, octyltin triisooctylate, butylstannic acid, octylstannic acid, polymeric tin compounds such as poly[oxy(dibutylstannylene)], and polymeric hydroxystannoxanes such as poly(ethylhydroxystannoxane). Another example is tin oxide.

- Examples of lead compounds include lead oxides such as PbO , PbO_2 ,
 20 and Pb_3O_4 ; lead sulfates such as PbS and Pb_2S ; lead hydroxides such as $Pb(OH)_2$ and $Pb_2O_2(OH)_2$; plumbites such as Na_2PbO_2 , K_2PbO_2 , $NaHPbO_2$, and $KHPbO_2$; plumbates such as Na_2PbO_3 , $Na_2H_2PbO_4$, K_2PbO_3 , $K_2[Pb(OH)_6]$, K_4PbO_4 , Ca_2PbO_4 , and $CaPbO_3$; lead carbonates such as $PbCO_3$, $2PbCO_3 \cdot Pb(OH)_2$, and their basic salts; lead salts and lead carbonates of organic acids and their basic
 25 salts such as $Pb(OCOCH_3)_2$, $Pb(OCOCH_3)_4$, and $Pb(OCOCH_3)_2 \cdot PbO \cdot 3H_2O$; organolead compounds such as R_4Pb , R_3PbCl , R_3PbBr , and R_3Pb or R_6Pb_2 , R_3PbOH , and R_3PbO (where R is an alkyl group such as C_4H_9 or an aryl group such as phenyl); alkoxyleads such as $Pb(OCH_3)_2$, $(CH_3O)Pb(OPh)$, and $Pb(OPh)_2$; aryloxyleads; lead alloys such as $Pb-Na$, $Pb-Ca$, $Pb-Ba$, $Pb-Sn$, and

Pb-Sb; lead minerals such as galena and sphalerite; and hydrates of these lead compounds.

5 Examples of copper family metal compounds include salts and complexes (where acac is a ligand chelated with acetylacetone) of copper family metals such as CuCl, CuCl₂, CuBr, CuBr₂, CuI, CuI₂, Cu(OAc)₂, Cu(acac)₂, copper olefinate, Bu₂Cu, (CH₃O)₂Cu, AgNO₃, AgBr, silver picrate, AgC₆H₆ClO₄Ag(bullvalene)₃NO₃, and [AuC^oC-C(CH₃)₃]_n[Cu(C₇H₈)Cl]₄.

Examples of alkali metal complexes include Li(acac) and LiN(C₄H₉)₂.

Examples of zinc complexes include Zn(acac)₂.

10 Examples of cadmium complexes include Cd(acac)₂.

Examples of iron family metal compounds include Fe(C₁₀H₈)(CO)₅, Fe(CO)₅, CoC₅F₆(CO)₇ [sic], Ni-C₅H₅NO, and ferrocene.

Examples of zirconium complexes include Zr(acac)₄ and zirconocene.

Acac in the above formulas stands for ligands of acetonylacetate.

15 Examples of solid catalysts include silica, alumina, titania, silica-titania, zinc oxide, zirconium oxide, gallium oxide, zeolite, and rare earth oxides.

These catalysts may be mixed with compounds or carriers that are inert in the reaction, and they may be supported on carriers. The catalysts may also be substances that react with the reaction materials and reaction products present in the reaction system, and they may be heat-treated in advance, together with the reaction materials and reaction products.

20 When a homogeneous catalyst is used as the catalyst in the present invention, it may be introduced into the reaction system by a continuous feed to the reaction column. Heterogeneous catalysts may be placed in the reaction column for introduction into the reaction system.

25 When a homogeneous catalyst is continuously fed to the reactor, it may be fed as a mixture with the dialkyl carbonate and/or aromatic hydroxy compound reaction material(s), or it may be fed separately.

In the present invention, where the reaction is conducted under specific conditions such as those described hereinabove, it is necessary to limit the amount of catalyst used with respect to the aromatic hydroxy compound used. Thus, of the various catalysts, homogeneous catalysts are preferred, especially
5 Lewis acids such as tetraphenoxytitanium and tetramethoxytitanium, organotin compounds such as Bu_2SnO , and $[(\text{Bu}_2\text{Sn}(\text{OPh}))_2]$, and alkoxylead compounds such as $\text{Pb}(\text{OPh})_2$.

The reaction of dialkyl carbonate and an aromatic hydroxy compound in the presence of the above-described catalyst can be conducted with a solvent
10 copresent, as desired. A solvent that is inert in the reaction can be used, examples including ethers, aliphatic hydrocarbons, and halogenated aromatic hydrocarbons.

The reaction can also be conducted with gases inert in it such as nitrogen, helium, and argon copresent.

15 Reaction columns that can be used include continuous reactors equipped with distilling columns, typified by reactors having reaction-type distilling columns or distilling columns.

It is preferred to use a reaction-type distilling column with a large vapor-liquid boundary to enhance the productivity of the above-mentioned reaction.
20 Specifically, a multistage distilling column having at least two distilling stages can be used, examples including conventional multistage distilling columns such as plate columns, packed columns, and columns combining plates and packing. It is preferred to have the catalyst present in all stages of such multistage distilling columns. When a solid catalyst is used in a packed
25 column, it can comprise part or all of the packing.

In the present invention, aromatic carbonates can be manufactured by conducting reactions (1) to (3) hereinabove in a single column, or two or more reaction columns may be used to manufacture aromatic carbonates. When two columns are used in the present invention, it is preferred to conduct reaction

(1), which produces principally alkyl aryl carbonate, in the first column and reactions (2) and (3), which produce diaryl carbonate, in the second column.

Alkyl aromatic ether by-products described by Ar^1OR^a or Ar^1OR^b are produced in the reaction column for the reaction of dialkyl carbonate and an aromatic hydroxy compound. When two reaction columns are used, the by-products are produced chiefly in the first column.

For example, anisole is a by-product of the reaction of dimethyl carbonate and phenol is anisole:



In the present invention, it is possible to suppress the production of this alkyl aromatic ether by-product and manufacture aromatic carbonates at high rates of selectivity by conducting the reaction under the following conditions.

15 When aromatic carbonates are manufactured by reacting dialkyl carbonate and an aromatic hydroxy compound in the presence of a catalyst in the present invention, the reaction is conducted under conditions that satisfy (1) to (4) hereinbelow. When two reaction columns are used, it is especially preferred to maintain the reaction conditions indicated hereinbelow in the
20 column used to conduct reaction (1).

Amount of Catalyst Used (c)

Catalyst is used in amounts of 0.01 to 5 molar percent, preferably 0.05 to 3 molar percent, based on the aromatic hydroxy compound.

When a homogeneous catalyst is used in a continuous operation, it is
25 easy to control the amount of catalyst used vis-a-vis the aromatic hydroxy compound.

Reaction Temperature (t)

The reaction is conducted at a temperature of 206 to 280°C, preferably 206 to 250°C. When a distilling column is used as the reactor, the reaction temperature is the temperature at the base of the column.

Reaction Time (r)

- 5 The reaction is conducted for 0.05 to 2 h, preferably 0.1 to 1 h. When the reaction is conducted as a continuous operation, the reaction time is the residence time. When a batchwise operation is used, the reaction time is the residence time at the base of the column.

Molar Ratio (d) for Raw Materials in the Reaction System

- 10 In the present invention, dialkyl carbonate and aromatic hydroxy compound are present in the reaction system at a molar ratio (dialkyl carbonate/aromatic hydroxy compound) of 0.5 to 2, preferably 0.5 to 1.8. When a distilling column is used as the reactor, this is the molar ratio at the base of the column.

The Values $g(r,t)$ and $f(c,r,t,d)$

The reaction is conducted under conditions that satisfy

$g(r,t) \leq 2$, more preferably ≤ 1.8 , most preferably ≤ 1.5 and

$f(c,r,t,d) \leq 0.02$, more preferably ≤ 0.05 , and most preferably ≤ 0.1

- where c is the amount of catalyst used (a molar percentage of the aromatic hydroxy compound), r is reaction time (h), t is reaction temperature (°C), and d is the molar ratio of the raw materials in the reaction system, and

$$g(r,t) = (r) \cdot \exp[36-17 \cdot \{1000/(273 + t)\}]$$

$$f(c,r,t,d) = (c) \cdot (r) \cdot \exp[36-17 \cdot \{1000/(273 + t)\}] \cdot d/(1 + d)^2.$$

- (4) The selectivity for alkyl aromatic ethers is less than 1 percent, more preferably less than 0.5 percent, based on the amount of aromatic hydroxy compound fed to the reaction.

The reaction pressure differs according to the type and construction of the reactor, the reaction materials, and the like, and the reaction may be

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

conducted at reduced, ordinary, or elevated pressure, but it is usually conducted at pressures ranging from 2,600 to 5.4 MPa.

As described hereinabove, the reaction of dialkyl carbonate and an aromatic hydroxy compound in the present invention is conducted at high
5 temperatures not seen in working examples of the prior art (at least 206°C) and under conditions in which amount of catalyst (c), reaction time (r), reaction temperature (t), and raw material molar ratio (d) satisfy both of the relational expressions $g(r,t)$ and $f(c,r,t,d)$.

When the reaction is conducted under such conditions, aromatic
10 carbonate (phenyl methyl carbonate) can be manufactured at high rates of selectivity without increasing the selectivity for alkyl aromatic ether by-product (anisole).

When $g(r,t)$ exceeds 2, anisole production increases, and when $f(c,r,t,d)$ is less than 0.02, the aromatic carbonate yield tends to decline.

15 In the present invention, it is preferred to use a continuous process to manufacture aromatic carbonate by the above-described reaction.

Reaction mixture, which may contain the product of this reaction (aromatic carbonate), alcoholic by-products, unreacted raw materials (dialkyl carbonate and aromatic hydroxy compound), or alkyl aromatic ether by-product, is
20 removed from the top and the bottom of the reaction column.

In the present invention, the unreacted raw materials obtained after the various components of this reaction mixture are separated can be returned to the reaction system.

For example, aromatic carbonate produced in the reaction is
25 continuously removed from the reaction column, usually in a liquid state from the bottom of the column. The aromatic carbonate from the reaction column can then be led to a refining column to be refined.

On the other hand, alcoholic by-products are usually removed from the top of the reaction column.

Unreacted dialkyl carbonate and aromatic hydroxy compound raw materials are continuously removed from the reaction column, after which they can be separated, recovered, and returned to the reaction system.

When these unreacted raw materials are recovered and returned to the reaction system in the present invention, it is preferred to separate the alkyl aromatic ether by-product produced in the reaction column (mainly in the first column when two columns are used) by distillation or the like before returning the unreacted raw materials to the reaction system.

In the present invention, it is possible to manufacture aromatic carbonates in good yields and at good rates of productivity, while keeping the selectivity for alkyl aromatic ether by-product low, by reacting dialkyl carbonate and an aromatic hydroxy compound under certain specified conditions.

The present invention is described concretely hereinbelow by means of working examples, but it is not limited by these examples.

Example 1

A 500 mL autoclave with a packed distilling column (column height: 1 m, column diameter: 1 inch) packed with 3 mm Dixon packing, shown in Drawing 1, was used as the reactor.

A feed pump was used to feed phenol (PhOH) and $\text{Ti}(\text{OPh})_4$ as catalyst (cata.) continuously to the autoclave.

Dimethyl carbonate (DMC) was also fed continuously with a feed pump.

Reaction liquid was continuously removed via a special pipe provided for that purpose in the bottom of the autoclave's column.

The low-boiling-point component containing alcoholic by-products was removed from the top of the distillation column and liquefied with a condenser. A portion of it was removed, and the balance was refluxed through the distillation column. The reflux ratio is shown in Table 1.

The required heat was supplied by heating the autoclave and distillation column with electric furnaces. The raw material feed lines were also heated, using heaters. The procedure was carried out as a continuous operation under the conditions in Table 1. The results are shown in Table 2.

- 5 Table 1 shows column-base temperature r , column-base residence time t calculated from the liquid volume in the bottom of the column and the amount of liquid removed, amount of catalyst c , raw material molar ratio d (DMC/PhOH), and the values $g(r,t)$ and $f(c,r,t,d)$ calculated from r , t , c , and d .

Examples 2-6

- 10 Continuous operations identical to the one in Example 1 were carried out, except that the reaction conditions were varied as shown in Table 1. The results are shown in Table 2.

Example 7

- 15 A 500 mL autoclave having a plate-type distilling column (column height: 3 m, column diameter: 2 inches) equipped with 40 sieve trays, shown in Drawing 2, was used as the reactor.

Phenol (PhOH) and $\text{Ti}(\text{OPh})_4$ as catalyst (cata.) were continuously fed to the twentieth stage of the distilling column, and the 20 plates above it were used for the distillation.

- 20 Dimethyl carbonate (DMC) was continuously fed to the autoclave.

- Reaction liquid was continuously removed through a pipe in the bottom of the autoclave's column. The low-boiling-point component containing alcoholic by-products was removed from the top of the distillation column and liquefied with a condenser. A portion of it was removed, and the balance was
25 refluxed through the distillation column. The reflux ratio is shown in Table 1.

The required heat was supplied by heating the autoclave and distillation column with electric furnaces. The raw material feed lines were also heated, using heaters. The procedure was carried out as a continuous operation under the conditions in Table 1. The results are shown in Table 2.

Comparative Examples 1 and 2

Continuous operations identical to the one in Working Example 1 were carried out, except that the reaction conditions were varied as shown in Table 1. The results are shown in Table 2.

Table 1

Table 1

Table 1

	Catalyst	Amounts Fed (g/h)			Reaction Conditions							$g(r, t)$	DMC /PhOH (Base of Column) d	$f(c, r, t, d)$
		DMC	Phenol PhOH	Amount of Catalyst c	Temperature at Base of Column r (°C)	Pressure at Top of Column (atm)	Liquid at Base of Column (mL)	Reflux Ratio	Amount Removed (g/h)		Residence Time t (h)			
									Top of Column	Base of Column				
Example 1	Ti(OPh) ₄	933	186	8	220	9	100	1/1	726	401	0.25	1.1	1.3	0.27
Example 2	Ti(OPh) ₄	996	188	0.8	220	10	100	1/1	744	441	0.23	1.0	1.5	0.025
Example 3	Ti(OPh) ₄	2483	563	23	250	14	70	1/1	1938	1131	0.08	2.0	1.2	0.49
Example 4	Bu ₂ SnO	955	203	5	220	9	100	1/1	698	465	0.22	1.0	1.5	0.22
Example 5	{Bu ₂ Sn(OPh)} ₂ O	936	174	7	220	9	100	1/1	705	412	0.25	1.1	1.6	0.27
Example 6	Pb(OPh) ₂ (PbO + PhOH)	982	192	4	220	9	100	1/1	729	449	0.22	1.0	1.5	0.24
Example 7	Ti(OPh) ₄	1220	280	13	206	8	250	1/1	973	540	0.46	0.9	1.0	0.22
Comparative Example 1	Ti(OPh) ₄	482	92	4	220	9	400	1/1	352	206	1.94	8.8	1.4	2.1
Comparative Example 2	Ti(OPh) ₄	905	212	0.05	220	9.5	100	1/1	705	412	0.25	1.1	1.0	0.006

Table 2

	Production (g/h)			PMC Yield	Anisole Selectivity
	PMC	DPC	Anisole		
Example 1	54	2	0.08	18	0.2
Example 2	43	1.5	0.03	14	0.1
Example 3	182	12	0.7	20	0.5
Example 4	52	2	0.04	16	0.1
Example 5	48	1.6	0.03	17	0.1
Example 6	50	1.6	0.03	16	0.1
Example 7	95	7	0.4	21	0.5
Comparative Example 1	24	0.8	0.2	16	1.1
Comparative Example 2	14	0.4	0.03	4	0.3

Abbreviations used in table: PMC Methyl phenyl carbonate DPC - Diphenyl carbonate

Brief Description of Drawings

Figure 1 Illustration of an apparatus used in the examples.

5 Figure 2 Illustration of an apparatus used in the examples.

We Claim:

1. A method of manufacturing aromatic carbonates comprising:

Charging to a reactor dialkyl carbonate and an aromatic hydroxy compound in a molar ratio of from about 0.5 to about 2 and

- 5 reacting the dialkyl carbonate and the aromatic hydroxy compound in the presence of from about 0.01 to about 5 molar percent based on the aromatic hydroxy compound for from about 0.05 to about 2 hours at a temperature of from about 206°C to about 280°C whereby the selectivity for alkyl aromatic ethers is less than about one percent by weight based on the
10 amount of aromatic hydroxy compound charged to the reactor.

2. The method of Claim 1 wherein the catalyst when employed as a catalyst in the reaction of a 1:1 molar ratio of dimethyl carbonate and phenol at a reaction temperature of 200°C has a catalytic activity whereby methyl phenylcarbonate is produced at a rate of at least 0.005 liters per mole per hour.

3. The method of Claim 2 wherein the dialkyl carbonate and the aromatic hydroxy compound are reacted under conditions whereby

$$g(r,t) \leq 2 \text{ and}$$

$$f(c,r,t,d) \leq 0.02$$

- 15 where c is the amount of catalyst used (a molar percentage of the aromatic hydroxy compound), r is reaction time (h), t is reaction temperature (°C), and d is a molar ratio

$$\text{and } g(r,t) = (r) \cdot \exp[36-17 \cdot \{1000/(273 + t)\}]$$

$$\text{and } f(c,r,t,d) = (c) \cdot (r) \cdot \exp[36-17 \cdot \{1000/(273 + t)\}] \cdot d/(1 + d^2);$$

$$20 \quad \text{and}$$

4. The method of Claim 3 wherein the dialkyl carbonate is diethyl carbonate or dimethyl carbonate.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



5. The method of Claim 4 wherein the dialkyl carbonate is dimethyl carbonate.

6. The method of Claim 4 wherein the aromatic hydroxy compound, is phenol, meta-cresol or para-cresol.

7. The method of Claim 4 wherein the aromatic hydroxy carbonate is phenol.

8. The method of Claim 7 wherein the dialkyl carbonate is dimethylcarbonate.

9. The method of Claim 4 wherein the alkyl aromatic ethers are anisole, phenetole, methyl tolyl ether, or ethyl tolyl ether.

10. The method of Claim 1 wherein the reactor is a reactive distillation column whereby reaction products are separated from reactants as they are formed.

11. The method of Claim 1 wherein the reactor is an autoclave.

12. The method of Claim 11 wherein the autoclave is connected to a distillation column to separate reaction product from reactants.

