

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/085711 A1

(51) International Patent Classification⁷: **C25B 15/00**,
C02F 1/461, C25B 9/20

(21) International Application Number:
PCT/NL2003/000234

(22) International Filing Date: 27 March 2003 (27.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: **ZILVOLD, Hendrik, Martin** [NL/NL]; Vale
Ouwelaan 202, NL-8084 JV 't Harde (NL).

(72) Inventor: **ZILVOLD, Gerrit, Albert**; Oude Bovendwar-
sweg 31, NL-8084 JD 't Harde (NL).

(74) Agents: **DOHMEN, Johannes, Maria, Gerardus et**
al.; Algemeen Octrooi- en Merkenbureau, P.O. Box 645,
NL-5600 AP Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR CARRYING OUT AN ELECTROLYTIC PROCESS ON A HALOGENIDE COMPOUND



(57) **Abstract:** The present invention relates to an apparatus for carrying out an electrolytic process on a halogenide compound, in which apparatus several electrolytic cells are electrically connected in series, which electrolysis cells each comprise a cell element, provided with underlying supply pipes for supplying electrolyte and with collecting discharge pipes disposed near the upper side thereof for discharging electrolyte and the gases formed during the electrolytic process, a cathode compartment including a cathode and an anode compartment including an anode, and a diaphragm or semi-permeable membrane, in which the electrolytic cells have been pressed together between two end plates with a certain bias, so that each anode compartment and each cathode compartment is constructed as one unit together with the supply pipes and the collecting discharge pipes.

WO 2004/085711 A1