

Leak Resistant Vane Cluster

Technical Field

5 [0010] This invention relates to shrouded vane clusters of the type used in turbine engines, and particularly to a cluster with a leak resistant, segmented shroud.

Background of the Invention

10

 [0020] The compressor section of a typical gas turbine engine comprises a case circumscribing an engine axis and axially alternating arrays of stationary vanes and rotatable blades. Each vane array may be constructed of multiple vane
15 clusters distributed circumferentially about the interior of the case with each cluster being supported by the case. Each vane cluster comprises a radially inner shroud, a radially outer shroud, and two or more airfoils extending between the shrouds. Collectively, the inner and outer
20 shrouds define the inner and outer boundaries of part of an annular flowpath for a working medium fluid.

 [0030] During engine operation, the vane clusters are subject to nonuniform heating and cooling. The accompanying
25 temperature gradients can cause damage by overstressing the clusters. To help alleviate these thermally induced stresses, one of the two shrouds may be divided into segments by slots that sever the shroud at locations circumferentially intermediate two neighboring airfoils.
30 Since the outer shroud of each cluster connects the cluster to the case, it is conventional to segment the inner shroud rather than the outer shroud. The slots reduce the risk of

damage by allowing the shroud segments to expand and contract independently of each other.

[0040] One technique for forming the slots is wire
5 electro-discharge machining (EDM). Wire EDM uses an electrically charged electrode in the form a wire wound around a source spool and extending to a take-up spool. The vane cluster shroud is exposed to the wire between the spools. During the EDM operation, the wire travels from the
10 source spool to the takeup spool and simultaneously advances toward the shroud. The difference in electrical charge between the wire electrode and the shroud causes an electrical discharge that removes material from the shroud. As material is removed, the wire advances through the shroud
15 until the slot is completely formed.

[0050] One drawback of the shroud slots is that they provide a path by which working medium fluid can leak out of the flowpath during engine operation or by which non-working
20 medium fluid can leak into the flowpath. Leakage can be mitigated, to some extent, by using a small diameter EDM wire to cut a thin slot, i.e. one with a correspondingly narrow kerf. However the use of thin EDM wire leads to increased machining time. Moreover, thin EDM wire is more
25 susceptible to breakage than thick EDM wire during the EDM operation. Thin EDM wire is also more likely than thick EDM wire to be stalled by the presence of minute particulate impurities trapped in the vane cluster. Finally, commercially available EDM equipment capable of using thin
30 wire is more specialized than EDM equipment capable using thicker wire. As a result, a manufacturer may find it economically unattractive to invest in the more specialized,

thin wire equipment. Accordingly, it may be desirable to avoid thin slots in favor of relatively wider slots

[0060] One way to reduce leakage through a wide slot is to provide a recess in the interior of the slot and install a seal in the recess. US Patents 3,728,041, 3,970,318, and 5,167,485 show arrangements of this type. Although such seals may be easily installable between the shrouds of individual vanes, or between the circumferential extremities of adjacent vane clusters, they are not easily installable in the inter-airfoil shroud slots of an otherwise unitary vane cluster. In addition, forming the intra-slot recess increases manufacturing cost and decreases manufacturing throughput. Another possible way to mitigate leakage is to install an external seal, such as the sealing strip 78 shown in US Patent 4,422,827, to bridge across each slot. However such external seals also increase manufacturing cost.

[0070] What is needed is a vane cluster with thermally independent shroud segments and which is economical and easy to manufacture.

Summary of the Invention

[0080] According to the invention, a vane cluster includes a shroud with a nonlinear slot extending therethrough to divide the shroud into thermally independent shroud segments. The slot is bordered by matching nonlinear surfaces that are easy and inexpensive to produce with conventional wire EDM equipment. The nonlinear slots effectively resist fluid leakage.

Brief Description of the Drawings

[0090] Figure 1 is a perspective view of a vane cluster
5 whose radially inner shroud is segmented by slots embraced
by the present invention.

[0100] Figures 2-5 are enlarged views of the slots
shown in Figure 1.

10 [0110] Figures 6-8 are enlarged views of slots having
curved portions.

[0120] Figure 9 is a view similar to Figure 1 showing a
15 vane cluster with a nonlinear profile at the lateral
extremities of its inner shroud.

Best Mode for Carrying Out the Invention

20 [0130] Referring to Figures 1-5, a vane cluster for a
turbine engine compressor includes a radially outer shroud
10, a radially inner shroud 12 and two or more airfoils 14
extending radially or spanwisely between the shrouds. Hooks
16 at the axial extremities of the outer shroud facilitate
25 its attachment to an engine case, not shown. Feet 18 at the
axial extremities of the inner shroud accommodate an inner
airseal, also not shown. The cluster extends
circumferentially between lateral extremities 20. When
several such clusters are installed in a turbine engine, the
30 shrouds define the radially inner and outer boundaries of a
portion of an annular fluid flowpath 22. The flowpath
circumscribes an engine axis, not shown. The vane cluster

itself is typically a cast metallic article finish machined to prescribed dimensions.

[0140] The inner shroud 12 is divided into individual segments 24 by nonlinear slots 26 between circumferentially neighboring airfoils 14. The slots are installed by wire EDM or other suitable process. Four different types of slots are depicted in Figure 1, however only one type of slot would ordinarily be used in a given cluster. The leftmost portion of the inner shroud is depicted in its "as-cast" state, i.e. without slots. Each slot is nonlinear, but may comprise two or more straight line portions as seen best in Figures 2-4. Each slot is bordered by a pair of matching surfaces, such as 28a, 28b. As used herein, the term "matching" surfaces refers to surfaces that are substantially exact counterparts of each other, i.e. surfaces that complement each other. This is in contrast to the surfaces shown in US Patents 3,728,041, 3,970,318, and 5,167,485, all of which feature intra-slot recesses that render the adjacent slot surfaces non-matching.

[0150] Figures 2-5 show the four slots in greater detail. Referring first to Figure 2, the nonlinear slot 26 comprises three straight line portions 26a, 26b, 26c, each of which has a juncture 32 with at least one of the other portions. Each juncture corresponds to a change of angular direction in the slot. For example, one juncture 32 between slot portions 26a and 26b corresponds to an approximate 90 degree change of angular orientation from the radial direction to the lateral direction. The other juncture 32 between slot portions 26b and 26c corresponds to another change of approximately 90 degrees from lateral to radial.

The accumulated angular change is therefore about 180 degrees.

5 [0160] Figure 3 shows a variant in which the slot comprises three straight line portions and two junctures. Each juncture corresponds to an approximately 120 degree change of angular orientation for an accumulated angular change of about 240 degrees.

10 [0170] Figure 4 shows a variant in which the slot comprises seven straight line portions and six junctures. Each juncture corresponds to an approximately 90 degree change of angular orientation for an accumulated angular change of about 540 degrees.

15

 [0180] The abrupt changes in angular orientation at the junctures 32 help resist fluid leakage through the slot and therefore permit the use of inexpensively installed, relatively wide slots that might otherwise be
20 unsatisfactory. Each change of orientation increases the resistance to fluid leakage. As a result, larger and/or more abrupt changes are superior to smaller and/or less abrupt changes. Accordingly, although a slot having only two straight line portions and one juncture can be used, it
25 is believed that the most practical and cost effective slots are those with at least three straight line portions and two changes of orientation totaling at least about 180 degrees. A larger quantity of straight line portions would be expected to further increase leak resistance of the slot,
30 but the correspondingly longer slot length would increase the time necessary to cut the slot using wire EDM. The tradeoff between leak resistance and manufacturing

complexity is a matter for consideration by the designers and manufacturers of the vane cluster.

[0190] As seen in Figures 6-8, the nonlinear slot need
5 not be comprised of linear portions as in the above
examples, but may instead be a curved slot having one or
more radii of curvature. The average radius of curvature R
may vary continuously along the length of the slot (Figure
6) or may vary discontinuously (Figure 7) thus defining one
10 or more distinct junctures 32 between individual portions
26a, 26b of the slot. As seen in Figure 8, a slot may
comprise both curved and straight line portions in
combination. Since the leak resistance of a slot depends on
the abruptness and quantity of directional changes, a
15 smoothly curved slot may provide unsatisfactory leak
resistance. A curved slot with an abrupt directional change
is expected to be superior to a smooth curve, but may be
more difficult to manufacture than a slot comprised of
straight line portions. One example of a curved slot having
20 multiple, continuously varying radii of curvature is the
serpentine slot of Figure 5.

[0200] The slots need not be installed
circumferentially between each and every airfoil, but may
25 instead be installed selectively, for example between every
second or third airfoil, to achieve the desired degree of
thermal independence.

[0210] The cluster of Figure 1 is one sector of a
30 single array or stage of vanes. In some engines the vane
clusters comprise two or more circumferentially aligned sub-
clusters, integral with each other but axially separated
from each other by an interstage space. In a fully

assembled engine, rotor blades extend radially into the interstage space. The invention includes such multi-stage clusters as well as the illustrated single stage cluster.

5 [0220] As seen in Figure 9, the nonlinear geometry of the slot 26 may also be employed as the interface between the lateral extremities 20 of adjacent vane clusters. Such a construction includes inner and outer shrouds 10, 12 with at least one airfoil extending between the shrouds. The
10 lateral extremities of at least one of the shrouds, e.g. inner shroud 12, has a nonlinear profile that matches a counterpart nonlinear profile on the extremity of a laterally adjacent vane cluster.

15 [0230] Although the invention has been presented in the context of stator vanes for a compressor, it is equally applicable to turbines. In addition, the invention includes clusters in which the outer shroud, rather than the inner shroud is the segmented shroud. It will be understood by
20 those skilled in the art that these and other changes in form and detail may be made without departing from the invention as set forth in the accompanying claims.

 [0240] I claim:

25

1. A vane cluster, comprising:

an outer shroud;

an inner shroud;

5 at least two airfoils extending between the shrouds;
one of the shrouds having a nonlinear slot extending
through the shroud between neighboring airfoils to define
shroud segments, each slot being bordered by matching
nonlinear surfaces.

10

2. The cluster of claim 1 wherein the nonlinear slot
comprises at least two slot portions with a juncture
therebetween, each juncture corresponding to a change of
angular orientation.

15

3. The cluster of claim 2 comprising at least three slot
portions with at least two changes of angular orientation.

4. The cluster of claim 3 wherein the changes of angular
20 orientation define an accumulated angular change of at least
about 180 degrees.

5. The cluster of claim 1 wherein the nonlinear slots
comprise a curved portion.

25

6. The cluster of claim 1 wherein each nonlinear slot
comprises at least two straight line segments.

7. The cluster of claim 1 wherein the shroud having a
30 nonlinear slot extending therethrough is the inner shroud.

8. The cluster of claim 1 wherein the nonlinear slots are present between each and every neighboring airfoil of the cluster.

5 9. The cluster of claim 1 wherein the slot is formed by electro-discharge machining.

10. A vane cluster, comprising:

an outer shroud having outer lateral extremities;

10 an inner shroud having inner lateral extremities;

at least one airfoil extending between the shrouds;

The lateral extremities of at least one of the outer and inner shrouds having a nonlinear profile that matches a counterpart nonlinear profile on the lateral extremities of
15 laterally neighboring vane clusters.