

DESCRIPTION

SERVICE PROVIDING METHOD AND INTEGRATED CIRCUIT

5 TECHNICAL FIELD

The present invention relates to an integrated circuit, a communication method and a system of the same using a communication apparatus incorporating the integrated circuit, and a communication apparatus, a processing apparatus and a method thereof used by the same.

BACKGROUND ART

Recently, e-commerce using an IC card or other IC devices is being conducted.

15 An IC (integrated circuit) of such an IC device has an interface for communicating with a transaction apparatus installed in a store, etc., a memory for storing an application program defining a process relating to a service performed using a data carrier function and/or an individual authentication function
20 built into a chip of the IC, and a CPU for executing the program built therein.

However, in the IC of the above-mentioned IC device, an application program is stored in the memory built into
25 the IC as explained above, and therefore from the

standpoint of miniaturization and price-reduction of the IC, there is a problem in that services performed using a data carrier function and/or an individual authentication function built into a chip of a single IC are limited due to the fact that there is a limit in a storage capacity of the memory.

DISCLOSURE OF THE INVENTION

An example embodiment can provide a communication method and a system of the same, a communication apparatus, a processing apparatus and a method thereof capable of providing a variety of services by using a single integrated circuit without limitations placed on a storage capacity of a memory built into the integrated circuit.

Further, the example embodiment can provide an integrated circuit and a communication apparatus capable of providing a variety of services by using a single integrated circuit without limitations placed on a storage capacity of a memory built into the integrated circuit.

According to a first aspect of the present invention, there is provided a service providing method wherein a communication apparatus and a processing apparatus communicate with each other in response to a service use request issued from the communication apparatus to provide a service to a user of the communication apparatus, comprising the steps of: performing communication between a

server apparatus storing a program defining a process relating to the service and the communication apparatus to judge if use of the program is permitted or not in response to the service use request, the program being stored in a storage area of the server apparatus allocated in advanced to the communication apparatus; executing the program by the server apparatus when use of the program is permitted; and performing communication between the server apparatus and the processing apparatus through the communication apparatus in response to the execution of the program by the server apparatus to provide the service to the user, the service being provided by using a function of data carrier and/or authentication in the communication apparatus and a reader/writer function in the processing apparatus.

In the example embodiment, the communication apparatus issues a service use request.

Then, in response to the service use request, the server apparatus and the communication apparatus communicate to judge if use of the program is permitted or not.

Next, when the use of the program is permitted, the server apparatus executes the program.

Then, in response to the execution of the program by the server apparatus, the server apparatus and the processing apparatus communicate through the communication apparatus to provide the service to the user, in the example embodiment.

According to a second aspect of the present invention, there is provided a server apparatus communicating with a communication apparatus and a processing apparatus that transfers data with the communication apparatus and used in a service to a user of the communication apparatus, comprising: means for storing a program defining a process relating to the service, the program being stored in a storage area of the server apparatus allocated in advance to the communication apparatus; means for receiving a service use request from the communication apparatus; means for authenticating if the service use request is legitimate or not; and means for controlling a processing for providing a service to the user in collaboration with the processing apparatus in response to the execution of a program defining a process relating to the service by reading the program from the storing means and executing the read program when it is judged that the service use request is legitimate, the service being provided by using a function of data carrier and/or authentication in the

communication apparatus and a reader/writer function in the processing apparatus.

In the example embodiment, the integrated circuit transmits a use request of the program through the communication circuit to the second communication apparatus storing a program defining a process relating to the service and executing the same.

Next, when the second communication apparatus judges that the use request is legitimate, it executes a program relating to the use request. Further, while the communication between the processing apparatus and the second communication apparatus conducted through the communication circuit is relayed by the integrated circuit, the processing apparatus and the second communication apparatus performs a process relating to the service in collaboration with each other in response to the execution of the program by the second communication apparatus.

In this manner, in the communication method of the example embodiment, by having the second communication apparatus execute the program stored therein in response to the use request from the integrated circuit to the second communication apparatus enables the second communication apparatus to communicate with the processing apparatus through the integrated circuit and perform in collaboration

with each other a service provided using the integrated circuit.

Therefore, in the example embodiment, the necessity to store the program in the integrated circuit is no longer required enabling a variety of services to be provided using an integrated circuit having its storage capacity limited. Further, when the second communication apparatus judges in response to a use request from the integrated circuit that the use request is legitimate, the integrated circuit relays the communication between the processing apparatus and the second communication apparatus. Thus, illicit access can be prevented.

Further, preferably, the communication method of the example embodiment comprises a step of storing by the second communication apparatus the program relating to the first communication apparatus in a storage area allocated in advance to the first communication apparatus among storage areas in the second communication apparatus.

Further, preferably, the communication method of the example embodiment comprises a step of transmitting by the first communication apparatus to the second communication apparatus the use request indicating use of the storage area allocated in advance to the first communication apparatus.

Further, preferably, the communication method of the example embodiment further comprises the steps of: transmitting from the first communication apparatus to the second communication apparatus a program select instruction specifying a program to be selected and used after the integrated circuit transmits the use request to the second communication apparatus; and reading and executing by the second communication apparatus a program specified by the program select instruction.

Further, in the communication method of the example embodiment, preferably, the first communication apparatus is a portable type communication apparatus, the communication circuit is a wireless communication circuit performing communication using a wireless communication network, the second communication apparatus is connected to a network, and the integrated circuit communicates with the second communication apparatus through the communication circuit, the wireless communication network, and the network.

According to a third aspect of the present invention, there is provided a communication method wherein a communication apparatus comprising an integrated circuit and a communication circuit communicates with a processing apparatus that transfers data with the integrated circuit and used in a service relating to the integrated circuit,

comprising the steps of: receiving a use request of a program from the integrated circuit through the communication circuit; reading an application program relating to the use request from a storing means; executing the read program; and communicating with the processing apparatus through the communication circuit and the integrated circuit in response to the execution of the program and performing a process relating to the service in collaboration with the processing apparatus; wherein the program being stored in a storage area of the storing means allocated in advanced to the communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the communication apparatus and a reader/writer function in the processing apparatus.

According to a fourth aspect of the present invention, there is provided a processing apparatus that transfers data with a first communication apparatus and used in a service provided to a user of the first communication apparatus, wherein, after a second communication apparatus storing a program defining a process relating to the service and executing the same, and the first communication apparatus have authenticated one another's legitimacy by a mutual authentication conducted through the communication circuit, the processing apparatus while communicating with

the second communication apparatus through the first communication apparatus, performs a process relating to the service in collaboration with the second communication apparatus; the program being stored in a storage area of the second communication apparatus allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function for the processing apparatus.

According to a fifth aspect of the present invention, there is provided an integrated circuit access apparatus transferring data between an integrated circuit built into a first communication apparatus and a processing apparatus used in a service provided to a user of the first communication apparatus, wherein after a second communication apparatus storing a program defining a process relating to the service and executing the same, and the first communication apparatus have authenticated one another's legitimacy by a mutual authentication conducted through the communication circuit, transfers data between the integrated circuit and the processing apparatus to relay communication between the second communication apparatus and the processing apparatus performed through the integrated circuit; the program being stored in a storage area of the second communication apparatus

allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function in the processing apparatus.

According to a sixth aspect of the present invention, there is provided a processing method transferring data with a first communication apparatus comprising an integrated circuit and a communication circuit and used in a service relating to the integrated circuit, comprising the steps of: conducting mutual authentication of a second communication apparatus storing a program defining a process relating to the service and executing the same, and the integrated circuit through the communication circuit, and after one another's legitimacy is authenticated by the mutual authentication; relaying the integrated circuit; and while communicating with the second communication apparatus executing the program, performs a process relating to the service in collaboration with the second communication apparatus; wherein the program being stored in a storage area of the second communication apparatus allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function for the integrated circuit.

According to a seventh aspect of the present invention, there is provided a communication method performing communication using a first communication apparatus comprising an integrated circuit and a communication circuit, a second communication circuit used in a service relating to the integrated circuit, and a third communication apparatus storing a program defining a process relating to the integrated circuit and executing the same, comprising the steps of: transmitting a use request of the program from the integrated circuit to the third communication apparatus through the communication circuit; conducting mutual authentication between the integrated circuit and the third communication apparatus through said communication circuit; and conducting mutual authentication between the second communication apparatus and the third communication apparatus when the legitimacy of the integrated circuit and the third communication apparatus has been authenticated by the mutual authentication thereof, and when the second communication apparatus and the third communication apparatus have authenticated one another's legitimacy by the mutual authentication, executing by the third communication apparatus the program relating to the use request, whereby the second communication apparatus and the third communication apparatus communicate to perform a process

relating to the service in collaboration with each other in response to the execution of the program; wherein the program being stored in a storage area of the third communication apparatus allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function in the second communication circuit.

In the example embodiment, first, a use request of the program is transmitted through the communication circuit from the integrated circuit to the third communication apparatus.

Next, mutual authentication is conducted between the integrated circuit and the third communication apparatus through the communication circuit.

Then, if the integrated circuit and the third communication apparatus have authenticated one another's legitimacy by the mutual authentication, mutual authentication is conducted between the second communication apparatus and the third communication apparatus.

Then, if the second communication apparatus and the third communication apparatus have authenticated one another's legitimacy by the mutual authentication, the

third communication apparatus executes the program relating to the use request.

Then, in response to the execution of the program, the second communication apparatus and the third communication apparatus communicate to perform a process relating to the service in collaboration with each other.

In the example embodiment, the necessity of storing a program in the integrated circuit is no longer required, and therefore a variety of services can be provided using an integrated circuit with a storage capacity limited. Further, since mutual authentication is conducted between the integrated circuit and the third communication apparatus and between the second communication apparatus and the third communication apparatus, illicit access can be prevented.

Further, the communication method of the example embodiment, preferably, further comprises the steps of: transmitting from the second communication apparatus to the first communication apparatus a program select instruction for instructing a program to be selected and used; transmitting by the first communication apparatus on the basis of the program select instruction a program select instruction to the third communication instruction; and executing by the third communication apparatus a program

specified by the program select instruction received from the first communication apparatus.

According to an eighth aspect of the present invention, there is provided a communication system comprising: a first communication apparatus comprising an integrated circuit and a communication circuit; a second communication apparatus used in a service relating to the integrated circuit; and a third communication apparatus storing a program defining a process relating to the service and executing the same, wherein: a use request of the program is transmitted from the integrated circuit to the third communication apparatus through the communication circuit; mutual authentication is conducted between the integrated circuit and the third communication apparatus through the communication circuit; when the integrated circuit and the third communication apparatus have authenticated one another's legitimacy by the mutual authentication, the second communication apparatus and the third communication apparatus conducts mutual authentication; and when the second communication apparatus and the third communication apparatus have authenticated one another's legitimacy by the mutual authentication, the third communication apparatus executes the program relating to the use request, and the second communication apparatus and the third communication apparatus communicate in

response to the execution of the program to perform a process relating to the service in collaboration with each other; the program being stored in a storage area of the third communication apparatus allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function in the second communication apparatus.

According to a ninth aspect of the present invention, there is provided a communication apparatus communicating with a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus storing a program defining a process relating to a service and used in a service relating to the integrated circuit, comprising: means for authenticating with the second communication apparatus after the integrated circuit and the second communication apparatus have authenticated one another's legitimacy by a mutual authentication; and means for communicating with the second communication apparatus executing the program to perform a process relating to the service in collaboration with each other after one another's legitimacy with the second communication apparatus has been authenticated by a mutual authentication through the authentication means;

wherein the program being stored in a storage area of the second communication apparatus, allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function in the communication apparatus.

According to a tenth aspect of the present invention, there is provided a communication method performed between a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus storing a program defining a process relating to a service to be provided using the integrated circuit and executing the same, comprising the steps of: conducting mutual authentication with the second communication apparatus after the integrated circuit and the second communication apparatus have authenticated one another's legitimacy by a mutual authentication; and communicating with the second communication apparatus executing the program to perform a process relating to the service in collaboration with each other after one another's legitimacy with the second communication apparatus has been authenticated by the mutual authentication with the second communication apparatus; wherein the program being stored in a storage area the second communication apparatus, allocated in advanced to

the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function for the first communication apparatus.

According to an eleventh aspect of the present invention, there is provided a communication apparatus communicating with a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus used in a service relating to the integrated circuit, comprising: a storing means for storing a program defining a process relating to the service in a storage area of the storing means allocated in advance to the first communication apparatus; a receiving means for receiving a use request of the program from the integrated circuit through the communication circuit; an authentication means for conducting mutual authentication with the integrated circuit through the communication circuit in response to the use request and after one another's legitimacy has been authenticated by the mutual authentication, conducting mutual authentication with the second communication apparatus; and when one another's legitimacy with the second communication apparatus has been authenticated by the mutual authentication, a controlling means for reading

the program relating to the use request from the storing means and executing the same, and communicating with the second communication apparatus in response to the execution of the program to perform a process relating to the service in collaboration with each other; wherein the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function in the communication apparatus.

According to a twelfth aspect of the present invention, there is provided a communication method wherein a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus used in a service relating to the integrated circuit communicates, comprising the steps of: receiving a use request of a program defining a process relating to the service from the integrated circuit through the communication circuit; conducting mutual authentication with the integrated circuit through the communication circuit in response to the use request, and after one another's legitimacy has been authenticated by the mutual authentication, conducting mutual authentication with the second communication apparatus; reading a program relating to the use request from a storing means and executing the same when one another's legitimacy with the second communication apparatus has been authenticated by the

mutual authentication; and communicating with the second communication apparatus in response to the execution of the program to perform a process relating to the service in collaboration with each other; wherein the program being stored in a storage area of the storing means allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function for the first communication apparatus.

According to a thirteenth aspect of the present invention, there is provided an integrated circuit transferring data with a communication circuit of a first communication apparatus and a processing apparatus performing a process relating to a predetermined service, comprising: a first interface for transferring data with the processing apparatus; a second interface for transferring data with the communication circuit; and a controlling means for accessing a second communication apparatus through the second interface and the communication circuit, and while communicating with the processing apparatus through the first interface, performs a process relating to the service using a program or data stored in the second communication apparatus; wherein the program or data being stored in a storage area of the

second communication apparatus allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function in the processing apparatus.

An operation of the integrated circuit of the example embodiment is as follows:

In the integrated circuit of the example embodiment, the controlling means accesses the second communication apparatus through the second interface and the communication circuit under a predetermined condition.

Then, the controlling means performs a process while communicating with the processing apparatus through the first interface using a program or data stored in the second communication apparatus.

In this manner, in the integrated circuit of the example embodiment, the second communication apparatus can be used as a virtual memory and as an apparatus to virtually execute a program.

Further, in the integrated circuit of the example embodiment, preferably, when the second communication apparatus stores a program defining a process relating to the service and executes the same, the controlling means conducts mutual authentication with the second communication apparatus through the second interface and

the communication circuit, and then controls communication of the second communication apparatus executing the program and the processing apparatus conducted through the communication circuit so that the first interface and the second interface relays the same.

Further, in the integrated circuit of the example embodiment, preferably, the controlling means communicates with the second communication apparatus through the second interface and the communication circuit to conduct the mutual authentication based on an authentication request received from the second communication through the communication circuit.

Further, the integrated circuit of the example embodiment, preferably, further comprises a storage circuit for storing a program relating to a service provided using the integrated circuit, wherein the controlling means judges if the program corresponding to a request received from the processing apparatus through the first interface is stored in the storage circuit or not, and when judged that the program is stored in the storage circuit, executes the program read from the storage circuit, and while communicating with the processing apparatus through the first interface in response to the execution of the program, performs a process relating to the service.

Further, in the integrated circuit of the example embodiment, preferably, when the controlling means judges that the program is not stored in the storage circuit, transmits a use request of the program to the second communication apparatus through the second interface and the communication circuit.

According to a fourteenth aspect of the present invention, there is provided an electronic circuit having a communication means and an integrated circuit mounted on a substrate, wherein the integrated circuit comprises: a first interface transferring data with a processing apparatus performing a process relating to a predetermined service; a second interface transferring data with the communication means; and a controlling means for accessing a second communication apparatus through the second interface and the communication circuit, and while communicating with the processing apparatus through the first interface, performs a process using a program or data stored in the second communication apparatus, the program or data is being stored in a storage area of the second communication apparatus allocated in advance to the electronic circuit; wherein the predetermined service being provided by using a function of data carrier and/or authentication in the electronic circuit and a reader/writer function in the processing apparatus.

According to a fifteenth aspect of the present invention, there is provided a communication apparatus comprising a communication circuit and an integrated circuit, wherein the integrated circuit comprises: a first interface for transferring data with a processing apparatus performing a process relating to a predetermined service; a second interface for transferring data with the communication circuit; and a controlling means for accessing another communication apparatus through the second interface and the communication circuit, and while communicating with the processing apparatus through the first interface, performs a process using a program or data stored in the another communication apparatus, the program or data is being stored in a storage area with another communication apparatus allocated in advanced to the communication apparatus; wherein the predetermined service being provided by using a function of data carrier and/or authentication in the communication apparatus and a reader/writer function in the processing apparatus.

Further, in the communication apparatus of the example embodiment, preferably, the communication circuit comprises a storage circuit for storing a program or data, and the controlling means accesses the storage circuit through the second interface, and performs a process while communicating with the processing apparatus through the

first interface using a program or data stored in the storage circuit.

According to a sixteenth aspect of the present invention, there is provided an integrated circuit transferring data with a communication circuit of a first communication apparatus, comprising: an interface for communicating with the communication circuit; and a controlling means for conducting mutual authentication with a second communication apparatus storing a program defining a process relating to a service through the interface and the communication circuit if an authentication request from the communication circuit is received through the interface; wherein the program being stored in a storage area of the second communication apparatus allocated in advanced to the first communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the first communication apparatus and a reader/writer function for the integrated circuit.

Further, in the integrated circuit of the example embodiment, preferably, a result of the mutual authentication is used for determining whether the second communication apparatus and a third communication apparatus for performing a process relating to a service using the integrated circuit should communicate to perform a process relating to the service or not.

Further, the integrated circuit of the example embodiment, preferably, further comprises a storage circuit for storing a program relating to a service provided using the integrated circuit, wherein the controlling means judges if the program corresponding to a request received from the communication circuit through the interface is stored in the storage circuit or not, and when judged that the program is stored in the storage circuit, executes the program read from the storage circuit and while communicating with the third communication apparatus through the interface and the communication circuit in response to the execution of the program, performs a process relating to the service.

Further, in the integrated circuit of the example embodiment, preferably, when the controlling means judges that the program is not stored in the storage circuit, transmits a use request of the program to the second communication apparatus through the interface and the communication circuit.

According to a seventeenth aspect of the present invention, there is provided a communication apparatus comprising a communication circuit and an integrated circuit, wherein the integrated circuit comprises: an interface for transferring data the communication circuit; a controlling means for conducting mutual authentication

with another communication apparatus storing a program defining a process relating to a service through the interface and the communication circuit if an authentication request from the communication circuit is received through the interface; wherein the program being stored in a storage area of the another communication apparatus allocated in advanced to the communication apparatus; and the service being provided by using a function of data carrier and/or authentication in the communication apparatus and a reader/writer function for the another communication apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view of the overall configuration of a communication system of a first embodiment of the present invention.

FIG. 2 is a view for explaining the outline of an example of an operation of the communication system shown in FIG. 1.

FIG. 3 is a functional block diagram of the virtual IC storage area server apparatus shown in FIG. 1.

FIG. 4 is a functional block diagram of the SAM shown in FIG. 3.

FIG. 5 is a view for explaining a storage area of the memory 52 shown in FIG. 3.

FIG. 6 is a view for explaining an application program stored in the IC virtual storage area shown in FIG. 5.

FIG. 7 is a functional block diagram of the control

unit shown in FIG.

FIG. 8 is a functional block diagram of a portable communication function unit of the portable telephone apparatus shown in FIG. 1.

5 FIG. 9 is a functional block diagram of an IC of the portable telephone apparatus shown in FIG. 1.

FIG. 10 is a view for explaining a case wherein the IC shown in FIG. 1 uses a memory of the virtual IC storage area server apparatus.

10 FIG. 11 is a view for explaining a control flow of the case shown in FIG. 10.

FIG. 12 is a view for explaining a case wherein the IC shown in FIG. 1 uses a memory of the portable communication function unit.

15 FIG. 13 is a flow chart for explaining an example of the operation of the communication system illustrating a case of performing a process relating to a service using the IC by utilizing an application program stored in the virtual IC storage area server apparatus shown in
20 FIG. 1 when a service specified by a user A to be used by the user A is selected.

FIG. 14 is a flow chart for explaining an example of the operation of the communication system illustrating a case of performing a process relating to a service
25 using the IC 21 by utilizing an application program

stored in the virtual IC storage area server apparatus shown in FIG. 1 when a service to be selected by the IC_R/W apparatus is automatically instructed to the virtual IC storage area server apparatus.

5 FIG. 15 is a flow chart for explaining an example of the operation of the communication system illustrating a case of registering (allocating) an IC virtual storage area used by the IC of the portable telephone apparatus in a storage area of the memory of the virtual IC storage
10 area server apparatus shown in FIG. 3.

 FIG. 16 is a flow chart for explaining an example of the operation illustrating a case of registering an application program in the IC virtual storage area allocated to the portable telephone apparatus in the
15 third exemplified operation in response to an operation of the user A.

 FIG. 17 is a flow chart for explaining an example of the operation illustrating a case wherein an application program is automatically registered in the IC
20 virtual storage area allocated to the portable telephone apparatus in the third exemplified operation by the IC_R/W apparatus.

 FIG. 18 is view of the overall configuration of a communication system of a second embodiment of the
25 present invention.

FIG. 19 is a functional block diagram of an IC service providing apparatus shown in FIG. 18.

FIG. 20 is a function block diagram of a virtual IC storage area server apparatus shown in FIG. 18.

5 FIG. 21 is a functional block diagram of an IC shown in FIG. 18.

FIG. 22 is a flow chart for explaining an example of an operation of the communication system illustrating a case of performing a process relating to a service using the IC by utilizing an application program stored in the virtual IC storage area server apparatus shown in FIG. 18 when a service to be used by a user A is specified and selected by the user A.

10

FIG. 23 is a flow chart for explaining an example of the operation of the communication system illustrating a case of performing a process relating to a service using the IC by utilizing an application program stored in the virtual IC storage area server apparatus shown in FIG. 18 when a service provided by the IC service providing apparatus itself is automatically instructed to the virtual IC storage area server apparatus.

15

20

FIG. 24 is a flow chart for explaining an example of the operation illustrating a case of registering an application program in the IC virtual storage area allocated to the portable telephone apparatus in the

25

third exemplified operation when a portable communication function unit does not conduct confirmation for an available space in the IC virtual storage area.

FIG. 25 is a flow chart for explaining an example of the operation illustrating a case of registering an application program in the IC virtual storage area allocated to the portable telephone apparatus in the third exemplified operation when the portable communication function unit conducts confirmation of available space in the IC virtual storage area.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, a communication system according to an embodiment of the present invention will be explained.

First Embodiment

FIG. 1 is a view of the overall configuration of a communication system 1 of the present invention.

As shown in FIG. 1, the communication system 1 comprises, for example, a gateway 10, an IC_R/W apparatus 11, an IC service providing apparatus 12, a virtual IC storage area server apparatus 13, and a portable telephone apparatus 14.

The portable telephone apparatus 14 and the virtual IC storage area server apparatus 13 communicate through the wireless communication line 17 or other portable

telephone communication network, the gateway 10, and a network 18 such as the Internet. Or, communicate by directly connecting to the gateway 10 which manages the wireless communication line 17.

5 Further, the portable telephone apparatus 14 and the IC_R/W apparatus 11 conduct, for example, wireless communication.

Further, the IC_R/W apparatus 11 and the IC service providing apparatus 12 communicates through, for example,
10 an exclusive transmission line.

Also, the portable telephone apparatus 14 comprises a portable communication function unit 20 and an IC 21.

The present embodiment is an embodiment corresponding to the first to 11th aspect of the present
15 invention and the 18th to 20th aspect of the present invention.

The IC_R/W apparatus 11 shown in FIG. 1 corresponds to a processing apparatus of the present invention.

Further, the portable telephone apparatus 14
20 corresponds to the communication apparatus of the first to fourth aspects of the present invention, the first communication apparatus of the fifth and sixth aspects of the present invention, the other communication apparatus of the seventh aspect of the present invention, the
25 communication apparatus of the eighth aspect of the

present invention, and the first communication apparatus of the ninth and 11th aspects of the present invention.

Further, the virtual IC storage area server apparatus 13 corresponds to the server apparatus of the first to fourth aspects of the present invention, the second communication apparatus of the fifth and sixth aspects of the present invention, the communication apparatus of the seventh and eighth aspects of the present invention, and the second communication apparatus of the ninth and 11th aspects of the present invention.

First, an outline of an example of the operation of the communication system 1 shown in FIG. 1 will be explained.

FIG. 2 is a view for explaining the outline of the example of the operation of the communication system 1 shown in FIG. 1.

A user A visits a store 30, and the IC_R/W apparatus 11 and the IC 21 are enabled into a wireless communication state via an antenna of the IC 21. In this case, data is transferred and power is supplied between the IC_R/W apparatus 11 and the IC 21 through the antenna, whereby a stabilized direct current voltage is supplied to each of the circuits inside the IC 21. Or, the IC_R/W apparatus 11 and the IC 21 may be enabled into a wireless communication state by a power source from a battery

inside the portable telephone apparatus 14.

Then, as shown in FIG. 2, first, in response to an operation of the portable communication function 20 of the portable telephone apparatus 14 by the user A, a
5 virtual storage area use demand (service use demand of the present invention or a use demand) is transmitted to the virtual IC storage area server apparatus 13 through the wireless communication line 17, the gateway 10, and the network 18 from the portable communication function
10 unit 20 (① in FIG. 2).

Next, mutual authentication is conducted between the IC 21 of the portable telephone apparatus 14 and the virtual IC storage area server apparatus 13 (② in FIG.
2).

15 Then, when each other's legitimacy is authenticated by mutual authentication, along with transmitting an application program selection instruction to the virtual IC storage area server apparatus 13 from the portable communication function unit 20 (③ in FIG. 2) in response
20 to an operation of the user A, a virtual storage area use instruction is transmitted to the IC_R/W apparatus 11 from the IC 21 (④ in FIG. 2).

Next, the IC_R/W apparatus 11 and the virtual IC storage area server apparatus 13 communicate through the
25 portable communication function unit 20 and the IC 21,

and after conducting mutual authentication, perform in collaboration with each other a process relating to a service performed using a data carrier function and/or an individual authentication function built into a chip of the IC 21 (⑤ in FIG. 20).

In this manner, according to the communication system 1, when the IC 21 performs a process relating to a service with the IC_R/W apparatus 11, the virtual IC storage area server apparatus 13 executes an application program stored in the server apparatus 13 after a predetermined authentication process, and performs a process relating to the above service while communicating with the IC_R/W apparatus 11.

Therefore, even if the storage capacity of the memory in the IC 21 is small, it is possible to provide a service using an application program having a large amount of data.

Note that the service of the present embodiment include services involving highly confidential processes relating to for example membership, electronic money, e-commerce, point accumulation, cash card, and credit card, and services relating to confirming and processing utilization rights of exiting a ticket barrier, entering and exiting, etc.

Below, each of the components of the communication

system 1 shown in FIG. 1 will be explained in detail.

[Gateway 10]

The gateway 10 is an apparatus for relaying communication between the wireless communication line 17 or other portable telephones and the network 18.

[IC_R/W Apparatus 11]

The IC_R/W apparatus 11 is installed in the store 30 of a service provider and transfers data with the IC 21 built into the portable telephone apparatus 14 by a contact system or non-contact system to thereby perform a process relating to a service performed using a data carrier function and/or an individual authentication function built into a chip of the IC 21. In the present embodiment, a case of transferring data between the IC_R/W apparatus 11 and the IC 12 by the non-contact system (wireless system) is exemplified.

The IC_R/W apparatus 11, as will be explained later, communicates with the virtual IC storage area server apparatus 13 which stores and executes an application program defining a process relating to the service through the portable telephone apparatus 14 to perform the process relating to the service in collaboration with the virtual IC storage area server apparatus 13 in response to the application program executed by the virtual IC storage area server apparatus 13.

As the above service of the present embodiment,
there are services involving highly confidential
processes such as authentication of the person in
question (individual), electronic money, e-commerce, and
5 issuance of a ticket.

[IC Service Providing Apparatus 12]

The IC service providing apparatus 12 transfer data
required in the service performed using a data carrier
function and/or an individual authentication function
10 built into a chip of the IC 21 with the IC_R/W apparatus
11.

Note that in the present invention (10th aspect of
the present invention), for example, the IC service
providing apparatus 12 may communicate with the virtual
15 IC storage area server apparatus 13 through the IC_R/W
apparatus 11 and the portable telephone apparatus 14 to
perform the process relating to the service in
collaboration with the virtual IC storage area server
apparatus 13 in response to the application program
20 executed by the virtual IC storage area server apparatus
13.

In this case, the IC_R/W apparatus 11 transfer data
between the IC 21 and the IC service providing apparatus
12 in order to relay communication between the IC service
25 providing apparatus 12 and the virtual IC storage area

server apparatus 13.

Note that the IC_R/W apparatus 11 and the IC service providing apparatus 12 may be configured as independent apparatuses, respectively, or as a single apparatus.

[Virtual IC Storage Area Server Apparatus 13]

The virtual IC storage area server apparatus 13 functions as a virtual memory of the IC 21 of the portable telephone apparatus 14, stores an application program relating to a service performed using a data carrier function and/or an individual authentication function built into a chip of the IC 21, and executes the application program in response to an instruction from the IC 21.

FIG. 3 is a functional block diagram of the virtual IC storage area server apparatus 13.

As shown in FIG. 3, the virtual IC storage area server apparatus 13 comprises, for example, a SAM 51, a memory 52, a control unit 53, and an I/F unit 54.

FIG. 4 is a functional block diagram of the SAM 51 shown in FIG. 3.

The SAM 51 is a tamper-resistant module of a hardware or software.

The SAM 51, as shown in FIG. 4, comprises an authentication unit 61, an encryption/decryption unit 62,

an IC control unit 63, and an IC related process unit 64.

The authentication unit 61 conducts mutual authentication with the IC 21 and mutual authentication with the IC_R/W apparatus 11.

5 The encryption/decryption unit 62 performs, for example, encryption of an application program to be registered (write) into the memory 52, and decryption of an application program read from the memory 52.

10 The IC control unit 63 controls, for example, communication with the IC 21.

The IC related process unit 64 performs a process relating to a predetermined service in collaboration with the IC 21.

15 The memory 52 is used as the virtual memory of the IC 21 to store an application program relating to a service performed using a data carrier function and/or an individual authentication function built into a chip of the IC 21.

20 The memory 52, as shown in FIG. 5, comprises IC virtual storage areas 60a, 60b, 60c... allocated to every user (portable telephone apparatus) in advance by a registration process which will be explained later. For example, the IC virtual storage area 60a is allocated to the user A of the portable telephone apparatus 14, the IC
25 virtual storage area 60b is allocated to a user B, and

the IC virtual storage area 60c is allocated to a user C.

Further, for example as shown in FIG. 6,
application programs 65a, 65b, and 65c registered by an
application program registering process which will be
5 explained later are stored in the IC virtual storage area
60a. The application programs 65a, 65b, and 65c
respectively are programs defining processes relating to
services provided using the IC 21.

The memory 52 has a storage capacity of, for
10 example, 2k, 4k, or 8k.

The control unit 53 integrates the processes of the
virtual IC storage area server apparatus 13 to control
the same.

FIG. 7 is a functional block diagram of the control
15 unit 53.

As shown in FIG. 7, the control unit 53 comprises a
portal unit 71, a user I/F unit 72, an AP (application
program) execution unit 73, a SAM control unit 74, and a
memory control unit 75.

20 The portal unit 71 realizes a portal function in
response to, for example, an access from the portable
telephone apparatus 14. For example, it displays a menu
screen of providable services on a display portion of the
portable telephone apparatus 14.

25 The user I/F unit 72 controls a user I/F screen to

be displayed on a display unit 34 of the portable telephone apparatus 14.

The AP execution unit 73 executes an application program read from the memory 52.

5 The SAM control unit 74 controls a process using the SAM 51.

 The memory control unit 75 manages an application program stored in the memory 52. Specifically, the memory control unit 75 for example allocates the IC virtual storage area 60a to the portable telephone apparatus 14 and registers the application programs 65a, 65b, and 65c to the IC virtual storage area 60a.

[Portable Telephone Apparatus 14]

 As shown in FIG. 1, the portable telephone apparatus 14 comprises the portable communication function unit 20 and the IC 21.

 Here, the portable communication function unit 20 corresponds to the communication circuit of the present invention, and the IC 21 corresponds to the integrated circuit of the present invention.

 Note that the portable telephone apparatus 14 comprising the portable communication function unit 20 and the IC 21 is exemplified in the present embodiment, however, for example, an IC chip module (electronic circuit of the 19th aspect of the present invention)

having the IC 21, the antenna, and a communication circuit (communication means of the present invention) mounted on a substrate can be used.

In this case, communication with the virtual IC storage area server apparatus 13 is conducted using the antenna and the communication circuit.

<Portable Communication Function Unit 20>

FIG. 8 is a functional block diagram of the portable communication function unit 20 shown in FIG. 1.

As shown in FIG. 8, the portable communication function 20 comprises, for example, an audio input/output unit 31, an A/D·D/A conversion unit 32, a DSP 33, a display unit 34, an operation unit 35, an IC_I/F unit 36, a memory 37, a base band processing unit 39, and a wireless unit 40.

The audio input/output unit 31 comprises a speaker for outputting voices/sounds in response to an analog audio signal inputted from the A/D·D/A conversion unit 32, and a mike for outputting an analog audio signal generated in response to the inputted voice/sound to the A/D·D/A conversion unit 32.

The A/D·D/A conversion unit 32 converts a digital audio signal inputted from the DSP 33 into an analog audio signal to thereby output it to the audio input/output unit 31.

Further, the A/D·D/A conversion unit 32 converts an analog audio signal inputted from the audio input/output unit 31 into to a digital audio signal thereby output it to the DSP 33.

5 The DSP 33 performs a band compression process of a digital audio signal.

The display unit 34 displays an image in response to an image signal inputted from the control unit 38, for example, a liquid crystal display.

10 The operation unit 35 comprises operating buttons and outputs operation signals to the control unit 38 in response to an operation of the operating buttons by a user.

 The IC_I/F unit 36 is a UART (Universal
15 Asynchronons Receiver Transmitter), IC2, USB, IEEE 139 or other interfaces for transferring data with the IC 21 shown in FIG. 1.

 The memory 37 stores programs and data required in processes in the control unit 38 and the base band
20 processing unit 39.

 The memory 37 may be, for example, a memory fixed to the portable communication function unit 20 in a state where it cannot be detached, or may be a memory card or other memories detachable from the portable communication
25 function unit 20.

The memory 37 has a storage capacity of, for example, 64k or 1M bytes, etc.

Further, the portable communication function unit 20 stores in the memory 37, for example, a program defining a process using the IC 21, and in response to an instruction from the IC 21, may transmit a program read from the memory 37 by the control unit 38 to a control unit 48 of the IC 21 through the IC_I/F unit 36 and an I/F unit 45. Further, the control unit 48 executes the read program, whereby a process relating to a service may be performed in collaboration with the control unit 38 and the control unit 48 through the IC_I/F unit 36 and the I/F unit 45

The control unit 38 comprehensively controls the processes of the portable communication function unit 20, and together with being controlled by the control unit 48 shown in FIG. 9, controls the control unit 48.

The base band processing unit 39 performs a base band process.

The wireless unit 40 perform processes such as amplifying and detecting a wave of the data (signal) transferred through the antenna 17 and generating an IQ signal.

<IC 21>

The IC 21 is a tamper-resistant integrated circuit

capable of preventing illicit monitoring and tampering of data and processes in the IC 21 and data to be transferred with the outside, and performs processes relating to various kinds of services determined in advance to be provided using the IC_R/W apparatus 11 and the IC service providing apparatus 12.

FIG. 9 is a functional block diagram of the IC 21 shown in FIG. 1.

As shown in FIG. 9, the IC 21 comprises, for example, the I/F unit 45, a memory 46, an analog unit 47, and the control unit 48.

The I/F unit 45 is an interface for transferring data with the IC_I/F unit 36 of the portable communication function unit 20 shown FIG. 8 by a wired system or wireless system.

The memory 46 stores data and a program required in a process of the control unit 48. Note that an application program used in a portion of a service of the various services provided by using the IC 21 may be stored in the memory 46.

The analog unit 47 amplifies data (signal) transferred with the IC_R/W apparatus 11 through the antenna 49 by a wireless system and other analog processes.

The control unit 48 integrates processes of the IC

21 to thereby control the same.

The control unit 48 controls the control unit 38 together with being controlled by the control unit 38 of the portable communication function unit 20.

5 The base band processing unit 39 performs a base band process of a signal transferred with the wireless unit 40.

10 The IC 21, as shown in FIG. 10, utilizes an application program stored in a memory 52 of the virtual IC storage area server apparatus 13 shown in FIG. 3 through the portable communication function unit 20, the wireless communication line 17, and the network 18. The virtual IC storage area server apparatus 13 may be directly connected to the wireless communication line 17
15 by an exclusive line or the like.

FIG. 11 is a view for explaining a process sequence between the IC 21, the portable communication function unit 20 and the virtual IC storage area server apparatus 13 in the case where the IC 21 utilizes an application
20 program stored in the memory 52 of the virtual IC storage area server apparatus 13.

As shown in FIG. 11, the control unit 48 of the IC 21 transmits a memory access request to the control unit 38 of the portable communication function unit 20 (Step
25 ST200), and in response thereto, the control unit 38

transmits the memory access request to control unit 53 of the virtual IC storage area server apparatus 13 (Step ST201).

Then, in the case access to the memory 52 from the
5 IC 21 is permitted, the control unit 53 transmits a memory access permission notification to the control unit 38 of the portable communication function unit 20 (Step ST202), and the control unit 38 transmits the memory access permission notification to the control unit 48 of
10 the IC 21 in response thereto (Step ST203).

Then, when the control unit 48 of the IC 21 receives the memory access permission notification at step ST203, it performs a memory access operation to the control unit 38 of the portable communication function 20
15 (Step ST204), and in response thereto, the control unit 38 performs the memory access operation to the control unit 53 of the virtual IC storage area server apparatus 13 (Step ST205).

The control unit 53 accesses the memory 52 in
20 response to the memory access operation received from the control unit 38.

Then, when memory access is completed, the control unit 53 of the virtual IC storage area server apparatus 13 outputs a memory access acknowledge to the control
25 unit 38 of the portable communication function unit 20

(Step ST206), and in response thereto, the control unit 38 outputs the memory access acknowledge to the control unit 48 of the IC 21 (Step ST207).

Further, in the case an application program
5 defining a process of the IC 21 is stored in the memory 37 of the portable communication function unit 20, as shown in FIG. 12, the control unit 48 of the IC 21 accesses the memory 37 through the I/F unit 45, the IC_I/F unit 36, and the control unit 38.

10 In this case, the control unit 48 may execute an application program read from the memory 37, or the control unit 38 may execute the application program.

Note that in this case the control unit 48 may hand
over the access authority of the application program
15 stored in the memory 37 to the control unit 38, or the control unit 48 and the control unit 38 may access the application program while transmitting commands between each other.

Thus, according to the portable communication
20 function unit 20 and the IC 21, providing the I/F unit 45 and the IC_I/F unit 36 enabled communication between the portable communication function unit 20 and the IC 21.

Below, an example of an operation of the
communication system shown in FIG. 1 will be explained.

25 [First Operation Example]

Below, an explanation will be given of the example of the operation of the communication system 1 illustrating a case of performing a process relating to a service using the IC 21 by utilizing an application program stored in the virtual IC storage area server apparatus 13 when a service to be used by the user A is specified and selected by the user A.

FIG. 13 is a flow chart for explaining the above explanation.

Below, each of the steps shown in FIG. 13 will be explained.

Step ST1:

The user A operates the operation unit 35 of the portable communication function unit 20 of the portable telephone apparatus 14 shown in FIG. 8, and in response to this operation, the control unit 38 shown in FIG. 8 generates a virtual storage area use request (use request of the present invention) and transmits the same to the virtual IC storage area server apparatus 13.

Step ST2:

When the virtual IC storage area server apparatus 13 shown in FIG 3 receives the virtual storage area use request at step ST1, based on a control of the control 53, the SAM 51 generates an authentication request and transmits this to the portable communication function

unit 20.

Step ST3:

When the portable communication function unit 20 shown in FIG. 8 receives the authentication request at step ST2, the control unit 38 generates an authentication request and transmits the authentication request to the IC 21 through the IC_I/F unit 36.

The IC 21 shown in FIG. 9 receives the authentication request from the portable communication function unit 20 by the I/F unit 45.

Step ST4:

The control unit 48 of the IC 21 performs mutual authentication with the virtual IC storage area server apparatus 13 through the portable communication function unit 20 in response to the authentication request received at step ST3.

Step ST5:

When one another's legitimacy is authenticated by the mutual authentication of step ST4, the control unit 53 of the virtual IC storage area server apparatus 13 displays a content (content of a service) of a virtual storage area corresponding to the portable telephone apparatus 14 on the display unit 34 of the portable communication function unit 20.

Step ST6:

The user A selects a service for use by operating the operation unit 35 based on the virtual storage area content displayed at step ST5. Due to this, the control unit 38 of the portable communication function unit 20
5 generates an application select instruction for instructing the selecting of an application program corresponding to the selected service, and transmits the same to the virtual IC storage area server apparatus 13.

Step ST7:

10 Further, the control unit 38 of the portable communication function unit 20 generates a virtual storage area use instruction and transmits this to the IC 21 through the IC_I/F unit 36.

The IC 21 shown in FIG. 9 receives the virtual
15 storage area use instruction from the portable communication function unit 20 by the I/F unit 45.

Step ST8:

The IC_R/W apparatus 11 and the IC 21 are enabled into a wireless communication state through the antenna
20 49 of the IC 21. In this case, data is transferred and power is supplied between the IC_R/W apparatus 11 and the IC 21 through the antenna 49, whereby a stabilized direct current voltage is supplied to each of the circuits in the IC 21. Or, the IC_R/W apparatus 11 and the IC 21 may
25 be enabled into a wireless communication state by a power

source from a battery inside the portable telephone apparatus 14.

Step ST9:

In response to the application select instruction
5 of step ST6 and the virtual storage area use instruction
of step ST7, mutual authentication is conducted between
the IC_R/W unit 11 and the virtual IC storage area server
apparatus 13 through the IC 21 and the portable
communication function unit 20.

10 Step ST10:

When one another's legitimacy is authenticated by
the mutual authentication of step ST9, the control unit
53 of the virtual IC storage area server apparatus 13
reads the application program determined by the
15 application select instruction received at step ST6 from
the memory 52 and starts executing the application
program.

Step ST11:

While communicating through the portable
20 communication function unit 20 and the IC 21, the virtual
IC storage area server apparatus 13 executing the
application program and the IC_R/W unit 11 execute a
process relating to a service in collaboration with each
other.

25 Step ST12:

When the processing of step ST11 ends, the virtual IC storage area server apparatus 13 displays a use record thereof and a use record of the service on the display unit 34 of the portable communication function unit 20.

5 [Second Operation Example]

Below, an explanation will be given of the example of the operation of the communication system 1 illustrating the case of performing a process relating to a service using the IC 21 by utilizing an application program stored in the virtual IC storage area server apparatus 13 when a service to be selected by the IC_R/W apparatus 11 is automatically instructed to the virtual IC storage area server apparatus 13.

15 FIG. 14 is a flow chart for explaining the above exemplified operation.

Step St31:

20 The IC_R/W apparatus 11 and the IC 21 are enabled into a wireless communication state through the antenna 49 of the IC 21. In this case, data is transferred and power is supplied between the IC_R/W apparatus 11 and the IC 21 through the antenna 49, whereby a stabilized direct current voltage is supplied to each of the circuits in the IC 21. Or, the IC_R/W apparatus 11 and the IC 21 may be enabled into a wireless communication state by a power source from a battery inside the portable telephone

25

apparatus 14.

Step ST32:

The IC_R/W apparatus 11 transmits an application select instruction for determining an application program
5 corresponding to a service performed using the IC_R/W apparatus 11 to the IC 21.

The IC 21 shown in FIG. 9 receives the application select instruction from the IC_R/W apparatus 11 by the antenna 49 shown in FIG. 9.

10 Step ST33:

The control unit 48 of the IC 21 shown in FIG. 9 conducts a search to check whether the application program determined by the application select instruction received at step ST 32 is stored in the memory 46 or not.

15 Then, when the control unit 48 judges that the application program is stored in the memory 46, proceeds to the processing of step ST34, while when it judges that the application program is not stored in the memory 46, proceeds to the processing of step ST36.

20 Step ST34:

When it has been judged at step ST33 that the application program is stored in the memory 46, the IC 21 and the IC_R/W apparatus 11 conduct mutual authentication.

Step ST35:

25 When one another's legitimacy is authenticated by

the mutual authentication of step ST34, the control unit 48 of the IC 21 shown in FIG. 9 reads the application program from the memory 46 to execute the same.

Due to this, the IC 21 and the IC_R/W apparatus 11, while in communication, execute the process relating to the service in collaboration with each other.

Step ST36:

When it has been judged at step ST33 that the application program is not stored in the memory 46, the IC 21 notifies the IC_R/W apparatus 11 through the antenna 49 that there is no application program.

Step ST37:

Further, the control unit 48 of the IC 21 generates a virtual storage area use request and transmits this to the portable communication function 20 through the I/F unit 45.

Step ST38:

The portable communication function 20 shown in FIG. 8 receives the virtual storage area use request from the IC 21 by the IC_I/F unit 36, and transmits the same to the virtual IC storage area server apparatus 13 from the antenna 41.

Step ST39:

When the virtual IC storage area server apparatus 13 shown in FIG. 3 receives the virtual storage area use

request at step ST38, based on the control of the control unit 53, the SAM 51 generates an authentication request and transmits this to the portable communication function unit 20.

5 Step 40:

 When the portable communication function unit 20 shown in FIG. 8 receives the authentication request at step ST39, the control unit 38 generates an authentication request and transmits the authentication request to the IC 21 through the IC_I/F unit 36.

 The IC 21 shown in FIG. 9 receives the authentication request from the portable communication function unit 20 through the I/F unit 45.

 Step ST41:

15 The control unit 48 of the IC 21 performs mutual authentication with the virtual IC storage area server apparatus 13 through the portable communication function unit 20 in response to the authentication request received at step ST40.

20 Step ST42:

 When one another's legitimacy is authenticated by the mutual authentication of step ST41, the control unit 53 of the virtual IC storage area server apparatus 13 generates a virtual storage area use instruction and transmits the same to the portable communication function

unit 20.

Step ST43:

When the virtual storage area use instruction is received, the control unit 38 of the portable communication function unit 20 transmits this to the IC 21 through the IC_I/F unit 36.

The IC 21 shown in FIG. 9 receives the virtual storage area use instruction from the portable communication function unit 20 by the I/F unit 45.

Step ST44:

The IC_R/W apparatus 11 transmits an application select instruction for determining an application program corresponding to a service performed using the IC_R/W apparatus 11 to the virtual IC storage area server apparatus 13 through the IC 21 and the portable communication function unit 20.

Step ST45:

The IC_R/W apparatus 11 and the virtual IC storage area server apparatus 13 perform mutual authentication through the IC 21 and the portable communication function unit 20.

Step ST46:

When one another's legitimacy is authenticated by the mutual authentication of step ST9, the control unit 53 of the virtual IC storage area server apparatus 13

reads the application program determined by the application select instruction received at step ST6 from the memory 52 and starts executing the application program.

5 Step ST47:

 The virtual IC storage area server apparatus 13 executing the application program, and the IC_R/W unit 11 execute a process relating to a service in collaboration with each other while communicating through the portable communication function unit 20 and the IC 21.

 Step ST48:

 When the processing of step ST47 ends, the virtual IC storage area server apparatus 13 displays a use record thereof and a use record of the service on the display unit 34 of the portable communication function unit 20.

 [Third Operation Example]

 Below, an explanation will be given of the example of the operation of the communication system 1 illustrating the case of registering (secure) the IC virtual storage area 60a used by the IC 21 of the portable telephone apparatus 14 in a storage area of the memory 52 of the virtual IC storage area server apparatus 13 shown in FIG. 3.

 FIG. 15 is a flow chart for explaining the above exemplified operation.

Step ST51:

The user A operates the operating unit 35 of the portable communication function unit 20 of the portable telephone apparatus 14 shown in FIG. 8, and in response to the operation, the control unit 38 shown in FIG. 8
5 generates a virtual storage area register request and transmits the same to the virtual IC storage server apparatus 13.

Step ST52:

10 The control unit 53 of the virtual IC storage area server apparatus 13 shown in FIG. 3, in response to the virtual storage area register request received at step ST 51, displays a registration form (registration screen) on the display unit 34 of the portable communication
15 function unit 20 shown in FIG. 8.

Step ST53:

The user A inputs information such as the user's own name, address, and e-mail address required for registration according to the registration form of the
20 display unit 34.

The inputted information is transmitted to the virtual IC storage area server apparatus 13 through the antenna 41.

Step ST54:

25 The control unit 53 of the virtual IC storage area

server apparatus 13 issues an ID and a one time password for the portable telephone apparatus 14 and transmits the same to the portable communication function unit 20.

Step ST55:

5 The control unit 53 of the virtual IC storage area server apparatus 13 temporarily secures from among the storage areas in the memory 52, for example, the IC virtual storage area 60a shown in FIG. 5 for the portable telephone apparatus 14 (user A).

10 Step ST56:

The portable communication function unit 20 accesses the IC virtual storage area 60a by using the ID and the one time password received at step ST54.

Step ST57:

15 The portable communication function unit 20 changes the password. The changed password is managed by the control unit 53.

Step ST58:

20 In the virtual IC storage area server apparatus 13 shown in FIG. 3, based on a control of the control 53, the SAM 51 generates an authentication request and transmits this to the portable communication function unit 20.

Step ST59:

25 When the portable communication function unit 20

shown in FIG. 8 receives the authentication request at step ST58, the control unit 38 generates an authentication request and transmits the authentication request to the IC 21 through the IC_I/F unit 36.

5 The IC 21 shown in FIG. 9 receives the authentication request from the portable communication function unit 20 through the I/F unit 45.

Step ST60:

10 The control unit 48 of the IC 21 performs mutual authentication with the virtual IC storage area server apparatus 13 through the portable communication function unit 20 in response to the authentication request received at step ST59.

Step ST61:

15 When one another's legitimacy is authenticated by the mutual authentication of step ST60, an ID of the IC 21 (individual data) is received from the SAM 51 of the virtual IC storage area server apparatus 13.

Step ST62:

20 The SAM 51 of the virtual IC storage area server apparatus registers the ID of the IC 21 received at step ST 61, the ID issued at step ST54, and the password received at step ST57 in correspondence with the IC virtual storage area 60a shown in FIG. 5.

25 Step ST63:

The virtual IC storage area server apparatus 13 notifies the portable communication function unit 20 the fact that the IC virtual storage area 60a has been allocated to the portable telephone apparatus 14.

5 [Fourth Operation Example]

Below, an explanation will be given of an example of the operation illustrating a case of registering the application program 65a in the IC virtual storage area 60a allocated to the portable telephone apparatus 14 in the above third exemplified operation in response to an operation of the user A.

FIG. 16 is a flow chart for explaining the above exemplified operation.

Step ST71:

15 The user A operates the operation unit 35 of the portable communication function unit 20 of the portable telephone apparatus 14 shown in FIG. 8, and in response to the operation, the control unit 38 shown in FIG. 8 generates an application register request and transmits the same to the virtual IC storage area server apparatus 13.

Step ST72:

When the virtual IC storage area server apparatus 13 shown in FIG. 3 receives the application register request at step ST71, the SAM 51 generates an

authentication request and transmits the same to the portable communication function unit 20 based on the control of the control unit 53.

Step ST73:

5 When the portable communication function 20 shown in FIG. 8 receives the authentication request at step ST72, the control unit 38 generates an authentication request and transmits the authentication request to the IC 21 through the IC_I/F unit 36.

10 The IC 21 shown in FIG. 9 receives the authentication request from the portable communication function unit 20 by the I/F unit 45.

Step St74:

15 The control unit 48 of the IC 21 performs mutual authentication with the virtual IC storage area server apparatus 13 through the portable communication function unit 20 in response to the authentication request received at step ST73.

Step ST75:

20 When one another's legitimacy is authenticated by the mutual authentication of step ST74, the control unit 53 of the virtual IC storage area server apparatus 13 notifies the portable communication function unit 20 that preparation of registering the application is completed.

25 Step ST76:

The portable communication function unit 20 generates a relay instruction based on the notification of step ST75 and transmits the same to the IC 21 through the IC_I/F unit 36.

5 The IC 21 shown in FIG. 9 receives the relay instruction from the portable communication function unit 20 by the I/F unit 45.

Step ST77:

10 The IC_R/W apparatus 11 and the IC 21 are enabled to be in a wireless communication state via the antenna 49.

Step ST78:

15 The IC_R/W apparatus 11 and the virtual IC storage area server apparatus 13 perform mutual authentication through the IC 21 and the portable communication function 20.

Step ST79:

20 When one another's legitimacy is authenticated by the mutual authentication of step ST78, the virtual IC storage area server apparatus 13 and the IC_R/W apparatus 11, while communicating through the portable communication function unit 20 and the IC 21, performs the registering process of the application program 65a in collaboration with each other.

25 Specifically, the application program 65a is

transmitted to the virtual IC storage area server apparatus 13 from the IC_R/W apparatus 11, whereby the application program 65a is written in the memory 52 of the virtual IC storage area server apparatus 13.

5 Step ST80:

When the processing of step ST79 ends, the IC_R/W apparatus 11 notifies the portable communication function unit 20 through the IC 21 that the application program registration process has ended.

10 Step ST81:

When the processing of step ST79 ends, the virtual IC storage area server apparatus 13 notifies the portable communication function unit 20 that the application program registration process has ended.

15 Due to this, the portable communication function unit 20 ends the application program registration process.

[Fifth Operation Example]

Below, an explanation will be given of an example of the operation illustrating a case wherein an application program is automatically registered in the IC virtual storage area 60a allocated to the portable telephone apparatus 14 in the above third exemplified operation by the IC_R/W apparatus 11.

20

FIG. 17 is a flow chart for explaining the above exemplified operation.

25

Step ST91:

The IC_R/W apparatus 11 and the IC 21 are enabled to be in a wireless communication state via the antenna 49.

5

Step ST92:

The IC_R/W apparatus 11 and the IC 21 perform mutual authentication.

Step ST93:

10

When one another's legitimacy is authenticated by the mutual authentication of step ST92, an application registration request is transmitted to the IC 21 from the IC_R/W apparatus 11.

The application registration request is received through the antenna 49 of the IC 21 shown in FIG. 9.

15

Step ST94:

The IC 21 transmits the application registration request received at step ST93 to the portable communication function unit 20 through the I/F unit 45 shown in FIG. 9.

20

Steps ST95 to ST105:

Each of the processes of steps St95 to ST105 shown in FIG. 17 are the same as the processes of steps ST71 to ST81 shown in FIG. 16.

25

As explained above, in the communication system 1, even though the storage capacity of the memory 46 of the

IC 21 shown in FIG. 1 and FIG. 9 is limited, by storing in the virtual IC storage area server apparatus 13 the application program relating to a service performed using the data carrier function and/or the individual authentication function built into a chip of the IC 21 and executing the same, a variety of services can be provided even if using the IC 21 provided with a comparatively small size memory. It is not necessary to download the application program from the virtual IC storage area server apparatus 13 to the IC 21.

In other words, the IC 21 can utilize the virtual IC storage area server apparatus 13 of the network 18 as a virtual memory, whereby a plurality of services performed using a plurality of applications can be provided using one IC 21.

Further, according to the communication system 1, after the IC 21 and the virtual IC storage area server apparatus 13 have performed mutual authentication, and the IC_R/W apparatus 11 and the virtual IC storage area server apparatus 13 have performed mutual authentication, in order for the virtual IC storage area server apparatus 13 executing an application program and the IC_R/W apparatus 11 to execute the process relating to a service in collaboration with each other, illicit access can be prevented.

An effect of the above-mentioned communication system 1 is realized by the configuration and operation of the IC 21 built into the aforementioned portable telephone apparatus 14.

5 Further, according to the IC 21 built into the portable telephone apparatus 14, as shown in FIG. 9, providing the I/F unit 45 for communicating with the portable communication function unit 20 in addition to the antenna 45 which communicates with the IC_R/W
10 apparatus 11 enabled the portable communication function unit 20 and the IC 21 to mutually control each other. Therefore, for example, the portable communication function unit 20 is capable of disabling the IC 21 and the IC 21 is capable of disabling the portable
15 communication function unit 20 under a constant condition, whereby various controls can be realized from the viewpoint of a content and security of a service.

Second Embodiment

FIG. 18 is a view of the overall configuration of a
20 communication system 101 of the present invention.

As shown in FIG. 18, the communication system 101 comprises, for example, the gateway 10, an IC service providing apparatus 112, a virtual IC storage area server apparatus 113, and a portable telephone apparatus 114.

25 The portable telephone apparatus 114 and the

virtual IC storage area server apparatus 113 communicate through the wireless communication line 17 or other portable telephone communication network, the gateway 10, and the network 18 such as the Internet.

5 Further, the gateway 10, the IC service providing apparatus 112, and the virtual IC storage area server apparatus 113 are connected to the network 18.

As shown in FIG. 18, the communication system 101 is different from the communication system 1 shown in FIG. 10 1 in that the IC service providing apparatus 112 is connected to the network 18.

In the communication system 101, after the portable telephone apparatus 114 and the IC service providing apparatus 112 have communicated, the virtual IC storage area server apparatus 13 for executing an application 15 program and the IC service providing apparatus 12 communicate through the network 18 to be in collaboration with each other to thereby execute a process relating to an IC 121. The virtual IC storage area server apparatus 113 is directly connected to the gateway 10, and the IC 20 service providing apparatus 112 may be connected through the gateway 10 and the network 18.

The present embodiment is an embodiment corresponding to the 12th to 17th aspects and the 21st 25 and 22nd aspects of the present invention.

The IC service providing apparatus 112 corresponds to the second communication apparatus of the 12th and 13th aspects of the present invention, the communication apparatus of the 14th aspect, and the second
5 communication apparatus of the 16th and 17th aspects of the present invention.

Further, the portable telephone apparatus 114 corresponds to the first communication apparatus of the 12th to 17th aspects of the present invention.

10 Further, the virtual IC storage area server apparatus 113 corresponds to the third communication apparatus of the 12th and 13th aspects of the present invention, the second communication apparatus of the 14th and 15th aspects of the present invention, and the
15 communication apparatus of the 16th aspect of the present invention.

Below, each of the components shown in FIG. 18 will be explained.

[IC Service Providing Apparatus 112]

20 FIG. 19 is block functional diagram of the IC service providing apparatus 112 shown in FIG. 18.

As shown in FIG. 19, the IC service providing apparatus 112 is comprised of, for example, an I/F unit 131, an authentication unit 132, and a control unit 133.

25 The I/F unit 131 is connected to the network 18

shown in FIG. 18 and transfers a request and data through the network 18.

The authentication unit 132 performs mutual authentication with the virtual IC storage area server apparatus 113.

The control unit 133 comprehensively controls the processes of the service providing apparatus 112.

[Virtual IC Storage Area Server Apparatus 113]

The virtual IC storage area server apparatus 113 functions as a virtual memory of the IC 121 of the portable telephone apparatus 114, stores an application program relating to a service performed using a data carrier function and/or individual authentication function built into a chip of the IC 121, and executes the application program in response to an instruction from the IC 121. In response to the execution of the application program, the virtual IC storage area server apparatus 113, while communicating with the IC service providing apparatus 112 through the network 18 without going through the portable telephone apparatus 114, executes a service in collaboration with the IC service providing apparatus 112.

Fig. 20 is a functional block diagram of the virtual IC storage area server apparatus 113 shown in FIG.

18.

As shown in FIG. 20, the virtual IC storage area server apparatus 113 comprises, for example, a SAM 151, a memory 152, a control unit 153, and an I/F unit 154.

The SAM 151 is a tamper-resistant module of a hardware or software.

The SAM 151 conducts mutual authentication with the IC 121, mutual authentication with the IC service providing apparatus 112, encryption of an application program to be registered (write) in the memory 152, and decryption of an application program read from the memory 152.

The memory 152 is used as a virtual memory of the IC 121 and stores an application program relating to a service using the IC 121.

The memory 152, as shown in FIG. 20, comprises the IC virtual storage areas 60a, 60b, 60c... allocated to every user (portable telephone apparatus) in advance by a registration process which will be explained later. For example, the IC virtual storage area 60a is allocated to the user A of the portable telephone apparatus 14, the IC virtual storage area 60b is allocated to a user B, and the IC virtual storage area 60c is allocated to a user C.

Further, for example as shown in FIG. 6, the application programs 65a, 65b, and 65c registered by an application program registering process which will be

explained later are stored in the IC virtual storage area 60a. The application programs 65a, 65b, and 65c respectively are programs defining processes relating to services provided using the IC 21.

5 The control unit 153 comprehensively controls the processes of the virtual IC storage area server apparatus 113.

 The control unit 153 executes for example an application program read from the memory 152.

10 Further, the control unit 153 manages an application program stored in the memory 152. Specifically, the memory control unit 75 for example allocates the IC virtual storage area 60a to the portable telephone apparatus 114 and registers the application programs 65a, 65b, and 65c to the IC virtual storage area 60a.

[Portable Telephone Apparatus 114]

 As shown in FIG. 18, the portable telephone apparatus 114 comprises a portable communication function unit 120 and the IC 121.

20 The portable communication function unit 120 has a configuration similar to that of the portable communication function unit 20 of the first embodiment explained using FIG. 8.

25 The IC 121 is a tamper-resistant integrated circuit

capable of preventing illicit monitoring and tampering of data and processes in the IC 121 and data to be transferred with the outside, and performs processes relating to various kinds of services determined in advance to be provided by using the IC service providing apparatus 112.

FIG. 21 is a functional block diagram of the IC 121 shown in FIG. 18.

As shown in FIG. 21, the IC 121 comprises, for example, an I/F unit 145, a memory 146, and a control unit 148.

The I/F unit 45 is an interface for transferring data with the portable communication function unit 120 shown FIG. 18 by a wired system or wireless system.

The memory 146 stores data and a program required in a process of the control unit 48. Note that an application program used in a portion of a service of the various services provided by using the IC 21 may be stored in the memory 146.

The control unit 148 comprehensively controls the process of the IC 121, transfers a command with the control unit 38 shown in FIG. 8, and conducts a predetermined control in collaboration therewith.

Below, an example of an operation of the communication system 101 shown in FIG. 18 will be

explained.

[First Operation Example]

Below, an explanation will be given of the example of the operation of the communication system 101 illustrating a case of performing a process relating to a service using the IC 121 by utilizing an application program stored in the virtual IC storage area server apparatus 113 when a service to be used by the user A is specified and selected by the user A.

FIG. 22 is a flow chart for explaining the above explanation.

Below, each of the steps shown in FIG. 22 will be explained.

Step ST301:

The user A operates the operation unit 35 shown in FIG. 8 of the portable communication function unit 120 of the portable telephone apparatus 114, and in response to this operation, the control unit 38 shown in FIG. 8 access the IC service providing apparatus 112 through the wireless communication line 17, the gateway 10, and the network 18.

Step ST302:

The user A operates the operation unit 35, whereby in response to this operation, the control unit 38 transmits a use service select instruction for selecting

and instructing a service to be used to the IC service providing apparatus 112.

Step ST303:

5 The control unit 133 of the IC service providing apparatus 112 shown in FIG. 19 generates an application select instruction that has specified an application program corresponding to the use service select instruction received at step ST302 and transmits the same to the portable communication function unit 120 of the
10 portable telephone apparatus 114.

Step ST304:

The control unit 153 of the virtual IC storage area server apparatus 113 shown in FIG. 20 generates a virtual storage area use request in response to the application
15 select instruction received at step ST303 and transmits the same to the virtual IC storage area server apparatus 113.

Step ST305:

20 When the virtual IC storage area server apparatus 113 shown in FIG. 20 receives the virtual storage area use request at step ST304, based on a control of the control unit 153, the SAM 151 generates an authentication request and transmits the same to the portable communication function unit 120.

25 Step ST306:

When the portable communication function unit 120 receives the authentication request at step ST305, the control unit 38 generates an authentication request and transmits the authentication request to the IC 121 through the IC_I/F unit 36.

The IC 121 shown in FIG. 21 receives the authentication request from the portable communication function unit 120 by the I/F unit 145.

Step ST307:

The control unit 148 of the IC 121 conducts mutual authentication with the virtual IC storage area server apparatus 113 through the portable communication function unit 120 in response to the authentication request received at step ST306.

Step ST308:

When one another's legitimacy is authenticated by the mutual authentication of step ST307, the control unit 153 of the virtual IC storage area server apparatus 113 displays a content (content of a service) of a virtual storage area corresponding to the portable telephone apparatus 114 on the display unit 34 of the portable communication function unit 120.

Step ST309:

The user A selects a service for use by operating the operation unit 35 based on the virtual storage area

content displayed at step ST308. Due to this, the control unit 38 of the portable communication function unit 120 generates an application select instruction for instructing the selecting of an application program corresponding to the selected service, and transmits the same to the virtual IC storage area server apparatus 113.

Step ST310:

In response to the application select instruction of step ST309, the IC service providing apparatus 112 and the virtual IV storage area server apparatus 113 conduct mutual authentication through the network 18.

Step St311:

When one another's legitimacy is authenticated by the mutual authentication of step ST310, the control unit 153 of the virtual IC storage area server apparatus 113 shown in FIG. 20 reads the application program determined by the application select instruction received at step ST309 from the memory 152 to start executing the same.

Step ST312:

While communicating through the network 18, the virtual IC storage area server apparatus 113 executing the application program and the IC service providing apparatus 112 perform a process relating to a service in collaboration with each other.

Step ST313:

When the processing of step ST312 ends, the IC service providing apparatus 112 notifies the portable communication function unit 120 the end of the application process.

5 Step ST314:

When the processing of step ST312 ends, the virtual IC storage area server apparatus 113 displays a use record thereof and a use record of the service on the display unit 34 of the portable communication function
10 unit 120.

[Second Operation Example]

Below, an explanation will be given of an example of the operation of the communication system 101 illustrating a case of performing a process relating to a
15 service using the IC 121 by utilizing an application program stored in the virtual IC storage area server apparatus 113 when a service provided by the IC service providing apparatus 112 itself is automatically instructed to the virtual IC storage area server
20 apparatus 113.

FIG. 23 is a flow chart for explaining the above exemplified operation.

Step ST320

The user A operates the operation unit 35 shown in
25 FIG. 8 of the portable communication function unit 120 of

the portable telephone apparatus 114, and in response to this operation, the control unit 38 shown in FIG. 8 access the IC service providing apparatus 112 through the wireless communication line 17, the gateway 10, and the network 18.

Step ST321:

The user A operates the operation unit 35, whereby in response to this operation, the control unit 38 transmits a use service select instruction for selecting and instructing a service to be used to the IC service providing apparatus 112.

Step ST322:

The control unit 133 of the IC service providing apparatus 112 shown in FIG. 19 generates an application select instruction that has specified an application program corresponding to the use service select instruction received at step ST321 and transmits the same to the portable communication function unit 120 of the portable telephone apparatus 114.

Step ST323:

The portable communication function unit 120 transmits a search instruction for the application program indicated by the application select instruction received at step ST322 to the IC 121.

The search instruction is received by the I/F unit

145 shown in FIG. 21.

Step ST324:

The control unit 148 of the IC 121 shown in FIG. 21 searches to check if the application program that became
5 the target of the search instruction is stored in the memory 146 or not.

Then, when the control unit 148 judges that the application program is stored in the memory 146, proceeds to step ST325, while when it judges that the application
10 program is not stored in the memory 146, proceeds to step ST328.

Step ST325:

When it has been judged that the application program is stored in the memory 146 by the search of step
15 ST324, the IC 121 and the IC service providing apparatus 112 conduct mutual authentication.

Step ST326:

When one another's legitimacy is authenticated by the mutual authentication of step ST325, the control unit
20 148 shown in FIG. 21 executes the application program read from the memory 146, whereby the IC 121 and the IC service providing apparatus 112 performs the process relating to a service in collaboration with each other.

Step ST327:

25 When the processing of step ST326 ends, the control

unit 133 of the IC service providing apparatus 112 shown in FIG. 19 generates an application end notification and transmits the same to the portable communication function unit 120 of the portable telephone apparatus 114.

5 Step ST328:

 When it has been judged that the application program is not stored in the memory 146 by the search of step ST324, the portable communication function unit 120 of the portable telephone apparatus 114 generates a
10 virtual storage area use request and transmits the same to the virtual IC storage area server apparatus 113.

 Step ST329:

 When the virtual IC storage area server apparatus 113 shown in FIG. 20 receives the virtual storage area
15 use request at step ST328, based on a control of the control unit 153, the SAM 151 generates an authentication request and transmits the same to the portable
communication function unit 120.

 Step ST330:

20 When the portable communication function unit 120 receives the authentication request at step ST329, the control unit 38 generates an authentication request and transmits the authentication request to the IC 121
through the IC_I/F unit 36.

25 The IC 121 shown in FIG. 21 receives the

authentication request from the portable communication function unit 120 by the I/F unit 45.

Step ST331:

5 The control unit 148 of the IC 121 conducts mutual authentication with the virtual IC storage area server apparatus 113 through the portable communication function unit 120 in response to the authentication request received at step ST330.

Step ST332:

10 When one another's legitimacy is authenticated by the mutual authentication of step ST331, the control unit 153 of the virtual IC storage area server apparatus 113 displays a content (content of a service) of a virtual storage area corresponding to the portable telephone apparatus 114 on the display unit 34 of the portable communication function unit 120.

Step ST333:

20 Based on the virtual storage area content displayed at step ST332, the user A selects a service for use by operating the operation unit 35. Due to this, the control unit 38 of the portable communication function unit 120 generates an application select instruction for instructing the selecting of an application program corresponding to the selected service, and transmits the same to the virtual IC storage area server apparatus 113.

25

Step ST334:

In response to the application select instruction of step ST333, the IC service providing apparatus 112 and the virtual IV storage area server apparatus 113 conduct mutual authentication through the network 18.

Step St335:

When one another's legitimacy is authenticated by the mutual authentication of step ST334, the control unit 153 of the virtual IC storage area server apparatus 113 shown in FIG. 20 reads the application program determined by the application select instruction received at step ST333 from the memory 152 to start executing the same.

Step ST336:

The IC service providing apparatus 112 and the virtual IC storage area server apparatus 113 communicate with each other in response to the execution of the application program and perform a process relating to a service in collaboration with each other.

Step ST337:

When the processing of step ST336 ends, the IC service providing apparatus 112 notifies the portable communication function unit 120 the end of the application process.

Step ST338:

When the processing of step ST336 ends, the virtual

IC storage area server apparatus 113 displays a use record thereof and a use record of the service on the display unit 34 of the portable communication function unit 120.

5 [Third Operation Example]

 An exemplified example of the communication system 101 of a case of registering (secure) the IC virtual storage area 60a used by the IC 121 of the portable telephone apparatus 114 in a storage area of the memory 10 152 of the virtual IC storage area server apparatus 113 shown in FIG. 20 is specifically the same as the case shown in FIG. 15 except for the point that communication is conducted between the IC 121, the portable communication function unit 120, and the virtual IC 15 storage area server apparatus 113.

 [Fourth Operation Example]

 Below, an explanation will be given of an example of the operation illustrating a case of registering the application program 65a in the IC virtual storage area 20 60a allocated to the portable telephone apparatus 114 in the above third exemplified operation when the portable communication function unit 120 does not conduct confirmation for an available space in the IC virtual storage area 60a.

25 FIG. 24 is a flow chart for explaining the above

exemplified operation.

Step ST341:

The user A operates the operation unit 35 shown in FIG. 8 of the portable communication function unit 120 of the portable telephone apparatus 114, and in response to the operation, the control unit 38 shown in FIG. 8 generates an application program register request and transmits the same to the IC service providing apparatus 112.

Step ST342:

When the IC service providing apparatus 112 receives the application register request at step ST341, it displays a registration format of the application program on the display unit 34 shown in FIG. 8 of the portable communication function unit 120.

Step ST343:

The user A operates the operation unit 35 shown in FIG. 8 of the portable communication function unit 120 of the portable telephone apparatus 114 to input information required for registration of the application program, and the inputted information is transmitted to the IC service providing apparatus 112.

Step ST344:

The IC service providing apparatus 112 inquires the portable communication function unit 120 a designation

for registering the application program.

Step ST345:

In response to the inquiry received at step ST344,
the portable communication function unit 120 transmits to
5 the IC service providing apparatus 112 a register
destination designation indicating the virtual IC storage
area server apparatus 113 (if necessary, IC virtual
storage area 60a) for registering an application program.

Step ST346:

10 The portable communication function 120 of the
portable telephone apparatus 114 generates an application
register request requesting registration of the
application program to the virtual IC storage area server
apparatus 113 and transmits the same to the IC storage
15 area server apparatus 113.

Step ST347:

When the virtual IC storage area server apparatus
113 shown in FIG. 20 receives the application register
request at step ST346, based on a control of the control
20 unit 153, the SAM 151 generates an authentication request
and transmits the same to the portable communication
function unit 120.

Step ST348:

When the portable communication function unit 120
25 receives the authentication request at step ST347, the

control unit 38 generates an authentication request and transmits the authentication request to the IC 121 through the IC_I/F unit 36.

5 The IC 121 shown in FIG. 21 receives the authentication request from the portable communication function unit 120 by the I/F unit 45.

Step ST349:

10 The control unit 148 of the IC 121 conducts mutual authentication with the virtual IC storage area server apparatus 113 through the portable communication function unit 120 in response to the authentication request received at step ST348.

Step ST350:

15 When one another's legitimacy is authenticated by the mutual authentication of step ST349, the control unit 153 of the virtual IC storage area server apparatus 113 notifies the portable communication function unit 120 that preparation for registering the application is completed.

20 Step ST351:

The portable communication function unit 120 generates a registration start request requesting the start of registering the application program on the basis of the notification of step ST350 and transmits the same to the IC service providing apparatus 112.

25

Step ST352:

71 The IC service providing apparatus 112 and the virtual IC storage area server apparatus 113 conduct mutual authentication.

5 Step ST353:

When one another's legitimacy is authenticated by the mutual authentication of step ST352, the IC service providing apparatus 112 and the virtual IC storage area server apparatus 113 communicate with each other and perform a registration process of the application program 65a.

Specifically, the application program 65a is transmitted from the IC service providing apparatus 112 to the virtual IC storage area server apparatus 113, whereby the application program 65a is written in the memory 152 of the virtual IC storage area server apparatus 113.

Step ST354:

20 When the processing of step ST353 ends, the IC service providing apparatus 112 notifies the portable communication function unit 120 through the IC 121 that the application registration process has ended.

Step ST355:

25 When the processing of step ST353 ends, the virtual IC storage area server apparatus 113 notifies the

portable communication function unit 120 through the IC 121 that the application registration process has ended.

Due to this, the portable communication function unit 120 ends the application registration process.

5 [Fifth Operation Example]

Below, an explanation will be given of an example of an operation illustrating a case of registering the application program 65a in the IC virtual storage area 60a allocated to the portable telephone apparatus 114 in 10 the above third exemplified operation when the portable communication function unit 120 conducts confirmation of available space in the IC virtual storage area 60a.

FIG. 25 is a flow chart for explaining the above exemplified operation.

15 The processing of steps ST361 to ST363 shown in FIG. 25 are the same as those of steps ST341 to ST343 shown in FIG. 24.

Further, the processing of steps ST368 to ST377 shown in FIG. 25 are the same as those of steps ST346 to 20 ST355 shown in FIG. 24.

In the process shown in FIG. 25, the IC service providing apparatus 112 transmits the registration designation inquiry together with a required memory capacity for storing the application program to be 25 registered to the portable communication function unit

120 (Step ST364).

Next, the portable communication function unit 120 searches the IC virtual storage area 60a of the virtual IC storage area server apparatus 113 to check if there is the required available space or not (Step ST365).

Then, when there is no available space, the IC service providing apparatus 112 is notified from the portable communication function unit 120 that there is no available space (Step ST366).

On the other hand, when there is available space, an application register request is outputted from the portable communication function unit 120 to the virtual IC storage area server apparatus 113 (Step ST368), and a register destination designation indicating the virtual IC storage area server apparatus 113 is transmitted to the IC service providing apparatus 112 from the portable communication function unit 120 (Step ST367).

As explained above, in the communication system 101, even though there is a limit in the storage capacity of the memory 146 of the IC 121 shown in FIG. 18 and FIG. 19, by storing in the virtual IC storage area server apparatus 113 the application program relating to a service performed using the data carrier function and/or the individual authentication function built into a chip of the IC 121 and the virtual IC storage area server

apparatus 113 executing the same, a variety of services can be provided using the IC 121 provided with a comparatively small size memory. Further, in this case, an application program need not be downloaded from the virtual IC storage area server apparatus 113 to the IC 121 because communication based on the application program is performed between the IC service providing apparatus 112 and the virtual IC storage area server apparatus 113.

In other words, a plurality of services performed using a plurality of applications can be provided using the IC 121 alone.

Further, according to the communication system 101, after the IC 121 and the virtual IC storage area server apparatus 113 have performed mutual authentication, and the IC service providing apparatus 112 and the virtual IC storage area server apparatus 113 have performed mutual authentication, in order for the virtual IC storage area server apparatus 113 executing an application program and the IC service providing apparatus 112 to execute the process relating to a service in collaboration with each other, illicit access can be prevented.

An effect of the above-mentioned communication system 101 is realized by the configuration and operation of the IC 121 built into the aforementioned portable

telephone apparatus 114.

Further, according to the IC 121 built into the portable telephone apparatus 114, as shown in FIG. 21, providing the I/F unit 145 for communicating with the portable communication function unit 120 enabled the portable communication function unit 120 and the IC 121 to mutually control each other. Therefore, for example, the portable communication function unit 120 is capable of disabling the IC 21 and the IC 121 is capable of disabling the portable communication function unit 120 under a constant condition, whereby various controls can be realized from the viewpoint of a content and security of a service.

The present invention is not limited to the above explained embodiments.

Although cases in which the ICs 21 and 121 built into the portable telephone apparatuses 14 and 114 were exemplified in the above explained embodiments, the present invention is applicable to a fixed telephone connected to fixed line, a portable information terminal (Personal Digital Assistants), that is, a compact information equipment, a clock, a computer, etc., and even to a case in which the ICs 21 or 121 is built into equipment having the capability of being able to be connected to a network by either the wired or wireless

system.

Further, the ICs 21 and 121 may be detachably built into the communication apparatus or non-detachably built therein. IC cards having the ICs 21 and 121 built therein or a memory card or other external storage mediums may be detachably configured in a portable telephone apparatus, a portable information terminal, a computer or the like.

INDUSTRIAL APPLICABILITY

As explained above, according to the present invention, a communication method and a system of the same, a communication apparatus, a processing apparatus and a method of the same capable of providing a variety of services by using a single integrated circuit without limitations placed on the storage capacity of the memory built into the integrated circuit can be provided.

CLAIMS

5 1. A service providing method wherein a communication apparatus and a processing apparatus communicate with each other in response to a service use request issued from said communication apparatus to provide a service to a user of said communication apparatus, comprising the steps of:

10 performing communication between a server apparatus storing a program defining a process relating to said service and said communication apparatus to judge if use of said program is permitted or not in response to said service use request, said program being
15 stored in a storage area of the server apparatus allocated in advanced to said communication apparatus;

 executing said program by said server apparatus when use of said program is permitted; and

 performing communication between said server
20 apparatus and said processing apparatus through said communication apparatus in response to the execution of said program by said server apparatus to provide said service to said user, said service being provided by using a function of data carrier and/or authentication
25 in said communication apparatus and a reader/writer function in said processing apparatus.

 2. A service providing method as claimed in claim 1, wherein said communication apparatus transmits said service use request indicating use of said storage
30 area to said server apparatus.

 3. A server apparatus communicating with a communication apparatus and a processing apparatus that transfers data with said communication apparatus and

used in a service to a user of said communication apparatus, comprising:

5 means for storing a program defining a process relating to said service, said program being stored in a storage area of the server apparatus allocated in advance to said communication apparatus;

means for receiving a service use request from said communication apparatus;

10 means for authenticating if said service use request is legitimate or not; and

means for controlling a processing for providing a service to said user in collaboration with the processing apparatus in response to the execution of a program defining a process relating to said service by
15 reading the program from said storing means and executing the read program when it is judged that said service use request is legitimate, said service being provided by using a function of data carrier and/or authentication in said communication apparatus and a
20 reader/writer function in said processing apparatus.

4. The service providing method claimed in claim 1, wherein:

said communication apparatus is a portable
25 communication apparatus and includes an integrated circuit and a wireless communication circuit performing communication using a wireless communication network, and

said server apparatus is connected to a
30 network, and

said integrated circuit communicates with said server apparatus through said wireless communication circuit, said wireless communication network, and said network.

5 5. The service providing method claimed in claim 4, wherein said integrated circuit comprises a first interface for transferring data with said processing apparatus and a second interface for transferring data with said communication circuit.

10 6. A communication method wherein a communication apparatus comprising an integrated circuit and a communication circuit communicates with a processing apparatus that transfers data with said integrated circuit and used in a service relating to the integrated circuit, comprising the steps of:

 receiving a use request of a program from said integrated circuit through said communication circuit;

15 reading an application program relating to said use request from a storing means;

 executing the read program; and

20 communicating with said processing apparatus through said communication circuit and said integrated circuit in response to the execution of the program and performing a process relating to said service in collaboration with the processing apparatus; wherein

25 said program being stored in a storage area of the storing means allocated in advanced to said communication apparatus; and

 said service being provided by using a function of data carrier and/or authentication in said communication apparatus and a reader/writer function in said processing apparatus.

30 7. A processing apparatus that transfers data with a first communication apparatus and used in a service provided to a user of said first communication apparatus, wherein,

after a second communication apparatus storing a program defining a process relating to said service and executing the same, and said first communication apparatus have authenticated one another's legitimacy by a mutual authentication conducted through said communication circuit, said processing apparatus while communicating with said second communication apparatus through said first communication apparatus, performs a process relating to said service in collaboration with said second communication apparatus;

said program being stored in a storage area of the second communication apparatus allocated in advanced to said first communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function for said processing apparatus.

8. A processing apparatus as claimed in claim 7, wherein in response to a use request of said program from said first communication apparatus to said second communication apparatus, said processing apparatus transmits to said second communication apparatus through said first communication apparatus an instruction selecting a program relating to said service to be executed by said second communication apparatus when use permission is received from said second communication apparatus through said first communication apparatus.

9. An integrated circuit access apparatus transferring data between an integrated circuit built into a first communication apparatus and a processing apparatus used in a service provided to a user of said first communication apparatus, wherein

after a second communication apparatus storing a program defining a process relating to said service and executing the same, and said first communication apparatus have authenticated one another's legitimacy by a mutual authentication conducted through said communication circuit, transfers data between said integrated circuit and said processing apparatus to relay communication between said second communication apparatus and said processing apparatus performed through said integrated circuit;

said program being stored in a storage area of the second communication apparatus allocated in advance to said first communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function in said processing apparatus.

10. A processing method transferring data with a first communication apparatus comprising an integrated circuit and a communication circuit and used in a service relating to said integrated circuit, comprising the steps of:

conducting mutual authentication of a second communication apparatus storing a program defining a process relating to said service and executing the same, and said integrated circuit through said communication circuit, and after one another's legitimacy is authenticated by the mutual authentication;

relaying said integrated circuit; and

while communicating with said second communication apparatus executing said program, performs a process relating to said service in collaboration with said second communication apparatus; wherein

100

said program being stored in a storage area of the second communication apparatus allocated in advanced to said first communication apparatus; and

5 said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function for said integrated circuit.

10 11. A communication method performing communication using a first communication apparatus comprising an integrated circuit and a communication circuit, a second communication circuit used in a service relating to said integrated circuit, and a third communication apparatus storing a program defining a
15 process relating to said integrated circuit and executing the same, comprising the steps of:

 transmitting a use request of said program from said integrated circuit to said third communication apparatus through said communication circuit;

20 conducting mutual authentication between said integrated circuit and said third communication apparatus through said communication circuit; and

 conducting mutual authentication between said second communication apparatus and said third
25 communication apparatus when the legitimacy of said integrated circuit and said third communication apparatus has been authenticated by the mutual authentication thereof, and

30 when said second communication apparatus and said third communication apparatus have authenticated one another's legitimacy by the mutual authentication, executing by said third communication apparatus said program relating to said use request, whereby said second communication apparatus and said third

101

communication apparatus communicate to perform a process relating to said service in collaboration with each other in response to the execution of said program; wherein

said program being stored in a storage area of the third communication apparatus allocated in advanced to said first communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function in said second communication circuit.

12. A communication method as claimed in claim 11, further comprising the steps of:

transmitting from said second communication apparatus to said first communication apparatus a program select instruction for instructing a program to be selected and used;

transmitting by said first communication apparatus on the basis of said program select instruction a program select instruction to said third communication instruction; and

executing by said third communication apparatus a program specified by said program select instruction received from said first communication apparatus.

13. A communication method as claimed in claim 11, further comprising the steps of:

transmitting from said second communication apparatus to said first communication apparatus a program select instruction for instructing a program to be selected and used;

judging by said integrated circuit if a program to be used in a service performed using said

102

second communication apparatus is stored or not in response to said program select instruction;

5 when said integrated circuit judges said program is stored, executing by said integrated circuit the program, and performing a process relating to said service by said integrated circuit and said second communication apparatus in collaboration with each other in response to the execution of the program; and

10 when said integrated circuit judges said program is not stored, transmitting by said first communication apparatus a program select instruction to said third communication apparatus, executing by said third communication apparatus a program specified by a
15 program select instruction received from said first communication apparatus, and performing a process relating to said service by said second communication apparatus and said third communication apparatus in collaboration with each other in response to the
20 execution of said program.

14. A communication method as claimed in claim 11, wherein:

 said first communication apparatus is a portable type communication apparatus;

25 said communication circuit is a wireless communication circuit performing communication using a wireless communication network;

 said second communication apparatus and third communication apparatus are connected to a network;

30 said integrated circuit communicates with said second communication apparatus and said third communication apparatus through said communication circuit, said wireless communication network, and said network; and

said second communication apparatus and said third communication apparatus communicate through said network.

5 15. A communication system comprising:

 a first communication apparatus comprising an integrated circuit and a communication circuit;

 a second communication apparatus used in a service relating to said integrated circuit; and

10 a third communication apparatus storing a program defining a process relating to said service and executing the same, wherein:

 a use request of said program is transmitted from said integrated circuit to said third communication apparatus through said communication circuit;

15 mutual authentication is conducted between said integrated circuit and said third communication apparatus through said communication circuit;

 when said integrated circuit and said third communication apparatus have authenticated one another's legitimacy by the mutual authentication, said second communication apparatus and said third communication apparatus conducts mutual authentication; and

20 when said second communication apparatus and said third communication apparatus have authenticated one another's legitimacy by the mutual authentication, said third communication apparatus executes said program relating to said use request, and said second communication apparatus and said third communication apparatus communicate in response to the execution of

25 the program to perform a process relating to said service in collaboration with each other;

30

said program being stored in a storage area of the third communication apparatus allocated in advanced to said first communication apparatus; and

5 said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function in said second communication apparatus.

10 16. A communication apparatus communicating with a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus storing a program defining a process relating to a service and used in a service relating to said integrated circuit, comprising:

15 means for authenticating with said second communication apparatus after said integrated circuit and said second communication apparatus have authenticated one another's legitimacy by a mutual authentication; and

20 means for communicating with said second communication apparatus executing said program to perform a process relating to said service in collaboration with each other after one another's legitimacy with said second communication apparatus has
25 been authenticated by a mutual authentication through said authentication means;

 wherein said program being stored in a storage area of the second communication apparatus, allocated in advanced to said first communication apparatus; and

30 said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function in said communication apparatus.

17. A communication method performed between a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus storing a program defining a process relating to a service to be provided using said integrated circuit and executing the same, comprising the steps of:

conducting mutual authentication with said second communication apparatus after said integrated circuit and said second communication apparatus have authenticated one another's legitimacy by a mutual authentication; and

communicating with said second communication apparatus executing said program to perform a process relating to said service in collaboration with each other after one another's legitimacy with second communication apparatus has been authenticated by said mutual authentication with said second communication apparatus;

wherein said program being stored in a storage area the second communication apparatus, allocated in advanced to said first communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function for said first communication apparatus.

18. A communication apparatus communicating with a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus used in a service relating to said integrated circuit, comprising:

a storing means for storing a program defining a process relating to said service in a storage area of

the storing means allocated in advance to said first communication apparatus;

5 a receiving means for receiving a use request of said program from said integrated circuit through said communication circuit;

10 an authentication means for conducting mutual authentication with said integrated circuit through said communication circuit in response to said use request and after one another's legitimacy has been authenticated by the mutual authentication, conducting mutual authentication with said second communication apparatus; and

15 when one another's legitimacy with said second communication apparatus has been authenticated by said mutual authentication, a controlling means for reading said program relating to said use request from said storing means and executing the same, and communicating with said second communication apparatus in response to
20 the execution of the program to perform a process relating to said service in collaboration with each other;

25 wherein said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function in said communication apparatus.

30 19. A communication method wherein a first communication apparatus comprising an integrated circuit and a communication circuit, and a second communication apparatus used in a service relating to said integrated circuit communicates, comprising the steps of:

receiving a use request of a program defining a process relating to said service from said integrated circuit through said communication circuit;

conducting mutual authentication with said integrated circuit through said communication circuit in response to said use request, and after one another's legitimacy has been authenticated by the mutual authentication, conducting mutual authentication with said second communication apparatus;

reading a program relating to said use request from a storing means and executing the same when one another's legitimacy with said second communication apparatus has been authenticated by said mutual authentication; and

communicating with said second communication apparatus in response to the execution of the program to perform a process relating to said service in collaboration with each other;

wherein said program being stored in a storage area of the storing means allocated in advanced to said first communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function for said first communication apparatus.

20. An integrated circuit transferring data with a communication circuit of a first communication apparatus and a processing apparatus performing a process relating to a predetermined service, comprising:

a first interface for transferring data with said processing apparatus;

a second interface for transferring data with said communication circuit; and

a controlling means for accessing a second communication apparatus through said second interface and said communication circuit, and while communicating

with said processing apparatus through said first interface, performs a process relating to said service using a program or data stored in said second communication apparatus; wherein

said program or data being stored in a storage area of the second communication apparatus allocated in advanced to said first communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function in said processing apparatus.

21. An integrated circuit as claimed in claim 20, wherein when said second communication apparatus stores a program defining a process relating to said service and executes the same, said controlling means conducts mutual authentication with said second communication apparatus through said second interface and said communication circuit, and then controls communication of said second communication apparatus executing said program and said processing apparatus performed through said communication circuit so that said first interface and said second interface relays the same.

22. An integrated circuit as claimed in claim 20, wherein said controlling means communicates with said second communication apparatus through said second interface and said communication circuit to conduct said mutual authentication based on an authentication request received from said second communication through said communication circuit.

23. An integrated circuit as claimed in claim 20, further comprising a storage circuit storing a program relating to a service provided using said integrated circuit, wherein

said controlling means judges if said program corresponding to a request received from said processing apparatus through said first interface is stored in said storage circuit or not, and when judged that said program is stored in said storage circuit, executes said program read from said storage circuit and while communicating with said processing apparatus through said first interface in response to the execution of the program, performs a process relating to said service.

24. An integrated circuit as claimed in claim 23, wherein when said controlling means judges that said program is not stored in said storage circuit, transmits a use request of said program to said second communication apparatus through said second interface and said communication circuit.

25. An integrated circuit as claimed in claim 20, wherein:

said first communication apparatus is a portable type communication apparatus;

said communication circuit is a wireless communication circuit performing communication using a wireless communication network;

said second communication apparatus is connected to a network; and

said controlling circuit communicates with said second communication apparatus through said second interface, said communication circuit, said wireless communication network, and said network.

26. An integrated circuit as claimed in claim 20, wherein said integrated circuit is a tamper-resistant circuit.

27. An electronic circuit having a communication means and an integrated circuit mounted on a substrate, wherein said integrated circuit comprises:

5 a first interface transferring data with a processing apparatus performing a process relating to a predetermined service;

 a second interface transferring data with said communication means; and

10 a controlling means for accessing a second communication apparatus through said second interface and said communication circuit, and while communicating with said processing apparatus through said first interface, performs a process using a program or data
15 stored in said second communication apparatus, said program or data is being stored in a storage area of the second communication apparatus allocated in advance to said electronic circuit;

 wherein said predetermined service being
20 provided by using a function of data carrier and/or authentication in said electronic circuit and a reader/writer function in said processing apparatus.

28. An electronic circuit as claimed in claim 27, wherein when said second communication apparatus stores
25 a program defining a process relating to said service and executes the same,

 said controlling means conducts mutual authentication said second communication apparatus through said second interface and said communication
30 circuit, and then controls communication of said second communication apparatus executing said program and said processing apparatus performed through said communication circuit so that said first interface and said second interface relays the same.

111

29. A communication apparatus comprising a communication circuit and an integrated circuit, wherein said integrated circuit comprises:

5 a first interface for transferring data with a processing apparatus performing a process relating to a predetermined service;

 a second interface for transferring data with said communication circuit; and

10 a controlling means for accessing another communication apparatus through said second interface and said communication circuit, and while communicating with said processing apparatus through said first interface, performs a process using a program or data
15 stored in said another communication apparatus, said program or data is being stored in a storage area with another communication apparatus allocated in advanced to said communication apparatus;

 wherein said predetermined service being
20 provided by using a function of data carrier and/or authentication in said communication apparatus and a reader/writer function in said processing apparatus.

30. A communication apparatus as claimed in claim 29, wherein:

25 said communication circuit comprises a storage circuit for storing a program or data; and

 said controlling means accesses said storage circuit through said second interface, and performs a process while communicating with said processing
30 apparatus through said first interface using a program or data stored in said storage circuit.

31. A communication apparatus as claimed in claim 29, wherein when said another communication apparatus

112

stores a program defining a process relating to said service and executes the same,

5 said controlling means conducts mutual authentication said another communication apparatus through said second interface and said communication circuit, and then controls communication of said another communication apparatus and said processing apparatus performed through said communication circuit so that
10 said first interface and said second interface relays the same.

32. A communication apparatus as claimed in claim 29, wherein:

15 said communication circuit comprises a controlling means for controlling a process of the communication circuit, and

20 said controlling means of said communication circuit and said controlling means of said integrated circuit communicate through said second interface to thereby collaborate and perform a process.

33. An integrated circuit transferring data with a communication circuit of a first communication apparatus, comprising:

25 an interface for communicating with said communication circuit; and

30 a controlling means for conducting mutual authentication with a second communication apparatus storing a program defining a process relating to a service through said interface and said communication circuit if an authentication request from said communication circuit is received through said interface; wherein

said program being stored in a storage area of the second communication apparatus allocated in advanced to said first communication apparatus; and

5 said service being provided by using a function of data carrier and/or authentication in said first communication apparatus and a reader/writer function for said integrated circuit.

10 34. An integrated circuit as claimed in claim 33, wherein a result of said mutual authentication is used for determining whether said second communication apparatus and a third communication apparatus for performing a process relating to a service using said integrated circuit should communicate to perform a
15 process relating to said service or not.

 35. A integrated circuit as claimed in claim 34, further comprising a storage circuit for storing a program relating to a service provided using said integrated circuit, wherein

20 said controlling means judges if said program corresponding to a request received from said communication circuit through said interface is stored in said storage circuit or not, and when judged that said program is stored in said storage circuit,

25 executes said program read from said storage circuit and while communicating with said third communication apparatus through said interface and said communication circuit in response to the execution of the program, performs a process relating to said
30 service.

 36. An integrated circuit as claimed in claim 35, wherein when said controlling means judges that said program is not stored in said storage circuit, transmits a use request of said program to said second

114

communication apparatus through said interface and said communication circuit.

5 37. An integrate circuit as claimed in claim 34, wherein:

 said first communication apparatus is a portable type communication apparatus;

10 said communication circuit is a wireless communication circuit performing communication using a wireless communication network;

 said second communication apparatus and said third communication apparatus are connected to a network; and

15 said controlling means communicates with said second communication apparatus through said interface, said communication circuit, said wireless communication network, and said network.

20 38. An integrated circuit as claimed in claim 33, wherein said integrated circuit is a tamper-resistant circuit.

 39. A communication apparatus comprising a communication circuit and an integrated circuit, wherein said integrated circuit comprises:

25 an interface for transferring data said communication circuit;

30 a controlling means for conducting mutual authentication with another communication apparatus storing a program defining a process relating to a service through said interface and said communication circuit if an authentication request from said communication circuit is received through said interface; wherein

said program being stored in a storage area of the another communication apparatus allocated in advanced to said communication apparatus; and

said service being provided by using a function of data carrier and/or authentication in said communication apparatus and a reader/writer function for said another communication apparatus.

40. A communication apparatus as claimed in claim 39, wherein a result of said mutual authentication is used for determining whether a first communication apparatus serving as said another communication apparatus and a second communication apparatus for performing a process relating to a service using said integrated circuit should communicate to perform a process relating to said service or not.

41. A communication apparatus as claimed in claim 40, wherein:

said communication circuit comprises a storage circuit for storing a program or data, and

said controlling means accesses said storage circuit through said interface, and performs a process while communicating with said second communication apparatus through said interface and said communication circuit using a program or data stored in said storage circuit.

ABSTRACT

An application program relating to a process of an IC 21 is stored in a virtual IC storage area server apparatus 13. Following a mutual authentication between the IC 21 and the virtual IC storage area server apparatus 13 through a portable communication function unit 20, the server apparatus 13 executes the application program and through the IC 21, the portable communication function unit 20, a wireless communication line 17, and a network 18, communicates with an IC_R/W apparatus 11 and performs a process relating to a service in collaboration with each other.