

Description

The invention relates to a cable clamp and particularly to a cable clamp which is suitable for incorporation with an electrical connector housing.

Cable clamps are required for many cable terminations with electrical connectors to ensure that stress imposed on the cable is not transmitted to the termination and does not result in deterioration of the electrical connection.

A very wide variety of cable clamps is available, but nevertheless a need exists for a cable clamp which can resist high tensile stress and can easily be assembled by hand with the cable in the field.

A known cable clamp described in GB Patent Specification 1551298 comprises first and second clamping members having first and second clamping walls respectively, locatable in laterally spaced, parallel relation in a cable receiving condition in which free ends of the walls engage respective axially spaced opposite sides of a cable located between them, cable engaging surface portions of the walls being progressively movable into overlapping relation to deform transversely and trap between them a portion of the cable in a clamping condition and means to secure the clamping members in the clamping condition.

In practice, there will be a tendency for the walls to be urged relatively apart by the cable during deformation reducing the area in contact with the cable and, consequently, the frictional retention force. Although means are provided in the prior cable clamp to retain constant the relative spacing of the walls during deformation of the cable, to achieve a high retention force it may be necessary to locate the walls closely together during initial engagement with the cable which may result in an undesirably high force being required to deform the cable, this being particularly significant with a multiconductor cable. Axial withdrawal of the cable from the termination may also result from the high frictional forces during movement of the walls into overlapping relation resulting in connection strain and electrical failure.

In a cable clamp according to the invention, means are provided on the clamping members to urge the walls progressively together during such movement into gripping engagement with the trapped cable portion into the clamping condition.

The walls may be relatively free to move apart or widely spaced during initial deformation of the cable avoiding excessive frictional drag on the cable and excessive closure forces.

Preferably, cam means are provided on the clamping members to urge the walls relatively together during final stages of movement to the clamping condition.

An effective clamping action is obtained simply, the wall surfaces providing a large area of contact with the cable in the clamping condition to enhance the frictional retention force.

Desirably, the cable engaging surface portion is formed with cable gripping barbs further to enhance the cable retention force. Preferably, the barbs have cable engaging edges facing the free end of the first wall enhancing the retention force in one direction, in practice usually to resist the cable being pulled away from the termination during movement of the cable clamp to the closed condition.

In a preferred embodiment, the cable engaging surface portions terminate at the free ends of the first and second walls in an angular cable gripping edge and a curved sliding surface, respectively.

This facilitates bending of the cable to a desired configuration during closure of the clamp, the angular edge tending to crease and retain the cable while the curved surface permits a portion of the cable to be drawn readily into the clamp from a direction remote from the termination. A cable locating lug may also be provided to prevent the cable diverging from a right angle formed by engagement with the edge during closure together of the clamping members.

Desirably, the first clamping member includes a third clamping wall located laterally spaced from and generally parallel to the first wall, the first and third walls upstanding from a common base and the third wall being of less height than the first wall, the second wall being received between the first and third walls in the clamping condition.

Thus, an interdigitating construction is achieved, the reduced height of the third wall providing sufficient clearance for the cable during movement to the clamping condition to enable unimpeded movement of the first and second walls together by the cam means into gripping engagement with the cable.

It is also desirable that interengagable guide means are provided on the first and second clamping members to guide the clamping members together during movement from the cable receiving condition to the cable clamping condition with the second wall nearer to the first wall than to the third wall.

The differential spacing of the walls also ensures sufficient clearance to enable cable to be drawn relatively freely across the third wall during movement of the clamp to a closed condition.

Preferably, the free end of the first wall is formed with an elongate, cable locating recess.

The recess provides additional clearance from the locating lug to enable relatively narrow and thick cables to be accommodated in the recess. Relatively thin and wide cables overlap the longitudinal edge portions of the recess.

The second clamping member may include a fourth wall extending in the same direction as the first wall and having a free end arranged to engage a cable adjacent a free end of the third wall remote from the second wall.

Conveniently, the cam surface is formed by a pair of laterally spaced ears extending from the

second wall towards the third wall and defining between them a cable receiving space, the abutment being constituted by a free end of the third wall.

In a particular embodiment, the first and second clamping members are integrally joined respectively to cable receiving ends of base member and cover member of an electrical connector housing, means being provided on the base member to secure an electrical terminal assembly to the base member adjacent a side of the first wall remote from the third wall.

A particular example of an electrical connector incorporating a cable clamp according to the invention will now be described with reference to the accompanying drawings in which :

Figure 1 is a perspective view of the connector terminating a ribbon cable ;

Figure 2 is an exploded perspective view of the connector ;

Figure 3 is a cross-sectional view of the connector in a wire-receiving condition ;

Figure 4A-C are cross-sectional views of the connector during progressive movement from the wire-receiving condition towards the wire clamping condition ;

Figure 5 is a cross-sectional view of the connector in the fully closed, wire clamping condition ; and

Figure 6 is a fragmentary perspective view of cable clamping members of the connector.

The electrical connector comprises a housing including a base member 11 and a cover member 12 each moulded in one piece of plastics material and containing an electrical terminal assembly including a printed circuit board 13 from which upstand slotted barrel, wire receiving terminals 14 similar to those described in U.S. Patent No. 3,860,318 receiving wire stuffing caps 15 similar to those described in U.S. Patent No. 4,186,948.

A telephone jack 16 similar to that described in U.S. Patent No. 4,231,628 is mounted on the printed circuit board adjacent a contact face of the housing with individual contacts electrically connected by the printed circuit board to individual wires 18 of a flat cable 19 terminated by the terminals 14.

The base member 11 and cover member 12 incorporate at wire receiving ends first and second clamping members 21 and 22, respectively. The first clamping member includes first and third clamping walls 24 and 25, respectively, upstanding in spaced apart parallel relation from a base wall 26. Two series of supporting brackets 27, 27' are respectively provided along front and rear faces of respective walls and two supporting brackets 28 are provided on the front of the third clamping wall to each side of a cable engaging end 33. A cable engaging portion of the first wall is formed with cable gripping means comprising a plurality of barbs 29 having cable engaging edges 29' facing a free end 30 of the wall. Apertures 31 in the base wall enable the moulding of the barbs 29. The cable engaging surface of the first wall terminates in a cable gripping edge 33 at

a cable engaging end 30 which is formed with an elongate cable locating recess 32.

The second clamping member 22 includes second and fourth clamping walls 35 and 36 depending from a top wall 37 of the cover member. The second wall 35 depends perpendicularly from the top wall located in laterally spaced, parallel relation to the first wall 24 in the operative condition of the clamping members and terminates, at a free cable engaging end 39, in a curved sliding, cable engaging, surface 38.

Cam members comprising laterally spaced ears 41 extend between the second and fourth walls and are provided with camming surfaces 42 towards a wire receiving end. Spaced supporting brackets 43 also extend between the second and fourth walls adjacent a cable receiving rebate 44 in the fourth wall.

A pair of spaced apart cable locating lugs 45 extend between the top and second walls of the cover. A side wall 47 of the cover is formed at a contact end of the connector with an opening 46 and at free ends with a peripheral skirt 48 joining the fourth wall 36 at the contact end of the connector. Latching detents 49 and eyes 50 are provided on the interiors of the opposite sides of the skirt and at the junction of the fourth wall and the skirt on each side of the cable receiving opening 44. A release tool receiving cut out 57 is formed on the free end of the skirt on each side of the connector.

The base member is formed with a side wall 53 upstanding and inset from the periphery of the base wall 26 to provide peripheral cover locating seat 54. A portion 53' of the side wall projects to the contact face of the base member. Latching recesses 55 and catches 56 are provided on opposite external sides of the side wall 53 and on the third wall 25 which is coextensive with the side wall 53.

Supporting ribs 58 extend in spaced parallel relation across the base wall 26 and a pair of locating bosses 59 upstand in spaced apart relation from the base wall adjacent the contact face. Terminal assembly retaining catches 60 extend inwardly from opposite free ends of the side wall 53 adjacent the first wall 24 for cooperation with a pair of resilient latches 61 which upstand from the base wall in spaced apart relation.

The printed circuit board 13 is formed with boss-receiving apertures 63 and the telephone jack is formed on opposite sides with a vertically extending, cover locating, ribs 64.

In operation, the terminal assembly is mounted in the base member by one end of the printed circuit board being received under the two catches 60 and the other end being subsequently received as a snap fit by the latches 61, the apertures 63 registering with the bosses 59. The individual wires 18 may be stuffed into the terminals 15 using the technique described in U.S. Patent No. 4,186,948 prior or subsequent to mounting the terminal assembly in the base member.

The cover member is then aligned with the base

member with the cable dressed over the first and third clamping walls on the base member as shown in Figure 3. Pressing the cover on to the base causes the free end of the second, clamping wall 35 to deform a discrete portion of the cable to extend transversely of the cable axis and draw more cable from the exterior of the connector as shown in Figure 4A. The cable is held by the relatively sharp edge 33 of the first wall and slides across the surface 38 of the second wall during such movement. Any tendency for the cable to pivot away from the edge 33 will be prevented by engagement ultimately with the cable locating lugs 45. Engagement between the skirt 48 on the cover member and the upstanding base wall 53 and the skirt and the ribs 64 will assist in guiding the first and second clamping walls together into parallel relation interdigitating with the third and fourth walls.

It should be noted that, as indicated in Figure 4B, the second wall will tend to be moved by the cable away from the first wall during initial closure together of the clamping members avoiding excessive frictional drag on the cable and excessive closure forces until cam surface 42 engages the free end of the third wall progressively urging the second wall back towards the first wall until the transversely deformed portion of the cable is gripped by the first and second walls as shown in Figure 4C. The barbs 29 assist in restraining the cable from being withdrawn away from the terminals during the latter stages of movement to the closed condition. Latching detents 49 and eyes 50 on the cover member and the recesses 55 and catches 56 on the base member snap into engagement in the fully closed condition shown in Figure 5.

Repeated release and effective clamping of the cable may be easily achieved enabling the individual wiring pattern to be altered in the field.

The cable clamp can, within limits, accommodate a range of cable sizes to avoid a need to manufacture, store and transport a range of parts. The cable clamp also requires only two components each of which can be manufactured economically using mass production techniques.

Claims

1. A cable clamp comprising first and second clamping members (21, 22) having first and second clamping walls (24, 35) respectively, locatable in laterally spaced, parallel relation in a cable receiving condition in which free ends of the walls engage respective, axially spaced opposite sides of a cable located between them, cable engaging surface portions (33, 38) of the walls being progressively movable into overlapping relation to deform transversely and trap between them a portion of the cable and means (49, 55) being provided to secure the clamping members in a clamping condition, characterized in that, means (42, 25) are provided on the clamping members (21, 22) to urge the walls (24, 35)

progressively together during such movement into gripping engagement with the trapped cable portion (19), into the clamping condition.

2. A cable clamp according to claim 1 characterized in that, the means (42, 25) to urge the walls (24, 35) relatively together comprise a cam surface (42) on one clamping member (22) engageable with an abutment (25) on the other clamping member (21) during such movement.

3. A cable clamp according to claim 2 characterized in that, the cable engaging surface portion of the first wall (24) is formed with cable gripping means (29).

4. A cable clamp according to claim 3 characterized in that, the cable gripping means (29) comprise a plurality of barbs (29) having cable engaging edges (29') facing the free end (30) of the first wall (24).

5. A cable clamp according to claim 3 characterized in that, the cable engaging surface portions terminate at the free ends (30, 39) of the first and second walls (24, 35) in an angular cable gripping edge (33) and a curved sliding surface (38), respectively.

6. A cable clamp according to any one of claims 1 to 5 characterized in that, the first clamping member (21) includes a third clamping wall (25) located laterally spaced from and generally parallel to the first wall (24), the first and third walls (24, 25) upstanding from a common base (26) and the third wall (25) being of less height than the first wall (24), the second wall (35) being received between the first and third walls (24, 25) in the clamping condition.

7. A cable clamp according to claim 6 characterized in that, interengagable guide means (48, 53, 64) are provided on the first and second clamping members (21, 22) to guide the clamping members (21, 22) together during movement from the cable receiving condition to the cable clamping condition with the second wall (35) nearer the first wall (24) than the third wall (25).

8. A cable clamp according to claim 6 or claim 7 characterized in that, the second clamping member (22) is provided with a cable locating lug (45) aligned with and spaced apart from the free end (30) of the first wall (24) to define a cable confining space which decreases in size as the first and second walls (24, 35) are moved into overlapping relation.

9. A cable clamp according to any one of claims 6-8 characterized in that, the free end (30) of the first wall (24) is formed with an elongate cable locating recess (32).

10. A cable clamp according to any one of claims 6-9 characterized in that, the second clamping member (22) includes a fourth wall (36) extending in the same direction as the first wall (24) and having a free end (44) arranged to engage a cable (19) adjacent a free end of the third wall (25) remote from the second wall (35).

11. A cable clamp according to claim 10 characterized in that, the fourth wall (36) diverges from the second wall (35) as it extends from a root end to the free end.

member with the cable dressed over the first and third clamping walls on the base member as shown in Figure 3. Pressing the cover on to the base causes the free end of the second, clamping wall 35 to deform a discrete portion of the cable to extend transversely of the cable axis and draw more cable from the exterior of the connector as shown in Figure 4A. The cable is held by the relatively sharp edge 33 of the first wall and slides across the surface 38 of the second wall during such movement. Any tendency for the cable to pivot away from the edge 33 will be prevented by engagement ultimately with the cable locating lugs 45. Engagement between the skirt 48 on the cover member and the upstanding base wall 53 and the skirt and the ribs 64 will assist in guiding the first and second clamping walls together into parallel relation interdigitating with the third and fourth walls.

It should be noted that, as indicated in Figure 4B, the second wall will tend to be moved by the cable away from the first wall during initial closure together of the clamping members avoiding excessive frictional drag on the cable and excessive closure forces until cam surface 42 engages the free end of the third wall progressively urging the second wall back towards the first wall until the transversely deformed portion of the cable is gripped by the first and second walls as shown in Figure 4C. The barbs 29 assist in restraining the cable from being withdrawn away from the terminals during the latter stages of movement to the closed condition. Latching detents 49 and eyes 50 on the cover member and the recesses 55 and catches 56 on the base member snap into engagement in the fully closed condition shown in Figure 5.

Repeated release and effective clamping of the cable may be easily achieved enabling the individual wiring pattern to be altered in the field.

The cable clamp can, within limits, accommodate a range of cable sizes to avoid a need to manufacture, store and transport a range of parts. The cable clamp also requires only two components each of which can be manufactured economically using mass production techniques.

Claims

1. A cable clamp comprising first and second clamping members (21, 22) having first and second clamping walls (24, 35) respectively, locatable in laterally spaced, parallel relation in a cable receiving condition in which free ends of the walls engage respective, axially spaced opposite sides of a cable located between them, cable engaging surface portions (33, 38) of the walls being progressively movable into overlapping relation to deform transversely and trap between them a portion of the cable and means (49, 55) being provided to secure the clamping members in a clamping condition, characterized in that, means (42, 25) are provided on the clamping members (21, 22) to urge the walls (24, 35)

progressively together during such movement into gripping engagement with the trapped cable portion (19), into the clamping condition.

2. A cable clamp according to claim 1 characterized in that, the means (42, 25) to urge the walls (24, 35) relatively together comprise a cam surface (42) on one clamping member (22) engageable with an abutment (25) on the other clamping member (21) during such movement.

3. A cable clamp according to claim 2 characterized in that, the cable engaging surface portion of the first wall (24) is formed with cable gripping means (29).

4. A cable clamp according to claim 3 characterized in that, the cable gripping means (29) comprise a plurality of barbs (29) having cable engaging edges (29') facing the free end (30) of the first wall (24).

5. A cable clamp according to claim 3 characterized in that, the cable engaging surface portions terminate at the free ends (30, 39) of the first and second walls (24, 35) in an angular cable gripping edge (33) and a curved sliding surface (38), respectively.

6. A cable clamp according to any one of claims 1 to 5 characterized in that, the first clamping member (21) includes a third clamping wall (25) located laterally spaced from and generally parallel to the first wall (24), the first and third walls (24, 25) upstanding from a common base (26) and the third wall (25) being of less height than the first wall (24), the second wall (35) being received between the first and third walls (24, 25) in the clamping condition.

7. A cable clamp according to claim 6 characterized in that, interengagable guide means (48, 53, 64) are provided on the first and second clamping members (21, 22) to guide the clamping members (21, 22) together during movement from the cable receiving condition to the cable clamping condition with the second wall (35) nearer the first wall (24) than the third wall (25).

8. A cable clamp according to claim 6 or claim 7 characterized in that, the second clamping member (22) is provided with a cable locating lug (45) aligned with and spaced apart from the free end (30) of the first wall (24) to define a cable confining space which decreases in size as the first and second walls (24, 35) are moved into overlapping relation.

9. A cable clamp according to any one of claims 6-8 characterized in that, the free end (30) of the first wall (24) is formed with an elongate cable locating recess (32).

10. A cable clamp according to any one of claims 6-9 characterized in that, the second clamping member (22) includes a fourth wall (36) extending in the same direction as the first wall (24) and having a free end (44) arranged to engage a cable (19) adjacent a free end of the third wall (25) remote from the second wall (35).

11. A cable clamp according to claim 10 characterized in that, the fourth wall (36) diverges from the second wall (35) as it extends from a root end to the free end.



12. A cable clamp according to any one of claims 6-11 when dependent on claim 2, characterized in that, the cam surface (42) is formed by a pair of laterally spaced ears (41) extending from the second wall (35) towards the third wall (25) and defining between them a cable receiving space, the abutment (25) being constituted by a free end of the third wall (25).

13. A cable clamp according to any one of claims 6-12 characterized in that, the first and second clamping members (21, 22) are integrally joined, respectively, to cable receiving ends of a base member and a cover member (11, 12) of an electrical connector housing, means (60, 61) being provided on the base member (11) to secure an electrical terminal assembly (13, 14) to the base member (11) adjacent a side of the first wall (24) remote from the third wall (25).

Patentansprüche

1. Kabelklemme mit einem ersten und einem zweiten Klemmglied (21, 22), die eine erste bzw. eine zweite Klemmwand (24, 35) aufweisen, die dazu ausgelegt sind, in seitlicher Beabstandung voneinander sowie parallel zueinander in einem Kabelaufnahmestand angeordnet zu werden, in dem freie Enden der Wände an entsprechenden axial beabstandeten, einander gegenüberliegenden Seiten eines dazwischen liegenden Kabels angreifen, wobei kabelangriffsflächenbereiche (33, 38) der Wände fortschreitend in eine Überlappung bewegbar sind, um einen Bereich des Kabels in Querrichtung zu verformen sowie zwischen sich einzuschließen, und wobei Einrichtungen (49, 55) zum Befestigen der Klemmglieder in einem Klemmzustand vorgesehen sind, dadurch gekennzeichnet, daß an den Klemmgliedern (21, 22) Einrichtungen (42, 25) vorgesehen sind, um die Wände (24, 35) während einer derartigen Bewegung fortschreitend aufeinander zu in greifenden Eingriff mit dem eingeschlossenen Kabelbereich (19) sowie in den Klemmzustand zu drücken.

2. Kabelklemme nach Anspruch 1, dadurch gekennzeichnet, daß die Einrichtungen (42, 25) zum Drücken der Wände (24, 25) relativ aufeinander zu eine Steuerfläche (42) an dem einen Klemmglied (22) aufweisen, die während einer derartigen Bewegung mit einem Widerlager (25) an dem anderen Klemmglied (21) in Eingriff bringbar ist.

3. Kabelklemme nach Anspruch 2, dadurch gekennzeichnet, daß der Kabelangriffsflächenbereich der ersten Wand (24) mit Kabelgreifeinrichtungen (29) ausgebildet ist.

4. Kabelklemme nach Anspruch 3, dadurch gekennzeichnet, daß die Kabelgreifeinrichtungen (29) eine Mehrzahl von Widerhaken (29) aufweisen, die dem freien Ende (30) der ersten Wand (24) zugewendete Kabelangriffskanten (29') besitzen.

5. Kabelklemme nach Anspruch 3, dadurch gekennzeichnet, daß die Kabelangriffsflächenbe-

reiche an den freien Enden (30, 39) der ersten und der zweiten Wand (24, 35) in einer winkelig ausgebildeten Kabelgreifkante (33) bzw. in einer gerundeten Gleitfläche (38) enden.

6. Kabelklemme nach einem der Ansprüche 1 bis 5, dadurch gekennzeichnet, daß das erste Klemmglied (21) eine dritte Klemmwand (25) aufweist, die von der ersten Wand (24) seitlich beabstandet und im allgemeinen parallel zu dieser ist, daß die erste und die dritte Wand (24, 25) von einer gemeinsamen Basis (26) wegstehen, daß die dritte Wand (25) eine geringere Höhe aufweist als die erste Wand (24), und daß die zweite Wand (35) im Klemmzustand zwischen der ersten und der dritten Wand (24, 25) aufgenommen ist.

7. Kabelklemme nach Anspruch 6, dadurch gekennzeichnet, daß miteinander in Eingriff bringbare Führungseinrichtungen (48, 53, 64) an dem ersten und dem zweiten Klemmglied (21, 22) vorgesehen sind, um die Klemmglieder (21, 22) während der Bewegung von dem Kabelaufnahmestand in den Kabelklemmzustand zusammenzuführen, wobei die zweite Wand (35) der ersten Wand (24) näher ist als die dritte Wand (25).

8. Kabelklemme nach Anspruch 6 oder 7, dadurch gekennzeichnet, daß das zweite Klemmglied (22) mit einer Kabelfestlegezunge (45) ausgestattet ist, die mit dem freien Ende (30) der ersten Wand (24) ausgerichtet sowie von dieser beabstandet ist, um einen Kabelbegrenzungsraum zu definieren, dessen Größe bei Bewegung der ersten und der zweiten Wand (24, 35) in die überlappende Beziehung geringer wird.

9. Kabelklemme nach einem der Ansprüche 6 bis 8, dadurch gekennzeichnet, daß das freie Ende (30) der ersten Wand (24) mit einer länglichen Kabelfestlegeausnehmung (32) ausgebildet ist.

10. Kabelklemme nach einem der Ansprüche 6 bis 9, dadurch gekennzeichnet, daß das zweite Klemmglied (22) eine vierte Wand (36) aufweist, die sich in dieselbe Richtung wie die erste Wand (24) erstreckt und ein freies Ende (44) besitzt, das dazu ausgelegt ist, an einem von der zweiten Wand (35) abgelegenen freien Ende der dritten Wand (25) an einem Kabel (19) anzugreifen.

11. Kabelklemme nach Anspruch 10, dadurch gekennzeichnet, daß die vierte Wand (36) in ihrer Erstreckung von einem Fußende zu dem freien Ende von der zweiten Wand (35) weg divergiert.

12. Kabelklemme nach einem der Ansprüche 6 bis 11 bei deren Abhängigkeit von Anspruch 2, dadurch gekennzeichnet, daß die Steuerfläche (42) durch zwei seitlich voneinander beabstandete Ansätze (41) gebildet ist, die sich von der zweiten Wand (35) in Richtung auf die dritte Wand (25) erstrecken und zwischen sich einen Kabelaufnahmeraum definieren, wobei das Widerlager (25) durch ein freies Ende der dritten Wand (25) gebildet ist.

13. Kabelklemme nach einem der Ansprüche 6 bis 12, dadurch gekennzeichnet, daß das erste und das zweite Klemmglied (21, 22) jeweils mit



Kabelaufnahmeenden eines Basisglieds und eines Abdeckglieds (11, 12) eines elektrischen Verbindergehäuses einstückig verbunden sind, und daß an dem Basisglied (11) Einrichtungen (60, 61) vorgesehen sind, um eine elektrische Anschlußanordnung (13, 14) in der Nähe einer von der dritten Wand (25) abgelegenen Seite der ersten Wand (24) an dem Basisglied (11) zu befestigen.

Revendications

1. Serre-câble comprenant des premier et second éléments de serrage (21, 22) comportant des première et seconde parois de serrage (24, 35), respectivement, pouvant être espacées latéralement l'une de l'autre et disposées parallèlement l'une à l'autre dans un état de réception de câble, dans lequel des extrémités libres des parois portent contre des côtés opposés respectifs, espacés axialement, d'un câble placé entre elles, des parties de surface (33, 38) de prise de câble des parois pouvant être amenées progressivement dans une disposition de recouvrement pour déformer transversalement et retenir entre elles une partie du câble et des moyens (49, 55) étant prévus pour fixer les éléments de serrage dans un état de serrage, caractérisé en ce que des moyens (42, 25) sont prévus sur les éléments de serrage (21, 22) pour rapprocher progressivement les parois (24, 35) l'une de l'autre, au cours de ce mouvement, jusqu'à une prise d'accrochage avec le tronçon de câble retenu (19), dans l'état de serrage.

2. Serre-câble selon la revendication 1, caractérisé en ce que les moyens (42, 25) destinés à rapprocher les parois (24, 35) l'une de l'autre comprennent une surface de came (42) située sur un premier élément de serrage (22) et pouvant entrer en contact avec une butée (25) située sur l'autre élément de serrage (21) au cours de ce mouvement.

3. Serre-câble selon la revendication 2, caractérisé en ce que la partie de surface de prise du câble de la première paroi (24) comporte des moyens (29) d'accrochage du câble.

4. Serre-câble selon la revendication 3, caractérisé en ce que les moyens (29) d'accrochage du câble comprennent plusieurs nervures (29) présentant des arêtes (29') de prise du câble tournées vers l'extrémité libre (30) de la première paroi (24).

5. Serre-câble selon la revendication 3, caractérisé en ce que les parties de surface de prise du câble se terminent, aux extrémités libres (30, 39) des première et deuxième parois (24, 35), par une arête angulaire (33) d'accrochage du câble et une surface incurvée (38) de glissement, respectivement.

6. Serre-câble selon l'une quelconque des revendications 1 à 5, caractérisé en ce que le premier élément de serrage (21) comprend une troisième paroi de serrage (25) espacée latéralement de, et à peu près parallèle à la première

paroi (24), les première et troisième parois (24, 25) s'élevant d'une base commune (26) et la troisième paroi (25) étant moins haute que la première paroi (24), la deuxième paroi (35) étant reçue entre les première et troisième parois (24, 25) dans l'état de serrage.

7. Serre-câble selon la revendication 6, caractérisé en ce que des moyens de guidage (48, 53, 64) pouvant être enclenchés mutuellement sont prévus sur les premier et second éléments de serrage (21, 22) afin de guider l'un vers l'autre les éléments de serrage (21, 22) pendant le mouvement de l'état de réception de câble à l'état de serrage de câble, la deuxième paroi (35) étant plus proche de la première paroi (24) que de la troisième paroi (25).

8. Serre-câble selon la revendication 6 ou la revendication 7, caractérisé en ce que le second élément de serrage (22) comporte une patte (45) de positionnement de câble alignée avec et espacée de l'extrémité libre (30) de la première paroi (24) afin de définir un espace de maintien du câble dont la dimension diminue au fur et à mesure que les première et deuxième parois (24, 35) sont amenées en position de recouvrement.

9. Serre-câble selon l'une quelconque des revendications 6-8, caractérisé en ce que l'extrémité libre (30) de la première paroi (24) présente un évidement allongé (32) de positionnement de câble.

10. Serre-câble selon l'une quelconque des revendications 6-9, caractérisé en ce que le second élément de serrage (22) comprend une quatrième paroi (36) s'étendant dans la même direction que la première paroi (24) et ayant une extrémité libre (44) agencée de façon à porter contre un câble (19) à proximité immédiate d'une extrémité libre de la troisième paroi (25) éloignée de la deuxième paroi (35).

11. Serre-câble selon la revendication 10, caractérisé en ce que la quatrième paroi (36) diverge de la deuxième paroi (35) en s'étendant d'une extrémité de pied vers l'extrémité libre.

12. Serre-câble selon l'une quelconque des revendications 6-11 en dépendance de la revendication 2, caractérisé en ce que la surface de came (42) est formée par deux languettes (41) espacées latéralement, s'étendant de la deuxième paroi (35) vers la troisième paroi (25) et définissant entre elles un espace de réception de câble, la butée (25) étant constituée par une extrémité libre de la troisième paroi (25).

13. Serre-câble selon l'une quelconque des revendications 6-12, caractérisé en ce que les premier et second éléments de serrage (21, 22) sont reliés d'une seule pièce, respectivement, à des extrémités de réception de câble d'un élément de base et d'un élément de couvercle (11, 12) d'un boîtier de connecteur électrique, des moyens (60, 61) étant prévus sur l'élément de base (11) pour fixer un bornier électrique (13, 14) à l'élément de base (11) à proximité immédiate d'un côté de la première paroi (24) éloigné de la troisième paroi (25).

