

**METHOD FOR DEPOSITING MAIL IN AN ELECTRONIC SAFETY DEPOSIT
BOX SYSTEM; SAFETY DEPOSIT SYSTEM**

Description:

5

The invention relates to a method for depositing shipments by a deliverer into an electronic locker system having several lockable compartments.

10 The invention also relates to an electronic locker system for implementing the method for depositing shipments.

Electronic locker systems having several lockable compartments for depositing and picking up shipments are
15 generally known. These shipments can be, for example, catalog products, food or other shipments that are deposited by a deliverer into a compartment of the locker system for a specific recipient. In particular, locker systems are known for depositing and picking up shipments
20 such as parcels and packages.

French patent application FR 2 563 987, for example, describes a locker system that has at least one lockable compartment, input and display means as well as a
25 connection to a remote computer. The patent application discloses the basic principle of a method for the operation of lockable compartments in various embodiments.



159159



G00002

With such types of locker systems, a deliverer typically identifies himself/herself at the locker system and uses an input means to select a mode for depositing shipments. Then the deliverer opens a first compartment, whereby the
5 opening can also take place automatically, so that a door opens up. The deliverer places the first shipment into the compartment, whereby during this procedure, it is often the case that information in the form of Identcodes or other character strings associated with the shipments is
10 recorded. After the compartment has been filled, the deliverer closes it and confirms the filling procedure, as a result of which the compartment is logged as having been filled. Then the deliverer opens the next compartment and the procedure is repeated with all of the individual steps.

15 When large numbers of shipments are deposited in several compartments of a system, the entire filling procedure is very time-consuming due to the various process steps required for each compartment. In addition to the negative
20 time factor, this can also put a burden on the deliverer which, in turn, can lead to errors in the operation of the locker system. For example, parcels are placed incorrectly, parcels are forgotten or information is not correctly recorded. These drawbacks can occur not only with locker
25 systems operated by postal service providers but also with any other kind of locker systems that are filled by deliverers.

Therefore, the objective of the invention is to provide a
30 method for depositing shipments into an electronic locker system in which the time needed by the deliverer to fill several compartments is reduced in comparison to known methods.

It is also the objective of the invention to provide a locker system for implementing such a method.

According to the invention, this objective is achieved in
5 that, with a method for depositing shipments into an electronic locker system having several lockable compartments, control means of the locker system cause one or more compartments to open up for the depositing of shipments, and at least one new compartment opens
10 automatically as soon as a compartment is closed and recording means of the locker system have previously recorded information, whereby the information is associated with the shipment.

15 The number of compartments that open at the beginning of the filling procedure can be stored in the control means. For example, just one empty compartment or else empty compartments of different sizes can open. A locker system typically has compartments of different dimensions in order
20 to receive shipments of various sizes. The selection of the compartments to be opened initially can likewise be stored in the control means.

In another possible embodiment of the invention, the
25 deliverer can select the number and sizes of the compartments to be opened, for example, at the beginning of the filling procedure.

The invention also provides that a new compartment opens up
30 automatically as soon as the deliverer closes a compartment and recording means have previously recorded information that is associated with the shipment. This information is, for example, one or more Identcodes or other character strings. The term recording means encompasses as any means

that is suitable for recording information such as, for example, scanners for reading in codes, keyboards for entering character strings or touchscreens.

- 5 If the deliverer closes a compartment before information associated with the shipment has been recorded, it has proven to be advantageous for the compartment to automatically open up again. In this manner, for instance, it can be prevented that a shipment - due to the closing
10 and simultaneous confirmation procedure - is logged as having been deposited even though no shipment was placed at all. On the other hand, if the deliverer closes a compartment after the information associated with the deposited shipment has been properly recorded, then the
15 closing of the compartment is construed as a confirmation and the compartment is logged as having been filled. The deliverer does not have to once again confirm the procedure via the input means and initiate the beginning of the next filling procedure, but rather this is done automatically
20 according to the invention.

An especially preferred embodiment of the invention is characterized in that the filling procedure is terminated when a termination function is selected.

25

- In an especially preferred embodiment of the invention, the deliverer can only terminate the entire filling procedure and close all of the opened compartments consecutively once he/she has previously selected an appropriate function via
30 the input means. Only in that case is the closing of a compartment not logged as a confirmation and filling of a compartment. This is not possible if he/she has previously recorded information associated with a shipment, since it

can be assumed that a shipment was deposited and this must not remain without a confirmation and logging.

Moreover, it is advantageous to configure the invention in
5 such a way that the amount of time that has lapsed since the compartment was closed and/or since the locker system was operated in any other way is recorded and that the filling procedure is terminated once a predefinable time interval has been exceeded.

10

The predefinable time interval can be freely selected and preferably amounts to between 15 seconds and two minutes, whereby values between 30 and 90 seconds are especially preferred.

15

An especially advantageous embodiment of the method calls for configuring the locker system in such a way that, after the time interval has lapsed, no more compartments can be opened and/or closed.

20

This measure prevents the possibility that fraudulent objects might be placed into the parcel compartment system. Moreover, this means that the automatic termination of the filling procedure can be achieved in an especially simple
25 and advantageous manner.

30

The invention also comprises an electronic locker system for implementing the method according to the invention for depositing shipments by a deliverer, having input means and display means for carrying out a dialog with the deliverer, whereby the input means is connected to control means and the locker system has several lockable compartments with locking mechanisms, whereby these locking mechanisms can be actuated by the control means on the basis of stored

instructions and information that has been entered via the input means.

5 The stored instructions are, for example, the number and size of the compartments to be opened at the beginning of the filling procedure. The information entered via the input means can be numbers selected manually by the deliverer and/or it can be the selection of a filling mode.

10 The invention also relates to an electronic locker system for implementing a method for depositing shipments by a deliverer. The locker system has input means and display means for carrying out a dialog with the deliverer, whereby the input and display means are connected to the control
15 means. The system also has several lockable compartments with locking mechanisms, whereby these locking mechanisms can be actuated by the control means on the basis of stored instructions and information entered via the input means.

20 Additional advantages, special features and practical refinements of the invention can be gleaned from the subordinate claims and from the following description of preferred embodiments of the invention.

25 In an especially preferred embodiment of the invention, a deliverer identifies himself/herself at an electronic locker system, thereby logging into the control system of the locker system at the beginning of the filling procedure. The identification can take place through
30 various known identification methods. For example, entering a code or reading in a card are options.

Electronic locker systems typically comprise means for controlling the system in various modes. These control

means include, for example, computer means and mechanical and/or electronic circuits by means of which the locker system is operated. In particular, the control means actuate locking mechanisms of the compartment doors and
5 thus open and close compartments. Moreover, the control means are connected to input means and output means such as monitors, keyboards and/or touchscreens. The deliverer uses these input and display means to carry out a dialog with the locker system.

10

In order to deposit shipments, he/she selects, for instance, the mode "deliver parcels". Information can be stored in the control means about how many compartments should open up at the beginning of this selected mode. It
15 has been found to be advantageous, for example, for one compartment of each available size to open up for the deliverer. That way, he/she has a suitable compartment available for all possible shipment sizes. If the locker system has, for example, three different compartment sizes,
20 then one compartment of each size would open up.

However, it can also be advantageous for the deliverer to individually select the number of compartments and their size. If the deliverer knows, for instance, that he/she
25 only needs a specific compartment size for the following filling procedure, he/she can select this size. In this case, the deliverer would use the input means to indicate the desired compartments to the control means of the locker system, which would then process the information and open
30 the desired number of compartments in the appropriate sizes.

In both cases, one or more empty compartments open up so that shipments can be deposited.

The shipments to be deposited can be, for example, of various kinds with the appertaining process steps. In typical logistic systems, for example, in the realm of postal applications, parcels or packages are associated with identification means such as codes, so that the route of a particular shipment can be controlled and tracked as efficiently as possible. Conventionally, such a code has to be recorded by the recording means of a locker system when a shipment is deposited. For example, a postal number in the form of a scanned-in code or a character string entered via a keyboard is recorded.

Whereas the recording of a postal number that identifies the shipment is advantageously provided for each shipment, it is also possible to have shipments that are additionally provided with a special Identcode that likewise has to be scanned in before the shipment is deposited. Furthermore, these can be C.O.D. deliveries with C.O.D. amounts that have to be entered, or any other special shipment calling for additional steps.

At the end of each filling procedure, the deliverer closes the compartment, which is construed as confirmation of the procedure. In an especially preferred embodiment, the confirmation means that the compartment is logged as having been filled. Thus, no more manual confirmations from the deliverer are needed, which reduces the filling time needed per compartment. Moreover, according to the invention, after the closing of a compartment, a new compartment automatically opens up so that the opening of a new compartment does not have to be initiated by the deliverer through additional manual input. This translates into additional time savings.

In addition to reducing the time needed, the automatic confirmation and opening approach has the advantage that the steps to be carried out by the deliverer are simplified and reduced in number, thus making his/her job easier. This, in turn, enhances his/her concentration so that fewer errors occur during the filling procedure. In actual practice, it has been found that deliverers are so familiar with the work steps at a locker system that the appertaining input and display means often respond too slowly to keep up with the deliverer, who is ready for the next step. This can cause the deliverer to become impatient and lose concentration. Particularly when a locker system is to be filled with a large number of shipments, the constantly recurring procedures, which have to be initiated and confirmed individually, cause the work to be more stressful and time-consuming.

Consequently, the reduction according to the invention of the process steps and of the work steps speeds the filling procedure, alleviates the workload of the deliverer and reduces the potential for errors. In order to check the consecutive filling of already opened compartments and to avoid errors, advantageous refinements can be provided in embodiments of the invention.

For example, it is advantageous for the new compartment that is opened after the closing of a compartment to have the same dimensions as the one that was previously closed. Here, it is assumed that a locker system typically has different sizes of compartments so that shipments with different dimensions can be accommodated, whereby the available space is utilized as optimally as possible. Therefore, small shipments are preferably placed into small

compartments so as not to waste any space in larger compartments. If the control means are programmed in such a way that, at the beginning, they open a certain range of sizes, then it is advantageous, every time a compartment is closed, to offer the deliverer a compartment of the same size so that he/she always has the same range of sizes to choose from. If no compartment of that size is available, then the next-larger compartment could be opened. It can also be provided that the deliverer is informed via a display about this and can select the further course of action.

Since the closing of a compartment is construed as a confirmation of the filling procedure, there is a risk that a deliverer might inadvertently close a compartment even though, for example, he/she has not placed any shipment into it or necessary information has not been recorded. Therefore, it is advantageous that the closing of a compartment is only construed as a confirmation once all of the necessary information has previously been recorded. In an especially preferred embodiment of the invention, this includes a postal number that is scanned in or entered for each shipment. If this has not yet been done, it is advantageous for the compartment to open up again automatically so that it cannot be closed. In this manner, no existing parcel will be logged as having been "deposited" and no important information can be forgotten for deposited shipments.

In order to terminate the entire filling procedure and to be able to close all of the compartments that are still open, the deliverer has to transmit this information to the control means of the locker system since otherwise the compartments cannot be closed. For this purpose, he/she can

select an appropriate function, for example, "terminate filling". Now the compartments can be closed without the procedure being construed as confirmation of the placement of a shipment. However, this presupposes that no
5 information about the shipment has previously been recorded since this would mean that this is a confirmation of a filling procedure after all.

If an error has occurred nevertheless during the filling of
10 the compartments, another function, for example "cancel", can be provided, which allows the deliverer to open an incorrectly filled compartment and to correct the filling. The completed procedure is thus reversed and the compartment in question opens up automatically.

Claims:

1. A method for depositing shipments by a deliverer into
5 an electronic locker system having several lockable compartments,
characterized in that
control means of the locker system cause one or more compartments to open up for the depositing of
10 shipments, and at least one new compartment opens automatically as soon as a compartment is closed by the deliverer, and recording means of the locker system have previously recorded information, whereby the information is associated with the shipment.
- 15
2. The method according to Claim 1,
characterized in that
the filling procedure is terminated when a termination function is selected.
- 20
3. The method according to Claim 1,
characterized in that
the amount of time that has lapsed since the compartment was closed and/or since the locker system
25 was operated in any other way is recorded and in that the filling procedure is terminated once a predefinable time interval is exceeded.
- 30
4. The method according to one or more of the preceding claims,
characterized in that
the closing of a compartment by the control means of the locker system is construed as a confirmation of the

filling procedure of the compartment in question, so that the compartment is logged as having been filled.

- 5 5. The method according to one or more of the preceding claims,
characterized in that
the recorded information about the shipment consists of one or more codes that are scanned in.
- 10 6. The method according to one or more of the preceding claims,
characterized in that
the recorded information about the shipment consists of at least one character string that is entered by the
15 deliverer into input means of the locker system.
7. The method according to one or more of the preceding claims,
characterized in that
20 the new automatically opened compartment has the same dimensions as the one that was previously closed.
8. The method according to Claim 7,
characterized in that
25 a compartment of the next-smaller or next-larger size opens up if no empty compartment in the size of the previously closed compartment is available in the locker system.
- 30 9. The method according to Claim 7,
characterized in that
the deliverer selects the further course of action at the input means if no empty compartment in the size of

the previously closed compartment is available in the locker system.

10. The method according to one or more of the preceding
5 claims,

characterized in that

no compartment opens up if no more empty compartments of any size whatsoever are available in the locker system.

10

11. The method according to one or more of the preceding claims,

characterized in that

the deliverer terminates the filling procedure of
15 still-opened compartments by selecting an appropriate function at an input means of the locker system and by closing the compartments in question, whereby the control means of the locker system does not cause any more compartments to open.

20

12. The method according to one or more of the preceding claims,

characterized in that

the control means of the locker system only allows the
25 deliverer to close an opened compartment if information associated with the shipment has previously been recorded.

13. The method according to one or more of the preceding
30 claims,

characterized in that

the control means of the locker system causes a compartment to automatically open up once again if no

information associated with the shipment is or has been recorded.

14. The method according to one or more of the preceding
5 claims,
characterized in that
the deliverer cancels the filling of a compartment by
selecting a function at an input means of the locker
system, in response to which the compartment in
10 question opens up.
15. An electronic locker system for implementing the method
described by one or more of Claims 1 to 14 for
depositing shipments by a deliverer,
15 **characterized**
by the following features:
- input means and display means for carrying out a
dialog with the deliverer, whereby the input means
20 and display means are connected to control means and
 - several lockable compartments with locking
mechanisms, whereby these locking mechanisms can be
actuated by the control means on the basis of stored
25 instructions and information that has been entered
via the input means.