

Description

The invention is related to a method of navigating an automated guided vehicle.

In industry there is an increased use of automated guided vehicles in transporting goods and material between different stations in storing premises and workshops. Then, the trucks are controlled automatically along predetermined paths between the various stations. In a reliable method of the truck steering the truck control system detects a cable loop arranged within or on the floor, or a painted loop on the floor. Such a control system is very reliable and simple to use but the conditions in the premises where the trucks are being used, are not always such that it is suitable to use a control loop within or on the floor, and in addition to this the system suffers from the no little drawback that the truck movement is limited strictly to the paths defined by the control loop, and that these paths cannot easily be altered because they are permanent installations.

Accordingly, systems of navigating automated guided trucks have been developed wherein the truck movement is not restricted to a permanently arranged control loop, the truck being provided with apparatus continuously defining its current position in relation to fixed objects in the premises through which the truck is moving. The present invention is related to this type of navigation system and accordingly concerns a method of navigating a vehicle moving generally in one plane in which a calculation of the current position and direction of the vehicle is effected by measuring the angles in said plane from a reference point on the vehicle to fixed positions in relation to a reference direction on the vehicle.

In a prior art system for free navigation of automated guided vehicles a laser beam is used detecting reflectors fixedly arranged in the premises where the truck is moving. This system is called TURTLE and is described in the FMS Magazine, July 1983, pp 232-236. It is based on the fact that the truck for each position to be determined "sees" a number of fixedly arranged reflectors in the premises and that these reflectors can be identified, which is effected by the optical signal emitted from each of the reflectors, being coded. This is done by the laser beam emitted from the truck scanning over 360° and, when passing a reflector, generating a bar coded reflected signal.

Another prior art system described in Journal of Dynamic Systems, Measurement, and Control Vol. 105, September 1983, pp 152-155 is based on a type of position calculation similar to the TURTLE-system, but using instead of laser light ultra sound for locating and identifying the fixed positions in the space. From each fixed position a sound signal is then emitted having a predetermined frequency unique to the actual position. The latter system is similar to the system described in Robotics Age, Mar/Apr 1983, pp 31-33

and which is also subject matter of US patent 4 328 545. However, in that case beacons are provided in the fixed positions for emitting light individually coded such that a receiver on the truck can identify the beacon emitting the light signal.

DE-A-3 305 119 discloses a positioning system utilizing a rotating beam device. Angles between the vehicle, in this case a ship, and reflectors on the shore which are known and either provided with means for transmitting automatically the identity thereof or being possible to identify by the crew of the ship are used to determine the position of the ship.

US-A-4 533 918 discloses a device for improving radar supported navigation. Signals received from the radar equipment on board are compared with signals stored of known targets such as topological features, isolated buildings, buoys and the like.

As far as the inventor of the present invention knows, prior art systems for free navigation of automated guided trucks are based on the fact that the signals received by the truck to be used for calculation of the current position of the truck, are specific to the points from which they originate, and can be used to identify these points. This is a limitation of the prior art systems, and the object of the invention is to make possible the use of simple and inexpensive reflectors providing the signals from the fixed points in the space without the necessity of coding these signals for identifying purposes. At the same time it will be possible to determine the position even if some of the fixed points are temporarily hidden or there are reflections not associated with the system.

For this object the method according to the invention has been given the characteristics appearing from claim 1.

In order to explain the invention in more detail reference is made to the accompanying drawings, in which

FIG 1 is a plan view of premises through which an automated guided truck is to navigate by applying the method according to the invention,

FIG 2 is a side view of the truck,

FIG 3 is a horizontal sectional view of the truck in FIG 2 taken along line III-III,

FIG 4 is diagrammatic side view of the optical system for emitting a scanning laser beam,

FIG 5 is a geometrical figure for calculating the position and direction of the vehicle from the angles to three fixed reference points,

FIG 6 is a block diagram of an electronic system for working the method according to the invention

FIG 7 is a more detailed block diagram of the electronic system arranged on the truck

FIG 8 is a diagrammatic front view of a detector suitable for use in the system

FIG 9 is a diagrammatic plan view illustrating the scanning of a reflector by use of the detector in FIG 8, and

FIG 10 is a graph illustrating the signal obtained from the detector from the scanning according to FIG 9.

With reference to FIG 1 a possible path 10 is shown to be followed by an automated guided truck 11 by applying the method according to the invention. The path extends through a free space in the premises, limited by the walls of the premises and/or objects existing therein, such as machines, storage racks or the like, here generally indicated with 12. The free space through which the truck can move does not actually have to be limited by fixed objects or be enclosed by walls; the space for the truck movement may be limited to a certain area having a specific shape and extension in the horizontal plane for other reasons. When utilizing the method according to the invention a plurality of reflectors 13 shall be mounted in the motion space, the reflectors being of the most simple and inexpensive type and are suitably made of reflecting tape, for instance of the type marketed by 3M Svenska AB under trademark SCOTCH LITE. The tape may be attached directly to walls or objects or may be mounted on located vertically standing pins and having a diameter of about 20 mm. The tape should have some extension in the vertical direction. Behind the reflectors a dark background should be arranged to make the reflectors sharply outlined against the background.

On the truck an optical system 14 is arranged for emitting a laser beam scanning 360°. The truck is constructed in a special way for the mounting of the optical system, FIG 2 and FIG 3. Thus, it comprises a chassis 15 supporting on two uprights or columns 16 and two flanges or webs 17 the body 18 of the truck, leaving a gap 19 between the chassis and the body. In this gap the optical system 14 is mounted in such a way that the flanges or webs 17 extend radially to the vertical scan movement axis 20. In that way there is an almost unbroken area for the scanning laser beam around the axis 20 at a level close to the floor or ground. Though the beam per se is harmless, a lot of people are of the opinion that every laser beam, though being weak, is dangerous to the eyes. In the described arrangement the beam is far below eye-level, this placing of the optical system providing also the advantage that the body and the load carried thereon at no occasion screens the laser beam during the scanning movement thereof, which is not the least important for a secure and reliable navigation.

The body 18 of the truck may comprise suitable lifting means or other load handling means and space for electronic equipment, batteries etc.

The optical system may in principle be arranged as is diagrammatically shown in FIG 4. A laser generator 21 which may be a gas laser (He-Ne) for visible light or a semiconductor laser for IR-radiation, possibly pulsed, directs its beam towards a mirror 22 which in turn directs the beam through an opening 23

in a mirror 24 to a mirror 25. The latter mirror is supported on a rotatably mounted balance wheel 26 connected over a drive belt to a drive motor 27 to be rotated at a constant rotational speed of the order of 2 or 3 revolutions per sec. The balance wheel is connected to an angle meter 28 of very high accuracy, or to a device for measuring the period used by the balance wheel to rotate at a constant speed from a reference position to a given position, the angle position of which is to be indicated. Such time measurement can be performed at very high reliability and by utilizing a simpler and less expensive device than an angle sensor of high accuracy.

When the laser beam hits a reflector 13 it is reflected back to the mirror 25 transmitting the reflected beam onto the mirror 24 from where the reflected beam by suitable optics 29 is directed onto a detector 30 to be focused thereon.

In FIG 5 the truck is shown in a co-ordinate system, and in order to identify the position of the truck in a given moment the co-ordinates x and y for the axis 20 and the angle ϕ have to be determined. The angle ϕ is the angle between the x -axis and a vehicle reference line L , usually the longitudinal axis of the vehicle. This determination can be done by utilizing three fixed points, i. e. by using three reflectors, which the truck "sees" from the actual position. On the basis of the angles ϕ_1 , ϕ_2 and ϕ_3 between the sight lines from the reference point 20 of the truck to the three reflectors having the co-ordinates (x_1, y_1) , (x_2, y_2) and (x_3, y_3) , and the reference line L , the position and direction of the truck can be determined by applying conventional trigonometry as previously known per se and as described in the above mentioned publication Journal of Dynamic Systems, Measurement, and Control, September 1983, Vol. 105/153. Thus, by utilization of the optical system on the truck the angles ϕ_1 , ϕ_2 , ϕ_3 are measured and on the basis of these angles the equation is determined for those two circles which in FIG 5 have been drawn through the three points and the position of the truck for calculating the position and direction of the truck. Since this technique is previously known per se these trigonometrical calculations are not presented here. There is, however, a substantial difference between the system described here and those systems previously known and described in the references initially referred to: the three points needed for the calculations have not identified themselves by a coding. The truck can see more fixed points than three and, thus, it is necessary to identify these points in one way or the other.

The motion area with reflectors and path are stored in an electronic memory. The storing in the electronic memory can be done by using known technique. A method which can be applied is the utilization of a CAD system, for instance AutoCAD, which is a designing program by means of which any drawing can be reproduced in a microcomputer. By using this

program the plan of the truck movement area of FIG 1 can be programmed into a micro computer. To store the decided truck path the truck as an alternative to storing via the AutoCAD program can be driven along said path and its position in relation to the reflectors be continuously stored in the program. The positions of the reflectors are determined by utilization of conventional land surveying technique, and the measured positions are stored in the program. As an alternative the reflector positions can be located by driving the truck along a known path and be determined by utilizing the optical system and a program loaded in the computer system of the truck.

Then, when the truck shall automatically follow the defined path, a truck position and direction must first be defined so as to serve later as a base for identifying subsequent positions and directions. This can be done in different ways. According to one method the truck is placed in a predetermined position and in a predetermined direction initially defined. According to another method the position and direction are defined from three fixed points at the time, assuming that said points have certain identities, and this is repeated with reference to all fixed points visible from the truck in a given position. This results in a plurality of positions and directions for each three points, which form the basis for the calculation. The variance of the obtained result is calculated, and then the calculations are repeated with another assumption as to the identity of the points. When the assumption is found, which giving the least variance, the points are identified.

As the truck is moving, consecutive calculations of the truck position and direction are made in each individual position on the basis of the angle measurements made by the apparatus 14 to the reflectors visible from the truck in the actual position by guidance of the obstacles programmed. Thus every new positioning of the truck will be based on information previously obtained with regard to the truck position and moving direction.

It should be noted that in each truck position several determinations of the truck position and direction may be made depending on how many reflectors that are seen by the truck from the actual position. Since the reflectors are of a simple and inexpensive nature and do not have to transmit a coded reflected signal, the detectors can be set out generously whereby a high accuracy in the calculation of position and direction can be obtained.

To work the method according to the invention by using the above mentioned calculations a computer system constructed in principle according to FIG 6 is used. A controlling stationary computer 31 which can be common to many trucks, is provided for programming the motion area and the desired paths in this area, for instance by using the above mentioned AutoCAD program. The computer 31 is also connected to

a operator's console 32 with a keyboard to allow temporary manual operations in the program loaded. The computer 31 is connected through a communication system 34, FIG 6, for instance a wireless link (radio or IR) to a micro computer 35 on each truck.

The computer 31 operates as a coordinator of several trucks in a system and gives through the link the necessary information to the computer 35 on the truck. The computer 35 can be a micro computer of the type Motorola MC 68010, and it is connected to another micro computer 36 on the truck which also can be of the type Motorola MC 68010 receiving angle measurement signals from the optical system 14 and processing these signals so as to give to the computer 35 information on the momentary position and direction of the truck by applying the above mentioned method. Then in the computer 35 a comparison with the programmed data is made, and depending on the result of the comparison control signals are sent to the driving system 37 of the truck to provide the correction of the truck movement necessary to make the truck move along the predetermined path. Also connected to the computer 35 is an appropriate sensor system 38 to stop the truck movement when a risk of collision with persons or objects arises.

The accuracy in the control of the truck can be substantially improved by utilizing a detector of the type described in FIG 8. This detector is of a known design and comprises two silicon photodiodes indicated at 39A and 39B. Each of the diodes has a width of the order of 100 μm , and the diodes are separated by a gap 40 of the order of 10 μm . The scanning of the reflectors 13 in principle can be regarded as a projection of the detector, that is the two silicon diodes, on the surface of the reflector. This is illustrated in FIG 9. When the projected image of the detector is entering the reflector in the direction of the arrow 41, one silicon diode 39A will first be in the area of the reflector and then the other one. By adding the signals from the silicon diodes with reversed polarity the detector will provide a signal as illustrated in FIG 10 where the horizontal axis defines the scanning angle and the vertical axis defines the signal from the detector. When the image of the diode 39A only is projected on the reflector, the signal from the detector will rise to a largest positive value so as to decrease again to zero later when the second diode starts to enter the reflector, as the signal provided by the second diode is subtracted from the signal from the first diode. After that no signal from the detector will be obtained until the projection of said first diode moves from the surface of the reflector, the signal from said second diode being emitted from the detector. In other words, by this arrangement there is obtained a distinct signal easy to define, which means that the determination of the angle can be done at high accuracy with a corresponding high accuracy in the determination of the position and direction of the truck.

The determination of the position and direction by applying the above described method can be completed with odometry, which means that sensors on the wheels and steering mechanism of the truck provide signals representing the distance run and the direction of the existing movement, respectively, and that these signals then are used for calculating the change of the position and direction of the truck, to that it is possible to obtain, on the basis thereof by calculations executed in the computer 36, information on the actual position and direction of the truck. The quantities hereby obtained then may be processed together with those obtained by applying the method according to the invention.

By using quantities representing the speed of the truck and easily calculated by known methods, it is also possible to compensate for the truck movement between the measurements of the angles to the fixed points. In other words, the truck is not immobilized during the measurements, and even if there is a slight movement it does effect the calculations of the position.

Means can be provided for manually controlling the truck, for instance a control panel connected to the truck through a cable.

Some minor lateral deviation between the path followed by the truck on one occasion and the path followed in the same part of the path on another occasion can be programmed providing an advantage as the truck in that case does not wear wheel tracks in the support (the floor) during movement along an unchanged path for a long time.

Essential of the invention is the method in which the position and direction of movement of the truck is determined by utilizing a number of reflectors providing anonymous reflection signals. The practical embodiment of the mechanical and electronical means through which this method is realized has been illustrated and described in the embodiment preferred at present but can be modified or replaced by other means than the one described here without departing from the scope of the appended claims.

Claims

1. Method of navigating a vehicle moving along a predetermined in a plane in a motion space according to which a determination of the actual position and direction of the vehicle is provided by emitting from said vehicle a light beam scanning 360° horizontally, receiving on said vehicle the beam when reflected from fixed points in said motion space, and by measuring the angles in a plane parallel to said plane of movement between sight lines from a reference point on the vehicle to said fixed points and a reference direction on the vehicle, at least three angles being used for a trigonometric determination by cal-

5 culation means of position and direction and according to which vehicle movement is corrected, if the actual position is not at said path characterized in that as said fixed points a plurality of reflectors anonymous but determined as to the position thereof are utilized for the navigation, that the position for each of the points as well as existing sight obstacles between the reference point of the vehicle and the fixed points is stored in an electronic memory, that the movement of the vehicle in said plane is initiated in a known position and with a known direction so as to identify the fixed points visible from the reference point in said position, and that in each position and direction of the vehicle during the movement thereof information with regard to position and direction which is previously obtained is utilized to determine by guidance of the position of the obstacles stored the identity of the fixed points visible from said reference point in said position.

2. Method according to claim 1, characterized in that the storing of the position of the fixed points is effected by reproducing said plane with sight obstacles and the fixed points in said electronic memory.

3. Method according to claim 2, characterized in that the reproducing is effected in a computer aided design system for visual representation of said plane with sight obstacles and the fixed points, said predetermined path to be followed by the vehicle being included in the visual representation.

4. Method according to claim 1, characterized in that the determination of the position of the fixed points is effected by driving the vehicle along a known path while measuring the angles to the fixed points by utilizing the optical system and the program controlled computing and storing of the positions of the fixed points in the electronic memory.

5. Method according to claim 1, characterized in that the angles are determined by measuring the period for the movement of the light beam scanning horizontally at constant speed, from a reference point to a position where it hits a reflector.

6. Method according to claim 1, characterized in that the reflected light beam is detected by utilizing two photo detectors arranged side by side, the outputs of which are added with reversed polarity and which are hit, one after the other, by the reflected light beam.

7. Method according to claim 1, characterized in that the light beam is emitted close to the plane of vehicle movement.

8. Method according to claim 1, characterized in that the vehicle during movement thereof is brought to a position in relation to a desired path, which is displaced more or less towards one side or the other of the nominal path on successive tours along said path.

The determination of the position and direction by applying the above described method can be completed with odometry, which means that sensors on the wheels and steering mechanism of the truck provide signals representing the distance run and the direction of the existing movement, respectively, and that these signals then are used for calculating the change of the position and direction of the truck, to that it is possible to obtain, on the basis thereof by calculations executed in the computer 36, information on the actual position and direction of the truck. The quantities hereby obtained then may be processed together with those obtained by applying the method according to the invention.

By using quantities representing the speed of the truck and easily calculated by known methods, it is also possible to compensate for the truck movement between the measurements of the angles to the fixed points. In other words, the truck is not immobilized during the measurements, and even if there is a slight movement it does effect the calculations of the position.

Means can be provided for manually controlling the truck, for instance a control panel connected to the truck through a cable.

Some minor lateral deviation between the path followed by the truck on one occasion and the path followed in the same part of the path on another occasion can be programmed providing an advantage as the truck in that case does not wear wheel tracks in the support (the floor) during movement along an unchanged path for a long time.

Essential of the invention is the method in which the position and direction of movement of the truck is determined by utilizing a number of reflectors providing anonymous reflection signals. The practical embodiment of the mechanical and electrical means through which this method is realized has been illustrated and described in the embodiment preferred at present but can be modified or replaced by other means than the one described here without departing from the scope of the appended claims.

Claims

1. Method of navigating a vehicle moving along a predetermined in a plane in a motion space according to which a determination of the actual position and direction of the vehicle is provided by emitting from said vehicle a light beam scanning 360° horizontally, receiving on said vehicle the beam when reflected from fixed points in said motion space, and by measuring the angles in a plane parallel to said plane of movement between sight lines from a reference point on the vehicle to said fixed points and a reference direction on the vehicle, at least three angles being used for a trigonometric determination by cal-

ulation means of position and direction and according to which vehicle movement is corrected, if the actual position is not at said path characterized in that as said fixed points a plurality of reflectors anonymous but determined as to the position thereof are utilized for the navigation, that the position for each of the points as well as existing sight obstacles between the reference point of the vehicle and the fixed points is stored in an electronic memory, that the movement of the vehicle in said plane is initiated in a known position and with a known direction so as to identify the fixed points visible from the reference point in said position, and that in each position and direction of the vehicle during the movement thereof information with regard to position and direction which is previously obtained is utilized to determine by guidance of the position of the obstacles stored the identity of the fixed points visible from said reference point in said position.

2. Method according to claim 1, characterized in that the storing of the position of the fixed points is effected by reproducing said plane with sight obstacles and the fixed points in said electronic memory.

3. Method according to claim 2, characterized in that the reproducing is effected in a computer aided design system for visual representation of said plane with sight obstacles and the fixed points, said predetermined path to be followed by the vehicle being included in the visual representation.

4. Method according to claim 1, characterized in that the determination of the position of the fixed points is effected by driving the vehicle along a known path while measuring the angles to the fixed points by utilizing the optical system and the program controlled computing and storing of the positions of the fixed points in the electronic memory.

5. Method according to claim 1, characterized in that the angles are determined by measuring the period for the movement of the light beam scanning horizontally at constant speed, from a reference point to a position where it hits a reflector.

6. Method according to claim 1, characterized in that the reflected light beam is detected by utilizing two photo detectors arranged side by side, the outputs of which are added with reversed polarity and which are hit, one after the other, by the reflected light beam.

7. Method according to claim 1, characterized in that the light beam is emitted close to the plane of vehicle movement.

8. Method according to claim 1, characterized in that the vehicle during movement thereof is brought to a position in relation to a desired path, which is displaced more or less towards one side or the other of the nominal path on successive tours along said path.



Patentansprüche

1. Verfahren zur Lenkung eines Fahrzeuges, das sich entlang eines vorbestimmten Weges in einer Ebene in einem Bewegungsbereich bewegt, bei dem eine Bestimmung der jeweiligen Position und Richtung des Fahrzeuges vorgesehen ist durch Ausstrahlen eines horizontal um 360° abtastenden Lichtstrahls von besagtem Fahrzeug, durch Empfang des Strahls auf besagtem Fahrzeug, nach Reflektion an fixen Punkten in besagtem Bewegungsbereich und durch Messen der Winkel in einer Ebene parallel zu besagter Ebene der Bewegung zwischen Sichtlinien von einem Referenzpunkt auf dem Fahrzeug zu besagten fixen Punkten und einer Referenzrichtung auf dem Fahrzeug, wobei zumindest drei Winkel für eine trigonometrische Bestimmung der Position und Richtung durch eine Recheneinrichtung verwendet werden und entsprechend dazu die Fahrzeugbewegung korrigiert wird, falls die jeweilige Position nicht auf besagtem Weg liegt, dadurch gekennzeichnet, daß für die Lenkung als besagte fixe Punkte eine Vielzahl von anonymen, aber hinsichtlich ihrer Position bestimmten Reflektoren verwendet werden, daß die Position für jeden der Punkte wie für vorhandene Sichthindernisse zwischen den Referenzpunkten des Fahrzeuges und den fixen Punkten in einem elektronischen Speicher eingegeben wird, daß die Bewegung des Fahrzeuges in besagter Ebene in einer bekannten Position und mit einer bekannten Richtung begonnen wird, um die von dem Referenzpunkt in besagter Position sichtbaren fixen Punkte zu identifizieren, und daß in jeder Position und Richtung des Fahrzeuges während seiner Bewegung eine Information in Bezug auf Position und Richtung, die zuvor erhalten worden ist, verwendet wird, um durch Führung der Position der gespeicherten Hindernisse die Identität der fixen Punkte zu bestimmen, die von besagtem Referenzpunkt in besagter Position sichtbar sind.

2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Speicherung der Position der fixen Punkte durch Reproduktion besagter Ebene mit Sichthindernissen und der fixen Punkte in besagtem elektronischen Speicher durchgeführt wird.

3. Verfahren nach Anspruch 2, gekennzeichnet, daß die Reproduktion in computerunterstützten Design-Systemen für die visuelle Darstellung besagter Ebene mit Sichthindernissen und der fixen Punkte durchgeführt wird, wobei besagter vorbestimmter Weg, der von dem Fahrzeug verfolgt werden soll, in der visuellen Darstellung eingeschlossen ist.

4. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Bestimmung der Position der fixen Punkte durch Verfahren des Fahrzeuges entlang eines bekannten Weges durchgeführt wird, während die Winkel zu den fixen Punkten durch Verwendung des optischen Systems und der programmgesteuerten Berechnungen und Speicherungen der Positio-

nen der fixen Punkte in dem elektrischen Speicher gemessen werden.

5. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Winkel durch Messung der Bewegungszeit des horizontal abtastenden Lichtstrahls bei konstanter Geschwindigkeit von einem Bezugspunkt zu einer Position, wo er auf einen Reflektor auftritt, bestimmt wird.

6. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die reflektierten Lichtstrahlen durch Verwendung von zwei nebeneinander angeordneten Photodetektoren erfaßt werden, wobei deren Ausgangssignale mit umgekehrter Polarität addiert werden und die einer nach dem anderen durch den reflektierten Lichtstrahl beaufschlagt werden.

7. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß der Lichtstrahl nahe der Ebene der Fahrzeugbewegung ausgestrahlt wird.

8. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß das Fahrzeug während seiner Bewegung in eine Position in Bezug auf den gewünschten Weg gebracht wird, die mehr oder weniger zu der einen oder anderen Seite des normalen Weges auf nachfolgenden Touren entlang besagten Weges versetzt ist.

Revendications

1. Procédé de contrôle de déplacement d'un véhicule se déplaçant le long d'une trajectoire prédéterminée, dans un plan, dans un espace de déplacement, suivant lequel on procède à la détermination de la position et de la direction instantanées du véhicule, en faisant émettre par ledit véhicule, (puis réfléchir contre des réflecteurs), un faisceau lumineux, suivant 360° et horizontalement, en recevant sur ledit véhicule le faisceau réfléchi par des points fixes, dans ledit espace de déplacement, et en mesurant les angles, dans un plan parallèle audit plan de déplacement, entre des lignes de visées partant d'un point de référence situé sur le véhicule et allant auxdits points fixes et une direction de référence du véhicule, au moins trois angles étant utilisés pour procéder à une détermination trigonométrique à l'aide de moyens de calcul de position et de direction, et procédé selon lequel on corrige le mouvement du véhicule, si la position instantanée n'est pas située sur ladite trajectoire, caractérisé en ce qu'auxdits points fixes, une pluralité de réflecteurs anonymes, mais déterminés quant à leur position, sont utilisés pour le contrôle de déplacement, que la position de chacun des points ainsi que celle des obstacles visuels existants entre le point de référence du véhicule et les points fixes est mise en mémoire dans une mémoire électronique, le déplacement du véhicule dans ledit plan étant commencé en une position connue et avec une direction connue, de façon à identifier les points fixes visi-



bles depuis le point de référence dans ladite position, et qu'en chaque position et direction du véhicule pendant son déplacement, l'information concernant la position et la direction, qui est obtenue au préalable, est utilisée pour déterminer, par la localisation de la position des obstacles mise en mémoire, l'identité des points fixes visibles depuis ledit point de référence dans ladite position. 5

2. Procédé selon la revendication 1, caractérisé en ce que la mise en mémoire de la position des points fixes est effectuée en reproduisant ledit plan avec les obstacles visuels et les points fixes dans ladite mémoire électronique. 10

3. Procédé selon la revendication 2, caractérisé en ce que la reproduction est effectuée dans un système de conception assisté par ordinateur, conçu pour la représentation visuelle dudit plan, avec les obstacles visuels et les points fixes, ladite trajectoire prédéterminée devant être suivie par le véhicule étant incluse dans la représentation visuelle. 15 20

4. Procédé selon la revendication 1, caractérisé en ce que la détermination de la position des points fixes est effectuée par pilotage du véhicule suivant une trajectoire connue tout en mesurant les angles aux points fixes par utilisation du système optique et le calcul contrôlé par programme et en mettant en mémoire les positions des points fixes dans la mémoire électronique. 25

5. Procédé selon la revendication 1, caractérisé en ce que les angles sont déterminés par mesure de la période du déplacement du faisceau lumineux, en explorant horizontalement à une vitesse constante, depuis un point de référence jusqu'à une position à laquelle il touche un réflecteur. 30

6. Procédé selon la revendication 1, caractérisé en ce que le faisceau lumineux réfléchi est détecté en utilisant deux photo-détecteurs, disposés côte-à-côte, dont les signaux de sortie sont ajoutés avec un signe opposé et qui sont touchés, l'un après l'autre, par le faisceau lumineux réfléchi. 35 40

7. Procédé selon la revendication 1, caractérisé en ce que le faisceau lumineux est émis près du plan de déplacement du véhicule. 45

8. Procédé selon la revendication 1, caractérisé en ce que, lors de son déplacement, le véhicule est placé dans une position en relation avec une trajectoire souhaitée, qui est déplacée plus ou moins d'un côté ou de l'autre de la trajectoire de consigne, lors des passages successifs sur ladite trajectoire. 50 55

