

METHOD AND APPARATUS FOR BIT RUN AND RETRIEVED CASING HANGER LOCKING DEVICE

BACKGROUND

[0001] The present disclosure provides an apparatus and methods for installing and selectively retrieving a casing hanger locking device within a wellhead system during the bit run and retrieval operations.

[0002] Natural resources such as oil or gas residing in a subterranean formation can be recovered by drilling a wellbore that penetrates the formation. The drilling operation involves the use of a drill bit at the end of a drill string to cut through the ground and drill the wellbore. A drilling fluid may be circulated downwardly through the drill string and then upwardly through the wellbore to the surface. The drilling fluid may be used to, among other things, cool the drill bit, lubricate the rotating drill string to prevent it from sticking to the walls of the wellbore, and remove drill cuttings from the wellbore.

[0003] During the drilling operations, the wellbore passes through subterranean formations with a variety of geological characteristics. Many of these subterranean formations contain fluids, including water and hydrocarbons, known as formation fluids. The formation fluids often exist at high temperatures and pressures. In certain circumstances, the high temperatures and pressures in the subterranean formation lead to upward loads and/or forces that require the pressures of the formation fluids to be controlled.

[0004] In ideal circumstances, the pressures of the formation fluids may be controlled by balancing the pressure of the formation fluid with the hydrostatic pressure of a drilling fluid. The weight of the drilling fluid, which can be adjusted by adding weighting agents, is usually sufficient to control the subterranean pressure and prevent the upward loads.

[0005] The subterranean pressures can change, however, and sometimes these changes can be sudden and unpredictable. For example, if the drill bit penetrates a formation with a higher pressure, the hydrostatic pressure of the drilling fluid may not be sufficient to balance this increased pressure of the formation fluid. In certain instances, this can lead to a blowout. Blowouts lead to loss of pressure control and possible heat transfer of (uncontrolled) fluid. These aspects in turn lead to increased annulus pressure, thermal growth which leads to mechanical loads, and direct mechanical loads.

[0006] Steps must be taken to control the upward loads from the formation fluids in the subterranean formation and the wellbore during the drilling operation. If these steps are not taken, the upward load can unseat the casing hanger used in the wellbore. This may result in the possible failure of the casing hanger annulus seal, which can lead to further loss of pressure control. Unseating the casing hanger can also create mechanical interference with separate pressure control or containment devices. The failure to control the upward loads in the wellbore can lead to loss of operator control in the drilling operations, damage to the drilling equipment, and even injury to the personnel on site.

[0007] Mechanical locking devices are used to control the upward loads and prevent the upward travel of the casing hanger in a blowout condition or similar condition. The locking devices are typically installed at the top of the casing hanger at the wellhead. The locking devices are designed to resist upward loads so that the casing hanger does not travel upward through the wellbore even if the subterranean pressure spikes. Thus, even when subterranean fluids flow upward, the casing hanger remains locked in place and does not interfere with the pressure control and containment devices.

[0008] Locking devices can be difficult and expensive to use, however. For example, subsequent casing runs cannot be made with the locking device installed in the wellhead because the locking device interfaces with many of the same components with which the next casing hanger would interface. As a result, the locking device must be removed from the wellbore each time casing is added. Conventional locking devices require a dedicated trip to run and retrieve, and three total trips are required to use a conventional locking device. The first trip is typically a measurement trip to verify the position of the most previously installed casing hanger. The second trip is typically the installation of the locking device. And the third trip is typically the retrieval of the locking device. These trips can be substantial, particularly in subsea drilling operations, where the wellhead may be located thousands of feet below the ocean surface. Each trip requires dedicated tooling to perform the intended task, and at current rig rates, these operations become very expensive.

SUMMARY

[0009] The present disclosure provides an apparatus and methods for installing and selectively retrieving a casing hanger locking device within a wellhead system during the bit run and retrieval operations.

[0010] An embodiment of the present disclosure is an apparatus comprising: a bit sub comprising a tong neck, a cylindrical portion below the tong neck, and at least one stabilizing fin below the cylindrical section, wherein the at least one stabilizing fin comprises a keyway; a casing hanger locking device comprising an annular structure and an expandable ring disposed around an upper portion of the annular structure, the casing hanger locking device disposed around the bit sub; an actuation sleeve that engages with the casing hanger locking device; and a selective retrieval collar comprising a segmented retrieval ring, wherein the selective retrieval collar is attached to the bit sub, the actuation sleeve, and the casing hanger locking device. Optionally, the selective retrieval collar is attached to the bit sub with a first plurality of sheer pins; the selective retrieval collar is attached to the casing hanger locking device with a second plurality of sheer pins; and the selective retrieval collar is attached to the actuation sleeve with the segmented retrieval ring. Optionally, the keyway comprises a tapered section. Optionally, the casing hanger locking device further comprises at least one key that interfaces with the at least one keyway. Optionally, the at least one stabilizing fin further comprises at least one groove. Optionally, the bit sub further comprises at least one load shoulder. Optionally, the segmented retrieval ring is configured to selectively engage the actuation sleeve by a special operational function.

[0011] Another embodiment of the present disclosure is an apparatus comprising: a bit sub comprising a tong neck, a cylindrical portion below the tong neck, and at least one stabilizing fin below the cylindrical section, wherein the at least one stabilizing fin comprises a keyway; a casing hanger locking device comprising an annular structure and an expandable ring disposed around an upper portion of the annular structure, the casing hanger locking device disposed around the bit sub; an actuation sleeve that engages with the casing hanger locking device; and a selective retrieval collar, wherein the selective retrieval collar is attached to both the bit sub and the casing hanger locking device. Optionally, the selective retrieval collar is attached to the bit sub with a first plurality of sheer pins; the selective retrieval collar is attached to the casing hanger locking device with a second plurality of sheer pins; and the selective

retrieval collar is not attached to the actuation sleeve. Optionally, the keyway comprises a tapered section. Optionally, the casing hanger locking device further comprises at least one key that interfaces with the at least one keyway. Optionally, the at least one stabilizing fin further comprises at least one groove. Optionally, the bit sub further comprises at least one load shoulder.

[0012] Another embodiment of the present disclosure is a method comprising: lowering an apparatus into a wellbore using a drill string, wherein the apparatus comprises: a bit sub comprising a tong neck, a cylindrical portion below the tong neck, and at least one stabilizing fin below the cylindrical section, wherein the at least one stabilizing fin comprises a keyway, a casing hanger locking device comprising an annular structure and an expandable ring disposed around an upper portion of the annular structure, the casing hanger locking device disposed around the bit sub, an actuation sleeve that engages with the casing hanger locking device, and a selective retrieval collar, wherein the selective retrieval collar is attached to both the bit sub and the casing hanger locking device; setting the casing hanger locking device in place in the wellbore; detaching the bit sub from the selective retrieval collar and the casing hanger locking device; lowering the bit sub further into the wellbore using the drill string to facilitate further drilling operations; and removing the drill string and the bit sub from the wellbore, wherein the bit sub engages the selective retrieval collar and removes the selective retrieval collar from the wellbore. Optionally, the casing hanger locking device remains in the wellbore after the bit sub and the selective retrieval collar have been removed from the wellbore. Optionally, the selective retrieval collar comprises a segmented retrieval ring and wherein the selective retrieval collar is attached to the actuation sleeve. Optionally, the step of removing the drill string and the bit sub from the wellbore further comprises removing the casing hanger locking device from the wellbore. Optionally, the step of detaching the bit sub from the selective retrieval collar and the casing hanger locking device further comprises rotating the bit sub relative to the selective retrieval collar and the casing hanger locking device. Optionally, the at least one stabilizing fin further comprises at least one groove, and wherein the step of detaching the bit sub from the selective retrieval collar and the casing hanger locking device further comprises at least one lock segment from the at least one groove. Optionally, the bit sub further comprises at least one load shoulder, and wherein the step of removing the drill string and the bit

sub from the wellbore further comprises contacting the selective retrieval collar with the at least one load shoulder.

[0013] The features and advantages of the present invention will be readily apparent to those skilled in the art. While numerous changes may be made by those skilled in the art, such changes are within the spirit of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] These drawings illustrate certain aspects of some of the embodiments of the present invention, and should not be used to limit or define the invention.

[0015] Figure 1 illustrates an example of an assembled apparatus in accordance with an embodiment of the present disclosure.

[0016] Figures 2a-2c illustrate an example of a casing hanger locking device in accordance with an embodiment of the present disclosure.

[0017] Figures 3a-3b illustrate an example of a bit sub in accordance with an embodiment of the present disclosure.

[0018] Figures 4a-4b illustrate how the casing hanger locking device may interface with the bit sub in accordance with an embodiment of the present disclosure.

[0019] Figures 5a-5b illustrate an example of a selective retrieval collar in accordance with an embodiment of the present disclosure.

[0020] While embodiments of this disclosure have been depicted, such embodiments do not imply a limitation on the disclosure, and no such limitation should be inferred. The subject matter disclosed is capable of considerable modification, alteration, and equivalents in form and function, as will occur to those skilled in the pertinent art and having the benefit of this disclosure. The depicted and described embodiments of this disclosure are examples only, and not exhaustive of the scope of the disclosure.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0021] The present disclosure provides an apparatus and methods for installing and selectively retrieving a casing hanger locking device within a wellhead system during the bit run and retrieval operations. This can save effort, time, and expense over the prior art locking devices that require dedicated trips to remove them from the wellbore each time a new casing section is added.

[0022] In certain embodiments, the apparatus of the present disclosure is an assembly that comprises three major components. The first component is a Casing Hanger Locking Device. The Casing Hanger Locking Device is the component of the apparatus that serves as the locking device and can resist upward loads. The Casing Hanger Locking Device may comprise an actuation sleeve. The second component is a Bit Sub. The Bit Sub is attached directly to the drill string and connects the apparatus of the present disclosure to the drill string. The third component is a Selective Retrieval Collar. The Selective Retrieval Collar is attached to both of the other components and provides for the selective retrieval or installation of the Casing Hanger Locking Device.

[0023] Illustrative embodiments of the present disclosure are described in detail below. In the interest of clarity, not all features of an actual implementation are described in this specification. It will of course be appreciated that in the development of any such actual embodiments, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure. The details of various illustrative embodiments will now be described with reference to the figures.

[0024] Figure 1 illustrates a cross-sectional view of an embodiment where the components of the apparatus are assembled. The Casing Hanger Locking Device **100** is provided and is generally in the shape of a tube or an annular ring. The Bit Sub **200** comprises the core of the assembly and is generally cylindrical in shape. The Casing Hanger Locking Device **100** fits around the Bit Sub **200** and is connected to the Bit Sub **200**. The Selective Retrieval Collar **300** is generally in the shape of a tube or an annular ring. The Selective

Retrieval Collar **300** fits between the Casing Hanger Locking Device **100** and the Bit Sub **200** and connects to both of these components. In certain embodiments, Selective Retrieval Collar **300** is at the top of the assembly. In other embodiments, however, Selective Retrieval Collar **300** may optionally be at the bottom of the assembly. The actuation sleeve **400** fits around the Selective Retrieval Collar **300** and engages with the Casing Hanger Locking Device **100**.

[0025] In Figure 1, the entire assembly is shown. The Casing Hanger Locking Device **100** — which forms the exterior of the assembly — may be deployed adjacent to a wellhead (not shown). The Casing Hanger Locking Device **100** may be positioned above the casing hanger (not shown). The Casing Hanger Locking Device **100** functions as the locking device and can resist upward loads in the wellbore. In particular, the Casing Hanger Locking Device **100** resists casing hanger movement by transferring upward load from the casing hanger into load shoulders within the wellhead. In other words, when the Casing Hanger Locking Device **100** is installed, it may mechanically prevent upward movement by the casing hanger.

[0026] Figures 2a, 2b and 2c illustrate an embodiment of the Casing Hanger Locking Device **100** and the actuation sleeve **400**. Figure 2a illustrates a profile view of the Casing Hanger Locking Device **100** along its axis. Figure 2b illustrates a cross-section of the Casing Hanger Locking Device **100** perpendicular to its axis. Figure 2c illustrates a sectional view of an embodiment of a spring loaded square key **134** that will be described in more detail below. As shown in the exemplary embodiment of Figures 2a, 2b and 2c, the Casing Hanger Locking Device **100** may be an annular structure with an upper end, a mid-section, and a lower end. When it is installed, the Casing Hanger Locking Device **100** can be locked in place through the use of an expandable ring **112** located at its upper end. The Casing Hanger Locking Device **100** locks during a designed operation by way of load shoulders **114** on the expandable ring **112** that engage a designed profile within the wellhead.

[0027] As shown in Figure 2a, the upper end of the Casing Hanger Locking Device **100** supports the expandable ring **112**. The upper end also engages with the actuation sleeve **400**. The left side of Figure 2a shows the Casing Hanger Locking Device **100** in its running position. The right side of Figure 2a shows the Casing Hanger Locking Device **100** in its locked and landed position. When the Casing Hanger Locking Device **100** is locked, the actuation sleeve **400** moves down and forces the expandable ring **112** in an outward axial

direction. When the Casing Hanger Locking Device **100** is set in the wellhead (as discussed below), this permits the load shoulders **114** to engage the profile in the wellhead.

[0028] The interior surface of the upper end of the Casing Hanger Locking Device **100** may have an upper shear pin groove **116a** and a lower shear pin groove **116b**. The upper shear pin groove **116a** and a lower shear pin groove **116b** are configured to engage shear pins connected to the Selective Retrieval Collar **300**. The lower side of the upper shear pin groove **116a** and a lower shear pin groove **116b** may be beveled to allow the Selective Retrieval Collar **300** to move in a downward direction relative to the Casing Hanger Locking Device **100** without breaking the shear pins. The interior surface of the upper end of the Casing Hanger Locking Device **100** may also have a groove **118**. Casing Hanger Locking Device **100** also includes a C-ring **120**.

[0029] The mid-section of the Casing Hanger Locking Device **100** includes a plurality of keyway slots **132** that extend through the wall of the Casing Hanger Locking Device **100**. The keys **134** in the keyway slots **132** have a stop shoulder **136** on them to prevent them from passing through the keyway slot **132**. These keys **134** are spring loaded inward. In some embodiments, the keys **134** may be square. As described below in more detail, the keys **134** may be used to attach the Casing Hanger Locking Device **100** to the Bit Sub **200**.

[0030] The lower end of the Casing Hanger Locking Device **100** is designed to rest on the casing hanger and extends into the bowl of the casing hanger (not shown in Figure 2) to protect these surfaces. The interior surface of this lower end of the Casing Hanger Locking Device **100** has spring loaded lock segments **152** that engage the Bit Sub **200** when the assembly is in a running position. The Casing Hanger Locking Device **100** also includes shear pins **154** and spherical nose pins **156**. When the Casing Hanger Locking Device **100** is deployed into the well, the spherical nose pins **156** contact the casing hanger **600**. This causes the shear pins **154** to break and releases the lock segments **152**.

[0031] As noted earlier, Figure 2b illustrates a cross-section of the same embodiment of the Casing Hanger Locking Device **100** perpendicular to its axis. Figure 2c illustrates a sectional view through the spring loaded key **134**. This key **134** is shown extending into the bore of the Casing Hanger Locking Device **100**. The c-ring **138** on the rod section of the key is shown expanded condition. The groove on the rod section will prevent the key from moving back to its current position once it is retracted.

[0032] Figures 3a and 3b illustrate an embodiment of the Bit Sub **200**. Figure 3a illustrates a profile view of the Bit Sub **200** along its axis. Figure 3b illustrates a cross-section of the Bit Sub **200** that is perpendicular to its axis. The Bit Sub **200** is similar to a standard stabilizer sub. The stabilizer sub acts as the running tool for the Casing Hanger Locking Device **100**. The Bit Sub **200** typically connects to the drill string above the drill bit. It interfaces with the drill string on both ends, providing the necessary means to deliver, lock, verify, and retrieve the Casing Hanger Locking Device **100**.

[0033] As shown in the exemplary embodiment of Figure 3a, the Bit Sub **200** may comprise a tong neck **210** and cylindrical section **220** below the tong neck **210**. The cylindrical section **220** may have a load shoulder **222** that is configured to engage with the Selective Retrieval Collar **300**. The cylindrical section **220** also has drilled holes **224** that accept shear pins. The shear pins may be used to release the Bit Sub **200** after it lands in the wellhead. These shear pins connect the Bit Sub **200** to the Selective Retrieval Collar **300** during deployment and installation. They are sheared during operation to allow further deployment of the Bit Sub **200** downhole for continued drilling operations.

[0034] As further shown in Figure 3a, the Bit Sub **200** also has load carrying taper in the stabilizing fins **240** (upper surface). These stabilizing fins **240** have a wide milled keyway **242** that extends vertically downward. This keyway **242** will interface with the square keys **134** in the Casing Hanger Locking Device **100**. In some embodiments, the keyway **242** have a tapered section **243** on one face of the slot near the upper end of the keyway. In other embodiments, the keyway **242** may have the face in this area removed. This area of the keyway **242** is provided in order that the stabilizing fins **240** may escape the slot when the drill string is rotated. Below this keyway **242** is a machined groove **244** that extends across the stabilizing fin **240**. This machined groove **244** will provide the load shoulders for the over-pull check that will ensure the Casing Hanger Locking Device **100** is locked into place.

[0035] Figure 3b shows the cross section of Bit Sub **200** including the stabilizing fins **240**. The keyway **242** can be seen in the profile of the stabilizing fin **240**. The tapered section **243** is also visible.

[0036] Figures 4a and 4b are cross-sectional views that are perpendicular to the axis of the assembly. Figures 4a and 4b demonstrate how the Casing Hanger Locking Device **100** may surround and interface with the Bit Sub **200** when the apparatus is assembled. In

particular, the square keys **134** pass through the wall of the Casing Hanger Locking Device **100** through the keyway slots **132** (not labeled in Figure 4). The square keys **134** fit in the keyway **242** of the stabilizing fins **240**.

[0037] Figures 5a and 5b illustrate an embodiment of the Selective Retrieval Collar **300**. Figure 5a illustrates a profile view of the Selective Retrieval Collar **300** along its axis. Figure 5b illustrates a cross-section of the Selective Retrieval Collar **300** that is perpendicular to its axis. The Selective Retrieval Collar **300** interfaces with both the Casing Hanger Locking Device **100** and the Bit Sub **200**. This component also provides the functionality that allows the operator to pre-determine if the Casing Hanger Locking Device **100** is to be retrieved on the same trip or left behind.

[0038] In the embodiment of Figure 5a, the Selective Retrieval Collar **300** has holes **310** that accept shear pins, which attach it to the Bit Sub **200**. These holes **310** align with the drilled holes **224** of the Bit Sub **200**. The shear pins in holes **310** break during the initial locking operation, whereby weight is slacked off the crown block/derrick and transferred into the Casing Hanger Locking Device **100** through the Bit Sub **200**. The Selective Retrieval Collar **300** includes a load transfer pin **320**. The load transfer pin **320** maybe positioned in a groove **325**. The Selective Retrieval Collar **300** also has a spring loaded key **330** that engages the groove **118** in the Casing Hanger Locking Device **100** to prevent rotation that might lead to wear and damage. The inside diameter of the Selective Retrieval Collar **300** has several flow-by holes that run the length of the part. The lower cylindrical face of the Selective Retrieval Collar **300** will act upon the adjacent upper faces of the stabilizing fins **240** of the Bit Sub **200**. The Selective Retrieval Collar **300** also has a row of shear pin pockets **340** that interfaces with Casing Hanger Locking Device **100**.

[0039] Depending on whether the operator wishes to retrieve the Casing Hanger Locking Device **100** (as discussed below), the Selective Retrieval Collar **300** may take the form of either of two configurations. In the first configuration, Selective Retrieval Collar **300** includes a high strength segmented retrieval ring **350**. In the second configuration, the Selective Retrieval Collar **300** does not include the high strength segmented retrieval ring **350**.

[0040] The present disclosure in some embodiments include methods for using the apparatus of the present disclosure to carry out a variety of drilling operations. During drilling operations, the apparatus of the present disclosure is connected to the drill string. In

certain embodiments, the apparatus of the present disclosure may be connected to the drill string above the drill bit. For example, the Bit Sub **200** may be connected to the drill string via industry-standard API tool joints. A person of ordinary skill in the art, with the benefit of this disclosure, would understand how to connect the apparatus to the drill string for the desired operations.

[0041] In certain embodiments, the apparatus of the present disclosure may be introduced into the wellbore as part of the drill string. The entire apparatus, including the Casing Hanger Locking Device **100**, the Bit Sub **200**, and the Selective Retrieval Collar **300**, may be lowered into the wellbore according to conventional methods. For example, the drill string may be run into the wellbore.

[0042] **Placing the Casing Hanger Locking Device:** When the apparatus of the present disclosure reaches the level of the casing hanger, the Casing Hanger Locking Device **100** may be locked into place. In an embodiment, the assembly is lowered with the drill string into the wellbore. When the assembly reaches the casing hanger, the Casing Hanger Locking Device **100** is unable to move any further downhole. However, the spherical nose pins **156** contact the casing hanger. The spherical nose pins **156** are depressed which causes the shear pins **154** to break and releases the lock segments **152**. The lock segments **152** disengage from the machined grooves **244** in the Bit Sub **200** which allows the Bit Sub **200** to move downward relative to the Casing Hanger Locking Device **100**.

[0043] To set the Casing Hanger Locking Device **100** in place, the Bit Sub **200**, the Selective Retrieval Collar **300**, and the actuation sleeve **400** continue to move downhole. Shear pins attaching the actuation sleeve **400** to the Casing Hanger Locking Device **100** break, allowing the actuation sleeve **400** to move relative to the Casing Hanger Locking Device **100**. The actuation sleeve **400** moves down and forces the expandable ring **112** in an outward axial direction. This permits the load shoulders **114** to engage the profile in the wellhead, setting the Casing Hanger Locking Device **100** in place.

[0044] The Selective Retrieval Collar **300** remains connected to the Casing Hanger Locking Device **100** and the Bit Sub **200** disengages from both components. In particular, the shear pins (in holes **310** Selective Retrieval Collar **300** and the drilled holes **224** of the Bit Sub **200**) break and allow the Bit Sub **200** to move downward relative to the Selective Retrieval Collar **300**.

[0045] As the Bit Sub **200** moves downward, it releases the load transfer pins **320**. The C-ring **120** that is biased inwardly moves into the groove **325** on the Selective Retrieval Collar **300**. If the Selective Retrieval Collar **300** is loaded upwardly, this load goes into these interfaces rather than the spring loaded shear pins **340**.

[0046] At this point, an over-pull may be performed to ensure that the Casing Hanger Locking Device **100** is properly set. The operator may continue to trip in until his weight indicator shows he has tagged the bit sub keyway **242** on the square keys **134** in the Casing Hanger Locking Device **100**. At this point an over-pull may be performed to ensure that the Casing Hanger Locking Device **100** is properly set.

[0047] The operator may then perform a rotation to completely disengage the Bit Sub **200** from the Casing Hanger Locking Device **100**. Rotating the Bit Sub **200** rotates the stabilizing fin **240** relative to the square keys **134**. This rotation allows the square keys **134** to be removed from the keyway **242**, for example, by passing over the tapered section **243**. As the stabilizing fin **240** retracts the square key **134** from the keyway **242**, a c-ring **138** snaps into a groove on the square key's rod section. This will not allow the key to re-enter the bore of the Casing Hanger Locking Device **100**. This completes the placement of the Casing Hanger Locking Device **100**.

[0048] Following the placement of the Casing Hanger Locking Device **100**, the drill string, including the drill bit and the Bit Sub **200**, are free to continue running down the wellbore. Therefore, drilling operations may continue after the Casing Hanger Locking Device **100** has been placed. When the Casing Hanger Locking Device **100** is locked into place, it is capable of resisting upward loads on the casing. This ensures that the well is kept under control if the drill bit penetrates a subterranean formation with increased temperature and pressure.

[0049] At some point, the operator may wish to remove the drill string from the wellbore. For example, the operator may need to change the drill bit or use a different tool. The drill string including the Bit Sub **200** may be removed from the wellbore according to conventional methods. According to embodiments of the present disclosure, the Casing Hanger Locking Device **100** may be selectively retrieved or left behind when the Bit Sub **200** reaches the level of the wellbore where it has been placed. In particular, and as discussed below, Bit Sub **200** will always retrieve Selective Retrieval Collar **300** but it will either retrieve or leave the

Casing Hanger Locking Device **100** depending on how the Selective Retrieval Collar **300** is configured.

[0050] The Casing Hanger Locking Device **100** may be selectively retrieved from the wellbore or left behind depending on the goal of the operator. For example, the Casing Hanger Locking Device **100** may be retrieved from the well bore under normal operations or, for example, when an additional casing is installed in the well bore. For example, an operator may retrieve the Casing Hanger Locking Device **100** when drilling operations are believed to be short enough to remove the locking device in preparation for subsequent casing hanger installation. Alternatively, the Casing Hanger Locking Device **100** may be left in the wellbore when the well bore needs to be sealed for a period of time. An operator may leave the Casing Hanger Locking Device **100** when, for example, the drilling operations are believed to be long enough to necessitate a drill bit replacement, there is possible inclement weather during drilling operations that would require a disconnect from the wellhead, or there are other reasons requiring temporary abandonment between drilling and production operations.

[0051] Whether the Casing Hanger Locking Device **100** is retrieved on the same trip or left behind is determined by the configuration of Selective Retrieval Collar **300**. As explained in more detail below, when retrieving the Casing Hanger Locking Device **100**, the operator will select the configuration of Selective Retrieval Collar **300** that includes a segmented retrieval ring **350**. The row of pockets **340** is loaded with spring loaded shear pins. This arrangement will allow the Casing Hanger Locking Device **100** to be carried to the surface. When leaving the Casing Hanger Locking Device **100**, the operator will select the configuration of Selective Retrieval Collar **300** that does not include a segmented retrieval ring **350** and the row **340** is loaded with spring loaded sheer pins.

[0052] **Retrieving the Casing Hanger Locking Device:** In one configuration, the apparatus of the present disclosure may be used to retrieve the Casing Hanger Locking Device **100**. In this first configuration, the Selective Retrieval Collar **300** is connected to the actuation sleeve **400** through the segmented retrieval ring **350**. This ensures that the Selective Retrieval Collar **300** remains connected to the actuation sleeve **400**. The row **340** that connects the Selective Retrieval Collar **300** to the Casing Hanger Locking Device **100** is loaded with spring loaded sheer pins.

[0053] As the Bit Sub **200** is removed from the well bore and pulled through the assembly, it tags out on the Selective Retrieval Collar **300**. In particular, the shoulder **222** engages the Selective Retrieval Collar **300**. The Selective Retrieval Collar **300** is connected to the actuation sleeve **400** through the segmented retrieval ring **350**, and as a result, this mechanical action pulls on the actuation sleeve **400**, which pulls on the Casing Hanger Locking Device **100**. The Selective Retrieval Collar **300** is connected to the Casing Hanger Locking Device **100** with spring loaded sheer pins. The spring loaded sheer pins break, which permits the actuation sleeve **400** to be lifted sufficiently high enough to disengage the expandable ring **112** and unlock the Casing Hanger Locking Device **100** from the mating wellhead profile. In certain embodiments, additional shear pins (not shown) may also be used. Continuing to lift pulls on the Bit Sub **200**, which pulls on the Selective Retrieval Collar **300**, which pulls on the actuation sleeve **400**, and which engages the Casing Hanger Locking Device **100** via a shoulder and removes it from the wellhead.

[0054] In certain embodiments, the apparatus of the present disclosure may be configured to permit the operator to determine whether to retrieve the Casing Hanger Locking Device **100** on the fly. In these embodiments, the Selective Retrieval Collar **300** may be provided with a segmented retrieval ring **350** as discussed above. However, in these embodiments, segmented retrieval ring **350** may be made passive and triggered to engage the actuation sleeve **400** by a special operational function. If the operational function is performed after the apparatus is deployed, the segmented retrieval ring **350** may engage the actuation sleeve **400** (to retrieve the Casing Hanger Locking Device **100**). On the other hand, if the operational function is not performed after the apparatus is deployed, the segmented retrieval ring **350** will not engage the actuation sleeve **400** (to leave the Casing Hanger Locking Device **100** behind).

[0055] **Leaving the Casing Hanger Locking Device:** In another configuration, the apparatus may be used to retrieve only the Bit Sub **200** and Selective Retrieval Collar **300**. In this second configuration, a Selective Retrieval Collar **300** without a segmented retrieval ring **350** is selected, such that the Selective Retrieval Collar **300** is not connected to the actuation sleeve **400**. This allows the Selective Retrieval Collar **300** to separate from the actuation sleeve **400**. The row **340** that connects the Selective Retrieval Collar **300** to the Casing Hanger Locking Device **100** is loaded with spring loaded sheer pins. Spring loaded sheer pins are used so that a

positive indication is given when the Selective Retrieval Collar **300** disengages from the Casing Hanger Locking Device **100**.

[0056] As the Bit Sub **200** is pulled through the assembly, it tags out on the Selective Retrieval Collar **300**, which pulls on the actuation sleeve **400**, which pulls on the Casing Hanger Locking Device **100**. The Selective Retrieval Collar **300** is pulled with sufficiently high force to shear the pins which attached it to the Casing Hanger Locking Device **100**. When the sheer pins break, neither the Bit Sub **200** nor the Selective Retrieval Collar **300** is connected, either directly or indirectly, to the Casing Hanger Locking Device **100**. Continuing to lift removes only the Bit Sub **200** and the Selective Retrieval Collar **300** from the wellhead.

[0057] Therefore, the present invention is well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The particular embodiments disclosed above are illustrative only, as the present invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular illustrative embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the present invention. All numbers and ranges disclosed above may vary by some amount. Whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range is specifically disclosed. In particular, every range of values (of the form, "from about a to about b," or, equivalently, "from approximately a to b," or, equivalently, "from approximately a-b") disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values. Moreover, the indefinite articles "a" or "an", as used in the claims, are defined herein to mean one or more than one of the element that it introduces. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee.

What is claimed is:

1. An apparatus comprising:
 - a bit sub comprising a tong neck, a cylindrical portion below the tong neck, and at least one stabilizing fin below the cylindrical section, wherein the at least one stabilizing fin comprises a keyway;
 - a casing hanger locking device comprising an annular structure and an expandable ring disposed around an upper portion of the annular structure, the casing hanger locking device disposed around the bit sub;
 - an actuation sleeve that engages with the casing hanger locking device; and
 - a selective retrieval collar comprising a segmented retrieval ring, wherein the selective retrieval collar is attached to the bit sub, the actuation sleeve, and the casing hanger locking device.
2. The apparatus of claim 1 wherein:
 - the selective retrieval collar is attached to the bit sub with a first plurality of sheer pins;
 - the selective retrieval collar is attached to the casing hanger locking device with a second plurality of sheer pins; and
 - the selective retrieval collar is attached to the actuation sleeve with the segmented retrieval ring.
3. The apparatus of claim 1 wherein the keyway comprises a tapered section.
4. The apparatus of claim 1 wherein the casing hanger locking device further comprises at least one key that interfaces with the at least one keyway.
5. The apparatus of claim 1 wherein the at least one stabilizing fin further comprises at least one groove.
6. The apparatus of claim 1 wherein the bit sub further comprises at least one load shoulder.

7. The apparatus of claim 1 wherein the segmented retrieval ring is configured to selectively engage the actuation sleeve by a special operational function.

8. An apparatus comprising:
a bit sub comprising a tong neck, a cylindrical portion below the tong neck, and at least one stabilizing fin below the cylindrical section, wherein the at least one stabilizing fin comprises a keyway;

a casing hanger locking device comprising an annular structure and an expandable ring disposed around an upper portion of the annular structure, the casing hanger locking device disposed around the bit sub;

an actuation sleeve that engages with the casing hanger locking device; and

a selective retrieval collar, wherein the selective retrieval collar is attached to both the bit sub and the casing hanger locking device.

9. The apparatus of claim 8 wherein:
the selective retrieval collar is attached to the bit sub with a first plurality of sheer pins;

the selective retrieval collar is attached to the casing hanger locking device with a second plurality of sheer pins; and

the selective retrieval collar is not attached to the actuation sleeve.

10. The apparatus of claim 8 wherein the keyway comprises a tapered section.

11. The apparatus of claim 8 wherein the casing hanger locking device further comprises at least one key that interfaces with the at least one keyway.

12. The apparatus of claim 8 wherein the at least one stabilizing fin further comprises at least one groove.

13. The apparatus of claim 8 wherein the bit sub further comprises at least one load shoulder.

14. A method comprising:

lowering an apparatus into a wellbore using a drill string, wherein the apparatus comprises:

a bit sub comprising a tong neck, a cylindrical portion below the tong neck, and at least one stabilizing fin below the cylindrical section, wherein the at least one stabilizing fin comprises a keyway,

a casing hanger locking device comprising an annular structure and an expandable ring disposed around an upper portion of the annular structure, the casing hanger locking device disposed around the bit sub,

an actuation sleeve that engages with the casing hanger locking device,
and

a selective retrieval collar, wherein the selective retrieval collar is attached to both the bit sub and the casing hanger locking device;

setting the casing hanger locking device in place in the wellbore;

detaching the bit sub from the selective retrieval collar and the casing hanger locking device;

lowering the bit sub further into the wellbore using the drill string to facilitate further drilling operations; and

removing the drill string and the bit sub from the wellbore, wherein the bit sub engages the selective retrieval collar and removes the selective retrieval collar from the wellbore.

15. The method of claim 14 wherein the casing hanger locking device remains in the wellbore after the bit sub and the selective retrieval collar have been removed from the wellbore.

16. The method of claim 14 wherein the selective retrieval collar comprises a segmented retrieval ring and wherein the selective retrieval collar is attached to the actuation sleeve.

17. The method of claim 16 wherein the step of removing the drill string and the bit sub from the wellbore further comprises removing the casing hanger locking device from the wellbore.

18. The method of claim 14 wherein the step of detaching the bit sub from the selective retrieval collar and the casing hanger locking device further comprises rotating the bit sub relative to the selective retrieval collar and the casing hanger locking device.

19. The method of claim 14 wherein the at least one stabilizing fin further comprises at least one groove, and wherein the step of detaching the bit sub from the selective retrieval collar and the casing hanger locking device further comprises at least one lock segment from the at least one groove.

20. The method of claim 14 wherein the bit sub further comprises at least one load shoulder, and wherein the step of removing the drill string and the bit sub from the wellbore further comprises contacting the selective retrieval collar with the at least one load shoulder.