


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau
SINGAPORE




9802013-4
IP05



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: H04R 7/06, B65D 79/00, 81/36	A2	(11) International Publication Number: WO 97/09855 (43) International Publication Date: 13 March 1997 (13.03.97)
(21) International Application Number: PCT/GB96/02146 (22) International Filing Date: 2 September 1996 (02.09.96) (30) Priority Data: 9517918.0 2 September 1995 (02.09.95) GB 9522281.6 31 October 1995 (31.10.95) GB 9606836.6 30 March 1996 (30.03.96) GB (71) Applicant (for all designated States except US): VERITY GROUP PLC [GB/GB]; Stonehill, Huntingdon, Cambridgeshire PE18 6ED (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): AZIMA, Henry [CA/GB]; 3 Southacre Close, Chaucer Road, Cambridge CB2 2TT (GB). COLLOMS, Martin [GB/GB]; 22 Burgess Hill, London NW2 2DA (GB). HARRIS, Neil [GB/GB]; 9 Davey Crescent, Great Shelford, Cambridge CB2 5JF (GB). (74) Agent: MAGUIRE & CO.; 5 Crown Street, St. Ives, Cambridgeshire PE17 4EB (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: PACKAGING



(57) Abstract

Packaging (111) comprising a board component (140), characterised in that the board is a distributed mode acoustic radiator (2) having a transducer (9) mounted wholly and exclusively on the radiator to vibrate the radiator to cause it to resonate.

5

TITLE: PACKAGING

10

DESCRIPTION

15

TECHNICAL FIELD


The invention relates to packaging and more particularly to packaging incorporating loudspeakers.

BACKGROUND ART

It is known from GB-A-2262861 to suggest a panel-form
20 loudspeaker comprising:-

a resonant multi-mode radiator element being a unitary sandwich panel formed of two skins of material with a spacing core of transverse cellular construction, wherein the panel is such as to have ratio of bending stiffness
25 (B), in all orientations, to the cube power of panel mass per unit surface area (μ) of at least 10;

a mounting means which supports the panel or attaches to it a supporting body, in a free undamped manner;




and an electro-mechanical drive means coupled to the panel which serves to excite a multi-modal resonance in the radiator panel in response to an electrical input within a working frequency band for the loudspeaker.

5

DISCLOSURE OF INVENTION

Embodiments of the present invention use members of nature, structure and configuration achievable generally and/or specifically by implementing teachings of our co-pending PCT application no. (Our case P.5711) of even date
10 herewith. Such members thus have capability to sustain and propagate input vibrational energy by bending waves in operative area(s) extending transversely of thickness often but not necessarily to edges of the member(s); are configured with or without anisotropy of bending stiffness
15 to have resonant mode vibration components distributed over said area(s) beneficially for acoustic coupling with ambient air; and have predetermined preferential locations or sites within said area for transducer means, particularly operationally active or moving part(s) thereof
20 effective in relation to acoustic vibrational activity in said area(s) and signals, usually electrical, corresponding to acoustic content of such vibrational activity. Uses are envisaged in co-pending International application No. (our file P.5711) for such members as or in "passive" acoustic
25 devices without transducer means, such as for reverberation or for acoustic filtering or for acoustically "voicing" a space or room; and as or in "active" acoustic devices with transducer means, such as in a remarkably wide range of



sources of sound or loudspeakers when supplied with input signals to be converted to said sound, or in such as microphones when exposed to sound to be converted into other signals.

5 This invention is particularly concerned with packaging incorporating acoustic devices e.g. in the form of loudspeakers. The term 'packaging' is intended to encompass containers generally whether or not they are disposable.

10 Members as above are herein called distributed mode radiators and are intended to be characterised as in the above PCT application and/or otherwise as specifically provided herein.

15 The invention is packaging comprising a board component, characterised in that the board is a distributed mode acoustic radiator having a transducer mounted wholly and exclusively on the radiator to vibrate the radiator to cause it to resonate. The board may be a panel having a cellular core sandwiched between skin layers. The board
20 may comprise a core of foamed plastics sandwiched between sheets of craft board. The transducer may be a piezo-electric bender.

25 The board formed one side of a box. The box may have a lid, and means may be associated with the lid for triggering actuation of the transducer on movement of the lid relative to the box.

 The packaging may comprise a signal generator, an amplifier and an electric battery.

BRIEF DESCRIPTION OF DRAWINGS

The invention is diagrammatically illustrated, by way of example, in the accompanying drawings, in which:-

Figure 1 is a diagram showing a distributed-mode
5 loudspeaker as described and claimed in our co-pending International application No. (our case P.5711);

Figure 2a is a partial section on the line A-A of Figure 1;

Figure 2b is an enlarged cross-section through a
10 distributed mode radiator of the kind shown in Figure 2a and showing two alternative constructions;

Figure 3 is a perspective diagram of an embodiment of packaging, and

Figure 4 is a perspective view of a transducer.

15 BEST MODES FOR CARRYING OUT THE INVENTION

Referring to Figure 1 of the drawings, there is shown a panel-form loudspeaker (81) of the kind described and claimed in our co-pending International application No. (our case P.5711) of even date herewith comprising a
5 rectangular frame (1) carrying a resilient suspension (3) round its inner periphery which supports a distributed mode sound radiating panel (2). A transducer (9) e.g as described in detail with reference to our co-pending International applications Nos. (our cases P.5683/4/5) of
10 even date herewith, is mounted wholly and exclusively on or in the panel (2) at a predetermined location defined by dimensions x and y , the position of which location is calculated as described in our co-pending International



WO 97/09855

PCT/GB96/02146

5

application No. (our case P.5711) of even date herewith, to launch bending waves into the panel to cause the panel to resonate to radiate an acoustic output.

The transducer (9) is driven by a signal amplifier (10), e.g. an audio amplifier, connected to the transducer by conductors (28). Amplifier loading and power requirements can be entirely normal, similar to conventional cone type speakers, sensitivity being of the order of 86 - 88dB/watt under room loaded conditions.

10 Amplifier load impedance is largely resistive at 6 ohms, power handling 20-80 watts. Where the panel core and/or skins are of metal, they may be made to act as a heat sink for the transducer to remove heat from the motor coil of the transducer and thus improve power handling.

15 Figures 2a and 2b are partial typical cross-sections through the loudspeaker (81) of Figure 1. Figure 2a shows that the frame (1), surround (3) and panel (2) are connected together by respective adhesive-bonded joints (20). Suitable materials for the frame include lightweight

20 framing, e.g. picture framing of extruded metal e.g. aluminium alloy or plastics. Suitable surround materials include resilient materials such as foam rubber and foam plastics. Suitable adhesives for the joints (20) include epoxy, acrylic and cyano-acrylate etc. adhesives.

25 Figure 2b illustrates, to an enlarged scale, that the panel (2) is a rigid lightweight panel having a core (22) e.g. of a rigid plastics foam (97) e.g. cross linked polyvinylchloride or a cellular matrix (98) i.e. a

honeycomb matrix of metal foil, plastics or the like, with the cells extending transversely to the plane of the panel, and enclosed by opposed skins (21) e.g. of paper, card, plastics or metal foil or sheet. Where the skins are of
5 plastics, they may be reinforced with fibres e.g. of carbon, glass, Kevlar (RTM) or the like in a manner known per se to increase their modulus.

Envisaged skin layer materials and reinforcements thus include carbon, glass, Kevlar (RTM), Nomex (RTM) i.e.
10 aramid etc. fibres in various lays and weaves, as well as paper, bonded paper laminates, melamine, and various synthetic plastics films of high modulus, such as Mylar (RTM), Kaptan (RTM), polycarbonate, phenolic, polyester or related plastics, and fibre reinforced plastics, etc. and
15 metal sheet or foil. Investigation of the Vectra grade of liquid crystal polymer thermoplastics shows that they may be useful for the injection moulding of ultra thin skins or shells of smaller size, say up to around 30cm diameter. This material self forms an orientated crystal structure in
20 the direction of injection, a preferred orientation for the good propagation of treble energy from the driving point to the panel perimeter.

Additional such moulding for this and other thermoplastics allows for the mould tooling to carry
25 location and registration features such as grooves or rings for the accurate location of transducer parts e.g. the motor coil, and the magnet suspension. Additional with some weaker core materials it is calculated that it would

be advantageous to increase the skin thickness locally e.g. in an area or annulus up to 150% of the transducer diameter, to reinforce that area and beneficially couple vibration energy into the panel. High frequency response will be improved with the softer foam materials by this means.

Envisaged core layer materials include fabricated honeycombs or corrugations of aluminium alloy sheet or foil, or Kevlar (RTM), Nomex (RTM), plain or bonded papers, and various synthetic plastics films, as well as expanded or foamed plastics or pulp materials, even aerogel metals if of suitably low density. Some suitable core layer materials effectively exhibit usable self-skinning in their manufacture and/or otherwise have enough inherent stiffness for use without lamination between skin layers. A high performance cellular core material is known under the trade name 'Rohacell' which may be suitable as a radiator panel and which is without skins. In practical terms, the aim is for an overall lightness and stiffness suited to a particular purpose, specifically including optimising contributions from core and skin layers and transitions between them.

Several of the preferred formulations for the panel employ metal and metal alloy skins, or alternatively a carbon fibre reinforcement. Both of these, and also designs with an alloy Aerogel or metal honeycomb core, will have substantial radio frequency screening properties which should be important in several EMC applications.

Conventional panel or cone type speakers have no inherent EMC screening capability.

In addition the preferred form of piezo and electro dynamic transducers have negligible electromagnetic radiation or stray magnet fields. Conventional speakers have a large magnetic field, up to 1 metre distant unless specific compensation counter measures are taken.

Where it is important to maintain the screening in an application, electrical connection can be made to the conductive parts of an appropriate DML panel or an electrically conductive foam or similar interface may be used for the edge mounting.

The suspension (3) may damp the edges of the panel (2) to prevent excessive edge movement of the panel. Additionally or alternatively, further damping may be applied, e.g. as patches, bonded to the panel in selected positions to damp excessive movement to distribute resonance equally over the panel. The patches may be of bitumen-based material, as commonly used in conventional loudspeaker enclosures or may be of a resilient or rigid polymeric sheet material. Some materials, notably paper and card, and some cores may be self-damping. Where desired, the damping may be increased in the construction of the panels by employing resiliently setting, rather than rigid setting adhesives.

Effective said selective damping includes specific application to the panel including its sheet material of means permanently associated therewith. Edges and corners

can be particularly significant for dominant and less dispersed low frequency vibration modes of panels hereof. Edge-wise fixing of damping means can usefully lead to a panel with its said sheet material fully framed, though
5 their corners can often be relatively free, say for desired extension to lower frequency operation. Attachment can be by adhesive or self-adhesive materials. Other forms of useful damping, particularly in terms of more subtle effects and/or mid- and higher frequencies can be by way of
10 suitable mass or masses affixed to the sheet material at predetermined effective medial localised positions of said area.

An acoustic panel as described above is bi-directional. The sound energy from the back is not
15 strongly phase related to that from the front. Consequently there is the benefit of overall summation of acoustic power in the room, sound energy of uniform frequency distribution, reduced reflective and standing wave effects and with the advantage of superior
20 reproduction of the natural space and ambience in the reproduced sound recordings.

While the radiation from the acoustic panel is largely non-directional, the percentage of phase related information increases off axis. For improved focus for the
25 phantom stereo image, placement of the speakers, like pictures, at the usual standing person height, confers the benefit of a moderate off-axis placement for the normally seated listener optimising the stereo effect. Likewise the

triangular left/right geometry with respect to the listener provides a further angular component. Good stereo is thus obtainable.

There is a further advantage for a group of listeners compared with conventional speaker reproduction. The intrinsically dispersed nature of acoustic panel sound radiation gives it a sound volume which does not obey the inverse square law for distance for an equivalent point source. Because the intensity fall-off with distance is much less than predicted by inverse square law then consequently for off-centre and poorly placed listeners the intensity field for the panel speaker promotes a superior stereo effect compared to conventional speakers. This is because the off-centre placed listener does not suffer the doubled problem due to proximity to the nearer speaker; firstly the excessive increase in loudness from the nearer speaker, and then the corresponding decrease in loudness from the further loudspeaker.

There is also the advantage of a flat, lightweight panel-form speaker, visually attractive, of good sound quality and requiring only one transducer and no crossover for a full range sound from each panel diaphragm.

Figure 3 illustrates packaging incorporating the loudspeaker technology of Figures 1 and 2. As shown in Figure 3, the packaging is in the form of a box (111) having a hinged lid (139), the box, or at least part of it being made from a composite comprising a core of foamed plastics sandwiched between sheets of craft board to form

a panel as shown in Figure 2, such that the box comprises a rigid, lightweight distributed mode acoustic radiator as described with reference to Figures 1 and 2.

In the present case, the rear panel (140) of the box
5 is used to form a distributed mode radiator loudspeaker (81), although any one of the panels making up the sides of the box would be suitable if suitably constructed. An alternative placement for the transducer (9) is shown in dotted lines.

10 A piezo transducer (9) as shown in Figure 4 is attached to the inner face of the rear panel (140) of the box and is driven by a sound generator/amplifier/battery unit (112) also mounted on the rear panel. The unit (112) is controlled by a switch formed integrally with a hinge
15 (53) by which the lid (139) is secured to the box, whereby the sound generator is activated when the lid is lifted.

In this arrangement the edge termination of the panel (2) is formed by the corners of the box so that no additional frame (1) or suspension (3) of the kind shown in
20 Figures 1 and 2 is required.

It will be appreciated that the packaging need not be of the shape shown in the drawing, and could, for example, be shaped according to the requirements of the contents. Thus the packaging might be shaped to enclose a compact
25 disc or the like and may be arranged to provide an audio preview of the contents of the compact disc or to provide other information relating thereto. As another example, the packaging may form a musical box. As a further example

the packaging may be arranged to give audio instructions concerning the contents.

Figure 4 shows a transducer (9) for a distributed mode panel (2) in the form of a crystalline disc-like piezo bender (27) mounted on a disc (118), e.g. of brass, which is bonded to a face of the panel (2), e.g. by an adhesive bond (20). In operation an acoustic signal applied to the transducer (9) via leads (28) will cause the piezo disc (27) to bend and thus locally resiliently deform the panel (2) to launch bending waves into the panel.



THIS SHEET HAS BEEN
REPLACED

WO 97/09855

PCT/GB96/02146

13


CLAIMS

1. Packaging comprising a board component, characterised in that the board is a distributed mode acoustic radiator having a transducer mounted wholly and exclusively on the
5 radiator to vibrate the radiator to cause it to resonate.
2. Packaging according to claim 1, characterised in that the board is a panel having a cellular core sandwiched between skin layers.
3. Packaging according to claim 1 or claim 2,
10 characterised in that the board comprises a core of foamed plastics sandwiched between sheets of craft board.
4. Packaging according to claim 1 or claim 2, characterised in that the transducer is a piezo-electric bender.
- 15 5. Packaging according to claim 4, characterised in that the bender is crystalline.
6. Packaging according to any preceding claims, characterised in that the board forms one side of a box.
7. Packaging according to claim 6, characterised in that
20 the box has a lid, and characterised by means associated with the lid for triggering actuation of the transducer on movement of the lid relative to the box.
8. Packaging according to claim 7, characterised by a signal generator, an amplifier and an electric battery.

This Sheet Has Been Replaced



1/4

*Fig. 1*

2/4




Fig. 2a




Fig. 2b

3/4




Fig.3

4/4




Fig. 4

and an electro-mechanical drive means coupled to the panel which serves to excite a multi-modal resonance in the radiator panel in response to an electrical input within a working frequency band for the loudspeaker.

5 US-A-4,607,747 of STEINER discloses packaging comprising means for generating a signal or melody when opening the packaging. A resiliently mounted signal generator is disclosed.

DISCLOSURE OF INVENTION

10 Embodiments of the present invention use members of nature, structure and configuration achievable generally and/or specifically by implementing teachings of our co-pending PCT publication No. WO97/09842 of even date herewith. Such members thus have capability to sustain and
15 propagate input vibrational energy by bending waves in operative area(s) extending transversely of thickness often but not necessarily to edges of the member(s); are configured with or without anisotropy of bending stiffness to have resonant mode vibration components distributed over
20 said area(s) beneficially for acoustic coupling with ambient air; and have predetermined preferential locations or sites within said area for transducer means, particularly operationally active or moving part(s) thereof effective in relation to acoustic vibrational activity in
25 said area(s) and signals, usually electrical, corresponding to acoustic content of such vibrational activity. Uses are envisaged in co-pending International publication No. WO97/09842 for such members as or in "passive" acoustic

devices without transducer means, such as for reverberation or for acoustic filtering or for acoustically "voicing" a space or room; and as or in "active" acoustic devices with transducer means, such as in a remarkably wide range of
5 sources of sound or loudspeakers when supplied with input signals to be converted to said sound, or in such as microphones when exposed to sound to be converted into other signals.

This invention is particularly concerned with
10 packaging incorporating acoustic devices e.g. in the form of loudspeakers. The term 'packaging' is intended to encompass containers generally whether or not they are disposable.

Members as above are herein called distributed mode
15 radiators and are intended to be characterised as in the above PCT application and/or otherwise as specifically provided herein.

The invention is packaging comprising a sound generator, characterised by a board component forming a
20 part of the packaging and acting as a member having capability to sustain and propagate input vibrational energy by bending waves in at least one operative area extending transversely of thickness to have resonant mode vibration components distributed over said at least one
25 area and have predetermined preferential locations or sites within said area for transducer means and having a transducer mounted wholly and exclusively on said member at one of said locations or sites to vibrate the member to

cause it to resonate forming an acoustic radiator which provides an acoustic output when resonating. The member may comprise a cellular core sandwiched between skin
5 layers. The member may comprise a core of foamed plastics sandwiched between sheets of craft board. The transducer may be a piezo-electric bender, and the bender may be crystalline. The member may form one side of a box. The box may have a lid, and means associated with the lid for
10 triggering actuation of the transducer on movement of the lid relative to the box. The packaging may comprise a signal generator, an amplifier and an electric battery to drive the transducer.

BRIEF DESCRIPTION OF DRAWINGS

The invention is diagrammatically illustrated, by way of example, in the accompanying drawings, in which:-

Figure 1 is a diagram showing a distributed-mode
5 loudspeaker as described and claimed in our co-pending International publication No. WO97/09842;

Figure 2a is a partial section on the line A-A of Figure 1;

Figure 2b is an enlarged cross-section through a
10 distributed mode radiator of the kind shown in Figure 2a and showing two alternative constructions;

Figure 3 is a perspective diagram of an embodiment of packaging, and

Figure 4 is a perspective view of a transducer.

15

BEST MODES FOR CARRYING OUT THE INVENTION

Referring to Figure 1 of the drawings, there is shown a panel-form loudspeaker (81) of the kind described and claimed in our co-pending International publication No. WO97/09842 of even date herewith comprising a rectangular
5 frame (1) carrying a resilient suspension (3) round its inner periphery which supports a distributed mode sound radiating panel (2). A transducer (9) e.g as described in detail with reference to our co-pending International publication Nos. WO97/09859, WO97/09861, WO97/09858 of even
10 date herewith, is mounted wholly and exclusively on or in the panel (2) at a predetermined location defined by dimensions x and y , the position of which location is calculated as described in our co-pending International

publication No. WO97/09842 of even date herewith, to launch bending waves into the panel to cause the panel to resonate to radiate an acoustic output.

The transducer (9) is driven by a signal amplifier (10), e.g. an audio amplifier, connected to the transducer by conductors (28). Amplifier loading and power requirements can be entirely normal, similar to conventional cone type speakers, sensitivity being of the order of 86 - 88dB/watt under room loaded conditions. Amplifier load impedance is largely resistive at 6 ohms, power handling 20-80 watts. Where the panel core and/or skins are of metal, they may be made to act as a heat sink for the transducer to remove heat from the motor coil of the transducer and thus improve power handling.

Figures 2a and 2b are partial typical cross-sections through the loudspeaker (81) of Figure 1. Figure 2a shows that the frame (1), surround (3) and panel (2) are connected together by respective adhesive-bonded joints (20). Suitable materials for the frame include lightweight framing, e.g. picture framing of extruded metal e.g. aluminium alloy or plastics. Suitable surround materials include resilient materials such as foam rubber and foam plastics. Suitable adhesives for the joints (20) include epoxy, acrylic and cyano-acrylate etc. adhesives.

Figure 2b illustrates, to an enlarged scale, that the panel (2) is a rigid lightweight panel having a core (22) e.g. of a rigid plastics foam (97) e.g. cross linked polyvinylchloride or a cellular matrix (98) i.e. a

CLAIMS

1. Packaging (111) comprising a sound generator, characterised by a board component (2) forming a part of the packaging and acting as a member (2) having capability
5 to sustain and propagate input vibrational energy by bending waves in at least one operative area extending transversely of thickness to have resonant mode vibration components distributed over said at least one area and have predetermined preferential locations or sites within said
10 area for transducer means and having a transducer (9) mounted wholly and exclusively on said member at one of said locations or sites to vibrate the member to cause it to resonate forming an acoustic radiator which provides an acoustic output when resonating.
- 15 2. Packaging according to claim 1, characterised in that the member (2) comprises a cellular core (22) sandwiched between skin layers (21).
3. Packaging according to claim 2, characterised in that the member (2) comprises a core (22) of foamed plastics
20 (97) sandwiched between sheets of craft board (21).
4. Packaging according to any one of claims 1 to 3, characterised in that the transducer (19) is a piezo-electric bender.
5. Packaging according to claim 4, characterised in that
25 the bender (9) is crystalline.
6. Packaging according to any preceding claims, characterised in that the member (2) forms one side of a box (111).

7. Packaging according to claim 6, characterised in that the box (111) has a lid (139), and by means (53) associated with the lid for triggering actuation of the transducer (9) on movement of the lid relative to the box.
- 5 8. Packaging according to claim 7, characterised by a signal generator, an amplifier and an electric battery (112) to drive the transducer.