

Description

Technical Field

The present invention relates generally to electrically conductive body straps and more particularly to electrically conductive body straps which are adjustable.

Background Art

The buildup of electrostatic charges and their subsequent discharge is a significant problem in certain industries. Individuals working in an everyday work environment commonly may develop thousands of volts of electrostatic charge potential by, as an example, walking across carpeting or moving dissimilar objects against each other. An individual, or object, so charged presents a severe hazard in certain environments. One example is an explosive environment where the danger is inherently obvious. Another example is the electronic integrated circuit (component) industry. The charged individual or object may discharge near or through an electrostatic sensitive electronic component. For example, an individual who is electrostatically charged may hold an electrostatic sensitive component and then lay the component on a surface, e.g., a grounded work surface, at a different potential from the individual. At the instant of contact, a potential difference of thousands of volts exists across the component, from the electrostatically charged individual to the grounded work surface. The current passing through or near, due to the electric field generated, may damage the component. The damage caused to the component may cause it to fail immediately or, worse, could degrade the operating characteristics or the reliability of the component. The result is either expensive rework or, worse, the existence of substandard or subreliable equipment in the field.

A device which is used to help control the electrostatic charge buildup on a person is a body strap or wrist strap to be worn by the individual. The body straps are conductive on the surface contacting the skin surface and provide for an electrical connection point. An electrical ground cord may then be connected to the strap connecting the strap to an electrical ground potential, preferably through a predetermined limiting resistance usually built into the connector or the cord itself. So connected, such a body strap operates by draining any accumulated electrostatic charge on the individual to ground before the electrostatic charge buildup reaches dangerous levels.

One prior art body strap is described in U.S. Patent No. 4,398,277, Christiansen et al, Conductive Elastomeric Body Strap, which is hereby incor-

porated by reference. Christiansen et al describes a body strap which is constructed from a band of fabric formed into a closed loop to encircle a body part, e.g., wrist, to which it is to be connected. The fabric is electrically conductive on the interior surface of the closed loop contacting the skin. A mechanical connection mechanism holds the loop of fabric in a fixed predetermined size. An electrical connection mechanism provides for an electrical connection between the conductive inner surface of the fabric to an electrical grounding cord which may be attached to the strap. The fabric is elastomeric to enable the body strap to expand to slip over the hand and still be snug around the wrist.

In the body strap described in Christiansen et al, the opposite ends of the fabric are permanently secured in the mechanical connector. The body of the connector has projections which grip the fabric and hold the fabric in the connector when the cover is secured. Thus, the resultant body strap formed is a fixed closed loop size. Since the fabric has a limit on the degree of its elastic nature, a range of sizes of closed loops for the body strap must be provided. This results in the necessity of stocking a plurality of differing sizes of body straps. Further, the elastomeric characteristics of the fabric generally means a fixed "life" of use of the fabric before its elastomeric or electroconductivity characteristics begin to break down. Since the fabric is secured in the connector at the factory, the replacement of the fabric requires replacement of the entire body strap.

The Charge-Guard 2200 series of static control wrist straps manufactured by Minnesota Mining and Manufacturing Company, St. Paul, Minnesota and marketed by Static Control Systems/3m, Austin, Texas is constructed generally as described in Christiansen et al (Charge-Guard is a registered trademark of Minnesota Mining and Manufacturing Company, St. Paul, Minnesota). In the Charge-Guard static control wrist straps, the ends of the projections 32, in Christiansen et al, are sonically welded after the fabric is in place to "mushroom" the ends of the projections in order to ensure that the fabric is secured in the connector.

U.S. Patent No. 4,577,256, Breidegam, Woven Stretchable Grounding Strap, describes a wrist strap designed to be used to control electrostatic charge accumulations and showing the features of the precharacterising portion of claim 1. The Breidegam strap has a clasp which allows its size to be adjusted. The adjustable clasp avoids the need to manufacture two or more models of the strap for different sized wrists. This does require that the strap be individually adjusted to fit snugly around the wrist of the individual wearer. If inadvertently or intentionally maladjusted, proper electro-

static protection may not be achieved. In the Breidegam strap, one end of the fabric is permanently secured into the clasp and held by plate and a rivet. Thus, one end of the fabric is fixed at the factory for the entire life of the strap. The second end of the fabric is engaged in the clasp by a pivotally mounted gate which when closed "jams" the fabric holding it in place, optionally with teeth to help the securing of the fabric. Typically, a pivotally mounted "jam" or "wedge" as is described in Breidegam is referred to as an "over-center" device. These devices operate by wedging the fabric between the jam member and a reaction member by using an eccentric pivot with a relatively long jam operating lever to gain the necessary leverage for the jam to work. One problem in a strap as described in Breidegam is that it does not allow for full 360 degree electrical contact with the skin and the fabric is electrically only connected at one end. Since electrical contact is only provided to the external ground cord from the one fixed end of the fabric, any charge contacting the inner surface of the fabric must travel around the strap in one direction only until reaching the fixed end. This requires, in some instances, a charge must follow only one path to travel almost entirely around the fabric before being connected to a ground strap. Since the electrical conductivity of the fabric, due to its elasticity, is typically the weakest link in a wrist strap grounding system, along with the fabric to skin contact, such one way only conductivity is a serious problem. Another problem with the Breidegam strap is that the pivotally mounted gate does not lend itself to economical manufacture. Because of the forces involved, the pivot points are required to be quite sturdily built.

Summary of the Invention

According to the present invention there is provided an adjustable, conductive body strap, having a strip of material having a first end and a second end, said strip of material being electrically conductive on at least one surface, being elastomerically extensible in its longitudinal direction, and being of at least a length to enable said strip of material to encircle a body part; and a mechanical connector receiving said first end and said second end of said strip of material to form a closed loop with said strip of material with said at least one surface toward the interior of said closed loop, said mechanical connector having a first part receiving said first end of said strip of material and having a second part receiving said second end of said strip of material; characterized by said first part of said mechanical connector having a recess receiving said first end of said strip of material, said recess being formed with a plurality of spikes

upon which said strip of material is impaled and secured; said second part of said mechanical connector having a transverse bar or plate over or around which said second end of said strip of material is passed, said transverse bar or plate having a plurality of spikes upon which said strip of material may be impaled after said strip of material has been pulled tight around said body part, said second part of said mechanical connector further having a hinged cover for being secured over said transverse bar trapping said strip of material thereon; and electrical connection means coupled to said strip of material for making electrical contact with said at least one conductive surface and for providing a connection point for an electrical cable capable of connecting said conductive body strap to ground.

Brief Description of the Drawings

The foregoing advantages, construction and operation of the present invention will become more readily apparent from the following drawings and accompanying description in which:

Figure 1 illustrates an isometric view of the body strap of the present invention;

Figure 2 illustrates a closeup of the mechanical connector in a closed position;

Figure 3 illustrates a closeup of the mechanical connector in an open position;

Figure 4 illustrates a cutaway bottom view of the mechanical connector;

Figure 5 illustrates a cross-section of the mechanical connector in a closed position;

Figure 6 illustrates one embodiment of the spikes used in the mechanical connector;

Figure 7 illustrates another embodiment of the spikes used in the mechanical connector;

Figure 8 illustrates another embodiment of the spikes used in the mechanical connector;

Figure 9 illustrates an exploded isometric view of a mechanical connector used in an adjustable, conductive body strap;

Figure 10 illustrates a cross-section view of a mechanical connector of the adjustable, conductive body strap showing the mechanical connector in the closed position; and

Figure 11 illustrates an exploded view of the mechanical connector and adjustment mechanism of the adjustable, conductive body strap

Description of the Preferred Embodiments

The adjustable, electrically conductive body strap 10 is illustrated in Figure 1. The body strap 10 is formed into a closed loop designed to fit snugly around a portion of the body, e.g., a wrist or an ankle. The loop is formed by a strip of material

12 formed into a loop by connector 14. Connector 14 forms both the mechanical connection holding both ends of the strip of material 12 and the electrical connection mechanism providing a point for external connection of the body strap 10 to a ground potential. The interior surface 16 of the strip of material 12 is electrically conductive and should intimately contact the skin of the individual wearer of the body strap 10 when it is in position. Thus, electrostatic charges accumulating on the person of the wearer can be transported from the skin of the wearer to the conductive interior surface 16 of the body strap 10 transported to connector 14 and made available for conduction to ground through provision for connecting a grounding cord such as cord connector 18. Strip of material 12 may be formed of any suitable elastomeric electrically conductive material such as a fabric to form the band portion of the body strap 10. In a preferred embodiment, strip of material 12 is a knit fabric containing both elastomeric and electrically conductive fibers as described in Christiansen et al. Optionally, however, strip of material 12 could also be constructed from a stretch weave material such as is described in Breidegam. A first end 20 of the strip of material 12 is mechanically secured in a first part 22 of connector 14. The second end 24 of the strip of material 12 is adjustably secured in a second part 26 of connector 14.

The details of connector 14 are more readily illustrated in Figures 2 and 3. The first end 20 of the strip of material 12 is secured in the first part 22 of the connector 14. Secured in this manner the first end 20 is semi-permanently secured in that only disassembly of connector 14 can release first end 20 of the strip of material 12 from the connector 14. It is anticipated that body strap 10 can be shipped from the factory with the first end 20 of the strip of material 12 semi-permanently secured in the first part 22 of connector 14. This can be shown in better detail in Figure 4 where the first end 20 and the strip of material 12 is formed into a recess 28 of the first part 22 of the connector 14. There the strip of material 12 is impaled upon a plurality of spikes 30 designed to secure first end 20 of the strip of material 12 within the connector 14 when metallic back plate 32 which is secured in the connector 14 through a stud 34 and its cord connector 18 forming a snap connector. Stud 34 as well as cord connector 18 are metallic allowing for electrical conductivity from the interior surface 16 of the strip of material 12 to cord connector 18 and, of course, subsequently by external cord (not shown) to a ground potential. Metallic back plate 32 also preferably contacts the interior surface 16 of the second end 24 of the strip of material 12 to provide for full 360 degree electrical conductivity around body strap 10.

Again referring to Figures 2 and 3, the second end 24 of the strip of material 12 is placed in the recess 36 in the second part 26 of connector 14. The second part 26 of connector 14 contains a transverse bar 38 upon which are mounted a plurality of spikes 40 extending outwardly from the transverse bar 38. The second end 24 of the strip of material 12 is passed under transverse bar 38 and pulled up on the far side of transverse bar 38 until the strip of material 12 is securely tightened around the body part with which it is to be utilized. When the strip of material 12 is suitably tight, the second end 24 of the strip of material 12 is then folded back over the top of transverse bar 38 and impaled upon spikes 40. Hinged cover 42 connected to the second part 26 of connector 14 by hinge 44 along one side, may then be closed over the top of the second end 24 of the strip material 12 and secured with a hook 46 securing hinged cover 42 in place and in turn securing the second end 24 of the strip of material 12 in the connector 14. The second end 24 of the strip of material 12 may be trimmed after the strip of material 12 is impaled upon spikes 40 and either before or after hinged cover 42 is secured in a closed position as illustrated in Figure 2. Such trimming will prevent the existence of an electrically conductive surface on the exterior of the body strap 10. Preferably, hinged cover 42 contains a plurality of recesses 48 which cooperate with and receive the tips of spikes 40 when hinge cover 42 is in a closed position. The receiving of the tip of spikes 40 in recesses 48 will help prevent spikes 40 from bending, and subsequent release of the strip of material 12 from connector 14. Also preferably, hinged cover 42 has transverse ridges so on one or both sides of transverse bar 38 to force the strip of material 12 into more intimate electrical contact with back plate 32 as can be illustrated from the cross-sectional view of Figure 5. Figure 5 also illustrates the impaling of the strip of material 12 upon spikes 30 and 40 as well as the electrical contact between back plate 32 and both the first end 20 and the second end 24 of the strip of material 12 forming full 360 degree electrical continuity around body strap 10. Figure 5 illustrates the second end 24 of the strip of material 12 having been trimmed with a short portion of the second end 24 extending beyond the edge of hinged cover 42. Optionally, and preferably, second end 24 of the strip of material 12 will be trimmed at least flush with the edge of hinged cover 42 so that no electrically conductive surface is present on the exterior surface of body strap 10. Also preferably, the second end 24 of the strip of material 12 is not trimmed so short that some material is left to allow for a small amount of unraveling. In a preferred embodiment, the material forming connector 14 except for back plate 32,

stud 34 and cord connector 18, is constructed from a plastic material preferably one that is static dissipative. In general, a material is static dissipative if it has a surface resistivity of between 10^8 and 10^{14} ohms per square. Examples of material which could be utilized and which are static dissipative include hygroscopic nylon and carbon loaded polypropylene. As can be seen from examining Figures 2, 3 and 5 the second end 24 of the strip of material 12 is secured in connector 14 not only by spikes 40 and hinged cover 42 but also by the tortuous path in which the fabric is forced to take when passed first under and then back over transverse bar 38.

The hinged cover 42 holds the fabric 12 onto spikes 40. Further, transverse ridges 50 assist in holding the fabric 12 onto spikes 40 and help form the tortuous path.

Figures 6, 7 and 8 are cross-sections illustrating various optional profiles of spikes 40 taken from a side view. In Figure 6, spike 40A is of conical shape which is probably the most economical to manufacture and will provide an adequate job of securing strip of material 12 for most purposes. However, severe loading upon spike 40A will tend to lead toward the strip of material 12 rising up toward the end of spike 40A which results in larger lateral forces against spike 40 than otherwise would be encountered. Accordingly, spike 40C is illustrated in Figure 8 is preferred. Spike 40C is also of conical shape but has a zero draft, i.e., vertical side, facing the extreme second end 24 of the strip of material 12. Spike 40C with one zero draft side is still economically manufacturable and since the side of the spike 40C which is loaded is vertical strip of material 12 will not tend to ride up toward the tip of the spike 40C and, thus, the lateral force on 40C will not be concentrated at its tip but rather more evenly over the entire length of spike 40C. This results in lower lateral forces on the tip of spike 40C than might otherwise be achieved with spike 40A as illustrated in Figure 6. If still more lateral loading resistance is desired, then spike 40B as illustrated in Figure 7 may be utilized. Spike 40B is angled toward the extreme end 24 of strip of material 12, in this case, 45 degrees, so that any lateral force on spike 40B will result in the strip of material 12 being forced more deeply onto to spike 40B and, thus, a more secure environment is provided. However, spike 40B probably is more difficult to manufacture.

Figures 9 and 10 illustrate another embodiment of the mechanical connector 14A. Mechanical connector 14A illustrated in Figures 9 and 10 is similar to mechanical connector 14 illustrated in Figures 1 through 5. The path of the securing of the strip of material 12 differs between the two embodiments. With mechanical connector 14 as illustrated in Fig-

ures 1 through 5 strip of material 12 is passed first under transverse bar 38 and back over transverse bar 38 whereupon it is impaled upon spikes 40 by hinged cover 42. Mechanical connector 14A, illustrated in Figures 9 and 10, has a plate 52 in place of transverse bar 38. Strip of material 12 passes over plate 52 where it is impaled upon spikes 40 and secured with hinged cover 42. The second end 24 of strip of material 12 then passes from connector 14A adjacent to hinged cover 42 for which a space is provided next to the first part 22 of mechanical connector 14A. All other aspects of mechanical connector 14A are identical to corresponding aspects of mechanical connector 14. Note that in the mechanical connector 14A the inner surface 16 of the strip of material 12 is forced by transverse ridges 50 into contact with the metallic electrically conductive second cover, back plate, 32 providing full 360 degree electrical continuity and skin contact around the interior of the adjustable conductive body strap.

Optionally, mechanical connector 14A has an element, or bar, 54 positioned adjacent hinged cover 42 above the path of the second end 24 of the strip of material 12 before the strip of material 12 passes over plate 52. Element 54 is positioned transverse to strip of material 12 and provides a convenient fulcrum around which the strip of material is pulled tight around the body part (not shown) and before the strip of material 12 is secured over spikes 40 in plate 52.

While Figures 1-10 have illustrated and described adjustable, electrically conductive body straps in general, and have described, in particular, a detailed example of two ways in which an adjustable conductive body strap may be constructed, Figure 11 illustrates an adjustable, conductive body strap 152.

A mechanical connector 154 is formed from an outer piece 156 and an inner piece 158. The outer piece 156 and the inner piece 158 are secured together by means of a snap connector 160 and stud 162. Since outer piece 156 is on the exposed exterior surface of the adjustable, conductive body strap 152, outer piece 156 is constructed from an electrically insulative material such as a plastic material, and preferably from nylon or static dissipative plastic. Since inner piece 158 is on the interior surface of the adjustable conductive body strap 152, inner piece 158 is constructed from an electrically conductive material, such as stainless steel or another metal. Inner piece 158 contacts the skin of the wearer and provides an additional electrical contact point from the adjustable conductive body strap 152 to the wearer. The first end 20 of the strip of material 12 is received into one side of mechanical connector 154 from a first direction by a recess formed by the joining of outer piece 156

and inner piece 158. Having been so received the first end 20 of strip of material 12 is held in place, alternative, by stud 162, by one or more spikes similar to spikes 30 illustrated in Figure 4 (not shown), or both. Secured in this manner, the inner conductive surface 16 of the strip of material 12 contacts the electrically conductive inner piece 158. A slot 164 on the other side of inner piece 158 allows for second end 24 of the strip of material to pass, first over and then under inner piece 158 with inner piece 158 making electrical contact with the electrically conductive surface 16 of the strip of material 12. The second end 24 of strip of material 12 is then secured back to itself by an eight-ring 166. Since the eight-ring 166 is exposed to the exterior of the adjustable, conductive body strap 152, it is preferred that it be constructed of an electrically insulative material, again such as a plastic material, preferably nylon or static dissipative plastic. The second end 24 of the strip of material 12 is wrapped around the central member of eight-ring 166 and secured, by any suitable mechanism, such as stitching, to itself firmly securing the second end 24 of the strip of material 12 to the eight-ring 166. The strip of material 12, having been passed between the center leg and the two outer legs of eight-ring 166, then provides a readily readjustable mechanism whereby the user of the adjustable conductive body strap 152 may resize the adjustable conductive body strap 152 in a readily efficient manner. Since there are not free ends of the strip of material 12 exposed following the strip of material 12 being secured in mechanical connector 154, there is no danger of the electrically conductive surface 16 of the strip of material 12 being left exposed to the exterior of the adjustable conductive body strap 152. Snap 60 along with stud 62 form the electrical connection mechanism whereby an electrical ground cable may be connected to snap 160 and the adjustable conductive body strap 152 may be then connected to an electrical ground. Because inner piece 158 is electrically conductive and makes electrical contact to both the first end 20 and the electrically conductive surface 16 of the strip of material 12 near second end 24, dual parallel paths for the drainage of an accumulated electrostatic charge are provided. The adjustable, conductive body strap has full 360 degree electrical continuity and near full 360 degree electrical skin contact with the only exception being the portion between slot 164 and eight-ring 166 which is a reasonable tradeoff for the elimination of any exposure of the conductive surface 16 of strip material 12 and for the readily readjustable feature of eight-ring 166.

Claims

1. An adjustable, conductive body strap (10), having a strip of material (12) having a first end (20) and a second end (24), said strip of material (12) being electrically conductive on at least one surface, being elastomerically extensible in its longitudinal direction, and being of at least a length to enable said strip of material (12) to encircle a body part; and a mechanical connector (14) receiving said first end (20) and said second end (24) of said strip of material (12) to form a closed loop with said strip of material (12) with said at least one surface (16) toward the interior of said closed loop, said mechanical connector (14) having a first part receiving said first end (20) of said strip of material (12) and having a second part receiving said second end (24) of said strip of material (12); characterized by said first part of said mechanical connector (14) having a recess (28) receiving said first end (20) of said strip of material (12), said recess (28) being formed with a plurality of spikes (30) upon which said strip of material (12) is impaled and secured; said second part of said mechanical connector (14) having a transverse bar (38) or plate (52) over or around which said second end (24) of said strip of material (12) is passed, said transverse bar (38) or plate (52) having a plurality of spikes (40) upon which said strip of material (12) may be impaled after said strip of material (12) has been pulled tight around said body part, said second part of said mechanical connector (14) further having a hinged cover (42) for being secured over said transverse bar (38) trapping said strip of material (12) thereon; and electrical connection means (18) coupled to said strip of material (12) for making electrical contact with said at least one conductive surface (16) and for providing a connection point for an electrical cable capable of connecting said conductive body strap (10) to ground.
2. An adjustable, conductive body strap (10) as in claim 1 wherein said transverse bar (38) or plate (52) is a transverse bar (38) and wherein said strip of material (12) passes firstly interior of said transverse bar (38) and secondly exterior of said transverse bar (38).
3. An adjustable, conductive body strap (10) as in claim 2 wherein said hinged cover (42) is releasably secured over said spikes (40).
4. An adjustable, conductive body strap (10) as in claim 3 wherein said hinged cover (42) has a



and inner piece 158. Having been so received the first end 20 of strip of material 12 is held in place, alternative, by stud 162, by one or more spikes similar to spikes 30 illustrated in Figure 4 (not shown), or both. Secured in this manner, the inner conductive surface 16 of the strip of material 12 contacts the electrically conductive inner piece 158. A slot 164 on the other side of inner piece 158 allows for second end 24 of the strip of material to pass, first over and then under inner piece 158 with inner piece 158 making electrical contact with the electrically conductive surface 16 of the strip of material 12. The second end 24 of strip of material 12 is then secured back to itself by an eight-ring 166. Since the eight-ring 166 is exposed to the exterior of the adjustable, conductive body strap 152, it is preferred that it be constructed of an electrically insulative material, again such as a plastic material, preferably nylon or static dissipative plastic. The second end 24 of the strip of material 12 is wrapped around the central member of eight-ring 166 and secured, by any suitable mechanism, such as stitching, to itself firmly securing the second end 24 of the strip of material 12 to the eight-ring 166. The strip of material 12, having been passed between the center leg and the two outer legs of eight-ring 166, then provides a readily readjustable mechanism whereby the user of the adjustable conductive body strap 152 may resize the adjustable conductive body strap 152 in a readily efficient manner. Since there are not free ends of the strip of material 12 exposed following the strip of material 12 being secured in mechanical connector 154, there is no danger of the electrically conductive surface 16 of the strip of material 12 being left exposed to the exterior of the adjustable conductive body strap 152. Snap 60 along with stud 62 form the electrical connection mechanism whereby an electrical ground cable may be connected to snap 160 and the adjustable conductive body strap 152 may be then connected to an electrical ground. Because inner piece 158 is electrically conductive and makes electrical contact to both the first end 20 and the electrically conductive surface 16 of the strip of material 12 near second end 24, dual parallel paths for the drainage of an accumulated electrostatic charge are provided. The adjustable, conductive body strap has full 360 degree electrical continuity and near full 360 degree electrical skin contact with the only exception being the portion between slot 164 and eight-ring 166 which is a reasonable tradeoff for the elimination of any exposure of the conductive surface 16 of strip material 12 and for the readily readjustable feature of eight-ring 166.

Claims

1. An adjustable, conductive body strap (10), having a strip of material (12) having a first end (20) and a second end (24), said strip of material (12) being electrically conductive on at least one surface, being elastomerically extensible in its longitudinal direction, and being of at least a length to enable said strip of material (12) to encircle a body part; and a mechanical connector (14) receiving said first end (20) and said second end (24) of said strip of material (12) to form a closed loop with said strip of material (12) with said at least one surface (16) toward the interior of said closed loop, said mechanical connector (14) having a first part receiving said first end (20) of said strip of material (12) and having a second part receiving said second end (24) of said strip of material (12); characterized by said first part of said mechanical connector (14) having a recess (28) receiving said first end (20) of said strip of material (12), said recess (28) being formed with a plurality of spikes (30) upon which said strip of material (12) is impaled and secured; said second part of said mechanical connector (14) having a transverse bar (38) or plate (52) over or around which said second end (24) of said strip of material (12) is passed, said transverse bar (38) or plate (52) having a plurality of spikes (40) upon which said strip of material (12) may be impaled after said strip of material (12) has been pulled tight around said body part, said second part of said mechanical connector (14) further having a hinged cover (42) for being secured over said transverse bar (38) trapping said strip of material (12) thereon; and electrical connection means (18) coupled to said strip of material (12) for making electrical contact with said at least one conductive surface (16) and for providing a connection point for an electrical cable capable of connecting said conductive body strap (10) to ground.
2. An adjustable, conductive body strap (10) as in claim 1 wherein said transverse bar (38) or plate (52) is a transverse bar (38) and wherein said strip of material (12) passes firstly interior of said transverse bar (38) and secondly exterior of said transverse bar (38).
3. An adjustable, conductive body strap (10) as in claim 2 wherein said hinged cover (42) is releasably secured over said spikes (40).
4. An adjustable, conductive body strap (10) as in claim 3 wherein said hinged cover (42) has a



plurality of recesses (28) receiving the tip of each of said spikes (40) mounted on said transverse bar (38).

5. An adjustable, conductive body strap (10) as in claim 3 wherein said spikes (40) mounted on said transverse bar (38) have a zero draft profile facing the direction toward said second end (24) of said strip of material (12).
6. An adjustable, conductive body strap (10) as in claim 3 wherein said spikes (40) mounted on said transverse bar (38) are angled toward said second end (24) of said strip of material (12).
7. An adjustable, conductive body strap (10) as in claim 3 wherein said hinged cover (42) of said mechanical connector (14) is hingably attached at one side.
8. An adjustable, conductive body strap (10) as in claim 3 wherein said hinged cover (42) is releasably secured in a closed position.
9. An adjustable, conductive body strap (10) as in claim 1 wherein said transverse bar (38) or plate (52) is a plate (52) over which said second end (24) of said strip of material (12) is passed.
10. An adjustable, conductive body strap (10) as in claim 9 wherein said hinged cover (42) is releasably secured over said spikes (40).
11. An adjustable, conductive body strap (10) as in claim 10 which further comprises a transverse element incorporated in said second part of said mechanical connector (14), said adjustment stop element positioned transversely to and above said strip of material (12) adjacent to said hinged cover (42).

Patentansprüche

1. Verstellbarer leitender Körperriemen (10), umfassend einen Materialstreifen (12) mit einem ersten Ende (20) und einem zweiten Ende (24), wobei der Materialstreifen (12) auf wenigstens einer Oberfläche elektrisch leitend ist, in seiner Längsrichtung gummielastisch dehnbar ist, und wenigstens so lang ist, daß der Materialstreifen (12) einen Körperteil umgeben kann; und ein mechanisches Verbindungselement (14), welches das erste Ende (20) und das zweite Ende (24) des Materialstreifens (12) aufnimmt, um mit dem Materialstreifen (12) einen geschlossenen Riemen zu bilden, wo die mindestens eine Oberfläche (16) auf der Innensei-

te des geschlossenen Riemens liegt, wobei das mechanische Verbindungselement (14) einen ersten Teil aufweist, der das erste Ende (20) des Materialstreifens (12) aufnimmt, und einen zweiten Teil, der das zweite Ende (24) des Materialstreifens (12) aufnimmt; dadurch gekennzeichnet, daß der erste Teil des mechanischen Verbindungselementes (14) eine Vertiefung (28) aufweist, die das erste Ende (20) des Materialstreifens (12) aufnimmt, wobei die Vertiefung (28) mit einer Vielzahl von Dornen (30) ausgebildet ist, auf denen der Materialstreifen (12) aufgespießt und befestigt ist; daß der zweite Teil des mechanischen Verbindungselementes (14) eine querverlaufende Stange (38) oder Platte (52) aufweist, über oder um die das zweite Ende (24) des Materialstreifens geführt ist, wobei die querverlaufende Stange (38) oder Platte (52) eine Vielzahl von Dornen (40) aufweist, auf die der Materialstreifen (12) aufgespießt werden kann, wenn der Materialstreifen (12) um das Körperteil festgezogen ist, wobei der zweite Teil des mechanischen Verbindungselementes (14) ferner einen Klappdeckel (42) aufweist, der über der querverlaufenden Stange (38) befestigt werden kann, die den Materialstreifen (12) festhält; und daß eine elektrische Verbindungseinrichtung (18) mit dem Materialstreifen (12) gekoppelt ist, um einen elektrischen Kontakt mit dieser mindestens einen leitenden Oberfläche (16) herzustellen, und um einen Anschlußpunkt für ein Stromkabel herzustellen, das den leitenden Körperriemen (10) an Erde legen kann.

2. Verstellbarer, leitender Körperriemen (10) nach Anspruch 1, dadurch gekennzeichnet, daß die querverlaufende Stange (38) oder Platte (52) eine Querstange (38) ist, und daß der Materialstreifen (12) zuerst auf der Innenseite der Querstange (38) und dann auf der Außenseite der Querstange (38) verläuft.
3. Verstellbarer, leitender Körperriemen (10) nach Anspruch 2, dadurch gekennzeichnet, daß der Klappdeckel (42) lösbar über den Dornen (40) befestigt ist.
4. Verstellbarer, leitender Körperriemen (10) nach Anspruch 3, dadurch gekennzeichnet, daß der Klappdeckel (42) eine Vielzahl von Vertiefungen (28) aufweist, die die Spitze von jedem der Dornen (40) aufnehmen, die auf der Querstange (38) befestigt sind.
5. Verstellbarer, leitender Körperriemen (10) nach Anspruch 3, dadurch gekennzeichnet, daß die auf der Querstange (38) befestigten Dornen



(40) in Richtung zu dem zweiten Ende (24) des Materialstreifens (12) im Profil keine Querschnittsverminderung zeigen.

6. Verstellbarer, leitender Körperriemen (10) nach Anspruch 3, dadurch gekennzeichnet, daß die Dornen (40), die auf der Querstange (38) befestigt sind, in Richtung zu dem zweiten Ende (24) des Materialstreifens (12) abgewinkelt sind. 5
7. Verstellbarer, leitender Körperriemen (10) nach Anspruch 3, dadurch gekennzeichnet, daß der Klappdeckel (42) des mechanischen Verbindungselementes (14) auf einer Seite angelenkt ist. 10
8. Verstellbarer, leitender Körperriemen (10) nach Anspruch 3, dadurch gekennzeichnet, daß der Klappdeckel (42) in einer geschlossenen Position lösbar befestigt ist. 15
9. Verstellbarer, leitender Körperriemen (10) nach Anspruch 1, dadurch gekennzeichnet, daß die quer verlaufende Stange (38) oder Platte (52) eine Platte (52) ist, über die das zweite Ende (24) des Materialstreifens (12) geführt ist. 20
10. Verstellbarer, leitender Körperriemen (10) nach Anspruch 9, dadurch gekennzeichnet, daß der Klappdeckel (42) lösbar über den Dornen (40) befestigt ist. 25
11. Verstellbarer, leitender Körperriemen (10) nach Anspruch 10, ferner umfassend ein querverlaufendes Element, welches in dem zweiten Teil des mechanischen Verbindungselementes (14) enthalten ist, wobei das Anschlagelement quer zu und oberhalb von dem Materialstreifen (12) im Bereich des Klappdeckels (42) angeordnet ist. 30

Revendications

1. Bandage corporel conducteur réglable (10), comprenant une bande de matière (12) qui présente une première extrémité (20) et une deuxième extrémité (24), la dite bande de matière (12) étant électriquement conductrice sur au moins une surface, étant élastiquement extensible dans sa direction longitudinale et ayant au moins une longueur qui permet à ladite bande de matière (12) d'encercler une partie du corps d'un utilisateur ; et un connecteur mécanique (14) recevant ladite première extrémité (20) et ladite deuxième extrémité (24) de la dite bande de matière (12) pour former une boucle fermée avec ladite bande de matière (12) de sorte que 45

ladite au moins une surface (16) est tournée vers l'intérieur de ladite boucle fermée, ledit connecteur mécanique (14) comportant une première partie qui reçoit ladite première extrémité (20) de ladite bande de matière (12) et comportant une deuxième partie qui reçoit ladite deuxième extrémité (24) de ladite bande de matière (12) ; caractérisé en ce que ladite première partie dudit connecteur mécanique (14) comprend un logement (28) de réception de ladite première extrémité (20) de ladite bande de matière (12), ledit logement (28) présentant une pluralité de pointes (30) sur lesquelles ladite bande de matière (12) est empalée et fixée ; ladite deuxième partie dudit connecteur mécanique (14) comprend une barrette (38) ou plaque (52) transversale sur ou autour de laquelle on fait passer ladite deuxième extrémité (24) de ladite bande de matière (12), ladite barrette (38) ou plaque (52) transversale présentant une pluralité de pointes (40) sur lesquelles ladite bande de matière (12) peut être empalée après traction et serrage de la dite bande de matière (12) autour de ladite partie de corps, ladite deuxième partie dudit connecteur mécanique (14) comportant en outre un couvercle pivotant (42) à fixer au-dessus de ladite barrette transversale (38) de manière à emprisonner ladite bande de matière (12) sur la barrette ; et des moyens de connexion électrique (18) sont associés à ladite bande de matière (12) pour effectuer un contact électrique avec ladite au moins une surface conductrice (16) et pour fournir un point de connexion à un câble électrique capable de relier le dit bandage corporel conducteur (10) à la terre électrique.

2. Bandage corporel conducteur réglable (10) suivant la revendication 1, dans lequel ladite barrette (38) ou plaque (52) transversale est une barrette transversale (38), et dans lequel ladite bande de matière (12) passe d'abord du côté intérieur de ladite barrette transversale (38) et ensuite du côté extérieur de ladite barrette transversale (38).

4. Bandage corporel conducteur réglable (10) suivant la revendication 2, dans lequel ledit couvercle pivotant (42) est fixé de façon séparable au-dessus desdites pointes (40).

4. Bandage corporel conducteur réglable (10) suivant la revendication 3, dans lequel ledit couvercle pivotant (42) comporte une pluralité de cavités (28) pour recevoir le bout de chacune desdites pointes (40) montées sur ladite barrette transversale (38).

5. Bandage corporel conducteur réglable (10) suivant la revendication 3, dans lequel lesdites pointes (40) montées sur ladite barrette transversale (38) ont un profil à dépouille nulle dans 55



la direction tournée vers ladite deuxième extrémité (24) de ladite bande de matière (12).

6. Bandage corporel conducteur réglable (10) suivant la revendication 3, dans lequel lesdites pointes (40) montées sur ladite barrette transversale (38) sont inclinées vers ladite deuxième extrémité (24) de ladite bande de matière (12). 5

7. Bandage corporel conducteur réglable (10) suivant la revendication 3, dans lequel ledit couvercle pivotant (42) dudit connecteur mécanique (14) est fixé sur un côté par une charnière. 10

8. Bandage corporel conducteur réglable (10) suivant la revendication 3, dans lequel ledit couvercle pivotant (42) est fixé de façon libérable dans une position fermée. 15

9. Bandage corporel conducteur réglable (10) suivant la revendication 1, dans lequel ladite barrette (38) ou plaque (52) transversale est une plaque (52) au-dessus de laquelle on fait passer ladite deuxième extrémité (24) de ladite bande de matière (12). 20

10. Bandage corporel conducteur réglable (10) suivant la revendication 9, dans lequel ledit couvercle pivotant (42) est fixé de façon séparable au-dessus desdites pointes (40). 25

11. Bandage corporel conducteur réglable (10) suivant la revendication 10, qui comprend en outre un élément transversal incorporé dans ladite deuxième partie dudit connecteur mécanique (14), ledit élément de butée de réglage étant placé transversalement et au-dessus de ladite bande de matière (12) et adjacent au dit couvercle pivotant (42). 30

35

40

45

50

55