(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/048190 A1

(51) International Patent Classification[7]: B63B 25/00, B60P 7/13

(21) International Application Number: PCT/EP2003/013297

(22) International Filing Date: 26 November 2003 (26.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 200201841 28 November 2002 (28.11.2002) DK

(71) Applicant and
(72) Inventor: **BRUUN, Kent, Roland, Hovmand** [DK/DK]; Strandgade 17, DK-5610 Assens (DK).


(74) Agent: **VAN WALSTIJN, B., Gerard, G.**; Walstijn Intellectual Property ApS, Parkovsvej 3, DK-2820 Gentofte (DK).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

[Continued on next page]

(54) Title: FASTENING DEVICE FOR SECURING A CONTAINER TO A SHIP



(57) Abstract: The invention relates to a fastening device (14) for establishing a self-adjusting fastening connection between at least two elements. The fastening device comprises a frame (15) having at least one opening and a connection (27) to one of said at least two elements. Further, it comprises a rod (18) with corrugations, said rod being movable through said at least one opening and it includes a connection to one of said at least two elements and a holding device (20) comprising at least two locking elements (20a, 20b), each locking element including at least one surface comprising dents/grooves partly or totally corresponding to said corrugations. Even further, at least said frame (15) or said holding device (20) comprises an at least partly tapered shape, and elastic means such as spring means (21) forcing said holding device (20) against said frame (15) and thereby said locking elements (20a, 20b) against each other.The invention also relates to a method of establishing a fastening connection between at least two elements with a fastening device, and use hereof.

WO 2004/048190 A1

162162

G00002

SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*

(48) Date of publication of this corrected version:
22 July 2004

(15) Information about Correction:
see PCT Gazette No. 30/2004 of 22 July 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.