

- 1 -

ACOUSTIC TRANSDUCER

Related Application

This application is based on and claims the benefit of the filing and priority dates of
5 Australian patent application no. 2016904446 filed 31 October 2016, the content of
which as filed is incorporated herein by reference in its entirety.

Field of the Invention

The present invention is generally related to an acoustic transducer, of particular but by
10 no means exclusive application as an underwater acoustic transducer.

Background to the Invention

Acoustic or sonar transducers are employed to conduct, for example, marine
geophysical surveys; they may be used as acoustic signal transmitters in sonobuoys,
15 as transmitters for communications buoys, or in towed arrays as active sources.

One type of such a transducer is referred to as a piezoelectric bender, because it
employs piezoelectric elements, typically of a ceramic material, to generate vibration.
In transducers of this kind, the piezoelectric ceramic is generally the most costly
20 component, and may amount to about 80% of the parts cost; it also usually contributes
significantly to the transducer's mass. Ideally it is therefore desirable to use the
smallest possible quantity of ceramic in a design, though the volume of ceramic
required to provide enough power handling capability imposes a lower limit to any such
paring or trimming of the ceramic components.

25 Figures 1A and 1B show schematically the configuration of such a known acoustic
transducer, in the form of a piezoelectric bender 10. Figure 1A is a top view (with
encapsulating waterproof overmoulding omitted for clarity), while figure 1B is a cross
sectional view through the centre of bender 10. These figures, it should be noted, are
30 not to scale. Bender 10 comprises two identical circular base plates 12, 14. Each
base plate 12, 14 has attached thereto a respective ceramic piezoelectric body 16, 18,
thereby forming a pair of active assemblies, each comprising a base plate and a
piezoelectric body. Bender 10 also includes an annular support structure 20 to which
base plates 12, 14 are attached, which flexes as base plates 12, 14 are driven to
35 vibrate about their respective equilibrium positions. (Support structure 20 would not
normally be visible in the view of figure 1A, but its inner periphery is shown in dashed
line to aid understanding.) In this example these components are circular, but in other

– 2 –

examples they may be elliptical or rectangular. All of these components are encapsulated in a waterproof overmoulding 22.

5 Base plates 12, 14 and support structure 20 define an internal cavity 24, which may be filled with air, some other gas, a liquid, or a liquid with compliant components. The piezoelectric body 16, 18 are driven electrically so that the active assemblies vibrate in phase and resonate at the same frequency.

10 US Patent No. 8,139,443 discloses an underwater sound projector system that includes an array of acoustic transducers of this general type.

Summary of the Invention

In a first broad aspect, the invention provides an acoustic transducer, comprising:

- 15 a support structure;
- an active assembly comprising a base plate supported by the support structure and a piezoelectric body supported by (and typically bonded to) the base plate; and
- a passive vibrator supported by the support structure and coupled via the support structure to the active assembly so that vibration of the active assembly drives the passive vibrator;
- 20 wherein the active assembly and the passive vibrator have the same resonant frequency.

25 The passive vibrator may be described as acting like a diaphragm. When the piezoelectric body is appropriately electrically driven, the active assembly and the passive vibrator radiate into the surrounding medium substantially equally.

In one embodiment, the piezoelectric body is a piezoelectric ceramic body. In another embodiment, the piezoelectric body is a single crystal body.

30 The base plate may be metallic. The passive vibrator may be metallic.

While the base plate and the passive vibrator may be of different (e.g. metallic) composition, in an embodiment, the base plate and the passive vibrator are of the same metallic composition, the passive vibrator differing in thickness from the base plate such that the active assembly and the passive vibrator have a common resonant frequency.

35

– 3 –

In an embodiment, the passive vibrator comprises a plate.

In one embodiment, the transducer is circular (that is, as seen in the view of, for example, figure 1A). In other embodiments, the transducer is elliptical or rectangular,
5 and still other shapes are contemplated.

A cavity defined by the active assembly, the vibrator and the support structure may be filled with a fluid, whether liquid or gas.

10 The support structure may be integral with the base plate and/or the passive vibrator.

In a second broad aspect, the invention provides a transducer array, comprising:
a plurality of acoustic transducers as claimed in any one of the preceding
claims;

15 wherein the plurality of acoustic transducers are spaced apart to utilise mutual interaction and thereby increase performance.

In a third broad aspect, the invention provides a method of manufacturing an acoustic transducer, the method comprising:

20 coupling an active assembly comprising a base plate and a piezoelectric body supported by the base plate to a passive vibrator by a support structure, such that vibration of the active assembly drives the passive vibrator at a common resonant frequency.

25 In an embodiment, the piezoelectric body is a piezoelectric ceramic body.

In another embodiment, the base plate and the passive vibrator are of the same metallic composition, the passive vibrator differing in thickness from the base plate such that the active assembly and the passive vibrator have a common resonant
30 frequency.

In one embodiment, the passive vibrator comprises a plate.

In certain embodiments, the transducer is circular, elliptical or rectangular.

35 In further embodiments, a cavity defined by the active assembly, the vibrator and the support structure is filled with a fluid.

– 4 –

In an embodiment, the support structure is integral with the base plate and/or the passive vibrator.

- 5 It should be noted that any of the various individual features of each of the above aspects of the invention, and any of the various individual features of the embodiments described herein including in the claims, can be combined as suitable and desired.

Brief Description of the Drawings

- 10 In order that the invention may be more clearly ascertained, embodiments will now be described, by way of example, with reference to the accompanying drawing, in which:

Figures 1A and 1B are schematic views of a piezoelectric bender according to the background art;

- 15 Figure 2 is a schematic cross-sectional view of a piezoelectric bender according to an embodiment of the present invention;

Figure 3 is a schematic cross-sectional view of the piezoelectric bender of figure 3 in use;

Figure 4 is a plot of transmit sensitivity (dB) versus frequency, for both a background art bender and a bender according to the embodiment of figure 2;

- 20 Figure 5 is a plot of efficiency (%) versus frequency (kHz), for both a background art bender and a bender according to the embodiment of figure 2; and

Figure 6 is a plot of source level versus drive voltage, for both a background art bender and a bender according to the embodiment of figure 2.

Detailed Description of Embodiments of the Invention

- 25 Figure 2 is a schematic cross sectional view (comparable to that of figure 1B) of an acoustic transducer in the form of a piezoelectric bender 30. Bender 30 comprises an active assembly comprising a circular base plate 32 and a piezoelectric body 34 bonded to the base plate 32. In this embodiment, base plate 32 is metallic (e.g. of steel) or made of a ceramic (e.g. alumina).

Bender 30 includes an annular support structure 36 or 'hinge' to which base plate 32 is attached, and a passive vibrator 38 in the form of a plate, also supported by the base plate 32 but on the opposite side of the base plate 32 relative to the active assembly.

- 35 These components are encapsulated in a waterproof overmoulding 40. In this embodiment the encapsulant is a polyurethane, but in other embodiment, the encapsulant is made of rubber or another low modulus material.

– 5 –

Bender 30 is, in use, activated by a power supply (not shown) that is coupled to the piezoelectric body 34. Such a power supply is typically a high voltage power supply that includes an amplifier having voltage, current or output power feedback to control its output.

The active assembly 32, 34 and the passive vibrator 38 are constructed to have the same resonant frequency, and are mechanically coupled via the support structure 36. Hence, when the piezoelectric body 34 and active assembly 32, 34 is driven, the passive vibrator 38—owing to its being coupled to active assembly 32, 34—is actuated by the moment induced in the support structure 36 and vibrates at the same resonant frequency.

The base plate 32, support structure 36 and passive vibrator 38 define an internal cavity 42, which may be filled with air, some other gas, a liquid, or a liquid with compliant components.

The physical characteristics of the passive vibrator 38 (such as its density, thickness and modulus) are selected so that it has the same resonant frequency as the active assembly 32, 34. It may be desirable, in order to match the respective resonant frequencies, to model bender 30 (with, for example, FEA) to account for the complex boundary conditions. In this embodiment, passive vibrator 38 is made from metals such as steel or aluminium, or from a ceramic such as alumina. Other materials may alternatively be used, subject to being able to withstand the static pressure due to the depth of likely deployment.

The support structure 36 is shown in figure 2 as a separate component, but may be formed integrally with base plate 32 or passive vibrator 38. The support structure 36 has a width w that is minimised in order to reduce the rotational constraint that it imposes on base plate 32 or passive vibrator 38. The elastic limits of the material of the support structure 36 determines how thin the hinge can be made, again subject to expected static and dynamic loads. In this embodiment, support structure 36 is made of high tensile metals such as steel, or from a ceramic such as alumina. Other materials may alternatively be used, subject to being able sufficiently to withstand dynamic fatigue and static pressure due to the depth of likely deployment.

Figure 3 is a schematic view of bender 30 in use (with waterproof overmoulding 40

– 6 –

omitted for clarity), with the active assembly 32, 34 and the passive vibrator 38 at maximum displacement from their equilibrium or undriven positions. Both are radiating into the surrounding medium.

5 Figure 4 is a plot of experimental results of measurements of transmit sensitivity (dB) versus frequency (relative to resonant frequency, F_R), for both a background art bender (of the type shown in figures 1A and 1B), shown with a dashed curve, and a bender according to this embodiment, shown with a solid curve. The plot shows, in effect, the output power as a function of frequency, for a fixed driving voltage. Figure 5 is a plot of
10 experimental results of measurements of efficiency (%) versus frequency (relative to resonant frequency, F_R , 3 kHz in this example), also for both a background art bender (of the type shown in figures 1A and 1B), shown with a dashed curve, and a bender according to this embodiment, shown with a solid curve.

15 It will be observed that the response of the bender according to this embodiment—measured as intensity—is approximately halved (that is, is 6 dB lower) compared with the background art bender, but that the efficiency of the bender according to this embodiment remains usefully high—and indeed is little diminished compared with the background art bender. It is also envisaged that refinement of the material of the
20 passive vibrator 38, including by the use of low damping materials, should improve the efficiency of the bender according to this embodiment further. The transmit voltage response is reduced (compared with the background art bender) but, to provide equivalent performance, this drop can be compensated for by increasing the driving voltage by the same factor.

25 Careful design of bender 30 (and in particular of the passive vibrator 38) should allow the amplitude of the displacement of the passive vibrator 38 to be matched to that of the active assembly 32, 34. Radiation area is then maintained giving the same cavitation threshold as the equivalent background art bender. This is demonstrated by
30 figure 6, which is a plot of experimental results of measurements of source level (dB) versus drive voltage (kV), for both a background art bender (of the type shown in figures 1A and 1B), shown with a dashed curve, and a bender according to this embodiment, shown with a solid curve. The cavitation threshold is also plotted, shown with a dotted line, demonstrating that it closely matches that of the bender of the
35 background art.

When compared with background art bender 10 of figures 1A and 1B, passive vibrator

– 7 –

38 of bender 30 is thicker than base plate 14 thereby compensating for the stiffness otherwise contributed by omitted ceramic piezoelectric body 18. However, passive vibrator 38 is thinner than the total thickness of the active assembly (comprising base plate 14 and ceramic body 18), as the passive vibrator is generally much stiffer than
5 the piezoceramic of ceramic piezoelectric body 18, allowing tighter packing and closer spacing of benders according to the present invention in a transducer array. It is envisaged that such a transducer array can exploit the phenomenon of the mutual coupling of the benders.

10 In addition, the overall mass of bender 30 may be reduced compared with the background art bender 10.

It will be understood to persons skilled in the art of the invention that many modifications may be made without departing from the spirit and scope of the
15 invention.

In the claims that follow and in the preceding description of the invention, except where the context requires otherwise due to express language or necessary implication, the word “comprise” or variations such as “comprises” or “comprising” is used in an
20 inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

It is to be understood that, if any prior art is referred to herein, such reference does not constitute an admission that such prior art forms a part of the common general
25 knowledge in the art, in any country.

– 8 –

Claims

1. An acoustic transducer, comprising:
a support structure;
5 an active assembly comprising a base plate supported by the support structure
and a piezoelectric body supported by the base plate; and
a passive vibrator supported by the support structure and coupled via the
support structure to the active assembly so that vibration of the active assembly drives
the passive vibrator;
10 wherein the active assembly and the passive vibrator have the same resonant
frequency.
2. An acoustic transducer as claimed in claim 1, wherein the piezoelectric body is a
piezoelectric ceramic body.
15
3. An acoustic transducer as claimed in either claim 1 or 2, wherein the base plate and
the passive vibrator are of the same metallic composition, the passive vibrator differing
in thickness from the base plate such that the active assembly and the passive vibrator
have a common resonant frequency.
20
4. An acoustic transducer as claimed in any one of the preceding claims, wherein the
passive vibrator comprises a plate.
5. An acoustic transducer as claimed in any one of the preceding claims, wherein the
25 transducer is circular.
6. An acoustic transducer as claimed in any one of claims 1 to 4, wherein the
transducer is elliptical or rectangular.
- 30 7. An acoustic transducer as claimed in any one of the preceding claims, wherein a
cavity defined by the active assembly, the vibrator and the support structure is filled
with a fluid.
8. An acoustic transducer as claimed in any one of the preceding claims, wherein the
35 support structure is integral with the base plate and/or the passive vibrator.
9. A transducer array, comprising:

– 9 –

a plurality of acoustic transducers as claimed in any one of the preceding claims;

wherein the plurality of acoustic transducers are spaced apart to utilise mutual interaction and thereby increase performance.

5

10. A method of manufacturing an acoustic transducer, the method comprising:
coupling an active assembly comprising a base plate and a piezoelectric body supported by the base plate to a passive vibrator by a support structure, such that vibration of the active assembly drives the passive vibrator at a common resonant frequency.

10

11. A method as claimed in claim 10, wherein the piezoelectric body is a piezoelectric ceramic body.

15

12. A method as claimed in either claim 10 or 11, wherein the base plate and the passive vibrator are of the same metallic composition, the passive vibrator differing in thickness from the base plate such that the active assembly and the passive vibrator have a common resonant frequency.

20

13. A method as claimed in any one of claims 10 to 12, wherein the passive vibrator comprises a plate.

14. A method as claimed in any one of claims 10 to 13, wherein the transducer is circular, elliptical or rectangular.

25

15. A method as claimed in any one of claims 10 to 14, wherein a cavity defined by the active assembly, the vibrator and the support structure is filled with a fluid.