

SYSTEM FOR PURIFYING INTERNAL COMBUSTION ENGINE EXHAUST GASES

BACKGROUND OF THE INVENTION

5 **[0001]** The invention relates to a method for purifying exhaust gases of internal combustion engines, preferably diesel engines, the method comprising the spraying of water mist into the exhaust gases by utilizing at least one spray nozzle.

10 **[0002]** The invention further relates to an apparatus for purifying exhaust gases of internal combustion engines, preferably diesel engines, the apparatus comprising a support structure for holding at least one spray nozzle, the spray nozzle being arranged to spray water mist into the exhaust gases.

[0003] One objective in environmental protection is to reduce exhaust emissions of combustion engines. The present method provides a solution for reducing the exhaust emissions of internal combustion engines.

15 **[0004]** Diesel engine exhaust emissions contain various harmful combustion products. They include gaseous carbon monoxide, which oxidises rapidly and forms carbon dioxide that contributes to the greenhouse effect, and volatile organic compounds, solid compounds, and particulates. When heavy oil burns, sulphur oxides SO_x , typically SO_2 and SO_3 , are produced, which contribute to the acidification of soil and the production of smog. During
20 the combustion process, some of the nitrogen gas present in the air oxidises to nitrogen oxides NO_x , particularly NO and NO_2 , which strongly contribute to the formation of smog, to the greenhouse effect and the acidification of soil and to retardation of forest growth, for example. In addition, a fuel that contains nitrogen may cause formation of nitrogen oxides.

25 **[0005]** The amount of sulphur emissions from diesel engines can be reduced by using low-sulphur fuel: the less sulphur the fuel contains, the lower are the sulphur emissions. Low-sulphur fuel can be produced in refineries, but at a high cost. The amount of sulphur oxides cannot be influenced by making changes to the combustion process.

30 **[0006]** Diesel engines of ships are major air polluters. According to a study made in the United States a few years ago, 14% of the world nitrogen emissions and 16% of sulphur emissions of oil exhaust gases originate from shipping. Nitrogen emissions from diesel engines are created most when the motor runs at a low power. In ships this typically takes place when the ship is
35 in port, which is naturally regrettable.

[0007] The amount of nitrogen emissions of diesel engines can be reduced by decreasing the combustion temperature. The temperature can be decreased either by adding water into the fuel or by spraying an emulsion containing water into the combustion chamber. By decreasing the combustion
5 temperature, the amount of nitrogen oxide emissions can be reduced by about 10%. A decrease in the combustion temperature reduces the efficiency of the engine.

[0008] Nitrogen emissions can be efficiently removed from exhaust gases with a catalytic converter in which a mixture of urea and water is
10 sprayed into the fuel gases to reduce nitrogen oxides to nitrogen and water vapour. However, in marine applications, catalytic converters are very expensive; they account for about 30% of the engine cost, and even more in large ships. In addition, a catalytic converter requires servicing, and a space needs to be provided for it in the ship.

[0009] US Patent 5,464,458 teaches a system in which diesel
15 engine exhaust gases are purified using mist-like water. The system employs nozzles to spray water into a chamber containing a flow of exhaust gases to separate products contained in the exhaust gases from them. The system allows carbon in particular, but also carbon monoxide, hydrocarbons and
20 nitrogen oxides, to be removed from the exhaust gases.

BRIEF DESCRIPTION OF THE INVENTION

[0010] It is an object of the present invention to provide a new, economical solution for purifying exhaust gas emissions of internal combustion engines and especially large-dimension both two-stroke and four-stroke diesel
25 engines, especially diesel engines of ships, the solution being implemented such that it does not complicate the discharge of exhaust gases from the engine.

[0011] To achieve this objective, the method of the invention is characterized by spraying water mist by utilizing said at least one spray nozzle
30 and thereby causing a negative pressure in the immediate vicinity of the nozzle for sucking the exhaust gases into the sprayed spray. The sucking causes exhaust gases to be entrained into the sprayed spray

[0012] The water mist is preferably created by a pressure of 10 to 300 bar and sprayed inside the exhaust manifold of the engine.

[0013] Preferred embodiments of the method of the invention are disclosed in the accompanying claims 2 to 6.

5 [0014] To achieve the above-mentioned objective, the apparatus of the invention is characterized in that the spray head is a spray head the operation of which creates a suction causing a negative pressure in the immediate vicinity of the spray head. The negative pressure draws the exhaust gases toward the spray head and guides the exhaust gases into the water spray coming from the spray head. This allows for an efficient reaction between the exhaust gases and water.

10 [0015] The spray head is preferably arranged inside a reaction chamber which comprises an inlet opening for directing a flow of exhaust gases into the suction of the spray head inside the reaction chamber.

[0016] Preferred embodiments of the apparatus of the invention are disclosed in the accompanying claims 8 to 26.

15 [0017] Major advantages of the invention for purifying internal combustion engine exhaust gases are that it is fairly simple and inexpensive to implement; the invention can be applied to existing internal combustion engines, such as diesel engines of ships, and therefore only minor changes are needed; the apparatus allows the flow of exhaust gases to be guided as
20 desired; and the apparatus provides for an efficient, even improved, removal of exhaust gases from the engine. Moreover, the operating costs of the apparatus, with service costs included, are very low.

BRIEF DESCRIPTION OF THE DRAWINGS

25 [0018] In the following, the invention will be described in greater detail with reference to three embodiments and the accompanying drawings, in which

Figure 1 illustrates a first embodiment of the invention;

Figure 2 illustrates a second embodiment of the invention;

Figure 3 illustrates a third embodiment of the invention.

30 DETAILED DESCRIPTION OF THE INVENTION

[0019] Figure 1 shows a preferred embodiment of the invention. The Figure shows an apparatus to be mounted to an exhaust pipe (not shown) of a diesel engine of a ship for purifying exhaust gases. If the diesel engine comprises a plurality of exhaust pipes, typically a plurality of purifying
35 apparatuses may be provided.

[0020] The apparatus shown in Figure 1 is mounted to an exhaust pipe at a position which is advantageous from the point of view of the exhaust gas temperatures and the mounting of the apparatus. The total height of the apparatus is relatively small whereby it is easy to find a mounting space for it.

5 A small height is possible when the exhaust gases are sideways deviated out of their principal exhaust flow direction at the inlet.

[0021] The apparatus comprises an inlet flange 1 for receiving unpurified exhaust gases from the engine, and a discharge flange 2 through which the purified exhaust gases are discharged. The inlet flange 1, which is
10 shown partly in section in the Figure, comprises a number of holes for fastening the apparatus to an exhaust pipe of the engine by utilizing bolts (not shown) to be inserted into the holes. The discharge flange 2 comprises a corresponding perforation to which can be attached an exhaust pipe portion through which the purified exhaust gases are discharged from the ship.

15 **[0022]** Between the flanges 1 and 2 there is provided a connection that allows the exhaust gases to be guided from the inlet flange 1 to the discharge flange 2.

[0023] The apparatus comprises a support structure, generally referred to with reference numeral 3, with a number of spray heads 4 attached
20 thereto. The number of the spray heads 4 varies according to application; in the solution of the Figure there are 10 of them, but a solution where one is sufficient is also possible (in which case suction and spreading ducts may be arranged to produce a larger area of suction), whereas some solutions may comprise dozens of spray heads. The spray heads 4 are of a type that can be
25 used at a high pressure causing a strong suction in their immediate vicinity. The pressure is within 10 to 300 bar, typically from about 20 to 100 bar. Each spray head 4 comprises preferably at least two nozzles arranged in a diverging position with respect to each other, and the structure of the head may be for example like the one disclosed in WO 92/20453. Due to the risk of clogging,
30 the spray head 4 is preferably simple in structure. The spray heads are arranged in a circle at a distance from one another, and they are directed to produce substantially parallel sprays. Reference numeral 5 designates a pipe system for supplying water to the spray heads 4. The arrangement for supplying water into the pipe system 5 is not shown, because it is easy for a
35 person skilled in the art to accomplish. In order to avoid the need to use the valuable water from the fresh water tanks, water known as grey water in ships

is preferably used in the process. The arrangement comprises a pressure source (not shown) being able to provide a pressure of at least 10 bar via the pipe system 5 to the spray heads. Preferably the pressure source is a high-pressure source able to provide a pressure of at least 20 bar and up to 100 - 300 bar.

[0024] The spray heads 4 are fastened to the ends of rods 6, which are in turn fastened to a flange 7 of the support structure, the spray heads being suspended from the flange so that they produce a downward spray. The spray heads 4 can be easily detached from the flange 7 for cleaning. This is carried out by opening the fastening means (not shown in Figure 1, but visible in Figure 2 in which rods 6' are fastened with screws 60').

[0025] The apparatus comprises a cylindrical housing 8 with a first, concentric cylindrical wall 9 arranged inside it. Inside the cylindrical wall 9 is arranged a second, concentric cylindrical wall 10.

[0026] Between the housing 8 and the first cylindrical wall 9 there is provided a flow space 11 for unpurified exhaust gases.

[0027] Between the first and the second cylindrical spaces there is provided a space comprising guide plates 12 that divide the space into a plurality of reaction chambers 13 formed of tubes 130, each reaction chamber being provided with a spray head 4. The guide plates 12 are fastened to the second wall 10. Between the free side edges of the guide plates 12 and the first wall 9 is left a passage 18. The top edges of the guide plates 12 are at a distance from the flange 7, their bottom edges extending to the top edge of a discharge opening 17 provided in the wall 10. The function of the discharge opening 17 is to guide purified exhaust gases into the space enclosed by the wall 10 and from there further toward the discharge flange 2. The purified exhaust gases flow inside the wall 10 in the same direction as a direction in which unpurified exhaust gases enter the inlet flange 1. Said direction can be called direction of principal exhaust flow path. Seen in the direction of flow of the exhaust gases, the discharge opening 17 is located after the spray heads 4. Seen from the direction of flow of the exhaust gases, the spray heads 4 are located below the top edges of the guide plates 12, or on the same level as they. The guide plates 12 are at an angle to the spray heads 4, the spray heads thus spraying towards the guide plates.


[0028] Unpurified exhaust gases enter the reaction chambers 13 through an inlet opening 14. The inlet opening is formed of a port or a gap 14 between the top edge of the second wall 10 and the flange 7.

[0029] The bottom end of the first wall 9 of the reaction chamber 13 is conical, whereby reaction products formed in the reaction chambers are guided out of the reaction chambers through a discharge conduit 15 at the bottom. The discharge conduit 15 is supplied through a hole 16 in the flange 1 to guide the reaction products out of the apparatus.

[0030] The second wall 10 of the reaction chamber 13 also guides the reaction products formed in the reaction chamber 13 into the discharge conduit 15. From the discharge conduit 15, the reaction products are guided to a place where they do not cause any harm.

[0031] In the following, the operation of the apparatus of Figure 1 will be described.

[0032] Unpurified exhaust gases flow into the apparatus through the inlet flange 1. If the spray heads 4 have not been activated, the exhaust gases flow through the inlet opening 14 into the discharge opening 17 and from there the unpurified gases flow pass the discharge flange 2. As can be understood from the figure when flowing from the inlet flange to the discharge flange 2, the exhaust gases are deviated out of the principal exhaust flow path. If the spray heads 4 have been activated, the suction effect of the spray heads 4 draws unpurified exhaust gases to them through the inlet opening 14. These exhaust gases are guided into the mist-like water spray of the spray heads 4. Thus the suction of the spray heads 4 together with the geometry of the apparatus effects deviation of the exhaust gases out of the principal exhaust flow path. The droplet size in the water spray is very small, thereby allowing for an efficient reaction between the exhaust gases and the water. 90 % of the volume of water (Dv90) is in droplets typically smaller than 200 μm , preferably smaller than 100 μm and most preferably smaller than 50 μm . The nitrogen oxides NO and NO₂ contained in the exhaust gases go through several reaction phases to form nitrogen acid. The following reaction formulae are approximations showing the starting products and the respective end product.



[0033] Reaction (1) works already at room temperature, but it is significantly more effective at a temperature of 100 - 150°C. The reaction is efficient because the exhaust gases are hot.

5 **[0034]** Reaction (2) works well already at room temperature. Since it is not desirable to have nitrogen dioxide in exhaust gases, it is changed to nitrogen acid, cf. reaction formula (3). In the reaction according to formula 3, nitrogen acid is the only non-volatile end product. Formula 3 is believed to produce nitrogen acid effectively already at a temperature of 50°C.

10 **[0035]** Because of the nitrogen acid formation, the components of the apparatus must be made of materials that sustain nitrogen acid. A material suitable for the walls 9 and 10, guide plates 12 and discharge conduit 15 is for example austenitic stainless steel.

15 **[0036]** When the invention is being applied, the temperature in the reaction chamber 13 is selected to allow for nitrogen acid to be formed, avoiding, however, a simultaneous formation of nitrogen oxides that would be guided out of the apparatus. A temperature within the range of 50 - 150°C could be suitable. This is a temperature inherently prevailing in exhaust pipes, or it can easily be created there (the water to be sprayed acting as a coolant). Since the reaction chamber contains a large number of chemical compounds,
20 the reactions are very complex and they cannot be theoretically calculated. Due to this, the temperatures that are most suitable for as low emissions as possible to be produced must be discovered experimentally.

[0037] Water mist not only reduces the number of nitrogen oxides, but also purifies the exhaust gases of other non-desirable compounds.

25 **[0038]** The apparatus of Figure 1 (and Figure 2) is provided with a sensor (not shown) for measuring nitrogen oxide contents. The sensor is used for controlling the supply of water to the spray heads 4, which is carried out by regulating the water pressure. Water flow is reduced, or even interrupted, when emissions are low or when the ship is in an area where emissions are
30 not very significant.

[0039] Figure 2 shows a second embodiment of the invention. In the Figure, the same reference numerals as in Figure 1 are used for corresponding elements.

35 **[0040]** The embodiment of Figure 2 deviates from the one in Figure 1 in that a portion of the exhaust gases flow unpurified through bypass openings 100' provided in a wall 910' toward the discharge flange 2'.

Compared with the arrangement of Figure 1, this arrangement provides the apparatus with a different kind of resistance towards exhaust gas flow, which may be advantageous in certain types of diesel engines (two-stroke diesel engines). The number and size of the bypass openings 100' may vary from those given above.

[0041] The apparatus comprises seven reaction chambers 13' formed of tubes 130' provided with inlet openings 14' which allow unpurified exhaust gases to be sucked into the reaction chambers by impact of the spray heads 4' (suction impact). The tubes 130' are curved, i.e. they comprise a curved portion, the water sprays from the spray heads 4' thus hitting the wall of the tubes. The tubes 130' are connected to a space enclosed by the wall 910', the bottom end of which is formed to be conical so as to allow reaction products to be guided into a discharge conduit 15'. The number of the tubes 130' and reaction chambers 13' can naturally vary, similarly as in the embodiment of Figure 1.

[0042] As can be understood from Figure 2, the spray heads 4' can be easily removed from the flange 7' to which they are fastened (the screws 60' are unscrewed and the rods 6', together with the spray heads 4', are lifted up. The unit of conduits for supplying water to the spray heads 4' is not shown, because a person skilled in the art is capable of designing one.

[0043] Figure 3 shows a third embodiment of the apparatus of the invention. In Figure 3, same reference numerals as in Figures 1 and 2 are used for corresponding elements. The apparatus of Figure 3 deviates from the those of Figures 1 and 2 in that the apparatus is meant to be fastened to the side of an exhaust manifold 500'' of the diesel engine, the apparatus comprising an inlet flange 1'' for this purpose. The discharge flange 2'' of the apparatus and the discharge conduit 15'' for the reaction products are made separate from the exhaust manifold 500''. The apparatus of Figure 3 is very simple to mount. The apparatus comprises a conduit 910'' arranged inside a housing 8'', an opening 100'' being provided at one end (bottom end) of the conduit for directing the exhaust gas flows to the second end of the conduit (top end) provided with an exhaust gas discharge opening''. The discharge flange 2'' can be connected to the manifold 500''.

[0044] In the above specification the invention is illustrated with reference to only three examples, on the basis of which it can be understood that the details of the invention may vary in many ways within the scope of the

accompanying claims. The position of the discharge opening 17 of Figure 1 and that of the bypass opening 100' of Figure 2, for example, may vary; the number of the discharge and bypass openings may vary; the shape of the apparatus may deviate from the one shown here, although from the point of view of the flows and the manufacturing, and the cleaning of the apparatus, a cylindrical shape is preferred. There may be a plurality of discharge conduits 15, 15', 15'', although it is recommended that the reaction products are guided in a centralized manner from the reaction chambers to a single discharge conduit, whereby it is not necessary to make several openings in the housing, and the reaction products can be removed from one and the same place. The direction of the spray heads 4, 4', 4'' may vary, although it is preferred that they point downward, because then the sprays facilitate the removal of the reaction products from the apparatus. This does not mean, naturally, that the spray heads would need to point directly downward. In addition, downward directed spray heads allow for an apparatus of small dimensions and easy mounting. The apparatus and method can be also applied to the purification of exhaust gases of other units than diesel engines of ships: it can be applied to diesel engines in general and even more generally to internal combustion engines in general.

CLAIMS

1. A method for purifying exhaust gases of internal combustion engines, preferably diesel engines, the method comprising the spraying of water mist into the exhaust gases by utilizing at least one spray nozzle,
5 **characterized** by the steps of
- spraying water mist into a reaction chamber by utilizing said at least one spray nozzle and thereby causing a negative pressure in the immediate vicinity of the nozzle for sucking the exhaust gases into the sprayed spray;
 - 10 - making water mist and exhaust gases to react in the reaction chamber; and
 - leading reaction products formed of water and exhaust gases to a discharge conduit.
2. A method according to claim 1, **characterized** by
15 effecting said spraying by a pressure of 10 - 300 bar.
3. A method according to claim 1, **characterized** by spraying the water mist inside an exhaust pipe of the internal combustion engine.
4. A method according to claim 1 or 2, **characterized** by
20 spraying the water mist in an at least approximately parallel direction with the exhaust gas flow.
5. A method according to any one of the preceding claims, **characterized** by deviating at least part of the exhaust gases to be purified out of a principal exhaust flow path by the suction provided by the
25 spray head.
6. A method for purifying the exhaust gases of diesel engines of ships according to any one of the preceding claims, **characterized** by supplying a ship's grey water to the nozzles to produce the water mist.
7. An apparatus for purifying exhaust gases of internal combustion
30 engines, preferably diesel engines, the apparatus comprising a support structure (3, 3', 3'') for holding at least one spray nozzle (4, 4', 4''), the spray head being arranged to spray water mist into the exhaust gases, **characterized** in that
- the spray head is a spray head (4, 4', 4'') the operation of which
35 creates a suction causing a negative pressure in the immediate vicinity of the

spray head;

- the reaction chamber (13, 13', 13'') is connected to a discharge conduit (15, 15', 15'') for receiving from the reaction chamber reaction products formed of water and exhaust gases and for guiding them out of the apparatus; and

- the apparatus comprises fastening means (1, 2, 1', 2', 1'') for mounting the apparatus to a manifold of the internal combustion engine. (Fig. 1, 2, 3)

8. An apparatus according to claim 7, **characterized** in that the spray head (4, 4', 4'') is arranged inside a reaction chamber (13, 13', 13'') which comprises an inlet opening (14, 14', 14'') for directing a flow of exhaust gases into the suction of the spray head, inside the reaction chamber. (Fig. 1, 2, 3)

9. An apparatus according to claim 8, **characterized** in that the spray head (4, 4', 4'') is arranged to spray in a direction that speeds up the discharge of the exhaust gases from the engine. (Fig. 1, 2, 3)

10. An apparatus according to claim 7, **characterized** in that the reaction chamber (13, 13') is surrounded by a muffle construction (8, 8'), and between the muffle construction and the reaction chamber there is provided a flow space (11, 11') which conveys the exhaust gases to the inlet opening (14, 14') of the reaction chamber. (Fig. 1, 2)

11. An apparatus according to claim 10, **characterized** in that part of the flow space (11) is defined by a first wall (9) which is at a distance from the muffle construction (8), the first wall in turn further partly defining the reaction chamber (13). (Fig. 1)

12. An apparatus according to claim 11, **characterized** in that the first wall (9) is arranged to convey the reaction products into the discharge conduit (15). (Fig. 1)

13. An apparatus according to claim 11 or 12, **characterized** in that part of the reaction chamber (13) is defined by a second wall (10) which is arranged to convey the reaction products into the discharge conduit (15). (Fig. 1)

14. An apparatus according to claim 13, **characterized** in that the first wall (9) and the second wall (10) are cylindrical walls which are at least approximately concentric. (Fig. 1)

15. An apparatus according to claim 13, **characterized** in

that it comprises a plurality of spray heads (4) mounted to the support structure (3) in the form of a circle between the first wall (9) and the second wall (10) and at a distance from one another, guiding plates (12) being provided between the walls, and the spray heads being arranged to spray
5 towards the guiding plates. (Fig. 1)

16. An apparatus according to claim 7, **characterized** in that it comprises a muffle construction (8'') and a conduit (910'') comprising a first end and a second end, the conduit being arranged inside the muffle construction, the spray head (4'') being arranged into a space (11'') between
10 the muffle construction and the conduit, the first end of the conduit comprising an opening (100'') for directing a flow of purified exhaust gases to the second end of the conduit which is provided with an exhaust gas discharge opening. (Fig. 3)

17. An apparatus according to claim 16, **characterized** in
15 that it comprises a plurality of spray heads (4'') mounted to the support structure (3'') in the form of a circle between the muffle construction (8'') and the conduit (910'') and at a distance from one another, the spray heads being arranged inside their respective tubes (130'') which form reaction chambers.

18. An apparatus according to claim 10, **characterized** in
20 that the flow space (11') comprises a bypass opening (100') for directing a portion of unpurified exhaust gases out of the apparatus through the bypass opening. (Fig. 2)

19. An apparatus according to claim 18, **characterized** in
25 that the bypass opening (100') is in a wall (910'), which is arranged to guide the reaction products from the reaction chamber (13') into the discharge conduit (15'). (Fig. 2)

20. An apparatus according to claim 19, **characterized** in
that it comprises a plurality of spray heads (4') mounted to the support structure (3') in the form of a circle between the muffle construction (8') and
30 the wall (910') and at a distance from one another, the spray heads being mounted inside their respective tubes (130') which form reaction chambers (13'). (Fig. 2)

21. An apparatus according to claim 17 or 20, **characterized** in that the tubes (130', 130'') comprise a curved portion
35 and they lead to a space defined inside the wall (910'), said discharge conduit (15') being in communication with said space. (Fig. 2)

22. An apparatus according to claim 15, 16 or 20, **characterized** in that the spray heads (4, 4', 4'') are detachably fastened to a flange (7, 7', 7'') of the support structure (3, 3', 3'') from which they suspend and can be detached by lifting. (Fig. 1, 2, 3)

5 23. An apparatus according to claim 7, **characterized** in that the fastening means comprise an inlet flange (1, 1', 1'') provided with an opening for conveying the exhaust gases of the internal combustion engine into the apparatus, and a discharge flange (2, 2', 2'') provided with an opening for conveying the exhaust gases out of the apparatus. (Fig. 1, 2, 3)

10 24. An apparatus according to claim 23, **characterized** in that the inlet flange (1'') is formed to be fastened to a side of the exhaust manifold of the internal combustion engine. (Fig. 3)

15 25. In a method for purifying exhaust gases of an internal combusting engine, the improvements comprising:

spraying water mist created by a spraying pressure of 10 to 300 bar into a first portion of the exhaust gases for causing a negative pressure about the spraying and sucking the first portion of the exhaust gases into the spraying, and

20 guiding a second portion of the exhaust gases through a bypass past the spraying for controlling flow resistance of the exhaust gases.

26. An apparatus for purifying exhaust gases of an internal combustion engine, the apparatus comprising

25 a support structure for holding at least one spray nozzle, means for creating a spraying pressure of 10 to 300 bar for the spray nozzle, the spray nozzle being arranged to spray water mist into the exhaust gases, wherein the spray nozzle and spraying pressure create a suction causing a negative pressure in the immediate vicinity of the spray nozzle, and being arranged inside a reaction chamber which comprises an inlet opening for directing a first portion of the exhaust gases into the suction of the spray nozzle, the suction being inside the reaction chamber, and

30 means for guiding a second portion of the exhaust gases through a bypass past the reaction chamber.

35 27. An apparatus for purifying a gas flow, the apparatus comprising

a support structure for holding a spray nozzle,
means for creating a spraying pressure of 10 to 300 bar for the
spray nozzle, the spray nozzle being arranged to spray water mist into the gas
flow,

5 wherein the spray nozzle is a spray nozzle the operation of which
creates a suction causing a negative pressure in the immediate vicinity of the
spray nozzle,

 wherein the spray nozzle is arranged inside a reaction chamber
which comprises an inlet opening for directing the gas flow into the suction of
10 the spray nozzle and the suction is inside the reaction chamber,

 wherein the reaction chamber is connected to a discharge conduit
for receiving from the reaction chamber exhaust gases, water mist and
reaction products formed of the water mist and exhaust gases,

 wherein the reaction chamber is surrounded by a mantle, and
15 between the mantle and the reaction chamber there is a flow space which
conveys the exhaust gases to an inlet opening of the reaction chamber,

 wherein part of the flow space is defined by a first wall which is at a
distance from the mantle and partly defines the reaction chamber,

 wherein the first wall is arranged to convey the reaction products
20 into the discharge conduit,

 wherein part of the reaction chamber is defined by a second wall
which is arranged to convey the reaction products into the discharge conduit,
and

 further comprising a plurality of spray nozzles mounted to the
25 support in a circle between the first wall and the second wall and at a distance
from one another, guiding plates being provided between the walls, and the
plurality of spray nozzles being arranged to spray towards the guiding plates.