

Scope of Claim

[Claim 1] A bedpan with a diaper that is characterized by comprising
an inner that has a defecation-receiving hole,
a urination-receiving hole and a defecation suctioning hole, and
functions as a bedpan, a diaper applied on the back of the inner to be attached
to the crotch, and an outer that is applied from behind the diaper so that the defecation-
receiving hole and the urination-receiving hole of the inner are exposed and holds the
diaper between the outer itself and the inner.

[Claim 2] A bedpan with a diaper described in Claim 1 that is characterized by its inner
that has a stool sensor, a urine sensor, and a washing nozzle.

[Claim 3] A bedpan with a diaper described in Claim 1 that is characterized by its outer
on which an inner fitting recess that holds the diaper tightly in a gap between the outer
peripheral surface of the inner and the inner periphery of the outer is formed.

[Claim 4] A bedpan with a diaper described in Claim 3 that is characterized by its diaper
which has an internal waterproof paper part that fits between the inner and the outer
and the outer peripheral surface of the waterproof paper is made of a cushion material.

[Claim 5] A bedpan with a diaper described in Claim 3 that is characterized by a soft
material formed at the defecation-part fitting wall and urination-part fitting wall at the
outer periphery of the inner fitting recess that protrudes toward outsides from the
defecation-receiving part and urination-receiving part when the inner is fitted.

[Claim 6] A bedpan with a diaper described in Claim 1 that is characterized by a hip-
receiving part mounted at the front end of the outer.

[Claim 7] A method for attaching a bedpan diaper that is characterized by comprising
a process in which a diaper to be attached to the crotch is placed on the back of
the inner that has a defecation-receiving hole, a urination-receiving hole and a defecation
suctioning hole and functions as a bedpan, and
a process in which the outer is applied from behind the diaper so that the front
surface of the inner is exposed, and holds the internal waterproof part of the diaper

between the outer itself and the inner.

[Claim 8] A method for attaching a bedpan diaper that is characterized by comprising

a process in which a diaper to be attached to the crotch is applied to an inner that has a defecation-receiving part, a urine-receiving part and a defecation suctioning hole at its front surface and an excretion suctioning hose connected to the defecation suctioning hole, an air supply tube, and a water supply tube connected to the washing nozzle at its back surface and functions as a bedpan, with the excretion suctioning hose, the air supply tube and the water supply tube at the back side of the inner protruding from the protrusion relief hole of the internal waterproof paper of the diaper, and

a process in which the inner fitting recess of the outer is applied from behind the diaper so that the front surface of the inner is exposed, with the excretion suctioning hose, the air supply tube and the water supply tube protruding from the protrusion relief hole of the outer, and holds the internal waterproof paper part of the diaper between the outer and the inner.

[Claim 9] A method for attaching a bedpan diaper described in Claim 8 that is characterized by

a process in it where a lower part protrusion at the front end of the inner is fixed, together with the internal waterproof paper of the diaper, to the lower part fixing recess of the inner fitting recess arranged in the outer while the diaper is placed on the back of the inner, and the inner and the diaper are fitted to the inner fitting recess by using the fixing part as the support point, when the outer is applied from behind the diaper and holds the diaper between itself and the inner.

[Claim 10] A method for attaching a bedpan diaper that is characterized by comprising

a process in which a diaper to be attached to the crotch is applied on the front surface of an outer, and a process in which an inner that has a defecation-receiving hole, a urination-receiving hole and a defecation suctioning hole at its front surface and functions as a bedpan is fitted to the diaper from above and holds the internal waterproof part of the diaper between the inner itself and the outer.

[Claim 11] A method for attaching a bedpan diaper that is characterized by comprising

a process in which the internal waterproof paper part of the diaper having a protrusion relief hole is applied to an inner fitting recess of the outer having protrusion relief holes, and

a process in which an inner that has a defecation-receiving part, a urine-receiving part, a defecation suctioning hose and a washing nozzle at its front surface and an excretion suctioning hose connected to the defecation suctioning hole, an air supply tube, and a water supply tube connected to the washing nozzle at its back surface and functions as a bedpan is pushed into the inner fitting recess through the protrusion relief hole of the internal waterproof paper of the diaper, with the excretion suctioning hose, the air supply tube and the water supply tube protruding through the protrusion relief holes of the outer.