

Description

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to chrominance signal processing circuits and video tape recorders (hereinafter, referred to as VTR) having a function of processing a chrominance signal and, more particularly, to an integrated chrominance signal processing circuit for converting a frequency of a chrominance signal in recording and reproducing of a video signal and a VTR comprising such a chrominance signal processing circuit.

Description of the Background Art

Conventionally, 2-head helical scanning system has been adopted in a home VTR. In a VTR of such a 2-head helical scanning system, no signal region e.g. a guard band is not provided between tracks in order to achieve high density recording, therefore, in reproducing, a crosstalk occurs from an adjacent track. Crosstalk is removed for example from a chrominance signal among signals recorded on a video tape by utilizing a line correlation.

Fig. 3 is a circuit diagram showing one example of a chrominance signal processing circuit provided in a reproduction system of a video signal in a conventional VTR, which is in effect implemented as an integrated circuit. The chrominance signal processing circuit converts a low-frequency converted and recorded chrominance signal into a high-frequency signal after being reproduced from a video tape, and removes a crosstalk from the high frequency signal. The example shown in Fig. 3 is for reproducing a video signal of NTSC system and is disclosed in US-A-4 405 937, for example.

In Fig. 3, a reproduced video signal from a head (not shown) is applied to an input terminal 1. Only a chrominance signal of 629KHz of the applied video signal passes through a low-pass filter (LPF) 2 to be inputted to a first frequency converting circuit 3. The first frequency converting circuit 3 causes the chrominance signal of 629KHz to be converted into a chrominance signal of $4.21\text{MHz} \pm 629\text{KHz}$. The frequency converted chrominance signal is supplied to a band-pass filter (BPF) 4 through which only a chrominance signal of 3.58MHz is extracted. The extracted chrominance signal of 3.58MHz is applied to a comb filter 5 wherein noise components are removed. Then, the output of the comb filter 5 is supplied to an output terminal 6.

The chrominance signal outputted from the comb filter 5 is applied to a burst extracting circuit 7 at the same time. The burst extracting circuit 7 extracts a burst signal from the chrominance signal in response

to a burst gate pulse (BGP) supplied from a terminal 8, thereby applying the burst signal to one input of a phase comparator circuit (PC) 9. On the other hand, an oscillating output signal having a center frequency of 3.58MHz is applied to the other input of the phase comparator circuit 9 from a first oscillation circuit 10, and the phase comparator circuit 9 compares phases of both of the inputted signals. Then, an error output corresponding to the result is smoothed in a low-pass filter 11 and applied to a second voltage controlled oscillator (VCO) 12.

An output of the VCO 12 is applied to a frequency limiting circuit 13, and when an oscillating frequency of the VCO 12 fluctuates, the frequency limiting circuit 13 generates an error signal corresponding to the fluctuation, thereby feeding back the same to the VCO 12. As a result, a frequency of the oscillating output signal of the VCO 12 is prevented from deviating from a predetermined range, so that oscillation of the VCO 12 is stabilized.

A central frequency of the oscillating output of the VCO 12 is set to $320f_H$ (f_H is a horizontal frequency of 15.734KHz), and the oscillating output signal is applied to a 1/8 frequency dividing circuit 14, wherein its frequency is frequency-divided into 1/8. The 1/8 frequency dividing circuit generates four frequency-divided signals which are out of phase from each other by 90° . Accordingly, the four signals shifted by 90° and each having a frequency of $40f_H$ are applied to a four-phase logic circuit 15. The four-phase logic circuit 15 selects any of four inputted signals of $40f_H$ to supply the same, and its selection is switched corresponding to a horizontal synchronizing signal supplied from a terminal 16. More specifically, a signal whose phase is advanced (or delayed) by 90° every 1H (H is one horizontal cycle) is selectively supplied to be applied to a second frequency converting circuit 17. An output of the four-phase logic circuit 15 is multiplied by an oscillating output of 3.58MHz of the first oscillation circuit 10 by the second frequency converting circuit 17 to be applied to a band-pass filter 18. Then, only a signal having a frequency component of a sum ($40f_H + 3.58\text{MHz} = 4.21\text{MHz}$) of the multiplication result passes through the band-pass filter 18 to be applied to the first frequency converting circuit 3. As a result, in the first frequency converting circuit 3, a chrominance signal of 629KHz and the above described signal of 4.21MHz are multiplied, so that its result is applied to the band-pass filter 4. Then, only a signal of 3.58MHz which is a frequency component of a difference of the multiplication result passes through the band-pass filter 4 to be applied to the comb filter 5.

The comb filter 5 has a 1H delay line using CCD or a glass delay line, and removes crosstalk by subtracting a chrominance signal advanced by 1H and a chrominance signal delayed by 1H to each other. A signal having a frequency of $2f_{sc}$ (f_{sc} is a chromi-

nance subcarrier frequency of 3.58MHz) is required to drive such a CCD. In the circuit of Fig. 3, such a $2f_{sc}$ signal is obtained by multiplying by double an oscillating output of f_{sc} of the first oscillation circuit 10. More specifically, the oscillating output of the first oscillation circuit 10 is applied to a multiplying circuit 19 directly and through a 90° phase shift circuit 20. Then, only a signal having a frequency of $2f_{sc}$ in multiplication results of the multiplying circuit 19 is extracted by a band-pass filter 21 to be supplied to the comb filter 5. On the other hand, the signal of $2f_{sc}$ is also used for a noise removing circuit (not shown) built in a luminance signal processing circuit 22.

As the foregoing, in the chrominance signal processing circuit shown in Fig. 3, a reproduced chrominance signal of 3.58MHz can be obtained by inversely converting the low-frequency converted and recorded chrominance signal, and a crosstalk is removed from the reproduced chrominance signal.

A VTR comprising the above described chrominance signal processing circuit is disclosed in Japanese Patent Laying Open No. 62-104296.

In the circuit of Fig. 3, the four-phase logic circuit 15 shifts the oscillating output of the VCO 12 by 90° every 1H. Accordingly, in an output signal of the four-phase logic circuit 15, a sideband having offset of $f_H/4$ to $40f_H$ occurs every 1H, and a sideband corresponding thereto also occurs in an output of the second frequency converting circuit 17. If Q of the band-pass filter 18 is high as shown in Fig. 4, the above described sideband cannot pass through the filter, thereby requiring more time for a phase change of every 1H, which results in distortion of waveform of the chrominance signal near the burst signal. Accordingly, as the band-pass filter 18, usually the one having a wide pass band as shown in Fig. 5 is used.

A band-pass filter having filter characteristics as shown in Fig. 5 cannot be implemented in a commonly used parallel resonance circuit as shown in Fig. 6 which is formed of a coil and a capacitor, but a structure of the above described band-pass filter becomes complicated such as shown in Fig. 7. Since the band-pass filter shown in Fig. 7 is implemented as an externally provided part of IC as shown, the number of externally provided parts is increased, and two external pins are necessary for every IC. As the foregoing, in the chrominance signal processing circuit as shown in Fig. 3, there were various difficulties in integrating a circuit.

In addition, in the chrominance signal processing circuit in Fig. 3, the multiplying circuit 19, the 90° phase shift circuit 20 and the band-pass filter 21 are required in order to generate a signal of $2f_{sc}$ to be supplied to the comb filter 5 and the luminance signal processing circuit 22, so that the number of the elements is increased. Although the band-pass filter 21 can be implemented in a simple structure shown in Fig. 6, it is implemented as being externally attached

to IC, which particularly obstructs integration of a circuit.

In order to resolve the above described problems, the chrominance signal processing circuit is proposed in which an output of the second frequency converting circuit is applied to a band-pass filter having high Q and a phase of the signal passes through the band-pass filter is shifted, which is disclosed in "Development of Color Signal Processor for VHS VTR" by N. Yamamoto et al., in the ITEJ Technical Report, Vol. 12, No. 17, pp.1 through pp.6, issued in May, 1988.

Fig. 8 is a block diagram showing main parts of such an improved chrominance signal processing circuit. In Fig. 8, an oscillating output of $320f_H$ of the VCO 12 is frequency-divided into $1/8$ in the $1/8$ frequency dividing circuit 14 to be a signal of $40f_H$, and applied to the second frequency converting circuit 17. On the other hand, a signal of f_{sc} from the first oscillation circuit 10 is applied to the second frequency converting circuit 17. An output of $f_{sc} + 40f_H$ is extracted from an output of $f_{sc} \pm 40f_H$ of the second frequency converting circuit 17 by a band-pass filter 118 having high Q to be applied to a four-phase logic circuit 115. An output of the four-phase logic circuit 115 is supplied to the first frequency converting circuit 3. Since the above described chrominance signal processing circuit is constituted such that a signal of $f_{sc} + 40f_H$ not containing a sideband component passes through the band-pass filter 118 having high Q, the number of parts externally attached to IC and external pins of IC can be reduced.

However, in the circuit shown in Fig. 8, since an input of the four-phase logic circuit 115 is a signal of $f_{sc} + 40f_H$, a linear circuit comprising a capacitor and a transistor shown in Fig. 9 should be used in order to generate from the signal of $f_{sc} + 40f_H$ four-phase signals out of phase from each other by 90° . Waveforms 1 through 4 of Fig. 10 indicate potentials of the corresponding nodes 1 through 4 in Fig. 9 and constitute outputs of the four-phase logic circuit. The circuit of Fig. 9 performs only a phase shift by 90° but not a frequency-dividing, however, performing a precise phase shift by 90° is difficult due to a capacitor and a transistor as shown, so that a complicated adjustment is necessary to implement a precise phase shift by 90° . In addition, the capacitor C should be provided externally to the IC in order to secure a large capacitance, which is not suitable for integrating the circuit.

GB-A-2 090 101 discloses a system for synchronizing the reproduced chrominance signal with the reproduced f_H -signal. This function corresponds to said one carried out by the frequency limiting circuit 13 shown in fig. 3.

SUMMARY OF THE INVENTION

An object of the present invention is to enable a

highly accurate converting of a frequency of a chrominance signal.

Another object of the present invention is to generate a highly accurate four-phase signal used for converting a frequency of a chrominance signal.

A further object of the present invention is to simplify a structure of a chrominance signal processing circuit so as to facilitate integration of a circuit.

These objects are achieved by a chrominance signal processing circuit according to claim 1 or claim 6. The claims 9 and 10 are related to corresponding video tape recorders. The further claims corresponds to different embodiments of the present invention.

Therefore, a principal advantage of the present invention is that since oscillating frequencies of the first and the second oscillation circuits are set such that an output of the second frequency converting circuit becomes $4n(f_{SC} \pm 40f_H)$, a four-phase signal used for converting a frequency of the chrominance signal by the first frequency converting circuit can be generated by using a highly precise four-phased logic circuit.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a chrominance signal processing circuit according to a first embodiment of the present invention.

Fig. 2 is a block diagram showing a chrominance signal processing circuit according to a second embodiment of the present invention.

Fig. 3 is a block diagram showing one example of a conventional chrominance signal processing circuit.

Fig. 4 and Fig. 5 are diagrams showing filter characteristics of a band-pass filter.

Fig. 6 is a circuit diagram showing an example of a band-pass filter.

Fig. 7 is a circuit diagram showing another example of a band-pass filter.

Fig. 8 is a block diagram showing another example of a conventional chrominance signal processing circuit.

Fig. 9 is a circuit diagram showing an example of the four-phase logic circuit shown in Fig. 8.

Fig. 10 is a timing chart for explaining an operation of the circuit in Fig. 9.

Fig. 11 is a block diagram showing an example of a phase shift circuit used in the first and the second embodiments of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a block diagram showing a chrominance signal processing circuit according to a first embodiment of the present invention. The first embodiment, as well as the conventional example shown in Fig. 3, converts a low-frequency converted and recorded chrominance signal into a high-frequency signal in a reproduction system of a video signal in VTR, and at the same time removes a cross-talk, and its structure is the same as that of a circuit in Fig. 3 except the following points.

More specifically, in place of the first oscillation circuit 10 in Fig. 3, a first oscillation circuit 23 having a free running frequency of $4f_{SC}$ is provided, and an oscillation signal of $4f_{SC}$ is applied to one input of a second frequency converting circuit 17, at the same time its frequency is divided into 1/2 in a first frequency dividing circuit 24 to become a signal of $2f_{SC}$. The signal of $2f_{SC}$ is applied to a comb filter 5 and a luminance signal processing circuit 22, at the same time its frequency is further divided into 1/2 in a second frequency dividing circuit 25 to be a signal of f_{SC} , so that the same is applied to one input of a phase comparator circuit 9.

On the other hand, an output of a second VCO 26 having a free running frequency of $320f_H$ is frequency-divided into 1/2 by a third frequency dividing circuit 27 to become a signal of $160f_H$, so that the same is applied to the other input of the second frequency converting circuit 17. An output of the second frequency converting circuit 17 is applied to a band pass filter 28 of a structure in Fig. 6 having high Q, and the band pass filter 28 extracts a signal of $4(f_{SC} + 40f_H)$ in the output of the second frequency converting circuit 17 and applies the same to a phase shift circuit 29. The phase shift circuit 29 is formed of a 1/4 frequency dividing circuit 30 for generating four frequency-divided output signals which are out of phase by 90° by dividing into 1/4 a frequency of an output signal of the band pass filter 28, and a four-phase logic circuit 31 for selecting every 1H any of the four frequency-divided outputs out of phase by 90° .

As shown in Fig. 11, the phase shift circuit 29 can be formed of two D-type flip-flops F1 and F2, wherein signals $\phi_1 - \phi_4$ out of phase by 90° outputted from the flip-flops are sequentially selected by a selecting circuit 600 to be outputted.

Since the embodiment of Fig. 1 is directed to a case wherein a video signal of NTSC system is processed, a free running frequency of the second VCO 26 is set to $320f_H$, however, if it is directed to a case wherein a video signal of PAL system is processed, the free running frequency of the second VCO 26 can be set to $321f_H$.

Now, an operation of the first embodiment shown in Fig. 1 will be described. In Fig. 1, as in Fig. 3, a chro-

minance signal of f_{sc} generated from the comb filter 5 is applied to the burst extracting circuit 7 and only a burst signal is extracted to be applied to one input of the phase comparator circuit 9. On the other hand, a signal of $4f_{sc}$ from the first oscillation circuit 23 is frequency-divided into $1/4$ in the first and the second frequency dividing circuits 24 and 25 to be a signal of f_{sc} , then applied to the other input of the phase comparator circuit 9. As a result, in the phase comparator circuit 9, phases are intermittently compared and its error output is applied through the low pass filter 11 to the second VCO 26. Then, an oscillating output of $320f_H$ of the second VCO 26 is frequency-divided into $1/2$ by the third frequency dividing circuit 27 to be an oscillating output of $160f_H$, whereby the same is applied to one input of the second frequency converting circuit 17.

On the other hand, a signal of $4f_{sc}$ from the first oscillation circuit 23 is directly applied to the other input of the second frequency converting circuit 17, and both signals are multiplied in the second frequency converting circuit 17. As a result, a signal of $4(f_{sc} \pm 40f_H)$ is applied from the second frequency converting circuit 17 to the band pass filter 28. As is obvious from Fig. 1, since the signal of $4(f_{sc} \pm 40f_H)$ has not been subjected to a phase shift of every $1H$ yet, it does not contain a side band component having an offset of $f_H/4$. Therefore, as the band pass filter 28, the one formed as in Fig. 6 and having filter characteristics of Fig. 4 can be used.

The signal of $4(f_{sc} + 40f_H) \approx 4 \times 4.21\text{MHz}$ which has passed through the band pass filter 28 is frequency-divided into $1/4$ in the $1/4$ frequency dividing circuit 30 to be a signal of $f_{sc} + 40f_H$ and four signals of $(f_{sc} + 40f_H)$ which are further out of phase by 90° are supplied to the four-phase logic circuit 31. Thus, a signal of $(f_{sc} + 40f_H)$ is generated at an output terminal of the four-phase logic circuit 31 every $1H$ with its phase shifted by 90° and supplied to the first frequency converting circuit 3. An operation in a following stage of the first frequency converting circuit 3 is the same as that of the prior art in Fig. 3.

On the other hand, since a signal of $2f_{sc}$ which is obtained by dividing a frequency of a signal of $4f_{sc}$ into $1/2$ is obtained at an output terminal of the first frequency dividing circuit 24 as described above, the signal can be used for an operation of an delay line (not shown) of the comb filter 5 and a noise removing circuit (not shown) of the luminance signal processing circuit 22.

As the foregoing, according to the first embodiment of the present invention, since a signal of $4(f_{sc} + 40f_H)$ is obtained as an output of the second frequency converting circuit 17, a four-phase signal can be easily generated by using a highly precise phase shift circuit as shown in Fig. 11, and complication of a circuit structure can be prevented.

Fig. 2 is a block diagram showing a chrominance

signal processing circuit according to a second embodiment of the present invention. In the second embodiment, a frequency of a chrominance signal to be recorded is converted into a low-frequency in a recording system of a video signal in VTR.

More specifically, a video signal to be recorded is inputted from a tuner and the like (not shown) to an input terminal 32. Only a chrominance signal of 3.58MHz in the inputted video signal passes through a band pass filter 33 to be inputted to a first frequency converting circuit 3 and applied to a burst extracting circuit 7. The burst extracting circuit 7 extracts a burst signal from the chrominance signal in response to a burst gate pulse supplied from a terminal 8 for applying the same to one input of a phase comparator circuit 34. On the other hand, an oscillating output of $4f_{sc}$ of a first voltage controlled crystal oscillation circuit (VXO) is frequency-divided by first and second frequency dividing circuits 24 and 25 to be applied to the other input of the phase comparator circuit 34. Then, since the first VXO 23 is controlled by an error output of the phase comparator circuit 34, the VXO 23 oscillates in synchronization with the burst signal and applies an oscillating output signal of $4f_{sc}$ to a second frequency converting circuit 17.

On the other hand, a horizontal synchronizing signal separated from the video signal is inputted from a terminal 35 and applied to one input of a phase comparator circuit 36. In addition, an oscillating output of a second VCO 26 oscillated at $320f_H$ is frequency-divided into $1/320$ by a $1/320$ frequency dividing circuit 37 to be a signal of f_H and the same applied to the other input of the phase comparator circuit 36. Then, in the phase comparator circuit 36, phases of the both signals are compared and its error output is applied to the second VCO 26 through a low pass filter 38. Therefore, the second VCO 26 oscillates in synchronization with the horizontal synchronizing signal. An oscillation output of the VCO 26 is frequency-divided into $1/2$ in a third frequency dividing circuit 39 to be a signal of $160f_H$ and the same is applied to one input of the second frequency converting circuit 17.

As a result, a signal of $4(f_{sc} \pm 40f_H)$ is generated at an output terminal of the second frequency circuit 17, so that only a signal of $4(f_{sc} + 40f_H)$ is extracted by the band pass filter 28 and applied to a phase shift circuit 29. The phase shift circuit 29 operates as the phase shift circuit 29 in Fig. 1. The signal of f_{sc} and the signal of $(f_{sc} + 40f_H)$ are multiplied in the first frequency converting circuit so that a signal of $(f_{sc} + 40f_H) \pm f_{sc}$ which is a component of the sum and the difference is applied to a low pass filter 40. Then, only the signal of $40f_H$ is extracted to be supplied to an output terminal 41. Also in this case, a signal of $2f_{sc}$ can be obtained from an output terminal of the first frequency dividing circuit 24.

As the foregoing, according to the second embodiment of the present invention, since a signal of 4

($f_{SC} + 40f_H$) is obtained at an output of the second frequency converting circuit 17, a four-phase signal can be generated by using a highly precise phase shift circuit as shown in Fig. 11.

In addition, according to the above described first and second embodiments, since a signal of $2f_{SC}$ can be generated only by frequency-dividing an oscillating output of $4f_{SC}$ of the first VCO, a multiplying circuit, a 90° phase shift circuit and a band pass filter which are required in the prior art shown in Fig. 3 are unnecessary, so that the number of the circuit elements and externally provided parts of the IC is further decreased.

In addition, the band-pass filter 28 thus formed as in Fig. 6 can be contained in IC if it can be implemented as an active filter.

Although the present invention has been described and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the scope of the present invention being limited only by the terms of the appended claims.

Claims

1. A chrominance signal processing circuit for converting a frequency band of a chrominance signal in a reproduced video signal into a high-frequency, comprising:
 - first frequency converting means (3) for receiving said chrominance signal and converting a frequency of the received chrominance signal,
 - first oscillating means (23) for supplying a signal of a first predetermined frequency,
 - second oscillating means (26) whose oscillation frequency is controlled corresponding to a phase difference between a burst signal in said reproduced video signal and an output signal of said first oscillating means for supplying a signal of a second predetermined frequency,
 - second frequency converting means (17) for receiving output signals of said first and second oscillating means for generating a signal having a frequency of $4n(f_{SC} \pm 40f_H)$, wherein n is an integer, f_{SC} is a chrominance subcarrier frequency, and f_H is a horizontal frequency,
 - filter means (28) for passing a signal having a frequency of $4n(f_{SC} + 40f_H)$ in the output signal of said second frequency converting means, characterized by
 - means (29) for dividing by 4 the frequency of a signal of $4n(f_{SC} + 40f_H)$ outputted from said filter means and shifting the phase of the frequency-divided signal by 90° every one horizontal period,
 - the output signal of said phase shifting

means being applied to said first frequency converting means, and said first frequency converting means converting a frequency of said chrominance signal by multiplying said chrominance signal and the output signal of said means (29).

2. A chrominance signal processing circuit according to claim 1, wherein
 - said second frequency converting means (17) generates a signal having a frequency of $4(f_{SC} \pm 40f_H)$, and said filter means (28) passes a signal having a frequency of $4(f_{SC} + 40f_H)$.
3. A chrominance signal processing circuit according to claim 2, wherein
 - said first predetermined frequency is $4f_{SC}$, and said second predetermined frequency is $160f_H$.
4. A chrominance signal processing circuit according to claim 1, wherein
 - said means (29) comprises
 - second frequency dividing means (30) for dividing by 4 the frequency of the output signal of said filter means (28) to generate four frequency-divided outputs which are out of phase by 90° from each other, and
 - four-phase logic means (31) for sequentially switching said four frequency-divided outputs every horizontal period to the output.
5. A chrominance signal processing circuit according to claim 4, further comprising noise removing means (5) driven by an output of said first oscillating means (23) for removing a noise in a chrominance signal outputted from said first frequency converting means (3).
6. A chrominance signal processing circuit for converting a frequency band of a chrominance signal in a video signal to be recorded into a low-frequency, comprising:
 - first frequency converting means (3) for receiving said chrominance signal and converting a frequency of the received chrominance signal,
 - first oscillating means (23) oscillating in synchronization with a burst signal in said video signal to be recorded for supplying a signal of a first predetermined frequency,
 - second oscillating means (26) oscillating in synchronization with a horizontal synchronizing signal in said video signal to be recorded for supplying a signal of a second predetermined frequency,
 - second frequency converting means (17) for receiving output signals of said first and second oscillating means for generating a signal



($f_{sc} + 40f_H$) is obtained at an output of the second frequency converting circuit 17, a four-phase signal can be generated by using a highly precise phase shift circuit as shown in Fig. 11.

In addition, according to the above described first and second embodiments, since a signal of $2f_{sc}$ can be generated only by frequency-dividing an oscillating output of $4f_{sc}$ of the first VCO, a multiplying circuit, a 90° phase shift circuit and a band pass filter which are required in the prior art shown in Fig. 3 are unnecessary, so that the number of the circuit elements and externally provided parts of the IC is further decreased.

In addition, the band-pass filter 28 thus formed as in Fig. 6 can be contained in IC if it can be implemented as an active filter.

Although the present invention has been described and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the scope of the present invention being limited only by the terms of the appended claims.

Claims

1. A chrominance signal processing circuit for converting a frequency band of a chrominance signal in a reproduced video signal into a high-frequency, comprising:

first frequency converting means (3) for receiving said chrominance signal and converting a frequency of the received chrominance signal,

first oscillating means (23) for supplying a signal of a first predetermined frequency,

second oscillating means (26) whose oscillation frequency is controlled corresponding to a phase difference between a burst signal in said reproduced video signal and an output signal of said first oscillating means for supplying a signal of a second predetermined frequency,

second frequency converting means (17) for receiving output signals of said first and second oscillating means for generating a signal having a frequency of $4n(f_{sc} \pm 40f_H)$, wherein n is an integer, f_{sc} is a chrominance subcarrier frequency, and f_H is a horizontal frequency,

filter means (28) for passing a signal having a frequency of $4n(f_{sc} + 40f_H)$ in the output signal of said second frequency converting means, characterized by

means (29) for dividing by 4 the frequency of a signal of $4n(f_{sc} + 40f_H)$ outputted from said filter means and shifting the phase of the frequency-divided signal by 90° every one horizontal period,

the output signal of said phase shifting

means being applied to said first frequency converting means, and said first frequency converting means converting a frequency of said chrominance signal by multiplying said chrominance signal and the output signal of said means (29).

2. A chrominance signal processing circuit according to claim 1, wherein

said second frequency converting means (17) generates a signal having a frequency of $4(f_{sc} \pm 40f_H)$, and said filter means (28) passes a signal having a frequency of $4(f_{sc} + 40f_H)$.

3. A chrominance signal processing circuit according to claim 2, wherein

said first predetermined frequency is $4f_{sc}$, and said second predetermined frequency is $160f_H$.

4. A chrominance signal processing circuit according to claim 1, wherein

said means (29) comprises
second frequency dividing means (30) for dividing by 4 the frequency of the output signal of said filter means (28) to generate four frequency-divided outputs which are out of phase by 90° from each other, and

four-phase logic means (31) for sequentially switching said four frequency-divided outputs every horizontal period to the output.

5. A chrominance signal processing circuit according to claim 4, further comprising noise removing means (5) driven by an output of said first oscillating means (23) for removing a noise in a chrominance signal outputted from said first frequency converting means (3).

6. A chrominance signal processing circuit for converting a frequency band of a chrominance signal in a video signal to be recorded into a low-frequency, comprising:

first frequency converting means (3) for receiving said chrominance signal and converting a frequency of the received chrominance signal,

first oscillating means (23) oscillating in synchronization with a burst signal in said video signal to be recorded for supplying a signal of a first predetermined frequency,

second oscillating means (26) oscillating in synchronization with a horizontal synchronizing signal in said video signal to be recorded for supplying a signal of a second predetermined frequency,

second frequency converting means (17) for receiving output signals of said first and second oscillating means for generating a signal



having a frequency of $4n (f_{sc} \pm 40f_H)$, and

filter means (28) for passing a signal having a frequency of $4n (f_{sc} + 40f_H)$ in the output signal of said second frequency converting means, characterized by

means (29) for dividing by 4 the frequency of a signal of $4n (f_{sc} + 40f_H)$ outputted from said filter means and shifting the phase of the frequency-divided signal by 90° each horizontal period,

an output signal of said means (29) being applied to said first frequency converting means, and said first frequency converting means converting a frequency of said chrominance signal by multiplying said chrominance signal and the output signal of said means (29).

7. A chrominance signal processing circuit according to claim 6, wherein

said second frequency converting means generates a signal having a frequency of $4 (f_{sc} \pm 40f_H)$, and said filter means passes a signal having a frequency of $4 (f_{sc} + 40f_H)$.

8. A chrominance signal processing circuit according to claim 6, wherein

said means (29) comprises

second frequency dividing means (30) for dividing by 4 the frequency of the output signal of said filter means to generate four frequency-divided outputs which are out of phase by 90° from each other, and

four-phase logic means (31) for sequentially switching said four frequency-divided outputs every horizontal period to the output.

9. A video tape recorder having a function of processing a chrominance signal by which a frequency band of the chrominance signal in a reproduced video signal is converted into a high-frequency, comprising:

first frequency converting means (3) for receiving said chrominance signal and converting a frequency of the received chrominance signal,

first oscillating means (23) for supplying a signal of a first predetermined frequency,

second oscillating means (26) whose oscillation frequency is controlled corresponding to a phase difference between a burst signal in said reproduced video signal and an output signal of said first oscillating means for supplying a signal of a second predetermined frequency,

second frequency converting means (17) for receiving output signals of said first and second oscillating means for generating a signal having a frequency of $4n (f_{sc} \pm 40f_H)$,

filter means (28) for passing a signal hav-

ing a frequency of $4 (f_{sc} + 40f_H)$ in the output signal of said second frequency converting means, and

means (29) for dividing by 4 the frequency of a signal of $4n (f_{sc} + 40f_H)$ outputted from said filter means and shifting the phase of the frequency-divided signal by 90° each horizontal period,

an output signal of said means (29) being applied to said first frequency converting means, and said first frequency converting means converting a frequency of said chrominance signal by multiplying said chrominance signal and the output signal of said means (29).

10. A video tape recorder having a function of processing a chrominance signal by which a frequency band of a chrominance signal in a video signal to be recorded is converted into a low-frequency, comprising:

first frequency converting means (3) for receiving said chrominance signal and converting a frequency of the received chrominance signal,

first oscillating means (23) oscillating in synchronization with a burst signal in said video signal to be recorded for supplying a signal of a first predetermined frequency,

second oscillating means (26) oscillating in synchronization with a horizontal synchronizing signal in said video signal to be recorded for supplying a signal of a second predetermined frequency,

second frequency converting means (17) for receiving output signals of said first and second oscillating means for generating a signal having a frequency of $4n (f_{sc} \pm 40f_H)$,

filter means (28) for passing a signal having a frequency of $4n (f_{sc} + 40f_H)$ in the output signal of said second frequency converting means, and

means (29) for dividing by 4 the frequency of a signal of $4n (f_{sc} + 40f_H)$ outputted from said filter means and shifting the phase of the frequency-divided signal by 90° every one horizontal period,

an output signal of said means (29) being applied to said first frequency converting means, and said first frequency converting means converting a frequency of said chrominance signal by multiplying said chrominance signal and the output signal of said means (29).

Patentansprüche

1. Chrominanzsignalverarbeitungsschaltung zur Wandlung eines Frequenzbandes eines Chromi-



- nanzsignals in einem wiedergegebenen Videosignal in eine Hochfrequenz mit:
 ersten Frequenzumwandlungsmitteln (3), um das Chrominanzsignal zu empfangen und eine Frequenz des empfangenen Chrominanzsignals umzuwandeln,
 einem ersten Oszillatormittel (23), um ein Signal einer ersten bestimmten Frequenz zu liefern,
 einem zweiten Oszillatormittel (26), dessen Schwingungsfrequenz entsprechend einer Phasendifferenz zwischen einem Farbsynchronsignal im wiedergegebenen Videosignal und einem Ausgabesignal des ersten Oszillatormittels gesteuert wird, um ein Signal einer zweiten bestimmten Frequenz zu liefern, zweiten Frequenzumwandlungsmitteln (17), um Ausgabesignale des ersten und des zweiten Oszillatormittels zu empfangen und ein Signal mit einer Frequenz von $4n(f_{sc} \pm 40 f_H)$ zu erzeugen, wobei n eine ganze Zahl ist, f_{sc} eine Chrominanzzwischensträgerfrequenz ist, und f_H eine Horizontal-Frequenz ist,
 einem Filtermittel (28), um ein Signal mit einer Frequenz von $4n(f_{sc} + 40 f_H)$ in dem Ausgabesignal des zweiten Frequenzumwandlungsmittels durchzulassen,
 gekennzeichnet durch
 Mittel (29), um die Frequenz eines Signals von $4n(f_{sc} + 40 f_H)$, das von den Filtermitteln ausgegeben wird, durch 4 zu teilen und um die Phase des frequenzgeteilten Signals um 90° in jedem Horizontal-Zeitabschnitt zu verschieben, wobei das Ausgabesignal des Phasenverschiebungsmittels dem ersten Frequenzumwandlungsmittel angelegt wird und das erste Frequenzumwandlungsmittel eine Frequenz des Chrominanzsignals umwandelt, indem er das Chrominanzsignal und das Ausgabesignal des Mittels (29) miteinander multipliziert.
2. Chrominanzsignalverarbeitungsschaltung nach Anspruch 1, bei der das zweite Frequenzumwandlungsmittel (17) ein Signal mit einer Frequenz von $4(f_{sc} \pm 40 f_H)$ erzeugt, und das Filtermittel (28) ein Signal mit einer Frequenz von $4(f_{sc} + 40 f_H)$ durchläßt.
 3. Chrominanzsignalverarbeitungsschaltung nach Anspruch 2, bei der die erste vorbestimmte Frequenz gleich $4 f_{sc}$ und die zweite vorbestimmte Frequenz gleich $160 f_H$ ist.
 4. Chrominanzsignalverarbeitungsschaltung nach Anspruch 1, bei der das Mittel (29) umfaßt:
 ein zweites Frequenzteilermittel (30), um die Frequenz des Ausgabesignals des Filtermittels (28) durch vier zu teilen, um vier frequenzgeteilte Ausgaben zu erzeugen, welche voneinander jeweils um 90° außer Phase sind, und
 ein 4-Phasen-Logikmittel (31), um nacheinander die vier frequenzgeteilten Ausgaben in jedem Horizontal-Zeitabschnitt auf den Ausgang zu schalten.
 5. Chrominanzsignalverarbeitungsschaltung nach Anspruch 4, die zusätzlich Rauschentfernungsmittel (5) umfaßt, welche durch eine Ausgabe der ersten Oszillatormittel (23) betrieben werden, um ein Rauschen in einem von dem ersten Frequenzumwandlungsmittel (3) ausgegebene Chrominanzsignal zu entfernen.
 6. Chrominanzsignalverarbeitungsschaltung zur Wandlung eines Frequenzbandes eines Chrominanzsignal in einem aufzuzeichnenden Videosignal in eine niedrige Frequenz mit:
 einem ersten Frequenzumwandlungsmittel (3), um das Chrominanzsignal zu empfangen und eine Frequenz des empfangenen Chrominanzsignals umzuwandeln,
 einem ersten Oszillatormittel (23), das synchron mit einem Farbsynchronsignal in dem aufzuzeichnenden Videosignal schwingt, um ein Signal einer ersten vorgegebenen Frequenz zu liefern,
 einem zweiten Oszillatormittel (26), das synchron mit einem horizontalen Synchronisierungssignal in dem aufzuzeichnenden Videosignal schwingt, um ein Signal einer zweiten vorgegebenen Frequenz zu liefern,
 einem zweiten Frequenzumwandlungsmittel (17), um die Ausgabesignale des ersten und des zweiten Oszillatormittels zu empfangen und ein Signal mit einer Frequenz von $4n(f_{sc} \pm 40 f_H)$ zu erzeugen, und
 einem Filtermittel (28), um ein Signal mit einer Frequenz von $4n(f_{sc} + 40 f_H)$ im Ausgabesignal des zweiten Frequenzumwandlungsmittels durchzulassen,
 gekennzeichnet durch
 Mittel (29), um die Frequenz eines Signals von $4n(f_{sc} + 40 f_H)$, das von dem Filtermittel ausgegeben wird, durch vier zu dividieren und die Phase des frequenzgeteilten Signals um 90° in jedem Horizontal-Zeitabschnitt zu verschieben, wobei ein Ausgabesignal des Mittels (29) auf dem ersten Frequenzumwandlungsmittel angelegt wird und das erste Frequenzumwandlungsmittel eine Frequenz des Chrominanzsignals umwandelt, indem es das Chrominanzsignal und das Ausgabesignal des Mittels (29) miteinander multipliziert.
 7. Chrominanzsignal-Verarbeitungsschaltung nach Anspruch 6, bei der das zweite Frequenzumwandlungsmittel ein Signal mit einer Frequenz von $4(f_{sc} \pm 40 f_H)$ er-



zeugt, und das Filtermittel ein Signal mit einer Frequenz von $4(f_{sc} + 40 f_H)$ durchläßt.

8. Chrominanzsignalverarbeitungsschaltung nach Anspruch 6, bei der das Mittel (29) umfaßt:

ein zweites Frequenzteilmittel (30), um die Frequenz des Ausgabesignals des Filtermittels durch vier zu dividieren, um vier frequenzgeteilte Ausgaben zu erzeugen, welche voneinander jeweils um 90° außer Phase sind, und ein 4-Phasen-Logikmittel (31), um die vier frequenzgeteilten Ausgaben während jedes Horizontal-Zeitabschnitts auf den Ausgang zu schalten.

9. Videorekorder mit der Funktion, ein Chrominanzsignal zu verarbeiten, bei welchem ein Frequenzband des Chrominanzsignals in einem wiedergegebenen Videosignal in eine hohe Frequenz umgewandelt wird, mit:

einem ersten Frequenzumwandlungsmittel (3), um das Chrominanzsignal zu empfangen und eine Frequenz des empfangenen Chrominanzsignals umzuwandeln,

einem ersten Oszillatormittel (23), um ein Signal einer ersten vorgegebenen Frequenz zu liefern, einem zweiten Oszillatormittel (26), dessen Schwingungsfrequenz entsprechend einer Phasendifferenz zwischen einem Farbsynchronsignal in dem wiedergegebenen Videosignal und einem Ausgabesignal des ersten Oszillatormittels gesteuert wird, um ein Signal einer zweiten vorgegebenen Frequenz zu liefern,

einem zweiten Frequenzumwandlungsmittel (17), um Ausgabesignale des ersten und des zweiten Oszillatormittels zu empfangen und ein Signal mit einer Frequenz von $4n(f_{sc} \pm 40 f_H)$ zu erzeugen,

einem Filtermittel (28), um ein Signal mit einer Frequenz von $4(f_{sc} + 40 f_H)$ im Ausgabesignal des zweiten Frequenzumwandlungsmittels durchzulassen, und

einem Mittel (29), um die Frequenz eines Signals von $4n(f_{sc} + 40 f_H)$, das von den Filtermitteln ausgegeben wird, durch vier zu dividieren und die Phase des frequenzgeteilten Signals um 90° in jedem Horizontal-Zeitabschnitt zu verschieben, wobei ein Ausgabesignal des Mittels (29) auf dem ersten Frequenzumwandlungsmittel angelegt wird, und wobei das erste Frequenzumwandlungsmittel eine Frequenz des Chrominanzsignals umwandelt, indem es das Chrominanzsignal und das Ausgabesignal des Mittels (29) miteinander multipliziert.

10. Videorekoder mit der Funktion, ein Chrominanzsignal zu verarbeiten, bei dem ein

Frequenzband des Chrominanzsignals in einem aufzuzeichnenden Videosignal in eine niedrige Frequenz umgewandelt wird, mit:

einem ersten Frequenzumwandlungsmittel (3), um das Chrominanzsignal zu empfangen und eine Frequenz des Chrominanzsignals umzuwandeln,

einem ersten Oszillatormittel (23), das synchron mit einem Farbsynchronsignal in dem aufzuzeichnenden Videosignal schwingt, um ein Signal einer ersten vorgegebenen Frequenz zu liefern, einem zweiten Oszillatormittel (26), das synchron mit einem Horizontal-Synchronisiersignal in dem aufzuzeichnenden Videosignal schwingt, um ein Signal einer zweiten vorgegebenen Frequenz zu liefern,

einem zweiten Frequenzumwandlungsmittel (17), um die Ausgabesignale des ersten und des zweiten Oszillatormittels zu empfangen und ein Signal mit einer Frequenz von $4n(f_{sc} \pm 40 f_H)$ zu erzeugen,

einem Filtermittel (128), um ein Signal mit einer Frequenz von $4n(f_{sc} + 40 f_H)$ in dem Ausgabesignal des zweiten Frequenzumwandlungsmittels durchzulassen, und

einem Mittel (29), um die Frequenz eines Signals von $4n(f_{sc} + 40 f_H)$, das von den Filtermitteln ausgegeben wird, durch vier zu dividieren und die Phase der frequenzdividierten Signale um 90° in jedem Horizontal-Zeitabschnitt zu verschieben, wobei ein Ausgabesignal des Mittels (29) dem ersten Frequenzumwandlungsmittel angelegt wird und wobei das erste Frequenzumwandlungsmittel eine Frequenz des Chrominanzsignals umwandelt, indem es das Chrominanzsignal und das Ausgabesignal des Mittels (29) miteinander multipliziert.

Revendications

1. Circuit de traitement de signal de chrominance pour convertir en haute fréquence une bande de fréquence d'un signal de chrominance d'un signal vidéo reproduit, comprenant :

un premier moyen convertisseur de fréquence (3) pour recevoir ledit signal de chrominance et convertir une fréquence du signal de chrominance reçu,

un premier moyen d'oscillateur (23) pour procurer un signal à une première fréquence prédéterminée,

un second moyen d'oscillateur (26) dont la fréquence d'oscillation est commandée suivant la différence de phase entre un signal de save dudit signal vidéo reproduit et un signal de sortie dudit premier moyen d'oscillateur afin de procurer un signal à une seconde fréquence prédéter-



minée,

un second moyen convertisseur de fréquence (17) pour recevoir les signaux de sortie desdits premier et second moyens d'oscillateur afin de générer un signal présentant une fréquence $4n (f_{sc} \pm 40f_H)$, dans lequel n est un nombre entier, f_{sc} est une fréquence de sous-porteuse de chrominance, et f_H est une fréquence horizontale,

un moyen de filtrage (28) pour laisser passer un signal d'une fréquence $4n (f_{sc} + 40f_H)$ dans le signal de sortie dudit second moyen convertisseur de fréquence, caractérisé en ce que

le moyen (29) pour diviser par 4 la fréquence d'un signal $4n (f_{sc} + 40f_H)$ qui sort dudit moyen de filtre et décaler la phase du signal divisé en fréquence de 90° pour chaque période horizontale, le signal de sortie dudit moyen de déphasage étant appliqué audit premier moyen convertisseur de fréquence, et ledit premier moyen convertisseur de fréquence convertissant la fréquence dudit signal de chrominance en multipliant ledit signal de chrominance et le signal de sortie dudit moyen (29).

2. Circuit de traitement de signal de chrominance selon la revendication 1, dans lequel

ledit second moyen convertisseur de fréquence (17) produit un signal ayant une fréquence $4 (f_{sc} \pm 40f_H)$, et ledit moyen de filtre (28) laisse passer un signal à une fréquence $4 (f_{sc} + 40f_H)$.

3. Circuit de traitement de signal de chrominance selon la revendication 2, dans lequel

ladite première fréquence prédéterminée est $4f_{sc}$, et ladite seconde fréquence prédéterminée est $160f_H$.

4. Circuit de traitement de signal de chrominance selon la revendication 1, dans lequel

ledit moyen (29) comprend un second moyen diviseur de fréquence (30) pour diviser par 4 la fréquence du signal de sortie dudit moyen de filtre (28) afin de produire quatre sorties divisées en fréquence qui sont déphasées de 90° l'une de l'autre, et

un moyen logique à quatre phases (31) pour commuter séquentiellement lesdites quatre sorties divisées en fréquence à chaque période horizontale vers la sortie.

5. Circuit de traitement de signal de chrominance selon la revendication 4, comprenant de plus un moyen de suppression de bruit (5) commandé par une sortie dudit premier moyen d'oscillateur (23) afin de supprimer le bruit dans un signal de chrominance qui sort du premier moyen convertisseur de fréquence (3).

6. Circuit de traitement de signal de chrominance pour convertir en basse fréquence une bande de fréquence d'un signal de chrominance d'un signal vidéo qui doit être enregistré, comprenant :

un premier moyen convertisseur de fréquence (3) pour recevoir ledit signal de chrominance et convertir une fréquence du signal de chrominance reçu,

un premier moyen d'oscillateur (23) oscillant en synchronisme avec un signal de salve dudit signal vidéo qui doit être enregistré afin de produire un signal à une première fréquence prédéterminée,

un second moyen d'oscillateur (26) oscillant en synchronisme avec un signal de synchronisation horizontal dudit signal vidéo qui doit être enregistré afin de produire un signal à une seconde fréquence prédéterminée,

un second moyen convertisseur de fréquence (17) pour recevoir les signaux de sortie desdits premier et second moyens d'oscillateur afin de produire un signal présentant une fréquence $4n (f_{sc} \pm 40f_H)$, et

un moyen de filtrage (28) pour laisser passer un signal à une fréquence $4n (f_{sc} + 40f_H)$ dans le signal de sortie dudit second moyen convertisseur de fréquence, caractérisé en ce que

le moyen (29) pour diviser par 4 la fréquence d'un signal $4n (f_{sc} + 40f_H)$ qui sort dudit moyen de filtrage et pour décaler la phase du signal divisé en fréquence de 90° à chaque période horizontale,

un signal de sortie dudit moyen (29) étant appliqué audit premier moyen convertisseur de fréquence, et ledit premier moyen convertisseur de fréquence convertissant une fréquence dudit signal de chrominance en multipliant ledit signal de chrominance et le signal de sortie dudit moyen (29).

7. Circuit de traitement de signal de chrominance selon la revendication 6, dans lequel

ledit second moyen convertisseur de fréquence produit un signal présentant une fréquence $4 (f_{sc} \pm 40f_H)$, et ledit moyen de filtre laisse passer un signal à une fréquence de $4 (f_{sc} + 40f_H)$.

8. Circuit de traitement de signal de chrominance selon la revendication 6, dans lequel

ledit moyen (29) comporte

un second moyen diviseur de fréquence (30) pour diviser par 4 la fréquence du signal de sortie dudit moyen de filtre afin de produire quatre sorties divisées en fréquence qui sont déphasées de 90° l'une de l'autre, et

un moyen logique à quatre phases (31) pour commuter séquentiellement lesdites quatre



sorties divisées en fréquence à chaque période horizontale vers la sortie.

9. Magnétoscope comprenant une fonction de traitement d'un signal de chrominance par laquelle une bande de fréquence du signal de chrominance d'un signal vidéo reproduit est converti en haute fréquence, comprenant :
- un premier moyen convertisseur de fréquence (3) pour recevoir ledit signal de chrominance et convertir une fréquence du signal de chrominance reçu,
 - un premier moyen d'oscillateur (23) pour procurer un signal à une première fréquence prédéterminée,
 - un second moyen d'oscillateur (26) dont la fréquence d'oscillation est commandée en correspondance avec la différence de phase entre un signal de salve dudit signal vidéo reproduit et un signal de sortie dudit premier moyen d'oscillateur afin de produire un signal à une seconde fréquence prédéterminée,
 - un second moyen convertisseur de fréquence (17) pour recevoir les signaux de sortie desdits premier et second moyens d'oscillateur afin de produire un signal à une fréquence $4n (f_{sc} \pm 40f_H)$,
 - un moyen de filtrage (28) pour laisser passer un signal à une fréquence $4 (f_{sc} + 40f_H)$ du signal de sortie dudit second moyen convertisseur de fréquence, et
 - un moyen (29) pour diviser par 4 la fréquence d'un signal $4n (f_{sc} + 40f_H)$ qui sort dudit moyen de filtre et décaler la phase du signal divisé en fréquence de 90° à chaque période horizontale,
 - un signal de sortie dudit moyen (29) étant appliqué audit premier moyen convertisseur de fréquence, et ledit premier moyen convertisseur de fréquence convertissant une fréquence dudit signal de chrominance en multipliant ledit signal de chrominance et le signal de sortie dudit moyen (29).
10. Magnétoscope comportant une fonction de traitement d'un signal de chrominance par laquelle une bande de fréquence d'un signal de chrominance d'un signal vidéo qui doit être enregistré est convertie en basse fréquence, comprenant :
- un premier moyen convertisseur de fréquence (3) pour recevoir ledit signal de chrominance et convertir une fréquence du signal de chrominance reçu,
 - un premier moyen d'oscillateur (23) oscillant en synchronisme avec le signal de salve dudit signal vidéo qui doit être enregistré afin de produire un signal à une première fréquence prédéterminée,

un second moyen d'oscillateur (26) oscillant en synchronisme avec un signal de synchronisation horizontale dudit signal vidéo qui doit être enregistré afin de produire un signal à une seconde fréquence prédéterminée,

un second moyen convertisseur de fréquence (17) pour recevoir les signaux de sortie desdits premier et second moyens d'oscillateur afin de produire un signal à une fréquence $4n (f_{sc} \pm 40f_H)$,

un moyen de filtre (128) pour laisser passer un signal à une fréquence $4n (f_{sc} + 40f_H)$ du signal de sortie dudit second moyen convertisseur de fréquence, et

un moyen (29) pour diviser par 4 la fréquence d'un signal $4n (f_{sc} + 40f_H)$ qui sort dudit moyen de filtre et décaler la phase du signal divisé en fréquence de 90° à chaque période horizontale,

un signal de sortie dudit moyen (29) étant appliqué audit premier moyen convertisseur de fréquence, et ledit premier moyen convertisseur de fréquence convertissant une fréquence dudit signal de chrominance en multipliant ledit signal de chrominance et le signal de sortie dudit moyen (29).