

ULTRASOUND CONTRAST AGENT DOSAGE FORMULATION

Background of the Invention

The present invention is in the general field of diagnostic imaging agents, and is particularly directed to specific ultrasound contrast agent dosage formulations that provide enhanced images and images of long duration.

When using ultrasound to obtain an image of the internal organs and structures of a human or animal, ultrasound waves, waves of sound energy at a frequency above that discernable by the human ear, are reflected as they pass through the body. Different types of body tissue reflect the ultrasound waves differently and the reflections that are produced by the ultrasound waves reflecting off different internal structures are detected and converted electronically into a visual display.

For some medical conditions, obtaining a useful image of the organ or structure of interest is especially difficult because the details of the structure are not adequately discernible from the surrounding tissue in an ultrasound image produced by the reflection of ultrasound waves absent a contrast-enhancing agent. Detection and observation of certain physiological and pathological conditions may be substantially improved by enhancing the contrast in an ultrasound image by administering an ultrasound contrast agent to an organ or other structure of interest. In other cases, detection of the movement of the ultrasound contrast agent itself is particularly important. For example, a distinct blood flow pattern that is known to result from particular cardiovascular abnormalities may only be discernible by administering the ultrasound contrast agent to the bloodstream and observing either blood flow or blood volume.

Materials that are useful as ultrasound contrast agents operate by having an effect on ultrasound waves as they pass through the body and are reflected to create the image from which a medical diagnosis is made. Different types of substances affect ultrasound waves in different ways and to varying degrees. Moreover, certain of the effects caused by contrast-enhancing agents are more readily measured and observed than others. In selecting an ideal composition for an ultrasound contrast agent, one would

prefer the substance that has the most dramatic effect on the ultrasound wave as it passes through the body. Also, the effect on the ultrasound wave should be easily measured. Gases are the preferred media for use as ultrasound contrast agents. The gas must be stabilized prior to usage as either surfactant
5 stabilized bubbles or by encapsulating in liposomes or microparticles. There are three main contrast-enhancing effects which can be seen in an ultrasound image: backscatter, beam attenuation, and speed of sound differential.

A variety of natural and synthetic polymers have been used to encapsulate ultrasound contrast agents, such as air, in an effort to make an
10 ultrasound contrast agent that lasts longer following administration. Schneider *et al.*, Invest. Radiol., Vol. 27, pp. 134-139 (1992) describes three micron, air-filled, synthetic, polymer particles. These particles were reported to be stable in plasma and under applied pressure. However, at 2.5 MHz, their echogenicity was low. Another type of microbubble suspension has
15 been obtained from sonicated albumin. Feinstein *et al.*, J. Am. Coll. Cardiol., Vol. 11, pp. 59-65 (1988). Feinstein describes the preparation of microbubbles that are appropriately sized for transpulmonary passage with excellent stability *in vitro*. However, these microbubbles are short-lived *in vivo*, having a half-life on the order of a few seconds (which is
20 approximately equal to one circulation pass) because of their instability under pressure. Gottlieb, S. *et al.*, J. Am. Soc. Echo., Vol. 3, pp. 328 (1990), Abstract; and Shapiro, J.R. *et al.*, J. Am. Coll. Cardiol., Vol. 16, pp. 1603-1607 (1990).

Gelatin-encapsulated microbubbles have also been described in WO
25 80/02365 by Rasor Associates, Inc. These are formed by "coalescing" the gelatin. Gas microbubbles encapsulated within a shell of a fluorine-containing material are described in WO 96/04018 by Molecular Biosystems, Inc.

Microbubbles stabilized by microcrystals of galactose (SHU 454 and
30 SHU 508) have also been reported by Fritzsch *et al.* Fritzsch, T. *et al.*, Invest. Radiol. Vol. 23 (Suppl 1), pp. 302-305 (1988); and Fritzsch, T. *et al.*, Invest. Radiol., Vol. 25 (Suppl 1), 160-161 (1990). The microbubbles last up to 15 minutes *in vitro* but less than 20 seconds *in vivo*. Rovai, D. *et al.*, J. Am.

Coll. Cardiol., Vol. 10, pp. 125-134 (1987); and Smith, M. *et al.*, J. Am. Coll. Cardiol., Vol. 13, pp. 1622-1628 (1989). EP 398 935 by Schering Aktiengesellschaft discloses the preparation and use of microencapsulated gas or volatile liquids for ultrasound imaging, where the microcapsules are
5 formed of synthetic polymers or polysaccharides. European Patent 458 745 by Sintetica discloses air or gas microballoons bounded by an interfacially deposited polymer membrane that can be dispersed in an aqueous carrier for injection into a host animal or for oral, rectal, or urethral administration, for therapeutic or diagnostic purposes.

10 WO 92/18164 by Delta Biotechnology Limited describes the preparation of microparticles by spray drying an aqueous protein solution to form hollow spheres having gas entrapped therein, for use in imaging. WO 93/25242 describes the synthesis of microparticles for ultrasonic imaging consisting of a gas contained within a shell of polycyanoacrylate or
15 polyester. WO 92/21382 discloses the fabrication of microparticle contrast agents which include a covalently bonded matrix containing a gas, wherein the matrix is a carbohydrate. U.S. Patent Nos. 5,334,381, 5,123,414 and 5,352,435 to Unger describe liposomes for use as ultrasound contrast agents, which include gases, gas precursors, such as a pH activated or photo-
20 activated gaseous precursor, as well as other liquid or solid contrast enhancing agents.

Others have looked at the effect of the gas which is encapsulated, and suggested the use of fluorinated gases to enhance imaging as compared to air. U.S. Patent No. 5,393,524 to Quay discloses the use of agents, including
25 perfluorocarbons, for enhancing the contrast in an ultrasound image. The agents consist of small bubbles, or microbubbles, of selected gases, which exhibit long life spans in solution and are small enough to traverse the lungs, enabling their use in ultrasound imaging of the cardiovascular system and other vital organs. EP 554213 by Bracco discloses the use of fluorinated
30 hydrocarbon gases to prevent collapse of microvesicles upon exposure to pressure in the bloodstream. WO 95/23615 by Nycomed discloses microcapsules for imaging which are formed by coacervation of a solution, for example, a protein solution, containing a perfluorocarbon. WO 95/03357

by Massachusetts Institute of Technology discloses microparticles formed of polyethylene glycol-poly(lactide-co-glycolide) block polymers having imaging agents encapsulated therein, including gases such as air and perfluorocarbons. As described in WO 94/16739 by Sonus Pharmaceuticals, Inc., while solids and liquids reflect sound to a similar degree, gases are known to be more efficient and are the preferred media for use as ultrasound contrast agents. In fact, as shown by Example 12 of WO 94/16739, protein microcapsules were dismissed as raising safety concerns (as well as efficacy issues) when administered to mini-pigs. U.S. Patent Numbers 6,132,699 and 5,611,344 both describe methods of enhancing contrast using perfluorocarbon gases in synthetic polymeric shells. U.S. Patent No. 5,837,221 describes a method of making a porous polymeric microparticle having a hydrophobic agent incorporated into the polymer to increase echogenicity.

Several ultrasound contrast agents have been approved in either the United States or Europe for very limited cardiac applications. OPTISON® (Amersham, Mallinkrodt) consists of heat denatured human albumin microcapsules containing the gas octafluoropropane. Each mL of microsphere suspension contains $5-8 \times 10^8$ microspheres with a mean diameter in the 2-4.5 micron size range and 220 µg octafluoropropane. These microspheres have not been approved for myocardial blood flow assessment and have only been approved for ventricular chamber enhancement. At high bolus doses (5 mL suspension or 1100 µg octafluoropropane), ventricular chamber enhancement lasts up to 5 minutes.

DEFINITY® (Bristol Myers Medical Imaging) consists of octafluoropropane containing lipid microspheres where the lipid shell is comprised of the phospholipids DPPA, DPPC, and mPEG-DPPE. Each mL of suspension contains 1.2×10^{10} microparticles having a mean diameter in the 1.1-3.3 micron size range and 1100 µg of octafluoropropane. The agent is only approved for ventricular chamber enhancement and not myocardial blood flow assessment. At a bolus dose of 700 µL (for a 70kg person) or

5133 µg of gas, the agent has an enhancement duration in the ventricular chambers of approximately 3.4 minutes.

IMAGENT® (Photogen Inc.) consists of lipid microspheres containing pefluorohexane where the lipid shell is comprised of the phospholipid DMPC. Each mL of suspension contains 1.4×10^9 microparticles having a mean diameter less than 3 microns and 92 µg of perfluorohexane. The agent is only approved for ventricular chamber enhancement and not myocardial blood flow assessment. At a bolus dose of 0.43 mL (for a 70kg person) or 40 µg of gas, the agent has a mean enhancement duration in the ventricular chambers of approximately 2.6 minutes.

In all cases, these commercial agents have limited utility and are not approved for applications other than ventricular chamber enhancement and provide mean image enhancement durations in the ventricular chambers lasting for periods of 5 minutes or less. There is a lack of commercial ultrasound contrast agents which allow enhanced images of the cardiovascular system, particularly of the myocardium and the ventricular chambers, for long duration. The agents described in the prior art when administered as a bolus or short infusion result in images of the myocardium which last for significantly less time than the amount of time required to conduct a complete examination of the heart. Typically, the prior art agents provide images that last for well below one minute for the myocardium. An agent which can provide enhanced image durations exceeding one minute in the myocardium and/or greater than 5 minutes in the ventricular chambers is desirable.

It is therefore an object of the invention to provide a dosage formulation containing microparticles that provides enhanced images and images of long duration, particularly for cardiac applications.

It is another object of the invention to provide a kit for administering the dosage formulation containing microparticles for use in ultrasound imaging techniques.

Summary of the Invention

Clinical studies have been conducted and specific dosage formulations developed using polymeric microparticles having incorporated therein perfluorocarbon gases that provide significantly enhanced images of long duration. The dosage formulation typically includes one, two or up to five doses, most preferably one or two doses, of microparticles formed of a biocompatible polymer, preferably including a lipid incorporated therein, and containing a perfluorocarbon that is a gas at body temperature. The microparticles are administered to a patient in a dose effective to enhance ultrasound imaging in the ventricular chambers for more than five minutes and/or in the myocardium for more than a minute, and a dose ranging from 0.025 to 8.0 mg microparticles/kg body weight. Preferably the dose administered to a patient ranges from 0.05 to 4.0 mg microparticles/kg body weight. In a preferred embodiment, the ultrasound imaging is enhanced in the ventricular chambers for more than 9 minutes and/or in the myocardium for more than 2 minutes.

The dosage formulation typically is provided in a vial or in a syringe. In a typical formulation, the dosage formulation is in the form of a dry powder that is reconstituted with sterile water prior to use by adding the water to the vial or syringe of the dry powder and shaking to yield an isosmotic or isotonic suspension of microparticles. In the preferred embodiment of this dosage formulation, the suspension contains $1.0 - 3.5 \times 10^9$ microparticles /mL of suspension or 25-50 mg microparticles/mL of suspension with the most preferred concentration yielding a suspension containing $1.5-2.8 \times 10^9$ microparticles/mL of suspension or 30-45 mg microparticles/mL of suspension. In a preferred embodiment, the microparticles have a mean particle size less than 8 microns, most preferably a mean particle size of 1.8-3.0 microns.

In the most preferred embodiment, the gas is CF_4 , C_2F_4 , C_2F_6 , C_3F_6 , C_3F_8 , C_4F_8 , C_4F_{10} , or SF_6 . In preferred embodiments, the gas is n-perfluorobutane (C_4F_{10}) provided in an amount between 75-500 $\mu\text{g/mL}$ of administered volume of microparticle suspension; preferably the n-

perfluorobutane is provided in an amount between 100-400 $\mu\text{g/mL}$ of administered volume of microparticle suspension and most preferably between 150-350 $\mu\text{g/mL}$ of administered volume of microparticle suspension; or the gas is n-octafluoropropane provided in an amount between
5 75-375 $\mu\text{g/mL}$ of administered volume of microparticle suspension, most preferably between 120-300 $\mu\text{g/mL}$ of administered volume of microparticle suspension.

In the most preferred embodiment, the microparticle is formed of a synthetic polymer such as poly(hydroxy acids) which include poly(lactic
10 acid), poly(glycolic acid), and poly(lactic acid-co-glycolic acid), polyglycolides, polylactides, and poly(lactide-co-glycolide), polyanhydrides, polyorthoesters, polyamides, polycarbonates, polyalkylenes such as polyethylene and polypropylene, polyalkylene glycols such as poly(ethylene glycol), polyalkylene oxides such as poly(ethylene oxide) polyvinyl alcohols,
15 poly(valeric acid), and poly(lactide-co-caprolactone), derivatives, copolymers and blends thereof and includes a hydrophobic compound incorporated with the polymer at a ratio of between 0.01 and 30% by weight of hydrophobic compound to weight of polymer, most preferably a lipid incorporated with the polymer at a ratio of between 0.01 and 30% (weight
20 lipid/weight polymer). In a particularly preferred embodiment, the lipid is dioleoylphosphatidylcholine (DOPC), dimyristoylphosphatidylcholine (DMPC), dipentadecanoylphosphatidylcholine (DPDPC) dilauroylphosphatidylcholine (DLPC), dipalmitoylphosphatidylcholine (DPPC), distearoylphosphatidylcholine (DSPC),
25 diarachidoylphosphatidylcholine (DAPC), dibehenoylphosphatidylcholine (DBPC), ditricosanoylphosphatidylcholine (DTPC), dilignoceroylphatidylcholine (DLGPC); or a phosphatidylethanolamine.

Most preferably, the synthetic polymer in the microparticles is poly(lactide-co-glycolide), with a lactide to glycolide ratio of 50:50 (i.e. 1:1)
30 and a weight average molecular weight in the range 20,000-40,000 Daltons, and the hydrophobic compound in the microparticles is DAPC, in a ratio of 5 to 6.6% (weight DAPC/ weight polymer).

The dosage formulation may be provided as a vial or a syringe of dry powder containing microparticles or in a kit including a solution for resuspending the microparticles. Typically the vial or syringe of dry powder will also include excipients such as sugars or salts to make the solution isosmotic or isotonic after reconstitution. This dosage formulation is then administered to a patient to be imaged by injection, either as a bolus or an injection over a period of up to 30 minutes.

The microparticles are useful in a variety of diagnostic imaging procedures including ultrasound imaging, magnetic resonance imaging, fluoroscopy, x-ray, and computerized tomography. The microparticles were tested in clinical trials for cardiology applications such as myocardial blood flow assessment and ventricular chamber enhancement.

Detailed Description of the Invention

Improved methods, microparticles, kits, and dosage formulations for ultrasound imaging are described herein. The microparticles are useful in a variety of diagnostic ultrasound imaging applications, particularly in ultrasound procedures such as blood vessel imaging and echocardiography such as myocardial blood flow assessment, myocardial blood volume assessment and ventricular chamber enhancement.

I. Definitions

As generally used herein, the term "microparticle" includes "microspheres" and "microcapsules", as well as other microparticles, unless otherwise specified. Microparticles may or may not be spherical in shape. "Microcapsules" are defined herein as microparticles having an outer polymer shell surrounding a core of a gas. "Microspheres" as defined herein can be solid polymeric spheres, or porous spheres with a honeycombed structure or sponge like structure formed by pores throughout the polymer that are filled with a gas. Some microspheres may contain an outer polymer shell with a honeycombed structure or a sponge like structure formed by pores throughout the polymer shell and the pores are filled with gas. For this type of microsphere, this outer polymer shell surrounds an internal core of gas.

As generally used herein, the terms "dosage" and "dose" are used synonymously to refer to the amount of a substance that is given at one time or the amount of substance that is required to produce the desired diagnostic or contrast effect.

5 As used herein, the term "dosage formulation" refers to a vial or other container such as a syringe, containing one or more dosages of substance required to produce the desired diagnostic or contrast effect.

As generally used herein "region of a patient" refers to a particular area or portion of the patient. In some instances "region of patient" refers to
10 regions throughout the entire patient. Examples of such regions are the pulmonary region, the gastrointestinal region, the cardiovascular region (including myocardial tissue or myocardium (i.e. heart muscle), ventricular chambers, atrial chambers, valve function), the renal region as well as other body regions, tissues, organs and the like, including the vasculature and
15 circulatory systems, and as well as diseased tissue, including cancerous tissue. "Region of a patient" includes, for example, regions to be imaged with diagnostic imaging. The "region of a patient" is preferably internal, although it may be external.

As generally used herein "vasculature" denotes blood vessels
20 (including arteries, veins, capillaries and the like).

As generally used herein "gastrointestinal region" includes the region defined by the esophagus, stomach, small and large intestines, and rectum.

As generally used herein "renal region" refers to the region defined by the kidney and the vasculature that leads directly to and from the kidney,
25 and includes the abdominal aorta.

As generally used herein "region to be targeted" and "targeted region" are used interchangeably to refer to a region of a patient where delivery of an agent is desired.

As generally used herein "region to be imaged" and "imaging region"
30 are used interchangeably to refer to a region of a patient where imaging is desired.

As generally used herein "ventricular blood flow or ventricular chamber enhancement" refers to the flow of blood through the ventricles of the heart in one or more cardiac cycles.

As generally used herein "atrial blood flow" refers to the flow of
5 blood through the atria of the heart in one or more cardiac cycles.

As generally used herein "myocardial blood flow" refers to the flow of blood in the vasculature of the heart muscle or myocardium, including the blood vessels in the heart, in one or more cardiac cycles.

As generally used herein "myocardial blood volume" refers to the
10 volume of blood in the vasculature of the heart muscle or myocardium.

As generally used herein "cardiac cycle" refers to a complete contractile period of the heart, and includes both the diastole and systole periods.

As generally used herein "increased brightness" refers to an increase
15 in the brightness of an image compared to an image obtained without an ultrasound contrast agent.

As generally used herein "enhanced image" refers to an image which has increased brightness relative to an image obtained without an ultrasound contrast agent.

As generally used herein "duration" refers to the total time over
20 which increased brightness of an image can be detected.

As generally used herein "coronary vasodilator" refers to a bioactive agent such as dipyridamole or adenosine which, when administered to a patient, causes dilation of the vasculature in the cardiovascular region.

25 II. Microparticles

In the preferred embodiment, the microparticles contain a polymer, a lipid and a perfluorocarbon gas. Microparticles may consist of both microspheres and microcapsules, or only microspheres or microcapsules.

Polymers

30 In the preferred embodiment, the microparticles are formed from synthetic polymers. Synthetic polymers produce microparticles that are biocompatible and are not contaminated by biological materials.

Additionally, synthetic polymers are preferred due to more reproducible

synthesis and degradation both *in vitro* and *in vivo*. The polymer is selected based on the time required for *in vivo* stability, i.e., that time required for distribution to the site where imaging is desired, and the time required for imaging. Synthetic polymers may be modified to produce microparticles
5 with different properties (e.g. changing molecular weight and/or functional groups).

Representative synthetic polymers are: poly(hydroxy acids) such as poly(lactic acid), poly(glycolic acid), and poly(lactic acid-co-glycolic acid), polyglycolides, polylactides, poly(lactide-co-glycolide) copolymers and
10 blends, polyanhydrides, polyorthoesters, polyamides, polycarbonates, polyalkylenes such as polyethylene and polypropylene, polyalkylene glycols such as poly(ethylene glycol), polyalkylene oxides such as poly(ethylene oxide) polyvinyl alcohols, poly(valeric acid), and poly(lactide-co-caprolactone), derivatives, copolymers and blends thereof. As used herein,
15 "derivatives" include polymers having substitutions, additions of chemical groups, for example, alkyl, alkylene, hydroxylations, oxidations, and other modifications routinely made by those skilled in the art.

Examples of preferred biodegradable polymers include polymers of hydroxy acids such as lactic acid and glycolic acid, polylactide,
20 polyglycolide, poly(lactide-co-glycolide), and copolymers with PEG, polyanhydrides, poly(ortho)esters, polyurethanes, poly(butyric acid), poly(valeric acid), poly(lactide-co-caprolactone), blends and copolymers thereof. The most preferred polymer is poly(lactide-co-glycolide) with a lactide to glycolide ratio of 50:50 (i.e. 1:1) and the polymer having a weight
25 average molecular weight in the range 20,000-40,000 Daltons. The weight average molecular weight (M_w) of the polymer is the average molecular weight calculated on the basis of the mass of molecules with a given molecular weight within the distribution of individual polymer chains. M_w can be determined using gel permeation chromatography (GPC).

30 **Hydrophobic Compounds**

In the preferred embodiment, the polymer includes a hydrophobic compound, as described in U.S. Patent No. 5,837,221. In general, incorporation of compounds such as lipids which are hydrophobic and in an

effective amount within the polymers, limits penetration and/or uptake of water by the microparticles and thus limits gas loss from the microparticles. This is effective in increasing the duration of enhanced imaging provided by microparticles that contain a lipid, a synthetic polymer and a gas

5 encapsulated therein, especially fluorinated gases such as perfluorocarbons.

Lipids which may be used to stabilize gas inside the polymeric microparticles include but are not limited to the following classes of lipids: fatty acids and derivatives, mono-, di and triglycerides, phospholipids, sphingolipids, cholesterol and steroid derivatives, terpenes and vitamins.

10 Fatty acids and derivatives thereof may include but are not limited to saturated and unsaturated fatty acids, odd and even number fatty acids, cis and trans isomers, and fatty acid derivatives including alcohols, esters, anhydrides, hydroxy fatty acids and prostaglandins. Saturated and unsaturated fatty acids that may be used include, but are not limited to,
15 molecules that have between 12 carbon atoms and 22 carbon atoms in either linear or branched form. Examples of saturated fatty acids that may be used include, but are not limited to, lauric, myristic, palmitic, and stearic acids. Examples of unsaturated fatty acids that may be used include, but are not limited to lauric, physeteric, myristoleic, palmitoleic, petroselinic, and oleic
20 acids. Examples of branched fatty acids that may be used include, but are not limited to, isolauric, isomyristic, isopalmitic, and isostearic acids and isoprenoids. Fatty acid derivatives include 12-(((7'-diethylaminocoumarin-3-yl)carbonyl)methylamino)-octadecanoic acid; N-[12-
(((7'-diethylaminocoumarin-3-yl) carbonyl)methyl-amino) octadecanoyl]-2-
25 aminopalmitic acid, N succinyl-dioleoylphosphatidylethanol amine and palmitoyl-homocysteine; and/or combinations thereof. Mono, di and triglycerides or derivatives thereof that may be used include, but are not limited to molecules that have fatty acids or mixtures of fatty acids between 6 and 24 carbon atoms, digalactosyldiglyceride, 1,2-dioleoyl-sn-glycerol;
30 1,2-dipalmitoyl-sn-3 succinylglycerol; and 1,3-dipalmitoyl-2-succinylglycerol.

Phospholipids which may be used include but are not limited to phosphatidic acids, phosphatidyl cholines with both saturated and

unsaturated lipids, phosphatidyl ethanolamines, phosphatidylglycerols, phosphatidylserines, phosphatidylinositols, lysophosphatidyl derivatives, cardiolipin, and β -acyl-alkyl phospholipids. Examples of phospholipids include, but are not limited to, phosphatidylcholines such as

- 5 dioleoylphosphatidylcholine (DOPC), dimyristoylphosphatidylcholine (DMPC), dipentadecanoylphosphatidylcholine (DPDPC), dilauroylphosphatidylcholine (DLPC), dipalmitoylphosphatidylcholine (DPPC), distearoylphosphatidylcholine (DSPC),
- 10 diarachidoylphosphatidylcholine (DAPC), dibehenoylphosphatidylcholine (DBPC), ditricosanoylphosphatidylcholine (DTPC), dilignoceroylphatidylcholine (DLPC); and phosphatidylethanolamines such as dioleoylphosphatidylethanolamine or 1-hexadecyl-2-
- 15 palmitoylglycerophosphoethanolamine. Synthetic phospholipids with asymmetric acyl chains (e.g., with one acyl chain of 6 carbons and another acyl chain of 12 carbons) may also be used.

Sphingolipids which may be used include ceramides, sphingomyelins, cerebroside, gangliosides, sulfatides and lysosulfatides. Examples of sphingolipids include, but are not limited to, the gangliosides GM1 and GM2.

- 20 Steroids which may be used include but are not limited to cholesterol, cholesterol sulfate, cholesterol hemisuccinate, 6-(5-cholesterol 3 β -yloxy) hexyl-6-amino-6-deoxy-1-thio- α -D-galactopyranoside, 6-(5-cholesten-3 β -tloxy)hexyl-6-amino-6-deoxyl-1-thio- α -D mannopyranoside and cholesteryl)
- 4'-trimethyl 35 ammonio)butanoate.

- 25 Additional lipid compounds which may be used include tocopherol and derivatives, and oils and derivatized oils such as stearlyamine.

- A variety of cationic lipids such as DOTMA, N-[1-(2,3-dioleoyloxy) propyl-N,N,N-trimethylammonium chloride; DOTAP, 1,2-dioleoyloxy-3-(trimethylammonio) propane; and DOTB, 1,2-dioleoyl-3-(4'-trimethyl-
- 30 ammonio) butanoyl-sn-glycerol may be used.

The most preferred lipids are phospholipids, preferably DPPC, DAPC, DSPC, DTPC, DBPC, DLPC and most preferably DPPC, DSPC, DAPC and DBPC.

- The lipid content ranges from 0.01-30% (w lipid/w polymer);
 5 preferably between 0.1-20% (w lipid/w polymer) and most preferably 1-12% (w lipid/w polymer).

When formed by the methods described herein, the size of the microparticles is consistently reproducible. As used herein, the terms "size" or "diameter" in reference to particles refers to the number average particle
 10 size, unless otherwise specified. An example of an equation that can be used to define the number average particle size (X_n) is shown below:

$$X_n = \frac{\sum_{i=1}^{\infty} n_i d_i}{\sum_{i=1}^{\infty} n_i}$$

where n_i = number of particles of a given diameter (d_i).

- As used herein, the term "volume average diameter" refers to the
 15 volume weighted diameter average. An example of equations that can be used to define the volume average diameter (X_v) is shown below:

$$X_v = \left[\frac{\sum_{i=1}^{\infty} n_i d_i^3}{\sum_{i=1}^{\infty} n_i} \right]^{1/3}$$

where n_i = number of particles of a given diameter (d_i).

- Particle size analysis can be performed on a Coulter counter, by light
 20 microscopy, scanning electron microscopy, transmittance electron microscopy, laser diffraction methods such as those using a Malvern Mastersizer, light scattering methods or time of flight methods. As used herein "Coulter method" refers to a method in which the powder is dispersed in an electrolyte, and the resulting suspension analyzed using a Coulter

Multisizer II fitted with a 50- μ m aperture tube. This method provides size measurements and particle concentrations.

In the preferred embodiment for the preparation of injectable microparticles capable of passing through the pulmonary capillary bed, the
5 microparticles have a diameter less than eight microns. Larger microparticles may clog the pulmonary bed, and smaller microparticles may not provide sufficient contrast effect. The preferred microparticle size for an intravenously administered ultrasound contrast agent is between 0.75 microns and 5 microns and is most preferably between 1.8 and 3.0 microns.

10 In the preferred embodiment, the microparticles have a honeycombed structure or sponge like structure, formed by pores throughout the polymer or the microparticles have a polymeric shell with a honeycombed or sponge like, porous structure. In both cases the pores are filled with gas. These microparticles are formed by spray drying a polymer solution containing a
15 pore forming agent such as a volatile salt as described below.

Ultrasound Contrast Imaging Agents

Examples of fluorinated gases include CF_4 , C_2F_4 , C_2F_6 , C_3F_6 , C_3F_8 , C_4F_8 , C_4F_{10} , and SF_6 . n-Perfluorobutane (C_4F_{10}) is particularly preferred because it provides an insoluble gas that will not condense at the temperature
20 of use and is pharmacologically acceptable.

The amount of gas contained with the microparticles will depend on the type of gas but is typically between 75-500 $\mu\text{g/mL}$ of administered volume of microparticle suspension. For n-perfluorobutane, the preferred gas content is between 100-400 $\mu\text{g/mL}$ of administered volume of
25 microparticle suspension and most preferably is between 150-350 $\mu\text{g/mL}$ of administered volume of microparticle suspension. For n-octafluoropropane, the preferred gas content is between 75-375 $\mu\text{g/mL}$ of administered volume of microparticle suspension, and most preferably between 120-300 $\mu\text{g/mL}$ of administered volume of microparticle suspension.

30 III. Methods for making Microparticles

The microparticles may be produced by a variety of methods, and are preferably produced by spray drying. A major criterion is that the polymer

must be dissolved or melted with the hydrophobic compound or lipid, prior to forming the microparticle.

Solvents

During formation, the polymer is generally dissolved in a solvent. As defined herein, the polymer solvent is an organic solvent that is volatile or has a relatively low boiling point or can be removed under vacuum and which is acceptable for administration to humans in trace amounts, such as methylene chloride. Other solvents, such as ethyl acetate, ethyl formate, ethanol, methanol, dimethyl formamide (DMF), acetone, acetonitrile, tetrahydrofuran (THF), formamide, acetic acid, dimethyl sulfoxide (DMSO) and chloroform also may be utilized, or combinations thereof. In general, the polymer is dissolved in the solvent to form a polymer solution having a concentration of between 0.1 and 60% weight to volume (w/v), more preferably between 0.25 and 30% (w/v) and most preferably between 0.5-10% (w/v).

Spray Drying

Microparticles are preferably produced by spray drying by dissolving a biocompatible polymer and lipid in an appropriate solvent, dispersing a pore forming agent as a solid or as a solution into the polymer solution, and then spray drying the polymer solution and the pore forming agent, to form microparticles. As defined herein, the process of "spray drying" a solution of a polymer and a pore forming agent refers to a process wherein the polymer solution and pore forming agent are atomized to form a fine mist and dried by direct contact with hot carrier gases. Using spray dryers available in the art, the polymer solution and pore forming agent may be atomized at the inlet port of the spray dryer, passed through at least one drying chamber, and then collected as a powder. The temperature may be varied depending on the gas or polymer used. The temperature of the inlet and outlet ports can be controlled to produce the desired products.

The size and morphology of the microparticles formed during spray drying is a function of the nozzle used to spray the polymer solution and the pore forming agent, the nozzle pressure, the flow rate of the polymer solution with the pore forming agent, the polymer used, the concentration of the

polymer in solution, the type of polymer solvent, the type and the amount of pore forming agent, the temperature of spraying (both inlet and outlet temperature) and the polymer molecular weight. Generally, the higher the polymer molecular weight, the larger the particle size, assuming the polymer solution concentration is the same.

Typical process parameters for spray drying are as follows: inlet temperature = 30-200°C, outlet temperature = 5-100°C, and polymer flow rate = 10-5,000 ml/min.

A gaseous diagnostic agent may be encapsulated by emulsifying the gas with the polymer solution and the pore forming agent prior to spray drying. Alternatively, air filled microparticles can be produced during the spray drying step and subsequently the air replaced with the perfluorocarbon gas by applying a stream of the desired gas to the microparticles, or pulling a vacuum on the microparticles to remove the encapsulated air, then filling with the desired perfluorocarbon gas. A lyophilizer or vacuum chamber may be used if a vacuum step is used to exchange the gas.

Additives to Facilitate Microparticulate Formation

A variety of surfactants may be added during the formation of the microparticles. Exemplary emulsifiers or surfactants which may be used (0.1-15% w/ w polymer) include most physiologically acceptable emulsifiers. Examples include natural and synthetic forms of bile salts or bile acids, both conjugated with amino acids and unconjugated such as taurodeoxycholate, and cholic acid.

Pore forming agents are included in the polymer solution in an amount of between 0.01% and 90% weight to volume of polymer solution, to increase pore formation. For example, in spray drying, a pore forming agent such as a volatile salt, for example, ammonium bicarbonate, ammonium acetate, ammonium carbonate, ammonium chloride or ammonium benzoate or other volatile salt as either a solid or as a solution in a solvent such as water can be used. The solid pore forming agent or the solution containing the pore forming agent is then emulsified with the polymer solution to create a dispersion or droplets of the pore forming agent in the polymer. This

dispersion or emulsion is then spray dried to remove both the polymer solvent and the pore forming agent. After the polymer is precipitated, the hardened microparticles can be frozen and lyophilized to remove any pore forming agent not removed during the polymer precipitation step.

- 5 The preferred microparticle is formed using the polymer, poly(lactide-co-glycolide) with a lactide to glycolide ratio of 50:50 and having a weight average molecular weight in the range 20,000-40,000 Daltons, and the phospholipid, diarachidoylphosphatidylcholine ((1,2-diarachidoyl-*sn*-glycero-3-phosphocholine (DAPC)) at a ratio of 5-6.6 %
10 (w DAPC/w polymer). The microparticles are further formulated in a solution of mannitol and TWEEN® 80 and processed to yield a dry powder of microparticles which are backfilled on a lyophilizer with n-perfluorobutane. The dry powder is reconstituted with 5 mL of sterile water prior to use by adding the water to the vial of the dry powder and shaking to
15 yield a suspension of microparticles in isosmotic mannitol. The preferred properties of the suspension are a gas content of 150-350 µg/mL of n-perfluorobutane per administered volume of microparticle suspension, 1.5-2.8 x 10⁹ microparticles/mL of administered volume of microparticle suspension, 30-45mg microparticles/mL of administered volume of
20 microparticle suspension, and a mean particle size in the range 1.8-3.0 microns.

IV. Applications for the Microparticles

1. Formulations for Administration to a Patient

- 25 The microparticles may undergo further processing with excipients to create a dry powder. The excipients provide tonicity or osmolality or ease of suspendability of the microparticles after reconstitution with a pharmaceutically acceptable carrier prior to administration to a patient. Excipients suitable for providing osmolality or tonicity are sugars including but not limited to mannitol, dextrose or glucose and salts including but not
30 limited to sodium chloride or sodium phosphate. Excipients suitable for providing ease of suspendability of the microspheres include any pharmaceutically acceptable wetting agent or surfactant including but not

limited to polysorbate 80 (TWEEN® 80), polysorbate 20 (TWEEN® 20), Pluronic or polyethylene glycol. Excipients suitable for providing osmolality or tonicity or that can be used as wetting agents are described in references such as the Handbook of Pharmaceutical Excipients (Fourth Edition, Royal Pharmaceutical Society of Great Britain, Science & Practice Publishers) or Remingtons: The Science and Practice of Pharmacy (Nineteenth Edition, Mack Publishing Company). The dry powder of microparticles and excipients is created by suspending the microparticles in a solution of excipients. Further size fractionation steps may be used if needed. The microparticles in the solution of excipients are filled into vials or syringes, frozen, and lyophilized to create the dry powder formulation. At the conclusion of the lyophilization step, the microparticles are filled with the perfluorocarbon gas by backfilling the lyophilizer with the perfluorocarbon gas. The vials or syringes are then stoppered or capped and in the case of vials, crimped. This results in a perfluorocarbon headspace in the vial or syringe.

Alternatively, the microparticles can be dry blended with the pharmaceutical excipients and then filled into vials or syringes. The microparticles can be filled with the perfluorocarbon gas by applying a vacuum after loading the vials or syringes on a lyophilizer or in a vacuum chamber. The vials or syringes are then stoppered or capped and in the case of vials, crimped. This results in a perfluorocarbon headspace in the vial or syringe.

2. Dosage Units

Different size dosage units of microparticles may be used. For example a small dosage unit may contain 25-75 mg of microparticles. An intermediate dosage unit may contain 75-150 mg. A large dosage unit may contain 150-250 mg of microparticles. An extra large dosage unit may contain 250-1000 mg of microparticles.

When the suspension of microparticles is formed following reconstitution, the mass concentration of microspheres in the suspension typically ranges from 20 to 60 mg/mL. The preferred mass concentration of microspheres in the suspension is 25-50 mg/mL; and the most preferred mass

concentration of microspheres in the suspension is 30 to 45 mg/mL. The preferred concentration of microparticles in the suspension is $1.0-3.5 \times 10^9$ microparticles/mL of suspension; and the most preferred concentration of microparticles in the suspension is $1.5-2.8 \times 10^9$ microparticles/mL. The
5 microparticles have a preferred mean particle size of less than 8 microns, most preferably in the range 1.8-3.0 microns.

Pharmaceutically acceptable carriers may include water for injection, sterile water, saline, saline containing glycerol, saline containing TWEEN[®] 20, saline containing TWEEN[®] 80, isosmotic dextrose (5%), $\frac{1}{2}$ isosmotic
10 dextrose (2.5%), isosmotic mannitol (5%), $\frac{1}{2}$ isosmotic mannitol (2.5%), isotonic mannitol containing TWEEN[®] 20 and isotonic mannitol containing TWEEN[®] 80.

3. Kits

Kits for parenteral administration of the microparticles containing the
15 perfluorocarbon gas may be provided. The kit contains at least two components. One component contains a dosage unit of the dry powder contrast agent in a vial or syringe, and the other component contains a pharmaceutically acceptable carrier in a vial or syringe. Prior to
administration to a patient, the pharmaceutically acceptable carrier is added
20 to the dosage unit of the dry powder contrast agent to form a suspension of gas filled microparticles that are usable as an ultrasound imaging contrast agent in diagnostic imaging by any route of administration.

4. Vials or Containers for microparticles

No specific vial or syringe or connection systems are required for the
25 kits; conventional vials, syringes and adapters may be used with the microparticles. The only requirement for a vial is a good seal between the stopper and the container. The quality of the seal, therefore, becomes a matter of primary concern; any degradation of seal integrity could allow undesirable substances to enter the vial or allow the gas to escape. In
30 addition to assuring sterility, vacuum retention is essential for products stoppered at reduced pressures to assure safe and proper reconstitution. As to the stopper, it may be a compound or multicomponent formulation based on an elastomer, such as poly (isobutylene) or "butyl rubber" and must be

impermeable to the gas used. The vial size is selected depending on the total dosage of dry powder in the vial. Preferred vial sizes are 5mL, 10 mL, 20 mL and 30 mL. The syringe size is selected depending on the total dosage of dry powder in the syringe. Preferred syringe sizes are 5mL, 10mL, 20mL, and 50 mL syringes.

5. Diagnostic Applications

The microparticle compositions may be used in a many different diagnostic applications including ultrasound imaging, magnetic resonance imaging, fluoroscopy, x-ray, and computerized tomography.

10 In the preferred embodiment, the microparticles are used in ultrasound procedures such as blood vessel imaging and echocardiography including but not limited to ventricular chamber imaging, myocardial blood flow assessment, myocardial blood volume assessment, diagnosis of coronary artery disease, and ejection fraction assessment.

15 The microparticles may be used in vascular imaging, as well as in applications to detect liver and renal diseases, in detecting and characterizing tumor masses and tissues, and in measuring peripheral blood velocity. The microparticles also can be linked with ligands that minimize tissue adhesion or that target the microparticles to specific regions of the body *in vivo*.

20 *General Method of obtaining images*

The microparticles in dry powder form are reconstituted with a pharmaceutically acceptable carrier prior to administration, then an effective amount for detection is administered to a patient using an appropriate route, by injection into a blood vessel (such as intravenously (i.v.) or intra-arterially (i.a.)), or orally. The microparticle composition may be administered
25 intravenously to the patient as a bolus injection or short infusion (less than 30 minutes). Preferably the injection is administered over a time period ranging from 15 seconds to 20 minutes, most preferably ranging from 30 seconds to 15 minutes. Typically, a dose ranging from 0.025 to 8 mg/kg
30 body weight per injection is administered intravenously to a patient, preferably the dose ranges from 0.05 to 4 mg/kg.

For diagnostic ultrasound applications, energy is applied to at least a portion of the patient to image the target tissue. A visible image of an

internal region of the patient is then obtained, such that the presence or absence of diseased tissue can be ascertained. Ultrasonic imaging techniques, including second harmonic imaging and gated imaging, are well known in the art and are described, for example, in Uhlendorf, IEEE

- 5 Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, 14(1):70-79 (1994) and Sutherland, *et al.*, Journal of the American Society of Echocardiography, 7(5):441-458 (1994), the disclosures of each is hereby incorporated herein by reference in its entirety.

- 10 Ultrasound waves may be applied with a transducer. The ultrasound can be pulsed or it may be continuous, if desired. Thus, diagnostic ultrasound generally involves the application of echoes, after which, during a listening period, the ultrasound transducer receives reflected signals. Harmonics, ultraharmonics or subharmonics may be used. The second harmonic mode may be beneficially employed, in which the 2x frequency is received, where x is the incidental frequency. This may serve to decrease the signal from the background material and enhance the signal from the transducer using the imaging agents, which may be targeted to a desired site, for example, blood clots. Other harmonic signals, such as odd harmonics signals, for example, 3x or 5x, would be similarly received using this method. Subharmonic signals, for example, $x/2$ and $x/3$, may also be received and processed so as to form an image.

- 25 In addition, Power Doppler or Color Doppler may be applied. In the case of Power Doppler, the relatively higher energy of the Power Doppler may resonate the vesicles. This can create acoustic emissions which may be in the subharmonic or ultraharmonic range or in some cases, in the same frequency as the applied ultrasound.

Specific Imaging Applications

- 30 The microparticles described herein can be used in both cardiology and radiology applications. For cardiology applications, the microparticle compositions are administered to a patient and the patient is scanned using an ultrasound machine to obtain visible images of the cardiovascular region. Optionally the microparticle composition is administered in combination with a pharmacological stressor or a physical stressor. Suitable

pharmacological stressors include a coronary vasodilator such as dipyridamole or adenosine, an inotropic agent (i.e. increases the strength of heart contraction) such as dobutamine or a chronotropic agent (i.e. increases the frequency of contraction) such as dobutamine. Suitable physical
5 stressors include physical exercise, such as by using a treadmill or a stationary bicycle.

For radiology applications, the microparticle compositions are administered to a patient and the patient is scanned using an ultrasound machine to obtain visible images of the region of a patient to be examined.

10 The microparticles can be used to assess the function of the cardiovascular system as well as to assess myocardial blood flow or myocardial blood volume or to diagnose coronary heart disease (coronary artery disease). For example the microparticles can enhance images of the ventricular chambers and thus assist in regional cardiac function analysis
15 through wall motion analysis and assist in global cardiac function through ejection fraction measurements. The microparticles can also be used to assess myocardial blood flow to differentiate functioning cardiac tissue from either ischemic (blood flow deficient) cardiac tissue or infarcted (dead) cardiac tissue. The contrast signals detected in the myocardium can be used
20 as an estimate of myocardial blood volume since ultrasound contrasts agents reside intravascularly following intravenous administration. The absence or reduction in contrast intensity or image brightness in a particular myocardial region over time is indicative of reduced blood flow (i.e. a defect).

Most often unless the patient has severe coronary heart disease, blood
25 flow to the various regions of the heart as assessed by techniques such as ultrasound contrast will appear normal. In order to detect blood flow abnormalities in patients without severe heart disease or to detect smaller myocardial blood flow defects, it is necessary to increase the blood flow requirements to the heart by inducing a state of stress. Stress can be induced
30 by having the patient exercise or by administering a pharmacological compound such as a vasodilator, an inotropic agent or a chronotropic agent. During exercise or pharmacological stress, blood flow defects can be more easily detected because the ability to increase blood flow is reduced in

regions supplied by coronary arteries with stenosis. A comparison of ultrasound images of the myocardium following ultrasound contrast agent administration can be made both in the pre-stress state (*i.e.* rest state) and in the stress state. A myocardial region without enhanced brightness found
5 during stress imaging but not during rest imaging is indicative of ischemia. A myocardial region without enhanced brightness found during stress imaging and during rest imaging is indicative of an infarct.

In one embodiment, the myocardial blood flow can be measured by
(1) administering a first injection of a microparticle composition to a patient,
10 (2) scanning the patient using an ultrasound machine imaging to obtain a visible image of the cardiovascular region, (3) inducing a state of stress in the patient using a pharmacological stressor or exercise, (4) administering a second injection of the microparticle composition and continuing the scanning, and (5) assessing differences in the images obtained in steps (2)
15 and (4) either visually or using quantitative image analysis.

For radiology applications, the microparticles may be used to improve the capabilities of ultrasound imaging for radiology indications, including imaging of the kidney, liver and peripheral vascular disease, increasing the visibility of blood flow and blood flow patterns and by
20 improving the detection of small lesions or structures deep within the body. The microparticles can be used for both macrovascular and microvascular indications. In macrovascular indications (the diagnosis of disease states and conditions of major arteries and veins of the body), the microparticles may aid in the detection of strokes and pre-stroke conditions through visualization
25 of intracranial blood vessels, detecting atherosclerosis in large vessels such as the carotid arteries by assessing the degree of carotid artery stenosis, vascular graft patency and peripheral vascular thrombosis. For microvascular indications (the diagnosis of disease states and through analysis of patterns of small vessel blood flow), the microparticles may aid
30 in identifying lesions, tumors or other diseases in the liver (*e.g.* adenomas or hemangiomas), kidneys, spleen (*e.g.* splenic artery aneurysms), breasts and ovaries and in other tissues and organs.

Diseased tissues in a patient may be diagnosed by administering the microparticle composition to the patient and scanning the patient using the ultrasound imaging to obtain visible images of any diseased tissues in the patient. Diseased tissues may manifest as a region of enhanced brightness or
5 a region that does not show enhanced brightness.

Enhanced Images obtained using Microparticle compositions

The microparticles produce an enhanced image following administration. Enhanced images may be manifested by an increase in brightness in the image compared to when no ultrasound contrast agent is
10 administered or by substantial elimination of artifacts in the image. Thus, in connection with ultrasound imaging of the cardiovascular region, including the heart tissue and the vasculature associated therewith, an enhanced image may be manifested, for example, by increased brightness in the image of the cardiovascular region and/or a substantial elimination in the occurrence of
15 artifacts in the image of the cardiovascular region. The images following a single administration of the agent last for between 10 seconds and 60 minutes. The images preferably last for between 20 seconds and 30 minutes and most preferably last for between 30 seconds and 20 minutes. In a preferred embodiment, the ultrasound imaging is enhanced in the ventricular
20 chambers for more than five minutes or in the myocardium for more than one minute.

The increase in brightness in the image may be assessed either visually by the naked eye or using quantitative image analysis. With particular reference to the gray scale (about 0 to about 255 VDUs or gray
25 levels) identified above, there is preferably an increase in the level of brightness of at least about 10 VDUs (gray levels). More preferably, the image has an increased brightness of greater than about 10 VDUs, for example, about 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, or 100 VDUs. In some embodiments, the increased brightness is greater
30 than about 100 VDUs, for example, about 105, 110, 115, 120, 125, 130, 135, 140, 145, or 150 VDUs. In other embodiments, the increased brightness is greater than about 150 VDUs, for example, about 155, 160, 165, 170, 175, 18-, 185, 190, 195, or 200 VDUs. Alternatively, the increased brightness is

greater than about 200 VDUs, for example about 205, 210, 215, 220, 225, 230, 235, 240, 245, 250, or 255 VDUs.

The methods and compositions described above will be further understood with reference to the following non-limiting examples.

5

Examples

Materials

Acetic acid, ammonium bicarbonate, mannitol USP, and polysorbate 80 (no animal-derived components) were purchased from Spectrum Chemicals, Gardena, CA. Polymer (poly(lactide-co-glycolide) (PLGA) (50:50)) and diarachidoylphosphatidylcholine (1,2-diarachidoyl-*sn*-glycero-3-phosphocholine (DAPC)) were obtained from Boehringer Ingelheim (Ingelheim, Germany) and Avanti (Alabaster, AL), respectively. Methylene chloride was purchased from EM Science (EMD Chemicals, Gibbstown, NJ). Vials (30 ml tubing vials) and stoppers (20 mm, gray, single-vent, Fluro-Tec) were obtained from West Pharmaceutical Services (Lionville, PA). n-Perfluorobutane (DFB) gas was purchased from F2 Chemicals Ltd, Lancashire, UK.

10

15

Analytical Methods

Quantitation of Mass Concentration of Microparticles

The mass concentration of microparticles in vials was quantitated using ICP-MS (inductively coupled plasma – mass spectrometry). The amount of polymer in the microparticles was determined by analyzing for tin by ICP-MS. The amount of polymer present in the microparticles was determined based on a comparison of the amount of tin found in the microparticles to the amount of tin found in the specific lot of polymer used to make the microparticles. The amount of phospholipid in the microparticles was determined by analyzing for phosphorus by ICP-MS. The amount of phosphorus present in the microparticles was determined based on the amount of phosphorous found in the microparticles in comparison to the amount of phosphorus in the phospholipid itself. The microparticle mass per mL of suspension was calculated by adding the amount of polymer and phospholipid per vial and then dividing that sum by the reconstitution volume (5 mL).

20

25

30

Particle Size Analysis

A sample of reconstituted microparticles was added to an electrolyte solution, and the resulting suspension analyzed for particle size and microparticle concentration using a Coulter Multisizer II fitted with a 50 μ m aperture tube.

Gas Content of Microparticles

Vials of the dry powder were reconstituted with 5mL water and shaken to create the microparticle suspension. The resulting suspension was analyzed for DFB content by withdrawing a set of 0.3 mL aliquots through the stopper using a needle and syringe. These aliquots were injected into sealed headspace vials. The headspace vials equilibrated for at least 10 hours at room temperature. Samples were then heated then heated to 45°C for 20 minutes in a headspace sampler oven. The headspace gas above the suspension was analyzed by gas chromatography using a purged packed inlet and a flame ionization detector. Quantitation was performed using an area based single point calibration.

The GC system parameters and temperature program are listed in Tables 1 and 2.

Table 1: GC System Parameters

Sampling:	Headspace, 1 mL sample loop
Detector:	FID
Column:	Supelco 60/80 Carbopack B 5% Fluorocol
Inlet Temperature:	150°C
Detector Temperature:	325°C
Carrier Gas:	Helium (25 mL/min)
FID Gases:	Hydrogen (60 mL/min)
	Air (350 mL/min)
	Nitrogen (5 mL/min)

Table 2: GC Temperature Program

	Initial Temp.	Rate	Final Temp.	Hold Time
Initial Cond.	40°C	N/A	N/A	2.0 min
First Ramp	40°C	5°C/min	65°C	0.0 min
Second Ramp	65°C	10°C/min	130°C	0.0 min
Third Ramp	130°C	50°C/min	200°C	0.0 min
Final Cond.	200°C	N/A	N/A	3.1 min

Example 1: Production of Microparticles for Use as an Ultrasound Contrast Agent

5 An organic solution was prepared by dissolving 176 g of PLGA, 10.6 g of diarachidoylphosphatidylcholine (1,2-diarachidoyl-*sn*-glycero-3-phosphocholine (DAPC)), and 2.26 g of acetic acid in 5.88 L of methylene chloride at 25°C. An aqueous solution composed of 68.5 g of ammonium bicarbonate dissolved in 338 ml of water for injection was added to the
10 organic solution and homogenized for 10 minutes at 4310 RPM in a 10L homogenization tank using a rotor-stator emulsifying mixer.

The resulting emulsion was spray dried using nitrogen as both the atomizing and drying gas. Emulsions were spray dried on a bench top, spray dryer using an air-atomizing nozzle from Spraying Systems (Wheaton,
15 IL) and a glass drying chamber/cyclone system from Buchi (Brinkmann, Westbury, NY). Spray drying conditions were as follows: 40 ml/min emulsion flow rate, 30 L/min atomization gas rate, 46 kg/hr drying gas rate, and 12°C outlet temperature.

The spray dried product was further processed through dispersion,
20 freezing, and lyophilization steps. An aqueous vehicle was prepared by dissolving 140 g of mannitol and 4.10 g of polysorbate 80 in 5.0 L of water. The spray dried microparticles were dispersed in the vehicle at a concentration of 25 mg/ml. The dispersion was deaggregated using a stainless steel, 800 series, flow-cell sonicator from Misonix Incorporated
25 (Farmingdale, NY) and sieved through a 10" diameter vibratory sieve (RBF-

- 10) from Vorti-Siv (Salem, OH). The sonicator was jacketed at 4°C to prevent heating of the dispersion. The dispersion was sieved through 25 µm and 20 µm screens in series at 150 mL/min. The sieved dispersion was filled into vials (10 ml fill in 30 ml vials), partially stoppered, and frozen by
- 5 immersion in liquid nitrogen.

Following freezing, the vials were lyophilized. At the conclusion of lyophilization, the chamber was isolated, and n-perfluorobutane (DFB) was backfilled into the vials to a pressure of -5 kilopascals prior to stoppering.

- The dry powder was reconstituted with 5 mL of sterile water prior to
- 10 use by adding the water to the vial of the dry powder and shaking to yield a suspension of microparticles in isosmotic mannitol. The suspension contained 2.2×10^9 microparticles/mL of suspension, and 37 mg microparticles/mL of suspension and the microparticles had a mean particle size of 2.2 microns.

15 **Example 2: Rate of Gas Leakage from the Microparticles**

- The rate of gas leakage from two separate batches (Batch 1 and Batch 2) of microparticles as produced by the methods of Example 1 was assessed using gas chromatography (GC) as described in the analytical methods sections. A third lot of microspheres (Batch 3) was produced similar to the
- 20 method of example 1, however, the phospholipid, diarachidoylphosphatidylcholine (1,2-diarachidoyl-*sn*-glycero-3-phosphocholine (DAPC)) was omitted during the production of the microparticles.

25 **Table 3: Gas Content and Rate of Gas Leakage for Microparticles**

	Gas Content (µg/mL suspension) Immediately Following Vial Reconstitution	Gas Content (µg/mL suspension) 70 minutes Following Vial Reconstitution	% Gas Content Lost over 70 minutes
Batch 1	341	312	9%
Batch 2	259	232	10%
Batch 3	139	18	87%

The microparticles which contained DAPC lost approximately 10% of the starting gas content after 70 minutes whereas the microparticles which did not contain DAPC lost 87% of the starting gas content. Additionally, the microparticles which contained DAPC had a higher starting initial gas
5 content relative to the microparticles without the DAPC. This indicates that the inclusion of DAPC is important to the formation of the internal porous structure of the microparticles during spray drying as well on retention of gas within the microparticles.

The total duration of intended use of an ultrasound contrast agent
10 following administration to a subject is generally on the order of 30 seconds to 60 minutes depending on the type of cardiology or radiology ultrasound examination conducted. Thus gas loss from the microparticles containing the lipid DAPC is estimated to be insignificant over the period of the ultrasound examination

15 **Example 3: Cardiac Image Enhancement as a Function of Microparticle Dose**

Microparticles as produced by the method in Example 1 were studied in healthy human adults. The dry powder was reconstituted prior to use by adding 5 mL of sterile water to the vial and shaking the vial ten times. The
20 final concentration of microspheres in the resulting suspension was approximately 37 mg/mL. Subjects received a single dose of either 0.5mg/kg, 2.0mg/kg or 4.0 mg/kg body weight. Subjects underwent transthoracic ultrasound imaging using continuous harmonic imaging (frame rate 15 Hz and transducer frequency 2.1/4.2 MHz). Images were visually
25 assessed for intensity and duration of enhancement.

The duration of enhancement in the ventricular chamber exceeded 9 minutes at both the 2 mg/kg and 4 mg/kg doses. The contrast effect was still apparent in 13 out of 15 of the subjects at these two doses when the subjects were re-imaged at 30 minutes, indicating the long duration of enhancement
30 provided by the microparticles.

The duration of ventricular chamber enhancement is summarized in the Table 4.

Table 4: Duration of Left Ventricular Image Enhancement

Dose (mg/kg body weight)	Mean Duration of Ventricular Chamber Enhancement (minutes)
0.5	2.6
2.0	>9.6
4.0	>9.6

Example 4: Comparison of Microparticles to Commercial Product for Assessing Cardiac Images

- 5 A comparative cardiac ultrasound imaging study was conducted in two adult men matched for body weight and cardiac function. The first subject received a single administration of microparticles as produced by the method of Example 1. The dry powder was reconstituted prior to use by adding 5 mL of sterile water to the vial and shaking the vial ten times. The
- 10 final concentration of microspheres in the resulting suspension was approximately 37 mg/mL and the gas content of the suspension was approximately 250 μ g/mL suspension. The first subject received a dose of 4mg microparticle/kg which corresponds to a gas dose of 27 μ g/kg body weight. The second subject received a single dose of the marketed
- 15 ultrasound contrast agent, OPTISON[®] (Amersham Health) which contains perfluoropropane containing albumin microspheres. The two subjects received the same total amount of gas (27 μ g/kg body weight) which is the acoustically active component. The two subjects underwent transthoracic ultrasound imaging using continuous harmonic imaging (frame rate 15 Hz
- 20 and transducer frequency 2.1/4.2 MHz). Images were visually assessed for intensity and duration of enhancement.

The duration of ventricular chamber enhancement and myocardial enhancement is summarized in Table 5.

Table 5: Duration of Image Enhancement with Different Ultrasound Contrast Agents

Contrast Agent and Dose of Gas Administered ($\mu\text{g/kg}$)	Duration of Ventricular Chamber Enhancement (minutes)	Duration of Myocardial Enhancement (seconds)
Example #1 Microparticles ($27\mu\text{g/kg}$ body weight)	> 9	160
OPTISON [®] ($27\mu\text{g/kg}$ body weight)	1	10

The microparticles produced using the method described in Example 1 provide enhanced images of both the ventricular chambers and the myocardium which are significantly longer than OPTISON[®] and which are of appropriate duration to conduct a complete cardiac exam by ultrasound.

Example 5: Assessment of Myocardial Blood Flow to Assess Ischemia

Using Microparticle Formulations

Microparticles produced as per the method in Example 1 were administered to a subject being evaluated for coronary heart disease. The subject received two injections of the microparticles separated by 60 minutes. The first injection of the microparticles ("rest injection", 1.7 mg/kg) was used to assess the myocardium at rest. Prior to the second injection of the microparticles, the subject was pharmacologically stressed using the coronary vasodilator, dipyridamole (0.56 mg/kg). After the induction of stress, the subject received a second injection of the microparticles ("stress injection" 1.3 mg/kg) to assess the myocardium under stress.

The comparison of the rest and stress images over time post administration of the microparticles for the subject indicate a region of the myocardium which has minimal increase in image enhancement and this region becomes larger in size following the induction of the stress. This

indicates the zone of myocardial tissue has both infarcted and ischemic components. The detection of ischemia was confirmed using an alternate diagnostic technique, nuclear imaging. Rest and stress nuclear perfusion were conducted following the administration of ^{99}Tc (MIBI) and the subject

5 was imaged using a commercial gamma counter. The defects noted on the ultrasound rest and stress images were confirmed on the rest and stress nuclear perfusion images.

We claim:

1. A dosage formulation providing enhanced ultrasound contrast images comprising microspheres comprising a biocompatible synthetic polymer and having incorporated therein a perfluorocarbon gas that is a gas at body temperature, wherein the microspheres are porous spheres with a honeycombed structure or sponge-like structure, wherein the dosage formulation comprises a dose of microspheres effective to provide enhanced ultrasound images for more than five minutes in the ventricular chambers or for more than one minute in the myocardium, when the microspheres are administered intravenously, and

wherein the dosage ranges from 0.5 to 4 mg microspheres /kg body weight.

2. The dosage formulation of claim 1 providing enhanced ultrasound images in the ventricular chambers for more than 9 minutes or in the myocardium for more than 2 minutes.

3. The dosage formulation of claim 1 providing enhanced ultrasound images in the ventricular chambers for at least 30 minutes.

4. The dosage formulation of claim 1 in the form of a dry powder of microspheres which can be reconstituted with sterile water prior to use by adding the water to the vial or syringe of the dry powder and shaking to yield an isosmotic suspension of microspheres.

5. A dosage formulation providing enhanced ultrasound contrast images comprising microspheres comprising a biocompatible synthetic polymer and having incorporated therein a perfluorocarbon gas that is a gas at body temperature, wherein the microspheres are porous spheres with a honeycombed structure or sponge-like structure,

wherein the dosage formulation comprises a dose of microspheres effective to provide enhanced ultrasound images for more than five minutes in the ventricular chambers or for more than one minute in the myocardium, when microspheres are administered intravenously, and

wherein the microspheres are in a dry powder form, and wherein the microspheres are reconstituted with sterile water prior to use forming a suspension having a microsphere concentration ranging from 1.0×10^9 to 3.5×10^9 microspheres /mL of suspension or a microsphere mass concentration ranging from 25 to 50 mg microspheres/mL suspension.

6. The dosage formulation of claim 5 forming a suspension having a microspheres concentration ranging from 1.5×10^9 to 2.8×10^9 microspheres/mL of suspension or a microsphere mass concentration ranging from 30 to 45mg microspheres/mL suspension.

7. The dosage formulation of claim 1 or 5 wherein the microspheres have a mean particle size of less than 8 microns.
8. The dosage formulation of claim 7 wherein the microspheres have a mean particle size ranging from 1.9 to 2.6 microns.
9. The dosage formulation of claim 1 wherein the dose is selected from the group consisting of 0.5mg microspheres /kg body weight, 2.0 mg microspheres /kg body weight and 4.0 mg microspheres /kg body weight.
10. The dosage formulation of claim 1 or 5 wherein the gas is selected from the group consisting of CF_4 , C_2F_4 , C_2F_6 , C_3F_6 , C_3F_8 , C_4F_8 , and C_4F_{10} .
11. The dosage formulation of claim 10 wherein the gas is n-perfluorobutane (C_4F_{10}) provided in an amount between 75 and 500 $\mu\text{g/mL}$ of administered volume of microsphere suspension.
12. The dosage formulation of claim 11 wherein the n- perfluorobutane (C_4F_{10}) is provided in an amount between 100 and 400 $\mu\text{g/mL}$ of administered volume of microsphere suspension.
13. The dosage formulation of claim 12 wherein the n- perfluorobutane (C_4F_{10}) is provided in an amount between 150 and 350 $\mu\text{g/mL}$ of administered volume of microsphere suspension.
14. The dosage formulation of claim 10 wherein the gas is n-octafluoropropane (C_3F_8) provided in an amount between 75 and 375 $\mu\text{g/mL}$ of administered volume of microsphere suspension.
15. The dosage formulation of claim 14 wherein the n- octafluoropropane (C_3F_8) is provided in an amount between 120 and 300 $\mu\text{g/mL}$ of administered volume of microsphere suspension.
16. The dosage formulation of claim 1 or 6 5 wherein the microsphere is formed of a synthetic polymer selected from the group consisting of poly(hydroxy acids), polyanhydrides, polyorthoesters, polyamides, polycarbonates, polyalkylenes, polyalkylene glycols, polyalkylene oxides, poly(valeric acid), poly(lactide-co-caprolactone), and copolymers and blends thereof.

17. The dosage formulation of claim 1 or 5, further comprising a hydrophobic compound incorporated with the polymer at a ratio of between 0.01 and 30% (weight hydrophobic compound/weight polymer).

18. The dosage formulation of claim 17 wherein the hydrophobic compound is a lipid incorporated with the polymer at a ratio of between 0.01 and 30% (weight lipid/weight polymer).

19. The dosage formulation of claim 18 wherein the lipid is a phospholipid selected from the group consisting of dioleoylphosphatidylcholine (DOPC), dimyristoylphosphatidylcholine (DMPC), dipentadecanoylphosphatidylcholine (DPDPC), dilauroylphosphatidylcholine (DLPC), dipalmitoylphosphatidylcholine (DPPC), distearoylphosphatidylcholine (DSPC), diarachidoylphosphatidylcholine (DAPC), dibehenoylphosphatidylcholine (DBPC), ditricosanoylphosphatidylcholine (DTPC), dilignoceroylphosphatidylcholine (DLGPC), and phosphatidylethanolamines.

20. The dosage formulation of claim 19, wherein the polymer is poly (lactide-co-glycolide) with a lactide to glycolide ratio of 1:1 and a weight average molecular weight ranging from 20 to 40 kDa, and wherein the lipid is diarachidoylphosphatidylcholine incorporated with the polymer at a ratio of between 5 and 6.6 % (weight lipid/weight polymer).

21. The dosage formulation of claim 1 or 5 in a vial or syringe comprising a dry powder of microspheres.

22. The dosage formulation of claim 21, wherein the vial or syringe further comprises one or more excipients selected from the group consisting sugars, salts, and surfactants.

23. The dosage formulation of claim 1 or 5 in a kit comprising a vial or syringe of dry microspheres and a vial or syringe of solution for resuspending the microspheres.

24. The dosage formulation of claim 1 or 5 consisting essentially of one or two doses.

25. The dosage formulation of claim 1 or 5 consisting essentially of up to five doses.

26. A kit comprising the dosage formulation of any one of claims 1-3, 4-8, or 9-25 and a solution for reconstituting the dosage formulation.

27. A method for making a dosage formulation for ultrasound contrast imaging comprising
suspending microspheres comprising a biocompatible polymer and a hydrophobic
compound in a solution optionally including excipients,
placing the suspension into a vial or syringe,
freezing the suspension,
lyophilizing the vial to create a dry powdered formulation in the vial or syringe, and
backfilling the lyophilizer with a perfluorocarbon gas,
to produce a dosage formulation as defined by any one of claims 1-3, 4-8 or 9-25.

28. A method for making a dosage formulation for ultrasound contrast imaging comprising
dry blending microspheres comprising a biocompatible polymer and a hydrophobic
compound optionally comprising excipients,
placing the mixture into a vial or syringe,
and applying a vacuum to the vial or syringe to remove the encapsulated air,
and filling the vial or syringe with a perfluorocarbon gas,
to produce a dosage formulation as defined by any one of claims 1-3, 4-8, or 9-25.