

A lamp with heat dissipating unit

BACKGROUND OF THE INVENTION

5 1. Field of the invention

The invention generally relates to a lamp with heat dissipating unit.

More particularly, the invention relates to a lamp with heat dissipating unit that can prevent the damages caused by dusts, water, insects, corrosion and erosion and can prevent the accumulation of dusts on top of the
10 lamp and its heat dissipating unit so that the heat dissipating capacity of a lamp would not be reduced.

2. Description of the prior art

Lamps are needed for roads, yards and outdoor places so as to ensure safety
15 at home and in the outdoor and prevent burglaries. Therefore, lamps are indispensable in the modern life. However, lamps of the prior art have the following disadvantages:

1. Traditionally, there have been several types of lamps: sodium lamp, mercury lamp, etc. As of now, LED lamp has become a major type of lamp
20 because it has a high efficiency, a longer service life and a variety of colors and is environmentally friendly. In comparison to these traditional types of lamps, LED lamp requires a higher heat dissipating capacity.

2. In the prior art, the heat dissipating apparatus for an LED lamp transfers heat to a cover and then to a plurality of heat dissipating pieces extending from
25 the cover. Its heat dissipating capacity and intensity of luminance may be

reduced and its service life may be shortened by the accumulation of dusts, birds' droppings and nests, etc.

From the above, we can see that the prior art lamps have many disadvantages and need to be improved.

5 To eliminate the disadvantages of the prior art lamps, the inventor has put in a lot of effort in the subject and has successfully come up with the lamp with heat dissipating unit of the present invention.

SUMMARY OF THE INVENTION

10

An object of the present invention is to provide a lamp with heat dissipating unit that can prevent the damages caused by dusts, water, insects, corrosion and erosion.

Another object of the present invention is to provide a lamp with heat
15 dissipating unit that can prevent the accumulation of dusts and wherein the heat dissipating pieces extend downwards or sideways so as to enhance the heat dissipating capacity by the ambient cold air rising upwards and to keep other undesirable factors (such as dusts) off.

A third object of the present invention is to provide a lamp with heat
20 dissipating unit wherein an AC/DC adopter unit is used to supply DC (direct current) to the light generating units so as to be more economical (because no battery is needed).

A fourth object of the present invention is to provide a lamp with heat
dissipating unit wherein a programmable timer and sensor circuit and an
25 overheating protection circuit are disposed in an AC/DC adopter unit so as to turn

off or on the light generating units and protect the light generating units from overheating.

The heat dissipating unit of the present invention comprises a supporting rod and a main body. The main body includes a heat dissipating unit, a light generating units plate, one or more heat conducting pieces, an AC/DC
5 adopter unit and a cover. The light generating units plate is fixedly fitted to an opening at the central portion or other appropriate location of the heat dissipating unit so that the light generating units point downwards or sideways. The AC/DC adopter unit is fitted on top of the heat conducting pieces. The cover is fitted on
10 top of the heat dissipating unit. The cover seals up the top portion of the heat dissipating unit, and hence a sealed space is formed. The light generating units plate, AC/DC adopter unit and heat conducting pieces are disposed in the sealed space. When heat is generated by the light generating units, heat is transferred to the light generating units plate and the heat conducting pieces and then to the heat
15 dissipating unit and the heat dissipating pieces. Heat is then dissipated into the ambient air. In addition, because the heat dissipating pieces of the heat dissipating unit extend downwards, dusts will not accumulate on them (so that their heat dissipating capacity will not be reduced) so that such lamp may have a longer service life.

20 These features and advantages of the present invention will be fully understood and appreciated from the following detailed description of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

25

Figs. 1A and 1B are perspective views showing the first embodiment of the present invention.

Fig. 2 is a perspective view showing the second embodiment of the present invention.

5 Fig. 3 is a perspective view showing the first embodiment of the present invention in operation.

Fig. 4 is a perspective view showing the third embodiment of the present invention.

10 Fig. 5 is a perspective view showing the fourth embodiment of the present invention.

Fig. 6 is a view showing the fifth embodiment of the present invention.

Fig. 7 is a view showing the fifth embodiment of the present invention in operation.

15 Fig. 8 is a view showing the sixth embodiment of the present invention in operation.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Please see Figs. 1A, 1B and 2 for the first embodiment of the present invention. The first embodiment of the heat dissipating unit comprises a heat
20 dissipating unit 11, a light generating units plate 12, one or more heat conducting pieces 16 and a cover 17.

An opening (not shown in the drawings) is provided at the central portion or other appropriate location of the heat dissipating unit 11. The top surface may
25 be a planer surface or other type of surface, and a plurality of heat dissipating

pieces 111 downwards extend from the bottom side of the heat dissipating unit 11. The heat dissipating pieces 111 may have the shape of a cylindrical rod (as illustrated in Figs. 1A and 1B) or the shape of a flat rectangular sheet (as illustrated in Fig. 2) or other shape. The heat dissipating pieces 111 point
5 downwards or sideways so that dusts, birds' droppings and nests, etc. will not fall and accumulate on the heat dissipating pieces 111 so that their heat dissipating capacity will not be reduced and their heat dissipating capacity may be enhanced by the ambient cold air rising upwards.

A plurality of light generating units are fitted on the light generating units
10 plate 12. The light generating units plate 12 may be made of aluminum or other types of highly conductive metals. The light generating units 13 may be fitted on the underside or wide walls of plate 12. The light generating units 13 may be LED, OLED or other types of light generating units. Also, a cover 4 is fitted on top of the light generating units 13. The plate 12 is fixedly fitted by fasteners 15 to an
15 opening at the central portion or other appropriate location of the heat dissipating unit 11 so as to seal up the opening and so that the light generating units 13 fitted on the underside of plate 12 may point downwards or sideways.

A portion of each heat conducting piece 16 is in contact with the top surface of the light generating units plate 12, and other portions are in contact with the top
20 surface of the heat dissipating unit 11. The heat conducting pieces 16 may be heat-conducting tubes or heat-conducting flat sheets.

The cover 17 may have the form of a lampshade. The cover 17 is fitted on top of the heat dissipating unit 11. The cover 17 seals up the top portion of the heat dissipating unit 11, and hence the light generating units plate 12 and the heat
25 conducting pieces 16 are sealed from the ambient surroundings so that they will

not be affected or damaged by dusts, water, insects, corrosion and erosion.

Now, please see Fig. 3, which illustrates the first embodiment of the present invention in operation. When heat is generated by the light generating units 13, heat is transferred to the light generating units plate 12 and the heat conducting
5 pieces 16 and then to the heat dissipating unit 11 and the heat dissipating pieces 111. Heat is then dissipated into the ambient air. In this way, heat may be dissipated quickly so that the light generating units 13 will not be damaged by overheating.

In addition, because the light generating units plate 12 and the heat
10 conducting pieces 16 are in a sealed space and the heat dissipating pieces 111 point downwards or sideways, no dusts will accumulate on light generating units plate 12, the heat conducting pieces 16 and the heat dissipating pieces 111; therefore, a high efficiency of heat dissipation may be ensured.

Now, please see Fig. 4, which illustrates a third embodiment of the present
15 invention. The design of the third embodiment is similar to the first embodiment illustrated in Figs. 1A and 1B except that an AC/DC adopter unit 18 is used in the third embodiment. The AC/DC adopter unit 18 is fitted on top of and in contact with the heat conducting pieces 16 so that heat generated by the AC/DC adopter unit 18 and a sensor circuit may be transferred to the heat conducting pieces 16
20 and then to the heat dissipating unit 11 and the heat dissipating pieces 111. Heat is then transferred to the ambient air. In this way, the AC/DC adopter unit 18 may have a longer service life.

The AC/DC adopter unit unit 18 serves to convert the AC supplied from an electrical outlet to DC; then the DC (direct current) is fed to the light generating
25 units 13. In addition, a programmable timer and sensor circuit and an overheating

protection circuit are disposed in the AC/DC adopter unit 18. The programmable timer circuit serves as a timer so as to turn off and turn on the light generating units 13. The overheating protection circuit can detect the temperatures of the light generating units 13; if the light generating units 13 overheat, the overheating protection circuit will turn off the light generating units 13 automatically.

Now, please see Fig. 5, which is a fourth embodiment of the present invention. The design of the fourth embodiment is similar to the first embodiment illustrated in Figs. 1A and 1B except that the cover 17 has a planer shape so that the cover 17 may be in contact with the top surface of the heat dissipating unit 11 so as to increase the efficiency of heat dissipation.

Now, please see Fig. 6, which is a fifth embodiment of the present invention. The lamp comprises a main body 2, which includes a heat dissipating unit 21 and a reflective cover 24.

The heat dissipating unit 21 may have a very long length. A plurality of heat dissipating pieces 211 extend from the bottom side of the heat dissipating unit 21 towards the ground. The heat dissipating pieces 211 may have the shape of a cylindrical rod or the shape of a flat rectangular sheet or other shape. A set of light generating units 22 are fitted on one side or both sides of the heat dissipating unit 21. A cover 23 is fitted onto each set of light generating units 22 so as to seal up the latter.

The reflective cover 24 has an arcuate shape. The width of the reflective cover 24 is larger than that of the heat dissipating unit 21, and the length of the reflective cover 24 may be very long. The reflective cover 24 is fixedly fitted on the top surface of the heat dissipating unit 21 so as to cover the light generating units 22 and so that the light generated by the light generating units 22 may be

reflected by the reflective cover 24 so as to propagate downwards so that the light would not dazzle our eyes and the light generating units 22 may become brighter and eye-friendly.

Now, please see Fig. 7, which illustrates the fifth embodiment as shown in
5 Fig. 6 in operation. When heat is generated by the light generating units 22, heat is quickly transferred to the heat dissipating unit 21 and then to the heat dissipating pieces 211. Heat is then dissipated into the ambient air. Because the heat dissipating pieces 211 point downwards, dusts would not fall and accumulate on the heat dissipating pieces 211 so that the heat dissipating pieces 211 may be kept
10 at their highest heat dissipating capacity.

Please see Fig. 8, which is a sixth embodiment of the present invention. The sixth embodiment of the present invention is similar to the fifth embodiment shown in Fig. 6 except that covers 23 are disposed on the reflective cover 24 so as to seal up light generating units 22.

15 In addition, the reflective cover may have a round shape, a rectangular shape, an oval shape or other shape.

In comparison to the prior art, the heat dissipating unit of the present invention has the following four advantages:

1. The heat dissipating unit of the present invention can prevent the
20 damages caused by dusts, water, insects, corrosion and erosion.

2. In the heat dissipating unit of the present invention, because the heat dissipating pieces of the heat dissipating unit extend downwards towards the ground, the heat dissipating capacity may be enhanced by the ambient cold air rising upwards and other undesirable factors (such as dusts) are kept off; therefore,
25 the heat dissipating pieces may be kept at their highest heat dissipating capacity.

3. In the heat dissipating unit of the present invention, an AC/DC adopter unit is used to supply DC (direct current) to the light generating units so as to be more economical (because no battery is needed).

4. In the heat dissipating unit of the present invention, a
5 programmable timer and sensor circuit and an overheating protection circuit are disposed in the AC/DC adopter unit. The programmable timer and sensor circuit serves as a timer so as to turn off or on the light generating units, while the overheating protection circuit can protect the light generating units from overheating.

10 Many changes and modifications in the above described embodiment of the invention can, of course, be carried out without departing from the scope thereof. Accordingly, to promote the progress in science and the useful arts, the invention is disclosed and is intended to be limited only by the scope of the appended claims.

What is claimed is:

1. A lamp with heat dissipating unit , comprising a heat dissipating unit (11), a light generating units plate (12) and heat conducting pieces (16) which are disposed in a completely sealed space created by a cover (17),
characterized in that a plurality of heat dissipating pieces (111) extend downwards from the heat dissipating unit (11),
the light generating units plate (12) is fixedly fitted to an opening at the central portion or other appropriate location of the heat dissipating unit (11) so that a plurality of light generating units (13) point downwards, and
a portion of each heat conducting piece (16) is in contact with the top surface of the light generating units plate (12) and other portions are in contact with the top surface of the heat dissipating unit (11),
whereby the heat generated by the light generating units (13) is transferred to the light generating units plate (12), the heat conducting pieces (16), heat dissipating unit (11) and the heat dissipating pieces (111) then finally into the ambient air.

2. A lamp with heat dissipating unit, comprising:

a heat dissipating unit (11), wherein an opening is provided at the central portion or other appropriate location of the heat dissipating unit (11) and a plurality of heat dissipating pieces (111) extending downwards from the bottom surface of the heat dissipating unit (11);

a light generating units plate (12), fixedly fitted to the opening so as to seal it up, wherein a plurality of light generating units (13) may be fitted on the underside or wide walls of the light generating units plate (12) so that the light generating units (13) may point downwards ;

one or more heat conducting pieces (16), wherein a portion of each heat conducting piece (16) is in contact with the top surface of the light generating units plate (12) and other portions are in contact with the top surface of the heat dissipating unit (11); and

a cover (17), fitted on top of the heat dissipating unit (11), wherein a completely sealed space is formed above the heat dissipating unit (11) so that the light generating units plate (12) and the heat conducting pieces (16) are disposed in such completely

sealed space.

3. A lamp with heat dissipating unit, comprising:

a heat dissipating unit (21), wherein a plurality of heat dissipating pieces (211) extends downwards from the bottom surface of the heat dissipating unit (21) and a set of light generating units (22) may be fitted on one side or both sides of the heat dissipating unit (21), and wherein a cover (23) is fitted onto each set of light generating units (22) so as to seal up the latter; and

a reflective cover (24), and is fixedly fitted on the top surface of the heat dissipating unit (21) so that the light generated by the light generating units (22) may be reflected by the reflective cover (24) so as to propagate downwards.

ABSTRACT OF THE DISCLOSURE

i A lamp with heat dissipating unit is disclosed. The
heat dissipating unit comprises a main body (1), which includes a cover. The
cover seals off the top of a heat dissipating unit (11), and hence a sealed space is
5 formed on the top portion of the heat dissipating unit (11). A plurality of light
generating units (13), a light generating units array plate (12), an AC/DC
converter (18) and at least one heat conducting pieces (16) are disposed in the
sealed space. The light generating units array plate is incorporated into the
opening which is located at the center or other appropriate position of the heat
10 dissipating unit. The light generating units (13) extend laterally or towards the
ground. The heat conducting pieces are disposed between the light generating
units array plate and the heat dissipating pieces (111). The AC/DC converter (18)
is provided in sealed space on top of light generating units array plate. The heat
dissipating pieces (111) provided on the heat dissipating unit extend laterally or
15 towards the ground. When heat is generated by the light generating units and the
AC/DC adapter unit, the heat is dissipated by the heat dissipating pieces