

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 October 2003 (02.10.2003)


PCT

(10) International Publication Number
WO 03/081192 A1

- (51) International Patent Classification⁷: G01K 1/02, 1/08, 7/02
- (21) International Application Number: PCT/US03/00914
- (22) International Filing Date: 13 January 2003 (13.01.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/100,606 18 March 2002 (18.03.2002) US
29/157,311 18 March 2002 (18.03.2002) US
- (71) Applicant (for all designated States except US): **TEXACO DEVELOPMENT CORPORATION** [US/US]; 6001 Bollinger Canyon Road, San Ramon, CA 94583-2324 (US).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **GROEN, John, Corwyn** [US/US]; 85 Derick Drive, Fishkill, NY 12524 (US).
- (74) Agents: **RODMAN, Philip et al.**; Rodman & Rodman, 7 South Broadway, White Plains, NY 10601 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,

[Continued on next page]

(54) Title: PROTECTIVE CAP FOR A THERMOCOUPLE IN A GASIFIER



(57) Abstract: The protective cap (80) for a thermocouple (44) in a gasifier (10) is installed at an opening of a thermocouple cavity in a hot-face lining of the reaction chamber of the gasifier. The cap is a generally disc-shaped structure that, in one embodiment, includes an upper slag deflecting surface over the receding surface to bypass the receding surface. A counterbore is formed in the refractory lining to accommodate the protective cap and to enable the protective cap to be recessed in the refractory lining. Holes can be formed in the cap with an upward incline to minimize the possibility of downwardly moving slag flowing through the holes into the thermocouple cavity (50). The holes can be made small enough to minimize the risk of allowing excessive radiant heat from reaching the gasifier vessel or shell (12). A peripheral edge of the cap has upper and lower portions that slope downwardly to help maintain the cap in its position in the counterbore.



SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*