

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 May 2006 (04.05.2006)

PCT

(10) International Publication Number
WO 2006/047349 A2

(51) International Patent Classification:
B23P 21/00 (2006.01)

(21) International Application Number:
PCT/US2005/038063

(22) International Filing Date: 21 October 2005 (21.10.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/971,489 22 October 2004 (22.10.2004) US

(71) Applicant (for all designated States except US): **FORM-FACTOR, INC.** [US/US]; 7005 Southfront Road, Livermore, CA 94551 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ELDRIDGE, Benjamin, N.** [US/US]; 651 Sheri Lane, Danville, CA 94526 (US). **MATHIEU, Gaetan, L.** [CA/CA]; 154 Chemin du Lac, Varennes, Québec 94550 (CA).

(74) Agents: **MERKADEAU, Stuart, L.** et al.; 7005 Southfront Road, Livermore, CA 94551 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTROFORM SPRING BUILT ON MANDREL TRANSFERABLE TO OTHER SURFACE



A



F

(57) Abstract: Resilient spring contact structures are manufactured by plating the contact structures on a reusable mandrel, as opposed to forming the contact structures on sacrificial layers that are later etched away. In one embodiment, the mandrel includes a form or mold area that is inserted through a plated through hole in a substrate. Plating is then performed to create the spring contact on the mold area of the mandrel as well as to attach the spring contact to the substrate. In a second embodiment, the mandrel includes a form that is initially plated to form the resilient contact structure and then attached to a region of a substrate without being inserted through the substrate. Attachment in the second embodiment can be achieved during the plating process used to form the spring contact, or by using a conductive adhesive, or solder either before or after releasing the spring contact from the mandrel.



WO 2006/047349 A2