

DESCRIPTION

PRODUCT DISCHARGING DEVICE

Field

[0001] The present invention relates to a product
5 discharging device, and more particularly, to a product
discharging device that is applied to a vending machine
vending product such as canned beverage or beverage in a
plastic bottle and that appropriately discharges product
stored in a product storage passage.

10 Background

[0002] In the related art, in a vending machine vending
product such as canned beverage or beverage in a plastic
bottle, a product storage rack is disposed in a product
storage in a main cabinet which is a main body of the
15 vending machine. The product storage rack includes a
product storage passage that extends in a vertical
direction and a product discharging device that is disposed
in a lower part of the product storage passage.

[0003] The product discharging device includes a lower
20 pedal, an upper pedal, a pedal stopper pin, and a rotation
stopper. The lower pedal is swingably disposed to move
forward to and backward from the product storage passage.
The upper pedal is swingably disposed to move forward to
and backward from the product storage passage in an area
25 above the lower pedal. The pedal stopper pin is coupled to
a pedal link linking the lower pedal and the upper pedal
and is movable with movement in the vertical direction of
the pedal link. Here, the pedal link is disposed to be
movable in the vertical direction and is linked to an AC
30 solenoid as an actuator. The pedal link moves upward by
supplying power to the AC solenoid. The rotation stopper
is swingably disposed to move forward to and backward from
the product storage passage along with the lower pedal by

linking the tip thereof to the lower pedal.

[0004] In such a product discharging device, in a standby state, the pedal link moves downward and the upper pedal moves backward from the product storage passage by
5 stopping the supply of power to the AC solenoid, and the lower pedal is held in a state in which the lower pedal moves forward to the product storage passage and downward movement of product is regulated by regulating backward movement of the rotation stopper due to the pedal stopper
10 pin.

[0005] When a product discharge command is issued, the pedal link moves upward by supplying power to the AC solenoid, the upper pedal moves forward to the product storage passage and comes in contact with a second lowest
15 product, and the lower pedal moves backward from the product storage passage and discharges the lowest product downward by releasing backward movement of the rotation stopper due to the pedal stopper pin.

[0006] The product discharging device includes a
20 blindfold plate in addition to the above-mentioned configuration. The blindfold plate is a flat panel-like member formed of a metal material and covers the side of the pedal stopper pin opposite to the product storage passage to improve antitheft capability (for example, see
25 Patent Literature 1).

Citation List

Patent Literature

[0007] Patent Literature 1: Japanese Laid-open Patent
Publication No. 2013-190927
30 Summary

Technical Problem

[0008] In the product discharging device proposed in Patent Literature 1, the blindfold plates corresponding to

the number of product discharging devices, that is, the number of product storage passages, are necessary. Since a vending machine is generally provided with plural product storage passages, the necessity for the blindfold plates
5 corresponding to the number of product storage passages causes an increase in manufacturing cost with an increase in the number of components.

[0009] The present invention is made in consideration of the above-mentioned circumstances and an object thereof is
10 to provide a product discharging device that can achieve a decrease in manufacturing cost and improvement in antitheft capability.

Solution to Problem

[0010] To achieve the above-described object, a product
15 discharging device according to the present invention includes: a lower pedal that is swingably disposed to move forward to and backward from a product storage passage storing input products in a vertical direction; an upper
20 pedal that is swingably disposed to move forward to and backward from the product storage passage in an area above the lower pedal; a pedal stopper pin that is coupled to a pedal link linking the lower pedal and the upper pedal and that is movable with movement in the vertical direction of the pedal link; and a rotation stopper of which a tip is
25 linked to the lower pedal and that is swingably disposed to move forward to and backward from the product storage passage along with the lower pedal, wherein in a standby state, the upper pedal moves backward from the product storage passage by causing the pedal link to move downward,
30 the lower pedal is held in a state in which the lower pedal moves forward to the product storage passage to regulate downward movement of the product by regulating backward movement of the rotation stopper due to the pedal stopper

pin, in an activated state, the upper pedal moves forward to the product storage passage to come in contact with a second lowest product by causing the pedal link to move upward and the lower pedal moves backward from the product storage passage to discharge a lowest product downward by releasing the regulation of the backward movement of the rotation stopper due to the pedal stopper pin, and the rotation stopper includes a blindfold portion that covers a side of the pedal stopper pin opposite to the product storage passage.

[0011] Moreover, in the above-described product discharging device according to the present invention, a protrusion protruding to the product storage passage is formed in the vicinity of an opening formed in an area above the upper pedal.

[0012] Moreover, in the above-described product discharging device according to the present invention, in the standby state, the lower pedal takes a first standby posture to regulate downward movement of the lowest product when the lowest product is placed on a top surface thereof and takes a second standby posture in which the tip is located higher than in the first standby posture when no product is placed on the top surface, and the product discharging device further comprises a sold-out detection switch that is switched to an ON state or an OFF state when the lower pedal takes the first standby posture and is switched to the OFF state or the ON state when the lower pedal takes the second standby posture so as to detect presence or absence of a product of the product storage passage.

Advantageous Effects of Invention

[0013] According to the present invention, since the rotation stopper includes a blindfold portion covering the

side of the pedal stopper pin opposite to the product storage passage, the blindfold plates as in the related art are not necessary and it is possible to decrease the number of components and to retain antitheft capability.

5 Accordingly, it is possible to achieve a decrease in manufacturing cost and improvement in antitheft capability.

Brief Description of Drawings

[0014] FIG. 1 is a cross-sectional side view illustrating an internal structure of a vending machine to which a product discharging device according to an embodiment of the present invention is applied when viewed from the right side.

FIG. 2 is a side view schematically illustrating the product dispensing system illustrated in FIG. 1 when viewed from the right side.

FIG. 3 is a front view of a first product discharging device illustrated in FIG. 1.

FIG. 4 is a perspective view of a second product discharging device illustrated in FIG. 1.

20 FIG. 5 is a rear view of the first product discharging device illustrated in FIG. 3.

FIG. 6 is a diagram schematically illustrating a principal part of the first product discharging device when viewed from the right side.

25 FIG. 7 is a diagram schematically illustrating a principal part of the first product discharging device when viewed from the right side.

FIG. 8 is a diagram schematically illustrating a principal part of the first product discharging device when viewed from the right side.

30 FIG. 9 is a diagram illustrating a principal part of the product dispensing system.

FIG. 10 is a diagram schematically illustrating a

configuration of a sold-out detection switch.

FIG. 11 is a perspective view of a rotation stopper constituting the first product discharging device.

FIG. 12 is an exploded perspective view illustrating
5 principal parts of a drive unit in the first product discharging device when viewed from the front-right side.

FIG. 13 is an exploded perspective view illustrating principal parts of the drive unit in the first product discharging device when viewed from the rear-left side.

10 FIG. 14 is a front view of a base of the first product discharging device.

FIG. 15 is a rear view of the base illustrated in FIG. 14.

FIG. 16 is a front view of the second product
15 discharging device.

FIG. 17 is a perspective view illustrating the second product discharging device when viewed from the front-right side.

FIG. 18 is a perspective view illustrating a mounted
20 state of a wiring cover.

FIG. 19 is a perspective view illustrating the mounted state of the wiring cover.

FIG. 20 is a diagram illustrating operations of the principal parts of the drive unit when viewed from the
25 front side.

FIG. 21 is a diagram illustrating the operations of the principal parts of the drive unit when viewed from the rear side.

FIG. 22 is a diagram illustrating a state in which the
30 second product discharging device is attached to the first product discharging device.

FIG. 23 is a diagram illustrating an operation of an inclined guide surface of a second sold-out link.

FIG. 24 is a diagram illustrating an operation of a contact piece of a pedal link.

Description of Embodiments

[0015] Hereinafter, a product discharging device
5 according to an exemplary embodiment of the present invention will be described in detail with reference to the accompanying drawings.

[0016] FIG. 1 is a cross-sectional side view
illustrating an internal structure of a vending machine to
10 which the product discharging device according to an embodiment of the present invention is applied when viewed from the right side. The vending machine exemplified herein vends product in a cooled or heated state and includes a main cabinet 1, an outer door 2, and an inner
15 door 3.

[0017] The main cabinet 1 has a rectangular
parallelepiped shape of which a front surface is opened by
appropriately combining plural steel sheets and includes a
product storage 4 having a heat-insulating structure
20 therein. The outer door 2 serves to cover the front opening of the main cabinet 1 and is disposed at one edge portion of the main cabinet 1 so as to be opened and closed. The front surface of the outer door 2 is provided with
elements required for vending product such as a display
25 window, a product selection button, a bill input port, a coin input port, a return lever, a built-in display, a coin return port, and a product output port 2a. The inner door 3 is a heat-insulating door which is divided into upper and lower parts to cover the front opening of the product
30 storage 4, an upper heat-insulating door 3a is disposed at a position inside the outer door 2 at one edge portion of the outer door 2 so as to be opened and closed, and a lower heat-insulating door 3b is disposed at one edge portion of

the main cabinet 1 so as to be opened and closed. A product discharge port 3c for discharging a product to the outside of the product storage 4 is disposed in a lower part of the lower heat-insulating door 3b of the inner door 3.

[0018] In the vending machine, a product chute 5 is disposed in the product storage 4, a temperature control unit 6 is disposed in an area below the product chute 5 (hereinafter, also referred to as a "heat exchange area"), and a product storage rack 10 is disposed in an area above the product chute 5 (hereinafter, also referred to as a "product storage area").

[0019] The product chute 5 is a plate-like member that guides a product discharged from the product storage rack 10 to the product discharge port 3c of the inner door 3 and is disposed to be gradually inclined downward toward the front side. Although not clearly illustrated in the drawing, plural vent holes (not illustrated) causing the heat exchange area and the product storage area to communicate with each other are formed in the product chute 5.

[0020] The temperature control unit 6 serves to maintain the internal atmosphere of the product storage 4 in a desired temperature state and includes an evaporator 6a, an electric heater 6b, and a blower fan 6c of a refrigeration cycle. In the temperature control unit 6, for example, when the blower fan 6c is driven in a state in which the refrigeration cycle operates, air cooled in the evaporator 6a is supplied upward through the vent holes of the product chute 5 and thus the product storage area can be maintained in a low-temperature state. On the other hand, when the blower fan 6c is driven in a state in which power is supplied to the electric heater 6b, air heated by the

electric heater 6b is supplied upward through the vent holes of the product chute 5 and thus the product storage area can be maintained in a high-temperature state.

Although not clearly illustrated in the drawing, a

5 compressor, a condenser, and an expansion valve of the refrigeration cycle are all disposed in a machine room 7 outside the product storage 4.

[0021] The product storage racks 10 are arranged in three lines in the front-rear direction, includes plural
10 (two in the illustrated example) product storage passages 13 which are disposed in a meandering shape in the vertical direction by disposing passage elements 12 between a pair of base side plates 11, and stores plural products with a sideways posture in the vertical direction in the product
15 storage passages 13. More specifically, the passage elements 12 are appropriately disposed on the front side and the rear side of the product storage passages 13 so as to face each other and are fixed to the base side plate 11. Accordingly, in each product storage rack 10, two product
20 storage passages 13 are disposed to be adjacent to each other in the front-rear direction. In the following description, the front product storage passage 13 in one product storage rack 10 is also referred to as a first product storage passage 13a and the rear product storage
25 passage 13 is also referred to as a second product storage passage 13b.

[0022] The passage elements 12 are provided with flappers which are not clearly illustrated in the drawing. The flappers are swingably disposed in the passage elements
30 12 so as to move forward to and backward from the product storage passage 13. The flappers are biased by coil springs (not illustrated) and moves forward to the product storage passages 13 in a normal state. The flapper moves

backward along the meandering product storage passage 13 against a bias force of the coil spring to correct the posture of a product by coming in contact with the product passing through the product storage passage 13.

5 [0023] In the product storage rack 10, a top tray 14 is disposed in the top of the product storage passage 13 and a product dispensing system 20 is disposed in the bottom of the product storage passage 13.

[0024] The top tray 14 is formed by bending a plate-like
10 metal sheet, and the top tray is disposed between the base side plates 11 so as to be gradually inclined downward from the front side to the rear side. The top surface of the top tray 14 constitutes a product guide passage 15 that guides a product input through an input port to the product
15 storage passage 13.

[0025] FIGS. 2 to 4 illustrate a product dispensing system illustrated in FIG. 1, where FIG. 2 is a side view, schematically illustrated, when viewed from the right side, FIG. 3 is a front view when viewed from the front side, and
20 FIG. 4 is a perspective view when viewed from the rear-left side.

[0026] As illustrated in FIGS. 2 to 4, the product dispensing system 20 includes one product discharging device (hereinafter, also referred to as a first product
25 discharging device) 20a and the other product discharging device (hereinafter, also referred to as a second product discharging device) 20b, where the first product discharging device 20a and the second product discharging device 20b are coupled to each other back to back and a
30 wiring cover 80 is attached thereto. FIGS. 2 to 4 illustrate a state in which the first product discharging device 20a and the second product discharging device 20b constituting the product dispensing system 20 store no

product.

[0027] FIG. 5 is a rear view of the first product discharging device 20a illustrated in FIGS. 2 and 3. In the following description, the configuration of the first product discharging device 20a will be first described and then the second product discharging device 20b and the wiring cover 80 will be described.

[0028] FIGS. 6 to 8 are diagrams schematically illustrating principal parts of the first product discharging device 20a when viewed from the right side. In the following description, the configuration of the first product discharging device 20a will be described appropriately with reference to FIGS. 6 to 8.

[0029] The first product discharging device 20a is applied to the first product storage passage 13a and is disposed in the bottom of the first product storage passage 13a. The first product discharging device 20a serves to store products in the first product storage passage 13a in a standby state and to discharge a product to the product chute 5 in an activated state by controlling behavior of product between an opposite passage width defining plate 16 and the first product discharging device, and includes a base 21.

[0030] The base 21 is formed by performing a cutting process and a bending process on a steel sheet and is disposed to cause its own surface to face the passage width defining plate 16. A side wall 21a of the base 21 is formed by bending both sides of the base and a first insertion hole 22 and a second insertion hole 23 are formed in an intermediate portion thereof. The circumferential edges of the first insertion hole 22 and the second insertion hole 23 are bent similarly to the side wall 21a to form a flange.

[0031] The first insertion hole 22 and the second insertion hole 23 are arranged in the right-left direction and have the same size in the vertical direction. Among the first insertion hole 22 and the second insertion hole 5 23, the first insertion hole 22 is located on the left side of the second insertion hole 23, and the width in the right-left direction of the first insertion hole 22 is larger than the width in the right-left direction of the second insertion hole 23. The first insertion hole 22 and 10 the second insertion hole 23 are through-openings (concave portions for enabling a lower pedal 28 and an upper pedal 29 to be described later to move backward into the base 21) having a substantially rectangular shape as a whole, the top end of the first insertion hole 22 protrudes to the 15 left side, and the top end of the second insertion hole 23 protrudes to the right side.

[0032] A first left bearing piece 22a is disposed at the left edge portion of the first insertion hole 22, a first right bearing piece 22b is disposed at the right edge 20 portion of the first insertion hole 22, a second left bearing piece 23a is disposed at the left edge portion of the second insertion hole 23, and a second right bearing piece 23b is disposed at the right edge portion of the second insertion hole 23. The first left bearing piece 22a 25 and the second right bearing piece 23b correspond to the flange formed at the circumferential edges of the first insertion hole 22 and the second insertion hole 23. The first right bearing piece 22b and the second left bearing piece 23a are formed integrally with the base 21 in which a 30 bearing portion 24 to be described later is fitted and supported and are formed in shaft insertion flanges forming both U-shaped leg portions in a bearing support portion formed in a U-shaped cross-section (discontinuous). The

bearing support portion has a function of maintaining the strength of the base 21 even when a large through-opening including the first insertion hole 22 and the second insertion hole 23 which form a substantially rectangular shape as a whole is formed in the base 21.

5 [0033] The bearing portion 24 and a sold-out detection switch 25 are attached to the base 21 having the above-mentioned configuration. The bearing portion 24 is formed of a resin material or the like and is interposed between the first right bearing piece 22b and the second left bearing piece 23a.

[0034] In the sold-out detection switch 25, as illustrated in FIG. 9, a first sold-out detection unit 25a and a second sold-out detection unit 25b are integrally disposed to be arranged in the front-rear direction. The sold-out detection switch 25 is a so-called push type switch and includes two contactors 251 and 252 that are biased to rise upright by a spring not illustrated. The sold-out detection switch 25 is switched to an OFF state to output an OFF signal when the first contactor 251 and the second contactor 252 are not pressed as illustrated in (a) of FIG. 10 and is switched to an ON state to output an ON signal when one of the first contactor 251 and the second contactor 252 is pressed and displaced against the biasing force of the spring as illustrated in (b) or (c) of FIG. 10. In this embodiment, the sold-out detection switch 25 is switched to the OFF state when the first contactor 251 and the second contactor 252 are not pressed and is switched to the ON state when one of the first contactor 251 and the second contactor 252 is pressed and displaced, but in the present invention, the sold-out detection switch may be switched to the ON state when the first contactor and the second contactor are not pressed and may be switched to the

OFF state when the first contactor and the second contactor are pressed and displaced.

[0035] The base 21 is provided with a first swing support shaft 28a and a second swing support shaft 29a.

5 The first swing support shaft 28a is an axial member which is disposed to extend substantially in the horizontal direction and to penetrate through-holes formed in the base 21 or the bearing portion 24, and supports the lower pedal 28 in the middle way thereof.

10 [0036] A first sold-out link 30 is disposed at the right end of the first swing support shaft 28a. As illustrated in FIG. 9, the first sold-out link 30 includes a first sold-out base portion 31 and a first sold-out pressing portion 32. The first sold-out base portion 31 is a
15 deformed portion in which a penetration portion penetrated by the right end of the first swing support shaft 28a is formed. The first sold-out pressing portion 32 protrudes to the right side from the top of the first sold-out base portion 31 and extends upward. The penetration portion
20 formed in the first sold-out base portion 31 is formed to be larger than the first swing support shaft 28a and is configured such that the first sold-out link 30 can freely move relative to the first swing support shaft 28a.

[0037] The second swing support shaft 29a is an axial
25 member disposed to penetrate the through-holes formed in the base 21 and the bearing portion 24 so as to extend substantially in the horizontal direction in an area above the first swing support shaft 28a, and supports the upper pedal 29 in the middle way thereof.

30 [0038] The lower pedal 28 is a plate-like member and is disposed to be swingable about the central axis of the first swing support shaft 28a by inserting the first swing support shaft 28a into the base end thereof.

[0039] The tip portion of the lower pedal 28 extends in an outer radial direction of the first swing support shaft 28a, and can move forward to and backward from the first product storage passage 13a via the first insertion hole 22 and the second insertion hole 23 when the lower pedal swings about the central axis of the first swing support shaft 28a. That is, the lower pedal 28 is swingably disposed to move forward to and backward from the first product storage passage 13a.

10 [0040] A lower pedal spring 28b is interposed between the lower pedal 28 and the base 21. The lower pedal spring 28b normally biases the lower pedal 28 in the forward moving direction to the first product storage passage 13a. More specifically, the lower pedal spring 28b causes the
15 lower pedal 28 to take a standby posture (hereinafter, also referred to as a product-absent standby posture) such that the tip portion of the lower pedal 28 is located higher than the first swing support shaft 28a as illustrated in FIG. 6. When product is placed on the top surface of the
20 lower pedal 28, the lower pedal spring 28b causes the lower pedal 28 to take a standby posture (hereinafter, also referred to as a product-present standby posture) such that the tip portion of the lower pedal 28 is located at the same height level as the first swing support shaft 28a as
25 illustrated in FIG. 7.

[0041] Accordingly, in the product-absent standby posture, the tip portion of the lower pedal 28 is located higher than in the product-present standby posture.

[0042] When the lower pedal 28 takes the product-absent standby posture, the base end of the lower pedal 28 comes in contact with a contact portion (not illustrated) disposed in the first sold-out base portion 31 in the first sold-out link 30 as indicated by a two-dot chained line in

FIG. 9, thus the first sold-out link 30 rotates about the first swing support shaft 28a, and thus the first sold-out pressing portion 32 presses the first contactor 251 of the sold-out detection switch 25. Accordingly, in the sold-out
5 detection switch 25, the first contactor 251 is pressed and displaced backward against the biasing force of the spring and is switched to the ON state, and thus an ON signal is output to the control unit.

[0043] On the other hand, when the lower pedal 28 takes
10 the product-present standby posture, the base end of the lower pedal 28 is separated from the contact portion of the first sold-out link 30 and thus the first sold-out link 30 is switched to a free state as indicated by a solid line in FIG. 9. Accordingly, in the sold-out detection switch 25,
15 the first contactor 251 is biased by the spring to rise upright and is switched to the OFF state, and thus an OFF signal is output to the control unit. That is, the first sold-out link 30 switched to the free state rotates about the first swing support shaft 28a by pressing the first
20 sold-out pressing portion 32 against the first contactor 251.

[0044] The lower pedal 28 includes a plate-like pedal body 281 and a pair of guide portions 282. The pair of guide portions 282 is disposed on the rear side of the
25 pedal body 281. Each guide portion 282 is a plate-like member extending in the vertical direction and both guide portions are formed to face each other. A guide groove 283 is formed on the facing surfaces of the guide portions 282.

[0045] The guide groove 283 includes a fitting portion
30 283a which is located at the lowest position in a state in which the lower pedal 28 is disposed at a forward-moved position at which the lower pedal most moves forward to the first product storage passage 13a (the state illustrated in

FIG. 6) and into which a pedal operating shaft 361 of a rotation stopper 36 to be described later is fitted, a contact portion 283d which is located at the highest position in a state in which the lower pedal 28 is disposed at a backward-moved position at which the lower pedal most moves backward from the first product storage passage 13a (the state illustrated in FIG. 8) and with which the pedal operating shaft 361 of the rotation stopper 36 comes in contact, and a first guide portion 283b and a second guide portion 283c which are continuously connected to the fitting portion 283a and the contact portion 283d.

[0046] The first guide portion 283b is formed in the guide portion 282 to be inclined obliquely upward from the fitting portion 283a so as to get away from the base 21, be inclined obliquely upward so as to get close to the base 21, and then reach the contact portion 283d in a state in which the lower pedal 28 is located at the position (forward-moved position) at which the lower pedal most moves forward to the first product storage passage 13a.

[0047] The second guide portion 283c is formed in the guide portion 282 to be inclined obliquely downward from the contact portion 283d so as to get away from the base 21 and then reach the fitting portion 283a in a state in which the lower pedal 28 is located at the position (forward-moved position) at which the lower pedal most moves forward to the first product storage passage 13a.

[0048] The length in the outer radial direction of the lower pedal 28 from the first swing support shaft 28a is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 16 and the lower pedal when the lower pedal is located at the position (forward-moved position) at which the lower pedal most

moves forward to the first product storage passage 13a.

[0049] The upper pedal 29 is a plate-like member and is disposed in the base 21 so as to be swingable about the central axis of the second swing support shaft 29a by inserting the second swing support shaft 29a into the base end thereof.

[0050] The tip portion of the upper pedal 29 extends in an outer radial direction of the second swing support shaft 29a, and can move forward to and backward from the first product storage passage 13a via the first insertion hole 22 and the second insertion hole 23 when the upper pedal swings about the central axis of the second swing support shaft 29a. That is, the upper pedal 29 is swingably disposed to move forward to and backward from the first product storage passage 13a.

[0051] An upper pedal spring (not illustrated) is interposed between the upper pedal 29 and the base 21. The upper pedal spring normally biases the upper pedal 29 in the backward moving direction to the first product storage passage 13a.

[0052] The upper pedal 29 is provided with a pressing inclined surface 291, a concave portion 292, a stopper contact portion 293, and a protrusion 294. The pressing inclined surface 291 is disposed in the tip portion of the upper pedal 29 and is a curved inclined surface which is formed to be gradually lowered toward the first product storage passage 13a when the upper pedal 29 moves backward from the first product storage passage 13a. The concave portion 292 is disposed on the rear side of the upper pedal 29 and is a set of concave places extending substantially in the horizontal direction and being formed to be opened to both side surfaces of the upper pedal 29. The stopper contact portion 293 is a portion with which a stopper pin

34a to be described later comes in contact and is disposed to be inclined to the upper side of the concave portion 292 on the rear surface of the upper pedal 29.

[0053] The protrusion 294 is disposed at the base end of
5 the upper pedal 29 so as to protrude toward the first product storage passage 13a.

[0054] The upper pedal 29 is biased to move backward from the first product storage passage 13a by a biasing force of the upper pedal spring, but the initial position
10 thereof is set in a state in which the upper pedal moves backward from the first product storage passage 13a by bringing the stopper pin 34a into contact with the concave portion 292.

[0055] The upper pedal 29 is inclined to the front side
15 with respect to the vertical plane passing through the second swing support shaft 29a in a state (the state illustrated in FIG. 8) in which the upper pedal is located at the position (forward-moved position) at which the upper pedal most moves forward to the first product storage
20 passage 13a. The length in the outer radial direction of the upper pedal 29 from the second swing support shaft 29a is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 16 and
25 the upper pedal in the state in which the upper pedal is inclined to the front side.

[0056] In the base 21, the stopper pin 34a, a pedal stopper pin 34b, and a stopper shaft 34c are disposed between the bearing portion 24 and the second right bearing
30 piece 23b.

[0057] The stopper pin 34a is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24 and the second right bearing piece

23b. The stopper pin 34a is coupled to a pedal link 35 and is movable in the vertical direction with the movement in the vertical direction of the pedal link 35. The stopper pin 34a comes in contact with the concave portion 292 of the upper pedal 29 located at the initial position.

[0058] The pedal stopper pin 34b is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24 and the second right bearing piece 23b. The pedal stopper pin 34b is coupled to the pedal link 35 and is movable in the vertical direction with the movement in the vertical direction of the pedal link 35.

[0059] The stopper shaft 34c is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24 and the second right bearing piece 23b. The stopper shaft 34c supports the rotation stopper 36 in the middle way thereof.

[0060] The rotation stopper 36 is disposed between the bearing portion 24 and the second right bearing piece 23b so as to insert the stopper shaft 34c into the insertion hole of the base end thereof and to be swingable about the central axis of the stopper shaft 34c.

[0061] The tip portion of the rotation stopper 36 extends in the outer radial direction of the stopper shaft 34c and is movable forward to and backward from the first product storage passage 13a via the second insertion hole 23 when the rotation stopper swings about the central axis of the stopper shaft 34c.

[0062] The rotation stopper 36 includes a pedal operating shaft 361 so as to insert the pedal operating shaft 361 into a through-hole 36a of the tip portion thereof. The pedal operating shaft 361 is an axial member which is disposed substantially in the horizontal direction and both ends thereof are fitted into the guide grooves 283

of the lower pedal 28.

[0063] A pedal operating spring (not illustrated) is interposed between the rotation stopper 36 and the base 21. The pedal operating spring normally biases the rotation stopper 36 in the forward moving direction to the first product storage passage 13a.

[0064] The rotation stopper 36 is biased in the forward moving direction to the first product storage passage 13a by the pedal operating spring, movement in the backward moving direction thereof is regulated by moving the pedal stopper pin 34b into a recessed portion 36b of the rotation stopper 36 to come in contact with the pedal stopper pin 34b, and the initial position thereof in the state in which the rotation stopper moves forward to the first product storage passage 13a is set. Since the lower pedal 28 is biased by the lower pedal spring 28b, the initial position of the rotation stopper 36 is set to a position at which both ends of the pedal operating shaft 361 are located in the fitting portion 283a of the guide grooves 283 and the lower pedal 28 moves forward to the first product storage passage 13a.

[0065] As illustrated in FIG. 11, the rotation stopper 36 is provided with a panel-like blindfold portion 36c extending upward on the rear side thereof, that is, on the rear side of the recessed portion 36b. The blindfold portion 36c covers a part of the pedal stopper pin 34b opposite to the first product storage passage 13a. More specifically, the blindfold portion 36c covers the part, which is opposite to the first product storage passage 13a, of the pedal stopper pin 34b moving in the vertical direction.

[0066] The pedal link 35 is a long plate-like member extending in the vertical direction and an upper portion

thereof is bent to the front side and then extends upward. The upper portion of the pedal link 35 is provided with a contact piece 351 extending backward and then extending obliquely upward and a locking portion 352 locking a link spring 35a. The link spring 35a is interposed between the pedal link 35 and the base 21 and normally biases the pedal link 35 downward.

[0067] In a state in which the pedal link 35 is biased by the link spring 35a and is located on the lower side, the concave portion 292 of the upper pedal 29 disposed at the backward-moved position comes in contact with the stopper pin 34a. The rotation stopper 36 disposed at the forward-moved position comes in contact with the pedal stopper pin 34b to regulate the backward movement of the rotation stopper 36. The pedal operating shaft 361 of the rotation stopper 36 disposed at the forward-moved position is fitted into the fitting portion 283a of the lower pedal 28 to regulate the backward movement of the lower pedal 28 disposed at the forward-moved position.

[0068] On the other hand, in the state in which the pedal link 35 is located on the upper side against the biasing force of the link spring 35a, as illustrated in FIG. 8, the stopper contact portion 293 of the upper pedal 29 comes in contact with the stopper pin 34a to regulate the backward movement of the upper pedal 29, and the upper pedal 29 moves forward against the biasing force of the upper pedal spring and is disposed at the forward-moved position.

[0069] On the other hand, since the regulation of the backward movement due to the pedal stopper pin 34b is released, the regulation of the backward movement of the rotation stopper 36 with respect to the stopper shaft 34c is released. Here, the weight of a product coming in

contact with the lower pedal 28 maintained at the forward-moved position by the rotation stopper 36 is applied to the rotation stopper 36, and the rotation stopper 36 starts its backward movement with releasing the regulation of the
5 backward movement of the rotation stopper 36. When the backward movement of the rotation stopper 36 is started, the pedal operating shaft 361 departs from the fitting portion 283a of the lower pedal 28. Accordingly, the lower pedal 28 is allowed to move backward about the first swing
10 support shaft 28a and moves backward against the elastic biasing force of the lower pedal spring 28b by the weight of the product (see FIG. 8).

[0070] When the lower pedal 28 moves backward in this way, the base end of the lower pedal 28 is separated from a
15 first sold-out contact portion 283d of the first sold-out link 30 and thus the first sold-out link 30 is switched to the free state. Accordingly, in the sold-out detection switch 25, the first contactor 251 is biased by the spring to rise upright and thus to maintain the OFF state. That
20 is, when the lower pedal 28 moves backward, similarly to the product-present standby posture, the first sold-out link 30 does not press the first contactor 251 of the sold-out detection switch 25.

[0071] The first product discharging device 20a having
25 the above-mentioned configuration includes a drive unit 40, a cover flapper 50, and a lever member 60 in addition to the above-mentioned configuration.

[0072] FIGS. 12 and 13 illustrate principal parts of the drive unit 40 in the first product discharging device 20a,
30 where FIG. 12 is an exploded perspective view thereof when viewed from the front-right side and FIG. 13 is an exploded perspective view thereof when viewed from the rear-left side.

[0073] The drive unit 40 is disposed in an upper center area of the rear side of the base 21. The drive unit 40 includes a unit base 42 which is attached to the rear surface of the base 21.

5 [0074] The unit base 42 is formed of, for example, a resin material and is formed in a box shape of which the rear surface is opened. In the unit base 42, the opening of the rear surface is closed by attaching a unit cover 41 formed of a resin thereto, thereby forming a storage space
10 between the unit base and the unit cover 41. A motor 43, a gear member 44, a carrier switch 45, and a link lever 46 are stored in the storage space formed by the unit base 42 and the unit cover 41.

[0075] The motor 43 serves as a drive source and is a DC
15 motor that is rotatable positively and reversely and that is driven in accordance with a command issued from the control unit not illustrated. The motor 43 is disposed in a state in which the motor is held by a motor holding portion 41a of the unit base 42.

20 [0076] The gear member 44 includes a worm gear 441, an intermediate gear 442, and an output gear 443. The worm gear 441 includes a worm 441a and a worm wheel 441b.

[0077] The worm 441a has a cylindrical shape and is attached to an output shaft 43a of the motor 43. The worm
25 wheel 441b includes a first worm wheel 441b1 having a disk shape and a second worm wheel 441b2 having a disk shape.

[0078] In the first worm wheel 441b1, an axial portion protruding rearward is formed at the center thereof and a gear portion including plural teeth is formed on the
30 circumferential surface thereof.

[0079] The second worm wheel 441b2 is located on the front side of the first worm wheel 441b1 and is formed such that an axial portion of which the central axis matches the

central axis of the axial portion of the first worm wheel 441b1 protrudes to the front side. A gear portion including plural teeth is also formed on the circumferential surface of the second worm wheel 441b2.

5 [0080] The worm wheel 441b is disposed to be rotatable about the central axis of the axial portion by inserting the axial portion into concave portions 41b and 42b of the unit base 42 and the unit cover 41 in a state in which the gear portion of the first worm wheel 441b1 engages with the
10 worm 441a.

[0081] The intermediate gear 442 includes a disk-like first intermediate gear 442a and a disk-like second intermediate gear 442b. In the first intermediate gear 442a, an axial portion protruding to the rear side is
15 formed at the center thereof and a gear portion including plural teeth is formed on the circumferential surface thereof.

[0082] The second intermediate gear 442b is located on the rear side of the first intermediate gear 442a and is
20 disposed such that an axial portion of which the central axis matches the central axis of the axial portion of the first intermediate gear 442a protrudes to the front side. A gear portion including plural teeth is also formed on the circumferential surface of the second intermediate gear
25 442b.

[0083] The intermediate gear 442 is disposed to be rotatable about the central axis of the axial portion by inserting the axial portion into concave portions 41c and 42c of the unit base 42 and the unit cover 41 in a state in
30 which the gear portion of the first intermediate gear 442a engages with the gear portion of the second worm wheel 441b2.

[0084] The output gear 443 has a disk shape having a

diameter larger than that of the worm wheel 441b or the intermediate gear 442. A gear portion including plural teeth is also formed on the circumferential surface of the output gear 443. An axial portion protruding in the front-rear direction is formed at the center of the output gear 443. A cam portion 443a is formed on the front surface of the output gear 443 and a pressing piece 443b is formed on the rear surface thereof.

[0085] The cam portion 443a has an arc shape and is formed to protrude to the front side. The cam portion 443a is formed such that the length of the arc shape thereof is set to a size sufficient for holding a state in which the pedal link 35 has moved upward.

[0086] The pressing piece 443b has a substantially V shape and is formed to protrude to the rear side on the rear surface opposite to the cam portion 443a.

[0087] The output gear 443 is disposed to be rotatable about the central axis of the axial portion by inserting the axial portion into concave portions 41d and 42d of the unit base 42 and the unit cover 41 in a state in which the gear portion engages with the gear portion of the second intermediate gear 442b.

[0088] The carrier switch 45 is a so-called push type switch and includes a contactor 45a. The carrier switch 45 is disposed in the unit base 42 in a state in which the carrier switch is held slightly above the area in which the output gear 443 is disposed. The carrier switch 45 is switched to an ON state to supply details thereof as an ON signal to the control unit when the contactor 45a is pressed, and is switched to an OFF state to supply details thereof as an OFF signal to the control unit when the contactor 45a is not pressed.

[0089] The link lever 46 includes a first link lever 461

and a second link lever 462. The first link lever 461 is formed of, for example, a resin material and a through-hole 461a1 is formed at a base end 461a thereof. The first link lever 461 has a hook shape in which a tip portion 461b
5 extends obliquely downward to the right side from the base end 461a and is then curved obliquely upward to the right side. The base end 461a of the first link lever 461 is provided with a locking portion 461c. The locking portion 461c is a plate-like elastic member which extends downward
10 from the left end of the base end 461a and which is elastically deformable.

[0090] The first link lever 461 is disposed to be rotatable about the central axis of a first link shaft 42e on the front side of the output gear 443 by inserting the
15 first link shaft 42e disposed in the unit cover 41 into the through-hole 461a1 of the base end 461a. In this case, the first link lever 461 penetrates a right opening (not illustrated) formed by the unit base 42 and the unit cover 41 and the tip portion 461b is located outside the unit
20 base 42 and the unit cover 41. The posture in the normal state of the first link lever 461 is determined by bringing the locking portion 461c into contact with a left edge portion 471 of the right opening.

[0091] The second link lever 462 is formed of, for
25 example, a resin material and a through-hole 462a1 is formed at a base end 462a thereof. The second link lever 462 has a hook shape in which a tip portion 462b extends obliquely downward to the left side from the base end 462a and is then curved obliquely upward to the left side. The
30 tip portion 462b of the second link lever 462 has a width in the front-rear direction larger than that of the tip portion 461b of the first link lever 461. The base end 462a of the second link lever 462 is provided with a

locking portion 462c. The locking portion 462c is a plate-like elastic member which extends downward from the right end of the base end 462a and which is elastically deformable.

5 [0092] The second link lever 462 is disposed to be rotatable about the central axis of a second link shaft 42f on the front side of the output gear 443 by inserting the second link shaft 42f disposed in the unit cover 41 into the through-hole 462a1 of the base end 462a. In this case,
10 the second link lever 462 penetrates a left opening (not illustrated) formed by the unit base 42 and the unit cover 41 and the tip portion 461b is located outside the unit base 42 and the unit cover 41. The posture in the normal state of the second link lever 462 is determined by
15 bringing the locking portion 462c into contact with a right edge portion 472 of the left opening.

[0093] The cover flapper 50 is a long member which has a width in the right-left direction slightly smaller than that of the base 21 and of which the right-left direction
20 is the length direction thereof as illustrated in FIGS. 14 and 15. In the cover flapper 50, a first tongue-like portion 51 is formed at an upper end of the central portion thereof and a second tongue-like portion 52 is formed on the left side of the first tongue-like portion 51. A cut-
25 raised portion 51a is formed in the first tongue-like portion 51.

[0094] In the cover flapper 50, the cut-raised portion 51a comes in contact with the rear surface of the base 21 by inserting the first tongue-like portion 51 into a first
30 axial support hole 211 formed at the center of the base 21 from the front side, and the cover flapper is disposed to be swingable so as to move forward to and backward from the first product storage passage 13a by inserting the second

tongue-like portion 52 into a second axial support hole 212 formed on the left side of the base 21 from the front side. The cover flapper 50 is pressed by the upper pedal 29 to move forward when the upper pedal 29 moves forward to the
5 first product storage passage 13a and moves backward along with the upper pedal 29 when the upper pedal 29 moves backward from the first product storage passage 13a. Here, the second tongue-like portion 52 is inserted into the second axial support hole 212 to regulate the rotational
10 movement of the cover flapper 50 about the first tongue-like portion 51 in the clockwise or counterclockwise direction in a front view.

[0095] In an area above the position at which the cover flapper 50 is disposed, that is, in an area above the upper
15 pedal 29, in the base 21 constituting the first product discharging device 20a, protrusions 213 protruding to the first product storage passage 13a are formed in an upper edge portion and a lower edge portion in the vicinity of plural openings to be formed.

[0096] The lever member 60 is swingably disposed to be movable forward to and backward from the first product storage passage 13a in a state in which the lever member penetrates a lever opening 214 of the right top end of the base 21. More specifically, a pair of right and left lever
20 locking pieces 215 protruding to the rear side is formed on both edges of the lever opening 214 on the rear side of the base 21, and the lever member 60 is disposed to be swingable about the axis of shaft portions 61 formed in the lever locking pieces 215 as illustrated in FIGS. 3 and 5.
25 A lever spring 62 is interposed between the lever member 60 and the base 21 so as to be wound on the shaft portion 61, and the lever member 60 is biased by the lever spring 62 and takes a posture in which the tip portion 461b moves

forward to the first product storage passage 13a in a normal state.

[0097] FIG. 16 is a front view illustrating the second product discharging device illustrated in FIGS. 2 and 4 when viewed from the front side and FIG. 17 is a diagram schematically illustrating principal parts of the second product discharging device when viewed from the right side. The most elements of the second product discharging device 20b are common to the elements of the first product discharging device 20a and are different from the elements of the first product discharging device 20a, in that the front-rear direction is different and thus the right-left direction is reversed. Accordingly, in the description of the second product discharging device 20b, the elements will be appropriately omitted, and the elements of the second product discharging device 20b common to the elements of the first product discharging device 20a will be referenced by adding "'" to the reference signs in the first product discharging device 20a and will be described in brief.

[0098] The second product discharging device 20b is applied to the second product storage passage 13b and is disposed in the bottom of the second product storage passage 13b. The second product discharging device 20b serves to store products in the second product storage passage 13b in a standby state and to discharge a product to the product chute 5 in an activated state by controlling behavior of product between an opposite passage width defining plate 17 and the second product discharging device, and includes a base 21'.

[0099] The base 21' is formed by performing a cutting process and a bending process on a steel sheet and is disposed to cause its own surface to face the passage width

defining plate 17. A side wall 21a' of the base 21' is formed by bending both sides and a first insertion hole 22' and a second insertion hole 23' are formed in an intermediate portion thereof. The circumferential edges of the first insertion hole 22' and the second insertion hole 23' are bent similarly to the side wall 21a' to form a flange.

[0100] The first insertion hole 22' and the second insertion hole 23' are arranged in the right-left direction and have the same size in the vertical direction. Among the first insertion hole 22' and the second insertion hole 23', the first insertion hole 22' is located on the right side of the second insertion hole 23', and the width in the right-left direction of the first insertion hole 22' is larger than the width in the right-left direction of the second insertion hole 23'. The first insertion hole 22' and the second insertion hole 23' are through-openings (concave portions for enabling the lower pedal 28' and the upper pedal 29' to be described later to move backward into the base 21') having a substantially rectangular shape as a whole, the top end of the first insertion hole 22' protrudes to the right side, and the top end of the second insertion hole 23' protrudes to the left side. A first right bearing piece 22a' is disposed at the right edge portion of the first insertion hole 22', a first left bearing piece 22b' is disposed at the left edge portion of the first insertion hole 22', a second right bearing piece 23a' is disposed at the right edge portion of the second insertion hole 23', and a second left bearing piece 23b' is disposed at the left edge portion of the second insertion hole 23'. The first left bearing piece 22b' and the second right bearing piece 23a' correspond to the flange formed at the circumferential edges of the first

insertion hole 22' and the second insertion hole 23'. The first left bearing piece 22b' and the second right bearing piece 23a' are formed integrally with the base 21' in a place in which a bearing portion 24' to be described later is fitted and supported and are formed in shaft insertion flanges forming both U-shaped leg pieces in a bearing support portion formed in a U-shaped cross-section (discontinuous). The bearing support portion has a function of maintaining the strength of the base 21' even when a large through-opening including the first insertion hole 22' and the second insertion hole 23' which form a substantially rectangular shape as a whole is formed in the base 21'.

[0101] The bearing portion 24' is attached to the base 21' having the above-mentioned configuration. The bearing portion 24' is formed of a resin material or the like and is interposed between the first left bearing piece 22b' and the second right bearing piece 23a'.

[0102] The base 21' is provided with a first swing support shaft 28a' and a second swing support shaft 29a'. The first swing support shaft 28a' is an axial member which is disposed to extend substantially in the horizontal direction and to penetrate through-holes formed in the base 21' and the bearing portion 24', and supports the lower pedal 28' in the middle.

[0103] A second sold-out link 70 is disposed at the right end of the first swing support shaft 28a'. As illustrated in FIG. 9, the second sold-out link 70 includes a second sold-out base portion 71 and a second sold-out pressing portion 72. The second sold-out base portion 71 is a deformed portion in which a penetration portion penetrated by the right end of the first swing support shaft 28a' is formed. The second sold-out pressing portion

72 protrudes to the right side from the top of the second sold-out base portion 71 and extends upward. The penetration portion formed in the second sold-out base portion 71 is formed to be larger than the first swing support shaft 28a' and is configured such that the second sold-out link 70 freely moves relative to the first swing support shaft 28a'.

[0104] In the second sold-out link 70, an inclined guide surface 73 is formed at the upper end of the second sold-out base portion 71. The inclined guide surface 73 is gradually inclined downward to the front side, that is, is gradually inclined downward as it approaches the first product discharging device 20a.

[0105] The second sold-out link 70 is disposed to interpose the sold-out detection switch 25 between the first sold-out link 30 and the second sold-out link. In other words, the sold-out detection switch 25 is interposed between the first sold-out link 30 and the second sold-out link 70.

[0106] The second swing support shaft 29a' is an axial member disposed to penetrate the through-holes formed in the base 21' and the bearing portion 24' so as to extend in the substantially horizontal direction in an area above the first swing support shaft 28a', and supports the upper pedal 29' in the middle.

[0107] The lower pedal 28' is a plate-like member and is disposed to be swingable about the central axis of the first swing support shaft 28a' by inserting the first swing support shaft 28a' into the base end thereof.

[0108] The tip portion of the lower pedal 28' extends in an outer radial direction of the first swing support shaft 28a', and can move forward to and backward from the second product storage passage 13b via the first insertion hole

22' and the second insertion hole 23' when the lower pedal swings about the central axis of the first swing support shaft 28a'. That is, the lower pedal 28' is swingably disposed to move forward to and backward from the second product storage passage 13b.

[0109] A lower pedal spring 28b' is interposed between the lower pedal 28 and the base 21'. The lower pedal spring 28b' normally biases the lower pedal 28' in the forward moving direction to the second product storage passage 13b. More specifically, the lower pedal spring 28b' causes the lower pedal 28' to take a standby posture (hereinafter, also referred to as a product-absent standby posture) such that the tip portion of the lower pedal 28' is located higher than the first swing support shaft 28a' as illustrated in FIG. 17. When product is placed on the top surface of the lower pedal 28', the lower pedal spring 28b' causes the lower pedal 28' to take a standby posture (hereinafter, also referred to as a product-present standby posture) such that the tip portion of the lower pedal 28' is located at the same height level as the first swing support shaft 28a'.

[0110] Accordingly, in the product-absent standby posture, the tip portion of the lower pedal 28' is located higher than that of the product-present standby posture.

[0111] When the lower pedal 28' takes the product-absent standby posture, the base end of the lower pedal 28' comes in contact with a contact portion (not illustrated) disposed in the second sold-out base portion 71 in the second sold-out link 70 as indicated by a two-dot chained line in FIG. 9, thus the second sold-out link 70 rotates about the first swing support shaft 28a', and thus the second sold-out pressing portion 72 presses the second contactor 252 of the sold-out detection switch 25.

Accordingly, in the sold-out detection switch 25, the second contactor 252 is pressed and displaced backward against the biasing force of the spring and is switched to the ON state, and thus an ON signal is output to the control unit.

[0112] On the other hand, when the lower pedal 28' takes the product-present standby posture, the base end of the lower pedal 28' is separated from the contact portion of the second sold-out link 70 and thus the second sold-out link 70 is switched to a free state as indicated by a solid line in FIG. 9. Accordingly, in the sold-out detection switch 25, the second contactor 252 is biased by the spring to rise upright and is switched to the OFF state, and thus an OFF signal is output to the control unit. That is, the second sold-out link 70 switched to the free state rotates about the first swing support shaft 28a' by pressing the second sold-out pressing portion 72 against the second contactor 252.

[0113] The lower pedal 28' includes a plate-like pedal body 281' and a pair of guide portions 282'. The pair of guide portions 282' is disposed on the rear side of the pedal body 281'. Each guide portion 282' is a plate-like member extending in the vertical direction and both are formed to face each other. A guide groove (not illustrated) is formed on the facing surfaces of the guide portions 282'.

[0114] The guide groove includes a fitting portion which is located at the lowest position in a state in which the lower pedal 28' is disposed at a forward-moved position at which the lower pedal most moves forward to the second product storage passage 13b and into which a pedal operating shaft (not illustrated) of a rotation stopper 36' to be described later is fitted, a contact portion which is

located at the highest position in a state in which the lower pedal 28' is disposed at a backward-moved position at which the lower pedal most moves backward from the second product storage passage 13b and with which the pedal
5 operating shaft of the rotation stopper 36' comes in contact, and a first guide portion and a second guide portion which are continuously connected to the fitting portion and the contact portion.

[0115] The first guide portion is formed in the guide
10 portion 282' to be inclined obliquely upward from the fitting portion so as to get away from the base 21', be inclined obliquely upward so as to get close to the base 21', and then reach the contact portion in a state in which the lower pedal 28' is located at the position (forward-
15 moved position) at which the lower pedal most moves forward to the second product storage passage 13b.

[0116] The second guide portion is formed in the guide
portion 282' to be inclined obliquely downward from the contact portion so as to get away from the base 21' and
20 then reach the fitting portion in a state in which the lower pedal 28' is located at the position (forward-moved position) at which the lower pedal most moves forward to the second product storage passage 13b.

[0117] The length in the outer radial direction of the
25 lower pedal 28' from the first swing support shaft 28a' is set to a length with which a gap smaller than the maximum width of a product having a small maximum width can be secured between the passage width defining plate 17 and the lower pedal when the lower pedal is located at the position
30 (forward-moved position) at which the lower pedal most moves forward to the second product storage passage 13b.

[0118] The upper pedal 29' is a plate-like member and is disposed in the base 21' so as to be swingable about the

central axis of the second swing support shaft 29a' by inserting the second swing support shaft 29a' into the base end thereof.

[0119] The tip portion of the upper pedal 29' extends in
5 an outer radial direction of the second swing support shaft 29a', and can move forward to and backward from the second product storage passage 13b via the first insertion hole 22' and the second insertion hole 23' when the upper pedal swings about the central axis of the second swing support
10 shaft 29a'. That is, the upper pedal 29' is swingably disposed to move forward to and backward from the second product storage passage 13b.

[0120] An upper pedal spring (not illustrated) is interposed between the upper pedal 29' and the base 21'.
15 The upper pedal spring normally biases the upper pedal 29' in the backward moving direction to the second product storage passage 13b.

[0121] The upper pedal 29' is provided with a pressing inclined surface 291', a concave portion 292', a stopper
20 contact portion 293', and a protrusion 294'. The pressing inclined surface 291' is disposed in the tip portion of the upper pedal 29' and is a curved inclined surface which is formed to be gradually lowered toward the second product storage passage 13b when the upper pedal 29' moves backward
25 from the second product storage passage 13b. The concave portion 292' is disposed on the rear side of the upper pedal 29' and is a set of concave places extending substantially in the horizontal direction and being formed to be opened to both side surfaces of the upper pedal 29'.
30 The stopper contact portion 293' is a portion with which a stopper pin to be described later comes in contact and is disposed to be inclined to the upper side of the concave portion 292' on the rear surface of the upper pedal 29'.

[0122] The protrusion 294' is disposed at the base end of the upper pedal 29' so as to protrude toward the second product storage passage 13b.

[0123] The upper pedal 29' is biased to move backward
5 from the second product storage passage 13b by a biasing force of the upper pedal spring, but the initial position thereof is set in a state in which the upper pedal moves backward from the second product storage passage 13b by bringing the stopper pin into contact with the concave
10 portion 292'.

[0124] The upper pedal 29' is inclined to the front side with respect to the vertical plane passing through the second swing support shaft 29a' in a state in which the upper pedal is located at the position (forward-moved
15 position) at which the upper pedal most moves forward to the second product storage passage 13b. The length in the outer radial direction of the upper pedal 29' from the second swing support shaft 29a' is set to a length with which a gap smaller than the maximum width of a product
20 having a small maximum width can be secured between the passage width defining plate 17 and the upper pedal in the state in which the upper pedal is inclined to the front side.

[0125] In the base 21', the stopper pin (not
25 illustrated), the pedal stopper pin 34b', and the stopper shaft 34c' are disposed between the bearing portion 24' and the second left bearing piece 23b'.

[0126] The stopper pin is an axial member which is disposed substantially in the horizontal direction between
30 the bearing portion 24' and the second left bearing piece 23b'. The stopper pin is coupled to the pedal link 35' and is movable in the vertical direction with the movement in the vertical direction of the pedal link 35'. The stopper

pin comes in contact with the concave portion 292' of the upper pedal 29' located at the initial position.

[0127] The pedal stopper pin 34b' is an axial member which is disposed substantially in the horizontal direction
5 between the bearing portion 24' and the second left bearing piece 23b'. The pedal stopper pin 34b' is coupled to the pedal link 35' and is movable in the vertical direction with the movement in the vertical direction of the pedal link 35'.

10 [0128] The stopper shaft 34c' is an axial member which is disposed substantially in the horizontal direction between the bearing portion 24' and the second left bearing piece 23b' and supports the rotation stopper 36' in the middle thereof.

15 [0129] The rotation stopper 36' is disposed between the bearing portion 24' and the second left bearing piece 23b' so as to insert the stopper shaft 34c' into the insertion hole of the base end thereof and to be swingable about the central axis of the stopper shaft 34c'.

20 [0130] The tip portion of the rotation stopper 36' extends in the outer radial direction of the stopper shaft 34c' and is movable forward to and backward from the second product storage passage 13b via the second insertion hole 23' when the rotation stopper swings about the central axis
25 of the stopper shaft 34c'.

[0131] The rotation stopper 36' includes a pedal operating shaft so as to insert the pedal operating shaft (not illustrated) into the through-hole (not illustrated) of the tip portion thereof. The pedal operating shaft is
30 an axial member which is disposed substantially in the horizontal direction and both ends thereof are fitted into the guide grooves of the lower pedal 28'.

[0132] A pedal operating spring (not illustrated) is

interposed between the rotation stopper 36' and the base 21'. The pedal operating spring normally biases the rotation stopper 36' in the forward moving direction to the second product storage passage 13b.

5 [0133] The rotation stopper 36' is biased in the forward moving direction to the second product storage passage 13b by the pedal operating spring, movement in the backward moving direction thereof is regulated by moving the pedal stopper pin 34b' into a recessed portion 36b' of the
10 rotation stopper 36' to come in contact with the pedal stopper pin 34b', and the initial position thereof in the state in which the rotation stopper moves forward to the second product storage passage 13b is set. Since the lower pedal 28' is biased by the lower pedal spring 28b', the
15 initial position of the rotation stopper 36' is set to a position at which both ends of the pedal operating shaft are located in the fitting portion of the guide grooves and the lower pedal 28' moves forward to the second product storage passage 13b.

20 [0134] The rotation stopper 36' is provided with a panel-like blindfold portion 36c' extending upward on the rear side thereof, that is, on the rear side of the recessed portion 36b'. The blindfold portion 36c' covers a part of the pedal stopper pin 34b' opposite to the second
25 product storage passage 13b. More specifically, the blindfold portion 36c' covers the part, which is opposite to the second product storage passage 13b, of the pedal stopper pin 34b' moving in the vertical direction.

[0135] The pedal link 35' is a long plate-like member
30 extending in the vertical direction and an upper portion thereof is bent to the rear side and then extends upward. The upper portion of the pedal link 35' is provided with a contact piece 351' extending forward and then extending

obliquely upward and a locking portion 352' locking a link spring 35a'. The link spring 35a' is interposed between the pedal link 35' and the base 21' and normally biases the pedal link 35' downward.

5 [0136] In a state in which the pedal link 35' is biased by the link spring 35a' and is located at a reference position on the lower side, the concave portion 292' of the upper pedal 29' disposed at the backward-moved position comes in contact with the stopper pin. The rotation
10 stopper 36' disposed at the forward-moved position comes in contact with the pedal stopper pin 34b' to regulate the backward movement of the rotation stopper 36'. The pedal operating shaft of the rotation stopper 36' disposed at the forward-moved position is fitted into the fitting portion
15 of the lower pedal 28' to regulate the backward movement of the lower pedal 28' disposed at the forward-moved position.

[0137] On the other hand, in the state in which the pedal link 35' is located on the upper side against the biasing force of the link spring 35a', the stopper contact
20 portion 293' of the upper pedal 29' comes in contact with the stopper pin to regulate the backward movement of the upper pedal 29', and the upper pedal 29' moves forward against the biasing force of the upper pedal spring and is disposed at the forward-moved position.

25 [0138] On the other hand, since the regulation of the backward movement due to the pedal stopper pin 34b' is released, the regulation of the backward movement of the rotation stopper 36' with respect to the stopper shaft 34c' is released. Here, the weight of a product coming in
30 contact with the lower pedal 28' maintained at the forward-moved position by the rotation stopper 36' is applied to the rotation stopper 36', and the rotation stopper 36' starts its backward movement with releasing the regulation

of the backward movement of the rotation stopper 36'. When the backward movement of the rotation stopper 36 is started, the pedal operating shaft departs from the fitting portion of the lower pedal 28'. Accordingly, the lower pedal 28' is allowed to move backward about the first swing support shaft 28a' and moves backward against the elastic biasing force of the lower pedal spring 28b' by the weight of the product.

5 [0139] When the lower pedal 28' moves backward in this way, the base end of the lower pedal 28' is separated from a second sold-out contact portion of the second sold-out link 70 and thus the second sold-out link 70 is switched to the free state. Accordingly, in the sold-out detection switch 25, the second contactor 252 is biased by the spring to rise upright and thus to maintain the OFF state. That is, when the lower pedal 28' moves backward, similarly to the product-present standby posture, the second sold-out link 70 does not press the second contactor 252 of the sold-out detection switch 25.

15 [0140] The second product discharging device 20b having such a configuration includes a cover flapper 50' and a lever member 60' in addition to the above-mentioned configuration.

[0141] The cover flapper 50' is a long member which has a width in the right-left direction slightly smaller than that of the base 21' and of which the right-left direction is the length direction thereof as illustrated in FIGS. 4 and 16. In the cover flapper 50', a first tongue-like portion 51' is formed at an upper end of the central portion thereof and a second tongue-like portion 52' is formed on the right side of the first tongue-like portion 51'. A cut-raised portion 51a' is formed in the first tongue-like portion 51'.

[0142] In the cover flapper 50', the cut-raised portion 51a' comes in contact with the front surface of the base 21' by inserting the first tongue-like portion 51' into a first axial support hole 211' formed at the center of the base 21' from the front side and the cover flapper is disposed to be swingable so as to move forward to and backward from the first product storage passage 13a by inserting the second tongue-like portion 52' into a second axial support hole 212' formed on the right side of the base 21' from the front side. The cover flapper 50' is pressed by the upper pedal 29' to move forward when the upper pedal 29' moves forward to the first product storage passage 13a and moves backward along with the upper pedal 29' when the upper pedal 29' moves backward from the first product storage passage 13a. Here, the second tongue-like portion 52' is inserted into the second axial support hole 212' to regulate the rotational movement of the cover flapper 50' about the first tongue-like portion 51' in the clockwise or counterclockwise direction in a rear view.

[0143] In an area above the position at which the cover flapper 50' is disposed, that is, in an area above the upper pedal 29', in the base 21' constituting the second product discharging device 20b, protrusions 213' protruding to the second product storage passage 13b are formed on an upper edge portion and a lower edge portion in the vicinity of plural openings to be formed.

[0144] The lever member 60' is swingably disposed to be movable forward to and backward from the second product storage passage 13b in a state in which the lever member penetrates a lever opening 214' of the right top end of the base 21'. More specifically, a pair of right and left lever locking pieces 215' protruding to the rear side is formed on both edges of the lever opening 214' on the rear

side of the base 21', and the lever member 60' is disposed to be swingable about the axes of shaft portions 61' formed in the lever locking pieces 215' as illustrated in FIGS. 4 and 16. A lever spring 62' is interposed between the lever member 60' and the base 21' so as to be wound on the shaft portion 61', and the lever member 60' is biased by the lever spring 62' and takes a posture in which the tip portion moves forward to the first product storage passage 13a in a normal state.

10 [0145] The wiring cover 80 is disposed to cover the lower ends of the first product discharging device 20a and the second product discharging device 20b. The wiring cover 80 is formed of an elastic resin material such as polypropylene and serves to guide wirings of the units such as the sold-out detection switch 25 and the drive unit 40 which are attached to the first product discharging device 20a.

[0146] The wiring cover 80 receives and locks a lower end 241' of the bearing portion 24' fitted to the second product discharging device 20b as illustrated in FIG. 18, and includes a regulation portion 81 on the front side of the lower end 241' as illustrated in FIG. 19. The regulation portion 81 regulates displacement of the lower end 241' of the bearing portion 24' going into the wiring cover 80 to the front side, that is, displacement in the direction getting close to the first product discharging device 20a.

[0147] The product dispensing system 20 having the above-mentioned configuration operates as follows in the standby state.

[0148] In the drive unit 40 of the first product discharging device 20a, the cam portion 443a and the pressing piece 443b of the output gear 443 are located at

the highest position and the pressing piece 443b presses the contactor 45a of the carrier switch 45. In this case, the carrier switch 45 is in the ON state. In this standby state, the tip portion 461b of the first link lever 461
5 constituting the drive unit 40 is located at a position separated downward from the contact piece 351 of the pedal link 35 and the tip portion 462b of the second link lever 462 is located at a position separated downward from the contact piece 351' of the pedal link 35'.

10 [0149] Accordingly, in the first product discharging device 20a, as illustrated in FIG. 5, the pedal link 35 is disposed on the lower side. When a product is placed on the top surface of the lower pedal 28 due to the products input to the first product storage passage 13a, the lower
15 pedal 28 takes the product-present standby posture and the upper pedal 29 takes the posture in which the upper pedal moves backward from the first product storage passage 13a. In this way, since the lower pedal 28 takes the product-present standby posture, the sold-out detection switch 25
20 (first sold-out detection unit 25a) takes the posture in which the first contactor 251 rises upright and is in the OFF state.

[0150] In the second product discharging device 20b, the pedal link 35' is disposed on the lower side, the lower
25 pedal 28' takes the product-present standby posture, and the upper pedal 29' takes the posture in which the upper pedal moves backward from the second product storage passage 13b. In this way, since the lower pedal 28' takes the product-present standby posture, the sold-out detection
30 switch 25 (second sold-out detection unit 25b) takes the posture in which the second contactor 252 rises upright and is in the OFF state.

[0151] When a command to discharge a product

(hereinafter, also referred to as "first product") stored in the first product storage passage 13a is issued from the control unit, the product dispensing system 20 operates as follows.

5 [0152] When the motor 43 is positively driven, the output gear 443 to which the driving force of the motor 43 is transmitted via the worm gear 441 and the intermediate gear 442 rotates clockwise in a front view.

[0153] When the output gear 443 rotates clockwise in a
10 front view, the pressing piece 443b of the output gear 443 departs from the contactor 45a of the carrier switch 45. Accordingly, the contactor 45a of the carrier switch 45 is released from the pressed state and is switched to the OFF state.

15 [0154] When the cam portion 443a comes in contact with the base end 461a of the first link lever 461 from the upper side with the rotation of the output gear 443, the first link lever 461 rotates counterclockwise in the front view as illustrated in FIGS. 20 and 21. When the first
20 link lever 461 rotates counterclockwise, the tip portion 461b moves upward. When the tip portion 461b moves upward in this way, the tip portion comes in contact with the contact piece 351 of the pedal link 35, the pedal link 35 can move upward by a predetermined distance against the
25 biasing force of the link spring 35a, and the pedal link 35 can be held in the state in which the pedal link moves upward by the predetermined distance while the cam portion 443a comes in sliding contact with the base end 461a.

[0155] In this case, when the first link lever 461 comes
30 in sliding contact with the cam portion 443a, the first link lever is adjusted such that the plane (A) including the portion coming in sliding contact with the cam portion 443a is substantially perpendicular to the plane (B)

including its central axis (the central axis of the first link shaft 42e) and a central axis of the output gear 443.

[0156] With the upward movement of the pedal link 35, the stopper pin 34a moves upward and the pedal stopper pin
5 34b moves upward.

[0157] At this time, since the stopper pin 34a moves upward while coming in contact with the edge wall of the concave portion 292 of the upper pedal 29, the upper pedal 29 moves forward from the initial position against the
10 biasing force of the upper pedal spring. The forward movement of the upper pedal 29 is performed along with the upward movement of the stopper pin 34a. At the time at which the stopper pin 34a reaches a predetermined top end, the stopper pin comes in contact with the stopper contact
15 portion 293 to regulate the backward movement of the upper pedal 29.

[0158] The upper pedal 29 moving forward comes in contact with a second lowest piece of first product (hereinafter, also referred to as a next product) to
20 regulate downward movement of the next product.

[0159] On the other hand, since the weight of the product coming in contact with the lower pedal 28 maintained at the forward-moved position is applied to the rotation stopper 36, the rotation stopper 36 starts its
25 backward movement by releasing the regulation of the backward movement due to the upward movement of the pedal stopper pin 34b.

[0160] When the rotation stopper 36 starts the backward movement in this way, the pedal operating shaft 361 departs
30 from the fitting portion 283a and the lower pedal 28 starts its backward movement against the biasing force of the lower pedal spring 28b with the weight of the product. The pedal operating shaft 361 of the rotation stopper 36

departing from the fitting portion 283a moves to a position at which the first guide portion 283b and the second guide portion 283c intersect each other along the first guide portion 283b.

5 [0161] Thereafter, the lower pedal 28 moves backward with the weight of the lowest product, the downward movement of the lowest product is allowed, and the lowest product is discharged downward (see FIG. 8). The discharged product is guided to the product discharge port
10 3c via the product chute 5 and can be taken out via the product output port 2a.

[0162] When the lowest product passes through the lower pedal 28, the lower pedal 28 moves to the forward-moved position with the elastic biasing force of the lower pedal
15 spring 28b and the rotation stopper 36 also moves to the forward-moved position with the elastic biasing force of the pedal operation spring. When the lower pedal 28 and the rotation stopper 36 move to the forward-moved position, the pedal operating shaft 361 held at the position at which
20 the first guide portion 283b and the second guide portion 283c intersect each other moves to the fitting portion 283a along the second guide portion 283c, and the lower pedal 28 and the rotation stopper 36 are returned to the forward-moved position.

25 [0163] In the meantime, the pedal link 35 moves upward, the stopper pin 34a is located at a predetermined top end, and the pedal stopper pin 34b is located at a predetermined top end.

[0164] Thereafter, when the contact of the cam portion
30 443a with the base end 461a is released with the rotation of the output gear 443, the pedal link 35 is biased to move downward by the link spring 35a.

[0165] With the downward movement of the pedal link 35,

the stopper pin 34a moves downward and the pedal stopper pin 34b moves downward.

[0166] When the pedal stopper pin 34b moves downward, the pedal stopper pin 34b comes in contact with the

5 recessed portion 36b on the rear side of the rotation stopper 36 returned to the forward-moved position.

Accordingly, the movement in the backward moving direction is regulated and the lower pedal 28 is returned to the product-absent standby posture in which the lower pedal

10 moves forward to the first product storage passage 13a by the biasing force of the lower pedal spring 28b.

[0167] On the other hand, the upper pedal 29 is biased by the upper pedal spring and moves backward with the downward movement of the stopper pin 34a. Accordingly, the
15 downward movement of the next product is allowed, then the next product comes in contact with the forward-moved lower pedal 28 to regulate the downward movement thereof, and the lower pedal 28 transitions to the product-present standby posture and is returned to the standby state.

20 [0168] In the drive unit 40, the cam portion 443a comes in contact with the base end 462a of the second link lever 462 with the clockwise rotation of the output gear 443 in a front view. In this case, since the locking portion 462c comes in contact with the right edge portion 472 of the
25 left opening, the rotation of the second link lever 462 about the central axis is regulated. Accordingly, the locking portion 462c is elastically deformed to bring the base end 462a close to the locking portion 462c, thereby not interfering with the movement of the cam portion 443a
30 due to the rotation of the output gear 443.

[0169] Thereafter, when the cam portion 443a is returned to the position of the standby state with the rotation of the output gear 443, the pressing piece 443b presses the

contactor 45a of the carrier switch 45 to switch the carrier switch 45 to the ON state. Immediately after the pressing piece 443b presses the contactor 45a of the carrier switch 45, the cam portion 443a departs from the base end 462a of the second link lever 462 and the second link lever 462 is returned to the original state by the locking portion 462c.

[0170] On the other hand, when a command to discharge a product (hereinafter, also referred to as "second product") stored in the second product storage passage 13b is issued from the control unit, the product dispensing system 20 operates as follows.

[0171] When the motor 43 is reversely driven, the output gear 443 to which the driving force of the motor 43 is transmitted via the worm gear 441 and the intermediate gear 442 rotates counterclockwise in a front view.

[0172] When the output gear 443 rotates counterclockwise in a front view, the pressing piece 443b of the output gear 443 departs from the contactor 45a of the carrier switch 45. Accordingly, the contactor 45a of the carrier switch 45 is released from the pressed state and is switched to the OFF state.

[0173] When the cam portion 443a comes in contact with the base end 462a of the second link lever 462 from the upper side with the rotation of the output gear 443, the second link lever 462 rotates clockwise in the front view. When the second link lever 462 rotates clockwise, the tip portion 462b moves upward. When the tip portion 462b moves upward in this way, the tip portion comes in contact with the contact piece 351' of the pedal link 35', the pedal link 35' can move upward by a predetermined distance against the biasing force of the link spring 35a', and the pedal link 35' can be held in the state in which the pedal

link moves upward by the predetermined distance while the cam portion 443a comes in sliding contact with the base end 462a.

[0174] In this case, when the second link lever 462 comes in sliding contact with the cam portion 443a, not clearly illustrated in the drawing, the second link lever is adjusted such that the plane including the portion coming in sliding contact with the cam portion 443a is substantially perpendicular to the plane including its central axis (the central axis of the second link shaft 42f) and the central axis of the output gear 443.

[0175] With the upward movement of the pedal link 35', the stopper pin moves upward and the pedal stopper pin 34b' also moves upward.

[0176] At this time, since the stopper pin moves upward while coming in contact with the edge wall of the concave portion 292' of the upper pedal 29', the upper pedal 29' moves forward from the initial position against the biasing force of the upper pedal spring. The forward movement of the upper pedal 29' is performed along with the upward movement of the stopper pin. At the time at which the stopper pin reaches a predetermined top end, the stopper pin comes in contact with the stopper contact portion 293' to regulate the backward movement of the upper pedal 29'.

[0177] The upper pedal 29' moving forward comes in contact with a second lowest piece of second product (hereinafter, also referred to as a next product) to regulate downward movement of the next product.

[0178] On the other hand, since the weight of the product coming in contact with the lower pedal 28' maintained at the forward-moved position is applied to the rotation stopper 36', the rotation stopper 36' starts its backward movement by releasing the regulation of the

backward movement due to the upward movement of the pedal stopper pin 34b'.

[0179] When the rotation stopper 36' starts the backward movement in this way, the pedal operating shaft 361'

5 departs from the fitting portion and the lower pedal 28' starts its backward movement against the biasing force of the lower pedal spring 28b' with the weight of the product. The pedal operating shaft 361' of the rotation stopper 36' departing from the fitting portion moves to a position at
10 which the first guide portion and the second guide portion intersect each other along the first guide portion.

[0180] Thereafter, the lower pedal 28' moves backward with the weight of the lowest product, the downward movement of the lowest product is allowed, and the lowest
15 product is discharged downward. The discharged product is guided to the product discharge port 3c via the product chute 5 and can be taken out via the product output port 2a.

[0181] When the lowest product passes through the lower pedal 28', the lower pedal 28' moves to the forward-moved
20 position with the elastic biasing force of the lower pedal spring 28b' and the rotation stopper 36' also moves to the forward-moved position with the elastic biasing force of the pedal operation spring. When the lower pedal 28' and the rotation stopper 36' move to the forward-moved position,
25 the pedal operating shaft 361' held at the position at which the first guide portion and the second guide portion intersect each other moves to the fitting portion along the second guide portion, and the lower pedal 28' and the rotation stopper 36' are returned to the forward-moved
30 position.

[0182] Thereafter, when the contact of the cam portion 443a with the base end 462a is released with the rotation of the output gear 443, the pedal link 35' is biased to

move downward by the link spring 35a'.

[0183] With the downward movement of the pedal link 35', the stopper pin moves downward and the pedal stopper pin 34b' also moves downward.

5 [0184] When the pedal stopper pin 34b' moves downward to a predetermined lower end, the pedal stopper pin 34b' comes in contact with the recessed portion 36b' on the rear side of the rotation stopper 36' returned to the forward-moved position. Accordingly, the movement in the backward moving
10 direction is regulated and the lower pedal 28' is returned to the product-absent standby posture in which the lower pedal moves forward to the second product storage passage 13b by the biasing force of the lower pedal spring 28b'.

[0185] On the other hand, the upper pedal 29' is biased
15 by the upper pedal spring and moves backward with the downward movement of the stopper pin. Accordingly, the downward movement of the next product is allowed, then the next product comes in contact with the forward-moved lower pedal 28' to regulate the downward movement thereof, and
20 the lower pedal 28' transitions to the product-present standby posture and is returned to the standby state.

[0186] In the drive unit 40, the cam portion 443a comes in contact with the base end 461a of the first link lever 461 with the counterclockwise rotation of the output gear
25 443 in a front view. In this case, since the locking portion 461c comes in contact with the left edge portion 471 of the right opening, the rotation of the first link lever 461 about the central axis is regulated. Accordingly, the locking portion 461c is elastically deformed to bring
30 the base end 461a close to the locking portion 461c, thereby not interfering with the movement of the cam portion 443a due to the rotation of the output gear 443.

[0187] Then, when the cam portion 443a is returned to

the position of the standby state with the rotation of the output gear 443, the pressing piece 443b presses the contactor 45a of the carrier switch 45 to switch the carrier switch 45 to the ON state.

5 [0188] For example, when the product in the second product storage passage 13b is sold out, the base end of the lower pedal 28' comes in contact with the contact portion of the second sold-out link 70 and thus the second sold-out link 70 rotates about the first swing support
10 shaft 28a' to cause the second sold-out pressing portion 72 to press the second contactor 252 of the sold-out detection switch 25. Accordingly, in the sold-out detection switch 25, the second contactor 252 is pressed and displaced forward against the biasing force of the spring into the ON
15 state, and outputs the ON signal to the control unit. Accordingly, it is determined that the second product is sold out and thus a sold-out lamp and the like can be lighted.

[0189] The product dispensing system 20 and the product
20 discharging devices 20a and 20b which have been described above exhibit the following operational advantages.

[0190] According to the above-mentioned product dispensing system 20, since the first product discharging device 20a includes the motor 43 serving as a drive source
25 for the first product discharging device 20a and the second product discharging device 20b and the drive unit 40 that alternatively selects the first product discharging device 20a and the second product discharging device 20b in accordance with a discharge command and applies the driving
30 force from the motor 43 to the selected discharging device when the discharge command is issued, it is possible to decrease the number of drive sources in comparison with the number of discharge mechanisms and to decrease the

manufacturing cost. Since the first product discharging device 20a includes the drive unit 40 including the motor 43, it is also possible to use only the first product discharging device 20a. That is, the present invention can
5 be applied to a product storage rack 10 in which an odd number of product storage passages 13 are arranged in the front-rear direction as well as the product storage rack 10 in which an even number of product storage passages 13 are arranged in the front-rear direction. Accordingly, it is
10 possible to achieve a decrease in manufacturing cost and to flexibly work depending on the number of product storage passages 13 adjacent in the front-rear direction.

[0191] According to the product dispensing system 20, the sold-out detection switch 25 is interposed between the
15 first sold-out link 30 and the second sold-out link 70. Accordingly, when the second product discharging device 20b is detached from the first product discharging device 20a, the second sold-out link 70 is not likely to interfere with the second contactor of the sold-out detection switch and
20 it is thus possible to easily detach the second product discharging device 20b.

[0192] According to the product dispensing system 20, the inclined guide surface 73 which is gradually inclined downward as it approaches the first product discharging
25 device 20a is formed at the upper end of the second sold-out link 70. Accordingly, when the second product discharging device 20b is attached to the first product discharging device 20a as illustrated in FIG. 22 and the second contactor 252 of the sold-out detection switch 25
30 comes in contact with the upper end of the second sold-out link 70 as illustrated in FIG. 23, the second contactor 252 can be guided to the front side along the inclined guide surface 73. Accordingly, it is possible to easily attach

the second product discharging device 20b.

[0193] According to the product dispensing system 20, since the first sold-out detection unit 25a and the second sold-out detection unit 25b are unified to constitute the
5 sold-out detection switch 25, the output wirings can be commonized as illustrated in (a) to (c) of FIG. 10.

Accordingly, it is possible to decrease the number of wirings and to reduce unbalance in assembly or the like and it is thus possible to achieve a decrease in manufacturing
10 cost and facilitation in manufacturing work.

[0194] According to the product dispensing system 20, the contact piece 351' of the pedal link 35' constituting the second product discharging device 20b extends forward, extends obliquely upward, that is, extends toward the first
15 product discharging device 20a, and then extends to be gradually inclined so as to be separated from a reference position while approaching the first product discharging device 20a. Accordingly, when the second product discharging device 20b is attached to the first product
20 discharging device 20a as illustrated in FIG. 22 and the second link lever 462 takes a posture in which the second link lever swings upward, the contact piece can come in contact with the second link lever 462 and guide the second link lever downward as illustrated in FIG. 24. As a result,
25 it is possible to easily attach the second product discharging device 20b.

[0195] According to the product dispensing system 20, since the pedal links 35 and 35' are long plate-like members extending in the vertical direction and the top
30 portions thereof are bent forward and then extend upward, curved portions are formed in the middle way thereof. Accordingly, even when a strong impact acts on the lower pedals 28 and 28' or the like due to contact of a product,

the curved portions can be bent to exhibit a damper effect, thereby preventing the impact from acting on the drive unit 40 or the like.

[0196] According to the product dispensing system 20,
5 since the regulation portion 81 of the wiring cover 80 regulates displacement of the lower end 241' of the bearing portion 24' going into the wiring cover 80 in the direction of approaching the first product discharging device 20a, the following operational advantages can be obtained. That
10 is, the second product discharging device 20b does not include the sold-out detection switch 25 and the drive unit 40 unlike the first product discharging device 20a, and thus is less in weight than the first product discharging device 20a. Accordingly, the second product discharging
15 device 20b can more easily move upward and downward relative to the first product discharging device 20a at the time of discharging a product. As a result, when the lower end 241' of the bearing portion 24' is displaced in the direction separated away from the base 21', the second
20 product discharging device 20b may depart from the first product discharging device 20a. However, since the regulation portion 81 regulates the displacement of the lower end 241' in the direction of approaching the first product discharging device 20a, it is possible to prevent
25 the second product discharging device 20b from departing from the first product discharging device 20a at the time of discharging a product.

[0197] According to the product dispensing system 20, since the motor 43 as a drive source is a DC motor, the
30 motor is not easily affected by a local voltage or a frequency fluctuation and can be disposed at various locations.

[0198] According to the product dispensing system 20,

since the first product discharging device 20a is provided with the sold-out detection switch 25 (the first sold-out detection unit 25a and the second sold-out detection unit 25b), it may be possible to use only the first product
5 discharging device 20a. Accordingly, it is possible to flexibly work depending on the number of product storage passages 13 adjacent in the front-rear direction. In addition, since electrical components are disposed in only the first product discharging device 20a, harnesses can be
10 integrated in the first product discharging device 20a.

[0199] In the first product discharging device 20a, the first sold-out detection unit 25a switches its state to detect presence or absence of the first product in the first product storage passage 13a when the lower pedal 28
15 transitions to the product-absent standby posture and the product-present standby posture, and the second sold-out detection unit 25b switches its state to detect presence or absence of the second product in the second product storage passage 13b when the lower pedal 28' transitions to the
20 product-absent standby posture and the product-present standby posture. Accordingly, it is possible to satisfactorily recognize that no product is present in the product storage passages 13 and to match the number of sales opportunities of product with the number of products
25 in the product storage passages 13. Therefore, according to the first product discharging device 20a, it is possible to increase the number of product sales opportunities.

[0200] When products are placed on the lower pedals 28 and 28', contents of a product flow out due to damage of a
30 product pack or the like, and the weight of the product decreases, the lower pedal 28 or 28' transitions to the product-absent standby posture. Accordingly, since there is no possibility that a product not having a body as

product will be sold, it is possible to prevent sale troubles.

[0201] According to the first product discharging device 20a and the second product discharging device 20b, the tip portions of the lever members 60 and 60' disposed in the bases 21 and 21' such that the tip portions move forward to and backward from the product storage passages 13 in the areas above the upper pedals 29 and 29' are biased by the lever spring 62 to move forward to the product storage passages 13 in the normal state, and move backward from the product storage passages 13 against the biasing force of the lever spring 62 when the tip portions come in contact with a product passing through the product storage passages. Accordingly, it is possible to stabilize the posture of a product passing through the product storage passages 13.

[0202] According to the first product discharging device 20a and the second product discharging device 20b, since the protrusions 213 protruding to the product storage passages 13 are formed in the vicinity of the openings formed in the areas above the upper pedals 29 and 29', it is possible to prevent a product passing through the product storage passage 13 from coming in contact with the edges of the openings and thus to prevent damage of the product.

[0203] In the first product discharging device 20a and the second product discharging device 20b, since the rotation stoppers 36 and 36' include the blindfold portions 36c and 36c' covering the sides of the pedal stopper pins 34b and 34b' opposite to the product storage passages 13, a blindfold plate as in the related art is not necessary and it is possible to retain the antitheft capability while decreasing the number of components. As a result, according to the first product discharging device 20a and

the second product discharging device 20b, it is possible to achieve a decrease in manufacturing cost and to improve the antitheft capability.

[0204] While the exemplary embodiment of the present invention has been described above, the present invention is not limited to the exemplary embodiment and can be modified in various forms.

[0205] In the above-mentioned embodiment, the first product discharging device 20a corresponds to the first product storage passage 13a and the second product discharging device 20b corresponds to the second product storage passage 13b, but the present invention is not limited to this configuration. One product discharging device may correspond to the other product storage passage and the other product discharging device may correspond to one product storage passage.

Reference Signs List

[0206] 1 MAIN CABINET
 4 PRODUCT STORAGE
 10 PRODUCT STORAGE RACK
 13 PRODUCT STORAGE PASSAGE
 20 PRODUCT DISPENSING SYSTEM
 20a FIRST PRODUCT DISCHARGING DEVICE
 20b SECOND PRODUCT DISCHARGING DEVICE
 25 SOLD-OUT DETECTION SWITCH
 251 FIRST CONTACTOR
 252 SECOND CONTACTOR
 28 LOWER PEDAL
 29 UPPER PEDAL
 30 FIRST SOLD-OUT LINK
 35 PEDAL LINK
 36c BLINDFOLD PORTION
 40 DRIVE UNIT

	50	COVER FLAPPER
	60	LEVER MEMBER
	70	SECOND SOLD-OUT LINK
	73	INCLINED GUIDE SURFACE
5	80	WIRING COVER

CLAIMS

1. A product discharging device comprising:

a lower pedal swingably disposed to move forward to
and backward from a product storage passage storing input
5 products in a vertical direction;

an upper pedal swingably disposed to move forward to
and backward from the product storage passage in an area
above the lower pedal;

a pedal stopper pin coupled to a pedal link linking
10 the lower pedal and the upper pedal, the pedal stopper
being is movable with movement of the pedal link in the
vertical direction;

a rotation stopper of which a tip linked to the lower
pedal and swingably disposed to move forward to and
15 backward from the product storage passage along with the
lower pedal; and

a drive unit configured to move the pedal link
downward into transition from an activated state to the
standby state and to move the pedal link upward to
20 transition from the standby state to the activated state,

wherein when the pedal link moves downward,

the upper pedal moves backward from the product
storage passage, and

the lower pedal moves forward to the product
25 storage passage and is held at the product storage passage
to regulate downward movement of the product by regulating
backward movement of the rotation stopper due to the pedal
stopper pin,

when the pedal link moves upward,

30 the upper pedal moves forward to the product
storage passage to come in contact with a second lowest
product, and

the lower pedal moves backward from the product

storage passage to discharge a lowest product downward by releasing the regulation of the backward movement of the rotation stopper due to the pedal stopper pin,

the rotation stopper includes a blindfold portion that
5 covers the pedal stopper pin opposite to the product storage passage, and

the blindfold portion is a panel portion fixed to the rotation stopper and structured to move toward the pedal stopper pin when the pedal link is moved downward, and to
10 move away from the pedal stopper pin when the pedal link is moved upward.

2. The product discharging device according to claim 1, wherein a protrusion protruding to the product storage passage is formed in the vicinity of an opening formed in
15 an area above the upper pedal.

3. The product discharging device according to claim 1 or 2, wherein in the standby state, the lower pedal has a first standby posture to regulate downward movement of the
20 lowest product when the lowest product is placed on a top surface thereof and a second standby posture in which a tip portion of the lower pedal is located higher than in the first standby posture when no product is placed on the top surface, and

the product discharging device further comprises a
25 sold-out detection switch that is switched to an ON state or an OFF state when the lower pedal takes the first standby posture and is switched to the OFF state or the ON state when the lower pedal takes the second standby posture
30 so as to detect presence or absence of a product of the product storage passage.

4. The product discharging device according to claim 2,

wherein in the standby state, the lower pedal has a first
standby posture to regulate downward movement of the lowest
product when the lowest product is placed on a top surface
thereof and a second standby phase in which a tip portion
5 of the lower pedal is located higher than in the first
standby posture when no product is placed on the top surface,
and

the product discharging device further comprises a
sold-out detection switch that is switched to an ON state
10 or an OFF state when the lower pedal takes the first
standby posture and is switched to the OFF state or the ON
state when the lower pedal takes the second standby posture
so as to detect presence or absence of a product of the
product storage passage.

15