

TITLE OF THE INVENTION
COMMUNICATION APPARATUS, METHOD OF CONTROLLING THE SAME,
AND STORAGE MEDIUM

5 BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to a communication apparatus, a method of controlling the same, and a storage medium.

10 Description of the Related Art

[0002] A printer having a wireless LAN (Local Area Network) access point function of an IEEE 802.11 standard is known (for example, Japanese Patent Laid-Open No. 2006-123239). When using such a printer, it is possible to use the printing function by directly connecting to the access point that the printer is equipped with from a terminal such as a personal computer, a smart phone, or a tablet. In addition, as wireless LAN encryption method standards, WPA (Wi-Fi Protected Access), WPA2 (WPA (Wi-Fi Protected Access 2)), and the like are known. When connecting to a wireless LAN access point in which these encryption functions are enabled, a passphrase as is known by WPA-PSK (Wi-Fi Protected Access Pre-Shared Key), WPA2-PSK (Wi-Fi Protected Access 2 Pre-Shared Key), or the like is necessary. In addition, a terminal that uses an access point having a function in which it stores in

advance the passphrase and an SSID (Service Set Identifier) for when connecting to the access point, and automatically connects when it discovers an access point that it succeeded in connecting to in the past is
5 commonly known.

[0003] However, although a printer equipped with the above-described access point can be used in a home or in an office in which there is a small number of users, who are employees or the like, there are problems such
10 as the following in the case of use in a large scale office in which there are many users. For example, if the SSID and passphrase of an access point that a printer has are fixed, when a terminal that has connected to the access point discovers the access
15 point, the terminal automatically connects to the access point regardless of the intention of the user of the terminal. Typically, a number of terminals that can simultaneously connect to an access point that a printer has is small. For this reason, when there are
20 many terminals that automatically connect in an office, there is a possibility that an access point is instantly connected to from a plurality of terminals when it activates, and a maximum number of connections that can simultaneously connect to the access point is
25 reached. In such a case, the terminals that connect to the access point first monopolize the access point, and a terminal of another user who wants to use the printer

becomes unable to connect to the access point. To avoid such a problem, frequently changing the SSID or passphrase of the access point that the printer is equipped with can be considered. However, with such a configuration, there is a problem in that a user who uses the printer must change the settings of the user's terminal each time the SSID and the passphrase of the access point are changed, and effort for the user increases.

10

SUMMARY OF THE INVENTION

[0004] An aspect of the present invention is to eliminate the above-mentioned problems with conventional technology.

15 **[0005]** A feature of the present invention is to provide a technique by which a communication apparatus obtains an SSID corresponding to a user, and then the communication apparatus uses the SSID to operate in a direct wireless communication mode.

20 **[0006]** The present invention in its first aspect provides a communication apparatus comprising: a wireless communication unit equipped with a direct wireless communications function configured to execute wireless communication between an external apparatus and the communication apparatus; a specifying unit
25 configured to specify a user of the communication apparatus; and a generation unit configured to generate

an SSID, to use in the direct wireless communications function, by using at least user information of the user specified by the specifying unit.

[0007] The present invention in its second aspect
5 provides a communication apparatus comprising: a wireless communication unit equipped with a direct wireless communications function configured to execute wireless communication between an external apparatus and the communication apparatus; a storage unit
10 configured to store an SSID, used by the direct wireless communications function, in correspondence with user information of a user; a specifying unit configured to specify a user of the communication apparatus; and a selection unit configured to select,
15 from a plurality of SSIDs stored in the storage unit, an SSID that corresponds to user information of the user specified by the specifying unit, wherein the wireless communication unit uses the SSID selected by the selection unit to execute the direct wireless
20 communications function.

[0008] The present invention in its third aspect provides a method of controlling a communication apparatus equipped with a direct wireless communications function that executes wireless
25 communication with an external apparatus, the method comprising: specifying a user of the communication apparatus; and generating an SSID, to use in the direct

wireless communications function, by using at least user information of the specified user.

[0009] The present invention in its fourth aspect provides a method of controlling a communication
5 apparatus equipped with a direct wireless communications function that executes wireless communication with an external apparatus, and a storage unit that stores an SSID, to be used in the direct wireless communications function, in correspondence
10 with user information of a user, the method comprising: specifying a user of the communication apparatus; and selecting, from a plurality of SSIDs stored in the storage unit, an SSID that corresponds to user information of the specified user, wherein the
15 communication apparatus uses the selected SSID to execute the direct wireless communications function.

[0010] Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached
20 drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The accompanying drawings, which are incorporated in and constitute a part of the
25 specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

[0012] FIG. 1 depicts a schematic view illustrating a configuration of a printing system according to a first embodiment of the present invention.

[0013] FIG. 2 is a block diagram for explaining a hardware configuration of a mobile terminal and an MFP according to the first embodiment.

[0014] FIG. 3A is a block diagram for describing a software configuration of the MFP according to the first embodiment and a data region in which software is managed.

[0015] FIG. 3B is a block diagram for describing a software configuration of a mobile terminal according to the first embodiment and a data region in which software is managed.

[0016] FIG. 4 depicts a view illustrating an example of screen transitions and user interfaces displayed on a console unit of the MFP according to the first embodiment.

[0017] FIG. 5 depicts a view illustrating an example of user interfaces displayed on an operation unit of the mobile terminal according to the first embodiment.

[0018] FIG. 6 is a flowchart for describing processing for activation of an access point by the MFP according to the first embodiment.

[0019] FIG. 7 depicts a view for explaining an algorithm by which an SSID and a passphrase are generated by the MFP according to the first embodiment

from information of a user who has logged-in.

[0020] FIG. 8 is a block diagram for describing a software configuration of the MFP according to a second embodiment and a data region in which software is
5 managed.

[0021] FIG. 9 depicts a view illustrating an example of user interfaces provided by a mobile connection corresponding to editing or deleting an SSID, in the second embodiment.

10 **[0022]** FIG. 10 is a flowchart for describing processing for activation of an access point by the MFP according to a second embodiment.

DESCRIPTION OF THE EMBODIMENTS

15 **[0023]** Embodiments of the present invention will be described hereinafter in detail, with reference to the accompanying drawings. It is to be understood that the following embodiments are not intended to limit the claims of the present invention, and that not all of
20 the combinations of the aspects that are described according to the following embodiments are necessarily required with respect to the means to solve the problems according to the present invention.

[0024] [First Embodiment]

25 FIG. 1 depicts a schematic view illustrating a configuration of a printing system according to a first embodiment of the present invention. In an environment

in the first embodiment, a plurality of multi-function peripherals (MFP: Multi-Function Peripheral) and a plurality of mobile terminals are present. For example, an office environment in which each user has one mobile terminal and normally walks around holding the mobile terminal is envisioned. A plurality of MFPs are installed in accordance with the office environment. Here, explanation is given of a multi-function peripheral (MFP) as an example of one aspect of a communication apparatus and a printing apparatus of the present invention.

[0025] An MFP 100 and a mobile terminal 101 in FIG. 1 are representative examples of the plural MFPs and mobile terminals. The MFP 100 is equipped with a wireless LAN access point function, and can connect to and perform direct communication with the mobile terminal 101, which is connected to the access point.

[0026] FIG. 2 is a block diagram for explaining hardware configurations of the MFP 100 and the mobile terminal 101 according to the first embodiment.

[0027] Firstly, explanation is given of a hardware configuration of the MFP 100.

[0028] A CPU 201 controls operation of the MFP 100 on the whole. The CPU 201 performs various control, such as reading control or transmission control, by reading a control program that is stored in a ROM 202 or an HDD (hard disk drive) 204, deploying it into a

RAM 203, and then executing the deployed program. The RAM 203 is a volatile memory that the CPU 201 uses, for example as a work area for executing various programs. The HDD 204 stores image data, various programs, or the like. A console unit 205 is equipped with a hard key, a display unit that has a function of a touch panel that is operable by a user's finger, or the like. A printer 206 prints an image on a print paper (a sheet) based on image data transferred via an internal bus. A scanner 207 generates image data by reading an image of an original. An IC card reader 208 reads an IC card that is used in authentication of a user. A wired LAN interface 209 is an NIC (Network Interface Card) for connecting to a wired LAN. A wireless LAN interface 210 is an access point for connecting to the MFP 100 from a terminal corresponding to a wireless LAN. These are mutually connected via an internal bus.

[0029] Next, explanation is given of a hardware configuration of the mobile terminal 101.

[0030] A CPU 211 controls operation of the mobile terminal 101 on the whole. A RAM 212 is a volatile memory that the CPU 211 uses, for example as a work area for executing various programs. A flash memory 213 is a non-volatile memory that stores various programs or data. A wireless LAN interface 214 is an interface for communicating by a wireless LAN, and can perform a wireless communication by connecting to a

wireless LAN access point. In the first embodiment,
the wireless LAN interface 214 is used to mutually
communicate with the MFP 100 after connecting to the
wireless LAN interface 210 that the MFP 100 is provided
5 with. An operation unit 215 is a display that operates
as a touch panel that is operable by a user's finger.
A speaker 216 converts an electrical signal into a
sound. A microphone 217 detects a sound and converts
it into an electrical signal. A camera unit 218
10 captures a still image or a moving image, and converts
it into electronic data.

[0031] Next, referring to FIG. 3, explanation is
given of a software configuration of the mobile
terminal 101 and the MFP 100 according to the first
15 embodiment.

[0032] FIG. 3A is a block diagram for explaining a
software configuration of the MFP 100 according to the
first embodiment and a data region in which software is
managed. Note, a function of software illustrated in
20 FIG. 3A is realized by the CPU 201 executing a program
deployed into the RAM 203.

[0033] FIG. 4 depicts a view illustrating an example
of screen transitions and user interfaces displayed on
the console unit 205 of the MFP 100 according to the
25 first embodiment. Below, explanation is given with
reference to FIG. 3A and FIG. 4.

[0034] A platform 301 is a platform that provides a

basic function of software that controls the MFP 100.

The platform 301 can be configured in a form that includes, for example, a device driver group, an OSGi framework, a JAVA (registered trademark) virtual

5 machine, and operating system such as Linux or the like.

The OSGi framework is a Java-based service platform defined by the OSGi Alliance (a standardization body).

The platform 301 is equipped with a device driver group for controlling various hardware, and provides APIs

10 (Application Programming Interface) for using the hardware to applications that operate on the platform.

The platform 301 is equipped with a wireless LAN control module 302.

[0035] The wireless LAN control module 302 is

15 equipped with a software access point mode in which the wireless LAN interface 210 is activated as a wireless LAN access point. It is also provided with a DHCP

(Dynamic Host Configuration Protocol) function that allocates an IP address to a mobile terminal when the

20 mobile terminal connects to the access point which is activated in the software access point mode. In

addition, the wireless LAN control module 302 provides an application with an API that performs software access point mode activation/stopping control, and

25 read/writes a passphrase or SSID (identification information) for the access point. Although it is not shown graphically, a printer module that controls the

printer 206, and a scanner module that controls the scanner 207 are also present in the platform 301. In addition, the platform 301 provides an application with an API for reading/writing data of an MFP setting
5 database 310 or the like.

[0036] Additionally, the above software access point mode is an example of a direct wireless communication mode in which the MFP 100 can operate and in which direct wireless communication with an external
10 apparatus (for example, the mobile terminal 101) is executed without going through an access point. The direct wireless communication mode is not limited to the software access point mode, and may be of another wireless communication method, such as Wi-Fi Direct.
15 When the MFP 100 operates in the direct wireless communication mode, the MFP 100 behaves as an access point.

[0037] A copy 303, a scan 304, a print 305, and a mobile connection306 are examples of applications that
20 operate on the platform 301. These applications display a user interface for providing functions of each kind of application on the console unit 205. For example, the copy 303 provides a function that controls the scanner 207 and the printer 206 via the platform
25 301 to execute a copy. The scan 304 provides a function that operates the scanner 207, and transmits obtained electronic data externally or stores it to the

HDD 204. The print 305 provides a function that displays a print history or an execution status of a print job received from the external unit.

[0038] The mobile connection 306 provides a user interface (connecting mobile device screen 403 of FIG. 4) for using the wireless LAN interface 210 in the access point mode. A user can activate a wireless LAN access point in an ad hoc manner by pressing an activate access point button 413 of the connecting mobile device screen 403. At this point, an SSID and a passphrase of a usable access point are displayed on an area 415 of the connecting mobile device screen 403. For example, a user of the mobile terminal 101 can use the MFP 100 from the mobile terminal by using the SSID and passphrase of the access point that are displayed in the area 415 to wirelessly connect the mobile terminal 101 to the wireless LAN interface 210 which is operating in access point mode. If usage of the wireless LAN has ended, a user presses a stop access point button 414 to stop the wireless LAN access point. Thereby the wireless connection with the mobile terminal 101 can be terminated.

[0039] MFP settings 307 provides an MFP settings screen 404 (FIG. 4) for an administrator of the MFP 100 to perform setting of the MFP 100. A menu 308 is a module that displays a menu screen 402 (FIG. 4) for selecting a previously explained application from the

console unit 205. For example, the menu screen 402 is equipped with an MFP settings button 411 and the like for displaying a screen for setting the MFP 100 and buttons 407-410 that display functions that various applications provide. A login service 309 is provided with a login function and an account management function for a user that uses the MFP 100. The MFP setting database 310 is a database that comprehensively manages settings of the MFP 100 and an application.

10 **[0040]** It is possible to perform the following settings via the setting screen 404 for the MFP 100 according to the first embodiment. A value set in the setting screen 404 of the MFP 100 is stored in the MFP setting database 310.

15 - ON/OFF of the login function (reference numeral 416 of the MFP settings screen 404 of FIG. 4)

If the login function is set to OFF, the menu screen 402 is displayed without a user performing a login operation, and it is possible to use a function selected in the menu screen.

20 **[0041]** If the login function is set to ON, the login service 309 displays a login screen 401 (FIG. 4) on the console unit 205. Thus, after performing a login operation via the login screen 401, a user can use the menu screen 402 and a function selected from the menu screen 402.

- Setting a default SSID and passphrase of an

access point (reference numeral 417 of the MFP settings screen 404 of FIG. 4)

A fixed SSID and passphrase are set for the MFP 100.

- 5 - Usage setting of a one-time SSID (reference numeral 418 of the MFP settings screen 404 of FIG. 4)

When this setting is ON, a function that activates the access point with a different SSID each time is activated.

- 10 - Usage setting of an SSID for each individual person (reference numeral 419 of the MFP settings screen 404 of FIG. 4)

When this setting is ON, a function that, in cooperation with the login function, activates the
15 access point with a different SSID for each user is activated.

[0042] The login service 309 is provided with a login function and a user account management function explained below.

- 20 **[0043]** The user account management function provides a user interface to perform registration and management of a user account to a user, and user information registered via this user interface is stored in a user database 312 and managed. Here the user information
25 that is managed includes a user name, a password, an IC card number, a role, and the like as illustrated in the list of user information of Table 1, for example.

[TABLE 1]

User name	Password	IC card number	Role
Administrator	password0	01a1b2c3d4e5f6g0	Administrator
Guest			Guest
Alice	password1	01a1b2c3d4e5f6g1	Administrator
Bob	password2	01a1b2c3d4e5f6g2	General user
Carol	password3	01a1b2c3d4e5f6g3	General user
Dave	password4	01a1b2c3d4e5f6g4	General user

[0044] The login function provides a login/logout function to a user who uses the console unit 205. Configuration is taken so that the login screen 401 is displayed on the console unit 205, and a user who has not logged-in cannot use the console unit 205. Note that configuration is taken at this point so that a number of users who can simultaneously login to the console unit 205 is set to "1", and that a plurality of users cannot simultaneously login to the console unit 205. If a user has succeeded in logging in, the display of the console unit 205 is caused to transition from the login screen 401 to the menu screen 402, and a state in which the user can use the MFP 100 is entered. Note that, multiple login schemes exist as schemes for performing this login. For example, a login scheme such as below is provided.

- Keyboard log in

A software keyboard is displayed on the login

screen 401 of the console unit 205, and when a press of a login button 405 is detected, an input user name (account) and password are obtained to perform user authentication to perform login processing.

5 - IC card log in

 Login processing is performed by obtaining an IC card number from an IC card that was held up to the IC card reader 208, and identifying a user.

[0045] Ordinarily a login service authenticates a
10 user by verifying whether a user name and password, or an IC card number, which are obtained by the keyboard login or the IC card login, match something that is registered in the user database 312. In addition, the login service may collaborate with a server for user
15 authentication that is connected by a wired LAN. In such a case, the login service performs user authentication by verifying whether the obtained user name and password, or IC card number match something that is registered in the server. Using an LDAP
20 (Lightweight Directory Access Protocol) server, Windows (trademark) Active Directory (trademark), an independent server, or the like can be considered for a server for user authentication.

[0046] In addition, the login service in the first
25 embodiment is equipped with a guest login function. The guest login function, for example, displays a guest login button 406 on the login screen 401. When a press

of the guest login button 406 is detected, a state in which a user can use the MFP 100 is entered, without performing authentication of the user. Note that configuration may be taken to have a portion of the functions of the MFP 100 become unusable when a guest has logged in. For example, the MFP settings button 411 is disabled so that a guest cannot perform a setting modification of the MFP 100. In addition, configuration may be taken to disable, for example, the print button 409 or the copy button 407 when letting a guest use print paper is not desired.

[0047] When a user logs in, the login service 309 generates an object that records information of the logged-in user, and stores it in the RAM 203. An object that records information of the logged-in user is referred to as a login context 311 below. An example of information recorded in the login context 311 is illustrated in Table 2 below.

[TABLE 2]

Item	Value
User name	Alice
Domain name	localhost
Role	General user

[0048] A region to record a domain name is provided in the login context 311, and configuration is taken such that it is possible to distinguish, as separate

accounts, a user account registered in the user database 312, and a user account managed by the server for user authentication. For example, if a user (Alice) who is registered in the user database 312 logs in, a character string "localhost" is recorded in the region that records the domain name. Alternatively, if logging in with a user account managed by the server for user authentication, the domain name or the server name is recorded as a character string in the region that records the domain name. An example of information recorded in the login context 311 when logging in with a user account that is managed by a server is illustrated in Table 3 below. Table 3, for example indicates a case in which a user (Alice) who is registered in the user database 312 has logged-in with a user account that is managed by a server, and a domain name (DomainA) is recorded in the region that records the domain name.

[TABLE 3]

Item	Value
User name	Alice
Domain name	DomainA
Role	General user

[0049] In addition, Table 4 illustrates an example of information recorded in the login context 311 at a time of a guest login.

[0050] Here the user name is set to "Alice", the domain name is set to "localhost", and the role is set to "guest".

[TABLE 4]

Item	Value
User name	Alice
Domain name	localhost
Role	guest

5 **[0051]** When a press of a logout button 412 of a screen displayed on the console unit 205 illustrated in FIG. 4 is detected, the information recorded in the login context 311 is deleted, and display of the login screen 401 is returned to again.

10 **[0052]** FIG. 3B is a block diagram for describing a software configuration of the mobile terminal 101 according to the first embodiment and a data region in which software is managed. FIG. 5 depicts a view illustrating an example of user interfaces displayed on
15 the operation unit 215 of the mobile terminal 101 according to the first embodiment. Below, explanation is given with reference to FIG. 3B and FIG. 5. Note, a function of software illustrated in FIG. 3B is realized by the CPU 211 executing a program deployed into the
20 RAM 212.

[0053] Wireless LAN information 315 indicates a data region of data that software records in the flash

memory 213 and manages. A platform 313 can be configured by a platform of Google Inc.'s Android (trademark) or Apple Inc.'s iOS (trademark), for example. The platform 313 is equipped with a device
5 driver group for controlling various hardware, and provides APIs for using the various hardware to applications that operate on the platform 313. The platform 313 is equipped with a wireless LAN control module 314. The wireless LAN control module 314 is
10 software that controls the wireless LAN interface 214. A wireless LAN setting screen 501 of FIG. 5 illustrates an example of a wireless LAN setting screen that the platform 313 displays on the operation unit 215. For example, it displays, in a list 502, wireless LAN
15 access point SSIDs that the wireless LAN control module 314 has found by searching. A user selects any access point from the list 502, inputs a passphrase of the access point in an area 503, and then presses a connection button 504. In this way, when a connection
20 succeeds, the platform 313 records the SSID and the passphrase in the wireless LAN information 315. When the wireless LAN function of the mobile terminal 101 is enabled and it is not connected to a wireless LAN, the platform 313 automatically searches for a wireless LAN
25 access point to which there was a connection in the past. It is equipped with a function that attempts to connect by an SSID and a passphrase recorded in the

wireless LAN information 315.

[0054] The mobile terminal 101 can install and cause to operate on the platform 313 various applications.

In the first embodiment, an MFP connection application

5 316 is installed in advance. A user interface screen

505 of FIG. 5 illustrates an example of a user

interface screen that the MFP connection application

316 displays on the operation unit 215. For example,

the MFP connection application 316, after connecting to

10 the MFP 100 by a wireless LAN, can use a function of

the printer 206 or the scanner 207 of the MFP 100 via

the wireless LAN. For example, it is possible to

instruct printing to the MFP 100 by a user touching a

print button in the screen 505.

15 **[0055]** FIG. 6 is a flowchart for describing

processing for activation of an access point by the MFP

100 according to the first embodiment. Note that a

program that executes this processing is stored in the

ROM 202 or the HDD 204, and at a time of execution, is

20 deployed to the RAM 203, and executed under the control

of the CPU 201. In addition, the performer of the

software that executes this flowchart is the wireless

LAN control module 302, which is illustrated in the

software configuration of FIG. 3A.

25 **[0056]** In this processing, when a user presses the

activate access point button 413 in the connecting

mobile device screen 403, the mobile connection 306

requests the wireless LAN control module 302 to activate an access point. In this way the processing is started in step S601 by the wireless LAN control module 302 accepting an activation request for the
5 access point. Note that, configuration may be taken such that, when the access point is already activated, the processing is started after stopping the currently activated access point.

[0057] Next, the processing proceeds to step S602
10 and the CPU 201 refers to the MFP setting database 310, and obtains the "SSID usage setting for each individual person" 419, which is set via the setting screen 404 of the MFP. The processing proceeds to step S603, and the CPU 201 determines whether or not the setting 419
15 obtained in step S602 is ON. Here, if the "SSID usage setting for each individual person" is ON, in other words if it is set so as to cooperate with the user login function to activate the access point with a different SSID for each user, the processing proceeds
20 to step S604. In step S604 the CPU 201 refers to the login context 311, and attempts to obtain logged-in user information. The processing proceeds to step S605, and the CPU 201 determines whether or not information of a logged-in user could be obtained. If obtainment
25 of information of a logged-in user other than a guest succeeded, the processing proceeds to step S606, and the CPU 201 generates an exclusive SSID and passphrase

for the obtained user. Note that, to generate an exclusive SSID and passphrase for the logged-in user at this point, configuration may be taken to employ an algorithm such that the same SSID and passphrase are
5 always generated if the obtained user information is the same. A method that always generates the same SSID and passphrase for each individual person from the user information is explained later. The processing proceeds to step S607, and the CPU 201 activates the
10 access point by the generated or obtained SSID and passphrase. The processing proceeds to step S608, and the CPU 201 terminates the activation processing for the access point.

[0058] Meanwhile, if it is determined that the "SSID
15 usage setting for each individual person" 419 is OFF in step S603, or if the logged-in user information indicates a guest in step S605, or if logged-in user information could not be obtained, the processing proceeds to step S609. In step S609, the CPU 201
20 refers to the MFP setting database 310, and obtains the "one-time SSID usage setting" 418. Next the processing proceeds to step S610, and the CPU 201 determines whether or not the obtained setting 418 is ON. Here, if the CPU 201 determines that the "one-time SSID usage
25 setting" 418 is ON, in other words that it is a setting for activating an access point with a different SSID each time, the processing proceeds to step S611. In

step S611 the CPU 201 uses a random number generator to generate, each time, a random SSID and passphrase as a one-time SSID and passphrase. Then the processing proceeds to step S612, and the CPU 201 activates the
5 access point with the generated one-time SSID and passphrase. Then, the processing proceeds to step S608, and the activation processing for the access point is terminated.

[0059] If in step S610 the CPU 201 determines that
10 the "one-time SSID usage setting" 418 is OFF, the processing proceeds to step S613, and the CPU 201 refers to the MFP setting database 310, and obtains a default SSID and passphrase. Next, the processing proceeds to step S614, and the CPU 201 activates the
15 access point by the default SSID and passphrase. Then, the processing proceeds to step S608, and the activation processing for the access point is terminated. Note that the SSID and passphrase of the activated access point may be displayed on the
20 connecting mobile device screen 403 of FIG. 4.

[0060] However, control is performed so as to not display the SSID and passphrase for a user on the connecting mobile device screen 403, even if an access point is activated, if a guest or another person has
25 logged-in, or if the login function is changed to OFF so that they cannot be viewed by another person.

[0061] Note that, in the above-described flowchart,

configuration may be taken to proceed to step S609 if the logged-in user information obtained in step S604 indicates a guest. However, when treating a guest account the same as a normal account, configuration may
5 be taken such that the processing proceeds to step S606, and an exclusive SSID and passphrase for a guest are generated or obtained.

[0062] In addition, if a login function setting 416 of the MFP 100 is OFF, because obtaining logged-in user
10 information is determined to have failed in step S605, even if the SSID usage setting for each individual person 419 is ON, SSID for each individual person will not be used.

[0063] FIG. 7 depicts a view for explaining an
15 algorithm by which the same SSID and passphrase are generated when information of a logged-in user is the same as information of a user who was logged-in previously in the MFP 100 according to the first embodiment. Note that the following explanation is
20 only an example, and an approach to generation is not limited to this.

[0064] If a user name and a domain name are used for an SSID for example, it is possible to generate an SSID that is easy to understand for a user. For example,
25 reference number 701 illustrates an example of generating an SSID as one character string by adding a fixed connection symbol (-) to a user name and a domain

name, and adding suffix letters (-AP).

[0065] When desiring to have the user-exclusive passphrase, or both of the SSID and the passphrase, be something confidential so that guessing by another
5 person is not possible, a method such as the following may be considered. For example, as illustrated by reference numeral 702 or reference numeral 703 of FIG. 7, a character string that includes a user name and a domain name is set as a message 710 and a value unique
10 to the MFP is set as a key 711, and an HMAC (Hash-based Message Authentication Code) algorithm known by RFC 2104 is used to calculate MAC (Message Authentication Codes) values 712 and 713. Next, these MAC values are converted to character strings, and used as the SSID
15 and the passphrase. In the example of reference numeral 702, a case in which an HMAC is used to generate only a passphrase 716 is illustrated. Also, in the example of reference numeral 703, an example of case in which an HMAC is used to generate both an SSID
20 714 and a passphrase 715 is illustrated. In the example of reference numeral 703, a long string 717 is generated, a front part of the string is set as the SSID 714, and a rear part of the string is set as the passphrase 715.

[0066] In addition, configuration may be taken such that, if there are a plurality of the MFPs according to the first embodiment in the same office, key

information used for HMAC is shared by the plurality of MFPs, and if the user information is the same, the same SSID and passphrase are generated. Thus, when the same SSID and passphrase can be used in a plurality of MFPs,
5 it is possible to reduce a burden of a user in registering, in the mobile terminal 101, SSIDs and passphrases that are different for each MFP. In addition, if a user cannot simultaneously use a plurality of MFPs, no problem occurs because there is
10 no case of access points having the same SSID and passphrase simultaneously activating in the plurality of MFPs.

[0067] By the first embodiment, as explained above, in a case where a user logs in to an MFP and activates
15 an access point, it is possible to activate the access point by an SSID and passphrase that are exclusive to the logged-in user. At this point, because the SSID and passphrase that are exclusive to the user do not change when the access point activates or stops, it is
20 always possible to use the same SSID and passphrase if the user is the same. Thereby, because registration of an SSID and a passphrase to the mobile terminal need only be performed once, it is possible to reduce effort for a user.

25 **[0068]** In addition, by configuring so that the SSID and passphrase that are exclusive to the user are not known by another person, a user who logs in to an MFP

and activates an access point will not have the access point used by another person. With this, a user can temporarily monopolize an access point that the MFP has activated.

5 **[0069]** Furthermore, by using this function together with a function that automatically connects to an access point to which the mobile terminal connected in the past, it is possible to achieve a further effect. In other words, upon a user of a mobile terminal first
10 registering and storing in the mobile terminal an SSID and passphrase exclusive to the user, the user can connect the mobile terminal and an MFP by just logging in to the MFP and activating the access point from the next time on.

15 **[0070]** In addition, even if the login function of the MFP is ON, there are cases in which a guest uses the MFP without performing user authentication. For this reason, configuration is taken to provide a temporary SSID and passphrase when a guest uses the
20 access point of the MFP. Thus, even for a guest it is possible to monopolize an access point that an MFP has temporarily activated, without the access point being used by another person.

[0071] In addition, there are users who feel that
25 setting the login function of an MFP to be always ON is cumbersome. For this reason, configuration is taken so that, when the login function is OFF, it is possible to

use the access point of the MFP with a default SSID or a temporary SSID.

[0072] In addition, there are cases in which, when a number of terminals that actually use the access point of the MFP is less than the maximum number of terminals that can simultaneously connect, SSID for each individual person is not used, and the access point of the MFP may always be activated by a default SSID and passphrase. For this reason, configuration is taken such that it is possible to set the usage setting of SSIDs for each individual person to OFF.

[0073] [Second Embodiment]

Next, a second embodiment of the present invention is explained. The second embodiment is explained with a configuration that records, and manages, an SSID for each individual person in the HDD 204 of the MFP 100. Note that, because the hardware configuration, printing system's configuration, and the like of the mobile terminal 101 and the MFP 100 according to the second embodiment are the same as those of the previously described first embodiment, explanation thereof is omitted.

[0074] FIG. 8 is a block diagram for describing a software configuration of the MFP 100 according to according to the second embodiment and a data region in which software is managed. Also, portions in common with FIG. 3A of the previously described first

embodiment are indicated by the same reference numerals, and explanation thereof is omitted.

[0075] Here, the platform 301 records and manages SSIDs for each individual person in an SSID management table 801 of the HDD 204. For example the SSID management table 801, as illustrated in Table 5 below, stores an SSID and passphrase in association with information that specifies a user uniquely (user name and domain name).

10 **[TABLE 5]**

User name	Domain name	SSID	Passphrase
Alice	localhost	Alice-AP	XHIQo1IyS144q2D18Cz8xQ
Bob	localhost	Bob-Ap	FPkxZggmzC/+00LoTUVSSg
Carol	localhost	Carol-AP	Astpr0h/Y3X0Iu0ixRQriw
Dave	localhost	Dave-AP	EtCQweUnrw55NNI/P+wXvA

[0076] FIG. 9 depicts a view illustrating an example of user interfaces provided by the mobile connection 306 that correspond to editing or deleting an SSID, in the second embodiment. Note that, in FIG. 9, a portion in common with FIG. 4 has the same reference numeral added.

[0077] The mobile connection 306 refers to the login context 311 to specify a logged-in user, and furthermore obtains, from the SSID management table 801, an SSID and passphrase associated with the logged-in

user, and displays them on the area 415.

[0078] In FIG. 9, the connecting mobile device screen 403 displays the access point information on the area 415, similarly to the previously explained FIG. 4.

5 If there is no information of an SSID and passphrase associated with the logged-in user in the SSID management table 801, the area 415 is displayed as blank. Upon detection of a press of an edit button 901 of the connecting mobile device screen 403, the mobile
10 connection 306 displays an editing screen 903 for editing the SSID and passphrase displayed in the area 415. A user can register a new SSID and passphrase by inputting the new SSID and passphrase in an area 904 of the editing screen 903 and then pressing an update
15 button 905. At this point, the mobile connection 306 obtains the SSID and passphrase that have been newly input in the area 904, and registers them in or updates the SSID management table 801. In this way, it is possible to generate a new SSID by concatenating a
20 predetermined character string to user identification information.

[0079] In addition, the connecting mobile device screen 403 is provided with a delete button 902. Upon detecting a press of the delete button 902 for the
25 connecting mobile device screen 403, the mobile connection 306 deletes, from the SSID management table 801, information of the SSID and passphrase that are

associated with the logged-in user.

[0080] FIG. 10 is a flowchart for describing processing for activation of an access point by the MFP 100 according to the second embodiment. Note that a program that executes this processing is stored in the ROM 202 or the HDD 204, and at a time of execution, is deployed to the RAM 203, and executed under the control of the CPU 201. In addition, the performer of the software that executes this flowchart is the wireless LAN control module 302, which is illustrated in the software configuration of FIG. 8. Also, in FIG. 10, portions in common with the flowchart of FIG. 6 in accordance with the previously described first embodiment are illustrated by the same reference numerals.

[0081] In step S605, the CPU 201 determines whether or not it was possible to obtain information of a logged-in user from the login context 311. Upon determining that it is possible to obtain information of the logged-in user, the processing proceeds to step S1001, the CPU 201 refers to the SSID management table 801, and attempts to obtain an SSID and passphrase associated with the information of the logged-in user. The processing proceeds to step S1002, and the CPU 201 determines whether or not it succeeded in obtaining the SSID and the passphrase. Upon determined that obtainment failed here, the processing proceeds to step

S1003, and as explained with reference to FIG. 7, the CPU 201 uses the information of the logged-in user to newly generate an SSID and passphrase. These are stored in the SSID management table 801 in association
5 with information of the logged-in user, and the processing proceeds to step S1004. In step S1004, the CPU 201 uses the SSID and passphrase generated in step S1003 to activate the access point to complete the access point activation processing.

10 **[0082]** Meanwhile, if in step S1002 the CPU 201 succeeded in obtaining the SSID and the passphrase, the processing proceeds to step S1004. In step S1004, the CPU 201 uses the SSID and passphrase obtained from the SSID management table 801 to activate the access point
15 to complete the access point activation processing.

[0083] According to the second embodiment, as explained above, if an SSID and passphrase are not stored in the SSID management table 801, an SSID and passphrase are newly generated, stored in the SSID
20 management table 801, and that are used to activate the access point. However, if there are an SSID and passphrase that are already stored, they are used to activate the access point. Thereby, it is possible to reduce a burden on a CPU in accordance with generation
25 of the SSID and passphrase.

[0084] In addition, by allowing a user to edit their own SSID and passphrase, the user can freely set a

desired SSID and passphrase, and MFP convenience increases. In addition, even if an SSID and passphrases for each individual person are leaked to another person, because a user can change or delete the
5 SSID and passphrase at any timing, it is possible to maintain security of the MFP.

[0085]Other Embodiments

Embodiments of the present invention can also be realized by a computer of a system or apparatus that
10 reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a 'non-transitory computer-readable storage medium') to perform the functions of one or more of the above-
15 described embodiments and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiments, and by a method performed by the computer of the system or apparatus by,
20 for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiments and/or controlling the one or more circuits to perform the functions of one or more
25 of the above-described embodiments. The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and

may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for
5 example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD),
10 digital versatile disc (DVD), or Blu-ray Disc (BD)[™]), a flash memory device, a memory card, and the like.

[0086] While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited
15 to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

WHAT IS CLAIMED IS:

1. A communication apparatus comprising:
 - a wireless communication unit equipped with a
 - 5 direct wireless communications function configured to execute wireless communication between an external apparatus and the communication apparatus;
 - a specifying unit configured to specify a user of the communication apparatus; and
 - 10 a generation unit configured to generate an SSID, to use in the direct wireless communications function, by using at least user information of the user specified by the specifying unit.
- 15 2. The communication apparatus according to claim 1, wherein the specifying unit specifies a user who is logged into the communication apparatus by user authentication processing as the user of the communication apparatus.
- 20 3. The communication apparatus according to claim 1 or 2, wherein if a setting that indicates use of a user-exclusive SSID is set in the communication apparatus, the wireless communication unit uses the
- 25 SSID generated by the generation unit to execute the direct wireless communications function.

4. The communication apparatus according to claim 3,
wherein if a setting that indicates use of a user-
exclusive SSID is not set in the communication
apparatus, the wireless communication unit uses a
5 randomly generated SSID to execute the direct wireless
communications function.

5. The communication apparatus according to claim 3,
wherein if a setting that indicates use of a user-
10 exclusive SSID is not set in the communication
apparatus, the wireless communication unit uses a
default SSID set in the communication apparatus in
advance to execute the direct wireless communications
function.

15

6. The communication apparatus according to claim 3,
wherein if a setting that indicates use of a user-
exclusive SSID is not set in the communication
apparatus, the wireless communication unit uses one of
20 a randomly generated SSID and a default SSID set in the
communication apparatus in advance to execute the
direct wireless communications function.

7. The communication apparatus according to any one
25 of claims 1 to 6, wherein the generation unit generates
the SSID to use in the direct wireless communications
function by concatenating a predetermined character

string to the user information.

8. The communication apparatus according to any one of claims 1 to 7, wherein the communication apparatus
5 is a printing apparatus that can execute printing.

9. A communication apparatus comprising:

a wireless communication unit equipped with a direct wireless communications function configured to
10 execute wireless communication between an external apparatus and the communication apparatus;

a storage unit configured to store an SSID, used by the direct wireless communications function, in correspondence with user information of a user;

15 a specifying unit configured to specify a user of the communication apparatus; and

a selection unit configured to select, from a plurality of SSIDs stored in the storage unit, an SSID that corresponds to user information of the user
20 specified by the specifying unit,

wherein the wireless communication unit uses the SSID selected by the selection unit to execute the direct wireless communications function.

25 10. The communication apparatus according to claim 9, wherein the specifying unit specifies a user who is logged into the communication apparatus by user

authentication processing as the user of the communication apparatus.

11. The communication apparatus according to claim 9
5 or 10, further comprising:

a determination unit configured to determine, when the communication apparatus receives from a user an instruction for executing the direct wireless communications function, whether or not the SSID that
10 corresponds to the user information of the user specified by the specifying unit is stored in the storage unit; and

a creation unit configured to create, when it is determined by the determination unit that the SSID that
15 corresponds to the user information of the user specified by the specifying unit is not stored in the storage unit, an SSID to be used in the direct wireless communications function,

wherein the storage unit stores the SSID created
20 by the creation unit in correspondence with the user information of the user specified by the specifying unit.

12. The communication apparatus according to claim 11,
25 wherein the creation unit creates the SSID to use in the direct wireless communications function by concatenating a predetermined character string to the

user information.

13. The communication apparatus according to any one of claims 9 to 12, wherein if a setting that indicates
5 use of a user-exclusive SSID is set in the communication apparatus, the wireless communication unit uses the SSID selected by the selection unit to execute the direct wireless communications function.

10 14. The communication apparatus according to claim 13, wherein if a setting that indicates use of a user-exclusive SSID is not set in the communication apparatus, the wireless communication unit uses a randomly generated SSID to execute the direct wireless
15 communications function.

15. The communication apparatus according to claim 13, wherein if a setting that indicates use of a user-exclusive SSID is not set in the communication
20 apparatus, the wireless communication unit uses a default SSID set in the communication apparatus in advance to execute the direct wireless communications function.

25 16. The communication apparatus according to claim 13, wherein if a setting that indicates use of a user-exclusive SSID is not set in the communication

apparatus, the wireless communication unit uses one of a randomly generated SSID and a default SSID set in the communication apparatus in advance to execute the direct wireless communications function.

5

17. The communication apparatus according to any one of claims 9 to 16, wherein the communication apparatus is a printing apparatus that can execute printing.

10 18. A method of controlling a communication apparatus equipped with a direct wireless communications function that executes wireless communication with an external apparatus, the method comprising:

specifying a user of the communication apparatus;

15 and

generating an SSID, to use in the direct wireless communications function, by using at least user information of the specified user.

20 19. A method of controlling a communication apparatus equipped with a direct wireless communications function that executes wireless communication with an external apparatus, and a storage unit that stores an SSID, to be used in the direct wireless communications function,
25 in correspondence with user information of a user, the method comprising:

specifying a user of the communication apparatus;

and

selecting, from a plurality of SSIDs stored in the storage unit, an SSID that corresponds to user information of the specified user,

5 wherein the communication apparatus uses the selected SSID to execute the direct wireless communications function.

20. A computer-readable storage medium storing a
10 program for causing a processor to execute a method according to claim 18 or 19.