

Service Transmission Method, Base Station, and Terminal

Technical Field

The present invention relates to the technical field of communications, in particular to a
5 method for transmitting a service, a base station and a terminal.

Background

In a Long Term Evolution (LTE) system, a terminal receives a downlink signal on a whole
system bandwidth. The downlink signal includes a Physical Downlink Control Channel (PDCCH)
10 and a downlink common reference signal, such as a Cell-specific Reference Signal (CRS), and a
Channel State Information Reference Signal (CSI-RS). The system bandwidths supported by the
LTE system include 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz and 20MHz. Among the system
bandwidths, system bandwidths of 20MHz and 10MHz are typical and widely used. For the
downlink channel, the system bandwidths of 20MHz and 10MHz correspond to 100 Physical
15 Resource Blocks (PRBs) and 50 PRBs respectively.

In the existing LTE system, the terminal always performs blind detection of PDCCH on the
whole downlink system bandwidth, which leads to a high power consumption of the terminal.
Especially in a system of 5-Generation (5G) mobile communication technology and a system of
future mobile communication technology with a large bandwidth, a bandwidth of a carrier may
20 be very wide, for example up to 200MHz. If the terminal still receives PDCCH on the whole
bandwidth as that in the LTE system, i.e. a system of 4-generation (4G) mobile communication
technology, then the power consumption of the terminal will be very high. For a terminal
supporting Machine Type Machine (MTC), downlink signals can be demodulated on the system
bandwidth of 1.4MHz, that is, 6 PRBs. For such type of the terminal, the power consumption of
25 the terminal can be saved due to the reduction of the downlink bandwidth. However, since such
type of the terminal can only work on a narrower bandwidth, such as 6 PRBs, functions of the
terminal will be greatly restricted. Data scheduled on the system bandwidth cannot be received
under the narrower bandwidth. Some pre-scheduled services, such as a high definition voice

(VoLTE) service, are transmitted on the system bandwidth in a way of Semi-Persistent Scheduling (SPS). For such pre-scheduled service, a base station indicates the terminal of current scheduling information through a PDCCH in an initial scheduling. When the terminal identifies it as the Semi-Persistent Scheduling, the current scheduling information is saved, and the service data are sent or received on same time-frequency resource locations at every fixed period. If the terminal receives a signal on the narrower bandwidth, there is a great restriction on the system performance, and the transmission of the pre-scheduled service may not be accomplished.

Summary

Embodiments of the invention provide a method for transmitting a service method, a base station and a terminal, which can enable the terminal to flexibly switch between a narrow bandwidth and a system bandwidth, obtain a balance between power consumption of the terminal and a system performance, and successfully complete transmission of a pre-scheduled service.

A first aspect of an embodiment of the present invention provides a method for transmitting a service. The method includes: a base station sends a switch message of a narrow bandwidth receiving mode to a terminal, indicating the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and the base station schedules the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, the method further includes: sending downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth; wherein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control-channel element aggregation level corresponding to the terminal.

In a possible implementation, before the base station sends the switch message of the narrow bandwidth receiving mode to the terminal, indicating the terminal to switch to the designated narrow bandwidth to receive the information, the method further includes: the base station sends information relevant to the pre-scheduled service to the terminal, wherein the information

relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

In a possible implementation, scheduling, by the base station, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted, includes: the base station configures information of time interval during which the terminal is in the narrow bandwidth receiving mode, and information of a time-period during which the terminal receives the pre-scheduled service, and sends the information of the time-period during which the terminal is in the narrow bandwidth receiving mode and the information of the time-period during which the terminal receives the pre-scheduled service to the terminal; the base station schedules the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, scheduling, by the base station, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted, includes: configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service.

In a possible implementation, scheduling, by the base station, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted, includes: the base station sends a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal

to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; sends second time information of when the terminal returns to the narrow bandwidth receiving mode in the downlink control information, or transmits a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; schedules the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

In a possible implementation, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the base station schedules the terminal to switch to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the base station schedules the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the base station schedules the terminal to switch to the bandwidth occupied by the pre-scheduled service on a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicates a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in downlink control information of the physical downlink control channel of the narrow bandwidth.

A second aspect of an embodiment of the present invention provides a method for transmitting a service. The method includes: a terminal receives a switch message of a narrow bandwidth receiving mode sent by a base station, and switches to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; when a pre-scheduled service needs to be transmitted, the terminal switches to the system bandwidth or a bandwidth occupied by the pre-scheduled service to receive the pre-

scheduled service according to scheduling of the base station.

In a possible implementation, the method further includes: the terminal receives downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth; wherein the downlink control information is in a terminal-specific search space
5 corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

In a possible implementation, before the terminal receives the switch message of the narrow bandwidth receiving mode sent by the base station and switches to the designated narrow bandwidth to receive the information, the method further includes: the terminal receives
10 information relevant to the pre-scheduled service sent by the base station, wherein the information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service and information of a resource allocated by the base station for the pre-scheduled service.

In a possible implementation, when the pre-scheduled service needs to be transmitted,
15 switching, by the terminal, to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the scheduling of the base station, includes: the terminal receives information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, sent by the base station; when the pre-scheduled
20 service needs to be transmitted, the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service.

25 In a possible implementation, when the pre-scheduled service needs to be transmitted, switching, by the terminal, to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the scheduling of the base station, includes: the terminal receives a preset period configured by the base station according

to the periodic information of the pre-scheduled service, and the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

In a possible implementation, when the pre-scheduled service needs to be transmitted, switching, by the terminal, to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the scheduling of the base station, includes: the terminal receives a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, , wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; the terminal receives second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information , or detects a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

In a possible implementation, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the terminal switches to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the terminal switches to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the terminal switches to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service, and receives a

modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth.

5 A third aspect of an embodiment of the present invention provides a base station, including a sending unit and a scheduling unit.

The sending unit is used for sending a switch message of a narrow bandwidth receiving mode to a terminal to indicate the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth.

10 The scheduling unit is used for scheduling the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, the sending unit is further used for sending downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth.

15 Herein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

20 In a possible implementation, the sending unit is further used for sending information relevant to the pre-scheduled service to the terminal before sending the switching message for the narrow bandwidth receiving mode to the terminal to indicate the terminal to switch to the designated narrow bandwidth to receive information, the information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, period information of the pre-scheduled service and information of a resource allocated by the base station for the pre-scheduled service.

25 In a possible implementation, the scheduling unit is specifically used for:

configuring information of time interval during which the terminal is in the narrow bandwidth receiving mode and information of time interval during which the terminal receives the pre-scheduled service, and sending the information of the time interval during which the

terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service to the terminal; and scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval
 5 during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, the scheduling unit is specifically used for: configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the
 10 narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service.

In a possible implementation, the scheduling unit is specifically used for: sending a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in
 15 downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; sending second time information of when the terminal returns to the narrow bandwidth receiving mode in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the
 20 narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

25 In a possible implementation, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the scheduling unit is specifically used for scheduling the terminal to switch to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, when the pre-scheduled service needs to be transmitted, the scheduling unit is specifically used for scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service;

- 5 If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the scheduling unit is specifically used for scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicating a modulation and coding scheme of the pre-scheduling service and a time-
10 frequency domain resource occupied by the pre-scheduling service in downlink control information of a physical downlink control channel of the narrow bandwidth.

A fourth aspect of an embodiment of the present invention provides a base station, including a processor, a storage, a transceiver and a bus. Herein the processor, the storage and the transceiver are connected through the bus, the transceiver is used for receiving and transmitting signals to
15 communicate with a terminal, the storage is used for storing a set of program codes, and the processor is used for calling the set of the program codes stored in the storage to perform operations of: sending a switch message of a narrow bandwidth receiving mode to a terminal through the transceiver to indicate the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than the width of a
20 system bandwidth; and scheduling the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, the processor is further used for sending downlink control information for the terminal through the transceiver in a physical downlink control channel on
25 the narrow bandwidth.

Herein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

In a possible implementation, the processor is further used for sending information relevant to the pre-scheduled service to the terminal through the transceiver before sending the switch message of the narrow bandwidth receiving mode to the terminal through the transceiver to indicate the terminal to switch to a designated narrow bandwidth to receive information, wherein
 5 the information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

In a possible implementation, the processor is specifically used for: configuring information of a time interval during which the terminal is in the narrow bandwidth receiving mode and
 10 information of a time interval during which the terminal receives the pre-scheduled service, and sending the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service to the terminal; scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service
 15 according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, the processor is specifically used for: configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow
 20 bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service.

In a possible implementation, the processor is specifically used for: sending a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in
 25 downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; sending second time information of when the terminal returns to the narrow bandwidth receiving mode in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the

narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time
5 information and the trigger signal.

In a possible implementation, the processor is specifically used for: if the bandwidth occupied by the pre-scheduled service is the system bandwidth, scheduling the terminal to switch to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted; if the bandwidth occupied by the pre-scheduled service is part of the
10 system bandwidth, scheduling the terminal switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted; or if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, scheduling the terminal to
15 switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicating a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in downlink control information of a physical downlink control channel of the narrow bandwidth.

A fifth aspect of an embodiment of the present invention provides a terminal, including a
20 receiving unit and a switching unit.

The receiving unit is used for receiving a switch message of a narrow bandwidth receiving mode sent by a base station.

The switching unit is used for switching to a designated narrow bandwidth to receive information according to the switch message, wherein a width of the narrow bandwidth is smaller
25 than a width of a system bandwidth.

The switching unit is further used for switching to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service according to scheduling of the base station when the pre-scheduled service needs to be transmitted.

In a possible implementation, the receiving unit is further used for receiving downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth.

5 Herein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

10 In a possible implementation, the receiving unit is further used for receiving information relevant to the pre-scheduled service sent by the base station before receiving the switching message for the narrow bandwidth receiving mode sent by the base station, the information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, period information of the pre-scheduled service and information of a resource allocated by the base station for the pre-scheduled service.

15 In a possible implementation, the receiving unit is specifically used for: receiving information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, sent by the base station.

20 The switching unit is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

In a possible implementation, the receiving unit is specifically used for: receiving a preset period configured by the base station according to the periodic information of the pre-scheduled service.

25 The switching unit is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

In a possible implementation, the receiving unit is specifically used for: receiving a process

identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal
 5 to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; and receiving second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth.

10 The switching unit is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

15 In a possible implementation, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the switching unit is specifically used for switching to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, when the pre-scheduled service needs to be transmitted, the switching unit is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled
 20 service.

If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the switching unit is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service, and the receiving unit is further used for receiving a modulation and coding
 25 scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth.

A sixth aspect of an embodiment of the present invention provides a terminal, including a

processor, a storage, a transmitter, a receiver and a bus. The processor, the storage, the transmitter and the receiver are connected through the bus. The transmitter is used for transmitting signals, the receiver is used for receiving signals, the transmitter and the receiver are independently configured respectively or integrated, the storage is used for storing a set of program codes, and
 5 the processor is used for calling the set of the program codes stored in the storage to perform operations of: receiving a switch message of a narrow bandwidth receiving mode sent by a base station through the receiver, and switching to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and switching to the system bandwidth or a bandwidth occupied by a pre-scheduled
 10 service to receive the pre-scheduled service according to a scheduling of the base station when the pre-scheduled service needs to be transmitted.

In a possible implementation, the processor is further used for receiving downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth through the receiver.

15 Herein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

In a possible implementation, the processor is further used for receiving information relevant to the pre-scheduled service sent by the base station through the receiver before receiving
 20 the switching message for the narrow bandwidth receiving mode sent by the base station through the receiver, and switching to the designated narrow bandwidth to receive information. Herein, the information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, period information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

25 In a possible implementation, the processor is specifically used for receiving information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service through the receiver, sent by the base station; switching to the system bandwidth or the bandwidth

occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

5 In a possible implementation, the processor is specifically used for: receiving through the receiver a preset period configured by the base station according to the periodic information of the pre-scheduled service, and switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

10 In a possible implementation, the processor is specifically used for: receiving, through the receiver, a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by
15 the pre-scheduled service; receiving, through the receiver, second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and switching to the system bandwidth or the bandwidth
20 occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

 In a possible implementation, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the processor is specifically used for switching to the system bandwidth to
25 receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

 If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, when the pre-scheduled service needs to be transmitted, the processor is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled

service.

If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the processor is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling
5 service, and receiving a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base station through the receiver in downlink control information of a physical downlink control channel of the narrow bandwidth.

A seventh aspect of an embodiment of the present invention provides a computer storage
10 medium including a set of program codes for executing the method according to any of the implementations of the first aspect of the embodiments of the present invention.

An eighth aspect of an embodiment of the present invention provides a computer storage medium including a set of program codes for executing the method according to any of the implementations of the second aspect of the embodiments of the present invention.

15 Implementations of the embodiments of the invention have the following beneficial effects.

The base station indicates the terminal a narrow bandwidth receiving mode to be switched to by sending a switch message, and in the narrow bandwidth receiving mode, the terminal can receive signals on a narrow bandwidth which is smaller than the system bandwidth, so that the terminal does not need to detect a large system bandwidth, and the power consumption of the
20 terminal and the time delay of detection signals can be reduced. Configuration for PDCCH of the narrow bandwidth only contains a UE-specific search space and a fixed control channel element aggregation level, which can reduce the amount of information detected by the terminal, thereby the power consumption of the terminal can be further reduced. When the pre-scheduled service needs to be transmitted, the base station may schedule the terminal to switch to the system
25 bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service, and the terminal does not need to detect the PDCCH on the system bandwidth or the bandwidth occupied by the pre-scheduled service, so that the power consumption of the terminal on the system bandwidth can be effectively controlled, and finally the balance between the power

consumption of the terminal and the system performance is achieved.

Brief Description of Drawings

5 To explain technical solutions of embodiments of the present invention or the existing technology more clearly, drawings referred to in the embodiments will be briefly introduced below. Obviously, the drawings in the following description are only some embodiments of the present invention. For those of ordinary skill in the art, other drawings may be obtained according to those drawings without paying an inventive effort.

10 FIG. 1 is a schematic diagram of architecture of a communication system according to an embodiment of the present invention.

FIG. 2 is a flow chart of a first embodiment of a method for transmitting a service according to the present invention.

FIG. 3 is a flow chart of a second embodiment of a method for transmitting a service according to the present invention.

15 FIG. 4 is a schematic diagram of receiving a pre-scheduled service by using the method for transmitting the service shown in FIG. 3.

FIG. 5 is a flow chart of a third embodiment of a method for transmitting a service according to the present invention.

20 FIG. 6 is a schematic diagram of transmitting a pre-scheduled service on a narrow bandwidth according to an embodiment of the present invention.

FIG. 7 is a flow chart of a fourth embodiment of a method for transmitting a service according to the present invention.

FIG. 8 is a flow chart of a method for transmitting a service according to the present invention.

25 FIG. 9 is a flow chart of a method for transmitting a service according to a sixth embodiment of the present invention.

FIG. 10 is a schematic diagram of composition of a first embodiment of a base station

according to the present invention.

FIG. 11 is a schematic diagram of a second embodiment of composition of a base station according to the present invention.

FIG. 12 is a schematic diagram of a second embodiment of composition of a terminal
5 according to the present invention.

FIG. 13 is a schematic diagram of a second embodiment of composition of a terminal according to the present invention.

Detailed Description

10 The terms "include" and "have" and any variations thereof in the description and the claims and the above drawings of the present invention are intended to cover non-exclusive inclusion. For example, a process, method, system, product, or apparatus that includes a series of steps or units is not limited to the listed acts or units, but optionally further includes acts or units not listed, or optionally further includes other acts or units inherent to the process, method, product, or
15 apparatus.

With continuous increasing of people's communication demands, communication technology is developing rapidly, and can provide users with larger bandwidth, faster uplink and downlink transmission speeds, etc. For example, in a 5G system, a system bandwidth of up to 200MHz may be provided. However, with the expansion of the system bandwidth, if the terminal
20 receives a PDCCH on a relatively large system bandwidth, the power consumption of the terminal is relatively high. If the terminal always works on a relatively narrow bandwidth, the system performance will be affected, which can cause some pre-scheduled services not to be transmitted normally. Therefore, embodiments of the present invention provide a method for transmitting a service, so that the terminal can switch to a narrow bandwidth that is smaller than the system
25 bandwidth to work, thereby saving the power consumption of the terminal, and further can switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted. For convenience of explanation, the embodiments of the present invention are described as a 5G system. Those

skilled in the art should understand that implementations in the embodiments of the present invention may also be applied to existing communication systems and future higher-level communication systems such as a 6G communication system and a 7G communication system. The embodiments of the present invention are limited thereto.

5 The method for transmitting the service and devices according to the embodiments of the present invention will be described in detail below with reference to the accompanying drawings.

Referring to FIG. 1, FIG.1 is a schematic diagram of architecture of a communication system according an embodiment of the present invention. A base station and at least one terminal may be included in the FIG. 1, and the terminal may also be referred to as User Equipment (UE).

10 The base station may be an Evolved Node B (eNB), a Node B (NB), a Base Station Controller (BSC), a Base Transceiver Station (BTS), a home base station (e.g., Home evolved NodeB, or Home Node B, HNB), a BaseBand Unit (BBU), etc. It may also be referred to as a base station transceiver, a wireless base station, a wireless transceiver, a transceiver function, a Base Station Sub system (BSS), or some other suitable terminology. The base station may bear
15 scheduling downlink control information in a PDCCH, and may specifically include transmission format information, resource allocation information, uplink scheduling grant information, power control information, uplink retransmission information, etc. And it may transmit downlink data of the service to the UE, and receive retransmission feedback of the terminal and the like. For the pre-scheduled service, the base station may allocate a time-frequency domain resource for the
20 terminal at initial scheduling, and the terminal may use the time-frequency domain resource in periods. Thus, for the pre-scheduled service, the base station does not need to allocate the resource for the terminal for each time, thereby the overhead of PDCCH is saved, the terminal does not need to detect PDCCH for each time, and the power consumption of the terminal can be reduced.

25 The terminal may include a cellular phone, a smart phone, a Session Initiation Protocol (SIP) phone, a laptop computer, a Personal Digital Assistant (PDA), a satellite radio, a global positioning system, a multimedia device, a video device, a digital audio player (e.g., an MP3 player), a camera, a game console, or any other device with similar functions. The terminal may also be referred, by those skilled in the art, to as a mobile station, a subscriber station, a mobile

unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communication device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handheld device, a user agent, a mobile client, a client, or some other suitable terminology. The terminal may receive control information
5 configured by the base station and a time-frequency domain resource scheduled by the base station to transmit uplink service data and retransmission feedback information. The terminal may further switch between a narrow bandwidth and a system bandwidth according to the scheduling of the base station.

To reduce the power consumption of the terminal, in the embodiments of the present
10 invention, the terminal may be configured to work on the narrow bandwidth that is smaller than the system bandwidth. To ensure normal transmission of the pre-scheduled service, in the embodiments of the present invention the base station may be scheduled to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

15 A method for transmitting a service according to the present invention will be described in detail with reference to FIGs. 2 to 7.

Referring to FIG. 2, FIG. 2 is a flow chart of a first embodiment of a method for transmitting a service according to the present invention. In the embodiment, the service transmission method includes following acts S201-S202.

20 In S201, a base station sends a switch message of a narrow bandwidth receiving mode to a terminal to indicate the terminal to switch to a designated narrow bandwidth to receive information.

A width of the narrow bandwidth is smaller than a width of a system bandwidth. The switch message may include indication of the time when the terminal enters the narrow bandwidth
25 receiving mode and a position of the narrow bandwidth on a frequency band when the terminal enters the narrow bandwidth receiving mode.

Optionally, the time of entering the narrow bandwidth receiving mode may include a starting time of entering the narrow bandwidth receiving mode. After receiving the switch

message, the terminal enters the narrow bandwidth receiving mode at a designated starting time, switches to the system bandwidth until the terminal receives a message of stopping the narrow bandwidth receiving mode sent from the base station. Or the terminal may switch from a current narrow bandwidth to another narrow bandwidth or the system bandwidth when receiving a message of switching to another narrow bandwidth or the system bandwidth sent by the base station.

The time of entering the narrow bandwidth receiving mode may include an ending time of being in the narrow bandwidth receiving mode besides the time of entering the narrow bandwidth receiving mode. The terminal may enter the narrow bandwidth receiving mode at a designated starting time and switch back to the system bandwidth at a designated ending time to receive information.

Optionally, the base station may indicate the terminal to switch to a mode of only receiving narrow bandwidth through a high-layer signaling, such as a Radio Resource Control (RRC) signaling, or a physical-layer signaling, such as DCI. The base station may indicate the terminal a specific time at which the narrow bandwidth receiving mode starts and a specific position of the narrow bandwidth on a frequency band. In such way, the terminal may switch to the designated narrow bandwidth to receive information according to the switch message. In the narrow bandwidth receiving mode, the terminal may retune its radio frequency bandwidth to a width of frequency domain, indicated by the system to the terminal, only on which to the terminal performs reception, that is, the designated narrow bandwidth. For example, if a narrow bandwidth that is indicated by the base station to the terminal is 6 PRBs (taking a subcarrier spacing of 15 KHz as an example, it is 1.4MHz), the terminal will retune its radio frequency unit to the position of the 6 PRBs of the narrow bandwidth on a frequency band, indicated by the system. At this case, the terminal can only receive signals on the 6 PRBs. Due to the reduction of the receiving radio frequency bandwidth, the terminal can obtain effect of saving power. The terminal does not need to detect signals on a wide system bandwidth, but only needs to receive signals and detect signals on a narrow bandwidth that is smaller than the system bandwidth, thereby reducing the workload of the terminal, reducing the power consumption of the terminal, and improving the efficiency of the terminal in receiving signals.

It should be noted that for a terminal supporting machine-to-machine (MTC), downlink signals may be demodulated on a bandwidth of 1.4MHz, that is, 6 PRBs. For such type of the terminal, the power consumption of the terminal can be saved as the downlink bandwidth becomes small. However, since such type of the terminal can only work on the narrow bandwidth, such as 6 PRBs, the functions of the terminal will be greatly restricted. The width of the narrow bandwidth in the embodiment of the present invention is smaller than the width of the system bandwidth, that is, the narrow bandwidth in the embodiment of the present invention refers to a width that is less than the width of the system bandwidth in the frequency domain. The narrow bandwidth is a different concept from the bandwidth of 1.4MHz in the existing 4G system. For example, typical system bandwidths in the existing 4G system are 10MHz and 20MHz. When the system bandwidth is 10MHz, the narrow bandwidth in the embodiment of the present invention may be a bandwidth that is less than 10MHz, such as 2MHz, 5MHz, etc. When the system bandwidth is 20MHz, the narrow bandwidth in the embodiment of the present invention may be a bandwidth that is less than 20MHz, such as 5MHz, 10MHz, 12MHz, etc. When the system bandwidth is 1.4MHz, the narrow bandwidth in the embodiment of the present invention may be a bandwidth that is less than 1.4MHz, such as 0.6MHz. For the 5G system with a large bandwidth, the narrow bandwidth may also be a bandwidth that is less than the system bandwidth in the 5G system.

The power consumption of the terminal is mainly represented in two aspects. In a first aspect, the terminal detects signals on the whole system bandwidth. In a second aspect, the terminal performs PDCCH blind detection, and the PDCCH blind detection includes detection of different control channel element aggregation levels such as 2, 4, 8, and detection of different DCI lengths, and the like. DCI detected by the terminal includes DCI only for a single terminal, which needs to be detected in a UE-specific search space, and DCI for multiple terminals, which needs to be detected in a common search space. Due to the large amount of detected contents, the power consumption of the terminal is relatively high. At this case, the downlink control information for the terminal may be sent in the physical downlink control channel on the narrow bandwidth.

Herein, the downlink control information is in a terminal-specific search space

corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

Under the narrow bandwidth receiving mode, the PDCCH used by the base station to schedule the terminal is on the narrow bandwidth indicated by the base station. To reduce the complexity of the terminal receiving such PDCCH, the PDCCH on the narrow bandwidth may carry DCI for an individual terminal, but does not carry DCI for all terminals on the narrow bandwidth. In other words, the PDCCH on the narrow bandwidth only contains the UE-specific search space, but does not contain the common search space. In addition, for the DCI for an individual terminal, its control channel element aggregation level may be fixed, for example, when the base station configures a narrow bandwidth receiving mode to the terminal, what the control channel element aggregation level of the terminal is may be designated to the terminal.

Since the PDCCH only contains the UE-specific search space and the fixed control channel element aggregation level, the amount of information that the terminal needs to detect when receiving the PDCCH on the narrow bandwidth, can be reduced, thus the power consumption of the terminal can be further reduced.

In S202, the base station schedules the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

Since the information relevant to the pre-scheduled service has been pre-configured to the terminal in the system bandwidth, when the terminal switches from the narrow bandwidth to the system bandwidth or the bandwidth occupied by the pre-scheduled service, the terminal may not need to detect the PDCCH on the system bandwidth or the bandwidth occupied by the pre-scheduled service, so that the power consumption of the terminal in the system bandwidth can also be effectively controlled.

Referring to FIG. 3, FIG. 3 is a flow chart of a second embodiment of a service transmission method according to the present invention. In the embodiment, the method includes following acts S301-S304.

In S301, a base station sends a switch message of a narrow bandwidth receiving mode to a

terminal to indicate a terminal to switch to a designated narrow bandwidth to receive information.

Herein a width of the narrow bandwidth is smaller than a width of a system bandwidth.

In S302, the base station sends information relevant to the pre-scheduled service to the terminal.

5 The information relevant to the pre-scheduled service may include, but is not limited to, process identification information of the pre-scheduled service, periodic information of the pre-scheduled service and information of a resource allocated by the base station for the pre-scheduled service.

10 The process identification information may be used to distinguish different pre-scheduled services, and the base station may pre-configure and send the information relevant to the pre-scheduled service to the terminal before the terminal enters the narrow bandwidth receiving mode. The base station may configure multiple pre-scheduled service processes to the terminal, and the different processes may have corresponding process identifications for distinguishing. Periods of the pre-scheduled services or resources used by the pre-scheduled services corresponding to
15 different processes are usually not exactly the same.

If there is only one pre-scheduled service, the process identification information may not be sent.

20 In S303, the base station configures information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, and sends the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service to the terminal.

25 In S304, the base station schedules the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

The base station may configure the time interval when the terminal is in the narrow

bandwidth receiving mode, the time interval when the terminal may retune to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service. When multiple pre-scheduled services are included, the base station may further configure which pre-scheduled service processes the terminal receives on the system bandwidth.

5 Referring to FIG. 4, FIG. 4 is a schematic diagram of receiving a pre-scheduled service by using the method for transmitting the service shown in FIG. 3. Herein, the base station may pre-configure that the terminal is in the narrow bandwidth receiving mode in a time interval of T1-T2, and receives the pre-scheduled service transmitted by the base station in a time interval of T3-T4, then returns to the narrow bandwidth receiving mode in a time interval of T5-T6. Herein,
10 the time interval of T2-T3 is a time interval reserved for the terminal to retune from the narrow bandwidth to the system bandwidth or the bandwidth occupied by the pre-scheduled service. The time interval of T4-T5 is a time interval reserved for the terminal to retune back to the narrow bandwidth from the system bandwidth or the bandwidth occupied by the pre-scheduled service.

Moreover, the base station may further configure, according to periodic information of the
15 pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service. At this case, in FIG. 4, T1 to T4 is one period, and starting from T5, the terminal repeats operations of T1 to T4.

In the embodiment, by designating a specific time interval of entering the narrow bandwidth
20 receiving mode and a specific time interval of receiving the pre-scheduled service, the base station may transmit the pre-scheduled service on the premise of less configuration times, which is beneficial to reduce the overhead of the base station.

In addition to the above uniformly configuration transmission way, a trigger way may further be used for the transmission of the pre-scheduled service.

25 Referring to FIG. 5, FIG. 5 is a flow chart of a third embodiment of a method for transmitting a service according to the present invention. In this embodiment, acts S501-S502 are the same as acts S301-S302 in FIG. 3 and will not be described repeatedly here. The method further includes the following acts S503-S505.

In S503, the base station sends a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth.

- 5 The downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service.

In S504, the base station sends second time information of when the terminal returns to the narrow bandwidth receiving mode in the downlink control information, or transmits a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset
10 area of a physical downlink control channel of the system bandwidth.

In S505, the base station schedules the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

- 15 When the terminal is in the narrow bandwidth receiving mode, the base station may trigger the terminal to retune to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service through the PDCCH of the narrow bandwidth. The base station may use DCI transmitted on the PDCCH of the narrow bandwidth as a trigger signal. The DCI may indicate one or more process identifications of the pre-scheduled services which
20 are to be received by the terminal, and the time when the terminal retunes to the system bandwidth or the bandwidth occupied by the pre-scheduled service.

To notify the terminal when to return to the narrow band receiving mode from the system bandwidth, the base station may further indicate the time when the terminal returns to the narrow band receiving mode in the DCI. Optionally, the base station may trigger the terminal to return
25 to the narrow band receiving mode through a trigger signal transmitted on a predetermined resource in the system bandwidth. For example, a signal of several bits transmitted in a predetermined time-frequency position, such as one or some certain Resource Element Groups (REGs), of a PDCCH in the system bandwidth, may be used as a trigger signal. It should be noted

that based on consideration of saving power consumption of the terminal, the terminal may not need to detect the PDCCH on the system bandwidth, but only needs to detect the time-frequency position where the trigger signal is located.

In addition to the above-mentioned way in which the DCI is used to trigger the bandwidth
 5 switching, and indicate the time of starting to receive the pre-scheduled service and the time of returning to the narrow bandwidth receiving mode, i.e. DCI is used for triggering, and provides a starting time point and an ending time point for receiving the pre-scheduled service, following triggering way may further be adopted.

DCI triggers the switching and indicates a switch delay switching from the narrow
 10 bandwidth receiving mode to the system bandwidth or the bandwidth occupied by the pre-scheduled service. The starting time point of receiving the pre-scheduled service may be obtained by the trigger signal and the switch delay, and then the DCI indicates the time of returning to the narrow bandwidth receiving mode, thereby the starting time point and the ending time point of receiving the pre-scheduled service are determined.

Optionally, information of the ending time point of receiving the pre-scheduled service in
 15 the above two ways may also be triggered by a trigger signal stored in a predetermined resource, and the predetermined resource may also be several bits in one or some certain REGs of the PDDCH of the system bandwidth. And the trigger signal may be used for triggering the terminal to return to the narrow bandwidth receiving mode immediately, once the trigger signal is detected,
 20 or to return to the narrow bandwidth receiving mode after predetermined time, thereby determining the ending time point of receiving the pre-scheduled service.

In the embodiment, the pre-scheduled service is transmitted through a triggering way, which can improve a flexibility of scheduling of the base station.

It should be noted that in the above embodiments shown in FIGs. 2-5, whether to
 25 specifically schedule to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service may be performed according to the bandwidth occupied by the pre-scheduled service.

Since a frequency-domain resource occupied by the pre-scheduled service may not occupy

the whole system bandwidth, when the terminal retunes to receive the pre-scheduled service, its receiving bandwidth only needs to be capable of receiving the pre-scheduled service configured by the base station, and the terminal may not need to receive downlink data of the whole system bandwidth. Therefore, the terminal may decide the bandwidth of the pre-scheduled service
 5 retuned and received by the terminal according to the bandwidth of the pre-scheduled service configured by the base station, or the base station may configure the bandwidth required by the pre-scheduled service retuned and received by the terminal.

For example, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the base station may schedule the terminal to switch to the system bandwidth to
 10 receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the base station may schedule the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

15 If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the base station may schedule the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicates a modulation and coding scheme of the pre-scheduling service and a time-frequency domain
 20 resource occupied by the pre-scheduling service in downlink control information of a physical downlink control channel of the narrow bandwidth. The situation may also be considered that the base station schedules and transmits the pre-scheduled service on the narrow bandwidth.

Referring to FIG. 6, FIG. 6 is a schematic diagram of transmitting a pre-scheduled service on a narrow bandwidth according to an embodiment of the present invention.

25 Herein, the terminal is in a narrow bandwidth receiving mode within T1-T2 and may adhere to the PDCCH of the narrow bandwidth, and the base station may schedule the terminal to receive the pre-scheduled service on the narrow bandwidth through the PDCCH of the narrow bandwidth. As shown in FIG. 6, the pre-scheduled service on the narrow bandwidth is received within T3-

T4, and T2-T3 is a time interval required for switching from the narrow bandwidth receiving mode to the transmission of the pre-scheduled service.

Since the frequency domain resource used by the pre-scheduled service is within the narrow bandwidth in this case, the terminal receives the pre-scheduled service within a narrow bandwidth without retuning to other frequency bands. For such type of the pre-scheduled service, the base station may directly schedule the pre-scheduled service on the narrow bandwidth through the PDCCH of the narrow bandwidth. Referring to FIG. 3, FIG. 3 is a schematic diagram of scheduling the pre-scheduled service on the narrow bandwidth. When the base station directly schedules the pre-scheduled service on the narrow bandwidth through the PDCCH of the narrow bandwidth, the base station needs to indicate a Modulation and Coding Scheme (MCS) of the pre-scheduled service, a time-frequency resource occupied by the pre-scheduled service in the DCI transmitted on the PDCCH of the narrow bandwidth. Since the bandwidth is relatively narrow, the overhead of the control information is also relatively small. It should be pointed out that when the terminal receives the pre-scheduled service on the narrow bandwidth, the terminal may normally detect the PDCCH of the narrow bandwidth. That is different from the case in which the terminal receives the pre-scheduled service on the system bandwidth. When the terminal receives the pre-scheduled service on the system bandwidth, since the information relevant to the pre-scheduled service has been obtained, the PDCCH of the system bandwidth may not be detected. If the pre-scheduled service is transmitted in periods on the narrow bandwidth, after information relevant to the pre-scheduled service transmitted on the narrow bandwidth is obtained during the first scheduling and detection of the PDCCH of the narrow bandwidth, the PDCCH of the narrow bandwidth may not be detected when subsequent transmissions are performed in periods.

It should be noted that the embodiments of the service transmission method shown in FIGs. 2-6 above may be implemented independently or in combination with each other, and the embodiments of the present invention are not limited thereto. Referring to FIG. 7, FIG. 7 is a flow chart of a fourth embodiment of a method for transmitting a service according to the present invention. In the embodiment, the service transmission method includes following acts S701-S702.

In S701, a terminal receives a switch message of a narrow bandwidth receiving mode sent by a base station, and switches to a designated narrow bandwidth to receive information.

Herein a width of the narrow bandwidth is smaller than a width of a system bandwidth. The switch message includes indication of the time when the terminal enters the narrow bandwidth receiving mode and a position of the narrow bandwidth on a frequency band when the terminal enters the narrow bandwidth receiving mode.

Optionally, the terminal may further receive downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth.

Herein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

In S702, the terminal switches to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service according to scheduling of the base station when the pre-scheduled service needs to be transmitted.

FIG. 7 is for description of the embodiment at the terminal side, and the specific process of the FIG. 7 may refer to the description of the embodiment at the base station side shown in FIG. 2, and is not repeated here.

Referring to FIG. 8, FIG. 8 is a flow chart of a fifth embodiment of a method for transmitting a service according to the present invention. In the embodiment, the service transmission method includes following acts S801-S804.

In S801, a terminal receives a switch message of a narrow bandwidth receiving mode sent by a base station, and switches to a designated narrow bandwidth to receive information.

In S802, the terminal receives information relevant to the pre-scheduled service sent by the base station.

The information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service and information of a resource allocated by the base station for the pre-scheduled service.

In S803, the terminal receives information of a time interval during the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, sent by the base station.

5 In S804, the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

10 Optionally, the terminal may further receive a preset period configured by the base station according to periodic information of the pre-scheduled service, and switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

15 FIG. 8 is for description of the embodiment at the terminal side, and the specific process of the FIG. 8 may refer to the description of the embodiment at the base station side shown in FIG. 3, and is not repeated here.

Referring to FIG. 9, FIG. 9 is a flow chart of a sixth embodiment of a service transmission method according to the present invention. In this embodiment, acts S901-S902 is as same as acts S801-S802 compared to the embodiment shown in FIG. 8, and will not be described repeatedly here. The method for transmitting the service further includes following acts S903-S905.

20 In S903, the terminal receives a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth.

25 The downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service.

In S904, the terminal receives second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detects a trigger signal for triggering the terminal to return to the narrow

bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth.

In S905, the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information
 5 and the second time information, or according to the first time information and the trigger signal.

FIG. 9 is for description of the embodiment at the terminal side, and the specific process may refer to the description of the embodiment at the base station side shown in FIGs. 5-6, and is not repeated here.

Referring to FIG. 10, FIG. 10 is a schematic diagram of a first embodiment of composition
 10 of a base station according to the present invention. In this embodiment, the base station includes a sending unit 100 and a scheduling unit 200.

The sending unit 100 is used for sending a switch message of a narrow bandwidth receiving mode to a terminal to indicate the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system
 15 bandwidth.

The scheduling unit 200 is used for scheduling the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

Optionally, the sending unit 100 is further used for sending downlink control information
 20 for the terminal in a physical downlink control channel on the narrow bandwidth.

The downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

Optionally, the sending unit 100 is further used for sending information relevant to the pre-scheduled service to the terminal before sending the switch message of the narrow bandwidth
 25 receiving mode to the terminal to indicate the terminal to switch to the designated narrow bandwidth to receive information. The information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-

scheduled service.

Optionally, the scheduling unit 200 is specifically used for:

5 configuring information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, and sending the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service to the terminal;

10 scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

15 Optionally, the scheduling unit 200 is specifically used for: configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service.

20 Optionally, the scheduling unit 200 is specifically used for: sending a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth. The downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; sending second time information of when the terminal returns to the narrow bandwidth receiving mode, in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

25

Optionally, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, when the pre-scheduled service needs to be transmitted, the scheduling unit 200 is specifically used for scheduling the terminal to switch to the system bandwidth to receive the pre-scheduled service.

5 If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, when the pre-scheduled service needs to be transmitted, the scheduling unit 200 is specifically used for scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service.

10 If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the scheduling unit 200 is specifically used for scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicating a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in downlink control
15 information of a physical downlink control channel of the narrow bandwidth .

Referring to FIG. 11, FIG. 11 is a scheme diagram of a second embodiment of composition of a base station according to the present invention. In this embodiment, the base station includes a processor 110, a storage120, a transceiver 130 and a bus 140. The processor 110, the storage120 and the transceiver 130 are connected through the bus 140. The transceiver 130 is used for
20 transmitting and receiving signals to communicate with terminals. The storage 120 is used for storing a set of program codes. The processor 110 is used for calling the set of the program codes stored in the storage 120 to perform following operations: sending a switch message of a narrow bandwidth receiving mode to a terminal through the transceiver 130 to indicate the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow
25 bandwidth is smaller than the width of a system bandwidth; and scheduling the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

Optionally, the processor 110 is further used for sending downlink control information for

the terminal through the transceiver 130 in a physical downlink control channel on the narrow bandwidth.

The downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

5 Optionally, the processor 110 is further used for sending information relevant to the pre-scheduled service to the terminal through the transceiver 130 before sending the switch message of the narrow bandwidth receiving mode to the terminal through the transceiver 130 to indicate the terminal to switch to the designated narrow bandwidth to receive the information. The information relevant to the pre-scheduled service includes process identification information of
10 the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

Optionally, the processor 110 is specifically used for:

15 configuring information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, and sending the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service to the terminal;

20 scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

25 Optionally, the processor 110 is specifically used for: configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service.

Optionally, the processor 110 is specifically used for: sending a process identification of the pre-scheduled service and first time information of when the terminal switches to the system

bandwidth or the bandwidth occupied by the pre-scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth. The downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; sending second time information of when the terminal returns to the narrow bandwidth receiving mode in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

Optionally, the processor 110 is specifically used for: if the bandwidth occupied by the pre-scheduled service is the system bandwidth, scheduling the terminal to switch to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted; if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted; or if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicating a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in the downlink control information of a physical downlink control channel of the narrow bandwidth.

Referring to FIG. 12, FIG. 12 is a schematic diagram of a first embodiment of composition of a terminal according to the present invention. In this embodiment, the terminal includes a receiving unit 300 and a switching unit 400.

The receiving unit 300 is used for receiving a switch message of a narrow bandwidth receiving mode sent by a base station.

The switching unit 400 is used for switching to a designated narrow bandwidth to receive information according to the switch message, wherein a width of the narrow bandwidth is smaller than the width of a system bandwidth.

5 The switching unit 400 is further used for switching to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service according to scheduling of the base station when the pre-scheduled service needs to be transmitted.

Optionally, the receiving unit 300 is further used for receiving downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth.

10 The downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

Optionally, the receiving unit 300 is further used for receiving information relevant to the pre-scheduled service sent by the base station before receiving the switch message of the narrow bandwidth receiving mode sent by the base station. The information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic
15 information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

Optionally, the receiving unit 300 is specifically used for: receiving information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, sent by the base
20 station.

The switching unit 400 is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the
25 pre-scheduled service when the pre-scheduled service needs to be transmitted.

Optionally, the receiving unit 300 is specifically used for: receiving a preset period configured by the base station according to the periodic information of the pre-scheduled service.

The switching unit 400 is specifically used for: switching to the system bandwidth or the

bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

Optionally, the receiving unit 300 is specifically used for: receiving a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; and receiving second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth.

The switching unit 400 is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

Optionally, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, when the pre-scheduled service needs to be transmitted, the switching unit 400 is specifically used for switching to the system bandwidth to receive the pre-scheduled service.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, when the pre-scheduled service needs to be transmitted, the switching unit 400 is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service.

If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the switching unit 400 is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service, and the receiving unit 300 is further used for receiving a modulation and coding method of the pre-scheduling service and time-frequency domain resources occupied by

the pre-scheduling service sent by the base station in the downlink control information of a physical downlink control channel of the narrow bandwidth.

Referring to FIG. 13, FIG. 13 is a schematic diagram of a second embodiment of composition of a terminal according to the present invention. In this embodiment, the terminal
 5 includes a processor 210, a storage 220, a transmitter 230, a receiver 240 and a bus 250. The processor 210, the storage 220, the transmitter 230 and the receiver 240 are connected through the bus 250. The transmitter 230 is used for transmitting signals, the receiver 240 is used for receiving signals, and the transmitter 230 and the receiver 240 are independently configured respectively or integrated. The storage 220 is used for storing a set of program codes. The
 10 processor 210 is used for calling the set of the program codes stored in the storage 220 to perform the following operations: receiving a switch message of a narrow bandwidth receiving mode sent by a base station through the receiver 240, and switching to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than the width of a system bandwidth; and switching to the system bandwidth or a bandwidth occupied by a pre-
 15 scheduled service to receive the pre-scheduled service according to a scheduling of the base station when the pre-scheduled service needs to be transmitted.

Optionally, the processor 210 is further used for receiving downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth through the receiver 240.

20 The downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

Optionally, the processor 210 is further used for receiving information relevant to the pre-scheduled service sent by the base station through the receiver 240 before receiving the switch message of the narrow bandwidth receiving mode sent by the base station through the receiver
 25 240 and switching to the designated narrow bandwidth to receive information. The information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

Optionally, the processor 210 is specifically used for receiving information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service through the receiver 240, sent by the base station; and switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

Optionally, the processor 210 is specifically used for: receiving a preset period configured by the base station through the receiver 240 according to the periodic information of the pre-scheduled service, and switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

Optionally, the processor 210 is specifically used for: receiving, through the receiver 240, a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; receiving, through the receiver 240, second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

Optionally, if the bandwidth occupied by the pre-scheduled service is the system bandwidth, when the pre-scheduled service needs to be transmitted, the processor 210 is specifically used for switching to the system bandwidth to receive the pre-scheduled service.

If the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, when the pre-scheduled service needs to be transmitted, the processor 210 is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service.

5 If the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the processor 210 is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service, and receiving a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base
10 station through the receiver 240 in the downlink control information of a physical downlink control channel of the narrow bandwidth .

The base station described in the embodiment may be used for implementing some or all of the processes in the method embodiments described in connection with FIGs. 2-6 of the present invention, and performing some or all of the functions in the device embodiments described in
15 connection with FIG. 10 of the present invention. The terminal described in the embodiment may be used for implementing some or all of the processes in the method embodiments described in connection with FIGs. 7-9 of the present invention, and performing some or all of the functions in the device embodiments described in connection with FIG. 12 of the present invention. Those will not be repeated here.

20 In one or more examples, the described functions may be implemented through hardware, software, firmware, or any combination thereof. If implemented through software, the functions may be stored in a computer-readable medium or transmitted via the computer readable medium as one or more instructions or codes, and the functions may be executed by a hardware-based processing unit. The computer-readable medium may include a computer-readable storage
25 medium (which corresponds to a tangible medium such as a data storage medium) or a communication medium including, for example, any medium that facilitates transfer of a computer program from one place to another place according to a communication protocol. In such way, the computer-readable medium may generally correspond to (1) a non-transitory tangible computer-readable storage medium, or (2) a communication medium such as a signal or

a carrier wave. The data storage medium may be any available medium accessible by one or more computers or one or more processors to retrieve instructions, codes, and/or data structures for implementing the techniques described in the present invention. The computer program product may include a computer-readable medium.

5 By an example which is not used for limitation, some computer readable storage media may include a RAM, a ROM, an EEPROM, a CD-ROM or any other optical disk memory or magnetic disk memory, or any other magnetic storage device or flash memory, or any other medium that may be used to store desired program codes in the form of instructions or data structures and may be accessed by the computer. Moreover, any connection may be appropriately referred to as a
10 computer readable medium. For example, if instructions are sent from a website, a server, or other remote source by using a coaxial cable, an optical cable, a twisted pair, a digital subscriber line (DSL), or wireless technologies (e.g., an infrared ray, radio, and a microwave), then the coaxial cable, the optical cable, the twisted pair, the DSL, or the wireless technologies (e.g., the infrared ray, the radio, and the microwave) are included in the definition of medium. However, it should
15 be understood that the computer readable storage medium and data storage medium do not include a connection, a carrier, a signal, or any other transitory medium, but include a medium related to the non-transitory tangible storage medium. As used herein, the magnetic disk and optical disk include a compact disk (CD), a laser disk, an optical disk, a digital video disk (DVD), a floppy disk, and a blue-ray disk, where the magnetic disk usually copies data magnetically,
20 while the optical disk copies data optically by the laser. Combinations of the above should further be included within the scope of the computer readable medium.

 The indications may be executed by one or more processors such as one or more digital signal processors (DSP), general purpose microprocessors, application specific integrated circuits (ASIC), field programmable logic arrays (FPGA) or other equivalent integrated or discrete logic
25 circuits. Thus, the term "processor" as used herein may refer to any of the foregoing structures or any other structure suitable for implementing the techniques described herein. In addition, in some aspects, the functionality described herein may be provided within dedicated hardware and/or software modules configured for encoding and decoding, or incorporated into a combined codec. Moreover, the techniques may be fully implemented in one or more circuits or logic

elements.

The techniques of the present invention may be widely implemented by a variety of apparatuses or devices including wireless handsets, integrated circuits (IC) or IC sets (e.g., chipsets). Various components, modules or units are described in the present invention to
5 emphasize functional aspects of devices configured to perform the disclosed techniques, but are not necessarily required to be implemented by different hardware units. Specifically, as described above, various units may be combined in codec hardware units, or provided by a collection of interactive and operable hardware units (including one or more processors as described above) in combination with suitable software and/or firmware.

10 It should be understood that the "one embodiment" or "an embodiment" in the specification means that particular features, structures, or characteristics related to the embodiments of the present invention may be included in at least one embodiment of the present invention. Thus, "in one embodiment" or "in an embodiment" in the specification may not definitely refer to the same embodiment. In addition, these specific features, structures, or characteristics may be combined
15 in one or more embodiments in any suitable manner.

It should be understood that, in various embodiments of the present invention, the values of the sequence numbers of the above-described processes do not imply the order of execution, and the order of execution of each process should be determined by its function and inherent logic, without constituting any limitation to the implementation process of the embodiments of the
20 present invention.

In addition, the terms "system" and "network" are often used interchangeably herein. The term "and/or" in this document is merely an association relationship describing associated objects, indicating that there may be three relationships, for example, A and/or B may indicate three situations: A alone, A and B, and B alone. In addition, the symbol "/" in this document generally
25 indicates that objects of the former and the latter connected by "/" has an "or" relationship.

In the embodiments provided in the present application, it should be understood that "B corresponding to A" means that B is associated with A, and B can be determined according to A. However, it should be further understood that determining B according to A does not mean B is

determined according to A only, but B may be determined according to A and/or other information.

Those of ordinary skill in the art will recognize that the exemplary elements and algorithm acts described in connection with the embodiments disclosed herein can be implemented in electronic hardware, or a combination of computer software and electronic hardware. In order to explain interchangeability of software and hardware clearly, the composition of the examples and the acts in the examples are described generally with respect to functions in the above description. Whether these functions are implemented in hardware or software depends on the specific application and design constraints of the technical solution. Skilled in the art may use different methods to realize the described functions for each particular application, but such realization should not be considered to be beyond the scope of the present invention.

Those skilled in the art can clearly understand that for convenience and conciseness of description, the specific working processes of the system, device and unit described above may refer to the corresponding processes in the aforementioned method embodiments and will not be described here.

In several embodiments provided by the present invention, it should be understood that the disclosed systems, devices and methods may be implemented in other ways. For example, the device embodiments described above are only illustrative, for example, the division of the units is only a logical function division, and there may be other division manners in actual implementation, for example, multiple units or components may be combined or integrated into another system, or some features may be ignored or not executed. On the other hand, the mutual coupling or direct coupling or communication connection shown or discussed may be indirect coupling or communication connection through some interface, device or unit, and may be in electrical, mechanical or other forms.

The unit described as a separate unit may or may not be physically separated, and the component shown as a unit may or may not be a physical unit, i.e., it may be located in one place or may be distributed over multiple network units. Some or all of the elements can be selected according to actual needs to achieve the purpose of the embodiments.

In addition, various functional units in various embodiments of the present invention may be integrated in one processing unit, or the various functional units may be physically present separately, or two or more units may be integrated in one unit.

5 What are described above are merely exemplary embodiments of the present invention, but the protection scope of the present invention is not limited thereto. Any person skilled in the art may easily conceive changes or substitutions within the technical scope disclosed by the present invention, which should be included within the protection scope of the present invention. Therefore, the protection scope of the present invention should be determined by the scope of the appended claims.

What is claimed is:

1. A method for transmitting a service, comprising:

sending, by a base station, to a terminal a switch message of a narrow bandwidth receiving mode, indicating the terminal to switch to a designated narrow bandwidth to receive information,
5 wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and

scheduling, by the base station, the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

2. The method of claim 1, wherein the method further comprises:

10 sending downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth, wherein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

3. The method of claim 1, wherein before sending, by the base station, the switch message
15 of the narrow bandwidth receiving mode to the terminal, indicating the terminal to switch to the designated narrow bandwidth to receive information, the method further comprises:

sending to the terminal information relevant to the pre-scheduled service, wherein the information relevant to the pre-scheduled service comprises process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of
20 a resource allocated by the base station for the pre-scheduled service.

4. The method of claim 3, wherein scheduling, by the base station, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted, comprises:

configuring, by the base station, information of a time interval during which the terminal is
25 in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, and sending to the terminal the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the

information of the time interval during which the terminal receives the pre-scheduled service;
and

scheduling, according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

5. The method of claim 3, wherein scheduling, by the base station, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted, comprises:

configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service in preset periods.

6. The method of claim 3, wherein scheduling, by the base station, the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted, comprises:

sending, by the base station, a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service;

sending second time information of when the terminal returns to the narrow bandwidth receiving mode in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and

scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by

the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

7. The method of any one of claims 1-6, wherein:

5 if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the base station schedules the terminal to switch to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

10 if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the base station schedules the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

15 if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the base station schedules the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service, and indicates a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in downlink control information of the physical downlink control channel of the narrow bandwidth.

8. A method for transmitting a service, comprising:

20 receiving, by a terminal, a switch message of a narrow bandwidth receiving mode sent by a base station, and switching to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and

25 switching, by the terminal, to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service according to scheduling of the base station when the pre-scheduled service needs to be transmitted.

9. The method of claim 8, wherein the method further comprises:

receiving downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth,

wherein the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

10. The method of claim 8, wherein before receiving, by the terminal, the switch message
5 of the narrow bandwidth receiving mode sent by the base station, and switching to the designated narrow bandwidth to receive information, the method further comprises:

receiving information relevant to the pre-scheduled service sent by the base station, wherein
the information relevant to the pre-scheduled service comprises process identification
information of the pre-scheduled service, periodic information of the pre-scheduled service and
10 information of a resource allocated by the base station for the pre-scheduled service.

11. The method of claim 10, wherein switching, by the terminal, to the system bandwidth
or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service
according to the scheduling of the base station when the pre-scheduled service needs to be
transmitted, comprises:

15 receiving information of a time interval during which the terminal is in the narrow
bandwidth receiving mode and information of a time interval during which the terminal receives
the pre-scheduled service, sent by the base station; and

switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service
to receive the pre-scheduled service according to the information of the time interval during
20 which the terminal is in the narrow bandwidth receiving mode and the information of the time
interval during which the terminal receives the pre-scheduled service when the pre-scheduled
service needs to be transmitted.

12. The method of claim 10, wherein switching, by the terminal, to the system bandwidth
or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service
25 according to the scheduling of the base station when the pre-scheduled service needs to be
transmitted, comprises:

receiving a preset period configured by the base station according to the periodic
information of the pre-scheduled service, and switching to the system bandwidth or the

bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

13. The method of claim 10, wherein switching, by the terminal, to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the scheduling of the base station when the pre-scheduled service needs to be transmitted, comprises:

receiving a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service;

receiving second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and

switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

14. The method of any one of claims 8 to 13, wherein if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the terminal switches to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the terminal switches to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, when the pre-scheduling service needs to be transmitted, the terminal switches to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service, and receives a

modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth.

15. A base station, comprising:

5 a sending unit, used for sending a switch message of a narrow bandwidth receiving mode to a terminal, indicating the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and

10 a scheduling unit, used for scheduling the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

16. The base station of claim 15, wherein the sending unit is further used for sending downlink control information for the terminal in a physical downlink control channel on the narrow bandwidth;

15 the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

17. The base station of claim 15, wherein the sending unit is further used for sending information relevant to the pre-scheduled service to the terminal before sending the switch message of the narrow bandwidth receiving mode to the terminal and indicating the terminal to
20 switch to the designated narrow bandwidth to receive information, wherein the information relevant to the pre-scheduled service comprises process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

18. The base station of claim 17, wherein the scheduling unit is specifically used for:

25 configuring information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, and sending the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval

during which the terminal receives the pre-scheduled service to the terminal; and

scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

19. The base station of claim 17, wherein the scheduling unit is specifically used for:

configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-scheduled service.

20. The base station of claim 17, wherein the scheduling unit is specifically used for:

sending a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service;

sending second time information of when the terminal returns to the narrow bandwidth receiving mode, in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and

scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

21. The base station of any one of claims 15 to 20, wherein if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the scheduling unit is specifically used for scheduling the terminal to switch to the system bandwidth to receive the pre-scheduled service

when the pre-scheduled service needs to be transmitted;

if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the scheduling unit is specifically used for scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, the scheduling unit is specifically used for scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service when the pre-scheduled service needs to be transmitted,, and indicating a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in downlink control information of the physical downlink control channel of the narrow bandwidth.

22. A base station, comprising:

a processor, a storage, a transceiver and a bus, wherein the processor, the storage and the transceiver are connected through the bus, the transceiver is used for receiving and transmitting signals to communicate with a terminal, the storage is used for storing a set of program codes, and the processor is used for calling the set of the program codes stored in the storage to perform following operations:

sending a switch message of a narrow bandwidth receiving mode to a terminal through the transceiver, indicating the terminal to switch to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and

scheduling the terminal to switch to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted.

23. The base station of claim 22, wherein the processor is further used for sending downlink control information for the terminal through the transceiver in a physical downlink control channel on the narrow bandwidth;

the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

24. The base station of claim 22, wherein the processor is further used for sending information relevant to the pre-scheduled service to the terminal through the transceiver before
 5 sending the switch message of the narrow bandwidth receiving mode to the terminal through the transceiver, indicating the terminal to switch to the designated narrow bandwidth to receive information, wherein the information relevant to the pre-scheduled service comprises process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

10 25. The base station of claim 24, wherein the processor is specifically used for:
 configuring information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, and sending the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval
 15 during which the terminal receives the pre-scheduled service to the terminal; and

scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service
 20 when the pre-scheduled service needs to be transmitted.

26. The base station of claim 24, wherein the processor is specifically used for:
 configuring, according to the periodic information of the pre-scheduled service, the terminal that is in the narrow bandwidth receiving mode to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to a preset period to receive the pre-
 25 scheduled service.

27. The base station of claim 24, wherein the processor is specifically used for:
 sending a process identification of the pre-scheduled service and first time information of when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-

scheduled service, in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service;

5 sending second time information of when the terminal returns to the narrow bandwidth receiving mode, in the downlink control information, or transmitting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and

10 scheduling the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

28. The base station of any one of claims 22-27, wherein the processor is specifically used for:

15 if the bandwidth occupied by the pre-scheduled service is the system bandwidth, scheduling the terminal to switch to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

20 if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, scheduling the terminal to switch to the bandwidth occupied by the pre-scheduled service in a physical downlink control channel of the narrow bandwidth to receive the pre-scheduling service when the pre-scheduling service needs to be transmitted,, and indicating a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service in downlink control information of the physical downlink control channel of the narrow bandwidth.

29. A terminal, comprising:

a receiving unit, used for receiving a switch message of a narrow bandwidth receiving mode

sent by a base station; and

a switching unit, used for switching to a designated narrow bandwidth to receive information according to the switch message, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth;

5 wherein the switching unit is further used for switching to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service according to scheduling of the base station when the pre-scheduled service needs to be transmitted.

30. The terminal of claim 29, wherein the receiving unit is further used for receiving downlink control information for the terminal in a physical downlink control channel on the
10 narrow bandwidth;

the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

31. The terminal of claim 29, wherein the receiving unit is further used for receiving information relevant to the pre-scheduled service sent by the base station before receiving the
15 switch message of the narrow bandwidth receiving mode sent by the base station, wherein the information relevant to the pre-scheduled service comprises process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of a resource allocated by the base station for the pre-scheduled service.

32. The terminal of claim 31, wherein the receiving unit is specifically used for:
20 receiving information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service, sent by the base station;

the switching unit is specifically used for:

switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service
25 to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

33. The terminal of claim 31, wherein the receiving unit is specifically used for: receiving a preset period configured by the base station according to the periodic information of the pre-scheduled service;

the switching unit is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

34. The terminal of claim 31, wherein the receiving unit is specifically used for:

receiving a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service; and

receiving second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth;

the switching unit is specifically used for: switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the first time information and the second time information, or according to the first time information and the trigger signal.

35. The terminal of any one of claims 29-34, wherein if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the switching unit is specifically used for switching to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the switching unit is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be

transmitted;

if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, the switching unit is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service when the pre-scheduled service needs to be transmitted, and the receiving unit is further used for receiving a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth.

36. A terminal, comprising:

a processor, a storage, a transmitter, a receiver and a bus, wherein the processor, the storage, the transmitter and the receiver are connected through the bus, wherein the transmitter is used for transmitting signals, the receiver is used for receiving signals, the transmitter and the receiver are independently configured respectively or integrated, the storage is used for storing a set of program codes, and the processor is used for calling the set of the program codes stored in the storage to perform following operations:

receiving a switch message of a narrow bandwidth receiving mode sent by a base station through the receiver, and switching to a designated narrow bandwidth to receive information, wherein a width of the narrow bandwidth is smaller than a width of a system bandwidth; and

switching to the system bandwidth or a bandwidth occupied by a pre-scheduled service to receive the pre-scheduled service according to scheduling of the base station when the pre-scheduled service needs to be transmitted.

37. The terminal of claim 36, wherein the processor is further used for receiving downlink control information for the terminal through the receiver in a physical downlink control channel on the narrow bandwidth;

the downlink control information is in a terminal-specific search space corresponding to the terminal, and uses a control channel element aggregation level corresponding to the terminal.

38. The terminal of claim 36, wherein the processor is further used for receiving information relevant to the pre-scheduled service sent by the base station through the receiver before receiving

the switch message of the narrow bandwidth receiving mode sent by the base station through the receiver and switching to the designated narrow bandwidth to receive information, wherein the information relevant to the pre-scheduled service includes process identification information of the pre-scheduled service, periodic information of the pre-scheduled service, and information of
 5 a resource allocated by the base station for the pre-scheduled service.

39. The terminal of claim 38, wherein the processor is specifically used for receiving information of a time interval during which the terminal is in the narrow bandwidth receiving mode and information of a time interval during which the terminal receives the pre-scheduled service sent by the base station through the receiver; and

10 switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service according to the information of the time interval during which the terminal is in the narrow bandwidth receiving mode and the information of the time interval during which the terminal receives the pre-scheduled service when the pre-scheduled service needs to be transmitted.

15 40. The terminal of claim 38, wherein the processor is specifically used for:
 receiving through the receiver a preset period configured by the base station according to the periodic information of the pre-scheduled service, and switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service according to the preset period to receive the pre-scheduled service.

20 41. The terminal of claim 38, wherein the processor is specifically used for:
 receiving, through the receiver, a process identification of the pre-scheduled service and first time information indicating when the terminal switches to the system bandwidth or the bandwidth occupied by the pre-scheduled service, sent by the base station in downlink control information of a physical downlink control channel of the narrow bandwidth, wherein the
 25 downlink control information is used for triggering the terminal to switch to the system bandwidth or the bandwidth occupied by the pre-scheduled service;

receiving, through the receiver, second time information indicating when the terminal returns to the narrow bandwidth receiving mode, sent by the base station through the downlink

control information, or detecting a trigger signal for triggering the terminal to return to the narrow bandwidth receiving mode in a preset area of a physical downlink control channel of the system bandwidth; and

switching to the system bandwidth or the bandwidth occupied by the pre-scheduled service
 5 to receive the pre-scheduled service according to the first time information and the second time information or according to the first time information and the trigger signal.

42. The terminal of any one of claims 36-41, wherein if the bandwidth occupied by the pre-scheduled service is the system bandwidth, the processor is specifically used for switching to the system bandwidth to receive the pre-scheduled service when the pre-scheduled service needs to
 10 be transmitted;

if the bandwidth occupied by the pre-scheduled service is part of the system bandwidth, the processor is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduled service when the pre-scheduled service needs to be transmitted;

15 if the bandwidth occupied by the pre-scheduled service is within the narrow bandwidth, the processor is specifically used for switching to the bandwidth occupied by the pre-scheduled service to receive the pre-scheduling service when the pre-scheduled service needs to be transmitted, and receiving a modulation and coding scheme of the pre-scheduling service and a time-frequency domain resource occupied by the pre-scheduling service sent by the base station
 20 through the receiver in downlink control information of a physical downlink control channel of the narrow bandwidth