

CLAIMS

What is claimed is:

1. A method of decoding a video signal, the method comprising:
constructing a merge candidate list of a current block;
5 deriving motion information of the current block from the merge candidate list,
wherein the motion information comprises at least one of a prediction direction flag, a
reference picture index, or a motion vector; and
performing inter-prediction of the current block using the motion information,
wherein the merge candidate list comprises at least one of a spatial merge candidate,
10 a temporal merge candidate, or a combined merge candidate,
the combined merge candidate is derived by combining n merge candidates
belonging to the merge candidate list, and
the combined merge candidate comprises a first merge candidate and a second merge
candidate, and motion information of the combined merge candidate is derived by a
15 weighted average of motion information of the first merge candidate and motion
information of the second merge candidate.
2. The method according to claim 1, wherein the n merge candidates are merge
candidates corresponding to indices of 0 to (n-1) in the merge candidate list.
3. The method according to claim 1, wherein an index of the combined merge
20 candidate is larger than an index of the temporal merge candidate.
4. The method according to claim 1,
wherein the motion information of the combined merge candidate is derived in
consideration of a prediction direction of the first merge candidate and a prediction
direction of the second merge candidate.
- 25 5. The method according to claim 1, wherein a weight of the weighted average is
any one of [1:1], [1:2], [1:3], or [2:3].
6. The method according to claim 1, wherein the motion vector is derived in units
of sub-blocks of the current block.

7. The method according to claim 6, wherein a size of a sub-block is a fixed size.
8. The method according to claim 6 or 7, wherein a size of a sub-block is 4x4.
9. The method according to claim 1, wherein performing inter-prediction of the current block using the motion information comprises:
- 5 selecting a reference picture from a reference picture list based on the reference picture index of the current block;
- determining a reference block within the reference picture based on the motion vector of the current block;
- generating a prediction pixel of the current block using a pixel of the determined
- 10 reference block; and
- reconstructing the current block by adding the prediction pixel of the current block and a residual pixel.
10. The method according to claim 9, further comprising:
- deriving the residual pixel by performing at least one of inverse quantization or
- 15 inverse transformation on a residual coefficient signaled through a bitstream.
11. An apparatus of decoding a video signal, the apparatus comprising:
- a memory configured to store a program for performing inter-prediction; and
- a processor configured to perform, when running the program, the method according to any one of claims 1-10.
- 20 12. A method of encoding a video signal, the method comprising:
- constructing a merge candidate list of a current block;
- deriving motion information of the current block from the merge candidate list, wherein the motion information comprises at least one of a prediction direction flag, a reference picture index, or a motion vector; and
- 25 performing inter-prediction of the current block using the motion information,
- wherein the merge candidate list comprises at least one of a spatial merge candidate, a temporal merge candidate, or a combined merge candidate,

the combined merge candidate is derived by combining n merge candidates belonging to the merge candidate list, and

the combined merge candidate comprises a first merge candidate and a second merge candidate, and motion information of the combined merge candidate is derived by a
5 weighted average of motion information of the first merge candidate and motion information of the second merge candidate.

13. An apparatus of decoding a video signal, the apparatus comprising:

a memory configured to store a program for performing inter-prediction; and

a processor configured to perform, when running the program, the method according
10 to claim 12.