

ADJUSTABLE DEBURRING TOOL

FIELD AND BACKGROUND OF THE INVENTION

The present invention relates to an adjustable deburring tool capable of deburring of bores of differing bore diameters. Deburring tools are generally designed to deburr a bore of a given bore diameter. In order to deburr bores of differing bore diameters, deburring tools with appropriate diameters are required. Inevitably, each deburring tool requires a cutting blade, or cutting insert, designed to match the diameter of the deburring tool. Therefore, the capability of deburring bores of different bore diameters requires a stock of deburring tools and a stock of appropriate cutting blades, or inserts.

SUMMARY OF THE INVENTION

Example embodiments of the present invention seek to provide an adjustable deburring tool capable of deburring bores with a varying range of bore diameter.

In accordance with a first aspect of the present invention, there is provided an adjustable deburring tool having a longitudinal axis of rotation and comprising a cutting head adjustably coupled to a shank, the cutting head having an insert pocket in which a cutting insert is retained; the cutting head having a front face and a rear face with a ridge projecting from the rear face, the ridge having a recessed portion; the shank having a groove communicating with an open ended and open sided threaded adjusting bore, the ridge being slidably located in the groove with an adjusting screw screw-threaded in the threaded

adjusting bore and partially located in the recessed portion of the ridge; wherein the cutting head is provided with two axially extending oval shaped through bores and the shank is provided with two corresponding axially extending threaded securing bores that open out to a front face of the shank; and wherein the cutting head is secured to the shank by means of two securing screws that are located in the through bores and screw threaded in the threaded securing bores.

In accordance with a second aspect of the present invention, there is provided an adjustable deburring tool holder having a longitudinal axis of rotation and comprising: a cutting head comprising an insert pocket, a front face and a rear face with a ridge projecting from the rear face, the ridge having a recessed portion; a shank comprising a groove communicating with a threaded adjusting bore; and an adjusting screw; wherein: the cutting head is adjustably coupled to the shank with the ridge being slidably located in the groove; the adjusting screw is screw-threaded in the threaded adjusting bore and partially located in the recessed portion of the ridge; the cutting head is provided with two axially extending oval shaped through bores and the shank is provided with two corresponding axially extending threaded securing bores that open out to a front face of the shank; and the cutting head is secured to the shank by means of two securing screws that are located in the through bores and screw threaded in the threaded securing bores.

Preferably, the ridge may have a dove-tail shape and the groove may have a complementary dove-tailed shape.

The groove and the threaded adjusting bore may extend laterally to the longitudinal axis of rotation.

Preferably, the cutting head may be provided with two axially extending oval shaped through bores and the shank may be provided with two corresponding axially extending threaded securing bores that open out to a front face of the shank.

Further preferably, the cutting head may be secured to the shank by means of two securing screws that are located in the through bores and screw threaded in the threaded securing bores.

Normally, a cutting insert may be retained in the insert pocket.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding, the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Fig.1 is a side view of a deburring tool in accordance with the present invention;

Fig. 2 is a side view of the deburring tool shown in Fig. 1 with the cutting head in an adjusted position;

Fig. 3 is an exploded perspective view of the deburring tool shown in Fig.1;

Fig. 4 is bottom perspective view of the cutting head of the deburring tool shown in Fig. 1; and

Fig. 5 is a partially cut away top rear perspective view of the deburring tool shown in Fig. 1.

DETAILED DESCRIPTION OF THE INVENTION

Attention is first drawn to Figs. 1 and 2, showing a deburring tool 10 in accordance with the present invention. The deburring tool 10 has a longitudinal axis of rotation A, defining a forward to rear direction, and comprises a generally cylindrical cutting head 12 adjustably coupled to a generally cylindrical shank 14. The cutting head has a cutting insert 16 fixed or slidably retained in an insert pocket 18. Two cutting edges 20 (20', 20'') are shown in the figures. A forward facing cutting edge 20' for deburring the front edge of a bore and a rearward facing cutting edge 20'' for deburring the rear edge of a through bore. In Fig. 1, the cutting head 12 is shown in a non-adjusted position. In the non-adjusted position, the deburring tool 10 is capable of deburring a bore with a given minimum diameter determined by the distance of the cutting edges 20 from the longitudinal axis of rotation A. In Fig. 2, the cutting head 12 is shown in an adjusted position. In the adjusted position, the deburring tool 10 is capable of deburring a bore with a diameter larger than the given minimum diameter due to the fact that the cutting head 12 is laterally displaced relative to the non-adjusted position shown in Fig. 1, so that the cutting edges 20 are at a greater distance from the longitudinal axis of rotation A in Fig. 2. For the convenience of an operator using the deburring tool 10, a scale 22 giving the relative displacement of the cutting head 12 relative to the non-adjusted position is provided.

Attention is now turned to Figs. 3 to 5. The cutting head 12 has a front face 24 and a rear face 26 with a laterally extending ridge 28 projecting from the rear face 26. The ridge 28 has a recessed portion 30. The ridge 28 has a dove-tail shape, that is, it diverges outwardly and rearwardly. The shank 14 has at its front face 32 a laterally extending groove 34 which has a complementary dove-tailed shape to that of the ridge 28 which enables the ridge 28 to be inserted into it in a direction perpendicular to the longitudinal axis of rotation A. The

cutting head 12 can move laterally, perpendicular to the longitudinal axis of rotation A, with the ridge 28 sliding in the groove 34. The dove-tail connection between the ridge 28 and the groove 34 ensures a certain degree of stability, so that while the ridge 28 is sliding in the groove 34 it will not fall out of the groove
5 34 from the front face 32 of the shank 14.

The groove 34 communicates with a laterally extending open ended and open sided threaded adjusting bore 36. Lateral adjustment of the cutting head 12 relative to the shank 14 is performed by means of an adjusting screw 38. The cutting head 12 is adjustably connected to the shank 14 with the ridge 28
10 located in the groove 34, the adjusting screw 38 located partially in the recessed portion 30 of the ridge 28 and screw-threaded in the threaded adjusting bore 36. When the adjusting screw 38 is rotated it moves laterally in the threaded adjusting bore 36 and at the same time urges the cutting head 12 laterally since it is located partially in the recessed portion 30 of the ridge 28.

15 The cutting head is provided with two axially extending oval shaped through bores 40 and the shank 14 is provided with two corresponding axially extending threaded securing bores 42 that open out to the front face 32 of the shank 14. The cutting head 12 is secured to the shank 14 by means of two securing screws 44 that are located in the through bores 40 and screw threaded in
20 the threaded securing bores 42. When adjusting the lateral position of the cutting head 12, it is sufficient to loosen the securing screws 44, they do not have to be completely removed since the oval shape of the through bores 40 is sufficient to ensure free lateral movement of the cutting head 12. It will be appreciated that the mechanism described hereinabove for lateral adjustment of the cutting head
25 12 enables the lateral location of the cutting edges 20 to be adjusted over a continuous range of values, thereby enabling the deburring tool 10 to deburr bores over a continuous range of diameters. The same cutting insert 16 being used for all the required diameters.

- 5 -

Although the present invention has been described to a certain degree of particularity, it should be understood that various alterations and modifications could be made without departing from the scope of the invention as hereinafter claimed.

CLAIMS:

1. An adjustable deburring tool having a longitudinal axis of rotation and comprising a cutting head adjustably coupled to a shank, the cutting head having an insert pocket in which a cutting insert is retained;

the cutting head having a front face and a rear face with a ridge projecting from the rear face, the ridge having a recessed portion;

the shank having a groove communicating with an open ended and open sided threaded adjusting bore, the ridge being slidably located in the groove with an adjusting screw screw-threaded in the threaded adjusting bore and partially located in the recessed portion of the ridge;

wherein the cutting head is provided with two axially extending oval shaped through bores and the shank is provided with two corresponding axially extending threaded securing bores that open out to a front face of the shank; and

wherein the cutting head is secured to the shank by means of two securing screws that are located in the through bores and screw threaded in the threaded securing bores.

2. The adjustable deburring tool of claim 1, wherein the ridge has a dove-tail shape and the groove has a complementary dove-tailed shape.

3. The adjustable deburring tool of claim 1, wherein the groove and the threaded adjusting bore extend laterally to the longitudinal axis of rotation.

4. The adjustable deburring tool of claim 1, wherein the shank is provided with a scale to indicate relative displacement of the cutting head.

5. The adjustable deburring tool of claim 1, wherein:

the ridge has a dove-tail shape and the groove has a complementary dove-tailed shape;

the groove and the threaded adjusting bore extend laterally to the longitudinal axis of rotation;

the shank is provided with a scale to indicate relative displacement of the cutting head.

6. An adjustable deburring tool holder having a longitudinal axis of rotation and comprising:

a cutting head comprising an insert pocket, a front face and a rear face with a ridge projecting from the rear face, the ridge having a recessed portion;

a shank comprising a groove communicating with a threaded adjusting bore;

and

an adjusting screw;

wherein:

the cutting head is adjustably coupled to the shank with the ridge being slidably located in the groove;

the adjusting screw is screw-threaded in the threaded adjusting bore and partially located in the recessed portion of the ridge;

the cutting head is provided with two axially extending oval shaped through bores and the shank is provided with two corresponding axially extending threaded securing bores that open out to a front face of the shank; and

the cutting head is secured to the shank by means of two securing screws that are located in the through bores and screw threaded in the threaded securing bores.

7. The adjustable deburring tool holder of claim 6, wherein the ridge has a dove-tail shape and the groove has a complementary dove-tailed shape.

8. The adjustable deburring tool holder of claim 6, wherein the groove and the threaded adjusting bore extend laterally to the longitudinal axis of rotation.

9. The adjustable deburring tool holder of claim 6, wherein the shank is provided with a scale to indicate relative displacement of the cutting head.

10. The adjustable deburring tool holder of claim 6, wherein the threaded adjusting bore is open ended and open sided.

11. The adjustable deburring tool holder of claim 6, further comprising a cutting insert retained in the insert pocket.

12. The adjustable deburring tool holder of claim 6, wherein:

the ridge has a dove-tail shape and the groove has a complementary dove-tailed shape;

the groove and the threaded adjusting bore extend laterally to the longitudinal axis of rotation;

the shank is provided with a scale to indicate relative displacement of the cutting head;

the threaded adjusting bore is open ended and open sided; and
a cutting insert is retained in the insert pocket.