

RETRIEVAL SYSTEMS AND METHODS FOR USE THEREOF

RELATED APPLICATIONS

[0001] This application is a non-provisional of U.S. Provisional Application Nos. 61/489,183 filed May 23, 2012 entitled RETRIEVAL SYSTEMS AND METHODS FOR USE THEROF, and 61/489,254 filed May 24, 2012 entitled STENT RETRIEVER WITH INTEGRATED PROTECTION the entirety of each of which is incorporated by reference.

FIELD OF THE INVENTION

[0002] The devices described herein are intended to retrieve obstructions from the body. Such devices have applicability throughout the body, including clearing of blockages within body lumens and providing passive protection of such, such as the vasculature, by providing a capturing portion that can translate and/or mobilize the obstruction within the body lumen.

BACKGROUND OF THE INVENTION

[0003] A large number of medical procedures require the use of medical device(s) to remove an obstruction from a body lumen, vessel, or other organ. An inherent risk in such procedures is that mobilizing or otherwise disturbing the obstruction can potentially create further harm if the obstruction or a fragment thereof dislodges from the retrieval device. If a particle or the obstruction breaks free from the device and flows downstream, it is highly likely that the particle or obstruction will become trapped in smaller and more tortuous anatomy. In many cases, the physician will no longer be able to use the same retrieval device to again remove the obstruction because the size of the device may prevent advancing the device to the site of the new obstruction.

[0004] Even in successful procedures, a physician must proceed with caution to prevent the walls of the vessel or body lumen from imparting undesired forces to shear or dislodge the obstruction as it is translated through the body during removal. These forces have the potential of breaking portions or fragments of the obstruction away. In some cases, the obstruction can simply break free from the retrieval device and can lodge in a new area causing more concern than the original blockage.

[0005] Procedures for restoring flow within the cerebral vasculature as a result of ischemic stroke are one example of where these issues present a concern. The brain relies on its arteries and veins to supply oxygenated blood from the heart and lungs and to remove carbon dioxide

and cellular waste from brain tissue. Blockages that interfere with this supply eventually cause the brain tissue to stop functioning. If the disruption in supply occurs for a sufficient amount of time, the continued lack of nutrients and oxygen causes irreversible cell death (infarction). Accordingly, immediate medical treatment of an ischemic stroke is critical for the recovery of a patient. To access the cerebral vasculature a physician typically advances a catheter from a remote part of the body (typically a leg) through the vasculature and into the cerebral region of the vasculature. Once within the cerebral region, the physician deploys a device for retrieval of the obstruction causing the blockage. Concerns about dislodged obstructions or the migration of dislodged fragments increases the duration of the procedure at time when restoration of blood flow is paramount. Furthermore, a physician might be unaware of one or more fragments that dislodge from the initial obstruction and cause blockage of smaller more distal vessels.

[0006] Many physicians currently use stents to perform thrombectomy (i.e. clot removal) to resolve ischemic stroke. Typically, the physician deploys the stent into the clot, in an attempt to push the clot to the side of the vessel and re-establish blood to flow. Tissue plasminogen activator ("Tpa") is often injected into the bloodstream through an intravenous line. The TPA must travel in the blood stream until it reaches the clot that is causing the blockage. Once the Tpa contacts the clot, it begins to break up the clot with the hope of restoring blood flow to the affected areas. Tpa is also often administered to supplement the effectiveness of the stent. Yet, if attempts at clot dissolution are ineffective or incomplete, the physician can attempt to remove the stent while it is expanded against or enmeshed within the clot. In doing so, the physician must effectively drag the clot from the vessel, in a proximal direction, into a guide catheter located within vessels in the patients neck (typically the carotid artery). While this procedure has been shown to be effective in the clinic and easy for the physician to perform, there remain some distinct disadvantages using this approach.

[0007] The stent may not sufficiently hold onto the clot as it drags the clot to the catheter. In such a case, the clot might not move from the vessel. Another risk is that use of the stent might mobilize the clot from the original blockage site, but the clot might not adhere to the stent during translation toward the catheter. This is a particular risk when translating through bifurcations and tortuous anatomy. Furthermore, blood flow can migrate the clot (or fragments of the clot) into a branching vessel at a bifurcation. If the clot is successfully brought to the guide catheter in the carotid artery, yet another risk is that the clot may be "stripped" or "sheared" from the stent as the stent enters the guide catheter. Regardless, simply dragging an expanded stent (either fully or partially expanded) can result in undesired

trauma to the vessel. In most cases, the stent is oversized compared to the vessel. Dragging a fixed metallic (or other) structure can pull the arteries and/or strip the cellular lining from the vessel, causing further trauma such as a hemorrhagic stroke (leakage of blood from a cerebral vessel). Also, the stent can become lodged on plaque on the vessel walls resulting in further vascular damage.

[0008] In view of the above, there remains a need for improved devices and methods that can remove occlusions from body lumens and/or vessels. While the discussion focuses on applications in the cerebral vasculature, the improved devices and methods described below have applications outside of the area of ischemic stroke.

SUMMARY OF THE INVENTION

[0009] The examples discussed herein show the inventive device in a form that is suitable to retrieve obstructions or clots within the vasculature. The term obstructions may include blood clot, plaque, cholesterol, thrombus, naturally occurring foreign bodies (i.e., a part of the body that is lodged within the lumen), a non-naturally occurring foreign body (i.e., a portion of a medical device or other non-naturally occurring substance lodged within the lumen.) However, the devices are not limited to such applications and can apply to any number of medical applications where elimination or reduction of the number of connection points is desired.

[0010] The devices discussed herein include interventional medical devices for retrieving and securing an obstruction within a vessel lumen. In one example the device comprises a shaft having a flexibility to navigate through tortuous anatomy, the shaft a distal portion and a proximal portion; a capturing structure located at a distal portion of the shaft comprising a plurality of struts, the capturing structure having a reduced profile for positioning in or adjacent to the obstruction and an expanded profile, such that when expanded into the obstruction, the struts at least partially enmesh with the obstruction such that subsequent movement of the capturing structure permits dislocation of at least a portion of the obstruction from the lumen; an eversible cover having a fixed section affixed relative to a proximal end of the capturing structure, a free section extending in a proximal direction from the distal section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable such that at least a portion of the eversible cover has a diameter equal to or greater than the capturing structure, the eversible cover being axially compliant such that when the shaft is moved proximally within the lumen, in some cases friction between the cover wall and the lumen resists proximal movement of the cover wall to cause the eversible

cover to evert over the capturing structure allowing for the free section of the cover to be distal to the fixed end of the capturing portion. Evert or eversible generally includes movement of the device within the cover causing the cover to turn inside out as it protects and covers the retrieval device. The covers disclosed herein can be expandable through self-expanding configurations, or via actuated expansion (e.g., a shape memory alloy, spring expansion, or other actuation).

[0011] In one example, the device includes a configuration where the eversible cover, capturing structure, and shaft are a unitary structure. The device can also be configured so that each wire located at an end of the free section loops back to the cover causing the wires at the end of the free section to be continuous.

[0012] In another variation at least a portion of the cover wall adjacent to the distal end has a set shape that is everted upon expansion. The device can also optionally include a catheter body, where in a delivery configuration, the shaft, capturing structure and eversible cover are located within the catheter body and where the capturing structure is advanceable in and out of a distal end of the catheter body.

[0013] The device can also be configured so that the fixed section of the eversible cover comprises a pre-set shape to reduce a force required to evert the evertable cover.

[0014] The retrieval devices can comprise any number of capturing or retrieval device such as a filter, an artherectomy device, a rotational cutter, an aspiration device, stent based retrievers and retrieval baskets.

[0015] The methods described herein can include methods of securing an obstruction within a vessel. In one example, the method can comprise: positioning a catheter within a vessel; advancing a shaft having a retrieval device affixed thereto out of the catheter; advancing an eversible cover out of the catheter such that a fixed end of the eversible cover is affixed adjacent to a proximal end of the retrieval device and a free end of the eversible cover is moveable relative to the shaft and retrieval device; expanding at least a portion of the eversible cover against a portion of a wall of the vessel; manipulating the retrieval device to become at least partially enmeshed with the obstruction; and proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.

[0016] In another variation, the methods can include further withdrawing the shaft from the vessel such that during withdrawal the eversible cover forms a protective barrier over the

obstruction to lessen shearing forces caused by the vessel and reduce dislodging portions of the obstruction from the retrieval device.

[0017] Another variation of a method includes a method of preparing a retrieval device comprising: providing a retrieval device having been previously removed from a body of a patient where the retrieval device includes a protective cover where a fixed end of the protective cover is affixed adjacent to a proximal end of the retrieval device and where a free end is located distally to the fixed end covering the retrieval device and is moveable relative to the second end; reversing the protective cover by moving the free end proximally of the fixed while the fixed end remains affixed adjacent to the proximal end of the retrieval device; inserting the retrieval device and cover into a catheter where the free end of the cover is proximal to the fixed end of the cover and retrieval device such that upon deployment from the catheter, the free end of the cover deploys proximally to the fixed end of the cover.

[0018] In another example, the devices described herein can include medical device retrieval systems for securing an obstruction within a vessel lumen and for use with a catheter configured to be navigated through the vasculature. In one variation, the device comprises an elongated stent comprising a plurality of struts, the stent being collapsible for positioning in the catheter during delivery and having an expanded profile such that when expanded the struts are configured to engage the obstruction; a shaft fixedly attached to the elongated stent and having a flexibility to navigate through tortuous anatomy; a fluid permeable cover having a distal end coupled to a proximal end of the elongated stent a cover wall defining a cavity and extending along the shaft, and a proximal end being moveable relative to the shaft, where the fluid permeable cover is collapsible for positioning in the catheter during delivery and is expandable upon deployment from the catheter such that at least a portion of the fluid permeable cover is expandable; where the fluid permeable cover is axially pliable such that when the device is deployed in the vessel the frictional forces between the vessel and the fluid permeable cover permit proximal movement of the shaft and elongated stent to cause inversion of the fluid permeable cover wall such that the fluid permeable cover wall everts over the elongated stent.

[0019] Another variation of a device includes an interventional medical device for use with a catheter configured for delivery through vasculature for securing an obstruction within a vessel lumen. For example, the device can comprise a shaft having a flexibility to navigate through tortuous anatomy, the shaft having a distal portion and a proximal portion; a capturing device comprising a sidewall, the capturing device fixedly located at a distal portion of the shaft and having a reduced profile for positioning in the catheter and an expanded

profile, such that upon deployment from the catheter, the capturing device expands to force a portion of the sidewall into the obstruction to at least partially attach to the obstruction; a cover having a distal end coupled adjacent to a proximal end of the capturing structure, a proximal end and a cover wall extending therebetween, where the proximal end of the cover is slidable relative to the distal end, where the cover is expandable such that when located in the catheter the cover is in a reduced delivery state and upon advancement from the catheter the cover expands with the proximal end located proximally of the distal end, where the cover wall is compliant such that when deployed from the catheter and the shaft is pulled in a proximal direction frictional forces between the vessel and the cover wall or proximal end cause the cover to invert as the cover wall inverts over the capturing device to surround the capturing device.

[0020] Another variation of the device include an interventional medical device for securing a retrieval device having one or more obstructions located therein for removal from a body. In one such example the medical device includes a sheath having a flexibility to navigate through tortuous anatomy, the sheath a distal portion and a proximal portion and a lumen extending therethrough; an eversible cover having a fixed section affixed to the distal portion of the sheath, a free section extending in a proximal direction from the fixed section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable, the eversible cover being axially compliant such that when the retrieval device is positioned through the sheath lumen moved in a proximal direction against the eversible cover, the eversible cover everts over the retrieval device allowing for the free section of the cover to be distal to the retrieval device.

[0021] Another variation of the method includes advancing a shaft having a retrieval device affixed thereto to the obstruction; advancing a protective device over the shaft, the protective device comprising a sheath having an eversible cover, where a fixed end of the eversible cover is affixed to a distal portion of the sheath and a free end of the eversible cover is located proximal to the fixed end; positioning the fixed end of the eversible cover adjacent to the retrieval device and expanding at least a portion of the eversible cover against a portion of a wall of the vessel; proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.

[0022] The capturing portions described herein can include a stent retrieval device for expanding against one or more occlusive bodies in a vasculature. In one example, the stent

retrieval device includes an elongate shaft having a flexibility to navigate through tortuous anatomy, the elongate shaft having a distal portion and a proximal portion; a plurality of filaments that diverge from the distal portion of the elongate shaft to form an expandable elongated stent body having a open distal end and a fluid permeable closed proximal end and a cavity therebetween, where divergence of the filaments at the distal portion of the elongate shaft forms the fluid permeable closed proximal end; where the plurality of filaments extending along the shaft are free of any connection joints in the distal portion to permit increased flexibility of the distal portion as it navigates through tortuous anatomy; and one or more connection joints proximal to the distal portion where the connection joints secure the plurality of filaments to the shaft.

[0023] The stent retrieval can also include at least one of the plurality of filaments that comprise at least two wires twisted together, the elongated stent body further comprising at least one intersection of filaments, where the wires of each filament are interwoven to provide increased outward radial strength of the elongated stent body and such that the wires slide relative to each other as the elongated stent body expands or compresses in diameter to reduce a force required to linearize the elongated stent body.

[0024] The stent retrieval device can have an exterior surface of the elongated stent body that comprises an irregular surface formed by intersection of filaments.

[0025] The stent retrieval device can also have intersection of filaments comprising a barb or knuckle and where a plurality of barbs or knuckles are radially spaced about the elongated stent body. The stent retrieval device can also have an intersection of filaments that comprises a barb or knuckle and where a plurality of barbs or knuckles are aligned with an axis of the elongated stent body.

[0026] In one variation of the devices described herein, the device comprises a main bundle or group of wires that diverge to form a device having various shapes but few or no connections points or joints (where fabrication of such a construction is referred to as "jointless"). Clearly, the inventive devices described herein are not limited to such a jointless construction. Additional variation includes one or more leading wires that are attached to a capturing portion as described below.

[0027] Devices of the present invention can incorporate any number of wires of different characteristics including, but not limited to, materials, shapes, sizes and/or diameters. Clearly, the number of permutations of device configurations is significant. Providing devices with such a composite construction allows for the manipulation of the device's properties to suite the intended application.

[0028] As noted herein, the joint-less construction improves the flexibility and strength of the device by eliminating joints, connection points, or other attachment points. In addition, the joint-less construction improves the ability of the device to be delivered through a small microcatheter. As a result, the device and microcatheter are able to access remote regions of the vasculature.

[0029] The devices may be fabricated to be self-expanding upon deployment from a catheter. Alternatively, the devices can be constructed from shape-memory alloys such that they automatically deploy upon reaching a pre-determined transition temperature.

[0030] It should be noted that in some variations of the invention, all or some of the device can be designed to increase their ability to adhere to the obstruction. For example, the wires may be coupled to an energy source (e.g., RF, ultrasonic, or thermal energy) to “weld” to the obstruction. Application of energy to the device can allow the surrounding portion to deform into the obstruction and “embed” within the obstruction. Alternatively, the device can impart a positive charge to the obstruction to partially liquefy the obstruction sufficiently to allow for easier removal. In another variation, a negative charge could be applied to further build thrombus and nest the device for better pulling force. The wires can be made stickier by use of a hydrophilic substance(s), or by chemicals that would generate a chemical bond to the surface of the obstruction. Alternatively, the filaments may reduce the temperature of the obstruction to congeal or adhere to the obstruction.

[0031] Additional devices and methods for treating ischemic stroke are discussed in commonly assigned U.S. Patent application nos.: 11/671,450 filed February 5, 2007; 11/684,521 filed March 9, 2007; 11/684,535 filed March 9, 2007; 11/684,541 filed March 9, 2007; 11/684,546 filed March 9, 2007; 11/684,982 filed March 12, 2007, 11/736,526 filed April 17, 2007, 11/736,537 filed April 17, 2007, 11/825,975 filed September 10, 2007; 12/344,378 filed 12/26/2008, 13/012,727 filed 1/24/2011, and 13/226,222 filed 9/6/2011; the entirety of each of which is incorporated by reference. The principles of the invention as discussed herein may be applied to the above referenced cases to produce devices useful in treating ischemic stroke. In other words, the wire-shaped construction of devices according to present invention may assume the shapes disclosed in the above-referenced cases when such a combination is not inconsistent with the features described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0032] Each of the following figures diagrammatically illustrates aspects of the invention. Variation of the invention from the aspects shown in the figures is contemplated.
- [0033] Fig. 1 illustrates an example of a device according to the present invention when used in a system for removing obstructions from body lumens.
- [0034] Figs. 2A to 2C illustrate working ends of various coverable retrieval devices.
- [0035] Figs. 2D and 2E show variations of retrieval devices.
- [0036] Fig. 2F shows an independent eversible cover on a delivery sheath.
- [0037] Figs. 3A to 3C illustrates an example of a coverable retrieval device where the cover everts about the retrieval structure.
- [0038] Fig. 4A to 4I illustrates an example where an improved retrieval device with passive protection retrieves a clot from tortuous anatomy.
- [0039] Figs. 4J and 4K illustrate examples of an obstruction or other material captured within a retrieval device with a cover further protecting the loaded retrieval device.
- [0040] Fig. 5A illustrates a retrieval device having a retrieval structure adjacent to a double layer cover.
- [0041] Fig. 5B shows a funnel with a free end that tapers down about the delivery wire.
- [0042] Figs. 5C and 5D show a fixed end of a cover that is pre-shaped to reduce the force required to evert the cover wall.
- [0043] Fig. 5E shows alternate variation of a passive cover integrated into a retrieval device.
- [0044] Fig. 5F illustrates a cover having a pre-set flattened cover wall at a fixed end of the retrieval structure.
- [0045] Figs. 5G to 5I illustrate various layered covers.
- [0046] Fig. 5J shows a cover that is constructed directly onto the retrieval structure rather than the delivery shaft.
- [0047] Figs. 5K and 5L show a variation of a cover and retrieval device where the cover is first mounted in a distal direction and then inverted in a proximal direction.
- [0048] Figs. 6A to 6L illustrate a variation of covers for use as describe herein.
- [0049] Figs. 7A to 7C show additional variations of covers.
- [0050] Fig. 8 illustrates a variation of a proximal and distal end of an additional retrieval device.
- [0051] Figs. 9A to 9C illustrate wires of different constructions within a delivery wire or shaft.

- [0052] Figs. 10A to 10E illustrate additional variations of covers for use as described above.
- [0053] Figs. 11A to 11C illustrate additional variations of covers for use with the devices and methods described herein.
- [0054] Figs. 12A to 12E illustrate various stent designs for increasing the ability of a stent to adhere to an occlusion within a vessel.
- [0055] Fig. 12G illustrates a proximal end of the stent structure.

DETAILED DESCRIPTION

- [0056] It is understood that the examples below discuss uses in the cerebral vasculature (namely the arteries). However, unless specifically noted, variations of the device and method are not limited to use in the cerebral vasculature. Instead, the invention may have applicability in various parts of the body. Moreover, the invention may be used in various procedures where the benefits of the method and/or device are desired.
- [0057] Fig. 1 illustrates a system **10** for removing obstructions from body lumens as described herein. In the illustrated example, this variation of the system **10** is suited for removal of an obstruction in the cerebral vasculature. As stated herein, the present devices and methods are useful in other regions of the body including the vasculature and other body lumens or organs. For exemplary purposes, the discussion shall focus on uses of these devices and method in the vasculature.
- [0058] It is noted that any number of catheters or microcatheters maybe used to locate the catheter/microcatheter **12** carrying the obstruction removal device **200** at the desired target site. Such techniques are well understood standard interventional catheterization techniques. Furthermore, the catheter **12** may be coupled to auxiliary or support components **14**, **16** (e.g., energy controllers, power supplies, actuators for movement of the device(s), vacuum sources, inflation sources, sources for therapeutic substances, pressure monitoring, flow monitoring, various bio-chemical sensors, bio-chemical substance, etc.) Again, such components are within the scope of the system **10** described herein.
- [0059] In addition, devices of the present invention may be packaged in kits including the components discussed above along with guiding catheters, various devices that assist in the stabilization or removal of the obstruction (e.g., proximal-assist devices that holds the proximal end of the obstruction in place preventing it from straying during removal or assisting in the removal of the obstruction), balloon-tipped guide catheters, dilators, etc.

[0060] Fig. 2A illustrates a working end of a coverable retrieval device **100**. Typically, the device includes a capturing or retrieval structure **200**. In the illustrated example, the retrieval structure **200** comprises an elongated stent structure. However, unless specifically noted, the capturing structure can comprise any number of devices, including but not limited to a filter, an artherectomy device, a rotational cutter, an aspiration catheter.

[0061] The retrieval structure **200** is located at a distal end of a delivery wire **202**. In one variation, the retrieval structure **200** can be permanently affixed to the delivery wire **202** by such methods including, but not limited to adhesive bonding, soldering, welding, polymer joining, or any other conventional method. In some variations, the retrieval device **200** can be formed from one or more wires forming the delivery wire **202** or shaft **202**. The delivery wire **202** can have sufficient column strength such that it can axially advance and retract the device **100** within the vasculature as the physician manipulates a non-working end of the delivery wire **202** outside of the body. Accordingly, the delivery wire **202** should have a length that is sufficient to extend from the target area, e.g., the cerebral vasculature, to the entry point on the body. Alternatively, additional variations of the device **100** can allow for the use of a support member or catheter that positions the retrieval structure **200** as needed. Additional features of the retrieval structure **200** can be found in the commonly assigned patents and applications cited herein and incorporated by reference.

[0062] The coverable retrieval device **100** further includes a cover **300** (also referred to as a funnel or sheath) affixed relative to a proximal end **206** of the retrieval structure **200**. By being affixed relative to a proximal end **206**, a distal end **204** of the retrieval structure **200** can move relative to the cover **300** so that the cover **300** everts over the proximal end **206** of the structure **200** when the cover **300** is expanded within a vessel and as the structure **200** is withdrawn into the distal end **302** of the cover **300**. This mechanism is discussed in detail below.

[0063] Figs. 2B and 2C illustrate alternative variations of a coverable retrieval device **100**. As shown in Fig. 2B and 2C, the distal end **302** of the cover **300** can be spaced from the proximal end **206** of the retrieval structure **200**. Alternatively, the distal end **302** of the cover **300** can extend over a portion of the retrieval structure **200**. In some variations, at least a section of the cover **300** expands to a greater diameter than a diameter of the retrieval structure **200**. This allows the cover **300** to expand to a vessel wall where the vessel holds the cover stationary while the device is pulled proximally through the cover to evert the cover. In alternate variations, the cover **300** expands to the same or lesser diameter than the retrieval structure **200** or other device.

- [0064] Fig. 2D shows a retrieval device **100** with a catheter **112** (usually a microcatheter). The retrieval device **100** can comprise a single unitary device of a cover **300** and retrieval structure **200** (in this case the retrieval structure is an elongated stent structure). One benefit of a unitary device is that additional devices complicates the procedure and can increase the duration of what is ordinarily a time sensitive procedure. The retrieval device **100** can be positioned through the catheter **112** that includes a hub **114**. As a result, the physician only needs to manipulate the unitary retrieval device **100** and the catheter/microcatheter **112**. The retrieval device **100** is loaded into the catheter **112** for placement at the target site. In addition, the retrieval device can be reloaded if the procedure must be repeated. The cover **300** and retrieval structure **200** described herein can comprise any construction described herein or as known by those skilled in the art.
- [0065] Fig. 2E shows a retrieval device **100** with a cover **300** and retrieval device **200** with a radiopaque marker **305** therebetween. As shown, variations of the device **100** do not require a catheter or microcatheter.
- [0066] Fig. 2F illustrates an eversible cover **300** located on a sheath **330** having a lumen **332** extending therethrough. A separable retrieval device **200** can be coupled to the cover **300** and sheath **330** by inserting the wire **202** of the cover retrieval device **200** through the lumen **332** of the sheath **330**. In this variation, the eversible cover **300** can be used with any number of different interventional tools. The separate devices can be assembled prior to delivery into the patient. Alternatively, the devices can be positioned within the body and subsequently joined once the retrieval device **200** engages the target area.
- [0067] Fig. 3A illustrates an example of a coverable retrieval device **100** where the cover **300** is in the process of everting about the retrieval structure **200**. As shown, arrow **50** illustrates a force applied on the wire **202** in a proximal direction. Arrows **52** illustrate a resistance force applied by the friction of the expanded cover **300** against a vessel or similar wall. This friction force **52** prevents or resists proximal movement of the free end **304** of the cover **300** while the fixed end **302** moves in a proximal direction with the proximal end **206** of the retrieval structure **200**. This action causes a wall **306** of the cover **300** to evert over the retrieval structure **200**. Ultimately, and as shown in Fig. 3B, the free end **304** of the cover **300** ends up distally over the fixed end **302**. As shown, the wall of the everted cover **300** provides a safety type cover for the retrieval device **200**. In additional variations, the fixed end **302** of the cover can actually be slidable or moveable along the delivery wire **202**. However, the similar principle as discussed above shall apply to cause everting of the cover **300** over the retrieval structure **200**.

[0068] Fig. 3C illustrates another variation of a coverable retrieval device 100 after the cover 300 is everted about the retrieval structure 200. In this variation, the free end 304 of the cover 300 ends up distally of the fixed end 302 and tapers or collapses towards the free end 304. The cover 300 can be shape set so that prior to eversion the cover is as shown above where the forces acting on the cover wall 306 expand outwards, but after eversion the forces on the cover wall 306 cause the tapering or collapsing as shown in Fig. 3C.

[0069] In accordance with the illustrations discussed above, the cover 300 can be made so that the cover wall 306 is atraumatic when dragged across a lumen wall. The cover can be manufactured from any number of materials including a fabric, a reinforced fabric, a braid, weave, or any such material that allows for expansion against a wall of the body lumen or vessel as well as to allow everting of a wall 306 of the cover over the retrieval device 200. The cover wall 306 can also comprise combinations of these materials such as braids of polymer material with metal fibers, soft braids with coil reinforcements or various other combinations.

[0070] The cover wall can comprise a mesh that can include any medically acceptable materials such as a Nitinol braid. Furthermore, the mesh allows for flow through the vessel or lumen while expanded. However, additional variations of the device can include a solid layer of material substituted for the mesh. Moreover the cover can comprise any number of configurations. For example, the cover can comprise a single layer wall or a multi layer wall, the open end of the cover could be made to have terminated ends such as by using continuous wire loops formed during the braiding process. Alternatively, the ends can be cut and then terminated by encasing in polymer, laser welds, or by folding inward for a discreet length and then terminating

[0071] In one example, the cover 300 comprises a continuous wire construction as described in earlier commonly assigned patent applications incorporated by reference. In one variation the cover 300 comprises a finely braided wire, such as 48-96 wires of .0005" to 0.002" diameter fine Nitinol wire or similar. Additionally, the wire can comprise cobalt chromium, stainless steel, or similar, or drawn filled tube (dft) with platinum core. In additional variations, a flat wire or oval wire can be used. The wire does not need to be uniform. Instead, a number of different types of wires can be used. Some of the individual wires could be platinum alloys for added radiopacity.

[0072] Fig. 4A to 4I illustrates an example where an improved retrieval device 100 with passive protection retrieves a clot 2 from tortuous anatomy. Fig. 4A illustrates a clot 2 that obstructs blood flow in a vessel 6. As noted herein, the vessel 6 can comprise any vessel in

cerebral vasculature, coronary or peripheral vasculature. Alternatively, the device and methods for use are not limited to use in the vasculature. Variations of the principles, concepts, method and devices described herein can be applicable wherever a retrieval device can be used. Fig. 4A also illustrates a guide sheath or access catheter **108** that is advanced within the vessel. During a procedure, the physician will advance the access catheter **108** as far distally as possible. However, due to the size of the access catheter **108**, a physician typically positions it a distance away from the obstruction **2**. As shown, there can be any number of bifurcations **8** in the vessel **6** located between the access catheter **108** and the obstruction **2**. As discussed herein, in some variations, the access catheter **108** can be used to remove the obstruction **2** from the body once the obstruction is captured by a retrieval device. However, the greater the distance between the initial location of the obstruction **2** and the location of the access catheter **108**, the greater the risk that the obstruction **2** can break free from the retrieval device or become dislodged due to anatomic or environmental features, including but not limited to bifurcations, the wall of the lumen, the tortuosity of the anatomy, vessel wall plaque, etc.

[0073] Fig. 4B illustrates an optional catheter **112** that advances from the access catheter **108** to the site of the obstruction **2**. Once at the site, the catheter **112** can deploy a retrieval device (not shown in Fig. 4B) so that the retrieval device can engage the clot **2**. Alternatively, the catheter **112** can traverse the obstruction **2** as shown in Fig. 4C and deploy a portion of the retrieval device **100** distally to the obstruction **2**. The physician then manipulates the retrieval device **100** to secure the obstruction **2**. For example, the physician can deploy the retrieval structure **200** distally to the obstruction **6** and withdraw the retrieval structure **200** proximally to secure the obstruction **2**. In another variation, the physician can position the retrieval structure **200** within the catheter **2** while the catheter **112** is through or adjacent to the obstruction **2**. Then, the physician can withdraw the catheter **112** to expose the retrieval structure **200** so that it secures to the obstruction **2** after expansion. In the illustrated example, the retrieval structure **200** comprises an elongated stent type structure that expands (or is expanded) to enmesh or secure to the obstruction. Although not illustrated, the system can include a distal capture filter or basket as described in any of the commonly assigned applications incorporated by reference herein.

[0074] Next, as shown in Fig. 4E, the physician can further withdraw the catheter **112** to expose a cover **300** as described above. In many cases, the physician exposes the cove **300** once the retrieval structure **200** is engaged with the obstruction **2**. This sequential process allows for easier repositioning of the retrieval structure **200** if necessary. Alternatively, the

cover 300 can be deployed prior to engaging the retrieval structure 200 with the obstruction 2. If necessary, the physician can apply a proximal force on the delivery wire 202 while withdrawing the catheter 112 to prevent inadvertent movement of the obstruction 2 and retrieval device 200.

[0075] Fig. 4F illustrates the stage with a fully exposed the cover 300 and a catheter 112 moved closer towards the access sheath 108. As shown, the free end 304 of the cover 300 is proximal to fixed end 302 of the cover 300. As also noted above, the cover 300 can be a shape memory alloy that expands against the walls of the vessel 6 upon reaching body temperature. Alternatively, the cover 300 can be self expanding upon deployment into the vessel 6. In some variations, the cover wall 306 comprises a porous material or construction that allows blood to continue to flow through the cover 300.

[0076] In addition, some variations of the retrieval device 100 include a cover 300 that has at least a section that expands to a greater diameter or dimension than the retrieval structure 200. This allows for expansion of the cover 300 against the wall of the vessel 6. In most variation, expansion of the cover 300 provides sufficient friction against the walls of the vessel to overcome column strength of the cover walls 306 allowing for everting of the cover walls 306 over the retrieval structure 200 and obstruction 2 as discussed herein. As noted above, in alternate variations the cover 300 can expand a diameter or dimension that is equal to or less than the retrieval structure 200.

[0077] Figs. 4G illustrates proximal movement of the delivery wire 202, which causes proximal translation of the obstruction 2 and retrieval structure 200. Because the cover 300 is expanded against the walls of the vessel 6 the free end 304 of the cover 300 does not move or moves less than the fixed end 306 of the cover 300. The fixed end 306 moves with the obstruction 2 and retrieval structure 200 in a proximal direction causing the cover walls 306 to evert over the obstruction 2 and retrieval structure 200. Unlike a conventional funnel, the everting cover functions similar to a conveyor belt type movement as the obstruction and retrieval structure move together. This action allows for a passive type of protection since cover 300 does not need to be actuated over the obstruction 2 and retrieval structure 200 and can be performed in a quick manner by simply withdrawing the deployed retrieval device 100.

[0078] Fig. 4H illustrates a stage where the fixed end 306 of the cover 300 is now proximal to the free end 304. As shown, the everted cover 300 forms a protective sheath or cover over the obstruction 2 and the retrieval structure 200. Fig. 4H also illustrates how the cover 300 protects the obstruction 2 and retrieval structure 200 as they are pulled along the vessel and navigate the tortuous anatomy, walls of the vessel, as well as bifurcations 8. The cover 300

and cover wall 306 also protects the vasculature from the surface of the retrieval structure 200 and obstruction 2.

[0079] Fig. 4I shows the obstruction 2 and retrieval structure 200 protected by the cover 300 as the retrieval device 100 is positioned against or within the access catheter 108 in preparation for removal from the body. The retrieval device 100 can remain outside of the access catheter 108 as the physician removes both devices from the body. Alternatively, the cover 300 can assist in pulling the retrieval device 100 and obstruction 2 into the access catheter 108 by compressing the obstruction 2 as it is pulled into the access catheter 108.

[0080] Figs. 4J and 4K illustrate examples of an obstruction or other material 2 captured within a retrieval device 2 with a cover 300 further protecting the loaded retrieval device 200.

[0081] Figs. 5A to 5K show a variety of cover configurations. Fig. 5A illustrates a retrieval device 100 having a retrieval structure 200 adjacent to a double layer cover 300 with an exterior wall 306 and an interior wall 308.

[0082] Fig. 5B shows a cover 300 with a free end 304 that tapers down about the delivery wire 202 where the cover 300 will eventually form a double wall configuration when the cover 300 everts over the retrieval structure 200. The tapered free end 304 limits the cover 304 from moving once the retrieval structure 200 reaches the free end 304 thereby forming double wall protection over the retrieval structure 200.

[0083] Figs. 5C and 5D show how a fixed end 302 of a cover 300 can be pre-shaped to reduce the force required to evert the cover wall 306 or to lower the threshold to trigger passive covering of the retrieval structure by the cover.

[0084] Fig. 5E shows alternate variation of a passive cover 300 integrated into a retrieval device 100. In this variation, the retrieval device 100 includes a control shaft or wire 202 to manipulate the working end of the retrieval device 100. The cover 300 floats along the shaft 202 between two fixed anchors or nodes 220, 222. The cover 300 can float or slide between the fixed nodes 220, 222. The nodes 220, 222 can comprise radiopaque marker bands, glue joints, or any other mechanical obstructions capable of stopping the translation of cover 300. When the device 100 advances through a microcatheter, the rear or proximal node 220 limits rearward movement of the cover 300. When positioned appropriately, the microcatheter can be withdrawn to expose the retrieval device 200 and cover 300 as described herein. When the retrieval structure 200 engages the obstruction (not shown) the retrieval device 100 can be withdrawn by pulling on the delivery shaft 202. While this occurs, the cover 300, being expanded against the vessel remains stationary (or moves at a slower rate than the obstruction and retrieval structure 200 due to the friction against the vessel wall). The retrieval structure

200 and clot enter the cover 300, causing the distal node 222 to make contact with the near end 320 of the cover 300. This contact causes the retrieval structure 200 and cover 300 to translate as an integrated unit. It should be appreciated that the cover could be a single layer or double layer cover, and could have any of the wire design variables and termination variables described herein.

[0085] Fig. 5F illustrates a cover having a pre-set flattened cover wall 304 at a fixed end 302 that is spaced from a proximal end of the retrieval structure 200. Figs. 5G to 5I illustrate various layered covers 300. The layered covers allow for shortening the axial length of the cover and therefore shortens the required translation length. Layering of the cover wall 306 allows for a shortened deployed length of the cover 300 when deployed in the vessel or body structure. As the cover 300 everts over the retrieval structure 200 the layered wall 306 extends. As a result, shortening the length reduces the length that the cover 300 extends into the proximal vessels and reduces the length of that the retrieval structure 200 must travel to become protected by the cover 300. This also helps shorten the distance required to move the device 100 to complete eversion of the cover 300.

[0086] Fig. 5J shows a cover 300 that is constructed directly onto the retrieval structure 200 rather than the delivery shaft 202. This construction also assists in reducing the distance necessary to complete passive protection of the retrieval structure by the cover.

[0087] Fig. 5K show a variation of a cover 300 that is mounted in a distal direction over the retrieval device 200 and then everted in a proximal direction over the wires or shaft 202 as shown by arrows 230. Once everted, as shown by Fig. 5L, the device 100 is ready for deployment as discussed herein.

[0088] Figs. 6A to 6B illustrate a variation of a cover 350 for use as describe herein. Additionally, the cover 350 can be used with any obstruction retrieval device not limited to the retrieval baskets and stents described herein. The covers 350 disclosed herein can be used where the physician desires to shield the obstruction being removed from the frictional effects of the arteries or from the local anatomy (e.g., branching vessels, tortuous anatomy, or other substances on the vessel walls). In use, the covers can be sized for use with guide catheters, micro-catheters, and/or distal access catheters. The covers can include any number of radiopaque marker bands to allow non-invasive imaging of the device (see marker 390 affixed between cover 350 and shaft 212 in Fig. 7B as one example). In any case, once the retrieval device captures a clot or obstruction, as described above, the device and clot are protected by the cover so that the cover eliminates or reduces direct contact between the interior of the wall of the vessel and the clot.

[0089] Figs. 6A to 6C show a variation in which a cover is created from one or more mesh tubes 372. Fig. 6B illustrates inversion of the tube 372 so that a first end 374 is drawn over the tube 372 towards a second end 376. As shown in Fig. 6C, this creates a double walled cover having an exterior wall 378 separated from an interior wall 380. In one example, such a spacing or gap could range between 0.001 inches to 0.100 inches. However, any range is contemplated within alternative variations of the device. In some variations the inverted cover 350 is heat set to maintain a separation between layers or walls 378 380 of the cover 350. Typically, if the cover 350 is not created from a radiopaque material, a marker band will be placed on the proximal end 376 and adjacent to a shaft or catheter to which the cover 350 is attached. In some variations the construction of the mesh material is compliant to allow for movement of a first part of the mesh relative to a second part of the mesh through compression and expansion of the mesh material. In such a case, the individual strands forming the mesh are moveable relative to one another to cause the mesh to be naturally compliant. Accordingly, this construction permits the inner wall 380 to move or deflect with the retrieval device and/or obstruction as the device is withdrawn into the cover 350. In some variations, both ends of the mesh 374 and 376 are affixed to the catheter, shaft or wire.

[0090] In many variations, the cover mesh is selected to minimize friction when the interior layer 380 moves against the exterior layer 378. For example, the braid pattern, wire, wire diameter, angle of the braid and or other features can be selected to reduce friction between the outer layer 378 and inner layer 380. This permits the inner layer 380 to move proximally with a retrieval device while the outer layer remains stationary. Again, as discussed above, the construction of the mesh permits compression and expansion of the mesh layer to permit movement of the inner layer while the outer layer remains affixed when engaged against the vessel wall. In certain variations, the cover is heat set so that the inner layer has cushioning and the ability to deflect to assist in movement of the inner layer. Fig. 5C also illustrates a cover 350 having a tapered design.

[0091] Figs. 6D to 6L illustrate additional variations of cover construction to produce covers having more than two walls. For example, a mesh tube 372 is everted or drawn over a second end 376 in the direction 420. As shown in Fig. 6E this produces a dual layer cover having an open ends 422 and 424 and a folded end 426. The dual layer tube is then folded over again in the direction 420. This creates a cover construction with an exterior layer 378 and an interior layer 380 as well as a first intermediate layer 381 and a second intermediate layer 383. As shown in Fig. 6F, the cover can be set to assume the tapered shape having an opening at the

first end 374 that is flared with the ends of the mesh at the second end 372, which are ultimately affixed to a shaft, wire or other catheter device as described herein.

[0092] Fig. 6G illustrates another example of a cover construction. As shown, a first mesh tube 372 is placed coaxially with a second tube 372. The concentric tubes are then everted in direction 420 to produce a four layer cover. As shown in Fig. 6H, the cover can comprise an interior mesh layer 380, and exterior mesh layer 378 as well as any number of intermediate layers 381, 383 depending on the number of tubes that are initially used. The second end 372 of the cover 350 includes four unconnected ends of the mesh tubes that can be affixed to a shaft or tube as discussed herein, while the first end 374 of the cover 350 can be shape set to taper from the opening.

[0093] Figs. 6I to 6L illustrate another example of the construction of a multi-wall cover. As shown in Fig. 6I, a first end 374 of a mesh tube 372 is everted over and beyond a second end 376 in direction 420 to produce the configuration of Fig. 6J. Next, the first end 374 is everted or folded back in direction 420 to produce the configuration of Fig. 6K. Finally, the first end 374 is folded again in direction 420 so that the ends 374 and 376 are even to produce the cover configuration shown in Fig. 6K. Again, one end of the cover 350 can be set to form the tapered shape while the other respective end can be affixed to a catheter or shaft.

[0094] Although the covers of the present disclosure are presented without additional structures, it should be noted that these covers are coupled with a shaft or other member so that the cover can be advanced within the target anatomy to assist in removal of a device, structure, or debris from the site.

[0095] Figs. 7A to 7C show additional variations of covers 350. Fig. 7A illustrates a cover in which the cover wall as defined by the inner layer 380 and outer layer 378 is set in a shape that varies along a length of the cover. For example, the end adjacent to the cover opening 382 can be set to a bulbous shape. Such a configuration assists in maintaining separation of layers 378 and 380, which aids in re-entry of the retrieval device. Additional configurations of cover walls that vary in thickness are within the scope of this disclosure.

[0096] One of the benefits of using a cover 350 as described herein is that the cover reduces flow through the vessel when deployed so that the retrieval device can remove the obstruction without the full force of the flow of blood opposing the obstruction. Typically, conventional devices relied upon the use of an inflated balloon to obstruct flow. However, use of a cover eliminates the need for total occlusion of blood flow. Fig. 7B illustrates a further improvement on a cover 350 that aids in flow reduction. As shown, the cover 350 includes a dense region 386 and a relatively less dense region 384. This configuration permits greater

blood flow through the region 385 while region 386 reduces or prevents blood flow. Furthermore, the distal section of the cover is more flexible and conformable. Additional mesh layers can be added to any of the cover designs to alter flow characteristics or even provide reinforcement to the cover. Alternatively, or in combination, the braid density can be altered to adjust the porosity of the braid at different sections. Furthermore, additional braid layers can also be used to affect porosity of portions of the cover or even the entire cover. Deployment of a cover can reduce blood flow by 30% to 40%. Adding additional layers or coatings can additionally reduce flow.

[0097] Fig. 7C shows another variation of a cover 350 in which the mesh partially or totally is obscured using a polymeric coating 388 that reduces the permeability of the mesh design. Furthermore, drugs or other substances can be placed within the cover wall of any of the covers or can be deposited on the cover using the polymeric coatings. In some examples, the covers described herein can range from a length of 10 mm up to 50 mm. The OD at the opening of the cover can range from 7 mm and could range between 4 mm to 10 mm. Again, any range of dimensions is contemplated within the disclosure.

[0098] The covers described herein can further be stacked on a device. For example, two or more covers can be placed on a device to provide added protection.

[0099] The cover/reentry devices described herein can be constructed of any material currently used in vascular applications, including those discussed above. Furthermore, fabrication of the cover from a DFT material can provide additional benefits as the entire cover remains radiopaque and can be imaged non-invasively. Furthermore, the covers can be provided with any type of medicament or bioactive substance either in a polymer that coats the mesh or in a delivery agent within the mesh or between layers. Such substances include tpa, urokinase, IIb/IIIa inhibitors, and other clot disruptors or inhibitors.

[0100] Fig. 8 illustrates another variation of a retrieval device 400 including a distal capture portion 426 coupled to one or more leading wires in the form of a main bundle 402. The main bundle extends through a sheath 106 that includes a proximal capture portion 460. The configuration of the retrieval device 400 can incorporate the proximal and distal capture portions discussed herein as well as various other configurations discussed in the commonly assigned patent applications noted above.

[0101] An end 464 of the proximal capture portion 460 is affixed to a distal end of the sheath 106. However, as noted above, other variations are within the scope of the disclosure. The main bundle 402 can optionally terminate at a handle 442. As noted above, in certain variations, the main bundle is joined to a stiffer wire or stiffer bundle of wires. This allows

the device 400 to have a very flexible distal section with a relatively stiffer proximal section. The device 400 can have a proximal bundle 403 that comprises either the exposed wires or a covering/tube over the wires. In certain variations, the bundle or wire 402, 403 can be encapsulated with a coating. The device also includes a cover 300 adjacent to the retrieval device.

[0102] The proximal end of the sheath 106 includes a sheath handle 444. As discussed herein, axial movement of the bundle 402 or proximal bundle 403 (typically at the handle 442) results in movement 126, or translation of the bundle within the sheath 106. This action moves the distal capture portion 426 (as shown by arrows 126). In certain variations, the device 400 is loaded into a microcatheter (not shown but discussed above) that is delivered to the site of the obstruction and crosses the obstruction.

[0103] In some variations, the sheath hub 444 includes one or more locking hubs 446. Where actuation (either axial or rotational) of the locking hub 446 locks the main bundle 402 relative to the sheath handle 444 and sheath 106. It follows that such locking action also locks the distal capture portion 426 relative to the proximal capture portion 460. A variety of methods can be employed to increase a frictional interference between the locking hub 446 and the proximal bundle 403. As a result, when a physician determines a length of an obstruction, the physician can set a spacing between the capturing portions 426 460 by locking the proximal bundle 403 relative to the sheath hub 444. Accordingly, the proximal bundle 403 can include any type of incremental markings to allow the physician to readily determine a spacing of the capturing portions. As illustrated, the sheath hub 444 can include additional injection ports to deliver fluid or other substances through the sheath 106.

[0104] As noted above, the device 400 can be used with a micro-catheter. In those variations it is important that the device 400 is loaded without damaging the distal bundle 402, capture portions 426 460, and/or sheath 106. As a result, the device 400 can include an optional cover 486 that reduces the proximal capture portion 460 (and /or the distal capture portion 426) for loading within the microcatheter and/or sheath 106.

[0105] Another variation of the device 400 includes an insertion tool 480 slidably affixed to the sheath 480. Because variations of the device 400 can be extremely flexible, the insertion tool 480 can be used to provide column strength to the sheath 106, bundle 402 or other components as the device 400 is pushed into the microcatheter. The insertion tool comprises a rigid section 482 and a frictional coupler 484. The rigid section 282 has a column strength that supports the device 400 to prevent buckling. The frictional coupler 484 can be a flexible material that allows an operator to squeeze or grip the coupler 484 to create a temporary

frictional interface between the loading tool 480 and the device 400 (typically the sheath 106). Such an action allows axial advancement of the device 400 as the loading tool 480 is advanced into the microcatheter. Once the rigid section 482 is fully inserted into the microcatheter, the operator releases the frictional coupler 484 and can withdraw the loading tool 480 from the catheter without withdrawing the device 400. The insertion tool 480 can also include an optional loading tube 486 slidably coupled to the rigid section 482. When used, the cover 486 can withdraw the proximal and distal capturing portion 226 260 within the loading tube 486. The loading tube 486 then couples to a microcatheter allowing the capturing portions to advance therein as the rigid section 482 and frictional coupler 484 advance the device 400 relative to the loading tube 486.

[0106] Figs. 9A to 9C show cross sectional views taken along the line 9A-9A in Fig. 2A. As shown, the wire form construction described herein allows for a number of configurations depending on the particular application. For example, the individual wires 254 (as discussed herein) may themselves comprise a bundle of smaller wires or filaments. In addition, the wires can be selected from materials such as stainless steel, titanium, platinum, gold, iridium, tantalum, Nitinol, alloys, and/or polymeric strands. In addition, the wires used in a device may comprise a heterogeneous structure by using combinations of wires of different materials to produce a device having the particular desired properties. For example, one or more wires in the device may comprise a shape memory or superelastic alloy to impart predetermined shapes or resiliency to the device. In some variations, the mechanical properties of select wires can be altered. In such a case, the select wires can be treated to alter properties including: brittleness, ductility, elasticity, hardness, malleability, plasticity, strength, and toughness.

[0107] The device may include a number of radiopaque wires, such as gold and platinum for improved visibility under fluoroscopic imaging. In other words, any combination of materials may be incorporated into the device. In addition to the materials, the size of the wires may vary as needed. For example, the diameters of the wires may be the same or may vary as needed.

[0108] In addition, the individual wires may have cross-sectional shapes ranging from circular, oval, d-shaped, rectangular shape, etc. Fig. 9A illustrates one possible variation in which a number of circular wires 254 are included around another larger wire 256. Moreover, the device is not limited to having wires having the same cross-sectional shape or size. Instead, the device can have wires having different cross-sectional shapes. For example, as shown in Fig. 9B, one or more wires 256 can have a different cross-sectional shape or size

than a reminder of the wires 254. Clearly, any number of variations is within the scope of this disclosure. This construction can apply to the retrieval portion, capturing portion and/or the covering portion of the device.

[0109] To illustrate one such example, a device can have 8-12 wires made of .003" round superelastic material (e.g., Nitinol). The device may additionally have 2-4 wires made from .002" platinum for fluoroscopy. Of the 8-12 Nitinol wires, 1-4 of these wires can be made of a larger diameter or different cross-section to increase the overall strength of the device. Finally, a couple of polymer fibers can be added where the fibers have a desired surface property for clot adherence, etc. Such a combination of wires provides a composite device with properties not conventionally possible in view of other formation means (such as laser cutting or etching the shape from a tube or joining materials with welds, etc.). Clearly, any number of permutations is possible given the principles of the invention.

[0110] In another example, the device may be fabricated from wires formed from a polymeric material or composite blend of polymeric materials. The polymeric composite can be selected such that it is very floppy until it is exposed to either the body fluids and or some other delivered activator that causes the polymer to further polymerize or stiffen for strength. Various coatings could protect the polymer from further polymerizing before the device is properly placed. The coatings could provide a specific duration for placement (e.g., 5 minutes) after which the covering degrades or is activated with an agent (that doesn't affect the surrounding tissues) allowing the device to increase in stiffness so that it doesn't stretch as the thrombus is pulled out. For example, shape memory polymers would allow the device to increase in stiffness.

[0111] In another variation, one or more of the wires used in the device may comprise a Drawn Filled Tube (DFT) such as those provided by Fort Wayne Metals, Fort Wayne, Indiana. As shown in Fig. 9C, such a DFT wire 252 comprises a first material or shell 258 over a second material 260 having properties different from the outer shell. While a variety of materials can be used, one variation under the present devices includes a DFT wire having a superelastic (e.g., Nitinol) outer tube with a radiopaque material within the super-elastic outer shell. For example, the radiopaque material can include any commercially used radiopaque material, including but not limited to platinum, iridium, gold, tantalum, or similar alloy. One benefit of making a capturing portion from the DFT wire noted above, is that rather than having one or more markers over the capturing portion, the entire capturing portion can be fabricated from a super-elastic material while, at the same time, the super-elastic capturing portion is made radiopaque given the core of radiopaque material within the super-elastic

shell. Clearly, any composite DFT wire **252** can be incorporated into the system and capturing portions described herein.

[0112] Another aspect applicable to all variations of the devices is to configure the devices or portions thereof that engage the obstruction to improve adherence to the obstruction. One such mode includes the use of coatings that bond to certain clots (or other materials causing the obstruction.) For example, the wires may be coated with a hydrogel or adhesive that bonds to a thrombus. Accordingly, as the device secures about a clot, the combination of the additive and the mechanical structure of the device may improve the effectiveness of the device in removing the obstruction. Coatings may also be combined with the capturing portions or catheter to improve the ability of the device to encapsulate and remove the obstruction (e.g., a hydrophilic coating).

[0113] Such improvements may also be mechanical or structural. Any portion of the capturing portion can have hooks, fibers, or barbs that grip into the obstruction as the device surrounds the obstruction. The hooks, fibers, or barbs **370** can be incorporated into any portion of the device. However, it will be important that such features do not hinder the ability of the practitioner to remove the device from the body.

[0114] In addition to additives, the device can be coupled to an RF or other power source (such as **14** or **16** in Fig. 1), to allow current, ultrasound or RF energy to transmit through the device and induce clotting or cause additional coagulation of a clot or other the obstruction.

[0115] Figs. 10A to 10E illustrate additional variations of covers **300** for use as described above. For example, as show in Fig. 10A, a cover **300** can comprise a single wire, coil, or laser cut tube **350**. Alternatively, as shown in Fig. 10B, the cover **300** can comprises two or more **350**, **352** wires or coils. Fig. 10C shows a cover **300** comprising a coil **350** inside a mesh structure **354**. A variation of the device shown in Fig. 10C can include a compliant atraumatic mesh **354** that is radially supported by the coil (whether interior or exterior to the mesh). The coil **350** provides the outward force against the vessel. Fig. 10D illustrates a polymeric film or membrane **356** coupled to a coil **350**. The polymeric film **356** can be permeable to fluid flow or impermeable. Fig. 10E illustrates a dual layer braid construction having an inner braid **358** and an outer braid **360**. The braids can be constructed to have unique properties. For example, the inner braid **358** can be composed of fewer wires or larger diameter wires, such that it provides an expansion force against the vessel wall. The outer braid **360** can comprise a softer construction and increased compliance. Accordingly, it can be comprised of a number of smaller diameter wires having a denser pattern to provide increased surface area to protect the obstruction as it is removed from the body. Alternatively,

these two constructional elements (e.g., braids of varying diameters) can be combined into a single layer or even multiple layers for the cover.

[0116] Fig. 11A illustrates yet another variation of a device 100 having a retrieval structure 200 and cover 300 where the cover is simply fabricated from the same material as the retrieval structure so long as it functions as described herein. The variation can optionally include one or more barbs 370 to increase resistance against a vessel wall.

[0117] Fig. 11B and 11C illustrate a variation where the cover 300 comprises a balloon material. Fig. 11B illustrates the balloon cover 370 prior to deployment. Fig. 11C illustrates the balloon cover 370 once deployed.

[0118] The retrieval devices described herein can optionally comprise elongated stents 400 as shown in Figs. 12A to 12E. These stents 400 can include any number of features to better assist the stent 400 in becoming enmeshed into the obstruction. For example, Fig. 12A illustrates a variation of a stent 400 affixed to a shaft 412. As noted herein, the shaft 412 can include a lumen extending therethrough. Alternatively, the shaft 412 can include a solid member with the stent 400 affixed to a distal end thereof. The variation shown in Fig. 12A includes a stent where a distal end 414 that is "closed off" by intersecting elements or wires 402 403. Accordingly, any of the variations of the stents disclosed herein can include an open lumen type stent or a closed lumen type stent as shown in Fig. 12A. As noted herein, the wires forming the stent 400 can comprise a single wire that is wound from a first direction (e.g., from proximal to distal) and then wound back in a second direction (e.g., from distal to proximal).

[0119] Fig. 12A also illustrates a stent 400 comprised of twisted wires 402 or elements. For example, Fig. 12B shows a magnified view of the section 12B in Fig. 12A. As illustrated, the elements 402 403 are twisted to increase the surface area at the exterior perimeter of the stent 400. The twisting or spiraling of the elements 402 403 creates additional surface area to increase the ability of the stent 400 to capture debris, thrombus, foreign body, etc. as the stent is expanded against the debris. The twisting elements 402 403 can twist along the entire length of the stent 400 or along one or more portions of the stent. In certain variations, the twisting of the elements 402 403 is sufficiently loose such that as the stent expands into a clot or obstruction, the twisted pairs slightly separate to allow material to become trapped between the elements making up the pairs. The construction shown in Figs. 12A and 12B also provide an additional benefit to a retrieval stent. In the illustrated variation, the twisted or spiraling elements interlock with crossing elements to form intersections 405 that provided added radial expansive force. As shown, a first twisted element 407 passes in between elements 402 403 of

an intersecting element 409. When in an expanded state, the element on the interior of the intersection 405 (in this case element 403) provides an added outward radial force against the intersection 405. However, since the elements are not affixed but instead are slidable at the intersection 405, the force required to linearize and compress the stent 400 is reduced due to the fact that the intersections are not affixed but slidable over the adjacent elements. This reduced linearization force allows the stent to be compressed to a small diameter for positioning within a microcatheter but allow for a significant radial expansive force once removed from the microcatheter. This design allows for a reduction in radial force of the stent against the vessel wall when the stent is pulled and removed from the vessel. However, this design also provides a high degree of radial force due to the interweaving of elements when the stent is deployed in the vessel prior to withdrawal of the stent.

[0120] Figs. 12C to 12F illustrate another variation of types of stents 400 that have an irregular surface at an exterior of the stent 400 that is formed by an intersection of elements 402 403. The intersection or crossing of the elements forms a type of barb or knuckle 416 that creates an irregular surface on the exterior of the stent 400. Fig. 12C illustrates a variation of a stent 400 having a plurality of knuckles 52 that are radially spaced about an axis 390 of the stent 400. Fig. 12E shows another variation of a stent 400 with knuckles 416 aligned with an axis 390 of the stent 400 as shown in Fig. 12D. Although the figures show the axial and radial aligned knuckles 416 on separate devices, both types of knuckles 416 can be incorporated into a single stent structure. Varying the alignment of knuckles can permit increased radial force as the stent expands into the obstruction or increased flexibility as the stent navigates through tortuous anatomy.

[0121] Fig. 12G illustrates a proximal end of the stent structure 400 as shown, a plurality of elements 402 and 403 extend along the shaft 412 and diverge to form the fluid permeable closed proximal end of the stent structure 400. The elements 402 and 403 that extend along the shaft 412 can be covered by a sheath, tube, spiral cut tube, or any structure 418 that prevents separation of the elements 402 403. A variation of the stent structure 402 includes a construction where the elements 402 403 are not glued, welded, or have any similar type of joint in the distal portion 420 of the shaft 412. Instead, the joint 411 is located proximal to the distal section of the shaft 412 in an intermediate section 422. Because joints or other similar features reduce flexibility of the joined structure, positioning the joints 411 in a proximal area allows the the distal portion 420 of the shaft to remain flexible.

[0122] The methods described herein may also include treating the obstruction prior to attempting to remove the obstruction. Such a treatment can include applying a chemical or

pharmaceutical agent with the goal of making the occlusion shrink or to make it more rigid for easier removal. Such agents include, but are not limited to chemotherapy drugs, or solutions, a mild formalin, or aldehyde solution.

[0123] As for other details of the present invention, materials and manufacturing techniques may be employed as within the level of those with skill in the relevant art. The same may hold true with respect to method-based aspects of the invention in terms of additional acts that are commonly or logically employed. In addition, though the invention has been described in reference to several examples, optionally incorporating various features, the invention is not to be limited to that which is described or indicated as contemplated with respect to each variation of the invention.

[0124] Various changes may be made to the invention described and equivalents (whether recited herein or not included for the sake of some brevity) may be substituted without departing from the true spirit and scope of the invention. Also, any optional feature of the inventive variations may be set forth and claimed independently, or in combination with any one or more of the features described herein. Accordingly, the invention contemplates combinations of various aspects of the embodiments or combinations of the embodiments themselves, where possible. Reference to a singular item, includes the possibility that there are plural of the same items present. More specifically, as used herein and in the appended claims, the singular forms “a,” “and,” “said,” and “the” include plural references unless the context clearly dictates otherwise.

[0125] It is important to note that where possible, aspects of the various described embodiments, or the embodiments themselves can be combined. Where such combinations are intended to be within the scope of this disclosure.

CLAIMS

We claim

1. An interventional medical device for retrieving and securing an obstruction within a vessel lumen, the device comprising:
 - a shaft having a flexibility to navigate through tortuous anatomy, the shaft a distal portion and a proximal portion;
 - a capturing structure located at a distal portion of the shaft comprising a plurality of struts, the capturing structure having a reduced profile for positioning in or adjacent to the obstruction and an expanded profile, such that when expanded into the obstruction, the struts at least partially enmesh with the obstruction such that subsequent movement of the capturing structure permits dislocation of at least a portion of the obstruction from the lumen;
 - an eversible cover having a fixed section affixed relative to a proximal end of the capturing structure, a free section extending in a proximal direction from the fixed section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable, the eversible cover being axially compliant such that when the shaft is moved proximally within the lumen, the eversible cover everts over the capturing structure allowing for the free section of the cover to be distal to the fixed end of the capturing portion.
2. The medical device of claim 1, where the eversible cover, capturing structure, and shaft are a unitary structure.
3. The medical device of claim 1, where each wire located at an end of the free section loops back to the cover causing the wires at the end of the free section to be continuous.
4. The medical device of claim 1, where at least a portion of the cover wall adjacent to the distal end has a set shape that is everted upon expansion.
5. The medical device of claim 1, further comprising a catheter body, where in a delivery configuration, the shaft, capturing structure and eversible cover are located within the catheter body and where the capturing structure is advanceable in and out of a distal end of the catheter body.

6. The medical device of claim 1, where the eversible cover comprises a plurality of layers forming the cover wall.
7. The medical device of claim 1, where the free section of the eversible cover partially restricts about the shaft without being attached to the shaft.
8. The medical device of claim 1, where a portion of the cover wall extends distally beyond the fixed section when the eversible cover is expanded.
9. The medical device of claim 1, where the fixed section of the eversible cover comprises a pre-set shape to reduce a force required to evert the evertable cover.
10. The medical device of claim 1, where the cover wall is layered in an undulating pattern upon deployment.
11. The medical device of claim 1, where the capturing structure comprises an elongated stent structure.
12. The medical device of claim 1, where the capturing structure comprises a device selected from a group consisting of a filter, an artherectomy device, a rotational cutter, an aspiration device, stent based retrievers and retrieval baskets.
13. The medical device of claim 1, where the cover is self expanding.
14. The medical device of claim 1, where a portion of the cover at or adjacent to the distal opening comprises a bulbous shape.
15. The medical device of claim 1, where the cover comprises a first porous section having a first porosity and at least a second porous section having a second porosity, where the first and second porosity are different such that the ability of fluid to flow through the first porous section and second porous section differs.
16. The medical device of claim 15, where the first porous section comprises a first braid density and the second porous section comprises a second braid density.
17. The medical device of claim 15, where the first porous section comprises an additional braid layer.

18. The medical device of claim 15, where the first porous section prevents fluid from flowing therethrough.
19. The medical device of claim 15, where the first porous section is distal to the second porous section and where the first porosity is greater than the second porosity.
20. The medical device of claim 15, where the first porous section comprises a circumferential area of the cover.
21. The medical device of claim 1, further comprising at least one polymeric layer on or adjacent to a region of the cover.
22. The medical device of claim 21, further comprising at least one medicament on or in the polymeric layer.
23. The medical device of claim 1, further comprising at least one radiopaque marker on a distal end of the shaft.
24. The medical device of claim 1, where the cover comprises a mesh material
25. The medical device of claim 24, where the mesh material comprises a single continuous wire.
26. The medical device of claim 24, where at least a portion of the mesh material is fabricated from a drawn filled tube material.
27. The medical device of claim 24, where at least a portion of the mesh material is fabricated from a radiopaque material.
28. The medical device of claim 1, where the eversible cover comprises at least one wire coiled such that turns of the coil form the cover wall.
29. The medical device of claim 28, where the cover further comprises a braid adjacent to the coil.
30. The medical device of claim 28, where the cover further comprises a film coupled to the coil.

31. The medical device of claim 1, where the eversible cover comprises at least one barb or knuckle at an exterior surface of the cover wall.
32. The medical device of claim 1, where the eversible cover comprises an inner braided layer and an outer braided layer, where the outer braided layer is relatively more compliant than the inner braided layer.
33. A method of securing an obstruction within a vessel, the method comprising:
positioning a catheter within a vessel;
advancing a shaft having a retrieval device affixed thereto out of the catheter;
advancing an eversible cover out of the catheter such that a fixed end of the eversible cover is adjacent to a proximal end of the retrieval device and a free end of the eversible cover is moveable relative to the shaft and retrieval device;
expanding at least a portion of the eversible cover against a portion of a wall of the vessel;
manipulating the retrieval device to become at least partially enmeshed with the obstruction; and
proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.
34. The method of claim 33, further comprising further withdrawing the shaft from the vessel such that during withdrawal the eversible cover forms a protective barrier over the obstruction to lessen shearing forces caused by the vessel and reduce dislodging portions of the obstruction from the retrieval device.
35. A method of preparing a retrieval device comprising:
providing a retrieval device *having been previously removed from a body of a patient* where the retrieval device includes a protective cover where a fixed end of the protective cover is affixed adjacent to a proximal end of the retrieval device and where a free end is located distally to the fixed end covering the retrieval device and is moveable relative to the second end;
reversing the protective cover by moving the free end proximally of the fixed while the fixed end remains affixed adjacent to the proximal end of the retrieval device;

inserting the retrieval device and cover into a catheter where the free end of the cover is proximal to the fixed end of the cover and retrieval device such that upon deployment from the catheter, the free end of the cover deploys proximally to the fixed end of the cover.

36. A method of securing an obstruction within a vessel, the method comprising:
- advancing a shaft having a retrieval device affixed thereto to the obstruction;
 - advancing a protective device over the shaft, the protective device comprising a sheath having an eversible cover, where a fixed end of the eversible cover is affixed to a distal portion of the sheath and a free end of the eversible cover is located proximal to the fixed end;
 - positioning the fixed end of the eversible cover adjacent to the retrieval device and expanding at least a portion of the eversible cover against a portion of a wall of the vessel;
 - proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.
37. A medical device retrieval system for securing an obstruction within a vessel lumen and for use with a catheter configured to be navigated through the vasculature, the device comprising:
- an elongated stent comprising a plurality of struts, the stent being collapsible for positioning in the catheter during delivery and having an expanded profile such that when expanded the struts are configured to engage the obstruction;
 - a shaft fixedly attached to the elongated stent and having a flexibility to navigate through tortuous anatomy;
 - a fluid permeable cover having a distal end coupled to a proximal end of the elongated stent a cover wall defining a cavity and extending along the shaft, and a proximal end being moveable relative to the shaft, where the fluid permeable cover is collapsible for positioning in the catheter during delivery and is expandable upon deployment from the catheter such that a portion of the fluid permeable cover is expandable;
 - where the fluid permeable cover is axially pliable such that when the device is deployed in the vessel and frictional forces are applied against the fluid permeable cover, proximal movement of the shaft and elongated stent cause inversion of the fluid

permeable cover wall such that the fluid permeable cover wall everts over the elongated stent.

38. An interventional medical device for use with a catheter configured for delivery through vasculature and for securing an obstruction within a vessel lumen, the device comprising:
- a shaft having a flexibility to navigate through tortuous anatomy, the shaft having a distal portion and a proximal portion;

- a capturing device comprising a sidewall, the capturing device fixedly located at a distal portion of the shaft and having a reduced profile for positioning in the catheter and an expanded profile, such that upon deployment from the catheter, the capturing device expands to force a portion of the sidewall into the obstruction to at least partially attach to the obstruction;

- a cover having a distal end coupled adjacent to a proximal end of the capturing structure, a proximal end and a cover wall extending therebetween, where the proximal end of the cover is slidable relative to the distal end, where the cover is expandable such that when located in the catheter the cover is in a reduced delivery state and upon advancement from the catheter the cover expands with the proximal end located proximally of the distal end, where the cover wall is compliant such that when deployed from the catheter and the shaft is pulled in a proximal direction frictional forces between the vessel and the cover wall or proximal end cause the cover to invert as the cover wall inverts over the capturing device to surround the capturing device.

39. An interventional medical device for securing a retrieval device having one or more obstructions located therein for removal from a body, the medical device comprising:

- a sheath having a flexibility to navigate through tortuous anatomy, the sheath a distal portion and a proximal portion and a lumen extending therethrough;

- an eversible cover having a fixed section affixed to the distal portion of the sheath, a free section extending in a proximal direction from the fixed section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable, the eversible cover being axially compliant such that when the retrieval device is positioned through the sheath lumen and moved in a proximal direction against the eversible cover, the eversible cover everts over the retrieval device allowing for the free section of the cover to be distal to the retrieval device.

40. A stent retrieval device for expanding against one or more occlusive bodies in a vasculature, the stent retrieval device comprising:
- an elongate shaft having a flexibility to navigate through tortuous anatomy, the elongate shaft having a distal portion and a proximal portion;
 - a plurality of filaments that diverge from the distal portion of the elongate shaft to form an expandable elongated stent body having an open distal end and a fluid permeable closed proximal end and a cavity therebetween, where divergence of the filaments at the distal portion of the elongate shaft forms the fluid permeable closed proximal end;
 - where the plurality of filaments extending along the shaft are free of any connection joints in the distal portion to permit increased flexibility of the distal portion as it navigates through tortuous anatomy; and
 - one or more connection joints proximal to the distal portion where the connection joints secure the plurality of filaments to the shaft.
41. The stent retrieval device of claim 40, wherein at least one of the plurality of filaments comprise at least two wires twisted together, the elongated stent body further comprising at least one intersection of filaments, where the wires of each filament are interwoven to provide increased outward radial strength of the elongated stent body and such that the wires slide relative to each other as the elongated stent body expands or compresses in diameter to reduce a force required to linearize the elongated stent body.
42. The stent retrieval device of claim 40, where the exterior surface of the elongated stent body comprises an irregular surface formed by intersection of filaments.
43. The stent retrieval device of claim 42, where the intersection of filaments comprises a barb or knuckle and where a plurality of barbs or knuckles are radially spaced about the elongated stent body.
44. The stent retrieval device of claim 42, where the intersection of filaments comprises a barb or knuckle and where a plurality of barbs or knuckles are aligned with an axis of the elongated stent body.
45. The stent retrieval device of claim 42, where the elongated stent body comprises a plurality of barbs or knuckles radially spaced about the elongated stent body and a plurality of barbs or knuckles axially aligned with an axis of the elongated stent body.

46. The stent retrieval device of claim 40, where at least one filament comprises a drawn filled tube material.
47. The stent retrieval device of claim 40, where at least one filament comprises at least one wire comprised of a first material and at least a second wire comprised of at least a second material different from the first material.
48. The stent retrieval device of claim 40, where at least one filament comprises at least one wire comprised of a first material and at least a second filament having at least one wire comprised of at least a second material different from the first material.