


MOTOR

This Sheet Has Been Replaced  


BACKGROUND OF THE INVENTION

Field of the Invention

5           The present invention relates to a motor that can be constructed in microstructure with enhanced workability.

Related Background Art

10           Among conventional compact motors, there is, for example, a compact, cylindrical step motor as shown in Fig. 13. A stator coil 105 is concentrically wound on each of bobbins 101, and each bobbin 101 is fixed as being axially sandwiched between two stator yokes 106. The stator yoke 106 have stator teeth 106a and stator  
15           teeth 106b arranged in alternating fashion along the circumferential direction of the bore surface of bobbin 101. The stator yokes 106 integral with the stator teeth 106a or 106b are fixed to cases 103, thus composing stators 102.

20           Flange 115 and bearing 108 are fixed to one of two sets of cases 103 and another bearing 108 is fixed to the other case 103. Rotor 109 is comprised of a rotor magnet 111 fixed to rotor shaft 110, and the rotor magnet 111 and the stator yoke 106 of stator 102 form  
25           radial gap portions. The rotor shaft 110 is rotatably supported between the two bearings 108.

The conventional compact step motor described

THIS SHEET HAS BEEN REPLACED



above, however, had the drawback that the outside dimensions of motor were large, because the cases 103, bobbins 101, stator coils 105, stator yokes 106, etc. were concentrically located outside the rotor. In addition, it has another drawback that the output of motor is not high, because the magnetic flux generated by energizing the stator coils 105 mainly passes end faces 106a1 of the stator teeth 106a and end faces 106b1 of the stator teeth 106b, as shown in Fig. 14, and does not effectively act on the rotor magnet 111.

The applicant proposed a motor solving such problems in United States Patent Application No. 08/831,863 (filed April 2, 1997).

This proposed motor is constructed in such structure that the rotor of permanent magnet partitioned and magnetized in the alternately different poles at equal intervals in the circumferential direction is formed in a cylindrical shape, that a first coil, the rotor, and a second coil are located in order along the axial direction of the rotor, that the first outside pole and first inside pole excited by the first coil are opposed to outside and inside peripheral surfaces of the rotor, and that the second outside pole and second inside pole excited by the second coil are opposed to the outside and inside peripheral surfaces of the rotor.

The motor of this structure was able to provide



high output and had small outside dimensions of motor,  
but the radial dimension of the first inside pole and  
second inside pole which comprise a pair of magnetic  
tooth with separated tip ends was also small. When  
5 these pole teeth were processed by press working, there  
were problems of strength of mold, emission of chip,  
and so on. Therefore, the processing was not easy and  
it was rather difficult to achieve high strength of the  
teeth. There were desires for readily processing the  
10 first outside pole and second outside pole, too.

#### SUMMARY OF THE INVENTION


An object of the present invention is to overcome  
the above drawbacks and to provide a motor that can be  
15 constructed in microstructure wherein the inside poles  
are formed in a shape with high workability.

Another object of the present invention is to  
provide a motor that can be constructed in  
microstructure wherein processing of the outside poles  
20 is easy.

Other objects of the present invention will become  
more apparent by specific embodiments which will be  
described below.

#### 25 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an exploded, perspective view of a motor  
of the first embodiment according to the present





invention;

Fig. 2 is a cross-sectional view of the assembled state of the motor shown in Fig. 1;

5 Figs. 3A, 3B, 3C, 3D, 3E, 3F, 3G, and 3H are drawings for explaining the rotor rotation operation of the motor shown in Fig. 2;

Fig. 4 is an enlarged view of the yoke as an inside pole in the motor shown in Fig. 2;

10 Fig. 5 is a drawing to show another example of the yoke as an inside pole in the motor shown in Fig. 2;

Fig. 6 is a cross-sectional view of the yoke shown in Fig. 5;

15 Fig. 7 is an exploded, perspective view of a motor of the second embodiment according to the present invention;

Fig. 8 is a cross-sectional view of the assembled state of the motor shown in Fig. 7;

20 Figs. 9A, 9B, 9C, 9D, 9E, 9F, 9G, and 9H are drawings for explaining the rotor rotation operation of the motor shown in Fig. 7;

Fig. 10 is a plan view of the motor shown in Fig. 7;

Fig. 11 is an exploded, perspective view to show another example of the motor shown in Fig. 7;

25 Fig. 12 is a plan view of the assembled state of the motor shown in Fig. 11;

Fig. 13 is a cross-sectional view to show a



conventional step motor; and

Fig. 14 is an explanatory drawing to show the magnetic flux in the conventional step motor shown in Fig. 13.

5

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments of the present invention will be described by reference to the drawings.

(Embodiment 1)

10            Fig. 1 to Fig. 4 are drawings to show Embodiment 1. Reference numeral 1 designates a permanent magnet of a cylindrical shape, which is composed of a first magnetic layer having four portions 1a, 1b, 1c, 1d  
15            obtained by quartering the circumference and alternately magnetized in the S and N poles, and a second magnetic layer having four portions 1e, 1f, 1g, 1h obtained similarly by quartering the circumference and alternately magnetized in the S and N poles. The  
20            first magnetic layer and the second magnetic layer are magnetized in respective phases shifted by 45° from each other.

25            The outside peripheral surfaces of the portions 1a, 1c of the first magnetic layer and the portions 1e, 1g of the second magnetic layer are magnetized in the S pole and the inside peripheral surfaces thereof in the N pole; the outside peripheral surfaces of the portions 1b, 1d of the first magnetic layer and the portions 1f,




1h of the second magnetic layer are magnetized in the N pole and the inside peripheral surfaces thereof in the S pole.

Numeral 2 denotes a rotational shaft, to which the permanent magnet 1 is fixed. The rotational shaft 2 and permanent magnet 1 compose a rotor. Numerals 3, 4 are coils which are located so as to be concentric with the permanent magnet 1 and to sandwich the permanent magnet 1 in the axial direction. Numeral 5 represents a first yoke made of a soft magnetic material, which has a portion 5d set in a bore portion 3a of the coil 3 and a pole section opposed to a bore portion of the first magnetic layer of the permanent magnet 1.

In the pole section, as shown in Fig. 4, portions 5b, 5c with a large outside diameter and portions 5e, 5f with a small outside diameter are alternately formed in the cross section taken in the direction perpendicular to the axis. The portions 5b, 5c are formed in the same phase, relative to the poles of the first magnetic layer. Namely, the portion 5b and the portion 5c are located as shifted by 180° from each other. A portion 2a of the rotational shaft 2 is fitted in a hole 5a of the first yoke so as to be rotatable.

Numeral 6 denotes a second yoke made of a soft magnetic material, which has a portion 6d set in a bore portion 4a of the coil 4 and a pole section opposed to





a bore portion of the second magnetic layer of the permanent magnet 1. In the pole section, portions 6b, 6c with a large outside diameter and portions 6e, 6f with a small outside diameter are alternately formed, as in the first yoke 5. The portions 6b, 6c are formed in the same phase, relative to the poles of the second magnetic layer. Namely, the portion 6b and the portion 6c are located as shifted by 180° from each other. A portion 2b of the rotational shaft 2 is fitted in a hole 6a of the second yoke so as to be rotatable. The large diameter portions 5b, 5c of the first yoke 5 and the large diameter portions 6b, 6c of the second yoke 6 are located in the same phase, i.e., opposed to each other with respect to the axial direction.

Numeral 8 stands for a third yoke made of a soft magnetic material, in which teeth 8a, 8b are formed at positions where they sandwich the portions 5b, 5c of the first yoke 5 and the first magnetic layer of the permanent magnet 1. Numeral 9 stands for a fourth outer yoke made of a soft magnetic material, in which teeth 9a, 9b are formed at positions where they sandwich the portions 6b, 6c of the second yoke 6 and the second magnetic layer of the permanent magnet 1.

Numeral 10 designates a coupling ring made of a non-magnetic material, which has grooves 10a, 10b engaged with the teeth 8a, 8b of the third yoke 8 and grooves 10c, 10d engaged with the teeth 9a, 9b of the



fourth yoke. The third yoke 8 and the fourth yoke 9 are fixed to the coupling ring 10 by a conventional method, for example, by bonding or the like. The third yoke 8 and the fourth yoke 9 are fixed with a  
5 predetermined space through portions 10e, 10f of the coupling ring 10. The teeth 8a, 8b of the third yoke 8 are so arranged as to face the teeth 9a, 9b of the fourth yoke 9.

The third yoke 8 is so arranged, as shown in Fig. 2, that one end thereof is connected to the first yoke  
10 5 and covers the outside-diameter portion of coil 3 and that the teeth 8a, 8b at the other end are opposed with a predetermined gap to the outside peripheral portion of the permanent magnet 1. The fourth yoke 9 is so  
15 arranged, as shown in Fig. 2, that one end thereof is connected to the second yoke 6 and covers the outside-diameter portion of coil 4 and that the teeth 9a, 9b at the other end are opposed with a predetermined gap to the outside peripheral portion of the permanent magnet  
20 1.


Fig. 2 is a cross-sectional view of the assembled state, Figs. 3A, 3B, 3C, and 3D are cross-sectional views along A-A in Fig. 2, and Figs. 3E, 3F, 3G, and 3H are cross-sectional views along B-B in Fig. 2. Figs.  
25 3A and 3E are cross-sectional views at a moment, Figs. 3B and 3F those at another moment, Figs. 3C and 3G those at still another moment, and Figs. 3D and 3H



those at yet still another moment. When from the state of Figs. 3A and 3E the coil 3 and coil 4 are energized to excite the pole portions 5b, 5c, 5e, 5f of the first yoke 5 to the S pole, the portions 8a, 8b of the third yoke opposed to the portions 5b, 5c to the N pole, the pole portions 6b, 6c, 6e, 6f of the second yoke 6 to the S pole, and the portions 9a, 9b of the fourth yoke 9 opposed to the portions 6b, 6c to the N pole, the permanent magnet 1 rotates 45° counterclockwise so as to go into the state shown in Figs. 3B and 3F.

Since the small-diameter portions 5e, 5f in the pole section of the first yoke 5 are more distant from the inside peripheral surface of the first magnetic layer than the portions 5b, 5c, the pole occurring in the small-diameter portions 5e, 5f little acts on the first magnetic layer and thus little affects the driving force generated. Accordingly, the first yoke 5 can function in the same manner as in the case of applicant's prior application No. 08/831,863 (filed April 2, 1997) which comprises inner magnetic pole with a pair of separated magnetic teeth. The shape of the first yoke 5 forms no chip when produced by press working. Therefore, no consideration is necessary for emission of chip and the production is thus easy.

Since the portions 5b, 5e, 5c, 5f are joined throughout the entire circumference, the strength is high and there is no possibility of deformation during assembly.



The above is also the case for the second yoke 6. Since the small-diameter portions 6e, 6f in the pole section of the second yoke 6 are more distant from the inside peripheral surface of the second magnetic layer than the portions 6b, 6c, the pole occurring in the small-diameter portions 6e, 6f little acts on the second magnetic layer and thus little affects the driving force generated. Accordingly, the second yoke 6 can function in the same manner as in the case of above-mentioned application No. 08/831,863. The shape of the second yoke 6 forms no chip when produced by press working. Therefore, no consideration is necessary for emission of chip and the production is thus easy. Since the portions 6b, 6e, 6c, 6f are joined throughout the entire circumference, the strength is high and there is no possibility of deformation during assembly.

Then the power supply to the coil 3 is inverted to excite the pole portions 5b, 5c, 5e, 5f of the first yoke 5 to the N pole, the portions 8a, 8b of the third yoke opposed to the portions 5b, 5c to the S pole, the pole portions 6b, 6c, 6e, 6f of the second yoke 6 to the S pole, and the portions 9a, 9b of the fourth yoke opposed to the portions 6b, 6c to the N pole, whereupon the permanent magnet 1 is rotated further 45° counterclockwise to go into the state shown in Figs. 3C and 3G.

This Sheet Has Been Replaced  


Then the power supply to the coil 4 is inverted to excite the pole portions 6b, 6c, 6e, 6f of the second yoke 6 to the N pole and the portions 9a, 9b of the fourth yoke opposed to the 6b, 6c to the S pole,  
5 whereupon the permanent magnet 1 is rotated further 45° counterclockwise. By successively switching the directions of power supply to the coil 3 and coil 4 in this manner, the rotor composed of the permanent magnet 1 and rotational shaft 2 rotates to the positions  
10 according to the phases of power supply.

Described below is the reason why the step motor of the above structure is optimum for microminiaturization of motor.

Features of the fundamental structure of the step  
15 motor are as follows.


First, the magnet is formed in the hollow cylinder shape.

Second, the outside peripheral surface of the magnet is divided circumferentially into n portions and  
20 the n portions are magnetized alternately in the different poles.

Third, the first coil, the magnet, and the second coil are located in order in the axial direction of the magnet.

25 Fourth, the outside pole and the inside pole of the first and second stators excited by the first and second coils are opposed to the outside peripheral

THIS SHEET HAS BEEN  
REPLACED



surface and to the inside peripheral surface,  
respectively, of the magnet.

Accordingly, a necessary diameter of this step  
motor is a size enough to oppose the poles of the  
5 stators to the diameter of the magnet; and a necessary  
axial length of the step motor is the sum of the length  
of the magnet and the lengths of the first and second  
coils. Therefore, the dimensions of the step motor are  
determined by the diameters and lengths of the magnet  
10 and coils, and the step motor can be microminiaturized  
by decreasing the diameters and lengths of the magnet  
and coils to very small values.

When the diameters and lengths of the magnet and  
coils are made very small, it becomes difficult to  
15 maintain the output accuracy of the step motor. This  
problem of the output accuracy of the step motor is  
solved by the simple structure wherein the magnet is  
formed in the hollow cylinder shape and the outside  
pole and inside pole of the first and second stators  
20 are opposed to the outside peripheral surface and to  
the inside peripheral surface of the magnet formed in  
the hollow cylinder shape.

Next described is another example in which the  
shape of the first and second yokes is modified.


25 Fig. 5 and Fig. 6 are drawings to show another  
example of the first embodiment.

Fig. 5 is a perspective view of the first yoke, in



which the pole section opposed to the inside peripheral surface of the first magnetic layer is formed in the shape of an ellipse 5g ( $A > B$  where A is the major axis and B is the minor axis) in the cross section perpendicular to the axis. Fig. 6 is a lateral, cross-sectional view of the motor in which the first yoke 5 is incorporated. The first yoke 5 is located so that the major axis A is directed toward the positions opposed to the teeth 8a, 8b of the third yoke 8. Similarly, though not illustrated, the second yoke is also formed in the elliptic shape with the major axis A and the minor axis B ( $A > B$ ) at least in the outside peripheral surface of the pole section, and the major axis is arranged so as to be directed toward the positions opposed to the teeth 9a, 9b of the fourth yoke.

The outside peripheral surfaces of the first yoke 5 and second yoke 6 in the minor-axis direction are apart from the circumferential surfaces of the first magnetic layer and the second magnetic layer, respectively, and thus they do not negatively affect the output of motor, similar to the portions 5e, 5f, 6e, 6f in the first example. Since the pole section of the first yoke and second yoke is continuous throughout the entire circumference, the strength is high and no chip is produced during press working, thus achieving high workability.



In the first embodiment described above the first to fourth yokes 5, 6, 8, 9 were separate members, but they may be formed in such structure that the first and third yokes 5, 8 are integrated into a first stator yoke and that the second and fourth yokes 6, 9 are integrated into a second stator yoke.

The first magnet 1 was constructed in the double layer structure consisting of the first magnetic layer and the second magnetic layer the phases of which were shifted by  $180/n$  degrees ( $n$  is the number of magnetic poles of the permanent magnet), i.e.,  $45^\circ$ , but, without having to be limited to this, the present invention can also be applied to the single layer structure of a magnetic layer in the permanent magnet 1 wherein the phase of the second and fourth yokes 6, 9 is shifted by  $180/n$  degrees, i.e.,  $45^\circ$ , relative to that of the first and third yokes 5, 8.

The second embodiment of the present invention will be described below.


(Embodiment 2)

Fig. 7 to Fig. 10 are drawings to show Embodiment 2 of the present invention. In Fig. 7 to Fig. 10, reference numeral 1 designates a magnet ring of a cylindrical shape made of a permanent magnet, which is composed of a first magnetic layer having portions 1a, 1b, 1c, 1d obtained by dividing the circumference into  $n$  (4 in the present embodiment) and alternately



magnetized in the S and N poles, and a second magnetic layer having portions 1e, 1f, 1g, 1h obtained similarly by dividing the circumference into 4 and alternately magnetized in the S and N poles. The phases of the first magnetic layer and the second magnetic layer are shifted by  $180/n$  degrees, i.e.,  $45^\circ$  from each other. In the present embodiment, the outside peripheral surfaces of the portions 1a, 1c of the first magnetic layer and the portions 1e, 1g of the second magnetic layer are magnetized in the S pole and the inside peripheral surfaces thereof in the N pole; the outside peripheral surfaces of the portions 1b, 1d of the first magnetic layer and the portions 1f, 1h of the second magnetic layer are magnetized in the N pole and the inside peripheral surfaces thereof in the S pole.

Numerals 2 denotes a rotational shaft to which the permanent magnet 1 is fixed. The rotational shaft 2 and permanent magnet 1 compose a rotor. Numerals 3, 4 are coils which are located so as to be concentric with the permanent magnet 1 and to sandwich the permanent magnet 1 in the axial direction. Numeral 5 represents a first yoke made of a soft magnetic material, which has a portion 5d set in the bore portion 3a of coil 3 and teeth 5b, 5c opposed to the bore portion of the first magnetic layer of the permanent magnet 1. The teeth 5b, 5c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the



same phase, relative to the poles of the first magnetic layer. A portion 2a of the rotational shaft 2 is fitted in a hole 5a of the first yoke so as to be rotatable.

5            Numeral 6 stands for a second yoke made of a soft magnetic material, which has a portion 6d set in the bore portion 4a of coil 4, and teeth 6b, 6c opposed to the bore portion of the second magnetic layer of the permanent magnet 1. The teeth 6b, 6c are formed as  
10 shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the same phase, relative to the poles of the second magnetic layer. A portion 2b of the rotational shaft 2 is fitted in a hole 6a of the second yoke 6 so as to be rotatable. The teeth 5b, 5c  
15 of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are located in the same phase, i.e., at positions where they are opposed to each other with respect to the axial direction.

            Numeral 7 denotes a third yoke made of a soft  
20 magnetic material. The third yoke is of a barrel shape, which is constructed so as to cover the outside peripheral surfaces of the coil 3, coil 4, and permanent magnet 1. The third yoke 7 is connected at the portion 7e to the portion 5h of the first yoke 5  
25 and at the portion 7f to the portion 6h of the second yoke 6. The third yoke 7 has portions 7a, 7b at positions opposite to the teeth 5b, 5c of the first



yoke 5 and the teeth 6b, 6c of the second yoke 6 on  
either side of the permanent magnet 1 and holes 7c, 7d  
formed in the other portions than the portions 7a, 7b.  
Since the teeth 5b, 5c of the first yoke 5 and the  
5 teeth 6b, 6c of the second yoke 6 are in the same  
phase, the pole portions 7a, 7b of the third yoke 7 to  
be faced to those teeth have the simple shape  
consisting of continuous parts of the pole portions 7a,  
7b as shown in Fig. 7, and the production thereof by  
10 press or the like is thus easy. In the pole teeth 7a,  
7b forming the continuous parts of the third yoke 7,  
holes 7g, 7h are formed at positions opposite to each  
other near the border between the first magnetic layer  
and the second magnetic layer of the magnet ring 1.

15 This makes the reluctance high near the third yoke  
7, so that the magnetic flux generated from the coil 3  
becomes reluctant to act on the coil 4, the second  
magnetic layer of the magnet ring 1, the second yoke 6,  
and so on and so that the magnetic flux generated from  
20 the coil 4 becomes reluctant to act on the coil 3, the  
first magnetic layer of the magnet ring 1, the first  
yoke 5, and so on. Thus, the rotor becomes smoothly  
rotatable according to the operation described below,  
thereby increasing the output of motor.

25 Fig. 8 is a cross-sectional view of the assembled  
state, Figs. 9A, 9B, 9C, and 9D are cross-sectional  
views along A-A in Fig. 8, and Figs. 9E, 9F, 9G, and 9H



are cross-sectional views along B-B in Fig. 8. Figs. 9A and 9E are cross-sectional views at a moment, Figs. 9B and 9F those at another moment, Figs. 9C and 9G those at still another moment, and Figs. 9D and 9H those at yet still another moment.

When from the state of Figs. 9A and 9E the coil 3 and coil 4 are energized to excite the teeth 5b, 5c of the first yoke 5 to the S pole, the portions 7a, 7b of the third yoke 7 opposed to the teeth 5b, 5c to the N pole, the teeth 6b, 6c of the second yoke 6 to the S pole, and the portions 7a, 7b of the third yoke 7 opposed to the teeth 6b, 6c to the N pole, the magnet ring 1 is rotated 45° leftward (counterclockwise) to go into the state shown in Figs. 9B and 9F.

Then the power supply to the coil 3 is inverted to excite the teeth 5b, 5c of the first yoke 5 to the N pole, the portions 7a, 7b of the third yoke 7 opposed to the teeth 5b, 5c to the S pole, the teeth 6b, 6c of the second yoke 6 to the S pole, and the portions 7a, 7b of the third yoke 7 opposed to the teeth 6b, 6c to the N pole, whereupon the magnet ring 1 is rotated further 45° counterclockwise to go into the state shown in Figs. 9C and 9G.

Then the power supply to the coil 4 is inverted to excite the teeth 6b, 6c of the second yoke 6 to the N pole and the portions 7a, 7b of the third yoke 7 opposed to the teeth 6b, 6c to the S pole, whereupon



the permanent magnet 1 is rotated further  $45^\circ$  counterclockwise. By successively switching the directions of power supply to the coil 3 and coil 4 in this way, the rotor comprised of the magnet ring 1 and rotational shaft 2 rotates to the positions according to the phases of power supply. Fig. 10 is a top plan view of this motor.

Next described is another example in which the shape of the third yoke is modified.

Fig. 11 and Fig. 12 are drawings to show another example of the second embodiment.

In Fig. 11 and Fig. 12, numeral 1 designates a magnet ring of a cylindrical shape made from a permanent magnet, which is composed of a first magnetic layer having portions 1a, 1b, 1c, 1d obtained by dividing the circumference into  $n$  (4 in this example) and alternately magnetized in the S and N poles, and a second magnetic layer having portions 1e, 1f, 1g, 1h obtained similarly by dividing the circumference into 4 and alternately magnetized in the S and N poles. The phases of the first magnetic layer and second magnetic layer are shifted by  $180/n$  degrees, i.e.,  $45^\circ$  from each other. In the present example, the outside peripheral surfaces of the portions 1a, 1c of the first magnetic layer and the portions 1e, 1g of the second magnetic layer are magnetized in the S pole and the inside peripheral surfaces thereof in the N pole; the outside



peripheral surfaces of the portions 1b, 1d of the first magnetic layer and the portions 1f, 1h of the second magnetic layer are magnetized in the N pole and the inside peripheral surfaces thereof in the S pole.


5            Numeral 2 represents a rotational shaft to which the permanent magnet 1 is fixed. The rotational shaft 2 and permanent magnet 1 compose the claimed rotor. Numerals 3, 4 are coils which are located so as to be concentric with the permanent magnet 1 and to sandwich  
10 the permanent magnet 1 in the axial direction. Numeral 5 designates a first yoke made of a soft magnetic material, which has a portion 5d set in the bore portion 3a of the coil 3 and teeth 5b, 5c opposed to the bore portion of the first magnetic layer of the  
15 permanent magnet 1. The teeth 5b, 5c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the same phase, relative to the poles of the first magnetic layer, and a portion 2a of the rotational shaft 2 is fitted in a hole 5a of the  
20 first yoke so as to be rotatable.

          Numeral 6 denotes a second yoke made of a soft magnetic material, which has a portion 6d set in the bore portion 4a of coil 4 and teeth 6b, 6c opposed to the bore portion of the second magnetic layer of the  
25 permanent magnet 1. The teeth 6b, 6c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the same phase, relative to the



poles of the second magnetic layer. A portion 2b of the rotational shaft 2 is fitted in a hole 6a of the second yoke 6 so as to be rotatable. The teeth 5b, 5c of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are located in the same phase, i.e., at positions opposite to each other with respect to the axial direction.

Numerical 7 stands for a third yoke made of a soft magnetic material. The third yoke is formed in a barrel shape so as to cover the outside peripheral surfaces of the coil 3, coil 4, and permanent magnet 1. The third yoke 7 is connected at the portion 7e to the portion 5e of the first yoke 5 and at the portion 7f to the portion 6e of the second yoke 6. The third yoke 7 has portions 7a, 7b at the positions opposite to the teeth 5b, 5c of the first yoke 5 and to the teeth 6b, 6c of the second yoke 6 on either side of the permanent magnet 1, and holes 7c, 7d are formed in the portions other than the portions 7a, 7b. The teeth 5b, 5c of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are in the same phase, and the pole portions 7a, 7b of the third yoke 7 to be opposed to those teeth are of the simple shape of continuous parts of the magnetic portions as shown in Fig. 11. The production thereof by press or the like is thus easy. In the pole teeth 7a, 7b forming the continuous parts of the third yoke 7, notch portions 7i, 7j with a narrower width than





that at the other positions are formed at positions opposite near the border between the first magnetic layer and the second magnetic layer of the magnet ring 1.

5           This makes the reluctance high near the third yoke 7, so that the magnetic flux generated from the coil 3 becomes reluctant to act on the coil 4, the second magnetic layer of the magnet ring 1, the second yoke 6, and so on and so that the magnetic flux generated from  
10   the coil 4 becomes reluctant to act on the coil 3, the first magnetic layer of the magnet ring 1, the first yoke 5, and so on. Thus, the rotor becomes smoothly rotatable according to the operation already described in the first embodiment, thereby increasing the output  
15   of motor.

As described above, the present invention can provide the cheap motors, because the yokes are formed in the shape with good workability and with high strength. The present invention can also provide the  
20   high-output motor that can be produced readily, that has a small diameter, and that rotates on a smooth basis.

In the above embodiments, the permanent magnet forming the rotor was one obtained by dividing the  
25   outside peripheral surface circumferentially into n and magnetizing the n portions in the S and N poles and by also dividing the inside peripheral surface

THIS SHEET HAS BEEN  
REPLACED

This Sheet Has Been Replaced  


circumferentially into  $n$  and magnetizing the  $n$  portions in the S and N poles so that the inside peripheral surface was magnetized in the poles different from those of the adjacent outside peripheral surface. The present invention, however, is not limited to this, but the permanent magnet may be one obtained by dividing only the outside peripheral surface circumferentially into  $n$  and magnetizing the  $n$  portions in the S and N poles.

In the above embodiments the number of poles of the permanent magnet was 4, but, without having to be limited to this, the present invention may be applied to the cases wherein the number of poles of the permanent magnet is not less than 4. In the case wherein the number of poles of the permanent magnet is not less than 4, the number of the outside and inside poles is also increased according thereto.

THIS SHEET HAS BEEN  
REPLACED

This Sheet Has Been Replaced



WHAT IS CLAIMED IS:

1. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside  
5 peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and  
10 second coil being located on either side of said magnet;


a first outside pole excited by said first coil, said first outside pole being opposed to the outside  
peripheral surface of said magnet on the side of one  
15 end thereof;

a first inside pole excited by said first coil, said first inside pole being formed as a first yoke  
opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke  
20 having such a shape that a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second outside pole excited by said second coil, said second outside pole being opposed to the outside  
25 peripheral surface of said magnet on the side of the other end thereof; and



THIS SHEET HAS BEEN  
REPLACED



a second inside pole excited by said second coil,  
said second inside pole being formed as a second yoke  
opposed to the inside peripheral surface of said magnet  
on the side of the other end thereof, said second yoke  
5 having such a shape that a cross section thereof in the  
direction perpendicular to the axis of said magnet  
comprises alternately formed regions with a large  
outside dimension and with a small outside dimension.

10 2. A motor according to Claim 1, wherein said  
magnet is magnetized so that the inside peripheral  
surface thereof is divided circumferentially into n  
portions and said n portions are magnetized in  
alternately different poles that are also different  
15 from those in the outside peripheral surface adjacent  
thereto.

3. A motor according to Claim 1, wherein said  
first outside pole is formed as a third yoke, said  
20 second outside pole is formed as a fourth yoke, said  
first yoke and said third yoke form a first stator, and  
said second yoke and said fourth yoke form a second  
stator.

25 4. A motor according to Claim 3, wherein said  
third yoke and said fourth yoke are connected by a  
connecting member of a cylindrical shape.





5. A motor according to Claim 3, wherein said first yoke or/and said second yoke are formed so that a cross-sectional shape thereof in the direction perpendicular to the axis of said magnet is an elliptic shape with the major axis A and the minor axis B ( $A > B$ ), wherein the major axis A is arranged so as to be located opposite to the poles of the third yoke and the fourth yoke.

6. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and second coil being located on either side of said magnet;

a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on the side of one end thereof;

a first inside pole excited by said first coil, said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke





having such a shape that a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

5           a second inside pole excited by said second coil, said second inside pole being formed as a second yoke opposed to the inside peripheral surface of said magnet on the side of the other end thereof, said second yoke having such a shape that a cross section thereof in the  
10           direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;  
and

          a second outside pole excited by said second coil,  
15           said second outside pole being opposed to the outside peripheral surface of said magnet on the side of the other end thereof, said second outside pole and said first outside pole forming a third yoke, said third yoke being formed in a barrel shape having a hole  
20           portion and a continuous portion forming pole portions of the first and second outside poles, wherein a further hole portion is also provided substantially in the center of the continuous portion.

25           7. A motor according to Claim 6, wherein said magnet has a first magnetic layer in which at least an outside peripheral surface thereof is divided



\* C L H S \*



circumferentially into n portions and said n portions  
are magnetized in alternately different poles, and a  
second magnetic layer in which at least an outside  
peripheral surface thereof is divided circumferentially  
5 into n portions and said n portions are magnetized in  
alternately different poles, said second magnetic layer  
being formed in a phase shifted by  $180/n$  degrees from  
that of the first magnetic layer and at a position  
adjacent thereto in the axial direction.

10

8. A motor according to Claim 7, wherein said  
magnet is magnetized so that the inside peripheral  
surface thereof is divided circumferentially into n  
portions and said n portions are magnetized in  
15 alternately different poles that are also different  
from those in the outside peripheral surface adjacent  
thereto.

9. A motor comprising:

20 a magnet formed in a cylindrical shape, said  
magnet being magnetized so that at least an outside  
peripheral surface thereof is divided circumferentially  
into n portions and said n portions are magnetized in  
alternately different poles;

25 a first coil and a second coil disposed in an  
axial direction of said magnet, said first coil and  
second coil being located on either side of said



THIS SHEET HAS BEEN  
REPLACED



magnet;

5 a first outside pole excited by said first coil,  
said first outside pole being opposed to the outside  
peripheral surface of said magnet on the side of one  
end thereof;

10 a first inside pole excited by said first coil,  
said first inside pole being formed as a first yoke  
opposed to an inside peripheral surface of said magnet  
on the side of the one end thereof, said first yoke  
having such a shape that a cross section thereof in a  
direction perpendicular to the axis of said magnet  
comprises alternately formed regions with a large  
outside dimension and with a small outside dimension;

15 a second inside pole excited by said second coil,  
said second inside pole being formed as a second yoke  
opposed to the inside peripheral surface of said magnet  
on the side of the other end thereof, said second yoke  
having such a shape that a cross section thereof in the  
direction perpendicular to the axis of said magnet  
20 comprises alternately formed regions with a large  
outside dimension and with a small outside dimension;  
and

25 a second outside pole excited by said second coil,  
said second outside pole being opposed to the outside  
peripheral surface of said magnet on the side of the  
other end thereof, said second outside pole and said  
first outside pole forming a third yoke, said third






yoke being formed in a barrel shape having a hole  
portion and a continuous portion forming pole portions  
of the first and second outside poles, wherein a notch  
portion continuous from said hole portion is provided  
5 substantially in the center of the continuous portion.

10. A motor according to Claim 9, wherein said  
magnet has a first magnetic layer in which at least an  
outside peripheral surface thereof is divided  
10 circumferentially into n portions and said n portions  
are magnetized in alternately different poles, and a  
second magnetic layer in which at least an outside  
peripheral surface thereof is divided circumferentially  
into n portions and said n portions are magnetized in  
15 alternately different poles, said second magnetic layer  
being formed in a phase shifted by  $180/n$  degrees from  
that of the first magnetic layer and at a position  
adjacent thereto in the axial direction.

20. 11. A motor according to Claim 9, wherein said  
magnet is magnetized so that the inside peripheral  
surface thereof is divided circumferentially into n  
portions and said n portions are magnetized in  
alternately different poles that are also different  
25 from those in the outside peripheral surface adjacent  
thereto.



\* C L N S \*



12. A motor comprising:

a magnet formed in a cylindrical shape, said magnet having a first magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, and a second magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, said second magnetic layer being located at a position adjacent to said first magnetic layer in the axial direction and having a phase shifted by  $180/n$  degrees from that of the first magnetic layer;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and second coil being located on either side of said magnet;

a first yoke of a barrel shape set inside of said first coil and opposed with a gap to an inside face of the first magnetic layer of said magnet, said first yoke forming a pole section in which a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second yoke of a barrel shape set inside of said






second coil and opposed with a gap to an inside face of  
the second magnetic layer of said magnet, said second  
yoke forming a pole section in which a cross section  
thereof in the direction perpendicular to the axis of  
5 said magnet comprises alternately formed regions with a  
large outside dimension and with a small outside  
dimension;

a third yoke comprising one end connected to said  
first yoke and covering an outside face of said first  
10 coil and another end having a pole portion opposed to  
the outside peripheral surface of the first magnetic  
layer of said magnet;

a fourth yoke comprising one end connected to said  
second yoke and covering an outside face of said second  
15 coil and another end having a pole portion opposed to  
the outside peripheral surface of the second magnetic  
layer of said magnet; and

a connecting member for holding said third yoke  
and said fourth yoke concentric with each other.





# ABSTRACT OF THE DISCLOSURE

A motor is formed in such structure that a rotor of permanent magnet, equally divided in the circumferential direction and magnetized in alternately different poles, is formed in a cylindrical shape, that  
5 a first coil, the rotor, and a second coil are located in order in the axial direction, that first outside and first inside poles excited by the first coil are opposed to outside and inside peripheral surfaces of  
10 the rotor, and that second outside and second inside poles excited by the second coil are opposed to the outside and inside peripheral surfaces of the rotor, wherein yokes forming the first and second inside poles of this motor are formed so that a cross section  
15 thereof in a direction perpendicular to the axis of the rotor has alternately formed regions with a large outside dimension and with a small outside dimension, thereby being formed in the shape with good workability. In addition, the working of a yoke for  
20 forming the outside poles is also made easy.

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G







FIG. 3H



**FIG. 4**



**FIG. 5**




**FIG. 6**

FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 9G






FIG. 9H



**FIG. 10**



**FIG. 12**





FIG. 11





## MOTOR

### BACKGROUND OF THE INVENTION

#### Field of the Invention


The present invention relates to a motor that can be constructed in microstructure with enhanced workability.

#### Related Background Art

Among conventional compact motors, there is, for example, a compact, cylindrical step motor as shown in Fig. 13. A stator coil 105 is concentrically wound on each of bobbins 101, and each bobbin 101 is fixed as being axially sandwiched between two stator yokes 106. The stator yoke 106 have stator teeth 106a and stator teeth 106b arranged in alternating fashion along the circumferential direction of the bore surface of bobbin 101. The stator yokes 106 integral with the stator teeth 106a or 106b are fixed to cases 103, thus composing stators 102.

Flange 115 and bearing 108 are fixed to one of two sets of cases 103 and another bearing 108 is fixed to the other case 103. Rotor 109 is comprised of a rotor magnet 111 fixed to rotor shaft 110, and the rotor magnet 111 and the stator yoke 106 of stator 102 form radial gap portions. The rotor shaft 110 is rotatably supported between the two bearings 108.

The conventional compact step motor described




above, however, had the drawback that the outside dimensions of motor were large, because the cases 103, bobbins 101, stator coils 105, stator yokes 106, etc. were concentrically located outside the rotor. In addition, it has another drawback that the output of motor is not high, because the magnetic flux generated by energizing the stator coils 105 mainly passes end faces 106a1 of the stator teeth 106a and end faces 106b1 of the stator teeth 106b, as shown in Fig. 14, and does not effectively act on the rotor magnet 111.

The applicant proposed a motor solving such problems in United States Patent Application No. 08/831,863 (filed April 2, 1997).

This proposed motor is constructed in such structure that the rotor of permanent magnet partitioned and magnetized in the alternately different poles at equal intervals in the circumferential direction is formed in a cylindrical shape, that a first coil, the rotor, and a second coil are located in order along the axial direction of the rotor, that the first outside pole and first inside pole excited by the first coil are opposed to outside and inside peripheral surfaces of the rotor, and that the second outside pole and second inside pole excited by the second coil are opposed to the outside and inside peripheral surfaces of the rotor.

The motor of this structure was able to provide



high output and had small outside dimensions of motor, but the radial dimension of the first inside pole and second inside pole which comprise a pair of magnetic tooth with separated tip ends was also small. When these pole teeth were processed by press working, there were problems of strength of mold, emission of chip, and so on. Therefore, the processing was not easy and it was rather difficult to achieve high strength of the teeth. There were desires for readily processing the first outside pole and second outside pole, too.

#### SUMMARY OF THE INVENTION


An object of the present invention is to overcome the above drawbacks and to provide a motor that can be constructed in microstructure wherein the inside poles are formed in a shape with high workability.

Another object of the present invention is to provide a motor that can be constructed in microstructure wherein processing of the outside poles is easy.

Other objects of the present invention will become more apparent by specific embodiments which will be described below.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an exploded, perspective view of a motor of the first embodiment according to the present



invention;

Fig. 2 is a cross-sectional view of the assembled state of the motor shown in Fig. 1;

Figs. 3A, 3B, 3C, 3D, 3E, 3F, 3G, and 3H are drawings for explaining the rotor rotation operation of the motor shown in Fig. 2;

Fig. 4 is an enlarged view of the yoke as an inside pole in the motor shown in Fig. 2;

Fig. 5 is a drawing to show another example of the yoke as an inside pole in the motor shown in Fig. 2;

Fig. 6 is a cross-sectional view of the yoke shown in Fig. 5;

Fig. 7 is an exploded, perspective view of a motor of the second embodiment according to the present invention;

Fig. 8 is a cross-sectional view of the assembled state of the motor shown in Fig. 7;


Figs. 9A, 9B, 9C, 9D, 9E, 9F, 9G, and 9H are drawings for explaining the rotor rotation operation of the motor shown in Fig. 7;

Fig. 10 is a plan view of the motor shown in Fig. 7;

Fig. 11 is an exploded, perspective view to show another example of the motor shown in Fig. 7;

Fig. 12 is a plan view of the assembled state of the motor shown in Fig. 11;

Fig. 13 is a cross-sectional view to show a



conventional step motor; and

Fig. 14 is an explanatory drawing to show the magnetic flux in the conventional step motor shown in Fig. 13.


#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments of the present invention will be described by reference to the drawings.

(Embodiment 1)

Fig. 1 to Fig. 4 are drawings to show Embodiment 1. Reference numeral 1 designates a permanent magnet of a cylindrical shape, which is composed of a first magnetic layer having four portions 1a, 1b, 1c, 1d obtained by quartering the circumference and alternately magnetized in the S and N poles, and a second magnetic layer having four portions 1e, 1f, 1g, 1h obtained similarly by quartering the circumference and alternately magnetized in the S and N poles. The first magnetic layer and the second magnetic layer are magnetized in respective phases shifted by 45° from each other.

The outside peripheral surfaces of the portions 1a, 1c of the first magnetic layer and the portions 1e, 1g of the second magnetic layer are magnetized in the S pole and the inside peripheral surfaces thereof in the N pole; the outside peripheral surfaces of the portions 1b, 1d of the first magnetic layer and the portions 1f,




1h of the second magnetic layer are magnetized in the N pole and the inside peripheral surfaces thereof in the S pole.

Numeral 2 denotes a rotational shaft, to which the permanent magnet 1 is fixed. The rotational shaft 2 and permanent magnet 1 compose a rotor. Numerals 3, 4 are coils which are located so as to be concentric with the permanent magnet 1 and to sandwich the permanent magnet 1 in the axial direction. Numeral 5 represents a first yoke made of a soft magnetic material, which has a portion 5d set in a bore portion 3a of the coil 3 and a pole section opposed to a bore portion of the first magnetic layer of the permanent magnet 1.

In the pole section, as shown in Fig. 4, portions 5b, 5c with a large outside diameter and portions 5e, 5f with a small outside diameter are alternately formed in the cross section taken in the direction perpendicular to the axis. The portions 5b, 5c are formed in the same phase, relative to the poles of the first magnetic layer. Namely, the portion 5b and the portion 5c are located as shifted by 180° from each other. A portion 2a of the rotational shaft 2 is fitted in a hole 5a of the first yoke so as to be rotatable.


Numeral 6 denotes a second yoke made of a soft magnetic material, which has a portion 6d set in a bore portion 4a of the coil 4 and a pole section opposed to



a bore portion of the second magnetic layer of the permanent magnet 1. In the pole section, portions 6b, 6c with a large outside diameter and portions 6e, 6f with a small outside diameter are alternately formed, as in the first yoke 5. The portions 6b, 6c are formed in the same phase, relative to the poles of the second magnetic layer. Namely, the portion 6b and the portion 6c are located as shifted by 180° from each other. A portion 2b of the rotational shaft 2 is fitted in a hole 6a of the second yoke so as to be rotatable. The large diameter portions 5b, 5c of the first yoke 5 and the large diameter portions 6b, 6c of the second yoke 6 are located in the same phase, i.e., opposed to each other with respect to the axial direction.

Numeral 8 stands for a third yoke made of a soft magnetic material, in which teeth 8a, 8b are formed at positions where they sandwich the portions 5b, 5c of the first yoke 5 and the first magnetic layer of the permanent magnet 1. Numeral 9 stands for a fourth outer yoke made of a soft magnetic material, in which teeth 9a, 9b are formed at positions where they sandwich the portions 6b, 6c of the second yoke 6 and the second magnetic layer of the permanent magnet 1.


Numeral 10 designates a coupling ring made of a non-magnetic material, which has grooves 10a, 10b engaged with the teeth 8a, 8b of the third yoke 8 and grooves 10c, 10d engaged with the teeth 9a, 9b of the



fourth yoke. The third yoke 8 and the fourth yoke 9 are fixed to the coupling ring 10 by a conventional method, for example, by bonding or the like. The third yoke 8 and the fourth yoke 9 are fixed with a predetermined space through portions 10e, 10f of the coupling ring 10. The teeth 8a, 8b of the third yoke 8 are so arranged as to face the teeth 9a, 9b of the fourth yoke 9.


The third yoke 8 is so arranged, as shown in Fig. 2, that one end thereof is connected to the first yoke 5 and covers the outside-diameter portion of coil 3 and that the teeth 8a, 8b at the other end are opposed with a predetermined gap to the outside peripheral portion of the permanent magnet 1. The fourth yoke 9 is so arranged, as shown in Fig. 2, that one end thereof is connected to the second yoke 6 and covers the outside-diameter portion of coil 4 and that the teeth 9a, 9b at the other end are opposed with a predetermined gap to the outside peripheral portion of the permanent magnet 1.

Fig. 2 is a cross-sectional view of the assembled state, Figs. 3A, 3B, 3C, and 3D are cross-sectional views along A-A in Fig. 2, and Figs. 3E, 3F, 3G, and 3H are cross-sectional views along B-B in Fig. 2. Figs. 3A and 3E are cross-sectional views at a moment, Figs. 3B and 3F those at another moment, Figs. 3C and 3G those at still another moment, and Figs. 3D and 3H



those at yet still another moment. When from the state of Figs. 3A and 3E the coil 3 and coil 4 are energized to excite the pole portions 5b, 5c, 5e, 5f of the first yoke 5 to the S pole, the portions 8a, 8b of the third yoke opposed to the portions 5b, 5c to the N pole, the pole portions 6b, 6c, 6e, 6f of the second yoke 6 to the S pole, and the portions 9a, 9b of the fourth yoke 9 opposed to the portions 6b, 6c to the N pole, the permanent magnet 1 rotates 45° counterclockwise so as to go into the state shown in Figs. 3B and 3F.

Since the small-diameter portions 5e, 5f in the pole section of the first yoke 5 are more distant from the inside peripheral surface of the first magnetic layer than the portions 5b, 5c, the pole occurring in the small-diameter portions 5e, 5f little acts on the first magnetic layer and thus little affects the driving force generated. Accordingly, the first yoke 5 can function in the same manner as in the case of applicant's prior application No. 08/831,863 (filed April 2, 1997) which comprises inner magnetic pole with a pair of separated magnetic teeth. The shape of the first yoke 5 forms no chip when produced by press working. Therefore, no consideration is necessary for emission of chip and the production is thus easy. Since the portions 5b, 5e, 5c, 5f are joined throughout the entire circumference, the strength is high and there is no possibility of deformation during assembly.



The above is also the case for the second yoke 6. Since the small-diameter portions 6e, 6f in the pole section of the second yoke 6 are more distant from the inside peripheral surface of the second magnetic layer than the portions 6b, 6c, the pole occurring in the small-diameter portions 6e, 6f little acts on the second magnetic layer and thus little affects the driving force generated. Accordingly, the second yoke 6 can function in the same manner as in the case of above-mentioned application No. 08/831,863. The shape of the second yoke 6 forms no chip when produced by press working. Therefore, no consideration is necessary for emission of chip and the production is thus easy. Since the portions 6b, 6e, 6c, 6f are joined throughout the entire circumference, the strength is high and there is no possibility of deformation during assembly.

Then the power supply to the coil 3 is inverted to excite the pole portions 5b, 5c, 5e, 5f of the first yoke 5 to the N pole, the portions 8a, 8b of the third yoke opposed to the portions 5b, 5c to the S pole, the pole portions 6b, 6c, 6e, 6f of the second yoke 6 to the S pole, and the portions 9a, 9b of the fourth yoke opposed to the portions 6b, 6c to the N pole, whereupon the permanent magnet 1 is rotated further 45° counterclockwise to go into the state shown in Figs. 3C and 3G.

Then the power supply to the coil 4 is inverted to excite the pole portions 6b, 6c, 6e, 6f of the second yoke 6 to the N pole and the portions 9a, 9b of the fourth yoke opposed to the 6b, 6c to the S pole, whereupon the permanent magnet 1 is rotated further 45° counterclockwise. By successively switching the directions of power supply to the coil 3 and coil 4 in this manner, the rotor composed of the permanent magnet 1 and rotational shaft 2 rotates to the positions according to the phases of power supply.

Described below is the reason why the step motor of the above structure is optimum for microminiaturization of motor.


Features of the fundamental structure of the step motor are as follows.

First, the magnet is formed in the hollow cylinder shape.

Second, the outside peripheral surface of the magnet is divided circumferentially into n portions and the n portions are magnetized alternately in the different poles.

Third, the first coil, the magnet, and the second coil are located in order in the axial direction of the magnet.

Fourth, the outside pole and the inside pole of the first and second stators excited by the first and second coils are opposed to the outside peripheral



surface and to the inside peripheral surface, respectively, of the magnet.


Accordingly, a necessary diameter of this step motor is a size enough to oppose the poles of the stators to the diameter of the magnet; and a necessary axial length of the step motor is the sum of the length of the magnet and the lengths of the first and second coils. Therefore, the dimensions of the step motor are determined by the diameters and lengths of the magnet and coils, and the step motor can be microminiaturized by decreasing the diameters and lengths of the magnet and coils to very small values.

When the diameters and lengths of the magnet and coils are made very small, it becomes difficult to maintain the output accuracy of the step motor. This problem of the output accuracy of the step motor is solved by the simple structure wherein the magnet is formed in the hollow cylinder shape and the outside pole and inside pole of the first and second stators are opposed to the outside peripheral surface and to the inside peripheral surface of the magnet formed in the hollow cylinder shape.

Next described is another example in which the shape of the first and second yokes is modified.


Fig. 5 and Fig. 6 are drawings to show another example of the first embodiment.

Fig. 5 is a perspective view of the first yoke, in



which the pole section opposed to the inside peripheral surface of the first magnetic layer is formed in the shape of an ellipse 5g ( $A > B$  where A is the major axis and B is the minor axis) in the cross section perpendicular to the axis. Fig. 6 is a lateral, cross-sectional view of the motor in which the first yoke 5 is incorporated. The first yoke 5 is located so that the major axis A is directed toward the positions opposed to the teeth 8a, 8b of the third yoke 8. Similarly, though not illustrated, the second yoke is also formed in the elliptic shape with the major axis A and the minor axis B ( $A > B$ ) at least in the outside peripheral surface of the pole section, and the major axis is arranged so as to be directed toward the positions opposed to the teeth 9a, 9b of the fourth yoke.

The outside peripheral surfaces of the first yoke 5 and second yoke 6 in the minor-axis direction are apart from the circumferential surfaces of the first magnetic layer and the second magnetic layer, respectively, and thus they do not negatively affect the output of motor, similar to the portions 5e, 5f, 6e, 6f in the first example. Since the pole section of the first yoke and second yoke is continuous throughout the entire circumference, the strength is high and no chip is produced during press working, thus achieving high workability.




In the first embodiment described above the first to fourth yokes 5, 6, 8, 9 were separate members, but they may be formed in such structure that the first and third yokes 5, 8 are integrated into a first stator yoke and that the second and fourth yokes 6, 9 are integrated into a second stator yoke.

The first magnet 1 was constructed in the double layer structure consisting of the first magnetic layer and the second magnetic layer the phases of which were shifted by  $180/n$  degrees ( $n$  is the number of magnetic poles of the permanent magnet), i.e.,  $45^\circ$ , but, without having to be limited to this, the present invention can also be applied to the single layer structure of a magnetic layer in the permanent magnet 1 wherein the phase of the second and fourth yokes 6, 9 is shifted by  $180/n$  degrees, i.e.,  $45^\circ$ , relative to that of the first and third yokes 5, 8.

The second embodiment of the present invention will be described below.


(Embodiment 2)

Fig. 7 to Fig. 10 are drawings to show Embodiment 2 of the present invention. In Fig. 7 to Fig. 10, reference numeral 1 designates a magnet ring of a cylindrical shape made of a permanent magnet, which is composed of a first magnetic layer having portions 1a, 1b, 1c, 1d obtained by dividing the circumference into  $n$  (4 in the present embodiment) and alternately



magnetized in the S and N poles, and a second magnetic layer having portions 1e, 1f, 1g, 1h obtained similarly by dividing the circumference into 4 and alternately magnetized in the S and N poles. The phases of the first magnetic layer and the second magnetic layer are shifted by  $180/n$  degrees, i.e.,  $45^\circ$  from each other. In the present embodiment, the outside peripheral surfaces of the portions 1a, 1c of the first magnetic layer and the portions 1e, 1g of the second magnetic layer are magnetized in the S pole and the inside peripheral surfaces thereof in the N pole; the outside peripheral surfaces of the portions 1b, 1d of the first magnetic layer and the portions 1f, 1h of the second magnetic layer are magnetized in the N pole and the inside peripheral surfaces thereof in the S pole.


Numeral 2 denotes a rotational shaft to which the permanent magnet 1 is fixed. The rotational shaft 2 and permanent magnet 1 compose a rotor. Numerals 3, 4 are coils which are located so as to be concentric with the permanent magnet 1 and to sandwich the permanent magnet 1 in the axial direction. Numeral 5 represents a first yoke made of a soft magnetic material, which has a portion 5d set in the bore portion 3a of coil 3 and teeth 5b, 5c opposed to the bore portion of the first magnetic layer of the permanent magnet 1. The teeth 5b, 5c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the



same phase, relative to the poles of the first magnetic layer. A portion 2a of the rotational shaft 2 is fitted in a hole 5a of the first yoke so as to be rotatable.

Numeral 6 stands for a second yoke made of a soft magnetic material, which has a portion 6d set in the bore portion 4a of coil 4, and teeth 6b, 6c opposed to the bore portion of the second magnetic layer of the permanent magnet 1. The teeth 6b, 6c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the same phase, relative to the poles of the second magnetic layer. A portion 2b of the rotational shaft 2 is fitted in a hole 6a of the second yoke 6 so as to be rotatable. The teeth 5b, 5c of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are located in the same phase, i.e., at positions where they are opposed to each other with respect to the axial direction.


Numeral 7 denotes a third yoke made of a soft magnetic material. The third yoke is of a barrel shape, which is constructed so as to cover the outside peripheral surfaces of the coil 3, coil 4, and permanent magnet 1. The third yoke 7 is connected at the portion 7e to the portion 5h of the first yoke 5 and at the portion 7f to the portion 6h of the second yoke 6. The third yoke 7 has portions 7a, 7b at positions opposite to the teeth 5b, 5c of the first



yoke 5 and the teeth 6b, 6c of the second yoke 6 on either side of the permanent magnet 1 and holes 7c, 7d formed in the other portions than the portions 7a, 7b. Since the teeth 5b, 5c of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are in the same phase, the pole portions 7a, 7b of the third yoke 7 to be faced to those teeth have the simple shape consisting of continuous parts of the pole portions 7a, 7b as shown in Fig. 7, and the production thereof by press or the like is thus easy. In the pole teeth 7a, 7b forming the continuous parts of the third yoke 7, holes 7g, 7h are formed at positions opposite to each other near the border between the first magnetic layer and the second magnetic layer of the magnet ring 1.

This makes the reluctance high near the third yoke 7, so that the magnetic flux generated from the coil 3 becomes reluctant to act on the coil 4, the second magnetic layer of the magnet ring 1, the second yoke 6, and so on and so that the magnetic flux generated from the coil 4 becomes reluctant to act on the coil 3, the first magnetic layer of the magnet ring 1, the first yoke 5, and so on. Thus, the rotor becomes smoothly rotatable according to the operation described below, thereby increasing the output of motor.

Fig. 8 is a cross-sectional view of the assembled state, Figs. 9A, 9B, 9C, and 9D are cross-sectional views along A-A in Fig. 8, and Figs. 9E, 9F, 9G, and 9H



are cross-sectional views along B-B in Fig. 8. Figs.

9A and 9E are cross-sectional views at a moment, Figs.

9B and 9F those at another moment, Figs. 9C and 9G

those at still another moment, and Figs. 9D and 9H

those at yet still another moment.

When from the state of Figs. 9A and 9E the coil 3 and coil 4 are energized to excite the teeth 5b, 5c of the first yoke 5 to the S pole, the portions 7a, 7b of the third yoke 7 opposed to the teeth 5b, 5c to the N pole, the teeth 6b, 6c of the second yoke 6 to the S pole, and the portions 7a, 7b of the third yoke 7 opposed to the teeth 6b, 6c to the N pole, the magnet ring 1 is rotated 45° leftward (counterclockwise) to go into the state shown in Figs. 9B and 9F.

Then the power supply to the coil 3 is inverted to excite the teeth 5b, 5c of the first yoke 5 to the N pole, the portions 7a, 7b of the third yoke 7 opposed to the teeth 5b, 5c to the S pole, the teeth 6b, 6c of the second yoke 6 to the S pole, and the portions 7a, 7b of the third yoke 7 opposed to the teeth 6b, 6c to the N pole, whereupon the magnet ring 1 is rotated further 45° counterclockwise to go into the state shown in Figs. 9C and 9G.

Then the power supply to the coil 4 is inverted to excite the teeth 6b, 6c of the second yoke 6 to the N pole and the portions 7a, 7b of the third yoke 7 opposed to the teeth 6b, 6c to the S pole, whereupon

16 FEB 1998

- 19 -

the permanent magnet 1 is rotated further  $45^\circ$  counterclockwise. By successively switching the directions of power supply to the coil 3 and coil 4 in this way, the rotor comprised of the magnet ring 1 and rotational shaft 2 rotates to the positions according to the phases of power supply. Fig. 10 is a top plan view of this motor.

Next described is another example in which the shape of the third yoke is modified.


Fig. 11 and Fig. 12 are drawings to show another example of the second embodiment.

In Fig. 11 and Fig. 12, numeral 1 designates a magnet ring of a cylindrical shape made from a permanent magnet, which is composed of a first magnetic layer having portions 1a, 1b, 1c, 1d obtained by dividing the circumference into  $n$  (4 in this example) and alternately magnetized in the S and N poles, and a second magnetic layer having portions 1e, 1f, 1g, 1h obtained similarly by dividing the circumference into 4 and alternately magnetized in the S and N poles. The phases of the first magnetic layer and second magnetic layer are shifted by  $180/n$  degrees, i.e.,  $45^\circ$  from each other. In the present example, the outside peripheral surfaces of the portions 1a, 1c of the first magnetic layer and the portions 1e, 1g of the second magnetic layer are magnetized in the S pole and the inside peripheral surfaces thereof in the N pole; the outside

peripheral surfaces of the portions 1b, 1d of the first magnetic layer and the portions 1f, 1h of the second magnetic layer are magnetized in the N pole and the inside peripheral surfaces thereof in the S pole.

Numeral 2 represents a rotational shaft to which the permanent magnet 1 is fixed. The rotational shaft 2 and permanent magnet 1 compose the claimed rotor. Numerals 3, 4 are coils which are located so as to be concentric with the permanent magnet 1 and to sandwich the permanent magnet 1 in the axial direction. Numeral 5 designates a first yoke made of a soft magnetic material, which has a portion 5d set in the bore portion 3a of the coil 3 and teeth 5b, 5c opposed to the bore portion of the first magnetic layer of the permanent magnet 1. The teeth 5b, 5c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the same phase, relative to the poles of the first magnetic layer, and a portion 2a of the rotational shaft 2 is fitted in a hole 5a of the first yoke so as to be rotatable.

Numeral 6 denotes a second yoke made of a soft magnetic material, which has a portion 6d set in the bore portion 4a of coil 4 and teeth 6b, 6c opposed to the bore portion of the second magnetic layer of the permanent magnet 1. The teeth 6b, 6c are formed as shifted by  $360/(n/2)$  degrees, i.e.,  $180^\circ$  from each other so as to be in the same phase, relative to the



poles of the second magnetic layer. A portion 2b of the rotational shaft 2 is fitted in a hole 6a of the second yoke 6 so as to be rotatable. The teeth 5b, 5c of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are located in the same phase, i.e., at positions opposite to each other with respect to the axial direction.


Numerical 7 stands for a third yoke made of a soft magnetic material. The third yoke is formed in a barrel shape so as to cover the outside peripheral surfaces of the coil 3, coil 4, and permanent magnet 1. The third yoke 7 is connected at the portion 7e to the portion 5e of the first yoke 5 and at the portion 7f to the portion 6e of the second yoke 6. The third yoke 7 has portions 7a, 7b at the positions opposite to the teeth 5b, 5c of the first yoke 5 and to the teeth 6b, 6c of the second yoke 6 on either side of the permanent magnet 1, and holes 7c, 7d are formed in the portions other than the portions 7a, 7b. The teeth 5b, 5c of the first yoke 5 and the teeth 6b, 6c of the second yoke 6 are in the same phase, and the pole portions 7a, 7b of the third yoke 7 to be opposed to those teeth are of the simple shape of continuous parts of the magnetic portions as shown in Fig. 11. The production thereof by press or the like is thus easy. In the pole teeth 7a, 7b forming the continuous parts of the third yoke 7, notch portions 7i, 7j with a narrower width than

that at the other positions are formed at positions opposite near the border between the first magnetic layer and the second magnetic layer of the magnet ring 1.

This makes the reluctance high near the third yoke 7, so that the magnetic flux generated from the coil 3 becomes reluctant to act on the coil 4, the second magnetic layer of the magnet ring 1, the second yoke 6, and so on and so that the magnetic flux generated from the coil 4 becomes reluctant to act on the coil 3, the first magnetic layer of the magnet ring 1, the first yoke 5, and so on. Thus, the rotor becomes smoothly rotatable according to the operation already described in the first embodiment, thereby increasing the output of motor.

As described above, the present invention can provide the cheap motors, because the yokes are formed in the shape with good workability and with high strength. The present invention can also provide the high-output motor that can be produced readily, that has a small diameter, and that rotates on a smooth basis.

In the above embodiments, the permanent magnet forming the rotor was one obtained by dividing the outside peripheral surface circumferentially into  $n$  and magnetizing the  $n$  portions in the S and N poles and by also dividing the inside peripheral surface




- 23 -


circumferentially into  $n$  and magnetizing the  $n$  portions in the S and N poles so that the inside peripheral surface was magnetized in the poles different from those of the adjacent outside peripheral surface. The present invention, however, is not limited to this, but the permanent magnet may be one obtained by dividing only the outside peripheral surface circumferentially into  $n$  and magnetizing the  $n$  portions in the S and N poles.

In the above embodiments the number of poles of the permanent magnet was 4, but, without having to be limited to this, the present invention may be applied to the cases wherein the number of poles of the permanent magnet is not less than 4. In the case wherein the number of poles of the permanent magnet is not less than 4, the number of the outside and inside poles is also increased according thereto.

This Sheet Has Been Replaced



- 24 -



WHAT IS CLAIMED IS:

1. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and second coil being located on either side of said magnet;

a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on the side of one end thereof;

a first inside pole excited by said first coil, said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke having such a shape that a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second outside pole excited by said second coil, said second outside pole being opposed to the outside peripheral surface of said magnet on the side of the other end thereof; and



THIS SHEET HAS BEEN  
REPLACED



16 FEB 1998

a second inside pole excited by said second coil, said second inside pole being formed as a second yoke opposed to the inside peripheral surface of said magnet on the side of the other end thereof, said second yoke having such a shape that a cross section thereof in the direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension.

2. A motor according to Claim 1, wherein said magnet is magnetized so that the inside peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in alternately different poles that are also different from those in the outside peripheral surface adjacent thereto.


3. A motor according to Claim 1, wherein said first outside pole is formed as a third yoke, said second outside pole is formed as a fourth yoke, said first yoke and said third yoke form a first stator, and said second yoke and said fourth yoke form a second stator.

4. A motor according to Claim 3, wherein said third yoke and said fourth yoke are connected by a connecting member of a cylindrical shape.


THIS SHEET HAS BEEN  
REPLACED

\* C L H S \*

This Sheet Has Been Replaced



- 26 -



5. A motor according to Claim 3, wherein said first yoke or/and said second yoke are formed so that a cross-sectional shape thereof in the direction perpendicular to the axis of said magnet is an elliptic shape with the major axis A and the minor axis B ( $A > B$ ), wherein the major axis A is arranged so as to be located opposite to the poles of the third yoke and the fourth yoke.

6. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and second coil being located on either side of said magnet;

a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on the side of one end thereof;


a first inside pole excited by said first coil, said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke




\* C L M S \*

THIS SHEET HAS BEEN  
REPLACED

This Sheet Has Been Replaced



- 27 -



having such a shape that a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second inside pole excited by said second coil, said second inside pole being formed as a second yoke opposed to the inside peripheral surface of said magnet on the side of the other end thereof, said second yoke having such a shape that a cross section thereof in the direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension; and

a second outside pole excited by said second coil, said second outside pole being opposed to the outside peripheral surface of said magnet on the side of the other end thereof, said second outside pole and said first outside pole forming a third yoke, said third yoke being formed in a barrel shape having a hole portion and a continuous portion forming pole portions of the first and second outside poles, wherein a further hole portion is also provided substantially in the center of the continuous portion.

7. A motor according to Claim 6, wherein said magnet has a first magnetic layer in which at least an outside peripheral surface thereof is divided

THIS SHEET HAS BEEN  
REPLACED



This Sheet Has Been Replaced



- 28 -

REPLACEMENT SHEET

16 FEB 1998

circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, and a second magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, said second magnetic layer being formed in a phase shifted by  $180/n$  degrees from that of the first magnetic layer and at a position adjacent thereto in the axial direction.

8. A motor according to Claim 7, wherein said magnet is magnetized so that the inside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles that are also different from those in the outside peripheral surface adjacent thereto.

9. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles;


a first coil and a second coil disposed in an axial direction of said magnet, said first coil and second coil being located on either side of said




\* C L M S \*

THIS SHEET HAS BEEN  
REPLACED

This Sheet Has Been Replaced



- 29 -




magnet;

a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on the side of one end thereof;

a first inside pole excited by said first coil, said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke having such a shape that a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second inside pole excited by said second coil, said second inside pole being formed as a second yoke opposed to the inside peripheral surface of said magnet on the side of the other end thereof, said second yoke having such a shape that a cross section thereof in the direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension; and


a second outside pole excited by said second coil, said second outside pole being opposed to the outside peripheral surface of said magnet on the side of the other end thereof, said second outside pole and said first outside pole forming a third yoke, said third



This Sheet Has Been Replaced



- 30 -




yoke being formed in a barrel shape having a hole portion and a continuous portion forming pole portions of the first and second outside poles, wherein a notch portion continuous from said hole portion is provided substantially in the center of the continuous portion.

10. A motor according to Claim 9, wherein said magnet has a first magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, and a second magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, said second magnetic layer being formed in a phase shifted by  $180/n$  degrees from that of the first magnetic layer and at a position adjacent thereto in the axial direction.

11. A motor according to Claim 9, wherein said magnet is magnetized so that the inside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles that are also different from those in the outside peripheral surface adjacent thereto.




\* C L M S \*



This Sheet Has Been Replaced



- 31 -



12. A motor comprising:

a magnet formed in a cylindrical shape, said magnet having a first magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, and a second magnetic layer in which at least an outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, said second magnetic layer being located at a position adjacent to said first magnetic layer in the axial direction and having a phase shifted by  $180/n$  degrees from that of the first magnetic layer;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and second coil being located on either side of said magnet;


a first yoke of a barrel shape set inside of said first coil and opposed with a gap to an inside face of the first magnetic layer of said magnet, said first yoke forming a pole section in which a cross section thereof in a direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second yoke of a barrel shape set inside of said




THIS SHEET HAS BEEN  
REPLACED

This Sheet Has Been Replaced



- 32 -




second coil and opposed with a gap to an inside face of the second magnetic layer of said magnet, said second yoke forming a pole section in which a cross section thereof in the direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a third yoke comprising one end connected to said first yoke and covering an outside face of said first coil and another end having a pole portion opposed to the outside peripheral surface of the first magnetic layer of said magnet;

a fourth yoke comprising one end connected to said second yoke and covering an outside face of said second coil and another end having a pole portion opposed to the outside peripheral surface of the second magnetic layer of said magnet; and

a connecting member for holding said third yoke and said fourth yoke concentric with each other.






MOTOR

ABSTRACT OF THE DISCLOSURE

A motor is formed in such structure that a rotor of permanent magnet, equally divided in the circumferential direction and magnetized in alternately different poles, is formed in a cylindrical shape, that a first coil, the rotor, and a second coil are located in order in the axial direction, that first outside and first inside poles excited by the first coil are opposed to outside and inside peripheral surfaces of the rotor, and that second outside and second inside poles excited by the second coil are opposed to the outside and inside peripheral surfaces of the rotor, wherein yokes forming the first and second inside poles of this motor are formed so that a cross section thereof in a direction perpendicular to the axis of the rotor has alternately formed regions with a large outside dimension and with a small outside dimension, thereby being formed in the shape with good workability. In addition, the working of a yoke for forming the outside poles is also made easy.

Figure 1



- 24 -

WHAT IS CLAIMED IS:

1. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside  
5 peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and  
10 said second coil being located on either side of said magnet;

a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on a side of one end  
15 thereof;

a first inside pole excited by said first coil, said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke  
20 having such a shape that a cross section thereof in a direction perpendicular to an axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

a second outside pole excited by said second coil,  
25 said second outside pole being opposed to the outside peripheral surface of said magnet on a side of an other end thereof; and



07 JAN 2000

-25-

a second inside pole excited by said second coil,  
said second inside pole being formed as a second yoke  
opposed to the inside peripheral surface of said magnet  
on the side of the other end thereof, said second yoke  
5 having such a shape that a cross section thereof in the  
direction perpendicular to the axis of said magnet  
comprises alternately formed regions with a large  
outside dimension and with a small outside dimension.

10 2. A motor according to Claim 1, wherein said  
magnet is magnetized so that the inside peripheral  
surface thereof is also divided circumferentially into  
said n portions and said n portions are magnetized in  
alternately different poles that are also different  
15 from those in the outside peripheral surface adjacent  
thereto.

3. A motor according to Claim 1, wherein said  
first outside pole is formed as a third yoke, said  
20 second outside pole is formed as a fourth yoke, said  
first yoke and said third yoke form a first stator, and  
said second yoke and said fourth yoke form a second  
stator.

25 4. A motor according to Claim 3, wherein said  
third yoke and said fourth yoke are connected by a  
connecting member of a cylindrical shape.



5. A motor according to Claim 3, wherein said first yoke or/and said second yoke are formed so that said cross-sectional shape thereof in the direction perpendicular to the axis of said magnet is an elliptic shape with a major axis A and a minor axis B ( $A > B$ ), wherein the major axis A is arranged so as to be located opposite to the poles of the third yoke and the fourth yoke.

10 6. A motor comprising:  
a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in  
15 alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and said second coil being located on either side of said magnet;

20 a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on a side of one end thereof;

a first inside pole excited by said first coil,  
25 said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke



07 JAN 2000

-27-

having such a shape that a cross section thereof in a direction perpendicular to an axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

5           a second inside pole excited by said second coil, said second inside pole being formed as a second yoke opposed to the inside peripheral surface of said magnet on a side of an other end thereof, said second yoke having such a shape that a cross section thereof in the  
10       direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;  
and

          a second outside pole excited by said second coil,  
15       said second outside pole being opposed to the outside peripheral surface of said magnet on the side of the other end thereof, said second outside pole and said first outside pole forming a third yoke, said third yoke being formed in a barrel shape having a hole  
20       portion and a continuous portion forming pole portions of the first and second outside poles, wherein a further hole portion is also provided substantially in a center of the continuous portion.

25           7. A motor according to Claim 6, wherein said magnet has a first magnetic layer in which at least an outside peripheral surface thereof is also divided



07 JAN 2000

- 28 -

circumferentially into said n portions and said n portions are magnetized in alternately different poles, and a second magnetic layer in which at least an outside peripheral surface thereof is divided

5 circumferentially into n portions and said n portions are magnetized in alternately different poles, said second magnetic layer being formed in a phase shifted by  $180/n$  degrees from that of the first magnetic layer and at a position adjacent thereto in the axial

10 direction.

8. A motor according to Claim 7, wherein said magnet is magnetized so that the inside peripheral surface thereof is also divided circumferentially into

15 said n portions and said n portions are magnetized in alternately different poles that are also different from those in the outside peripheral surface adjacent thereto.

20 9. A motor comprising:

a magnet formed in a cylindrical shape, said magnet being magnetized so that at least an outside peripheral surface thereof is divided circumferentially into n portions and said n portions are magnetized in

25 alternately different poles;

a first coil and a second coil disposed in an axial direction of said magnet, said first coil and



said second coil being located on either side of said magnet;

5 a first outside pole excited by said first coil, said first outside pole being opposed to the outside peripheral surface of said magnet on a side of one end thereof;

10 a first inside pole excited by said first coil, said first inside pole being formed as a first yoke opposed to an inside peripheral surface of said magnet on the side of the one end thereof, said first yoke having such a shape that a cross section thereof in a direction perpendicular to an axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

15 a second inside pole excited by said second coil, said second inside pole being formed as a second yoke opposed to the inside peripheral surface of said magnet on a side of an other end thereof, said second yoke having such a shape that a cross section thereof in the direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension; and

20 a second outside pole excited by said second coil, said second outside pole being opposed to the outside peripheral surface of said magnet on the side of the other end thereof, said second outside pole and said



07 JAN 2000


- 30 -

first outside pole forming a third yoke, said third yoke being formed in a barrel shape having a hole portion and a continuous portion forming pole portions of the first and second outside poles, wherein a notch  
5 portion continuous from said hole portion is provided substantially in a center of the continuous portion.

10. A motor according to Claim 9, wherein said magnet has a first magnetic layer in which at least an  
10 outside peripheral surface thereof is divided circumferentially into  $n$  portions and said  $n$  portions are magnetized in alternately different poles, and a second magnetic layer in which at least an outside peripheral surface thereof is also divided  
15 circumferentially into said  $n$  portions and said  $n$  portions are magnetized in alternately different poles, said second magnetic layer being formed in a phase shifted by  $180/n$  degrees from that of the first magnetic layer and at a position adjacent thereto in  
20 the axial direction.

11. A motor according to Claim 9, wherein said magnet is magnetized so that the inside peripheral surface thereof is also divided circumferentially into  
25 said  $n$  portions and said  $n$  portions are magnetized in alternately different poles that are also different from those in the outside peripheral surface adjacent





- 31 -

thereto.

12. A motor comprising:

a magnet formed in a cylindrical shape, said  
5 magnet having a first magnetic layer in which at least  
an outside peripheral surface thereof is divided  
circumferentially into  $n$  portions and said  $n$  portions  
are magnetized in alternately different poles, and a  
second magnetic layer in which at least an outside  
10 peripheral surface thereof is also divided  
circumferentially into said  $n$  portions and said  $n$   
portions are magnetized in alternately different poles,  
said second magnetic layer being located at a position  
adjacent to said first magnetic layer in an axial  
15 direction and having a phase shifted by  $180/n$  degrees  
from that of the first magnetic layer;

a first coil and a second coil disposed in said  
axial direction of said magnet, said first coil and  
said second coil being located on either side of said  
20 magnet;

a first yoke of a barrel shape set inside of said  
first coil and opposed with a gap to an inside face of  
the first magnetic layer of said magnet, said first  
yoke forming a pole section in which a cross section  
25 thereof in a direction perpendicular to the axis of  
said magnet comprises alternately formed regions with a  
large outside dimension and with a small outside



07 JAN 2000

- 32 -

dimension;

5 a second yoke of a barrel shape set inside of said second coil and opposed with a gap to an inside face of the second magnetic layer of said magnet, said second yoke forming a pole section in which a cross section thereof in the direction perpendicular to the axis of said magnet comprises alternately formed regions with a large outside dimension and with a small outside dimension;

10 a third yoke comprising one end connected to said first yoke and covering an outside face of said first coil and another end having a pole portion opposed to the outside peripheral surface of the first magnetic layer of said magnet;

15 a fourth yoke comprising one end connected to said second yoke and covering an outside face of said second coil and another end having a pole portion opposed to the outside peripheral surface of the second magnetic layer of said magnet; and

20 a connecting member for holding said third yoke and said fourth yoke concentric with each other.

