

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 August 2004 (19.08.2004)


PCT

(10) International Publication Number
WO 2004/070933 A1

- (51) International Patent Classification⁷: **H02P 7/29**, H02M 7/5387, H02P 7/00
- (21) International Application Number: PCT/FI2004/000041
- (22) International Filing Date: 29 January 2004 (29.01.2004)
- (25) Filing Language: Finnish
- (26) Publication Language: English
- (30) Priority Data: 20030190 7 February 2003 (07.02.2003) FI
- (71) Applicant (for all designated States except US): **KONE CORPORATION** [FI/FI]; Kartanontie 1, FIN-00330 Helsinki (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **JAHKONEN, Pekka** [FI/FI]; Marjamäenkatu 18, FIN-05820 Hyvinkää (FI). **PUTKINEN, Esa** [FI/FI]; Yli-Anttilantie 12, FIN-05830 Hyvinkää (FI).
- (74) Agent: **KONE CORPORATION**; Patent Department, P.O. Box 677, FIN-05801 Hyvinkää (FI).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: DC/DC BRIDGE FOR CONTROLLING A DIRECT-CURRENT LOAD



(57) Abstract: A DC/DC bridge for controlling a direct-current load (M1), said bridge being provided with controllable semiconductor switch units (S21-S26) and having two bridge sections (B11, B12), one (B12) of which bridge sections conducts direct current while the other one (B11) is controlled via pulse-width modulation (PWM) to regulate the current magnitude, where the DC/DC bridge (B1) consists of three bridge arms, two (B111, B112) of which arms are connected in parallel, and where the semiconductor switches in the parallel-connected bridge arms are controlled via PWM to form a PWM-controlled bridge section.

WO 2004/070933 A1