

ELEVATOR GROUP SUPERVISORY CONTROL SYSTEM

BACKGROUND OF THE INVENTION

The present invention relates to an elevator group supervisory control system and in particular to control of elevator assignment to generated hall calls.

5 An elevator group supervisory control system treats multiple elevator cages as one group to provide more efficient transport service to users. Specifically, four to eight elevator cages are typically controlled as one group. If a hall call
10 occurs at a floor, the most appropriate one is selected from this group and assigned to the hall call.

Assignment control based on an assignment evaluation function of waiting time, which constitutes the basic assignment control principle of existing
15 group supervisory control systems, was developed around 1980 when microcomputers were introduced. In this method, yet-to-be served hall calls are kept under management. If a new hall call occurs, the time for which the new hall call would wait until served is
20 calculated for each cage according to the predicted waiting time of each yet-to-be served hall call. Consequently, the new hall call is assigned to either a cage that requires the shortest waiting time or a cage that is not to serve a hall call which has long been
25 pendent. This control principle, determining call

assignment according to an evaluation function of predicted waiting time, provided an epoch-making control method in those days and has been inherited to the present elevator makers for group supervisory
5 control. However, this control has the following two problems:

1) Optimum cage assignment is determined based only on the yet-to-be served hall calls. Influence on future assignments is not taken into
10 consideration.

2) Assignment is made to a cage which minimize the evaluation function where no cage-to-cage spatial relation is considered. There is no concept of cooperation among the cages.

15 To solve these problems with the aforementioned assignment method using an evaluation function of predicted waiting time, a variety of control methods have so far been proposed. To be brief, their basic policies are to control the
20 respective cages so as to arrange them at temporally equal intervals. If the respective cages are not evenly distributed, that is, some is temporally distant from another, a hall call occurring between them is likely to wait long until served. If the respective
25 cages are arranged at temporally equal intervals, it is possible to prevent long waits. The conventional control methods which are aimed at temporally equal interval arrangement are listed below.

1) Equal interval-prioritized zone control
(disclosed in JP-A-1-226676)

2) Equal interval-prioritized zone/Inhibited
zone control (disclosed in JP-A-7-117941)

5 In each of these two methods, a priority zone
consisting of some served floors and an inhibited zone
of other served floors are set to each car. If a new
hall call occurs in the priority zone of a cage, the
evaluation value is manipulated so as to raise the
10 probability of the hall call being assigned to the
cage. In the case of a new hall call in the inhibited
zone, the evaluation value is manipulated so as to
lower the probability of assignment. This intends to
make the respective cages closer to a temporally equal
15 interval state.

3) Temporally equal interval-considered
assignment-evaluated control (disclosed in JP-B-7-
72059)

20 The position of each cage at a future point
of time is predicted. Accordingly, cage-to-cage
temporal intervals at that time are predicted. The
assignment limiting evaluation value is calculated from
this predicted cage-to-cage intervals. This evaluation
value is used to control assignments to prevent many
25 cages from being assigned to specific floors. This
intends to consequently make the cage-to-cage intervals
more temporally even.

4) Assignment correction by making service

availability time distribution uniform (disclosed in WO98/45204)

This basic concept is similar to the method 3). The arrangement of the respective cages at a
5 future point of time is predicted. From the predicted cage arrangement, the fastest time of arrival at each floor is calculated as the service availability time. Further, the service availability time distribution is calculated. The hall call assignment evaluation values
10 are corrected so as to make the service availability time distribution uniform. This intends to consequently make the service availability time constant not depending on the floor.

5) Position evaluation value-used assignment
15 method (JP-A-2000-118890)

In this method, a position evaluation value to prevent cages from clustering is calculated for each cage. Assignment to a hall call is determined using a position evaluation-included assignment evaluation
20 value. The position evaluation value of a cage is calculated based on the relation between its absolute position and the average absolute position of the other cages when the hall call is generated. This method also intends to evenly arrange the respective cages.

25 However, the above-listed prior art techniques do not substantially solve the problem of arranging the cages evenly to attain equal interval condition. Since cage-to-cage intervals/positioning

are evaluated only at one point of time, the
aforementioned prior art techniques are difficult to
stably keep the respective elevator cage in temporally
equal interval state over a long period of time.

5

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present
invention to allow cages to settle in temporally equal
interval state over a long period of time by solving
10 the problems of the prior art control techniques.

To attain the above-mentioned object, the
present invention provides a system comprising:
reference route generating means which, for each
elevator, generates a reference route which the
15 elevator should follow with respect to the time axis
and position axis; and assignment means which selects
an elevator for assignment to a generated hall call so
as to make the actual trajectory of each elevator
closer to the reference route of the elevator.

20 An elevator group supervisory control system
according to the present invention allows cages to
settle in temporally equal interval condition over a
long period of time since reference routes which guides
the cages into temporally equal interval condition are
25 generated and car assignment is executed so as to make
the respective cages follow their reference routes.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and advantages of the invention will become apparent from the following description of embodiments with reference to the accompanying drawings in which:

5 Fig. 1 shows the general control configuration of an elevator group supervisory control system according to an embodiment of the present invention;

10 Fig. 2 shows the control configuration of the target route preparation section in the first embodiment of the present invention;

 Fig. 3 shows the control configuration of a target route preparation section in a second embodiment of the present invention;

15 Fig. 4 shows the target route specification setting section 102;

 Fig. 5 shows the control configuration of the predicted route preparation section in an embodiment of the present invention;

20 Fig. 6 shows the control configuration of the predicted route preparation section in an embodiment of the present invention;

 Fig. 7 shows the control configuration of the route evaluation function calculating section in an embodiment of the present invention;

 Fig. 8 is a first diagram illustrating the control concept of an elevator group supervisory control system according to the present invention;

Fig. 9 is a second diagram illustrating the control concept of an elevator group supervisory control system according to the present invention;

Figs. 10A and 10B show the difference between
5 control according to the present invention and conventional control;

Figs. 11A and 11B show an example of target routes prepared in the first embodiment of the present invention;

10 Fig. 12 is a first diagram illustrating the target route preparation concept of the first embodiment of the present invention;

Fig. 13 is a second diagram illustrating the target route preparation concept of the first
15 embodiment of the present invention;

Figs. 14A and 14B show the process of preparing target routes in the first embodiment of the present invention;

Fig. 15 illustrates the concept of the
20 temporal phase value;

Figs. 16A and 16B show a first example of target routes prepared in the second embodiment of the present invention;

Figs. 17A and 17B show a second example of
25 target routes prepared in the second embodiment of the present invention;

Figs. 18A and 18B illustrate how the inter-route distance between a target route and predicted

route is calculated;

Fig. 19 is a flowchart showing the general control processing flows of an elevator group supervisory control system according to an embodiment
5 of the present invention;

Fig. 20 shows the flows of processing to prepare target routes;

Fig. 21 shows the flows of the predicted route preparation process A;

10 Fig. 22 shows the flows of the predicted route preparation process B;

Fig. 23 shows the flows of processing to calculate the route evaluation function; and

Fig. 24 is a flowchart of the target route
15 update judgment process.

DETAILED DESCRIPTION OF THE EMBODIMENTS

A first embodiment of the present invention will be described below with reference to the drawings. Figs. 1, 2, 4 through 9 and 11 through 15 each concern
20 the first embodiment.

Firstly, control images (principles of control) of an elevator group supervisory control system of the present invention is described based on Figs. 8 and 9. Fig. 8 is an example of a control image
25 concerning the elevator group supervisory control system in accordance with the present invention. Left in Fig. 8, a longitudinal (vertical) section of shafts

within a building is conceptually shown with elevator cars moving therein. Shown right in Fig. 8 is a diagram (generally called an operation diagram) which depicts the trajectory of each elevator car with the horizontal axis (A01) representing the time and the vertical axis (A02) representing the vertical position of a given floor in the building. In the example of Fig. 8, the elevator group supervisory control system controls two cars. Left in Fig. 8, the first car (given reference numeral 1) is going up after changing its direction at the first floor while the second car (given reference numeral 2) is going down from the second floor. This situation can be grasped by examining the operation diagram shown right in Fig. 8. To the left of the point representing the present time along the time axis, the first car (A03) and the second car (A04) were descending toward the landings of the first floor and second floor, respectively. That is, the actual trajectory of each car is shown to the left of the present time in the operation diagram of Fig. 8. That is, the actual trajectory of the first car is a trajectory A031 while the actual trajectory of the second car is a trajectory A041.

The present invention concerns the future trajectory of each car to the right of the present time along the time axis in the operation diagram. This represents a "target trajectory" which the car should follow after the present time. Hereinafter, this

target trajectory is denoted as a "target route". An elevator group supervisory control system according to the present invention is characterized in that the operation (to be precise, assignment) of each car is
5 controlled so as to follow the target route.

Specifically, A032 is the target route of the first car while A042 is the target route of the second car.

Introduction of these target routes or target (or reference) trajectories, which the respective cars
10 should be controlled to follow along the time axis, makes the present invention different from the conventional group supervisory control systems.

Fig. 9 depicts how an elevator car is decided to be assigned to a hall call according to the target
15 route. Basically identical to Fig. 8, the left side provides a vertical sectional view of the shafts showing the situation of the elevators while the right side provides an operation diagram. Firstly, assume that a new hall call demanding upward transportation
20 has occurred at the third floor (see the left diagram of Fig. 9). The group supervisory control assigns an appropriate car, the first car (B03) or the second car (B04). Here, give attention to the movement of the first car (B93). The target route of the first car is
25 trajectory B032. The predicted route (a trajectory predicted to be followed after the present time) of the first car is route B033 (predicted route 1) if the new hall call is not assigned or route B034 (predicted

route 2) if the new hall call is assigned. Group
supervisory control according to the present invention
tries to move each car so that its target route is
followed. Accordingly, since predicted route 1, that
5 is, the route predicted to be taken if the hall call is
not assigned is nearer to the target route, the hall
call is not assigned to the first car. Consequently,
the actual trajectory of the first car approximates to
the target route.

10 Although the effect of this control will
separately be described, the effect is essentially
derived by drawing the target routes so that the
respective elevator cars run at temporally equal
intervals. As a result of the actual trajectories of
15 the respective cars following the target routes, it is
possible in the long run to stably control the
respective cars so as to maintain the trajectories of
the respective cars at temporally equal intervals.

For example, in the case of Fig. 9, the
20 actual trajectory (B031) of the first car (B03) is
close to the actual trajectory (B041) of the second car
(B04), that is, they are run in a string-of-cars
condition until the present time. At this time, if a
new hall call demanding upward transportation,
25 generated at the third floor, is assigned to the second
car, the first car (B03) and the second car (B04) will
continue to be close to each other in a string-of-cars
condition. However, if the first car is controlled so

as to distance itself from the second car by following its target route designed to locate the respective cars at temporally equal intervals, that is, if the new hall call is not assigned to the first car (B03), the first
5 car will follow its target route aimed at the temporally equal interval condition.

Based on Figs. 8 and 9, the following summarizes what characterize the control principles of an elevator group supervisory control system in
10 accordance with the present invention.

1) As shown in Fig. 8, target routes which the respective cars should follow along the time axis are set.

2) As shown in Fig. 9, in order that the
15 respective cars follow their target routes, a hall call is assigned to a car which would come closer to its target route if the car serves the hall call based on the result of comparing the target routes with the predicted routes.

20 3) Consequently, each car runs so as to follow its target route.

4) Since the target routes are set so as to locate the trajectories of the respective cars at temporally equal intervals, the respective cars are
25 stably controlled in the long run to keep them in the temporally equal interval condition.

By using Fig. 1, the following describes how an elevator group supervisory control system in

accordance with the present invention is configured. While Fig. 1 depicts the control system configuration of an elevator group supervisory control system in accordance with the present invention, this control
5 system is implemented on a microcomputer, DSP (Digital Signal Processor), system LSI, computer (personal computer, etc.) or the like. Referring to Fig. 1, the following four components are key components: a target route preparation section 103, a predicted route
10 preparation section 104, a route evaluation function-used route evaluation function calculating section 105, and an assignment elevator selecting unit 2 within a target route control unit 101. Basically, target route-based control as described with Figs. 8 and 9 is
15 executed by these four components.

The following provides a detailed description of the control configuration of Fig. 1. Firstly, Fig. 1 is largely composed of: a plurality of elevators (42A, 42B and 42C); controllers (41A, 41B and 41C)
20 which respectively control these individual elevators (the first through Nth elevators); and a group supervisory control system 1 which collectively controls these elevators as one group. The controllers (41A, 41B and 41C) associated respectively with the
25 individual elevators or the first through Nth elevators control the positions and velocities of their elevators based on the hall calls assigned to elevators and the car call information derived from the hall calls.

The function of the group supervisory controller 1 is to determine which car is the most appropriate for a generated hall call based on the information regarding each elevator (position, moving
5 direction, already assigned hall call, derived car call, hall call waiting time, etc.) and assign the hall call to the car. This function is described below in detail.

In the target route control unit 101, a
10 target route specification setting section 102 sets specifications for target routes based on the information from a traffic data unit 7. This will be described later in detail. Basically, trajectories that keep the respective elevators at temporally equal
15 intervals are set as these specifications. The traffic data unit 7 outputs the latest information about traffic within the building (statistical information about elevator-used human traffic).

The target route preparation section 103
20 generates target routes (such as A032 and A042 in Fig. 8) for the respective elevator cars. As input data, this target route preparation uses: hall call information (information about hall calls assigned to the respective cars) obtained from a hall call data
25 unit 8; car call information (information about car calls assigned to the respective cars) obtained from a car call data unit 9; traffic information obtained from the traffic data unit 7; average stop frequencies (for

example, how many times an elevator is expected to stop during ascent or descent) obtained from an average stop frequency data unit 5; stoppage time information (for example, average stoppage time per stop) obtained from
5 a stoppage time data unit 6; each elevator car's rated velocity and other specification information obtained from an individual car specification data unit 11; available car count/name information (indicating how many and which cars can be controlled as a group at
10 that time or in that period) obtained from an available car count/name data unit 12; service floor information (information about which floors can be served at that time or in that period) obtained from a service floor data unit 13; and predicted route information obtained
15 from the predicted route preparation section 104. Note that since the average stop frequency and stoppage time of each elevator depends on the current traffic within the building (for example, the elevator is expected to have longer stops at the beginning of office hours),
20 the average stop frequency data unit 5 and the stoppage time data unit 6 are configured to receive traffic information from the traffic data unit 7. By using such detailed information about the traffic in the building and the situation of the elevators, it is
25 possible to set more appropriate target routes. The target route preparation method will be described later in detail.

In the predicted route preparation section

104, predicted routes are prepared for each car.
Predicted route 1 (B033) and predicted route 2 (B034)
shown in Fig. 9 are specific examples. A predicted
route of a car is a predicted trajectory that the car
5 may follow from the present time. Like when target
routes are prepared, the predicted route preparation
uses the following input data: hall call information
obtained from the hall call data unit 8; car call
information obtained from the car call data unit 9;
10 traffic information obtained from the traffic data unit
7; average stop frequencies obtained from the average
stop frequency data unit 5; stoppage time information
obtained from the stoppage time data unit 6; each
elevator car's specification information obtained from
15 the individual car specification data unit 11;
available car count/name information (indicating how
many and which cars can be run at that time or in that
period) obtained from the available car count/name data
unit 12; service floor information (information about
20 which floors can be served at that time or in that
period) obtained from the service floor data unit 13;
and provisional assignment information from a
provisional assignment car setting unit. In this
control system, accurate prediction is one of the
25 important points. This can be realized by using
detailed information about the traffic in the building
and the condition of the elevators as mentioned above.
How to prepare predicted routes will be described later

in detail.

In the route distance index-used route evaluation function calculating section 105, 'nearness' between a target route and a predicted route is
5 evaluated for each car by a route distance index-used route evaluation function. In determining which car to assign to a hall call, use of this route evaluation function makes it possible to select an elevator car whose predicted route to be taken by the car if
10 assigned to the hall call is closer to its target route. In the example of Fig. 9, the route distance index is an index to quantify the nearness between the first car's target route (B032) and predicted route (B033 or B034). The route distance index and the route
15 evaluation function will be described later in detail.

A waiting time evaluation value calculating unit 15 calculates an evaluation value for each car based on the time for which a hall call is predicted to wait if assigned to the car. For example, the
20 evaluation value for a car assigned provisionally to a newly generated hall call may directly be the time for which the hall call is predicted to wait. Likewise, the largest of the times for which all hall calls already assigned to the car are respectively predicted
25 to wait may be set as the evaluation value for the car.

In a total evaluation value calculating unit 14, a waiting time evaluation value calculated by the waiting time evaluation value calculating unit 15 is

weighted and added to a route evaluation function value calculated by the route distance index-used route evaluation function calculating section 105 to calculate a total evaluation value. Using $\Phi R(k)$,
5 $\Phi W(k)$, WC and $\Phi T(k)$ to respectively denote the route evaluation function value, waiting time evaluation value, weighting factor and total evaluation value, the total evaluation value $\Phi T(k)$ is given by the following equation.

10
$$\Phi T(k) = \Phi W(k) + \Phi R(k) \times WC \quad \dots (A)$$

Where, k means the car is the k-th car. The weighting factor WC is varied depending on the traffic condition at that time. For example, when the building is deserted (midnight, early morning, etc.), the WC value
15 is made smaller since hall calls do not frequently occur and it is therefore appropriate to give greater importance to the waiting time evaluation value than to the route evaluation value. On the other hand, when the building is crowded, the WC value is made larger
20 since hall calls occur frequently and target route-based control is effective. By using the total evaluation value as given by equation (A), it is possible to change the relation of priority between waiting time-based evaluation and target route-based
25 evaluation for assignment depending on the traffic condition.

Based on the total evaluation values calculated for the respective cars by the total evaluation value calculating unit 14, the assignment elevator selecting unit 2 determines which car is to be
5 assigned to the hall call.

Through the operation of each component of the control configuration described with Fig. 1, it is possible to implement the target route-based control principle described with Figs. 8 and 9. To be
10 accurate, Figs. 8 and 9 focus on the operation of target route control unit 101 and the operation of the waiting time evaluation value calculating unit 15 is omitted therein.

The following describes the general
15 processing flows of the target route-based group supervisory control with reference to the flowchart of Fig. 19. Firstly, an input information update process (ST101) updates input information and data as the latest input information required for control. The
20 input information and data include: hall call information (input from the hall call data unit 8 of Fig. 1), car call information (input from the car call data unit 9 of Fig. 1), car information (input from the car information data unit 10 of Fig. 1), traffic
25 information (input from the individual car's specification data unit 11 of Fig. 1), traffic information-dependent average stop frequencies (input from the average stop frequency data unit 5 of Fig. 1),

traffic information-dependent stoppage times (input
from the stoppage time data unit 6 of Fig. 1),
available car count/names (input from the available car
count/name data unit 12 of Fig. 1) and serviced floors
5 (input from the service floor data unit 13 of Fig. 1).
Note that although Fig. 19 conveniently indicates that
all the above information is entered at a time by the
input information update process, it is also possible
to enter the information in steps as necessary. For
10 example, the information is entered in several places
in the general flow of Fig. 19. It is also possible to
enter some of the information at a time and another at
another time. Also note that each elevator car's rated
speed and other specification information (obtained
15 from the individual car's specification data unit of
Fig. 1) is set as constants which are determined
depending on the building where the elevators are
installed. In the subsequent target route
specification setting process (ST102), a target route
20 specification is set through the operation of the
target route specification setting section 102 of Fig.
1. Basically, a temporally equal interval state is set
as this specification. In a target route preparation
process (ST103), target routes are prepared according
25 to the set target route specification through the
operation of the target route preparation section 103
of Fig. 1. In a predicted route preparation process A
(ST104), predicted routes are prepared through

operation of the predicted route preparation section 104 of Fig. 1. Then, if car assignment processing is invoked due to the detection of a newly generated hall call (ST105), a series of car assignment processes

5 shown below the conditional branch is executed. The following describes the car assignment process flow. Here, provisional assignment of each car to the hall call is executed by loop processing. In Fig. 19, this loop is named a "provisional car assignment loop"

10 (ST106). In the provisional car assignment loop (ST106), the variable k_a which means the k_a -th car is incremented one by one from 1 to N so that each elevator car is given the provisional car assignment processing in a loop form. The provisional assignment

15 setting unit 3 of Fig. 1 executes the provisional assignment process noted above. Within the loop, a predicted route preparation process B (ST107) is executed at first. This process prepares a predicted route which the k_a -th car would take if assigned to the

20 hall call (whereas provisional assignment is not considered in the predicted route preparation process A (ST104)). This process is executed by the predicted route preparation section 104 of Fig. 1 (Information about the provisionally assigned car is obtained from

25 the provisional assignment setting unit 3). Then, the route evaluation function is calculated for the provisionally assigned k_a -th car ($k_a = 1$ to N) by using the prepared predicted route of the k_a -th car (ST108).

The route evaluation function is an index that basically represents the closeness between the target route and the predict route and its calculation is executed by the route evaluation unction-used route evaluation function calculating section 105 of Fig. 1. Then, a waiting time evaluation value is calculated based on the predicted waiting time of the hall call for the provisionally assigned ka-th car (ST 109). The waiting time evaluation value for the ka-th car may directly be the time for which the hall call is predicted to wait for the ka-th car if assigned. Likewise, the largest of the times for which all hall calls already assigned to the ka-th car are respectively predicted to wait may be set as the evaluation value for the ka-th car. By weighted summation of the route evaluation function value and waiting time evaluation value calculated by the above-mentioned processes, a total evaluation value is calculated (ST110) as given by equation (A). The provisional car assignment loop processing mentioned so far is repeated until the loop is terminated (with $K_a = N$) (ST111). Consequently, N total evaluation values (N: the number of cars under group supervisory control) are obtained as a result of provisionally and sequentially assigning the hall call to the respective cars by incrementing ka from 1 to N. In an assignment elevator selecting process, the most appropriate car is selected for assignment based on the N total evaluation

values (ST112). This process is executed by the elevator selecting unit 2 of Fig. 1. By following the flowchart of Fig. 19 described so far, it is possible to provisionally and sequentially assign the respective
5 elevator cars to a newly generated hall call, evaluate the nearness between the predicted route and target route of each car by a route evaluation function, calculates a total evaluation value for each car by adding a waiting time-based index to the nearness
10 evaluation value and, for actual assignment, select the most appropriate car, namely the car given the best total evaluation value (lowest evaluation value) when assigned provisionally.

The control system configuration of the
15 elevator group supervisory control system shown in Fig. 1 includes the target route control unit 101 comprising: 1) the target route preparation section (103 of Fig. 1), 2) the predicted route preparation section (104 of Fig. 1), 3) the route evaluation
20 function calculating section (105 of Fig. 1) and 4) the target route specification setting section (102 of Fig. 1). The following provides a detailed description of how these components operate.

At first, with reference to Figs. 2 and 11
25 through 16, a detailed description is made of what is done in the route preparation section, one of the most importance components in the present invention. Fig. 2 shows an example of the configuration of the target

route preparation section. In Fig. 2, the configuration of the target route preparation section is largely composed of four components: 1) a target route update judgment block (103A of Fig. 2), 2) a
5 current temporal phase value calculating block (103B of Fig. 2), 3) an individual car's temporal phase value adjustment amount calculating block (103C of Fig. 2) and 4) an adjusted route preparation block (103D of Fig. 2).

10 At first, the following describes the operations of the four components described above in order to provide a general control image. In the target route update judgment block (103A of Fig. 2), it is judged whether the current target route is to be
15 updated. If it is judged that the target route is to be updated, the subsequent current temporal phase value calculating block (103B of Fig. 2) evaluates the temporal relation among the current predicted routes of the respective elevator cars by calculating the
20 temporal phase value of each predicted route as an index. Using the concept of "phase" is reasonable if, for example, three-phase alternating sinusoidal waveforms are considered in electrical circuit theory. The respective waveforms are evenly separated from each
25 other when the waveforms are separated from each other by $2\pi/3$ (rad) in phase. That is, considering the route of each car as a waveform and using a "phase-like index" for it makes it easier to evaluate the route-to-

route intervals of the respective cars. This "phase-like index" corresponds to what is called the temporal phase value used in the present invention as an index. The temporal phase value will be described later in
5 detail. After the current temporal phase values are calculated in the current temporal phase value calculating block (103B in Fig. 2), the individual car's temporal phase value adjustment amount calculating block (103C in Fig. 2) calculates
10 adjustment amounts to make the temporal phase values distributed evenly. Based on the thus calculated adjustment amounts, the adjusted route preparation block (103D in Fig. 2) adjusts the temporal phase values of the predicted routes of the respective cars.
15 The routes obtained as a result of this adjustment become the target routes of the respective cars.

With reference to an operation image of Figs. 11A and 11B, the following describes the general operation of the control configuration described above.
20 Figs. 11A and 11B illustrate an operation image of the target route preparation process executed by the target route preparation section shown in Fig. 2. At first, a description will be made of the control operation image based on the above general description of the control
25 (Figs. 11A and 11B will be described later in further detail.) The graph (target route profiles before adjusted) of Fig. 11A corresponds to the current predicted routes of the respective cars based on which

target routes are prepared as described with Fig. 2. Here, the elevator group supervisory control system is assumed to control three cars. In Fig. 11A, the first car (C010), second car (C020) and third car (C030) are
5 now on the present time axis (C050) and descending from the eighth floor, third floor and fourth floor, respectively. The predicted routes (predicted trajectories) of these three cars beyond the present time are respectively drawn by a solid line (C011) for
10 the first car, a chain line (C021) for the second car and a broken line (C031) for the third car. The predicted route preparation method will be described as part of the description of the predicted route preparation section. As shown, since these
15 trajectories are close to each other, the cars are to some extent in a string-of-cars condition. Referring back to the control configuration of the target route preparation section in Fig. 2, if it is judged by the target route update judgment block (103A in Fig. 2) to
20 update the target routes, the current temporal phase value calculating block (103B in Fig. 2) calculates the temporal phase values of the predicted routes (C011, C021 and C031) of the respective cars by regarding these routes as waveforms of a kind. These temporal
25 phase values are calculated at points where the predicted routes of the respective cars intersect the adjustment reference time axis (C040) in the graph of Fig. 11A. Then, based on these temporal phase values,

adjustment amounts to make the respective predicted routes distributed evenly are calculated in the individual car's temporal phase value adjustment amount calculating block (103C in Fig. 2). In Fig. 11A, three
5 black circle points on the adjustment reference time axis (C040) are for these adjustment amounts. For example, the point C01A reflects the adjustment amount for the first car. The predicted route (C011 in Fig. 11A) of the first car is adjusted by the subsequent
10 process so as to go through this point (C01A). Likewise, the predicted route (C021 in Fig. 11A) of the second car and the predicted route (C031 in Fig. 11A) of the third car are respectively adjusted by the subsequent process so as to go through the point C02A
15 and point C03A. This process is executed by the adjusted route preparation block 103D in Fig. 2 to prepare new target routes by adjusting the predicted routes based on the adjustment amounts. This results in trajectories shown in Fig. 11B. Fig. 11B shows the
20 new target routes prepared based on the predicted routes shown in Fig. 11A. The target routes of the three cars (C010, C020 and C030 in Fig. 11B) are respectively drawn by a solid line (C011N) for the first car (C010), a chain line (C021N) for the second car
25 (C020) and a broken line (C031N) for the third car (C030). The trajectories of the target routes are characterized in that they are drawn so as to guide the cars into the temporally equal interval condition as

shown in Fig. 11B. Specifically, beyond the adjustment reference axis (C040) in Fig. 11B, the target routes of the three cars are in a temporally equal interval condition. In the area (titled Adjustment Area in Fig. 5 11B) sandwiched between the axis (C050) representing the present time and the adjustment reference time axis (C040), the trajectories of the respective cars are drawn so as to guide the cars into the temporally equal interval condition. Based on the predicted routes 10 shown in Fig. 11A, it is possible to prepare these routes (target routes shown in Fig. 11B) by adjusting the respective routes so as to go through the points (C01A, C02A and C03A in Figs. 11A and 11B) obtained by the adjustment amounts. This preparation method will 15 be described again later in detail. Before that, the following summarizes the basic concept of the target route preparation method with reference to Figs. 12 and 13.

Figs. 12 and 13 represent the basic concept 20 of how to prepare target routes unique to the present invention. Firstly, a description is made of what is shown in Fig. 12. Fig. 12 is provided to describe the concept of the adjustment area-based target route preparation method. In the graph of Fig. 12, the 25 horizontal axis represents the time while the vertical axis represents the position of a given floor in the building. The graph is divided by the adjustment reference time axis (D04) into two areas. Of them, the

left area is the adjustment area. As briefly described with Fig. 11B, the adjustment area is sandwiched between the time axis (D03) representing the present time and the adjustment reference time axis (D04). As
5 shown in Fig. 12, this area is used as a transient state area, that is, an area for transition to an ideal temporally equal interval state. The subsequent area (D02) beyond the adjustment reference time axis is a steady state area, that is, an area where the cars are
10 to settle in the ideal temporally equal interval state. Thus, a transient state is generated in the adjustment area so as to guide the cars into the ideal state in the steady state area (D02). Fig. 13 depicts the concept of using the adjustment area to control the
15 target routes. This figure shows the processes that prepare target routes by using the adjustment area. As already described briefly with Fig. 2, target routes are prepared by four processes: 1) drawing the current predicted routes (ST701 in Fig. 13), 2) calculating the
20 current temporal phase values of the respective cars on the adjustment reference time axis (ST702), 3) based on the current temporal phase values, calculating adjustment amounts to make the respective cars come at temporally equal intervals (ST703) and 4) obtaining
25 target routes by adjusting the predicted route grids in the adjustment area according to the adjustment amounts (ST704). Thus, target routes, key to the present invention, are prepared by the four basic processes

shown in Fig. 13 according to the basic concept described with Fig. 12.

The description has been made of the basic components concerning the preparation of target routes, their general operations and the basic preparation concept and processes.

A detailed description is made of how target routes are prepared with reference to Figs. 2, 11, 14 and 15. At first, a description will be made of the internal components of the target route preparation section shown in Fig. 2. The current temporal phase value calculating block (103B in Fig. 2) comprises an initial route preparation part (103B1), an adjustment reference time axis setting part (103B2), an adjustment reference time axis-based individual car's temporal phase value calculating part (103B3) and a temporal phase value sorting part (103B4). In the initial route preparation part (103B1), the current predicted routes of the respective cars are prepared as the initial routes. These initial routes correspond to the pre-adjustment target route profiles shown in Fig. 11A. In the adjustment reference time axis setting part (103B2), an adjustment reference time axis is set. In the adjustment reference time axis-based individual car's temporal phase value calculating part (103B3), the temporal phase values of the respective cars are calculated on the adjustment reference time axis. With reference to Fig. 15, the following describes the

temporal phase value in detail. In Fig. 15, the horizontal axis of the graph represents the temporal phase value while the vertical axis represents the position of a given floor in the building. The graph shown in Fig. 15 indicates a predicted route of an elevator car on the assumption that this predicted route is given by a periodic function with a period of T . For example, the predicted route (C011 in Fig. 11A) of the first car in Fig. 11A corresponds to this route. As shown, the predicted route (C011 in Fig. 11A) of the first car in Fig. 11A is given by a periodic function. The graph of Fig. 15 shows one period of this predicted route given by a periodic function. Starting at the lowest floor, this one-period has a car-ascending segment (G01 in Fig. 15) and a car-descending segment (G02 in Fig. 15), making one round in the building. Here, the phase is considered as the floor position. Accordingly, when the car is at the lowest floor, the phase is considered 0 or 2π (rad). Likewise, when the car is at the highest floor, the phase is π (rad). In addition, similar to a sinusoidal wave, the phase is considered positive in polarity when the phase is between 0 and π (the car is ascending) whereas negative when the phase is between π and 2π (the car is descending). When the phase is π (at time $T\pi$ in Fig. 15), since the polarity of the phase changes from positive to negative, this point of time is named the turnaround temporal phase $T\pi$. In addition, $y_{\max}$ is

used to mean the position of the highest floor. Under these assumed conditions, the temporal phase value t_p ($0 \leq t_p < T$) of a given point of a predicted route is defined by the following equation.

5 $t_p = (T\pi/y_{\max}) \times y$ (car ascending: $0 \leq t_p < T$) ... (1)

$$t_p = -\{(T - T\pi)/y_{\max}\} \times y + T$$

(car descending: $T\pi \leq t_p < T$) ... (2)

Where, the amount y is represented by the floor axis and means the car's predicted floor position. For
10 example, the temporal phase value t_p of a predicted route point (G03 in Fig. 15) whose position is y can be calculated according to equation (1) $(T\pi/y_{\max}) \times y$. Temporal phase value t_p is characterized in that the amount of phase of any route point can be evaluated
15 uniquely since dimensional conversion is made from phase to time. Thus, by using temporal phase values, it is possible to easily evaluate the degree of temporal equality of intervals among the predicted routes of the respective cars.

20 Returning to Fig. 2, in the adjustment reference time axis-based individual car's temporal phase value calculating part (103B3) of the current temporal phase value calculating block (103B in Fig. 2), the temporal phase values of points at which the
25 predicted routes of the respective cars intersect the

adjustment reference time axis are calculated by using equation (1) or (2). Figs. 14A and 14B show how a target route is prepared. To facilitate understanding, only one car (2nd car) is picked up in this figure. In 5 Fig. 14A, the predicted route (C021 in Fig. 14A) is shown as a pre-adjustment target route profile. This predicted route is prepared in the initial route preparation part (103B1 in Fig. 2). The adjustment reference time axis (C040) in Fig. 14A is set in the 10 adjustment reference time axis setting part (103B2 in Fig. 2). The temporal phase value t_p of the predicted route of the second car on this adjustment reference time axis (C040 in Fig. 14A), or the temporal phase value t_p of a point (C060 in Fig. 14A) where the 15 predicted route of the second car intersects the adjustment reference time axis is calculated by the adjustment reference time axis-based individual car's temporal phase value calculating part (103B3 in Fig. 2). In the case of the intersecting point C060 in Fig. 20 14A, since the car is ascending (between 0 (rad) and Π (rad) in phase), the temporal phase value t_p can be calculated from the car's predicted position y according to equation (1). Here, the period T can be obtained from the following data: the number of stories 25 of the building, width per story, car's rated speed and current traffic-dependent average stop frequency and stoppage time. Likewise, the turnaround temporal phase T_n can also be obtained from the above-mentioned data.

The highest floor's position $y_{\max}$ is a fixed value dependent on the building. Referring back to Fig. 2, after the temporal phase values of the respective cars are calculated by the adjustment reference time axis-based individual car's temporal phase value calculating part (103B3 in fig. 2), these temporal phase values of the respective cars are sorted into the increasing order of phase by the temporal phase value sorting part (103B4 in Fig. 2). Hereinafter, this order is denoted as increasing phase order. As described with Fig. 15, the temporal phase value tp of each car is defined during one period of the waveform. In Fig. 15, the more the waveform is advanced, the larger its temporal phase value becomes. On the other hand, adjustment is made so that $0 \leq tp(k) < T$ is met by tp . For example, consider the pre-adjustment target route profiles (or predicted routes) of three cars in Fig. 11A. According to the points at which the predicted routes (C011, C021 and C031 in Fig. 11A of the respective cars intersect the adjustment reference axis (C040 in Fig. 11A), the third car has the smallest temporal phase value, followed by the second car and then the first car in increasing phase order. This order is determined in the temporal phase value sorting part (103B4 in Fig. 2) by using a sorting algorithm (for example, selection sort, bubble sort or the like). Based on the calculated temporal phase values of the respective cars and their increasing phase order, the adjustment amount

calculating block (103C of Fig. 2) calculates the car-to-car interval of each car in terms of temporal phase, compares this temporal phase value with a reference value for equal intervals and calculates their

5 difference as the adjustment amount for the temporal phase value of the car. The basic concept is to calculate the car-to-car interval (in terms of temporal phase) of each car from the predicted routes, compare it with a reference value for equal intervals and

10 calculate their difference as the amount for adjustment. Taking the case of Fig. 11A, the following describes how the individual car's temporal phase value adjustment amount calculating block (103C in Fig. 2) operates. In Fig. 11A, as described earlier, the third

15 car comes first, followed by the second car and the first car in increasing phase order according to the temporal phase values of the predicted routes (C011, C021 and C031 in Fig. 11A) of the respective cars on the adjustment reference time axis (C040 in Fig. 11A).

20 If one period of each predicted route is given by T (common to the three cars), the temporal phase value $tp(k)$ of the k -th car is: $tp(3) = 0.09T$ for the third car, $tp(2) = 0.17T$ for the second car and $tp(1) = 0.77T$ for the first car. The respective car-to-car intervals

25 are calculated in increasing phase order. The result is $tp(2) - tp(3) = 0.08T$ for the second-to-third car interval, $tp(1) - tp(2) = 0.6T$ for the first-to-third car interval and $tp(3) - tp(1) + T = 0.32T$ for the

third-to-first car interval. Thus, the respective car-to-car intervals can be evaluated quantitatively using the temporal phase values. That is, it is found from the result that the second and third cars are very
5 close to each other. Since one period is T , the target car-to-car interval to run the cars in a temporally equal interval condition is given by T/N if N cars are collectively controlled. In the case of Fig. 11A, the target interval is $T/3 = 0.33T$ since three cars are
10 collectively controlled. The difference between this target interval and the current car-to-car interval should be eliminated by adjustment. For instance, the second-to-third car interval should be corrected by $+0.25T (= 0.33T - 0.08T)$, the first-to-second car
15 interval should be corrected by $-0.27T (= 0.33T - 0.6T)$ and the third-to-first car interval should be corrected by $+0.01T (= 0.33T - 0.32T)$. In this context, the positive sign means to increase the interval (widen the current interval toward the target) whereas the
20 negative sign means to decrease the interval (narrow the current interval toward the target). Based on these correction values for adjusting the intervals, correction values for the temporal phase values of the respective cars are calculated. This is possible by
25 using the following algorithm. For example, assume that three cars, car A, car B and car C in increasing phase order, are collectively controlled (for generalization, here, each car is given an alphabetic

name). Therefore, $0 \leq tp(A) \leq tp(B) \leq tp(C) < T$ is met. Here, let us denote the temporal phase time of a given car by $\Delta tp(k)$ (k means car k). For each car-to-car interval to become equal to the target interval $T/3$ after adjustment, the following equations must be met.

$$(tp(B) + \Delta tp(B)) - (tp(A) + \Delta tp(A)) = T/3 \quad \dots (3)$$

$$(tp(C) + \Delta tp(C)) - (tp(B) + \Delta tp(B)) = T/3 \quad \dots (4)$$

$$(tp(A) + \Delta tp(A)) - (tp(C) + \Delta tp(C)) + T = T/3 \quad \dots (5)$$

In equation (3), the adjusted temporal phase value is given by $tp(B) + \Delta tp(B)$ where the current temporal phase value is given by $tp(B)$. Accordingly, equation (3) indicates that the difference between the adjusted temporal phase value of car B and the adjusted temporal phase value of car A, or the interval between them, must be $T/3$. Since the above three equations are not independent of each other, only these three equations can not be solved for $\Delta tp(A)$, $\Delta tp(B)$ and $\Delta tp(C)$. Therefore, another condition is added. This condition is that the center of gravity of the distributed cars must not change after they are adjusted. This condition is expressed in terms of the temporal phase value of each car by the following equation.

$$\begin{aligned} (tp(A) + tp(B) + tp(C))/3 = \{ & (tp(A) + \Delta tp(A)) + \\ & (tp(B) + \Delta tp(B)) + \\ & (tp(C) + \Delta tp(C)) \} / 3 \\ & \dots (6) \end{aligned}$$

5 Equation (6) can be simplified to equation (7) below.

$$\Delta tp(A) + \Delta tp(B) + \Delta tp(C) = 0 \quad \dots (7)$$

Solving equations (3), (4), (5) and (7) for $\Delta tp(A)$, $\Delta tp(B)$ and $\Delta tp(C)$ results in the following equations.

$$\begin{aligned} \Delta tp(A) = & (-2/3)tp(A) + (1/3)tp(B) + \\ 10 & (1/3)tp(C) + (-1/3)T \quad \dots (8) \end{aligned}$$

$$\begin{aligned} \Delta tp(B) = & (1/3)tp(A) + (-2/3)tp(B) + \\ & (1/3)tp(C) \quad \dots (9) \end{aligned}$$

$$\begin{aligned} \Delta tp(C) = & (1/3)tp(A) + (1/3)tp(B) + \\ & (-2/3)tp(C) + (1/3)T \quad \dots (10) \end{aligned}$$

15 In summary, when the temporal phase values $tp(A)$, $tp(B)$ and $tp(C)$ of three cars A, B and C meet the relation $0 \leq tp(A) \leq tp(B) \leq tp(C) < T$, correction values $\Delta tp(A)$, $\Delta tp(B)$ and $\Delta tp(C)$ to adjust the temporal phase values of the respective cars so as to put the
20 respective cars in a temporally equal interval state without changing the center of gravity of the

distributed respective cars can be obtained respectively according to equations (8), (9) and (10). In the case of Fig. 11A where the third, second and first cars correspond respectively to cars A, B and C, 5 $tp(A) = tp(3) = 0.09T$, $tp(B) = tp(2) = 0.17T$ and $tp(C) = tp(1) = 0.77T$. Accordingly, as the correction values for the respective cars, $\Delta tp(A) = \Delta tp(3) = -0.081T$, $\Delta tp(B) = \Delta tp(2) = 0.177T$ and $\Delta tp(C) = -0.096T$ are obtained according to equations (8), (9) and (10). For 10 verification, the adjusted temporal phase values of the respective cars are calculated. The result is $tp(A) + \Delta tp(A) = tp(3) + \Delta tp(3) = 0.010T$, $tp(B) + \Delta tp(B) = tp(2) + \Delta tp(2) = 0.343T$ and $tp(C) + \Delta tp(C) = tp(1) + \Delta tp(1) = 0.677T$. All car-to-car intervals are 15 therefore $0.33T$, meeting the interval-equalizing requirement. Referring back to Fig. 2, the following provides a detailed description of how the adjusted route preparation block (103D of Fig. 2) operates to prepare adjusted routes by using the correction values 20 obtained in the individual car's temporal phase value adjustment amount calculating block (103C in Fig. 2). At first in the adjusted route preparation block, correction values to adjust the grids of the pre-adjustment target routes (corresponding to the 25 predicted routes) of the respective cars are calculated by the individual car's route grid adjustment amount calculating part (103D1 in Fig. 2). Grids are shown in Fig. 14A. To facilitate understanding, Fig. 14A shows

the pre-adjustment target route (corresponding to the predicted route) of the second car alone. A grid is defined as a turnaround point of a route of concern within the adjustment area. In Fig. 14A, three

5 turnaround points C022, C023 and C024 of the pre-adjustment target route (C021) are grids (restricted to these three turnaround points within the adjustment area). The temporal phase of the route of concern can be adjusted by changing the horizontal positions of

10 these grids. The grid adjustment values are determined one by one for the grids in temporal order starting from the grid nearest to the present time. The grid adjustment values must amount in total to the adjustment value determined for the car. Each grid is

15 given the largest adjustment value which does not exceed a limiter value set to the grid by the grid limiter value setting part (103D2 in Fig. 2). Taking the case of Fig. 14A, the following describes this method. $\Delta g_{tp}(k = 2, i = 1, 2, 3)$ is used to denote a

20 adjustment value to be given to a grid. Here, k means the number of the car ($k = 2$ for the second car) whereas i means the number of the grid. The grids, in temporal order from the present time forward, are given increasing numbers. In addition, $L\Delta g_{tp}(k = 2, i = 1,$

25 $2, 3)$ is used to denote the limiter value set as the maximum adjustment value allowed for the grid. The temporal phase adjustment value for the second car, $tp(2) + \Delta tp(2) = 0.343T$ as calculated above, is

distributed as $\Delta gtp(k = 2, i = 1)$, $\Delta gtp(k = 2, i = 2)$ and $\Delta gtp(k = 2, i = 3)$ which do not exceed the respective limiter values. For example, if the limiter values of the respective grids are $L\Delta gtp(k = 2, i = 1) = 0.2T$, $L\Delta gtp(k = 2, i = 2) = 0.2T$ and $L\Delta gtp(k = 2, i = 3) = 0.1T$, the adjustment value for the first grid, $\Delta gtp(k = 2, i = 1)$, is set to $0.2T (= L\Delta gtp(k = 2, i = 1); \text{limiter value})$ at first. The remaining required temporal phase adjustment is $0.343T - 0.2T = 0.143T$. Then, the adjustment value for the second grid, $\Delta gtp(k = 2, i = 2)$, is set to $0.143T$. Since the remaining required temporal phase adjustment is zero, the adjustment value for the third grid, $\Delta gtp(k = 2, i = 3)$, is set to 0. Referring back to Fig. 2, the adjusted grid position calculating part (103D3 in Fig. 2) calculates the adjusted positions ($gp_N(k, i)$) of the respective grids from the adjustment values ($\Delta gtp(k, i)$) for the respective grids and the pre-adjustment positions ($gp(k, i)$) of the respective grids. For example, if the car is the second car ($k=2$) and there are three grids ($i=1, 2, 3$), the respective grids are located as given by the following equations.

$$gp_N(k=2, i=1) = gp(k=2, i=1) + \Delta gtp(k=2, i=1) \quad \dots (11)$$

$$\begin{aligned} gp_N(k=2, i=2) = & gp(k=2, i=2) + \\ & \Delta gtp(k=2, i=1) + \\ & \Delta gtp(k=2, i=2) \quad \dots \quad (12) \end{aligned}$$

$$\begin{aligned} gp_N(k=2, i=3) = & gp(k=2, i=3) + \\ & \Delta gtp(k=2, i=1) + \\ & \Delta gtp(k=2, i=2) + \\ & \Delta gtp(k=2, i=3) \quad \dots \quad (13) \end{aligned}$$

Since an adjustment value for a grid is effective to the subsequent grids, the position of the last grid is adjusted by the total temporal phase adjustment value required for the car. By connecting
5 the thus adjusted grid positions, it is possible to prepare a new target route. The target route data calculating part (103D4 in Fig. 2) updates the target route data by calculating new target data. In Fig. 14B, a route drawn by a thick line is the adjusted
10 target route prepared based on the pre-adjustment target route (corresponding to a predicted route) shown in Fig. 14A. In Fig. 14A, the pre-adjustment target route is drawn by a thin chain line (C021) whereas the adjusted target route is drawn by a thick chain line
15 (C021N). An adjusted grid position is calculated in the adjusted grid position calculating part (103D3 in Fig. 2). As a result of adjustment, the grid C022 is shifted to C022N. Likewise, the grids C023 and C024

are shifted respectively to C023N and C024N. By connecting these three grids, it is possible to draw the thick chain line route (C021N) as a newly updated target route. As apparent from Fig. 14B, the newly
5 updated target route (adjusted target route) goes through the post-adjustment target point set according to the temporal phase adjustment value. As shown in Fig. 11B, since the routes of the respective cars are adjusted so as to go through their post-adjustment
10 target points as described above, the resultant target routes (C011N, C021N and C031N) are in temporally equal interval state after the adjustment reference time axis (C040 in Fig. 11B). As a matter of course, the respective routes (C011N, C021N, C031N) go through
15 their post-adjustment target points (C01A, C02A and C03A in Fig. 11B). It is also apparent that the target routes adjusted by the grids in the adjustment area play a transient role to guide the cars into a temporally equal interval condition beyond the
20 adjustment reference time axis. The foregoing has provided a detailed description of the target route preparation process based on Fig. 2.

With reference to the flowchart of the target route preparation process in Fig. 20, the following
25 describes the flows of the target route preparation process. At first, it is judged whether the target routes are to be updated (ST201). This step is executed by the target route update judgment block

(103A) in Fig. 2. If it is decided to perform no update as the result of the update judgment, control exits the process. If it is decided to perform update, control goes to the subsequent step. The update judgment method will be described later in detail with reference to Fig. 24. If it is decided to update the target routes, a car number loop (ST202) is executed to apply loop processing to each car. In the loop processing, a current temporal phase value calculating step is executed (ST203). This step is executed by the current temporal phase value calculating block (103B) described earlier with Fig. 2. When a current temporal phase value of the last car is calculated, control exits the car number loop (ST204). Then, a temporal phase adjustment value is calculated for each car (ST205). This is executed by the individual car's temporal phase value adjustment amount calculating block (103C) in Fig. 2. This processing is already described in detail. Based on the temporal phase adjustment values calculated for the respective cars, an adjusted route preparation step is performed for each car (ST207) by executing the car loop again (ST206). This adjusted route preparation step is executed by the adjusted route preparation block (103D) in Fig. 2. This processing is already described in detail as well. When the above-mentioned processing is performed for all cars, control exits the car number loop (ST208) to terminate the target route preparation

process.

With reference to the flowchart of Fig. 24, the following provides a detailed description of the target route update judgment process. Largely, target routes may be updated by three methods: 1) periodically updating the target routes at certain intervals; 2) detecting the distance between the target route and predicted route of each car (hereinafter, called the inter-route distance) and, if the inter-route distance exceeds a certain value, updating the target routes; and 3) a combination of methods 1) and 2). Of them, Fig. 24 corresponds to method 3). Either method 1) or method 2) may be executed by partly using method 3). At first, a watch or timer is examined to check if the predetermined update period has passed (ST601 in Fig. 20). If the update period has passed, the target route update processing is performed (ST606). This processing corresponds to the processing done by the components downstream of the target route update judgment block (103A in Fig. 2), or the processing which is done (by the ST202 and subsequent steps in Fig. 20) if the result of the update judgment (ST201) is YES. If the update period has not passed, loop processing is done through a car number loop (ST602 in Fig. 24) to calculate the distance (inter-route distance) between the target route and predicted route of each car and judges whether this distance is not smaller than a predefined threshold (ST603). The

distance (inter-route distance) between the target route and the predicted route is an index to indicate how the target route is distant from the predicted route. This will be described later in detail with
5 reference to Figs. 18A and 18B. In short, a predetermined threshold is used to judge whether the target route is so deviated from the predicted route as to require correction. If the inter-route distance of any one car is beyond the threshold (ST603), the target
10 route update processing is performed (ST606). The inter-route distance of each car is checked (ST606). If the inter-route distance of any car is smaller than the threshold, the current target routes are used without updating them (ST605). Two different policies
15 may be adopted in updating the target routes. One is to keep the target routes always appropriate by correcting them as necessary ('flexible target routes'). The other is not to change the target routes as long as possible once determined ('rigid target
20 routes'). Since either has both merits and demerits, it is reasonable to appropriately set the two control parameters, namely, the update period and inter-route distance threshold described with Figs. 18A and 18B.

The foregoing has provided a description of
25 the target route preparation method, the core of the target route-based elevator group supervisory control of the present invention. The following provides a description of how to prepare predicted routes which

are consulted in guiding the actual trajectories of the cars to the target routes.

How to prepare predicted routes is described below with reference to Figs. 5, 6, 19, 21 and 22.

5 Referring to Fig. 19, firstly note that predicted routes are prepared in two different cases. As already described, Fig. 19 is a flowchart showing the general control processing flows of an elevator group supervisory control system in accordance with the
10 present invention. In Fig. 19, there are two predicted route preparation processes: Predicted Route Preparation Step A (ST104 in Fig. 19) and Predicted Route Preparation Step B (ST107 in Fig. 19). The predicted route preparation step A prepares predicted
15 routes without assuming assignment to any hall call. In other words, only the current condition is reflected in the preparation of predicted routes. Such a predicted route is used to judge its distance from the target route and as a pre-adjustment target route or
20 the prototype (initial profile before adjustment) of a target route to be prepared. The other predicted route preparation step B prepares a predicted route of each car on the provisional assumption that the car is assigned. Such predicted routes are used to evaluate
25 provisional assignments, for example, when a new hall call occurs.

Referring to Fig. 6, the following firstly provides a description of how predicted routes are

prepared by the predicted route preparation step A described above. In Fig. 6, an estimated each floor arrival time calculating block 104B1 calculates the estimated times of arrival at the respective floors by
5 using: average stop frequency data and stoppage time data dependent on the current traffic condition; data on the hall calls assigned to the respective cars (hall call-generated floors, etc.); data on the car calls occurring in the respective cars (car call-generated
10 floors, etc.); car condition data (current position, direction, speed, etc.); each car's specification data (rated speed, etc.); available car count/name data; and service floor data (data on the floors to be served by the respective cars). As a simple example, assume that
15 a car of concern in a four-floor building is stopped at the first floor and is going to ascend. For simplification, it is assumed here that it takes 2 seconds per story for the car to move and the car waits 10 seconds per stop. In addition, it is assumed that
20 the car is assigned to a hall call generated at the second floor and a car call demanding transport to the fourth floor is generated (by a passenger who has entered the car at the first floor). The current traffic condition is normal with relatively heavy
25 inter-floor traffic. Accordingly, the average stop frequencies at the respective floors are assumed to be
- first floor (up): 0.25, second floor (up): 0.25,
third floor (up): 0.25, fourth floor (up): 0.25, fifth

floor (down): 0.25, fourth floor (down): 0.25, third floor (down): 0.25, second floor (down): 0.25. Here, an average stop frequency means the number of times the car stops at a given floor on the average during one
5 round trip in the building. Under these conditions, the estimated times of arrival at the respective floors are calculated - first floor (up): 0 sec, second floor (up): 2 sec, third floor (up): 14 sec, fourth floor (up): 18.5 sec, fifth floor (turnaround): 30.5 sec,
10 fourth floor (down): 35 sec, third floor (down): 39.5 sec, second floor (down): 44 sec and 0.25, first floor (turnaround): 48.5 sec. Reversely, these estimated times of arrival at the respective floors indicate the predicted positions of the car at given future times.
15 Accordingly, in a coordinate system where the horizontal axis represents the time while the vertical axis represents the floor position, a predicted route can be prepared by connecting the points each of which is plotted according to the estimated time of arrival
20 at the floor position. Taking the above case, $(t(\text{sec}), y(\text{floor}))$ points $(0, 1)$, $(2, 2)$, $(14.3, 3)$, $(18.5, 4)$, $(30.5, 5)$, $(35, 4)$, $(39.5, 3)$, $(44.2, 2)$ and $(48.5, 1)$ can be plotted in a coordinate system with a horizontal time axis (t axis) and a vertical floor position axis
25 (y axis). A predicted route can be prepared by connecting these points. Although stoppage times are omitted in this example, it is also possible to include stoppage times in drawing the predicted route. If

stoppage times are included by adding stop end points,
the predicted route is prepared more accurately.

Referring back to Fig. 6, a predicted route data
calculating block (104B2) prepares predicted route data
5 through the above-described procedure based on the
estimated times of arrival at the respective floors
calculated by the estimated each floor arrival time
calculating block (104B1). To summarize the procedure,
the estimated times of arrival at the respective
10 floors, considered as the predicted positions of the
car at future times, are plotted in a coordinate system
where the horizontal axis represents the time while the
vertical axis represents the floor position. A
predicted route is prepared by connecting the plotted
15 points. This predicted route can be regarded as a
function plotted in a coordinate system where the
horizontal axis represents the time while the vertical
axis represents the floor position. This function can
be expressed by $y = R(t, k)$ wherein t , y and k ($1 \leq k \leq$
20 N : N is the total number of cars) respectively denote
the time, the floor position and the number of the car.

Then, the following describes the flows of
processing done by the predicted route preparation step
A to prepare predicted routes with reference to Fig.
25 21. Firstly, it is judged whether predicted routes are
to be updated (ST301). Since updating the predicted
routes every time imposes a great load on the processor
consisting of a microcomputer or the like, this step

intends to update the predicted routes at such long intervals (for example, 0.5 sec) as not to cause a substantial load. If it is decided to perform no update as the result of the update judgment, control exits the process. If it is decided to perform update, control goes to the subsequent step. In this case, through a car number loop (ST302), an estimated each floor arrival time calculating step (ST303) and an estimated arrival time-based predicted route data calculating step (S304) are executed for each car. These steps are executed respectively by the estimated each floor arrival time calculating block (104B1) and predicted route data calculating block (104B2) in Fig. 6. These steps were already described in detail. When the above-mentioned processing is performed for all cars, control exits the process (ST305). In this manner, the predicted routes of all cars are appropriately updated at certain intervals. Although new hall calls and car calls occur irregularly, it is possible to apply proper predicted routes depending on the situation by following the flowchart of Fig. 21.

Fig. 5 shows the components of the predicted route preparation section which implement the predicted route preparation step B (ST107 in Fig. 19 to prepare assignment-considered predicted routes). Conceptually, the predicted route preparation step B is identical to the predicted route preparation step A of Fig. 6 except that each car is provisionally assigned and this

provisional assignment is reflected in the preparation of its predicted route. Specifically, if the k_a -th car is provisionally assigned to a new hall call, estimated times of arrival at the respective floors are

5 calculated (by an estimated each floor arrival time calculating block 104A1) from the provisional assignment information (provisionally assigned car (k_a -th car) and hall call-generated floor and direction) in addition to the input information required for the

10 preparation of an ordinary predicted route (information described with Fig. 6). Further, based on the result, predicted route data is calculated (by a predicted route data calculating block). Each predicted route obtained in this manner by reflecting a provisional

15 assignment can be expressed as a function $R(t, k_a)$ in a time-floor position coordinate system. For each car (other than k_a -th car) which is not provisionally assigned, the same process as the process described with Fig. 6 is done. Estimated times of arrival at the

20 respective floors are firstly calculated by the estimated each floor arrival time calculating block (104A3) and, based on the result, predicted route data is prepared by the predicted route data calculating block (104A4). Each predicted route obtained can be

25 expressed as a function $R(t, k) (1 \leq k \leq N, k \neq k_a)$.

Fig. 22 shows a flowchart of the predicted route preparation processing which corresponds to the above-described predicted route preparation step B.

Firstly, provisional assignment (hall call-generated floor, direction, etc.) information concerning a provisionally assigned ka-th car is obtained (ST401). Estimated times of arrival at the respective floors are
5 calculated based on the information (ST402) and predicted route data is calculated based on the estimated times of arrival at the respective floors (ST403). Then, a car number loop is executed (ST404) to calculate the estimated times of arrival at the
10 respective floors for each car excluding the provisionally assigned ka-th car (ST405). Further, based on the result, predicted route data is calculated (ST406). This process is terminated after executed for all cars excluding the ka-th car (ST406). Thus, it is
15 possible to prepare the predicted route of the provisionally assigned ka-th car and the predicted route of each k-th car not assigned provisionally ($1 \leq k \leq N, i \neq ka$).

The foregoing has provided a description of
20 how predicted routes are prepared. The following describes the inter-route distance, an index of nearness between a target route and a predicted route, and the route evaluation function which is used as an index in determining which car to assign. In the
25 conventional method, "assignment evaluation function" to quantitatively evaluate each assignment to a call is defined as a function of the predicted waiting time. The control method of the present invention is greatly

characterized in that "assignment evaluation function" is defined as a function of the quantity (inter-route distance) representing the target route-to-predicted route nearness instead of the predicted waiting time.

5 With reference to Figs. 18A and 18B, the following firstly describes the inter-route distance, an index to represent the nearness between a target route and a predicted route. Route distance calculation methods are shown in Figs. 18A and 18B. A
10 description is made of Fig. 18A at first. In the graph of Fig. 18A where the horizontal axis represents the time while the vertical axis represents the floor position, a target route $R^*(t, k)$ (where, t : time and k : car number of the car) is drawn as a trajectory F011
15 and a predicted route $R(t, k)$ is as a trajectory F012. From Fig. 18A, the area sandwiched by the target route and predicted route is considered the most appropriate index to indicate their nearness. Apparently, the area decreases as the two routes come closer to each other.
20 When the two routes agree with each other, the area is zero. Accordingly, the area sandwiched between the function $R^*(t, k)$ representing the target route and the function $R(t, k)$ representing the predicted route is defined as the inter-route distance. The area can be
25 obtained by integration. The integration may be done along either the time axis or the floor height axis. In Fig. 18A, the integration is done along the time axis. This integration is given by

$$\int \{R^*(t, k) - R(t, k)\} dt \quad \dots (14)$$

The area in the time range from the present time to the adjustment reference time axis, that is, the area in the adjustment area is obtained.

5 Accordingly, the area to be calculated is shown in Fig. 18A as vertical line-filled regions sandwiched between the target route $R^*(t, k)$ (F011) and the predicted route $R(t, k)$ (F012). $L[R^*(t, k), R(t, k)]$ is here used to denote the inter-route distance between the
10 target route and the predicted route. $L[R^*(t, k), R(t, k)]$ is given by the following equation.

$$L[R^*(t, k), R(t, k)] = \int \{R^*(t, k) - R(t, k)\} dt \quad \dots (15)$$

(integration interval = adjustment area)

15 In actual calculation by a microcomputer or the like, the above-described integration is realized approximately by adding up the areas of rectangles. For example, assume a rectangle (F013) of length Δt in the direction of the time axis, sandwiched between the
20 target route and the predicted route. ΔS is used to denote the area of this rectangle. ΔS is given by the following equation.

$$\Delta S = \{R^*(t, k) - R(t, k)\} \times \Delta t$$

Such a rectangle is cut out for every Δt over the adjustment area. The value of equation (15) can be calculated approximately by adding up the areas of such rectangles. This method can be expressed by the
5 following equation.

$$L[R^*(t, k), R(t, k)] = \sum \Delta S = \sum \{R^*(t, k) - R(t, k)\} \times \Delta t$$

(Rectangles are cut out over the adjustment area.)
... (16)

10 In the case of Fig. 18B, integration is done along the floor position axis. Symbol y is used as a variable representing the floor position and $R^*(y, k)$ and $R(y, k)$ to denote the target route and the predicted route, respectively. Accordingly, the inter-
15 route distance is given by the following equation.

$$L[R^*(y, k), R(y, k)] = \int \{R^*(y, k) - R(y, k)\} dy$$

(integration interval = all floors) ... (17)

As apparent from Fig. 18B, when integration is done along the floor position axis, $R^*(y, k)$ (and $R(y, k)$ as
20 well) can take two or more values for the same y value. This must be considered in actual calculation. Therefore since this integration along the floor position axis involves complex processing, integration

along the time axis (equation (15) or (16)) should be used in actual cases.

With reference to Figs. 7 and 23, the following provides a detailed description of the route distance index-based route evaluation function calculating section (105 in Fig. 1) which calculates the value of the assignment evaluation function to evaluate each provisional assignment by using inter-route distances. This processing corresponds to the route evaluation function calculating step (ST108 in Fig. 19) where for each provisionally assigned car, the inter-route distances between the target route and predicted route of the provisionally assigned car and between those of each non-assigned car are calculated and, based on the result, the route evaluation function is calculated. Referring to Figs. 7 and 23, this route evaluation function calculating process is described below in detail. In Fig. 7, it is assumed that the k -th car is provisionally assigned. From the k -th car's target route data $R^*(t, k)$ and predicted route data $R(t, k)$, the inter-route distance $L[R^*(t, k), R(t, k)]$ is firstly calculated by an inter-route distance calculating block 105A. Stopping of the car due to the provisional assignment is reflected in the predicted route data $R(t, k)$. The calculated inter-route distance $L[R^*(t, k), R(t, k)]$ is converted to an absolute value $|L[R^*(t, k), R(t, k)]|$ by an absolute value calculating block 105B. In addition, for the

non-assigned k-th car ($1 \leq k \leq N$, $k \neq k_a$, N = total number of elevator cars), an inter-route distance calculating block 105C calculates the inter-route distance $L[R^*(t, k), R(t, k)]$ from the k-th car's target route data $R^*(t, k)$ and predicted route data $R(t, k)$. The inter-route distance $L[R^*(t, k), R(t, k)]$ is converted to an absolute value $|L[R^*(t, k), R(t, k)]|$ by an absolute value calculating block 105D. The absolute inter-route distance of each car excluding the k_a -th car is calculated in this manner and added up by a sum calculating block 105E. This sum is expressed as below.

$$\sum |L[R^*(t, k), R(t, k)]| \quad (1 \leq k \leq N, k \neq k_a, N = \text{total number of elevator cars}) \quad \dots (18)$$

The result obtained by the absolute value calculating block 105F and the result obtained by the sum calculating block 105E are added by an addition calculating 105B to calculate the route evaluation function $\Phi R(k_a)$ to evaluate the provisional assignment of the k_a -th car. The route evaluation function $\Phi R(k_a)$ is expressed as below.

$$\Phi R(k_a) = |L[R^*(t, k_a), R(t, k_a)]| + \sum |L[R^*(t, k), R(t, k)]| \quad (1 \leq k \leq N, k \neq k_a, N = \text{total number of elevator cars}) \quad \dots (19)$$

In the case of a predicted waiting time-used conventional assignment evaluating function, it is typical to evaluate only the provisionally assigned car (only the first term in the case of equation (19)). In
5 the case of the inter-route distance-used assignment evaluating function according to the present invention, it is characterized in that an evaluation term for non-assigned cars (corresponding to the second term in equation (19)) is added to the evaluation term for
10 provisionally assigned car.

Fig. 23 shows a flowchart of the route evaluating function calculating process described with Fig. 7. Its flows are briefly described below. Firstly, information about the provisionally assigned
15 ka-th car (provisionally assigned hall call-generated floor, direction, etc.) is obtained (ST501). The inter-route distance $L[R^*(t, k_a), R(t, k_a)]$ of the provisionally assigned ka-th car is calculated based on the information and converted to an absolute value
20 (ST502). Then, a car number loop is executed for each car excluding the provisionally assigned ka-th car (ST503). Within the car number loop, the inter-route distance $L[R^*(t, k), R(t, k)]$ of the k-th car is calculated and converted to an absolute value (ST504).
25 Further, this value of each car is added up (ST505) by repeating the car number loop until the processing is done for all cars (ST506). When the processing is complete for all cars, the route evaluation function

$\Phi R(ka)$ given by equation (19) is calculated by adding the absolute value $|L[R^*(t, ka), R(t, ka)]|$ of the inter-route distance of the provisionally assigned ka-th car to the sum $\sum |L[R^*(t, k), R(t, k)]|$ of the
5 absolute value of the inter-route distance of each car excluding the provisionally assigned ka-th car (ST507).

Based on the route evaluation function $\Phi R(ka)$ ($1 \leq k \leq N$) described above, it is decided which car is to be assigned to the hall call. N $\Phi R(ka)$ values are
10 calculated. The smallest $\Phi R(ka)$ value indicates that the assignment would make the target routes of the respective cars closer to their predicted routes than the other assignments. Accordingly, a car which minimizes $\Phi R(ka)$ is selected as the car to be assigned
15 to the hall call of concern. This process is executed by the assignment elevator selecting unit 2 in Fig. 1.

To finalize the detailed description of the control components of Fig. 1, the following describes the target route specification setting section (102 in
20 Fig. 1) in detail with reference to Fig. 4. In Fig. 4, a route specification selecting block 102A, based on the current traffic data and time data, selects the most appropriate route specification from a route specification database 102B. As the route
25 specification to be implemented, this specification is output to the target route preparation section (103 in Fig. 1). In the route specification database 102B, several route specification patterns (hereinafter,

denoted as route modes) are stored to cope with different traffic conditions in the building. That is, they may include a temporally equal interval route mode 102B1 as described already, clock-in time-addressed
5 route mode 102B2, lunch start time-addressed route mode 102B3, lunch end time-addressed route mode 102B4, special traffic A-addressed route mode 102B5, and special traffic B-addressed route mode 102B6. The temporally equal interval route mode 102B1 is the most
10 basic mode and its specification intends to put the routes of the respective cars in a temporally equal interval state. Normally, this temporally equal interval route mode is selected. The clock-in time-addressed route mode 102B2 prescribes a specification
15 to cope with the up-peak type of traffic which occurs at the beginning of office hours. Likewise, the lunch start time-addressed route mode 102B3 prescribes a target specification to cope with the down-peak type of traffic which occurs during the first half of the lunch
20 hour while the lunch end time-addressed route mode 102B4 is for the last half of the lunch hour which shows both up-peak and down-peak types of traffic. Further, the special traffic A-addressed route mode 102B5 and special traffic B-addressed route mode 102B6
25 prescribe target specifications to cope with special types of traffic unique to the building.

The foregoing has described the control configuration and processing of the first embodiment of

the present invention (new collective control using target routes) based on Fig. 1. In summary, the following describes what makes the control according to the present invention different from the conventional control with reference to Figs. 10A and 10B. Fig. 10A illustrates the target route-used control concept of the present invention on an operation diagram. Likewise, Fig. 10B illustrates the conventional control concept on an operation diagram. In the case of the target route-used control in Fig. 10A, since routes which should be taken by the respective cars in the future are determined as target routes, it is possible to control the respective cars by considering their future movements based on the target routes. More specifically, since the target routes are determined so as to put the cars in temporally equal interval state along the time axis, the respective cars can be kept stably in temporally equal interval state, reducing the possibility of long waits (longer than, for example, 1 min) occurring in the future. In the case of the conventional control method, however, evaluation of a car assignment to a newly generated call is basically made based only on the waiting time for which the call is predicted to wait as shown in Fig. 10B. The future situation of the cars is not taken into consideration in this evaluation. Therefore, since the future trajectories of the respective cars cannot be controlled, this method is likely to cause a string-of-

cars condition, increasing the possibility of long waits occurring. Although some prior art control method evaluates the future situation of the respective cars, since this evaluation is done at one or plural
5 discrete points of time, continuous control of the future trajectories is not possible, making it difficult to stably keep the cars in temporally equal interval state. Also apparent from comparison between Fig. 10A and Fig. 10B, more information (future target
10 routes and predicted routes drawn continuously along the time axis) is used in Fig. 10A to evaluate the car assignment. As a matter of course, it is therefore possible to implement control by taking into the account the current situation which may widely vary.

15 Finally, the following provides a supplementary description of characteristics of target routes prepared by the target route preparation method of Fig. 2. As an initial route (also called a pre-adjustment target route) to prepare a target route, a
20 predicted route is applied in the target route preparation method of Fig. 2. As described with Figs. 5 and 6, this predicted route is prepared by using data which reflect the current traffic situation, namely, average stop frequency data on an each floor/direction
25 basis and average stoppage time data (in addition to data on hall calls already assigned and data on a generated hall call). Therefore, the current traffic situation is reflected in the profile of the predicted

route. For example, at the beginning of office hours, since the car stops almost only while the car is ascending (i.e. after the car receives passengers at the first floor, the car stops at each upper floor to
5 unload passengers and goes back to the first floor), the profile of the predicted route has a gentle uphill slope ($\Delta y/\Delta t$ is a positive small value) and a steep downhill slope ($\Delta y/\Delta t$ is a negative large value). Since a target route is prepared by adjusting the grids
10 of this predicted route in the adjustment area, the profile of the target route reflects the traffic situation at that time. For example, at the beginning of office hours, the profile of the target route has a gentle uphill slope and a steep downhill slope,
15 reflecting the traffic situation at the beginning of office hours as well. During the first half of the lunch time and at the end of office hours, the profile of the target route has a steep uphill slope (average stop frequency low) and a gentle downhill slope
20 (average stop frequency high), reflecting the traffic situation at that time. That is, the target route preparation method shown in Fig. 2 can prepare appropriate target routes by reflecting the current traffic situation. In the target route-based control
25 method according to the present invention, the method for preparing target routes as reference routes has a great influence on the control performance. The target route preparation method of Fig. 2, capable of

accurately reflecting the traffic situation, is considered very effective.

The following describes an elevator group supervisory control system according to a second embodiment of the present invention. The general control configuration of the second embodiment is identical to that of the first embodiment of Fig. 1 except for the target route preparation method implemented by the target route preparation section 103 in Fig. 1. The target route preparation method in the second embodiment is described below with reference to Figs. 3, 16 and 17. Firstly, refer to Figs. 16A and 16B where the target route preparation concept of the second embodiment is shown. Fig. 16A shows the profile of a pre-adjustment target route (an initial route to prepare a target route). Like in the first embodiment, a predicted route at that time is used as the pre-adjustment target route. Fig. 16B shows the profile of the target route that is adjusted. The difference between the target route profile by the second embodiment in Fig. 16B and the target route profile by the first embodiment in Fig. 11A appears on the present time axis. In Fig. 11B (first embodiment), each target route is drawn from the current position of the car. In the case of Fig. 16B (second embodiment), each target route is not drawn from the current position of the car. This difference is attributable to their different policies about target routes. In Fig. 11B

(first embodiment), the target routes provide transient routes that the cars should take from the current positions in order to settle in temporally equal interval state. On the other hand, in Fig. 16B (second
5 embodiment), the target routes provide routes that the cars should reach. In plain language, the target routes in Fig. 11B (first route) are 'kind' target routes which guide the cars from the current positions into temporally equal interval state. The target
10 routes in Fig. 16B (second embodiment) do not have such a guiding part. Only the final target routes are shown to indicate "anyway follow these routes". These different policies result in different start points (current position and not current position of the car)
15 of each target route.

The cars can be controlled so as to follow such target routes as used in the second embodiment. This is described below with reference to Figs. 17A and 17B. Figs. 17A and 17B show a target route and the
20 subsequent actual trajectory of the car. In Fig. 17A, the subsequent actual trajectory of the car indicates that the car is not assigned many times, namely, not stopped many times. In the case of Fig. 17B, the car is assigned many times and therefore stopped many
25 times. Apparent from comparison between Fig. 17A and Fig. 17B, the deviation of the actual trajectory from the target route is smaller in Fig. 17B. As described earlier, assignment control according to the present

invention selects such a car as to make the deviation (inter-route distance) of its predicted route from the target route. Therefore, control should be done so as to assign many calls to this car (2nd car assumed) in 5 Fig. 17B. Consequently, the actual routes follow the target routes. That is, the cars can be controlled so as to follow such target routes as prepared in the second embodiment.

The control configuration of the target route 10 preparation section in the second embodiment described above is illustrated in Fig. 3 in detail. In Fig. 3, the components identical to those in Fig. 2 (the target route preparation section in the first embodiment) are given common reference numerals and not described here. 15 That is, a target route update judgment block 103A, current temporal phase value calculating block 103B and individual car's temporal phase value adjustment amount calculating block 103C in Fig. 3 are identical in processing to those in Fig. 2 (first embodiment). An 20 adjusted route preparation block 103E is unique. In the adjusted route preparation block 103E: 1) target points on the adjustment reference time axis are calculated by an each car's target point calculating part 103E1; 2) target route grids are calculated by a 25 target point-based grid position calculating part 103E2; 3) grids are connected by a target route data calculating part 103E3 to calculate target route data. The following provides a detailed description of how

this adjusted route preparation block 103E operates.
Firstly, a target point on the adjustment reference
axis is calculated in the each car's target point
calculating part 103E1 for each car by using the
5 temporal phase adjustment value $\Delta tp(k)$ (k means the k -
th car) calculated by the individual car's temporal
phase value adjustment amount calculating block 103C.
Using $tp(k)$ to denote the pre-adjustment temporal phase
value (the adjustment reference time axis-based
10 temporal phase of the pre-adjustment route), the
adjusted temporal phase value $tp_N(k)$ is given by the
following equation.

$$tp_N(k) = tp(k) + \Delta tp(k) \quad \dots (20)$$

The adjusted temporal phase value $tp_N(k)$
15 plotted on the adjustment reference axis (along the
floor position axis) becomes the target point of the
car. Symbol $y_N(k)$, the target point position of a
car, can be given by the following equation (see Fig.
15).

20 When the car is ascending,

$$y_N(k) = (y_max/T\pi) \times tp_N(k) \quad \dots (21)$$

When the car is descending,

$$y_N(k) = -(y_max/(T-T\pi)) \times (tp_N(k) - T) \quad \dots (22)$$

In Fig. 16A where pre-adjustment target route profiles are shown, the target points of the respective cars are points E012 (first car), E022 (second car) and E032 (third car). Based on these target points, the
5 pre-adjustment target routes (or predicted routes) E011, E021 and E031 of the respective cars are translated so that they go through their respective target points, thus calculating the adjusted target routes (routes in Fig. 16B). This translating
10 calculation is done by the target point-based grid position calculating part 103E2 in Fig. 3. Using $gp(k, i)$ (k : number of the car, i : number of the grid) to denote the temporal position of a grid of the pre-adjustment target route of a car, the temporal position
15 of the adjusted target route of the car $gp_N(k, i)$ is given by the following equation.

$$gp_N(k, i) = gp(k, i) + tp_N(k) \quad \dots (23)$$

Equation (23) means to translate all grids of the k -th car by adjustment amount $tp_N(k)$. In the
20 target route calculating part predicted route preparation section 103E3, target route data is calculated by connecting these adjusted grids according to their temporal positions $gp_N(k, i)$. Consequently, the pre-adjustment target routes (E011, E021 and E031
25 in Fig. 16A) are converted to adjusted target routes

(E011, E021 and E031 in Fig. 16B which come at temporally equal intervals. It can be verified in Fig. 16B that the adjusted target routes go through their respective target points E012, E022 and E032 on the adjustment reference axis (E040 in Fig. 16B) as intended. Note that as understood from the foregoing description, the target points themselves do not directly relate to the adjusted target route calculating process. Accordingly, the adjusted target routes (E011, E021 and E031 in Fig. 16B) can be obtained even if the each car's target point calculating part 103E1 is removed from the adjusted route preparation block 103E. The target points themselves are used for operation check, etc. Also note that referring to Fig. 16B although the target route profiles are completely in temporally equal interval state in the adjustment area between the present time axis (E050) and the adjustment reference time axis (E040), they are simplified on the assumption that there is no hall/car call which is already assigned. If hall/car calls are already assigned, the target routes are not always in temporally equal interval state in the adjustment area since the stop calls are not evenly distributed among the cars.

Although control by the aforementioned embodiments intends to put the respective cars in temporally equal interval condition, the present invention is not limited to the control for temporally

equal interval condition. According to the present invention, it is possible to run elevators according to a specific purpose only by determining the target routes in consistence with the purpose. If the target
5 routes of the respective elevators are determined by taking, for example, energy saving into consideration, it is possible to realize energy-saved elevator group supervisory control.

While the invention has been described in its
10 preferred embodiments, it is to be understood that the words which have been used are words of description rather than limitation and that changes within the purview of the appended claims may be made without departing from the true scope and spirit of the
15 invention in its broader aspects.

CLAIMS:

1. An elevator group control system to control multiple elevators each of which serves a plurality of floors, comprising:

reference route generating means which, for each elevator, generates a reference route which indicates reference positions of the elevator during a certain period starting from the present time; and

control means which makes an actual trajectory of each elevator closer to the reference route of the elevator.

2. An elevator group control system to control multiple elevators each of which serves a plurality of floors, comprising:

reference route generating means which, for each elevator, generates a reference route which indicates reference positions of the elevator during a certain period starting from the present time; and

assignment means which selects a car for assignment to a generated hall call so as to make an actual trajectory of each elevator, which indicates actual positions of the elevator in real time, closer to the reference route of the elevator.

3. An elevator group control system to control multiple elevators each of which serves a plurality of floors, comprising:

first reference route generating means which generates a reference route which indicates reference

positions of a first elevator during a certain period starting from the present time;

second reference route generating means which generates a reference route which indicates reference positions of a second elevator during a certain period starting from the present time; and

assignment means which selects a car for assignment to a generated hall call so as to either make an actual trajectory of the first elevator, which indicates actual positions of the first elevator in real time, closer to the first reference route of the first elevator or make an actual trajectory of the second elevator, which indicates actual positions of the second elevator in real time, closer to the second reference route of the second elevator.

4. An elevator group control system according to Claim 1, 2 or 3, wherein:

said reference route is generated based on the positional relation with another elevator.

5. An elevator group control system according to Claim 1, 2 or 3, further comprising means for displaying said reference route and said actual trajectory.

6. An elevator group control system to control multiple elevators each of which serves a plurality of floors, comprising:

reference route generating means which for each elevator, generates a reference route which

indicates reference positions of the elevator during a certain period starting from the present time;

predicted route generating means which, for each elevator, generates a predicted route indicating predicted positions of the elevator during a certain period starting from the present time;

evaluation means which, for each elevator, calculates an evaluation value of the predicted route with respect to the reference route; and

assignment means which selects an elevator for assignment to a generated hall call based on the evaluation values calculated by the evaluation means.

7. An elevator group control system to control multiple elevators each of which serves a plurality of floors, comprising:

reference route generating means which, for each elevator, generates a reference route which indicates reference positions of the elevator during a certain period starting from the present time;

predicted route generating means which, for each elevator, generates a predicted route indicating predicted positions which the elevator would go through during a certain period if the elevator is assigned to a generated hall call;

evaluation means which, for each elevator, calculates an evaluation value of the predicted route with respect to the reference route; and

assignment means which selects an elevator

for assignment to the generated hall call based on the evaluation value calculated by the evaluation means.

8. An elevator group control system according to any one of Claims 1 through 7 wherein:

a plurality of said reference routes are separate from each other by a certain distance along a time axis..

9. An elevator control system according to Claim 6 or 7 wherein:

said evaluation means which, for each elevator, calculates an evaluation value of the predicted route with respect to the reference route takes a deviation along the time axis or a positional axis, a value obtained by integrating the deviation, a value corresponding to the deviation, or a value corresponding to the integration value as the evaluation value.

10. An elevator control system according to any one of Claims 1 through 9 wherein:

the reference route generating means updates the reference route of each elevator at certain intervals of time.

11. An elevator control system according to any of Claims 1 through 9 wherein:

the reference route generating means sets, for each elevator, a reference position at a reference point of time which is a certain time later and updates the reference route so that the elevator may go through

the reference position at the reference point of time.

12. An elevator control system according to Claim 1, 3 or 3 wherein:

if a relation between the reference route and actual trajectory of the elevator meets a certain condition, the reference route generating means updates the reference route of the elevator.

13. An elevator control system according to Claim 6 or 7 wherein:

if a relation between the reference route and predicted route of the elevator meets a certain condition, the reference route generating means updates the reference route of the elevator.

14. An elevator control system according to Claim 6 or 7, further comprising means for displaying the reference route and the predicted route.

15. An elevator group control system to control multiple elevators each of which serves a plurality of floors, comprising:

reference route generating means which for each elevator, generates a reference route which indicates reference positions of the elevator during a certain period starting from the present time;

assignment means which selects an elevator for assignment to a generated hall call based on the reference routes generated for the respective elevators;

means which displays the reference route of

each elevator and the actual trajectory indicating actual positions of each elevator in real time; and means which changes the reference route of each elevator.

16. An elevator group control system comprising:
a group control device to control multiple elevators each of which serves a plurality of floors;
and

individual-elevator control devices which control the respective elevators based on a signal from the group control device;

wherein the group control device comprises:
reference route generating means which, for each elevator, generates a reference route which indicates reference positions of the elevator during a certain period starting from the present time; and

assignment means which selects a car for assignment to a generated hall call so as to make an actual trajectory of each elevator, which indicates actual positions of the elevator in real time, closer to the reference route of the elevator; and

the individual-elevator control devices control the elevators based on the elevator assignments of the assignment means.