

Engine Device for Unmanned Flying Apparatus

[Technical Field]

[0001]

The present invention relates to an engine device for an unmanned flying apparatus.

- 5 More precisely, an engine device for an unmanned flying apparatus with two centrifugal clutches attached corresponding to two crankshafts provided in a horizontally opposed engine for an unmanned flying apparatus.

[Background Art]

[0002]

- 10 A reciprocating engine has been used more often for an unmanned flying apparatus (a drone). An inline engine and a horizontally opposed engine are representatives of a reciprocating engine. A horizontally opposed engine has piston and cylinder blocks arranged on the left and right side of a crankshaft. A horizontally opposed engine has advantages such as less engine vibration and less length of the engine in the
15 front-to-back direction, compared with an inline engine.

[0003]

- Patent Document 1 discloses an engine in which a first piston and a second piston that are arranged upright in vertical direction; and a first crankshaft and a second crankshaft corresponding to the first piston and the second piston, respectively, are arranged
20 horizontally under the first piston and the second piston. The first crankshaft and the second crankshaft rotate in opposite directions to each other to cancel the gyroscopic effect of the flying apparatus.

[0004]

- The following points are required for a reciprocating engine in an unmanned flying
25 apparatus with a plurality of propellers.

(1) Improvement of the weight balance of the flying apparatus. Concretely, the output shaft of the engine is located in the center of the flying apparatus, and the center of gravity of the engine coincides with the center of gravity of the flying apparatus.

5 (2) The gyroscopic effect of the rotating parts inside of an engine does not adversely affect controllability of a flying apparatus.

(3) A flying apparatus can land safely even if an engine stops due to trouble, that is, propellers can auto rotate by receiving air flow, even if the engine stops.

[Prior Art Documents]

10 **[Patent Document]**

[0005]

[Patent Document 1]

Japanese Unexamined Patent Application Publication No. 2019-148186

[Summary of the Invention]

15 **[Technical Problems to be Solved]**

[0006]

The purpose of the present invention is to provide an engine device for an unmanned flying apparatus that

(1) has good weight balance for the flying apparatus;

20 (2) can cancel the gyroscopic effect that adversely affects controllability of the flying apparatus; and

(3) has propellers that can auto rotate even if the engine stops.

[Means for Solving the Problem]

[0007]

The engine device for an unmanned flying apparatus according to the present invention comprises: a first cylinder and a second cylinder arranged horizontally and opposed to each other on an axis in the left-to-right direction, and pistons within the cylinders advance and retract in opposite directions to each other; a first crankshaft and a second crankshaft arranged in the vertical direction perpendicular to the axis, driven by the first cylinder and the second cylinder, respectively, and rotate in opposite directions to each other; a first centrifugal clutch and a second centrifugal clutch arranged above the first crankshaft and the second crankshaft, and rotate in opposite directions to each other; a final drive shaft transmitting rotational force to a gear mechanism to rotate a propeller shaft; a one-way clutch arranged between

(1) the first crankshaft and the second crankshaft and

(2) the final drive shaft, and driven by both of the first crankshaft and the second crankshaft.

[0008]

The engine device, wherein an exhaust pipe from the first cylinder and an exhaust pipe from the second cylinder are connected at the point of equal length, and then turned in a U shape and connected to a muffler arranged below the exhaust pipes.

[0009]

The engine device, wherein a first camshaft and a second camshaft are provided in the first cylinder and the second cylinder respectively to control respective valves, and one of the camshafts is driven by the first crankshaft and the other is driven by the second crankshaft via an reversing gear; and the first camshaft and the second camshaft rotate in the same direction.

[Effects of the Invention]

[0010]

According to the engine device for an unmanned flying apparatus of the present

invention,

(1) The first centrifugal clutch and the second centrifugal clutch are provided, and because the first centrifugal clutch and the second centrifugal clutch rotate in opposite directions to each other with a large momentum, the gyroscopic effect can be canceled and the attitude control of the flying apparatus becomes easy.

(2) Providing two centrifugal clutches can make the height of an engine device lower than providing one centrifugal clutch with large radius and height. Also, the first centrifugal clutch and the second centrifugal clutch can be arranged in symmetric positions near the center of the engine, and the center of gravity can be maintained in the center.

(3) Because a one-way clutch is provided, auto rotation becomes possible, that can reduce the risk of crash drastically. For example, the propeller side of the axis of the one-way clutch can keep rotating.

(4) Because

(a) the first cylinder and the second cylinder are arranged horizontally and opposed to each other on an axis in the left-to-right direction and

(b) pistons within the cylinders advance and retract in opposite directions to each other, the vibration of pistons is canceled, this makes an engine device with low vibration.

(5) Because the first crankshaft and the second crankshaft are arranged upright in the vertical direction, the length of the engine in the front-to-back direction can be reduced.

[0011]

According to Claim 2,

(1) the center of gravity of the engine can be maintained near its center because the muffler is arranged at the bottom of the engine;

(2) the engine device can be lightweight and compact because there is only one muffler;

(3) the exhaust pipe volume can be saved because the exhaust pipes are connected at the point of equal length and merged into one.

5 [0012]

According to Claim 3, because the first camshaft and the second camshaft rotate in the same direction, the control unit of the first cylinder, the second cylinder, pistons and valves can be common. Although the camshafts rotate in the same direction, the gyroscopic effect by this is very small and can be negligible. The advantageous effect of
10 communalizing members is larger than the very small gyroscopic effect.

[Brief Descriptions of the Drawings]

[0013]

[Fig. 1] This figure is a perspective view of an engine device of an unmanned flying apparatus according to the present invention.

15 [Fig. 2] This figure is a perspective view of an engine device of an unmanned flying apparatus according to the present invention.

[Fig. 3] This figure shows rotation directions of main members of an engine device of an unmanned flying apparatus.

[Fig. 4] This figure is an external view of an engine device of an unmanned flying
20 apparatus including accessories.

[Fig. 5] This figure is a left side view of the engine device of Fig. 4.

[Description of the Embodiments]

[0014]

Hereinafter, the engine device of an unmanned flying apparatus of the present invention
25 is explained in detail.

[Embodiments]

[0015]

Fig. 1 is a perspective view of an engine device of an unmanned flying apparatus according to the present invention. This perspective view is seen diagonally downward from the upper right rear. The view is illustrated so that the outer cover is removed so that the inside can be seen. The engine device 100 is a two-cylinder engine, and a first cylinder and a second cylinder are arranged horizontally and opposed to each other on an axis in the left-to-right direction. A first piston 11 is equipped in the first cylinder and a second piston 21 is equipped in the second cylinder. As an example, the second camshaft is provided and rotated by a second gear 27 driven by a second belt 28 to control an exhaust valve and air intake valve.

[0016]

As shown in Fig. 1, a first crankshaft 30 and a second crankshaft 40 are arranged upright in the vertical direction perpendicular to the axis. The first crankshaft 30 is driven by a first piston 11 of a first cylinder 10 and rotates. The second crankshaft 40 is driven by a second piston 21 of a second cylinder 20 and rotates. The first crankshaft 30 and the second crankshaft 40 rotate in opposite directions to each other, and can cancel the gyroscopic effect. A first generator 64 is provided under the first crankshaft 30, and a second generator 65 is provided under the second crankshaft 40. The first generator 64 and the second generator 65 generate electricity by rotation of the first crankshaft 30 and the second crankshaft 40, and supply power to an ignition system of the engine, a fuel feed system and a control unit of the unmanned flying apparatus, etc. A starter 75 is provided at the lower rear side of the engine.

[0017]

A first centrifugal clutch 80 and a second centrifugal clutch 90 are arranged above the first crankshaft 30 and the second crankshaft 40, respectively. The rotational force of the first crankshaft 30 is transmitted to the first centrifugal clutch 80. The rotational force of

the second crankshaft 40 is transmitted to the second centrifugal clutch 90. When the rotational speed of the first crankshaft 30 increases, centrifugal force acts on inside weight(s), and clutch plates of the first centrifugal clutch 80 are engaged, and the first centrifugal clutch 80 rotates its output gear projecting downward in Fig. 2. Similarly, the second centrifugal clutch 90 rotates its output gear projecting downward in Fig. 2, when the rotational speed of the second crankshaft 40 increases.

[0018]

A one-way clutch 50 is arranged under the first centrifugal clutch 80 and the second centrifugal clutch 90. An outer gear of the one-way clutch 50 is driven by both the first centrifugal clutch 80 and the second centrifugal clutch 90. The first centrifugal clutch 80 and the second centrifugal clutch 90 rotate in opposite directions to each other. In this embodiment, the rotational direction of the output gear of the first centrifugal clutch 80 is reversed by a reversing gear 34, and the output gear drives the one-way clutch 50 via the reversing gear. The output gear of the second centrifugal clutch 90 drives the one-way clutch 50 directly. The output shaft of the one-way clutch 50 rotates in one direction by transmitting the rotational forces of the first centrifugal clutch 80, and the second centrifugal clutch 90 are transmitted to an output shaft of the one-way clutch 50 by a hook inside, and the output shaft rotates in one direction. The output shaft can rotate in one direction even if it is not driven by the hook, and acts as a so-called one-way clutch.

[0019]

The output shaft of the one-way clutch 50 transmits its rotational force to a final drive shaft 60 via gears. A gear mechanism 70 comprising orthogonal transform gears is provided in the final drive shaft 60, and transmits rotational force to propeller shafts 71 to 74 in four directions.

[0020]

Fig. 2 is a perspective view of an engine device of an unmanned flying apparatus 100

according to the present invention. This perspective view is seen diagonally upward from the lower right rear. Explanation will be made as a supplement to Fig. 1. The first cylinder 10 and the second cylinder 20 are arranged horizontally and opposed to each other. The first crankshaft 30 and the second crankshaft 40 are arranged in the vertical direction perpendicular to the line connecting the first cylinder 10 and the second cylinder 20.

[0021]

As shown in Fig. 2, the first camshaft 16 is rotated by a first gear 17 driven by a first belt 18, and the first camshaft 16 controls an exhaust valve and air intake valve of the first cylinder 10. The first piston 11 is inside of the first cylinder, and is connected to its connecting rod, and rotates the first crankshaft 30. The second piston 21 is inside of the second cylinder, and is connected to its connecting rod, and rotates the second crankshaft 40. The second belt 28 of the second cylinder 20 is driven by a gear provided in the shaft of a reversing gear 29 to reverse the rotational direction of the second crankshaft 40. That is, the rotational direction of the second camshaft 26 is opposite to the rotational direction of the second crankshaft 40.

[0022]

The part under the first centrifugal clutch 80 is configured as follows. A driven gear 31 is driven by the gear of the first crankshaft 30, and rotates the first centrifugal clutch shaft 32. When the rotational speed of the first centrifugal clutch shaft 32 increases, centrifugal force acts on weight(s) inside of the first centrifugal clutch 80 and clutch plates provided inside of the first centrifugal clutch 80 are engaged. The first centrifugal clutch output gear 33 under the first centrifugal clutch 80 is rotated by this. The rotational direction of the first centrifugal clutch output gear 33 is reversed by a reversing gear 34. The reversing gear 34 engages with a one-way clutch gear 51 of a one-way clutch 50, and rotates the one-way clutch 50. Accordingly, a one-way clutch shaft 52 rotates, and the rotational force is transmitted to a final drive shaft 60 by a drive

gear 53 provided in the one-way clutch shaft 52 via a driven gear 63. The second centrifugal clutch 90 has similar configuration, and the output of the second centrifugal clutch 90 is shown in the second centrifugal clutch output gear 43. However, there is no reversing gear, and the second centrifugal clutch output gear 43 engages with the one-way clutch gear 51, and the rotational force is transmitted.

[0023]

Fig. 3 shows rotation directions of main members of an engine device of an unmanned flying apparatus. This perspective view is seen diagonally downward from the upper right front. The rotational directions are defined as the first crankshaft 30 rotates clockwise, and the second crankshaft 40 rotates counterclockwise. From the arrangement of gears, the first centrifugal clutch 80 rotates counterclockwise, and the second centrifugal clutch 90 rotates clockwise. In either case, the direction of rotation is opposite to each other, and the gyroscopic effect can be canceled by this. Although the first camshaft 16 and the second camshaft 26 rotate in the same clockwise direction, the gyroscopic effect by this is very small and can be negligible. The advantageous effect of communalizing members is larger than the very small gyroscopic effect.

[0024]

Referring to Fig. 3, the configuration under the first centrifugal clutch 80 is explained as follows. The driven gear 31 of the first centrifugal clutch 80 is driven by a drive gear 37 of the first crankshaft 30, and rotates the first centrifugal clutch shaft 32. When the first centrifugal clutch shaft 32 rotates, centrifugal force acts on weight(s) inside of the first centrifugal clutch 80, and inside clutch plates are engaged. By this, the first centrifugal clutch output gear 33 under the first centrifugal clutch 80 rotates (please refer to Fig. 2). Similarly, the driven gear 41 of the second centrifugal clutch 90 is driven by a drive gear 47 of the second crankshaft 40, and rotates the second centrifugal clutch shaft 42. When the second centrifugal clutch shaft 42 rotates, centrifugal force acts on weight(s) inside of the second centrifugal clutch 90, and inside clutch plates are engaged. By this,

the second centrifugal clutch output gear 43 under the second centrifugal clutch 90 rotates (please refer to Fig. 2).

[0025]

As shown in Fig. 3, two gears 36, with the same number of teeth are arranged between
5 the first crankshaft 30 and the second crankshaft 40, and engage each other to rotate. Because one gear 36 is driven by the first crankshaft 30, and another gear 36 is driven by the second crankshaft 40, the rotation speeds of the first crankshaft 30 and the second crankshaft 40 are the same.

[0026]

10 Fig. 4 is an external view of an engine device of an unmanned flying apparatus including accessories, and Fig. 5 is a left side view of the engine device of Fig. 4. As shown in Fig. 4, a first radiator or oil cooler 67 and a second radiator or oil cooler 68 are used for cooling of the first cylinder 10 and the second cylinder 20, respectively. Exhaust pipe 55 comprises a first exhaust pipe 56 and a second exhaust pipe 57 that are
15 connected at the connecting part, and then turned in a U shape and connected to the muffler 59. The lengths of the first exhaust pipe 56 and the second exhaust pipe 57 to the connecting part are the same. As shown in Fig. 5, the muffler 59 is arranged in the center of the bottom of the engine, so the center of gravity of the flying apparatus can be maintained without shifting in the front-to-back direction.

20 **[Industrial Applicability]**

[0027]

According to the present invention, the first centrifugal clutch and the second centrifugal clutch, provided corresponding to the first camshaft and the second camshaft, respectively, rotate in opposite directions to each other, so the gyroscopic effect can be
25 canceled and the attitude control of the flying apparatus becomes easy. The engine device of the present invention is suitable for an unmanned flying apparatus.

[List of Reference Numbers]

[0028]

- 10: first cylinder
- 11: first piston
- 5 16: first camshaft
- 17: first gear
- 18: first belt
- 20: second cylinder
- 21: second piston
- 10 26: second camshaft
- 27: second gear
- 28: second belt
- 29: reversing gear
- 30: first crankshaft
- 15 31: driven gear
- 32: first centrifugal clutch shaft
- 33: first centrifugal clutch output gear
- 34: reversing gear
- 35: shaft
- 20 36: gear
- 37: drive gear
- 40: second crankshaft
- 41: driven gear
- 42: second centrifugal clutch shaft
- 25 43: second centrifugal clutch output gear
- 47: drive gear
- 50: one-way clutch

- 51: one-way clutch gear
- 52: one-way clutch output shaft
- 53: drive gear
- 55: exhaust pipe
- 5 56: first exhaust pipe
- 57: second exhaust pipe
- 58: connecting part
- 59: muffler
- 60: final drive shaft
- 10 63: driven gear
- 64: first generator
- 65: second generator
- 67: first radiator or oil cooler
- 68: second radiator or oil cooler
- 15 70: gear mechanism
- 71, 72, 73, 74: propeller shaft
- 75: starter
- 80: first centrifugal clutch
- 90: second centrifugal clutch
- 20 100: engine device for an unmanned flying apparatus

[CLAIMS]

1. An engine device for an unmanned flying apparatus comprises:

a first cylinder and a second cylinder arranged horizontally and opposed to each other on an axis in left-to-right direction, and pistons within the cylinders advance and retract in opposite directions to each other;

a first crankshaft and a second crankshaft arranged in vertical direction perpendicular to the axis, and driven by the first cylinder and the second cylinder, respectively, and rotate in opposite directions to each other;

a first centrifugal clutch and a second centrifugal clutch arranged above the first crankshaft and the second crankshaft, and rotate in opposite directions to each other;

a final drive shaft transmitting rotational force to a gear mechanism comprising orthogonal transform gears, to rotate a propeller shaft;

a one-way clutch arranged between

- (1) the first crankshaft, the second crankshaft and
- (2) the final drive shaft, and driven by both of the first crankshaft and the second crankshaft.

2. The engine device according to claim 1, wherein an exhaust pipe from the first cylinder and an exhaust pipe from the second cylinder are connected at the point of equal length, and then turned in a U shape and connected to a muffler arranged below the exhaust pipes.

3. The engine device according to claim 1, wherein a first camshaft and a second camshaft are provided in the first cylinder and the second cylinder respectively to control respective valves, and one of the camshafts is driven by the first crankshaft and the other is driven by the second crankshaft via an reversing gear; and the first camshaft and the second camshaft rotate in the same direction.