

ICE WORTHY JACK-UP DRILLING UNIT WITH TELESCOPING RISER

FIELD OF THE INVENTION

[0001] This invention relates to mobile offshore drilling units, often called “jack-up” drilling units or rigs that are used in shallow water, typically less than 400 feet, for drilling for hydrocarbons.

BACKGROUND OF THE INVENTION

[0002] In the never-ending search for hydrocarbons, many oil and gas reservoirs have been discovered over the last one hundred and fifty years. Many technologies have been developed to find new reservoirs and resources and most areas of the world have been scoured looking for new discoveries. Few expect that any large, undiscovered resources remain to be found near populated areas and in places that would be easily accessed. Instead, new large reserves are being found in more challenging and difficult to reach areas.

[0003] One promising area is in the offshore Arctic. However, the Arctic is remote and cold where ice on the water creates considerable challenges for prospecting for and producing hydrocarbons. Over the years, it has generally been regarded that six unprofitable wells must be drilled for every profitable well. If this is actually true, one must hope that the unprofitable wells will not be expensive to drill. However, in the Arctic, little, if anything, is inexpensive.

[0004] Currently, in the shallow waters of cold weather places like the Arctic, a jack-up or mobile offshore drilling unit (MODU) can be used for about 45-90 days in the short, open-water summer season. Predicting when the drilling season starts and ends is a game of chance and many efforts are undertaken to determine when a jack-up may be safely towed to the drilling location and drilling may be started. Once started, there is considerable urgency to complete the well to avoid having to disconnect and retreat in the event of ice incursion. Even during the few weeks of open water, ice floes present a significant hazard to jack-up drilling rigs where the drilling rig is on location and legs of the jack-up drilling rig are exposed and quite vulnerable to damage.

[0005] Jack-up rigs are mobile, self-elevating, offshore drilling and workover platforms equipped with legs that are arranged to be lowered to the sea floor and then to

lift the hull out of the water. Jack-up rigs typically include the drilling and/or workover equipment, leg-jacking system, crew quarters, loading and unloading facilities, storage areas for bulk and liquid materials, helicopter landing deck and other related facilities and equipment.

[0006] A jack-up rig is designed to be towed to the drilling site and jacked-up out of the water so that the wave action of the sea only impacts the legs which have a fairly small cross section and thus allows the wave action to pass by without imparting significant movement to the jack-up rig. However, the legs of a jack-up provide little defense against ice floe collisions and an ice floe of any notable size is capable of causing structural damage to one or more legs and/or pushing the rig off location. If this type of event were to happen before the drilling operations were suspended and the well was suitably secured, a hydrocarbon leak would possibly occur. This type of risk is completely unacceptable in the oil and gas industry, to the regulators and to the public.

[0007] Thus, once it is determined that a potentially profitable well has been drilled during this short season, a very large, gravity based production system, or similar structure may be brought in and set on the sea floor for the long process of drilling and producing the hydrocarbons. These gravity based structures are very large and very expensive, but are built to withstand the ice forces year around.

BRIEF SUMMARY OF THE DISCLOSURE

[0008] The invention more particularly relates to an ice worthy jack up rig for drilling for hydrocarbons in potential ice conditions in offshore areas including a flotation hull having a relatively flat deck at the upper portion thereof. The flotation hull further includes an ice bending shape along the lower portion thereof and extending around the periphery of the hull where the ice bending shape extends from an area of the hull near the level of the deck and extends downwardly near the bottom of the hull along with an ice deflecting portion extending around the perimeter of the bottom of the hull to direct ice around the hull and not under the hull. The rig includes at least three legs that are positioned within the perimeter of the bottom of the hull wherein the legs are arranged to be lifted up off the seafloor so that the rig may be towed through shallow water and also extend to the sea floor and extend further to lift the hull partially or fully out of the water. A jack up device is associated with each leg to both lift the leg from the sea bottom so

that the ice worthy jack up rig may float by the buoyancy of the hull and push the legs down to the seafloor and push the hull partially up and out of the water when ice floes threaten the rig and fully out of the water when ice is not present. A riser is included having telescoping sections to adjust in length while on a drilling site to permit the hull to be raised and lowered.

[0009] The invention further relates to a method for drilling wells in ice prone waters. The method includes providing a flotation hull having a relatively flat deck at the upper portion thereof and an ice bending shape along the lower portion thereof where the ice bending shape extends from an area of the hull near the level of the deck and extends downwardly near the bottom of the hull and an ice deflecting portion extending around the perimeter of the bottom of the hull to direct ice around the hull and not under the hull. At least three legs are positioned within the perimeter of the bottom of the hull. Each leg is jacked down in a manner that feet on the bottom of the legs engages the sea floor and lifts the hull up and fully out of the water when ice is not threatening the rig while the rig is drilling a well on a drill site. The hull is further lowered into the water into an ice defensive configuration so that the ice bending shape extends above and below the sea surface to bend ice that comes against the rig to cause the ice to submerge under the water and endure bending forces that break the ice where the ice flows past the rig. The method includes drilling through a riser that has telescoping sections for adjusting the effective length of the riser and permit the hull to raise and lower the hull.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] A more complete understanding of the present invention and benefits thereof may be acquired by referring to the follow description taken in conjunction with the accompanying drawings in which:

[0011] Figure 1 is an elevation view of the present invention where the drilling rig is floating in the water and available to be towed to a well drilling site;

[0012] Figure 2 is an elevation view of the present invention where the drilling rig is jacked up out of the water;

[0013] Figure 3 is an elevation view of the first embodiment of the present invention where the drilling rig is partially lowered into the sea, but still supported by its legs, in a defensive configuration for drilling during potential ice conditions;

[0014] Figure 4 is an enlarged fragmentary elevation view showing one end of the first embodiment of the present invention in the Figure 3 configuration with ice moving against the rig;

[0015] Figure 5 is a partially fragmentary elevation view showing the riser extended to accommodate the out-of-water configuration of the drilling rig; and

[0016] Figure 6 is a partially fragmentary elevation view showing the riser telescopically retracted to accommodate the hull-in-water configuration of the drilling rig.

DETAILED DESCRIPTION

[0017] Turning now to the detailed description of the preferred arrangement or arrangements of the present invention, it should be understood that the inventive features and concepts may be manifested in other arrangements and that the scope of the invention is not limited to the embodiments described or illustrated. The scope of the invention is intended only to be limited by the scope of the claims that follow.

[0018] As shown in Figure 1, an ice worthy jack-up rig is generally indicated by the arrow 10. In Figure 1, jack-up rig 10 is shown with its hull 20 floating in the sea and legs 25 in a lifted arrangement where much of the length of the legs 25 extend above the deck 21 of the hull 20. On the deck 21 is derrick 30 which is used to drill wells. In the configuration shown in Figure 1, the jack-up rig 10 may be towed from one drilling location to another and to and from shore bases for maintenance and other shore service.

[0019] When the jack-up rig 10 is towed to a drilling site in generally shallow water, the legs 25 are lowered through the openings 27 in hull 20 until the feet 26 at the bottom ends of the legs 25 engage the seafloor 15 as shown in Figure 2. In a preferred embodiment, the feet 26 are connected to spud cans 28 to secure the rig 10 to the seafloor 15. Once the feet 26 engage the seafloor 15, jacking rigs within openings 27 push the legs 25 down and therefore, the hull 20 is lifted out of the water. With the hull 20 fully jacked-up and out of the water, any wave action and heavy seas more easily break past the legs 25 as compared to the effect of waves against a large buoyant object like the hull 20.

[0020] When ice begins to form on the sea surface 12, the risk of an ice floe contacting and damaging the legs 25 or simply bulldozing the jack-up rig 10 off the

drilling site becomes a significant concern for conventional jack-up rigs and such rigs are typically removed from drill sites by the end of the open water season. The ice-worthy jack-up drilling rig 10 of the present invention is designed to resist ice floes by assuming an ice defensive, hull-in-water configuration as shown in Figure 3. In Figure 3, ice tends to dampen waves and rough seas, so the sea surface 12 appears less threatening, however, the hazards of the marine environment have only altered, and not lessened.

[0021] When the ice-worthy jack-up rig 10 assumes its ice defensive, hull-in-water configuration, the hull 20 is lowered into the water to contact same, but not to the extent that the hull 20 would begin to float. A significant portion of the weight of the rig 10 preferably remains on the legs 25 to hold the position of the rig 10 on the drill site against any pressure an ice flow might bring. The rig 10 is lowered so that inwardly sloped, ice-bending surface 41 as shown in Figure 4 bridges the sea surface 12 to engage any floating ice that may come upon the rig 10.

[0022] The sloped ice-bending surface 41 runs from shoulder 42, which is at the edge of the deck 26, down to neckline 44. Ice deflector 45 extends downward from neckline 44. Thus, when an ice floe, such as shown at 51 comes to the rig 10, the ice-bending surface 41 causes the leading edge of the ice floe 51 to submerge under the sea surface 12 and apply a significant bending force that breaks large ice floes into smaller, less damaging, less hazardous bits of ice. For example, it is conceivable that an ice floe being hundreds of feet and maybe miles across could come toward the rig 10. If the ice floe is broken into bits that are less than twenty feet in the longest dimension, such bits are able to pass around the rig 10 with much less concern.

[0023] It should be noted that conventional jack-up drilling rigs do not have moon pools. As shown in Figure 5, a moon pool 32 is provided. The drilling system associated with derrick 30 includes a drill string extending down into blow out preventer (BOP) 33 and into riser 35. Riser 35 includes an upper portion 36 and lower portion 37 that are arranged to extend and retract telescopically. In other words, lower portion 37 slides up into upper portion 36 to change the length of the riser 35.

[0024] As seen in Figure 6, where the rig 10 has assumed its hull-in-water ice defensive position, the riser 35 has been retracted to permit the hull 20 to settle to the sea. The riser 35 is shown attached to a seafloor valving system that may be any conventional

technology to permit the rig to disconnect from the well and leave the well sealed up for later production or other access. It should be noted that the riser 35 and moon pool 32 are arranged within the ice deflector 45 to protect the riser from ice damage.

[0025] Ice has substantial compressive strength being in the range of 4 to 12 MPa, but is much weaker against bending with typical flexure strength in the range of 0.3 to 0.5 MPa. As shown, the force of the ice floe 51 moving along the sea surface 12 causes the leading edge to slide under the sea surface 12 and caused section 52 to break off. With the ice floe 51 broken into smaller floes, such as section 52 and bit 53, the smaller sections tend to float past and around the rig 10 without applying the impacts or forces of a large floe. It is preferred that ice not be forced under the flat of bottom of the hull 20 and the ice deflector 45 turns ice to flow around the side of the hull 20. If the ice is really thick, the ice deflector 45 is arranged to extend downwardly at a steeper angle than ice-bending surface 41 and will increase the bending forces on the ice floe. At the ice deflector 45, an ice deflector is positioned to extend down from the flat of bottom of the hull 20. In an optional arrangement, the turn of the bilge is the flat of bottom at the bottom end of the ice deflector 45.

[0026] To additionally resist the forces that an ice floe may impose on the rig 10, the feet 26 of the legs may be arranged to connect to cans 28 set in the sea floor so that when an ice floe comes against the ice-bending surface 41, the legs 25 actually hold the hull 20 down and force the bending of the ice floe and resist the lifting force of the ice floe which, in an extreme case, may lift the near side of the rig 10 and push the rig over on its side by using the feet 26 on the opposite side of the rig 10 as the fulcrum or pivot. The cans in the sea floor are known for other applications and the feet 26 would include appropriate connections to attach and release from the cans, as desired.

[0027] It should probably be noted that shifting from a conventional open water drilling configuration as shown in Figure 2 to a hull-in-water, ice defensive configuration shown in Figure 3 may require considerable planning and accommodation depending on what aspect of drilling is ongoing at the time. While some equipment can accommodate shifting of the height of the deck 21, other equipment may require disconnections or reconfiguration to adapt to a new height off the sea floor 15.

[0028] The ice-worthy jack-up drill rig 10 is designed to operate like a conventional jack-up rig in open water, but is also designed to settle to the water in an ice defensive position and then re-acquire the conventional stance or configuration when wave action becomes a concern. It is the shape of the hull 20 (as well as its strength) that provides ice bending and breaking capabilities.

[0029] The hull 20 (as viewed from above) may have a circular or oval configuration so as to present a shape that is conducive to steering the broken bits and sections of ice around the periphery of the rig 10 regardless of the direction of origin or path of travel. The ice tends to flow with the wind and sea currents, which tend not to be co-linear, or some path reflecting influences of both sea and air.

[0030] The hull 20 preferably has a faceted or multisided shape that provides the advantages of a circular or oval shape, and may be less expensive to construct. The plates that make up the hull would likely be formed of flat sheets and so that the entire structure comprises segments of flat material such as steel would likely require less complication. The ice-breaking surface would preferably extend at least about five meters above the water level, recognizing that water levels shift up and down with tides and storms and perhaps other influences. The height above the water level accommodates ice floes that are quite thick or having ridges that extend well above the sea surface 12, but since the height of the shoulder 42 is well above the sea surface 12, the tall ice floes will be forced down as they come into contact with the rig 10. At the same time, the deck 21 at the top of the hull 20 should be far enough above the water line so that waves are not able to wash across the deck. As such, the deck 25 is preferred to be at least 7 to 8 meters above the sea surface 12. Conversely, the neckline 42 is preferred to be at least 4 to 8 meters below the sea surface 12 to adequately bend the ice floes to break them up into more harmless bits. Thus, the hull 20 is preferably in the range of 5-16 meters in height from the flat of bottom to the deck 20, more preferably 8-16 meters or 11-16 meters.

[0031] It should also be noted that the legs 25 and the openings 27 through which they are connected to the hull 20 are within the perimeter of the ice deflector 45 so that the ice floes are less likely to contact the legs while the rig 10 is in its defensive ice condition configuration as shown in Figure 3 and sometimes called hull-in-water

configuration. Moreover, the rig 10 does not have to handle every ice floe threat to significantly add value to oil and gas companies. If rig 10 can extend the drilling season by as little as a month, that would be a fifty percent improvement in some ice prone areas and therefore provide a very real cost saving benefit to the industry.

[0032] In closing, it should be noted that the discussion of any reference is not an admission that it is prior art to the present invention, especially any reference that may have a publication date after the priority date of this application. At the same time, each and every claim below is hereby incorporated into this detailed description or specification as an additional embodiment of the present invention.

[0033] Although the systems and processes described herein have been described in detail, it should be understood that various changes, substitutions, and alterations can be made without departing from the spirit and scope of the invention as defined by the following claims. Those skilled in the art may be able to study the preferred embodiments and identify other ways to practice the invention that are not exactly as described herein. It is the intent of the inventors that variations and equivalents of the invention are within the scope of the claims, while the description, abstract and drawings are not to be used to limit the scope of the invention. The invention is specifically intended to be as broad as the claims below and their equivalents.

CLAIMS

1. An ice-worthy jack-up rig for drilling for hydrocarbons in potential ice conditions in offshore areas comprising:
 - a flotation hull having a relatively flat deck at the upper portion thereof and an ice-bending shape along the lower portion thereof and extending downwardly and inwardly around the periphery of the hull where the ice-bending shape extends from an area of the hull near the level of the deck and extends downwardly near the bottom of the hull;
 - an ice deflecting portion extending around the perimeter of the bottom of the hull to direct ice around the hull and not under the hull;
 - at least three legs that are positioned within the perimeter of the bottom of the flotation hull wherein the legs are arranged to be lifted up off the seafloor so that the rig may be towed through shallow water and also extend to the sea floor and extend further to lift the hull partially or fully out of the water; and
 - a jack-up device associated with each leg to both lift the leg from the sea bottom so that the ice worthy jack-up rig may float by the buoyancy of the hull and push the legs down to the seafloor and push the hull partially up and out of the water when ice floes threaten the rig and fully out of the water when ice is not present.; and
 - a riser having telescoping sections to adjust in length while on a drilling site to permit the hull to be raised and lowered.
2. The ice worthy jack-up rig according to claim 1, further including an anchoring mechanism associated with a foot of each leg to provide additional resistance to the forces an ice floe may impose on the rig.
3. The ice worthy jack-up rig according to claim 1 or claim 2, wherein the ice bending surface is slanted upwardly and outwardly from a smaller dimension neckline to a larger dimension shoulder.

4. The ice worthy jack-up rig according to any preceding claim, wherein the ice bending surface extends vertically at least 8 to 10 or more meters.
5. The ice worthy jack-up rig according to claim 4, wherein the angle of the ice-bending surface is in the range of 30 to 60 degrees from the vertical.
6. The ice worthy jack-up rig according to any preceding claim, wherein the ice-bending surface comprises a plurality of relatively flat, sloped, segments extending around the periphery of the rig.
7. The ice worthy jack-up rig according to any preceding claim, wherein the ice-bending surface is a reinforced surface.
8. A method for drilling a well in ice prone waters, the method comprising:
 - providing rig having a flotation hull having a relatively flat deck at the upper portion thereof and an ice-bending shape along the lower portion thereof where the ice-bending shape extends from an area of the hull near the level of the deck and extends downwardly near the bottom of the hull and an ice deflecting portion extending around the perimeter of the bottom of the hull to direct ice around the hull and not under the hull;
 - providing at least three legs that are positioned within the perimeter of the bottom of the hull;
 - jacking down each leg in a manner that feet on the bottom of the legs engages the sea floor and lifts the hull up and fully out of the water when ice is not threatening the rig while the rig is drilling a well on a drill site;
 - lowering the hull into the water into an ice defensive configuration so that the ice-bending shape extends above and below the sea surface to bend ice that comes against the rig to cause the ice to submerge under the water and

- endure bending forces that break the ice where the ice flows past the rig;
and
drilling through a riser that has telescoping sections for adjusting the effective
length of the riser and permit the hull to raise and lower the hull.
9. The method according to claim 8 further including the step of anchoring the legs to the seafloor to further resist the force of ice floes.
 10. The method according to claim 8 or claim 9 wherein the ice-bending surface extends from a shoulder to a neckline and the step of lowering the hull into the water more particularly comprises lowering the hull into the water so that the neckline is at least 4 meters below the sea surface and the shoulder is at least 7 meters above the sea surface.
 11. The method according to any of claims 8 to 10 further including the step of raising the hull up out of the water when the threat of ice floes are reduced.
 12. A method for drilling in ice prone waters comprising the use of a rig as claimed in any of claims 1 to 7.