CLAIMS

1. An effervescent beverage can comprising:

a top surface;

a bottom surface; and

a body, wherein

an inner surface of the body is provided with first recesses and second recesses, the first recesses have a diameter of 5 μm or more and 20 μm or less, the number of the first recesses is 200 to 1200 per 1 mm^2, the second recesses have a diameter of 0.5 μm or more and less than 5 μm, and the number of the second recesses is 7000 to 15000 per 1 mm^2.

2. The effervescent beverage can according to claim 1, wherein

the number of the first recesses is 256 to 768 per 1 mm^2,

the number of the second recesses is 6000 to 9552 per 1 mm^2.

3. The effervescent beverage can according to claim 1 or 2, wherein the first recesses have a diameter of 5 μm or more and 8.8 μm or less.

4. The effervescent beverage can according to any one of claims 1 to 3, wherein

the inner surface of the body is provided with a resin layer, and

the first recesses and the second recesses are formed in the resin layer.

5. The effervescent beverage can according to any one of claims 1 to 4, wherein the top surface is formed by a can lid configured to be opened in a fully open manner.

6. An effervescent beverage comprising:

the effervescent beverage can according to claim 5; and

a drinkable liquid filled in the effervescent beverage can, wherein

upon opening, the drinkable liquid is caused to effervesce so as to hide a top end portion of the effervescent beverage can.

7. The effervescent beverage according to claim 6, the drinkable liquid is a beer-like effervescent beverage.