

DESCRIPTION

Power switching assembly

5

FIELD OF INVENTION

The present invention relates to the field of power distribution systems.

10

ART BACKGROUND

As is known from practice, a power distribution bus of a power distribution system may be splitted into several bus sections for reliability purposes. The bus sections may be connected with a removable bus link.

15

In view of the above-described situation, there exists a need for an improved technique that enables to provide a power distribution bus with improved characteristics.

20

SUMMARY OF THE INVENTION

25

This need may be met by the subject matter according to the independent claims. Advantageous embodiments of the herein disclosed subject matter are described by the dependent claims.

30

According to a first aspect of the herein disclosed subject matter, there is provided a power switching assembly for switching power in a power distribution bus, the power switching assembly comprising a first terminal; a second terminal; and a first semiconductor element and a second semiconductor element electrically coupled between the first terminal and the second terminal so as to provide

35

semiconductor elements, a current flows from the first terminal to the second terminal and vice versa depending on the direction of the current.

5 By providing controllability of the current flow between the first terminal and the second terminal the characteristics of the power distribution bar can be increased. Embodiments of the first aspect provide numerous advantages as noted below.

10 It should be understood that according to embodiments of the herein disclosed subject matter, more than two semiconductor elements may be provided. In an embodiment, at least two of the semiconductor elements are transistors or thyristors. For example, in an embodiment, the power switching assembly
15 includes two semiconductor elements in the form of an insulated gate bipolar transistor (IGBT). According to other embodiments, other kinds of transistors are used. According to an embodiment, the transistors are coupled in parallel. According to another embodiment, the transistors are coupled
20 in series. In particular in the latter case further semiconductor elements, e.g. passive semiconductor elements such as diodes are provided in order to provide the controllability of the current flow between the terminals in both directions.

25 According to an embodiment, the power switching assembly further comprises a current sensor for sensing a current flowing between the first terminal and the second terminal and providing a current signal in response hereto; and a
30 controller being configured for receiving the current signal and controlling in response hereto the first semiconductor element and the second semiconductor element.

35 The power switching assembly being operable by the at least one terminal through the power switching assembly provides several advantages. In an embodiment the controller is configured for controlling the first semiconductor element and the second

semiconductor element in response to the current signal so as to electrically disconnect the first terminal and the second terminal under predetermined current signal conditions. For example, according to an embodiment, the controller is

5 configured for controlling the semiconductor elements so as to disconnect the first terminal and the second terminal if the magnitude of the current exceeds a current magnitude threshold. In such an embodiment, the power switching assembly forms a breaker. Further, while in an embodiment the

10 controller defines a current magnitude threshold, in other embodiments the controller defines a current duration threshold. In an embodiment, the current duration threshold depends on the actual current magnitude. For example, in an embodiment the controller is configured for disconnecting the

15 first terminal and the second terminal if the current magnitude is within a current magnitude interval for a time that exceeds a first duration threshold. According to further embodiments two or more of such current magnitude intervals and associated duration thresholds are defined in the

20 controller.

While above the power switching assembly provides two states, connected first and second terminal and disconnected first and second terminals, without intermediate state, in other

25 embodiments the power switching assembly provides intermediate states between the "connected" and "disconnected" extremes.

For example, according to a further embodiment, the

30 controller is configured for controlling the first semiconductor element and the second semiconductor element in response to the current signal so as to control the magnitude of the current flowing between the first terminal and the second terminal in response to the current signal. Hence in

35 this embodiment the power switching assembly provides at least one intermediate state in which the current flow

power switching assembly and the controller, and the controller is configured for controlling the power switching assembly.

In an embodiment, the power switching assembly is operable as a current limiter. For example, in an embodiment the controller is configured for controlling the first semiconductor element and the second semiconductor element in response to the current signal so as to limit the current flowing between the first terminal and the second terminal with regard to a predetermined current limit.

An application of current limitation by the power switching assembly may be the handling of a faulty bus section of the power distribution bus. For example, in an embodiment the controller is configured limiting the current flowing into a bus section. Such a case may arise if a consumer connected to the respective bus section and hence the terminal connected thereto draws too much current due to a fault. If the current drawn by the respective bus section is within a predetermined interval for a predetermined time, indicating such a fault, the controller is configured for disconnecting the respective bus section, in an embodiment.

Another application of current limitation is the control operation of the power switching assembly during energizing a bus section to which a plurality of devices with high input capacitances (such as inverters) are connected. The input capacitances lead to a high inrush current during energizing the bus section and having set therein a current limit, the power switching assembly acts as a current limiter. For example, in an embodiment, the control assembly is configured for operating the semiconductor devices so as to chop the power provided to the respective terminal, thereby operating the power switching assembly as a chopper.

Embodiments of the present invention are described above with reference to block diagrams and signal flow diagrams. Those skilled in the art will understand that the present invention is not limited to the specific details described herein.

external control signal; wherein the controller is configured for controlling, in response to the external control signal, the first semiconductor element and the second semiconductor element. The external control signal may be provided by a
5 further control assembly (e.g. a higher level control assembly). For example, in an embodiment, the external signal is a load balancing signal provided by a control assembly (e.g. a load controller) that balances the load of generators electrically coupled to the power switching assembly.

10

According to a second aspect of the herein disclosed subject matter, a power distribution system is provided, the power distribution system comprising: A power distribution bus having a first bus section and a second bus section, wherein
15 to each bus section at least one electrical consumer is electrically coupleable; a power switching assembly according to the first aspect or an embodiment thereof, the power switching assembly having its first terminal electrically coupled to the first bus section and having its second
20 terminal electrically coupled to the second bus section.

For example, according to an embodiment, the power distribution system comprises: a first generator for providing electrical energy to the first bus section; a
25 second generator for providing electrical energy to the second bus section; a load controller, the load controller being configured for providing the external control signal to the control input of the power switching assembly in order to control to the magnitude of the current flowing between the
30 first terminal and the second terminal so as alter a load distribution among the first generator and the second generator.

According to a further embodiment the power distribution bus
35 is a DC power distribution bus which receives and distributes DC power.

According to a third aspect of the herein disclosed subject matter a method of operating a power distribution system having a power distribution bus with a first bus section and a second bus section is provided, the method comprising:

- 5 Controlling a current flow from the first bus section to the second bus section and from the second bus section to the first bus section.

According to an embodiment, the method comprises sensing a
10 current flowing between the first bus section and the second bus section; and controlling in response hereto a first semiconductor element and a second semiconductor element electrically coupled between the first bus section and the second bus section so as to control the current flowing
15 between the first bus section and the second bus section.

In a further embodiment the method comprises controlling the first semiconductor element and the second semiconductor element in response to the sensed current so as to
20 electrically disconnect the first terminal and the second terminal under predetermined current signal conditions. For example, according to an embodiment, the method comprises controlling the semiconductor elements so as to disconnect the first terminal and the second terminal if the magnitude
25 of the current exceeds a current magnitude threshold. In a further embodiment the method comprises controlling the semiconductor elements so as to disconnect the first terminal and the second terminal if a duration, during which the current remains above a current magnitude, exceeds a current
30 duration threshold. In an embodiment, the current duration threshold depends on the actual current magnitude. For example, in an embodiment the first terminal and the second terminal are disconnected if the current magnitude is within a current magnitude interval for a time that exceeds a first
35 duration threshold.

In other embodiments the power the current between the first bus section and the second bus section is controlled to take an intermediate level between zero and a maximum level.

5 For example, according to a further embodiment, the method comprises controlling the first semiconductor element and the second semiconductor element so as to control the magnitude of the current flowing between the first terminal and the second terminal in response to the sensed current flowing
10 between the first bus section and the second bus section. For example, in an embodiment, the magnitude of the current is controllably altered depending on the sensed current.

In an embodiment, the current is controlled so as to be
15 limited to a magnitude below a current magnitude threshold.

For example, in an embodiment the magnitude of the current flowing into one of the first bus section and the second bus section is limited depending to the sensed current. For
20 example, if a consumer connected to the respective bus section draws too much current due to a fault, this will not result in a damaging magnitude of the current. In a further embodiment, if the current drawn by the respective bus section is within a predetermined interval for a
25 predetermined time, indicating such a fault, the respective bus section is disconnected.

According to a further embodiment, the power provided to the respective bus section is chopped so as to limit the current
30 flowing to the bus section.

According to a further embodiment, the method further comprises balancing the load of a first generator electrically coupled to the first bus section and the load of
35 the second generator electrically coupled to the second bus section.

According to still further embodiments of the third aspect, the functions as disclosed with regard to the first aspect are performed. These functions may be performed in any suitable way. Accordingly, the device features specified with
5 regard to the first aspect are not limiting for the definition of embodiments of the method of the third aspect. Only the disclosed functions limit respective embodiments of the third aspect. However, according to an embodiment, these functions are performed with the configuration of the power
10 distribution system as disclosed with regard to the second aspect. According to other embodiments, these functions are performed with the configuration of the power switching assembly as disclosed with regard to the first aspect.

15 According to a fourth aspect of the herein disclosed subject matter, a computer program for controlling a physical object, namely a power switching assembly in a power distribution bus, is provided, the computer program being configured for carrying out the method according to the third aspect or an
20 embodiment thereof when being executed by a processor assembly.

According to an embodiment, the computer program also influences the operation of the generator(s) in regard of
25 frequency and voltage. For example, in a further embodiment, the computer program is configured for influencing the operation of the generator in order to achieve the optimal operation and load flow of the complete system including starting and stopping of the generators dependent of the mode
30 of operation. For example, in both embodiments set values are provided to a generator controller.

According to a fifth aspect of the herein disclosed subject matter, there is provided the use of a power switching
35 assembly as a coupler of two bus sections of a power distribution bus, wherein the power switching bus is

configured according to the first aspect or an embodiment thereof.

5 According to an embodiment of the herein disclosed subject matter, the power distribution system is a subsea electrical power distribution system. According to an embodiment of the herein disclosed subject matter, the power distribution system is a subsea direct current (DC) electrical power distribution system.

10

According to an embodiment, the subsea electrical power distribution system is a subsea electricity network for supplying electrical power to a plurality of electrical consumers. For example, in an embodiment, the subsea
15 electrical power distribution system is a subsea electrical power grid.

According to an embodiment, the subsea electrical power distribution system is configured for connection to a system
20 onboard a ship or onboard an oilrig. Such systems may include a propulsion system and/or a drilling system. Other kinds of sectioned power supply systems should also be covered. For installations except subsea applications liquid or air cooling is the most likely solution.

25

According to a further embodiment, the voltage of the DC power provided to the power distribution bus is in a range between 500 volts and 5 kilovolts, e.g. between 700 volts and 2 kilovolts, e.g. 1 kilovolt.

30

According to a further embodiment, one or more of the elements of the power distribution system (referred to hereinafter as system element) is configured for installation at a seabed. For example, in respective embodiments the
35 system element is capable of operating in a water depth below a predefined upper level, e.g. 100 meters (m), 800 meters, 2000 meters or 3000 meters with each upper level

corresponding to a respective embodiment of the herein disclosed subject matter. According to respective further embodiments, the system element is capable of operating under a pressure corresponding to the specified depth, wherein in
5 one embodiment the pressure is a pressure generated by sea water of the specified depth and in another embodiment the pressure is a pressure generated by fresh water of the specified depth. According to respective further embodiments, the system element is capable of operating up to predefined
10 lower level of water depth, e.g. 200 meters (m), 1000 meters, 3000 meters or 4000 meters with each lower level corresponding to a respective embodiment of the herein disclosed subject matter, leading to respective pressures which are dependent on the density of the water, e.g. on the
15 temperature and on the type of water (sea water or fresh water).

In the above mentioned embodiments and generally herein, "electrically coupling/decoupling" does not necessarily imply
20 an direct connection of the coupled entities, nor does it necessarily imply an electrical (galvanical) connection. Rather, the electrically coupled entities may be galvanically separated in one embodiment. In such an embodiment the electrical coupling nonetheless provides for transfer of
25 electrical energy between the electrically coupled entities. According to a further embodiment, electrical decoupling prohibits the transfer of electrical energy between the electrically decoupled entities. Further, any intermediate element may be located between the electrically coupled
30 entities.

According to an embodiment, one or more system elements, e.g. any semiconductor element, are installed in an oil-filled container. For example, according to a further embodiment,
35 the power switching assembly is installed in an oil-filled container.

As used herein, reference to a computer program is intended to be equivalent to a reference to a program element and/or a computer readable medium containing instructions for controlling a computer system to coordinate the performance of the above described method.

The computer program may be implemented as computer readable instruction code by use of any suitable programming language, such as, for example, JAVA, C++, and may be stored on a computer-readable medium (removable disk, volatile or non-volatile memory, embedded memory/processor, etc.). The instruction code is operable to program a computer or any other programmable device to carry out the intended functions. The computer program may be available from a network, such as the World Wide Web, from which it may be downloaded.

Embodiments of the herein disclosed subject matter may be realized by means of a computer program respectively software. However, embodiments of the herein disclosed subject matter may also be realized by means of one or more specific electronic circuits respectively hardware. Furthermore, embodiments of the herein disclosed subject matter may also be realized in a hybrid form, i.e. in a combination of software modules and hardware modules.

In the above there have been described and in the following there will be described exemplary embodiments of the subject matter disclosed herein with reference to a power switching assembly, power distribution system and a method of operating a power distribution system. It has to be pointed out that of course any combination of features relating to different aspects of the herein disclosed subject matter is also possible. In particular, some embodiments have been described with reference to apparatus type claims whereas other embodiments have been described with reference to method type claims. However, a person skilled in the art will gather from

the above and the following description that, unless other notified, in addition to any combination of features belonging to one aspect also any combination between features relating to different aspects or embodiments, for example even between features of the apparatus type claims and features of the method type claims is considered to be disclosed with this application. For example, a controller of a power switching assembly may have implemented therein one or more of the embodiments disclosed herein.

The aspects and embodiments defined above and further aspects and embodiments of the present invention are apparent from the examples to be described hereinafter and are explained with reference to the drawings, but to which the invention is not limited.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows in part an electrical power distribution system in accordance with embodiments of the herein disclosed subject matter.

Fig. 2 shows in part a further electrical power distribution system in accordance with embodiments of the herein disclosed subject matter.

Fig. 3 shows a power switching assembly in accordance with embodiments of the herein disclosed subject matter.

DETAILED DESCRIPTION

The illustration in the drawings is schematic. It is noted that in different figures, similar or identical elements are

provided with the same reference signs or with reference signs, which are different from the corresponding reference signs only within the same figure.

5 Fig. 1 shows a power distribution system 100 comprising a DC power distribution bus 102 having a first bus section 104 and a second bus section 106. The DC power distribution bus 102 is operated with direct current (DC) power. The system 100 further comprises a power switching assembly 108 having a
10 first terminal 110 and a second terminal 112. In accordance with an embodiment, the first terminal 110 is electrically coupled to the first bus section 104 and the second terminal 112 is electrically coupled to the second bus section 106.

15 The power switching assembly 108 comprises a first semiconductor element 114 and a second semiconductor element 116 electrically coupled between the first terminal 110 and the second terminal 112 so as to provide controllability of a current flow from the first terminal 110 to the second
20 terminal 112 and from the second terminal 112 to the first terminal 110. In accordance with an embodiment, the semiconductor elements 114, 116 are insulated gate bipolar transistors coupled to the terminals 110, 112 such that the first semiconductor element 114 conducts current from the
25 first terminal 110 to the second terminal 112 and that the second semiconductor element 116 conducts current from the second terminal 112 to the first terminal 110. In order to bypass the respective other semiconductor element, freewheel diodes 118, 120 as further semiconductor elements are
30 provided. In particular, a first diode 118 is coupled in parallel to the first semiconductor element 114 wherein the conduction direction of the first semiconductor element 114 is reversed to the conduction direction of the associated first diode 118. Likewise, a second diode 120 is coupled in
35 parallel to the second semiconductor element 116 wherein the conduction direction of the second semiconductor element 116 is reversed to the conduction direction of the associated

second diode 120, as shown in Fig. 1. In accordance with an embodiment, the first and second semiconductor elements 114, 116 are coupled in series between the first terminal 110 and the second terminal 112.

5

In accordance with an embodiment, the power switching assembly 108 further comprises a current sensor 122 coupled in series to the first and second semiconductor elements 114, 116 (transistors). The current sensor 122 is configured for
10 sensing a current flowing between the first terminal 110 and the second terminal 112 and providing a current signal 124 in response hereto. Further, the power switching assembly 108 comprises a controller 126 being configured for receiving the current signal 124 and controlling in response hereto the
15 first semiconductor element 114 and the second semiconductor element 116, e.g. by providing a respective first voltage signal 128 to the first semiconductor element 114 and a second voltage signal 130 to the second semiconductor element 116.

20

The controller 126 may be configured in accordance with any embodiment disclosed herein. For example, in an embodiment the controller 126 is configured for controlling the first semiconductor element 114 and the second semiconductor
25 element 116 so as to connect and disconnect the bus section 104, 106 to each other, depending on the current signal 124. In such an embodiment, the power switching assembly 108 forms a breaker. The breaker according to embodiments of the herein disclosed subject matter has the advantage that it is capable
30 of handling the power level, typically 1000 volts (V), that occurs at the power distribution bus 102.

In accordance with a further embodiment, the controller 126 is configured for controlling the first semiconductor element 114 and the second semiconductor element 116 so as to limit
35 the current flowing through the power switching device 108. To this end, the current sensor 122 is configured and

positioned so as to provide a current signal 124 that is indicative of the whole current flowing through the power switching element 108. Various control schemes can be implemented in the controller 126, e.g. control schemes which
5 employ the limiting of the current flowing through the power switching assembly 108.

For example, in case of a failure in one bus section 104, 106 of the bus the sensed current flowing from one bus section
10 (e.g. 104) to the other (e.g. 106) will be monitored and limited by operating the semiconductors. In case the current flows for a time longer than a set limit, the power switching element 108 will open and disconnect the faulty bus section, by virtue of the respective operation of the controller 126.
15 The current limit may be set according to the actual mode of operation in a way that no disturbance of the remaining bus section occurs.

In accordance with an embodiment, the electrical power
20 distribution system 100 further comprises a choke 132 or an inductance coupled in series with the current sensor 122 or, in another embodiment in series with the controllable semiconductor elements 114, 116. The choke 132 serves to reduce current spikes and hence provides for a reliable
25 operation of the current sensor 122.

In accordance with a further embodiment, the power switching assembly 108 comprises a fuse 134 which is coupled in series with the semiconductor elements 114, 116 and serves to
30 protect the semiconductor elements 114, 116, e.g. in case of a malfunction of the control assembly 126.

In accordance with a further embodiment, the electrical power distribution system 100 includes a first disconnecter 136
35 which is electrically connected between the first bus section 104 and the first terminal 110 of the power switching assembly 108 and a second disconnecter 138 which is

electrically connected between the second bus section 106 and the second terminal 112 of the power switching assembly 108. The disconnectors 136, 138 are closed in normal operation, thereby providing an electrical connection between the
5 respective bus sections and terminals. For maintenance purposes, the disconnectors 136, 138 can be opened thereby disconnecting the power switching system 108 from the power distribution bus 102.

10 It should be noted that generally herein the elements that are associated with a certain entity in exemplary (depicted) embodiments may also be associated with another entity in other embodiments. For example, in an embodiment, the disconnectors 136, 138 are associated with the power
15 switching assembly 108 (not shown in Fig. 1).

Fig. 2 shows in part a further electrical power distribution system 200 in accordance with embodiments of the herein disclosed subject matter.

20

The structure of power switching assembly 208 in Fig. 2 is similar to the structure of the power switching assembly 108 which is shown in detail in Fig. 1 and the description thereof is not repeated here. However, the controller 226 of
25 the power switching assembly 208 in Fig. 2 is configured different as compared with the controller 126 of Fig. 1.

In accordance with an embodiment of the power switching assembly 208, the controller implements a precharging device:

30 In a DC distribution system 200 where a number of inverters 240 are connected to the power distribution bus 202, all the DC capacitors (not shown in Fig. 2) in the inverters are connected to the DC bus 202. Further shown in Fig. 2 are electrical consumers, indicated at 242. Electrical coupling
35 of the individual elements may be performed in any suitable way, e.g. by electrical wires or cables. This is exemplarily indicated at 244 in Fig. 2. When energizing the bus 202 the

current must be limited. The power switching assembly 208 may
in this situation be operate as a chopper, by virtue of the
respectively configured controller 226, limiting the current
to a selected level, ensuring an effective limitation of the
5 inrush current.

In accordance with an embodiment of the controller according
to the herein disclosed subject matter, also implemented in
the controller 226 of the power switching assembly 208 in
10 Fig. 1, the power switching assembly 208 is configured for
implementing a load balancer. To this end and in accordance
with a further embodiment, the power switching assembly 208
further comprises at least one control input 246 for
receiving an external control signal 248. In an embodiment,
15 the external control signal 248 is received from a voltage
control system 250 which also provides control signals 251 to
generators 252, 253 feeding the bus sections 204, 206 via
rectifiers 254. The controller 226 is configured for
controlling, in response to the external control signal 248,
20 the first semiconductor element and the second semiconductor
element (not shown in Fig. 2) of the power switching assembly
208.

In response the received external control signals 248 from
25 the voltage control system 250, the power switching assembly
operates as a load balancer by limiting the current flowing
e.g. from a first generator electrically coupled to the first
bus section 204 through the first bus section 202 and through
the power switching assembly 208 into the second bus section
30 206, thereby ensuring an optimized operation of the
generators and still remaining the reliability of two
independent bus sections 204, 206 in case of failure.

Fig. 3 shows in part a power switching assembly 308 in
35 accordance with embodiments of the herein disclosed subject
matter.

In accordance with embodiments of the herein disclosed subject matter, the power switching assembly 308 comprises a first terminal 310, a second terminal 312 and a first semiconductor element 314 and a second semiconductor element 5 316. The first semiconductor element 314 and the second semiconductor element 316 are electrically coupled in parallel between the first terminal 310 and the second terminal 312 so as to provide controllability of a current flow from the first terminal 310 to the second terminal 312 10 and from the second terminal 312 to the first terminal 310.

In accordance with an embodiment shown in Fig. 3, the first and second semiconductor elements are IGBT's. In other embodiments, the semiconductor elements may be e.g. 15 thyristors.

It should be noted that the above described embodiments may be varied while still remaining in accordance with the appended claims. For example, in respective embodiments, the 20 choke 132 and/or the fuse 134 and/or the disconnectors 136, 138 may be omitted. According to an embodiment, the DC power is a dipole power. According to another embodiment, the DC power is not a dipole DC power but rather a multipole DC power having more than two poles.

25 Further, the specified number and arrangement of rectifiers, inverters, electrical consumers and controllers does not exclude other numbers and arrangements of such entities. For example, the controller of the power switching assembly may 30 be located in close proximity to the semiconductor elements or may be located remote from the semiconductor element. Further it should further be noted that a subsea electrical power distribution system or a land-based electrical power distribution system in accordance with embodiments of the 35 herein disclosed subject matter is not limited as to include the dedicated entities described in some embodiments above. Further, the herein disclosed subject matter may be

implemented in various ways in various locations in a subsea electrical power distribution system or in a land-base electrical power distribution system while still providing the desired functionality.

5

It should be noted that the term "comprising" does not exclude other elements or steps and the "a" or "an" does not exclude a plurality. Also elements described in association with different embodiments may be combined. It should also be
10 noted that reference signs in the claims should not be construed as limiting the scope of the claims.

In order to recapitulate the above described embodiments of the present invention one can state:

15

It is described a power switching assembly for switching power in a power distribution bus, and a power distribution system comprising such a power switching assembly, the power switching assembly comprising a first terminal, a second
20 terminal, a first semiconductor element and a second semiconductor element electrically coupled between the first terminal and the second terminal so as to provide controllability of a current flow from the first terminal to the second terminal and from the second terminal to the first
25 terminal. A controller for controlling the semiconductor elements may be configured to implement one or more of various control schemes such as a breaker, a current limiter, a load balancer and a precharging device. All power electronic modules may be installed in oil filled canisters
30 and exposed to the ambient pressure at the seabed.

CLAIMS:

- 5 1. Power switching assembly (108, 208, 308) for switching power in a power distribution bus (102, 202), the power switching assembly (108, 208, 308) comprising:
 - a first terminal (110, 310);
 - a second terminal (112, 312);
 - 10 - a first semiconductor element (114, 314) and a second semiconductor element (116, 316) electrically coupled between the first terminal (110, 310) and the second terminal (112, 312) so as to provide controllability of a current flow from the first terminal (110, 310) to the
 - 15 second terminal (112, 312) and from the second terminal (112, 312) to the first terminal (110, 310).
2. Power switching assembly according to claim 1, further comprising:
 - 20 - a current sensor (122) for sensing a current flowing between the first terminal (110, 310) and the second terminal (112, 312) and providing a current signal (124) in response hereto;
 - a controller (126, 226) being configured for receiving
 - 25 the current signal (124) and controlling in response hereto the first semiconductor element (114, 314) and the second semiconductor element (116, 316).
3. Power switching assembly according to claim 2,
 - 30 - wherein the controller (126, 226) is configured for controlling the first semiconductor element (114, 314) and the second semiconductor element (116, 316) in response to the current signal (124) so as to control the magnitude of the current flowing between the first
 - 35 terminal (110, 310) and the second terminal (112, 312) in response to the current signal (124).

4. Power switching assembly according to claim 2 or 3,
- a control input (246) for receiving an external control signal (248);
 - wherein the controller (126, 226) is configured for controlling, in response to the external control signal (248), the first semiconductor element (114, 314) and the second semiconductor element (116, 316).
5. Power distribution system (100, 200) comprising:
- a power distribution bus (102, 202) having a first bus section (104, 204) and a second bus section (106, 206), wherein to each bus section at least one electrical consumer (242) is electrically coupleable;
 - a power switching assembly (108, 208, 308) according to claim 1 to 4, the power switching assembly having its first terminal (110, 310) electrically coupled to the first bus section (104, 204) and having its second terminal (112, 312) electrically coupled to the second bus section (106, 206).
6. Power distribution system (100, 200) according to claim 5 with the power switching assembly (108, 208, 308) being configured according to claim 4, the power distribution system comprising:
- a first generator (252) for providing electrical energy to the first bus section (104, 204);
 - a second generator (253) for providing electrical energy to the second bus section (106, 206);
 - a load controller (250), the load controller being configured for providing the external control signal (248) to the control input (246) of the power switching assembly (108, 208, 308) in order to control to the magnitude of the current flowing between the first terminal (110, 310) and the second terminal (112, 312) so as to alter a load distribution among the first generator (252) and the second generator (253).

1. A power distribution system (102, 202) having a power distribution bus (102, 202) with a first bus section (104, 204) and a second bus section (106, 206), the method comprising:

8. Method of operating a power distribution system having a power distribution bus (102, 202) with a first bus section (104, 204) and a second bus section (106, 206), the method comprising:
- controlling a current flow from the first bus section (104, 204) to the second bus section (106, 206) and from the second bus section (106, 206) to the first bus section (104, 204).

9. Computer program for controlling a physical object, namely a power switching assembly in a power distribution bus (102, 202), the computer program being configured for carrying out the method according to claim 8 when being executed by a processor assembly.

10. Use of a power switching assembly (108, 208, 308) according to one of claims 1 to 4 as a coupler of two bus sections (103, 204, 106, 206) of a power distribution bus (102, 202).