

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/012294 A2

(51) International Patent Classification⁷: **H01M 10/00**

(21) International Application Number:
PCT/US2003/024009

(22) International Filing Date: 31 July 2003 (31.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/399,881 31 July 2002 (31.07.2002) US

(71) Applicant: **RAYOVAC CORPORATION** [US/US]; 601
Rayovac Drive, Madison, WI 53744-4960 (US).

(72) Inventors: **BUSHONG, William, C.**; 6306 Keelseon
Drive, Madison, WI 53705 (US). **FREY, Karen, A.**; 320
West Pearl Street, Belleville, WI 53508 (US). **LUNDERT,**

Larry, J.; W8537 White Crow Road, Fort Atkinson, WI
53538 (US). **ROSE, Janna, L.**; 6110 Knollwood Drive,
Oregon, WI 53575 (US). **SCHUMACHER, Rhonda, E.**;
N4510 Hwy A, Lot 3C, Cambridge, WI 53523 (US).


(74) Agent: **FORMAN, Adam, J.**; Quarles & Brady LLP, 411
East Wisconsin Avenue, Milwaukee, WI 53202 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR DETECTING THE PRESENCE OF RECHARGEABLE BATTERIES



(57) Abstract: A method and apparatus are disclosed for automatically detecting the presence of a secondary cell and additionally differentiating between various types of secondary cells within the charger. Certain secondary cells include a band of ink that surrounds the cells and has a predetermined resistance that is detectable via charger contacts to identify the charging capability. The cell is detected using a pair of contacts that engage the outer surface of the cell at a predetermined location. The charger applies a charge to the cell that varies based on the sensed cell type.



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*