

PCT

WORLD INDUSTRIAL PROPERTY ORGANISATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED IN PURSUANCE OF THE PATENT CO-OPERATION TREATY (PCT)

5

(51) International Patent Classification ⁶ :
H05K 9/00

AI

(11) International Publication No:
WO 98/39957

10

(43) International publication date:
11th Sept 1998 (11.09.98)

15

(21) International application No:
PCT/DE98/00682(81) Designated States:
AL, AU, AZ, BA, BB, BG, BR,
CA, CN, CU, CZ, DE, EE, GE, HU, ID, IL, IS,
JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN,
MX, NO, NZ, PL, RO, SG, SI, SK, SL, TR, TT,
UA, US, UZ, VN, YU, ARIPO patent (GH, GM,
KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, DE, DK, ES, FI,
FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI
patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML,
MR, NE, SN, TD, TG).

20

25

(22) International filing date:
5th March 1998 (05.03.98)

30

(30) Priority data:
197 13 524.2
5th March 1997 (05.03.97)

DE

Published
With international Search Report.
Prior to expiry of the period allowed for amendment in the
claims. Publication is repeated if amendments are received.

35

(71)(72) Applicants and inventors
TIBURTIUS Bernd (DE/DE); Rosenhag 10,
D-14532 Kleinmachnow (DE), KAHL Helmut
(DE/DE); Horstwalder Str 23, D-12307 Berlin (DE)

40

(74) Attorney:
CHRISTIANSEN, Henning;
Pacellallee 43/45
D-14195 Berlin (DE)

45

(54) Title: METHOD OF PRODUCING A SHIELDING CASING
(57) Abstract

50

Method of producing a shielding casing (4) in which there is provided a sealing and shielding profile section (9) which fills a gap between first and second adjoining casing portions (1, 2) and which comprising pasty material is applied under pressure from a coordinate-controlled applicator device (5) having an applicator needle or nozzle directly on to the first casing portion and then sets there elastically adhering thereto in self-supporting relationship, wherein the sealing and shielding profile section is produced by simultaneously applying at least one first material (8a) with material properties adapted for a good sealing action and a second material (8b) with material properties adapted to a good shielding action, from the applicator needle or nozzle (6) provided with at least a first and a second passage (6a, 6b), whereby the second material firmly adheres to the first material.

55

60