

SYSTEM AND METHOD FOR PRODUCING HIGH PRESSURE FOAM SLURRY

BACKGROUND OF THE INVENTION

[0001] The statements in this section merely provide background information related to the present disclosure and may not constitute prior art.

[0002] In oil field well servicing applications, fluids can be foamed to create a dual phase system (i.e. bi-phase fluid) consisting of both gas and liquid phases. One example of the dual phase system is a foamed slurry which may be a cement or sand and water. A foamed cement slurry is particularly useful in certain oilfield operations.

[0003] US4,797,003 discloses an apparatus and process for uniformly dispersing gas through a slurry to provide a stable foam slurry.

[0004] Co-pending and co-assigned US patent application with serial no.: 12/641380, filed on December 18, 2009, discloses a method and system for monitoring the production of a bi-phase fluid.

[0005] However, there remains a need to further improve the system and method for generating high quality bi-phase fluid, such as foamed cement slurries for use at the wellsite. Currently, the foaming process requires the setup of a system that comprises multiple equipments scattered over a relatively large area operated by multiple workers/personnel. The setup includes both the conventional cementing equipment utilized for non-foamed operations and those highly specialized equipments for foam generation, mixing and delivery. Moreover, many foaming operations are requested by wellsite workers/personnel on a *pro hoc* basis, a significant amount of equipment handlings and pipe connections are typically required at the site of the operation. This reduces the efficiency of the operation and may compromise the quality and safety of the project. Accordingly, it is desirable to have systems and methods with reduced amount of equipment and pipe handling at the site of operation, so foam generating processes may be quickly and safely delivered. This application aims to address one or more problems associated with the current foamed cement operations.

SUMMARY

[0006] According to one aspect, there is provided a method of generating high pressure dual phase mixture. The method comprises mounting a dual phase mixture generator on a transportable platform where the dual phase mixture generator comprises a mixing chamber connected with at least a first inlet, a second inlet, and a first outlet. The method further comprises mounting a first container and a first pump on the transportable platform where the first pump is operably connected with the first container. The method additionally comprises deploying the transportable platform at a wellsite, introducing a base fluid into the first inlet under high pressure, introducing a gas into the second inlet under high pressure, combining the base fluid with the gas in the mixing chamber to generate a high pressure dual phase mixture, and discharging the generated high pressure dual phase mixture via the outlet.

[0007] According to another aspect, provided are systems for generating high pressure dual phase mixtures. The systems comprise a transportable platform, a dual phase mixture generator mounted on the transportable platform, a first container mounted on the transportable platform and operably connected with a first pump mounted on the transportable platform. The dual phase mixture generator comprises a mixing chamber connected with at least a first inlet, a second inlet, and a first outlet. The first inlet is configured to receive a base fluid under high pressure, the second inlet is configured to receive a gas under high pressure, the mixing chamber is configured to combine the base fluid and the gas to generate a high pressure dual phase mixture, and the outlet is configured to discharge the generated high pressure dual phase mixture for use at the wellsite, such as injecting the mixture into a well located at the wellsite.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] These and other features and advantages will be better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings.

[0009] FIG. 1 is a schematic representation of a dual phase mixture generator according to an embodiment of the current application.

[0010] FIG. 2 is a schematic representation of a dual phase mixture generator according to another embodiment of the current application.

[0011] FIG. 3 is a schematic representation of a system for generating a dual phase mixture according to one embodiment of the current application.

[0012] FIG. 4 is a schematic representation of another system for generating a dual phase mixture according to another embodiment of the current application.

DETAILED DESCRIPTION OF SOME ILLUSTRATIVE EMBODIMENTS

[0013] Some embodiments relate generally to systems and methods for producing high pressure foam slurry for use in wellbores penetrating a subterranean formation.

[0014] As used herein, the term “high pressure” means a pressure that is substantially higher than atmospheric pressure. In some cases, the high pressure is at least about 1000 psi, inclusive. In some other cases, the high pressure is at least about 2500 psi, inclusive. In some further cases, the high pressure is at least about 5000 psi, inclusive. In yet some other cases, the high pressure is at least about 7500 psi, inclusive. In some additional cases, the high pressure is at least about 10,000 psi, inclusive, or at least about 15,000 psi, inclusive, or any other pressures readily conceivable by people skilled in the art in view of the teachings of the current application.

[0015] As used herein, the term “base fluid” may comprise a fluid, a liquid, a solid, a gas, and combinations thereof, as will be appreciated by those skilled in the art. Additionally, the term “liquid” or “fluid” is used in a broad sense, including traditional liquids such as water and dissolved solutions, as well as mixtures of solids and liquid such as suspensions and slurries. In particular, as used herein, the term “base fluid” includes cement slurries for use in the oil and gas industry, with or without additives such as foaming agent, stabilizing agent, and the combination thereof.

[0016] According to one aspect, FIG. 1 shows a system for generating high pressure dual phase mixture generally indicated at **100**. The system **100** comprises a transportable platform **90**, a dual phase mixture generator **10** mounted on the transportable platform **90**, a first container **20** mounted on the transportable platform **90**, and a first pump **30** mounted on the transportable platform **90**, wherein the first pump **30** is operably connected with the first container **20**.

[0017] In one embodiment, the dual phase mixture generator **10** comprises a mixing chamber **18** that is connected with and is in fluid communication with a first inlet **12**, a

second inlet **14**, and a first outlet **16**. The first inlet **12** is configured to receive a base fluid under high pressure. The second inlet **14** is configured to receive a gas under high pressure. The mixing chamber **18** is configured to combine the base fluid received from the first inlet **12** and the gas received from the second inlet **14** to form a high pressure dual phase mixture. The generated dual phase mixture is then discharged from the outlet **16** for use at the wellsite **4**. In some cases, the generated high pressure dual phase mixture is pumped into a well **2** located at the wellsite **4**.

[0018] According to another embodiment, the dual phase mixture is a foamed cement slurry. In some cases, the base fluid is a cement slurry containing a foaming additive. In some cases, the gas is nitrogen, although any suitable gas may be used.

[0019] The container **20** contains a foaming additive that may be a foaming agent, a foaming stabilizer, or a mixture thereof. Optionally, the first container **20** is further divided into two separate compartments **20A** and **20B**, with compartment **20A** containing a foaming agent and compartment **20B** containing a foaming stabilizer. The foaming agent and stabilizer may be mixed in a desired ratio at the wellsite **4** before the commencement of the well treatment operation. In some cases, the foaming agent and stabilizer are mixed at a 50/50 ratio.

[0020] In another embodiment, the container **20** contains liquid nitrogen and the first pump **30** is a liquid nitrogen pump that pumps the nitrogen from the first container **20** into the second inlet **14** of the dual phase mixture generator **10**.

[0021] Optionally, the system **100** for generating high pressure dual phase mixture further includes a data acquisition and/or control console **40**. The console **40** may function as a monitoring device that collects data from various sensors deployed in the system and verifies if the system is operating according to the required specification. (See FIG. 2 of the current application for more details.) Alternatively, the console **40** may function as a control station from where the field operator may enter parameters of a particular foaming project and control the progress of the foaming project. In some embodiments, the console **40** functions as both a monitoring device and a control station.

[0022] Optionally, the system **100** for generating high pressure dual phase mixture may further include a power supply **50** supplying energy to the equipment mounted on the transportable platform **90**.

[0023] Variations to the above depicted system **100** are possible. For example, as shown in FIG. 2 of the current application, the base fluid may be introduced to the system **100** via a fluid conduit **11** and split into two steams **11A** and **11B** at a "T" connector **19**. Steam **11A** is then fed into inlet **12A** of the dual phase mixture generator **10'**. Steam **11B** is then fed into inlet **12B** of the dual phase mixture generator **10'**. The gas component is introduced into the system **100** via a fluid conduit **13** and fed into inlet **14'** of dual phase mixture generator **10'**. The generated high pressure dual phase mixture is discharged through outlet **16'** via fluid conduit **17**.

[0024] Optionally, the system **100** includes a plurality of sensors **42**, **44**, **46**, **48** in data communication with the console **40** to monitor characteristics of materials flowing through a plurality of conduits **11**, **13**, **17** that are in fluid communication with each other. As a non-limiting example, the first sensor **42** may be a coriolis flow meter to measure a flow rate of the base fluid flowing through the fluid conduit **11**. Similarly, the second sensor **44** is a turbine flow meter measuring a flow rate of a gas flowing through the gas conduit **13**. The third sensor **46** may be a pressure transducer to measure a pressure of the foam conduit **17**. The fourth sensor **48** may be a temperature sensor for measuring the temperature of a foamed bi-phase fluid flowing in the foam conduit **17**. It is understood that any sensors capable of measuring like characteristics of a bi-phase fluid can be used. It is further understood that any number of sensors can be used.

[0025] According to one embodiment of the current application, the console **40** is in data communication with each of the sensors **42**, **44**, **46**, **48** to receive data therefrom. The console **40** may be any device or system adapted to receive data from at least one of the sensors **42**, **44**, **46**, **48**, analyze the received data based upon an instruction set **41**, and calculate at least one parameter of the materials flowing through the conduits **11**, **13**, **17**. The instruction set **41** may be embodied within any computer readable medium, includes processor executable instructions for configuring the console **40** to perform a variety of tasks and calculations.

[0026] In certain embodiments, the console **40** includes a storage device **43** such as a solid state storage system, a magnetic storage system, an optical storage system or any other suitable storage system or device. The storage device **30** is adapted to store the instruction set **41** as well as other data and information received and/or calculated by the console **40**. The console **40** may further include a programmable

device or component **45** that is in communication with any other component of the system **100** such as the sensors **42, 44, 46, 48**, for example. In some embodiments, the programmable component **45** is adapted to manage and control processing functions of the console **40**, the sensors **42, 44, 46, 48**, and/or other components of the system **100**.

[0027] In operation, a base fluid is caused to flow through the fluid conduit **11** while a gas is caused to flow through the gas conduit **13**. The gas is combined with the base fluid to form a foamed bi-phase fluid routed through the foam conduit **17**. The sensors **42, 44, 46, 48** measure characteristics of the base fluid, the gas, and the foamed bi-phase fluid, as they pass through the respective conduits **11, 13, 17**. Each of the sensors **42, 44, 46, 48** transmits data representing the measured characteristics to the processor of console **40**. The processor of console **40** receives the data and uses the measured characteristics to calculate an unknown parameter of the foamed bi-phase fluid. Specifically, based on the measured pressure and temperature from the third sensor **46** and the fourth sensor **48** respectively, the measured characteristics of the fluid in the fluid conduit **11** received from the first sensor **42**, the measured characteristics of the gas in the gas conduit **13** received from the second sensor **44**, and other known parameters, at least one of the quality, the density, the flow rate, and the velocity of the bi-phase fluid can be calculated at conditions present in the foam conduit **17**. In certain embodiments the calculated parameter of the bi-phase fluid is at least one of presented on a display **47** connected to the processor of console **40** and stored in the storage device **43**.

[0028] Referring now to FIG. 3 of the current application, system **100** is provided for generating high pressure dual phase mixtures where the dual phase mixture is a foamed cement slurry. The system **100** comprises a transportable platform **90**, a dual phase mixture generator **10'** mounted on the transportable platform **90**, a first container **20** mounted on the transportable platform **90**, and a first pump **30** mounted on the transportable platform **90**, where the first pump **30** is operably connected with the first container **20**.

[0029] In one embodiment, system **100** further includes a data acquisition/control console **40**, cement generating equipment **70** and nitrogen supply unit **80**. The data acquisition/control console **40** acquires data from sensors deployed in the system **100**, analyzes the data, monitors the status of the system **100**, and/or controls the operation of the system **100**, according to the description set forth above.

[0030] The cement generating equipment **70** produces cement slurries and feeds the cement slurries into the dual phase mixture generator **10'**. In one embodiment, the cement generating equipment **70** comprises a high pressure pump (not shown) having a suction side and a discharge side. The suction side is under a low pressure, which receives a cement slurry from other components of the cement generating equipment **70** and the foaming additive(s) from a source, such as the first pump **30** and the first container **20** according to one embodiment. The discharge side of the high pressure pump is under a high pressure, which pumps the mixture of the cement slurry and the foaming additive(s) under the high pressure into inlet **12**, **12A**, **12B** of the dual phase mixture generator **10**, **10'**.

[0031] Alternatively, the foaming additive(s) can be added directly to conduit **11**, **11A**, or **11B** or at the position where the "T" connector **19** occupies, as depicted in FIG. 2. In this embodiment, the foaming additive(s) will bypass the cement generating equipment **70**. The cement slurry generated by equipment **70** mixes with the foaming additive(s) in conduit **11**, **11A**, or **11B** and the mixture thereof is introduced into the dual phase mixture generator **10**, **10'** via the first inlet **12**, **12A**, **12B**.

[0032] In the depicted embodiment in FIG. 3, the cement generating equipment **70** is not mounted on the transportable platform **90**, but instead, positioned at a distance from the transportable platform **90**. In some cases, the cement generating equipment **70** is mounted on a separate truck or platform; in some other cases, the cement generating equipment **70** is positioned on the ground at the wellsite **4**. However, it is understood that the cement generating equipment **70** or a portion thereof can be mounted on the transportable platform **90** as well.

[0033] In FIG. 3, the system **100** further comprises a nitrogen supply unit **80** that supplies nitrogen to the dual phase mixture generator **10'**. The nitrogen supply unit **80** may comprise a container, such as a tank, containing a high pressure nitrogen pump and a nitrogen pump that pumps nitrogen under high pressure into inlet **14** of the system **100**. Alternatively, the nitrogen supply unit **80** may comprise a series of nitrogen bottles containing compressed nitrogen gas. It is understood that in order to deliver high pressure nitrogen gas, a series of nitrogen bottles must be employed because each individual nitrogen bottle typically can only deliver nitrogen gas at about 50 to 250 psi maximum. In some embodiments, 5 nitrogen bottles are connected together to achieve the necessary high pressure. In some other cases, 10

nitrogen bottles are employed. In some further cases, 25 nitrogen bottles are connected together for a foaming operation. Variations to the numbers of nitrogen bottles are thus within the teachings of the current application.

[0034] In FIG. 3, the depicted embodiment shows that the nitrogen supply unit **80** is not mounted on the transportable platform **90**, but instead is positioned at a distance from the transportable platform **90**. In some cases, the nitrogen supply unit **80** is mounted on a separate truck or platform; in some other cases, the nitrogen supply unit **80** is simply rested on the ground at the wellsite. However, it is understood that the nitrogen supply unit **80** or a portion thereof can be mounted on the transportable platform **90** as well.

[0035] Accordingly, as shown in FIG. 4 in accordance with another embodiment, system **200** is provided for generating high pressure dual phase mixture, where the system comprises a dual phase mixture generator **210** mounted on a transportable platform **290**, a first container **220** that is mounted on the transportable platform and is operably connected to a first pump **230**, and a second container **225** that is mounted on the transportable platform **290** which is operably connected to a second pump **235**, where the first container **220** contains a foaming additive and the second container **225** contains a source of a gas. System **200** may further include cement generating equipment **270** that is either mounted or not mounted on the transportable platform **290**.

[0036] The transportable platform **90**, **290** can be in any form perceivably by people skilled in the art in view of the teachings of the current application. In some embodiments, the transportable platform **90**, **290** is a chassis of a road legal truck. In some other embodiments, the transportable platform **90**, **290** is a deck or a portion of a deck of a ship, vessel, or a towboat. In some additional embodiments, the transportable platform **90**, **290** is a flatbed or grillage that can be lifted and mounted on a transportation vehicle, such as a truck, a trailer, a ship, a vessel, or a towboat, etc. Variations to the form of the transportable platform **90**, **290** are within the disclosure of the current application.

[0037] The preceding description has been presented with reference to some illustrative embodiments of the Inventors' concept. Persons skilled in the art and technology to which this invention pertains will appreciate that alterations and changes in the described structures and methods of operation can be practiced

without meaningfully departing from the principle, and scope of this invention. Accordingly, the foregoing description should not be read as pertaining only to the precise structures described and shown in the accompanying drawings, but rather should be read as consistent with and as support for the following claims, which are to have their fullest and fairest scope.

We claim:

1. A method of generating high pressure dual phase mixture, the method comprising:

mounting a dual phase mixture generator on a transportable platform, wherein the dual phase mixture generator comprises a mixing chamber connected with at least a first inlet, a second inlet, and a first outlet;

mounting a first container and a first pump on the transportable platform, wherein the first pump is operably connected with the first container;

deploying the transportable platform at a wellsite;

introducing a base fluid into the first inlet under high pressure;

introducing a gas into the second inlet under high pressure;

combining the base fluid with the gas in the mixing chamber to generate a high pressure dual phase mixture;

discharging the generated high pressure dual phase mixture via the outlet.

2. The method of claim 1, further comprising introducing the high pressure dual phase mixture into a well at the wellsite.

3. The method of claim 1, wherein the dual phase mixture is a foamed cement slurry.

4. The method of claim 3, wherein the base fluid is a cement slurry containing a foaming additive and the gas is nitrogen.

5. The method of claim 4, wherein the cement slurry containing a foaming additive is produced by cement generating equipment, the equipment either mounted transportable platform, not mounted on the transportable platform, or partially mounted on the transportable platform.

6. The method of claim 5, wherein the first container contains the foaming additive and the first pump pumps the foaming additive to the cement generating equipment for mixing with the cement slurry, and a mixture of the foaming additive and the cement slurry is introduced into the first inlet of the dual phase mixture generator.

7. The method of claim 6, wherein the foaming additive is a foaming agent, a foam stabilizer, or a mixture thereof.

8. The method of claim 7, wherein the first container comprises two separate compartments, wherein a first compartment contains the foaming agent and a second compartment containing the foam stabilizer.

9. The method of claim 5, wherein the first container contains liquid nitrogen and the first pump pumps the liquid nitrogen from the first container into the second inlet of the dual phase mixture generator.

10. The method of claim 5, further comprising:

mounting a second container and a second pump on the transportable platform, wherein the second pump is operably connected with the second container;

wherein the first container contains a foaming additive and the first pump pumps the foaming additive to the cement generating equipment for mixing with the cement slurry produced therein, and a mixture of the foaming additive and the cement slurry is introduced into the first inlet of the dual phase mixture generator; and,

wherein the second container contains liquid nitrogen and the second pump pumps the liquid nitrogen from the second container into the second inlet of the dual phase mixture generator.

11. The method of claim 10, wherein the cement generating equipment comprises a high pressure pump and the foaming additive is pumped into a suction end of the high pressure pump.

12. The method of claim 10, wherein the transportable platform is mounted on a trailer or a vessel.

13. A system for generating high pressure dual phase mixture, the system comprising:

a transportable platform;

a dual phase mixture generator mounted on the transportable platform,

wherein the dual phase mixture generator comprises a mixing chamber connected with at least a first inlet, a second inlet, and a first outlet, and

wherein the first inlet is configured to receive a base fluid under high pressure, the second inlet is configured to receive a gas under high pressure, the mixing chamber is configured to combine the base fluid and the gas to generate a high pressure dual phase mixture, and the outlet is configured to discharge the generated high pressure dual phase mixture; and

a first container and a first pump mounted on the transportable platform, wherein the first pump is operably connected with the first container.

14. The system of claim 13, wherein the transportable platform is mounted on a trailer or a vessel.

15. The system of claim 13, wherein the dual phase mixture is a foamed cement slurry, the base fluid is a cement slurry containing a foaming additive, and the gas is nitrogen.

16. The system of claim 15, wherein the cement slurry containing a foaming additive is produced by cement generating equipment, the equipment either mounted transportable platform, not mounted on the transportable platform, or partially mounted on the transportable platform.

17. The system of claim 16, wherein the first container contains the foaming additive selected from a foaming agent, a foam stabilizer, or a mixture thereof.

18. The system of claim 17, wherein the first container comprises two separate compartments, wherein a first compartment contains the foaming agent and a second compartment containing the foam stabilizer.

19. The system of claim 16, wherein the first container contains liquid nitrogen and the first pump pumps the liquid nitrogen from the first container into the second inlet of the dual phase mixture generator.

20. The system of claim 16, further comprising:

a second container and a second pump mounted on the transportable platform, wherein the second pump is operably connected with the second container;

wherein the first container contains a foaming additive and the first pump pumps the foaming additive to the cement generating equipment for mixing with the cement slurry produced therein, and a mixture of the foaming additive and the cement slurry is introduced into the first inlet of the dual phase mixture generator;

wherein the second container contains liquid nitrogen and the second pump pumps the liquid nitrogen from the second container into the second inlet of the dual phase mixture generator.

21. The system of claim 13, further comprising a control panel that monitors a condition of the apparatus and/or controls a process of generating high pressure dual phase mixture.