

DESCRIPTION

【Invention Title】

ANASTOMAT FOR CIRCUMCISION

【Technical Field】

The present invention relates to a medical apparatus and instrument, particularly to an apparatus and instrument for cutting off the excess foreskin of a male.

【Background Art】

The redundant prepuce or phimosis is one of the origins of diseases such as male urinary system disease and sexually transmitted disease, which may results in the chronic prostatitis as well as a series of symptoms such as backache, impotence and premature ejaculation. Therefore, removing the redundant prepuce or phimosis is one of the measures to prevent such diseases mentioned above.

Methods for removing the redundant prepuce or phimosis have been innovated for several times since early times of new Country, one of which is to perform a surgical operation. However, an operation inevitably produces bleeding and suffering, and the wound needs to be stitched, the patient needs to take antiphlogistic or hang an antiphlogistic bottle as well as change dressing every day after the operation. Moreover, the stitches need to be removed after healing, which may result in walking inconvenience. Therefore, such operation is preferred to be performed under hospitalization which costs much for an entire treatment. Another method is the circumcision utilizing laser. Due to the clinical application of laser, the problem of bleeding during an operation was resolved. However, it may burn the skin and cause edema. Furthermore,

the stitching of wound requires catgut and costs a longer time. The treatment required mass of antibiotics is expensive for the public. Additionally, obvious scars would occur.

There is still another method disclosed in the Chinese patent No. 200310118525.7, titled “tubular anastomat for circumcision with bearings”, in which, problems such as bleeding, stitching, antiphlogistic requirement and expensive cost which may occur during a surgical operation for removing the redundant foreskin were resolved. However, said tubular anastomat for circumcision is arranged as an integrated sleeve equipped with an annular knife therein whose cutting edge is relatively sharp, this causes severely suffering during the operation and healing process. Moreover, since the tubular anastomat for circumcision formed into an integrated configuration whose weight cannot be ignored has to be suspended on the penis for a while after the foreskin cutting process, the patient may feel uncomfortable. Furthermore, it would directly influence the foreskin cutting as well as the postoperative recovery, if the penis becomes hyperemia due to erection. Additionally, when used, the cut deepness to the foreskin is adjusted by a spring arranged at one side of the bearing or stop collar, which is not accurate enough and hard to control.

【Content of the Invention】

The present invention is intended to overcome drawbacks of existing technology and provide an anastomat for circumcision which can minimize the possibility of bleeding, suffering, suture and antiphlogistic requirement, and prevent the occurrence of penile erection during the foreskin cutting and postoperative recovery, as well as facilitate the cut

deepness control, by utilizing a movable and elevating cutting knife.

In order to resolve the problems mentioned above, an anastomat for circumcision is provided, which comprises:

- an inner cutting ring comprising an upper casing pipe, a lower casing pipe and a connecting plate for connecting said upper casing pipe and said lower casing pipe;

- an outer cutting ring comprising an upper sleeve, an upper annular blocking piece arranged at the upper end of said upper sleeve, a lower sleeve, and a connecting rod for connecting said upper sleeve and said lower sleeve;

- a connecting ring comprising a casing pipe and a lower annular blocking piece arranged at the lower end of said casing pipe;

- a detachable anti-erection plate with several evenly distributed projecting spots thereon is arranged at the inner side of said connecting plate of the inner cutting ring;

said inner cutting ring is sleeved within said outer cutting ring, wherein said upper casing pipe of the inner cutting ring has an upper end connecting to the inner side of said upper annular blocking piece of the outer cutting ring in a crimped mode, and said lower casing pipe of the inner cutting ring has a lower end connecting to the inner side of said lower annular blocking piece of the connecting ring in a crimped mode; said lower sleeve of the outer cutting ring is detachably connected with said casing pipe of the connecting ring;

there is clearance between said inner cutting ring and said outer cutting ring for accommodating the foreskin.

Wherein,

- an elevating tubular cutting knife for cutting the foreskin comprising

a cutting casing pipe, a helix groove arranged on the pipe wall of said cutting casing pipe, a pipe foot arranged at the lower end of said cutting casing pipe, and a rotary buckle connected with said pipe foot;

said elevating tubular cutting knife is sleeved between said inner cutting ring and said outer cutting ring; said pipe foot is inserted through an arc groove on said lower annular blocking piece in the connecting ring and then connected to said rotary buckle on the tubular cutting knife.

Said connecting plate of the inner cutting ring is provided with a projecting snap on its external surface which is fitted with a helix groove provided on the pipe wall of the cutting casing pipe.

Said cutting casing pipe of the elevating tubular cutting knife has an end provided with an acute-angled cutting edge or a zigzag cutting edge which is fitted with the inner side of said upper annular blocking piece of the outer cutting ring, or with a rubber washer arranged in said upper annular blocking piece of the outer cutting ring, in a pressing mode.

Said cutting casing pipe of the elevating tubular cutting knife has an inner diameter equal to the outer diameter of said upper casing pipe and lower casing pipe in said inner cutting ring.

Said connecting rod is provided with a graduated ruler, a digital ruler and an alarm at its external surface.

The external wall of said lower sleeve of the outer cutting ring and the external wall of said casing pipe of the connecting ring are also provided with graduated rulers respectively.

Said digital ruler includes a raster digital ruler, an electromagnetic induced digital ruler, and an infrared digital ruler.

Said alarm comprises a circuit board, on which a warning or reminding memory chip and a speech chip for alarming and reminding

are provided, said speech chip is used for reminding the situation that said lower sleeve of the outer cutting ring is connected with said casing pipe of the connecting ring overly tight, and/or reminding the information of healing.

Said upper casing pipe of the inner cutting ring is evenly distributed with several face tooth formed into patterns on its end surface, which are fitted with the inner side of said upper annular blocking piece of the outer cutting ring or a rubber washer arranged in said upper annular blocking piece, in a pressing mode.

Said upper casing pipe of the inner cutting ring has an upper end whose section is formed into V-type tooth or M-type tooth which are fitted with the inner side of said upper annular blocking piece of the outer cutting ring or a rubber washer arranged in said upper annular blocking piece, in a pressing mode.

Each of said upper casing pipe and lower casing pipe of the inner cutting ring is formed into a circular splicing casing pipe consisted of several segments of arc plates which are spliced together in a snap-fit way; a lacerable strip which is liable to be torn in a longitudinal direction is arranged on the pipe wall of each of said upper casing pipe and lower casing pipe of the inner cutting ring.

Said outer cutting ring and said connecting ring are connected with each other by a thread, or by clamping a snap arranged on the external wall of said outer cutting ring into a slot arranged on said connecting ring, or by engaging a ratchet arranged on said outer cutting ring with a screw thread arranged on said connecting ring, wherein the ratchet arranged on said connecting ring is liable to be torn.

Said upper annular blocking piece is provided with several

projecting spots on its internal surface; a washer is arranged below said projecting spots, while a rubber pad is arranged below said washer.

There are frosted patterns arranged on the surface of each of said inner cutting ring, outer cutting ring and connecting ring.

An anastomat for circumcision comprising a tubular inner ring, a tubular outer ring sleeved outside of said tubular inner ring, and a empty cavity for accommodating the foreskin arranged between said tubular inner ring and said tubular outer ring, said tubular outer ring is consisted of an outer ring A and an outer ring B connected with each other, the end part of each is provided with a stop collar having a washer at its inner side; one end of said tubular inner ring is formed as a circumcision end whose external side is provided with a projecting edge; the lower end of said projecting edge is equipped with a binding strip for securing the foreskin; said circumcision end is fitted with said washer arranged at the inner side of the stop collar arranged at the end part of the outer ring A so as to extrude the foreskin; while the other end of said tubular inner ring is fitted with the internal side of said stop collar arranged at the end part of the outer ring A so as to axially compress against the tubular inner ring.

Wherein,

There are through holes for injecting medicine solution or cleaner fluid therethrough arranged on the side wall of said tubular outer ring or the end surface of said stop collar; said side wall of the tubular outer ring is further provided with several dismounting holes for dismounting the connection between said outer ring A and outer ring B.

The external wall of said tubular outer ring is provided with bumps or recesses or patterns used for slip-resistance.

Said circumcision end is provided with several projecting spots at its

end part.

Said circumcision end is provided with several saw teeth at its end part.

Said tubular inner ring has another end connected with said stop collar arranged on the outer ring B, to form a whole.

The projecting edge on the external side of said circumcision end has a surface formed into a taper face whose lower end forms a right angle with the external wall of said tubular inner ring, through which the foreskin can be secured on the external wall of the tubular inner ring by a binding strip; wherein said taper face is fitted with positioning bumps on a taper face or arc face between the internal surface of the outer ring A and the internal surface of the stop collar.

Said projecting edge can be broken down into several segments.

Said tubular inner ring is a splicing ring consisted of at least two semicircles which are spliced together.

Said tubular outer ring is consisted of two semicircles whose adjacent ends are connected with each other through a snap fastener or a screw thread.

An anastomat for circumcision comprises an outer ring for cutting and clamping, and an inner ring for casing the foreskin; said inner ring can be formed into a whole ring or two semicircles or more than two arc segments whose external surface is provided with at least one circle of recess having an elastic washer at its surface; the inner side of said outer ring is provided with at least one circle of knife edge having several saw teeth or projecting spots evenly distributed at its fringe; said knife edge is fitted with said recess so as to extrude and/or cut off the foreskin; the side wall of said outer ring is provided with channels for injecting medicine

solution which are communicated with an empty cavity arranged between said outer ring and inner ring.

Said outer ring is formed into two semicircular split rings or an integrated flexible split ring having at least one opening with two ends provided with an upper knife edge junction and a corresponding lower knife edge junction respectively; each of said upper knife edge and lower knife edge is a single-layered knife edge or a double-layered knife edge coated with anti-infection coating; several cutting blades vertical to said double-layered knife edge are sandwiched therebetween.

The end of said opening, where the upper knife edge junction is arranged, is provided with a first ladder snap-fitted block, while the other end of said opening, where the lower knife edge junction is arranged, is provided with a second ladder snap-fitted block, and said first ladder snap-fitted block and said second ladder snap-fitted block are fitted with each other; each of said first ladder snap-fitted block and said second ladder snap-fitted block is formed as single-layered or double-layered;

Said first ladder snap-fitted block is arranged below the upper knife edge junction, and said second ladder snap-fitted block is arranged above the lower knife edge junction;

The fringe of each of said upper knife edge junction and said lower knife edge junction is provided with a round corner;

Each of said upper knife edge and/or said lower knife edge is provided with patterns.

said outer ring is consisted of two semicircular split rings providing two openings, one of which may be connected by a connecting snap; while the integrated flexible split ring provides a opening and a un-split connected part;

one of the openings of said two semicircular split rings, or the opening of said integrated flexible split ring has two ends provided with an upper knife edge junction and a corresponding lower knife edge junction respectively; the fringe of each of said upper knife edge junction and said lower knife edge junction is provided with a round corner.

The un-split connected part of said integrated flexible split ring or the other opening of said two semicircular split rings is locked and fixed through a screw stem.

Any opening of said two semicircular split rings, or the opening of said integrated flexible split ring has two ends provided with L-shaped parts respectively which are fitted with each other; each of said L-shaped parts is provided with a connecting rod at its top end and a connecting hole on a platform at its bottom end; wherein the connecting rod of one L-shaped part is fitted with the connecting hole of the other L-shaped part; each of said L-shaped parts has a vertical end whose internal side is provided with a dentoid protuberance or dentoid groove, wherein the dentoid protuberance or dentoid groove of one L-shaped part is fitted with the dentoid groove or dentoid protuberance of the other L-shaped part.

Any opening of said two semicircular split rings, or the opening of said integrated flexible split ring has two ends provided with a hook-like protuberance or a slotted hole respectively, wherein the hook-like protuberance or slotted hole arranged on one end is fitted with the slotted hole or hook-like protuberance arranged on the other end; each of said hook-like protuberances is consisted of a connecting plate and an inverted-V-type clamping piece, wherein said connecting plate has one end connecting to the middle part of the clamping piece. Any opening of

said two semicircular split rings, or the opening of said integrated flexible split ring has two ends provided with concave slotted holes respectively; said concave slotted holes receives a bow tie-like block. Any opening of said two semicircular split rings, or the opening of said integrated flexible split ring has two ends provided with bar-type denticles or bar-type sprocket holes respectively, wherein the bar-type denticle or bar-type sprocket hole arranged at one end is fitted with the bar-type sprocket hole or bar-type denticle arranged on the other end.

Said outer ring formed into two semicircular split rings or an integrated flexible split ring is provided with two circles of snap rings thereon; while said inner ring is provided with recesses thereon which are fitted with said snap rings; said recesses are provided with a convex ring therebetween; said inner ring is consisted of a left ferrule and a right ferrule which are configured to be spaced apart from each other with a junction provided with a round corner.

One opening of said two semicircular split rings, or the opening of said integrated flexible split ring has one end provided with a graduated ruler or a digital ruler for displaying dates indicating the tightness degree of the snap-fit, and the other end provided with an alarm for reminding an overly tight snap-fitted situation and/or information of wound healing.

Either end of one opening of said two semicircular split rings or the opening of said integrated flexible split ring said opening is provided with an unlocking stem and an unlocking hole.

A rubber pad is arranged between said outer ring and said inner ring.

There are frosted patterns arranged on the surface of said outer ring and said inner ring.

The channels for injecting medicine solution formed on the outer ring are configured to be two or more.

When used, said inner cutting ring I, elevating tubular cutting knife II, connecting ring IV are arranged onto the outside of the penis, and the excess foreskin is turned over to be covered onto the outside of the upper casing pipe 1 of the inner cutting ring I, then the outer cutting ring III is connected with said inner cutting ring I through a thread or snap; at this time, the patterns 11 or the A-typed tooth and M-typed tooth on the face teeth 12 is gradually compressed against the inner side of the upper annular blocking piece 6 of the outer cutting ring III or to the rubber washer 4 arranged at the inner side of said upper annular blocking piece 6, so as to gradually extrude the root of the excess foreskin there between and hold back its blood circulation; finally, the rotary buckle 26 arranged at the lower end of the elevating tubular cutting knife II is rotated, which enables the helix groove 24 on the cutting casing pipe 24 to be fitted with the projecting snap arranged on the external wall of the connecting plate in the inner cutting ring I; in this way, the cutting casing pipe 24 is lifted up along said helix groove 14 so as to cut off the necrotic foreskin through the acute-angled cutting edge 21 or zigzag cutting edge 21a arranged on the end part of the cutting casing pipe 24; after that, the rotary buckle 26 is inversely rotated so as to withdraw the cutting casing pipe 24 , thereby a foreskin cutting is finished.

Alternatively, the elevating tubular cutting knife II may be dismantled completely several days after the excess foreskin being compressed at its root part, when the compressed foreskin is gradually necrotic and separated from the penis automatically. Once the excess foreskin is cut off by the elevating tubular cutting knife II, or during the

cutting process or healing stage, an anti-erection plate V provided with projecting spots for stimulating the penis is required to be inserted between the penis skin and the inner side of the upper casing pipe 1, lower casing pipe 2 and connecting plate 3 of the inner cutting ring I, so as to avoid penile erection which may stretch the penis. Moreover, scale marks are provide on the external side of the connecting rod 8 of the outer cutting ring III and the casing pipe 9 of the connecting ring IV, in order to control or adjust the cutting deepness to the foreskin as desired.

The anastomat for circumcision according to the present invention provides a treatment for curing redundant prepuce or phimosis without suffering, creating wounds, bleeding, stitching, taking medicine and feeling of fear. Particularly, when used, the M-type teeth 12b included will compress the foreskin tightly, and an M-type recess of said M-type teeth 12b allows the antalgescic provided therein, so that the whole operation may cost only several minutes. Furthermore, when finished, the patient is able to leave the treatment place immediately and the affected part will be healing in four days without leaving obvious scars, which does not influence normal working and studying.

Since its configuration of only arranging an upper casing pipe and a lower casing pipe in the upper part and lower part of the inner cutting ring I and outer cutting ring III respectively which are connected through a connecting plate 3 or connecting rod 8, the anastomat for circumcision according to the present invention has reduced entire weight. Furthermore, the upper casing pipe 1 of the inner cutting ring I has an upper end face 11 formed into patterns, which significantly relieves the suffering, when compared with known annular knife edge. Moreover, the connecting plate 3 of the inner cutting ring I is additionally provided with an anti-erection

plate V for preventing the penis from erecting, which effectively avoids the suffering due to wound produced by penile erection. Besides, the graduated ruler arranged on the external side of the connecting rod 8 of the outer cutting ring III may facilitate adjusting the crimping force produced between the outer cutting ring and connecting ring depending on the thickness of the foreskin, as well as facilitate adjusting the cut deepness of the foreskin when an elevating cutting knife II is arranged between the outer cutting ring III and the connecting ring IV. In addition, since either the upper casing pipe 1 or the lower casing pipe 2 of the inner cutting ring I may be designed into a splicing ring, the inner diameter of the inner cutting ring I may be adjusted according to the requirement of patients. Due to the moveable configuration, the elevating cutting knife II may be lifted up and withdrawn back as desired, which provides a flexible operation. Finally, the present anastomat for circumcision is a disposable product which prevents the disease spreading. Therefore, the present invention provides advantages such as small and exquisite, light weight, convenient to use, as well as low cost, which is valuable to be widely popularized in general hospitals.

【Description of Figures】

Fig.1 illustrates an exploded assembly view of an anastomat for circumcision according to the present invention;

Fig.2 illustrates another exploded assembly view of an anastomat for circumcision according to the present invention;

Fig.3 illustrates a perspective view of an acute-angled cutting edge of a detachable cutting knife in an anastomat for circumcision according to the present invention;

Fig.4 illustrates a perspective view of a zigzag cutting edge of a

detachable cutting knife in an anastomat for circumcision according to the present invention;

Fig.5 illustrates a sectional view of an anastomat for circumcision provided with a rubber washer according to the present invention;

Fig.6 illustrates a sectional view of an anastomat for circumcision without the rubber washer according to the present invention;

Fig.6A illustrates a projection view of the upper annular blocking piece with projecting spots on the internal surface according to the present invention;

Fig.7 illustrates a sectional view of an anastomat for circumcision provided with the rubber washer, but without the detachable tubular cutting knife according to the present invention;

Fig.8 illustrates a sectional view of the upper end face of an V-typed tooth formed on the section of the upper casing pipe in the inner cutting ring of an anastomat for circumcision according to the present invention;

Fig.9 illustrates a sectional view of the upper end face of an M-typed tooth formed on the section of the upper casing pipe in the inner cutting ring of an anastomat for circumcision according to the present invention;

Fig.10 illustrates a sectional view of the connecting ring in an anastomat for circumcision according to the present invention;

Fig.11 illustrates the detachable casing pipes which are spliced together of the inner cutting ring in an anastomat for circumcision according to the present invention;

Fig.12 illustrates a top view of the end face formed into patterns of the upper casing pipe of the inner cutting ring in an anastomat for circumcision according to the present invention;

Fig.13 illustrates a sectional view showing the assembly

configuration of an anastomat for circumcision according to the present invention;

Fig.14 illustrates the assembly configuration of an anastomat for circumcision according to the present invention;

Fig.15 illustrates a sectional view of the tubular inner ring in an anastomat for circumcision according to the present invention;

Fig.16 illustrates a top view of the tubular inner ring in an anastomat for circumcision according to the present invention;

Fig.17 illustrates the configuration of the tubular outer ring A in an anastomat for circumcision according to the present invention;

Fig.18 illustrates the configuration of the tubular outer ring B in an anastomat for circumcision according to the present invention;

Fig.19 is partial view of the snap-fitted configuration of the tubular outer ring A in an anastomat for circumcision according to the present invention;

Fig.20 is partial view of the snap-fitted configuration of the tubular outer ring B in an anastomat for circumcision according to the present invention;

Fig.21 illustrates the assembly configuration of an anastomat for circumcision according to the present invention;

Fig.22-1 illustrates the configuration of the tubular inner ring formed into two semicircles in an anastomat for circumcision according to the present invention;

Fig.22-2 illustrates the configuration of the tubular inner ring formed into a whole in an anastomat for circumcision according to the present invention;

Fig.23 illustrates the configuration of the tubular outer ring in an

anastomat for circumcision according to the present invention;

Fig.24 illustrates a sectional view of the tubular outer ring in an anastomat for circumcision along K-K line according to the present invention;

Fig.25 illustrates a sectional view of the tubular inner ring in an anastomat for circumcision along L-L line according to the present invention;

Fig.26A illustrates the enlarged details of a configuration of part A of the tubular outer ring in an anastomat for circumcision according to the present invention;

Fig.26B illustrates the enlarged details of another configuration of part A of the tubular outer ring in an anastomat for circumcision according to the present invention;

Fig.26C illustrates the enlarged details of still another configuration of part A of the tubular outer ring A in an anastomat for circumcision according to the present invention;

Fig.26D illustrates the enlarged details of further another configuration of part A of the tubular outer ring in an anastomat for circumcision according to the present invention;

Fig.27 illustrates the sectional configuration of the upper and lower single-layered knife edge junctions of an anastomat for circumcision along M-M line according to another example in the present invention;

Fig.28 illustrates the sectional configuration of the upper and lower double-layered knife edge junctions of an anastomat for circumcision along M-M line according to another example in the present invention;

Fig.29 illustrates the configuration of the tubular outer ring of an anastomat for circumcision according still another example in the present

invention;

Fig.30 illustrates the enlarged sectional details of part A in figure 29;

Fig.31 illustrates the configuration of the tubular outer ring formed into an integrated flexible split ring in an anastomat for circumcision according to the present invention.

In which,

1、the upper casing pipe; 2、the lower casing pipe; 3、the connecting plate; 4、the rubber washer; 5、the upper sleeve; 6、the upper annular blocking piece; 6-1、the projecting spot; 7、the lower sleeve; 8、the connecting rod; 9、the casing pipe; 10、the lower annular blocking piece; 11、the patterns; 12、the face tooth; 12a、the Λ -shaped tooth; 12b、the M-shaped tooth; 13、the projecting snap; 14、the helix groove; 15、the graduated ruler; 16、the arc groove; 17、the graduated ruler; 17-1、the digital ruler; 17-2、the alarm; 18、the detachable casing pipe; 19、the arc plate; 20、the snap fastener; 21、the acute-angled cutting edge; 21a、the zigzag cutting edge; 22、the thread; 23、the clearance; 24、the cutting casing pipe; 25、the pipe foot; 26、the rotary buckle; 27、the lacerable strip; I、the inner cutting ring; II、the elevating tubular cutting knife; III、the outer cutting ring; IV、the connecting ring; V、the anti-erection plate; 28、the tubular inner ring; 29、the tubular outer ring; 29-1、the outer ring A; 29-2、the outer ring B; 30、the empty cavity; 31、the stop collar; 32、the washer; 33、the circumcision end; 34、the projecting edge; 35、the binding strip; 36、the through hole; 37、the dismounting hole; 37A、the ratchet A; 37B、the ratchet B; 38、the bump; 39、the projecting spot; 40、the saw tooth; 41、the taper face; 42、a right angle; 43、the positioning bump; 44、the outer ring; 44A、the left semicircle part; 44B、the right semicircle part; 45、the inner ring; 46、

the recess; 47、 the elastic washer; 48、 the saw tooth or projecting spot; 49、 50、 the snap ring; 51、 the convex ring; 52、 the channel; 53、 the connecting snap; 54、 the L-shaped part; 55、 the L-shaped part; 56、 the connecting rod; 57、 the connecting hole; 58、 the dentoid protuberance; 59、 the dentoid groove; 60、 the hole; 61、 the hook-like protuberance; 62、 the slotted hole; 63、 the connecting plate; 64、 the clamping piece; 65、 the hole; 66、 the concave slotted holes; 67、 the bow tie-like block; 68、 the hole; 69、 the bar-type tooth; 70、 the bar-type perforation; 71、 the hole; 72A、 the upper knife edge; 72B、 the lower knife edge; 73、 the first ladder snap-fitted block; 74、 the second ladder snap-fitted block; 75、 the unlocking rod; 76、 the unlocking hole; 77、 the integrated flexible split ring; 78、 the double-layered knife edge; 79、 the cutting blade; 80、 the unlocking rod; 81、 the unlocking hole; 82、 the screw stem; 83、 the graduated ruler; 84、 the digital ruler; 85、 the alarm.

【Embodiments】

The following embodiments described in details with reference to the appended drawings are illustrated for the purpose of explaining the present invention only, rather than limiting the protection scope thereof.

Refer to fig.1, fig8 and fig9, the present invention relates to an anastomat for circumcision comprising an inner cutting ring I consisted of an upper casing pipe 1 for tightly compressing the subcutaneous tissue prepuce and vessels in the foreskin to death, and a connecting rod 3 for connecting said upper casing pipe 1 and lower casing pipe 2; said upper casing pipe 1 has an upper end face evenly provided with several face teeth 12 in various shapes functioning to compress against said upper casing pipe 1, each of said face teeth 12 may form into patterns 11 alternated with concave form and convex form, or form into a Λ -typed

tooth 12a or M-typed tooth 12b; said inner cutting ring I may be formed into an integrated ring or several parts spliced together; the pipe wall of said upper casing pipe 1 and lower casing pipe 2 of the inner cutting ring I may be further provided with a lacerable strip 27, through which an axial tear action may be done easily.

The anastomat for circumcision according to the present embodiment further comprises a cutting casing pipe 24 for cutting off the excess foreskin which is provided with a helix groove 14 on its pipe wall and a pipe foot 25 at its lower end; said pipe foot 25 is connected with a rotary buckle 26; said cutting casing pipe 24, pipe foot 25 and rotary buckle 26 are connected together to form an elevating tubular cutting knife II which can be lifted up and lowered down.

The anastomat for circumcision according to the present embodiment further comprises an upper sleeve 5 for fixing a blocking piece, an upper annular blocking piece 6 arranged at the upper end of said upper sleeve 5 functioning for cooperating with the upper casing pipe 1 of the inner cutting ring I so as to tightly compress the foreskin to death; a lower sleeve 7 connecting to a connecting ring; a connecting rod 8 for connecting the upper sleeve 5 with the lower sleeve 7; and an outer cutting ring III consisted of said upper sleeve 5, lower sleeve 7 and connecting rod 8.

The anastomat for circumcision according to the present embodiment further comprises a connecting ring IV consisted of an casing pipe 9 connecting with said outer cutting ring III and tightly clamping said inner cutting ring I; and a lower annular blocking piece 10 arranged at the lower end of said casing pipe 9.

The anastomat for circumcision according to the present

embodiment further comprises a detachable anti-erection plate V arranged at the inner side of the connecting plate 3 of the inner cutting ring I.

As illustrated in figures 1-12, the inner cutting ring I is sleeved into the outer cutting ring III in such a manner that the upper end face of the upper casing pipe 1 of the inner cutting ring I can be connected to the inner side of the upper annular blocking piece 6 in the outer cutting ring III in a tightly crimped mode, and the lower end face of the lower casing pipe 2 of the inner cutting ring I can be connected to the inner side of the lower annular blocking piece 10 in the connecting ring IV in a tightly crimped mode; the elevating tubular cutting knife II which can be lifted up and lowered down is arranged between the inner cutting ring I and outer cutting ring III in such a manner that the pipe foot 25 at the lower end of the elevating tubular cutting knife II can pass through an arc groove 16 arranged on the lower annular blocking piece 10 of the connecting IV and then be connected to a rotary buckle 26 arranged on the elevating tubular cutting knife II; wherein, the connection between the lower casing pipe 7 of the outer cutting ring III and the casing pipe 9 of the connecting IV is a detachable connection.

Alternatively, as illustrated in figures 2, 7, 8, 9, the above-mentioned embodiment may be provided without the elevating tubular cutting knife II.

The upper casing pipe 1 of the inner cutting ring I according to the present invention has an end face evenly distributed with a plurality of face teeth 12 formed into patterns 11 alternated with concave form and convex form, or formed into Λ -typed tooth 12a or M-typed tooth 12b; Λ -typed tooth 12a or M-typed tooth 12b is fitted with the inner side

of the upper annular blocking piece 6 in the outer cutting ring III or a rubber washer 4 arranged in the upper annular blocking piece 6, by the way of tightly compressing against there, which functions to compress the cells, tissues and vessels at the root of the excess foreskin to death.

According to the present invention, the connecting plate 3 of the inner cutting ring I is provided with a projecting snap 13 at its external surface which can be fitted with a helix groove 14 arranged on the wall of the cutting casing pipe 24 of the elevating tubular cutting knife II, so as to enable said elevating tubular cutting knife II to be lifted up or lowered down.

When used, an anti-erection plate V provided with projecting spots is required to be inserted into the inner side of the connecting plate 3 of the inner cutting ring I during the night, so as to stimulate the external surface of the penis thus to prevent it from erection.

In order to accurately control the cutting deepness and compression deepness to the foreskin, the present invention provides a graduated ruler 17 indicating the compression deepness arranged at the outer side of the connecting rod 8 of the outer cutting ring III or arranged on the external wall of the lower casing pipe 7 of the outer cutting ring III is adoptable; moreover, a graduated ruler 15 indicating the cutting deepness to the foreskin arranged on the external wall of the casing pipe 9 of the connecting ring IV along its circumference is also feasible.

Refer to figure 3 and figure 4, according to the present invention, one end of the cutting casing pipe 24 of the elevating tubular cutting knife II may be formed into an acute-angled cutting edge 21 or zigzag cutting edge 21a. One end of said acute-angled cutting edge 21 or zigzag cutting edge 21a is allowed for compressing against the inner side of the upper

annular blocking piece 6 of the crimping part so as to cut off the foreskin, or, on the contrary, not compressing against said inner side so as to return back to its original position. Alternatively, the acute-angled cutting edge 21 or zigzag cutting edge 21a is allowed for compressing against the rubber washer 4 in the upper annular blocking piece 6 so as to cut off the foreskin, or, on the contrary, not compressing against said rubber washer 4 so as to return back to its original position.

According to the present invention, the elevating tubular cutting knife II which can be lifted up and lowered down has a cutting casing pipe 24 whose inner diameter is identical with the outer diameter of the upper casing pipe 1 or lower casing pipe 2 of the inner cutting ring I.

According to the present invention, the crimping part and the connecting ring IV can be connected with each other through a thread 22.

According to the present invention, clearance 23 should be remained between each of the upper casing pipe 1, the lower casing pipe 2, the connecting plate 3 of the inner cutting ring I and each of the upper sleeve 5, lower sleeve 7 and connecting rod 8 of the outer cutting ring III, so as to accommodate the foreskin.

As illustrated in figure 7 and figure 11, the present embodiment is distinguished from the first embodiment in that the upper casing pipe 1 and lower casing pipe 2 of the inner cutting ring I may be formed into a detachable casing pipe 18 consisted of four segments of arc plates 19 which are spliced together through snap fasteners 20. Furthermore, the pipe wall of each of said upper casing pipe 1 and lower casing pipe 2 of the inner cutting ring I is provided with a lacerable strip 27, through which an axial tear action may be done easily.

The present embodiment is distinguished from the first embodiment

further in that a snap arranged on the external wall of the crimping part is clamped into a slot arranged on the connecting ring, so that the crimping part can be connected with the connecting ring in a snap-fit mode.

The present embodiment is distinguished from the first embodiment still further in that the crimping part is connected with the connecting ring IV in such a manner that a ratchet arranged on the outer cutting ring III and a thread arranged on the connecting IV is fitted with each other; wherein said ratchet is liable to be torn, so that a reuse of those cutting devices which may results in disease transmission would be prevented. Therefore, the whole assembly of those cutting devices becomes a disposable product.

Another embodiment according to the present invention would be described in details below in conjunction with the appended drawings, as shown from figure 13- 20.

An anastomat for circumcision comprises a tubular inner ring 28, which is arranged onto the outside of the penis of a patient in such a way that the internal side of the excess foreskin is turned over and covered onto the outside of the tubular inner ring 28, then a tubular outer ring 29 is arranged onto the outside of the tubular inner ring 28; an empty cavity 30 is arranged between said inner ring 28 and outer ring 29 for accommodating the excess foreskin to be cut. Wherein, said tubular outer ring 29 is consisted of a tubular outer ring A 29-1 and a tubular outer ring B 29-2 which are connected together in a snap-fit mode. Stop collars 31 each having a washer 32 arranged at its inner side are arranged at the end parts of said tubular outer ring A 29-1 and tubular outer ring B 29-2 respectively. Said tubular inner ring 28 has one end formed into a circumcision end 33 which is provided with a projecting edge 34 at its

outer side. Said projecting edge 34 is provided with a binding strip 35 at its lower end for fixing the foreskin. Once said tubular outer ring A 29-1 is snap-fitted with said tubular inner ring B 29-2 through the ratchet A 37A and ratchet B 37B, said circumcision end 33 of the tubular inner ring 28 would be fitted with said washer 32 arranged at the inner side of the stop collar 31 arranged at the end part of the tubular outer ring A 29-1 so as to extrude the foreskin. Wherein, the other end of said tubular inner ring 28 is fitted with the inner side of said stop collar 31 arranged at the end part of the tubular outer ring B 29-2 so as to axially compress against the tubular inner ring 28.

At least two through holes 36 for injecting medicine solution or cleaner fluid are arranged on the side wall of said tubular outer ring 29 or the end face of the stop collar 31; furthermore, several dismounting holes 37 for dismounting the connection between the tubular outer ring A 29-1 and tubular outer ring B 29-2 are arranged at the side wall of said tubular outer ring 29.

The external wall of said tubular outer ring 29 is provided with bumps 38 or patterns for skid resistance.

The end part of said circumcision end 33 of the tubular inner ring 28 is provided with several projecting spots 39 or saw teeth 40, through which the foreskin can be secured on the circumcision end and then be extruded.

The other end of said tubular inner ring 28 may be connected with the stop collar 31 arranged on the tubular outer ring B 29-2, so as to form into a whole to be connected with said tubular outer ring A 29-1 to extrude the foreskin.

The surface of the projecting edge of said circumcision end 33 may

be designed into a taper face 41 whose lower end forms a right angle 42 with the external wall of said tubular inner ring 28; said right angle 42 provides a place where the binding strip 35 can fasten the foreskin on the external wall of the tubular inner ring 28; said taper face 41 functions to be fitted with positioning bumps 43 on a taper face or an arc face between the internal surface of the outer ring A 29-1 and the internal surface of the stop collar 31. Wherein said positioning bump 43 is arranged for the purpose of positioning the circumcision end 33 which is arranged on the tubular inner ring 28.

Said projecting edge 34 may be broken down into several segments which are evenly distributed on the circumference of the external wall of the circumcision end 33 of the tubular inner ring 28.

Said tubular inner ring 28 may be a splicing ring consisted of at least two semicircles which are spliced together.

Said outer ring may be consisted of two semicircles whose ends are connected with each other correspondingly by a clamping piece or a screw.

The anastomat for circumcision according to the present invention may be operated according to the following steps: firstly, the tubular outer ring B 29-2 and the tubular inner ring 28 are arranged onto the outside of the penis in such a way that the circumcision end 33 of the tubular inner ring 28 is faced to the glans penis, then the excess foreskin is turned over and covered onto the outside of the tubular inner ring 28. Since the projecting edge 34 arranged on the external wall of the circumcision end 33 has a lower end forming a right-angled groove 42 with the external wall of the tubular inner ring 28, the foreskin covered onto the external wall of the tubular inner ring 28 is fastened by the binding strip 35, so as

to hold the excess foreskin between the tubular inner ring 28 and the tubular outer ring 29; finally, the tubular outer ring A 29-1 and tubular outer ring B 29-2 are connected with each other in a snap-fit mode. Wherein, the end parts, where the tubular outer ring A 29-1 and tubular outer ring B 29-2 are connected with each other, are provided with stop collars 31 respectively; wherein, the stop collar close to the inner side of the outer ring A 29-1 is provided with a washer 32 has a thickness, when added by the length of tubular inner ring, almost equal to the distance from the inner side of the stop collar 31 close to the tubular outer ring A 29-1 to the inner side of the stop collar 31 close to the tubular outer ring B 29-2. Therefore, when the tubular outer ring A 29-1 and the tubular outer ring B 29-2 are snap-fitted with each other, the washer 32 on the inner side of the tubular outer ring A 29-1 will be fitted with the circumcision end 33 of the tubular inner ring 28, so as to extrude the circumcision portion of the foreskin, which allows the subcutaneous tissue prepuce of the foreskin under the extruded portion necrotic due to ischemia, while the anastomat for circumcision will be separated from the penis just 5-7 days after the surgery. It can be seen from the aforesaid process that said anastomat for circumcision is convenient to operate; furthermore, it may be formed into plastic piece or stainless steel piece having small volume, light weight, simple configuration and low cost. Therefore, the present invention may be manufactured into disposable products. Additionally, since at least two through holes 36 are arranged on the side wall or the stop collar of the tubular outer ring, through which medicine solution containing analgesic, anti-inflammatory or cleaner fluid would be injected into the empty cavity, so as to relieve the patient's pain and accelerate healing.

In another embodiment according to the present invention, the anastomat may be designed into a splicing tubular inner ring 28, a splicing tubular outer ring 29 or a flexible split tubular outer ring 29, in order to adapt to various requirements from various patients. Wherein, the splicing inner ring may be formed into several pieces of inner ring which are fastened on the penis through an elastic washer, while the splicing outer ring is generally consisted of two semicircles connected with each other through two junctions, one of which is implemented by a hinge, and the other one is implemented by snap fit or fastening screw. Similarly, the ends of the opening of the flexible split tubular outer ring 29 also may be connected by snap fit or fastening screw.

Another embodiment according to the present invention would be described in details below in conjunction with the appended drawings, as shown from figure 21 to figure 31.

As illustrated in figures 21-23, an anastomat for circumcision comprises a outer ring 44 for cutting and clamping, and a inner ring 45 for covering the foreskin; said inner ring 45 may be formed into a integrated ring or two semicircles or more than two arc segments; said inner ring 45 is provided with at least one circle of recess 46 on its external surface; said recess 46 is provided with an elastic washer 47 on its surface; said outer ring 44 is provided with at least one circle of knife edge 78 whose fringe is evenly distributed with several saw teeth or projecting spots 48 ; said knife edge 78 is fitted with said recess 46 so as to extrude and/or cut the foreskin; channels 52 for injecting medicine solution, which are communicated with the empty cavity between said outer ring 44 and inner ring 45, are arranged on the side wall of said outer ring 44.

The inner ring 45 and outer ring 44 included in the anastomat for circumcision may be made of high-grade 372-type organic material without toxic and side-effect.

The outer ring 44 may be consisted of a left semicircle part 44-A and a right semicircle part 44-B; alternatively, the outer ring 44 may also be an integrated flexible split ring. Each of the semicircle part and the flexible split ring has two junctions, one of which can be implemented by a connecting snap 53, while the other one can be implemented by a fastener 75 and an unlocking hole 76; of course, the outer ring 44 may also be formed as an integrated configuration having an opening which can be connected with the fastener 75. The fastener 75, which would be explained below through examples, may be implemented in the form of fastening screw 82 or other connection.

Figure 24 illustrates the K-K directional cross-sectional view of the outer ring of an anastomat for circumcision according to one embodiment of the present invention;

Figure 25 illustrates the L-L directional cross-sectional view of the inner ring of an anastomat for circumcision according to one embodiment of the present invention. As illustrated, the present invention focuses on following technical features: said two semicircular split rings or said integrated flexible split outer ring 44 are/is provided with two circles of snap rings 49, 50 thereon, while said inner ring 45 is provided with recesses 46 thereon which are fitted with said snap rings 49, 50; said recesses 46 are provided with convex 51 there between; said inner ring 45 is consisted of a left ferrule and a right ferrule configured to be spaced apart from each other with a junction, and there is a round corner arranged at said junction. The inner ring 45 and outer ring 44 are fitted

with each other, so as to clamp the foreskin to be cut off. In this way, the foreskin will be necrosis due to a blood circulation failure. Due to the unavoidable occurrence of infection during the operation, the assistant treatment of medicine solution is required to eliminate inflammation and facilitate skin renewal, which allows for further accelerating healing. The medicine solution accommodated within the empty cavity mentioned-above directly penetrates into the infection portion so as to eliminate inflammation and facilitate skin renewal. Such medicine solution specifically prepared for a circumcision whose prescription has no reference to the present invention will not be given unnecessary details here.

Since known operation for fastening the connecting part A of the outer ring 44 is extremely inconvenient which causes patients to be went under the knife extremely suffering, this reinforce their sense of fear and increase the duration of surgery. Several types of connection configuration would be provided below.

Figure 26A illustrates enlarged detail of a configuration of part A of the outer ring 44 in an anastomat for circumcision according to one embodiment of the present invention. Said outer ring 44 is consisted of two semicircle parts 44-A, 44-B, and a connecting snap 53 for connecting one end of said semicircle part 44-A and one end of said semicircle part 44-B, while the other ends of the semicircle parts are provided with L-shaped parts 54, 55 respectively, which are fitted with each other. A connecting rod 56 and a connecting hole 57 are arranged on the top end and bottom platform of each of said L-shaped parts 54, 55, respectively. Wherein, the connecting rod 56 arranged on one end of a semicircle part is fitted with the connecting hole 57 arranged on the other end of the

remaining semicircle part. Each of said L-shaped parts has a vertical end whose internal side is provided with a dentoid protuberance 58 or dentoid groove 59, wherein the dentoid protuberance 58 or dentoid grooves 59 on one L-shaped part is fitted with the dentoid groove 59 or dentoid protuberance 58 on the internal side of the vertical end of the remaining L-shaped part. In such a manner, nothing but to simply insert the connecting rod 56 into the connecting hole 57 and hold it therein, meanwhile make the dentoid protuberance 58 and the dentoid grooves 59 fitting with each other, so as to close the whole outer ring 44 in a locking way, when it's desired to lock the semicircle parts 44-A, 44-B together. The operation of inserting a screwdriver or other tool into a hole 44 arranged on the L-shaped part so as to destroy the whole configuration therein by acting a slight force thus to open the anastomat for circumcision in the present embodiment is also possible, when it's desired to break the closed configuration (since the present embodiment is a disposal anastomat for circumcision).

Figure 26B illustrates the enlarged detail showing another configuration of part A of the outer ring 44 in an anastomat for circumcision according to one embodiment of the present invention. Said outer ring 44 is consisted of two semicircle parts 44A, 44B and a connecting snap 53 for connecting one end of said semicircle part 44-A and one end of said semicircle part 44-B, while the other ends of the semicircle parts are provided with a hook-like protuberance 61 or slotted hole 62 respectively, the hook-like protuberance 61 or slotted hole 62 arranged at said semicircle part 44-A is fitted with the slotted hole 62 or hook-like protuberance 61 arranged at said semicircle part 44-B. Said hook-like protuberance 61 includes a connecting plate 63 and an

inverted-V type clamping piece 64; said connecting plate 63 has one end connecting to the end part of the semicircle part 44-A and the other end connecting to the middle part of the clamping piece 64; said inverted-V type clamping piece 64 is configured to possess both considerable flexibility and certain hardness, such as stalloy, while said slotted hole 62 has an opening with relatively larger caliber and the internal empty cavity 50 has a relatively larger volume. Said semicircle part 44-A is provided with a hole 65 at the end thereof, which plays the same role as that of the hole 60 shown in figure 26A. When it's desired to lock the outer ring 44, the hook-like protuberance 61 is inserted into the slotted hole 62, at this time, the clamping piece 64 is fixed and positioned due to its elastic characteristic and then resist against the internal wall of the slotted hole 62 due to its hardness characteristic, so as to be locked there.

Figure 26C illustrates the enlarged detail showing still another configuration of part A of the outer ring 44 in an anastomat for circumcision according to one embodiment of the present invention. Said outer ring 44 is consisted of two semicircle parts 44-A, 44-B and a connecting snap 53 for connecting one end of said semicircle part 44-A and one end of said semicircle part 44-B, while the other ends of the semicircle parts are provided with concave slotted holes 66 respectively. Each of said concave slotted holes 66 receives a bow tie-like block 67. Said semicircle part 44-A is provide with a hole 68 on its end part which plays the same role as those of the holes 60, 62 mentioned above. When it's desired to lock the outer ring 44, both ends of the bow tie-like block 67 are inserted into the concave slotted holes 66 respectively.

Figure 26D illustrates the enlarged detail showing still another configuration of part A of the outer ring 44 in an anastomat for

circumcision according to one embodiment of the present invention. Said outer ring 44 is consisted of two semicircle parts 44-A, 44-B and a connecting snap 53 for connecting one end of said semicircle part 44-A and one end of said semicircle part 44-B, while the other ends of the semicircle parts are provided with bar-type denticles 69 or bar-type sprocket holes 70 respectively. It can be seen from the enlarged details of the bar-type denticle 69 that there are a plurality of small horizontal-strip style protuberances laterally arranged thereon which are fitted with several small recesses laterally arranged in the bar-type sprocket hole 70, so as to be clamped and further locked therein, when the bar-type denticle 69 is inserted into the bar-type sprocket hole 70. It should be noticed that the function of clamping and locking is unidirectional, which requires tilt direction of both said small horizontal-strip style protuberances of the bar-type denticle 69 and that of the small recesses in the bar-type sprocket hole 70 form an obtuse angle with insertion direction. That is to say, once locked and positioned, the bar-type denticle 69 won't be simply pulled out from the bar-type sprocket hole 70 under normal circumstances, which ensures a firm locking and provides a good operability. The present embodiment also provides holes for destroying the connection of the outer ring as mentioned above. When it's desired to open the closed configuration, a screwdriver or other tool may be inserted into the hole 71 so as to destroy the whole configuration therein by acting a slight force thus to open the anastomat for circumcision in the present embodiment.

Figure 31 illustrates an outer ring formed into an integrated flexible split ring 77 according to the present invention. The opening of said split ring 77 provides two ends equipped with knife edge junctions respectively which are corresponding to each other; said knife edge may

be formed into a double-layered knife edge sandwiched with several cutting pieces 79 vertically therebetween. Each of said knife edge junctions is provided with a first ladder snap-fitted block 73, a second ladder snap-fitted block 74, an unlocking stem 80, an unlocking hole 81, a graduated ruler 83, a digital ruler 84 and an alarm 85.

Figures 27 to 30 illustrate the outer ring of an anastomat for circumcision according to another embodiment of the present invention. Said outer ring 44 has an opening of which the ends are provided with an upper knife edge 72A junction and a lower knife edge 72B junction correspondingly, respectively. One end of said opening, where the upper knife edge 72A junction is arranged, is provided with a first ladder snap-fitted block 73, the other end of said opening, where the lower knife edge 72B junction is arranged, is provided with a second ladder snap-fitted block 74, and the first ladder snap-fitted block 73 and the second ladder snap-fitted block 74 are fitted with each other. In the section, the first ladder snap-fitted block 73 is positioned below the upper knife edge 72A junction, while the second ladder snap-fitted block 74 is positioned above the lower knife edge 72B junction. When used, the lower knife edge 72B junction is inserted into a position under the upper knife edge 72A junction, while the second ladder snap-fitted block 74 is clamped above the first ladder snap-fitted block 73, so that the first and second ladder snap-fitted blocks 73, 74 can be tightly engaged with each other due to the position limiting function of the upper and lower knife edge 72A, 72B junctions. In such a way, the whole outer ring can be locked strictly. The first ladder snap-fitted block 73 or the second ladder snap-fitted block 74 is provided with a hole 65, so that a screwdriver or other tool may be inserted therein and destroy the whole configuration by

acting a slight force thus to open the anastomat for circumcision in present invention (since the anastomat for circumcision in present invention is a disposal one).

Under given several designs of the connection configuration, the operation of the anastomat for circumcision according to the present invention would be provided as follows:

Step 1, cleaning and disinfecting the penis, and push the foreskin which covers the glans backwards, so that it can be exposed completely;

Step 2, adjusting and positioning the inner ring, then pulling out the foreskin which has been pushed backwards, until it completely covers the inner ring and the glans;

Step 3, opening the outer ring, then arranging it onto the outside of the inner ring and fixing it thereon, so that the foreskin will be necrosis due to a blood circulation failure;

Step 4, injecting medicine solution into the empty cavity through the channel, by which the medicine solution would be directly supplied to the affected part, so as to diminish inflammation and relieve pains;

Step 5, removing the necrotic foreskin after 2-5 (or a litter more) days, meanwhile loosening the outer ring or later.

A foam-rubber mattress arranged between the outer ring and inner ring may reduce the stress produced during the foreskin cutting process.

Known anastomat for circumcision usually comprises an inner ring formed into an integrated circle whose diameter remains unchanged may aggravate the uncomfortable feeling. What is illustrated is an exploded view showing the anastomat for circumcision according to another embodiment of the present invention. Wherein, known integrated inner ring is improved into a left semicircle part 45-1 and a right semicircle part

45-2, so as to adapt to the circumstance that the penis may be erected and enlarged. In this way, the extrusion force may be reduced.

Additionally, as shown in figure 27 and figure 28, in another embodiment, the outer ring 44 comprises a semicircle part 44-A provided with an upper knife edge 72A junction thereon, and a semicircle part 44-B provided with a lower knife edge 72B junction which is corresponding to the upper knife edge 72A junction. Such configuration allows the outer ring 44 to be well connected. Each of said knife edge junction is provided with a round corner 72 at its fringe which allows the foreskin prevented from being clamped during the operation, thus to ensure the operation successfully and avoid pains. If the foreskin was clamped, a granulation would be formed, which may extend the time for healing and increase the suffering. Similarly, a same or similar round corner may be arranged on the junction of the left and right semicircle parts in the inner ring, so that the foreskin can be prevented from being clamped.

When used, the present invention will not cause pains or obvious scar. Instead, it provides an accurate position where the rings will fall from the affected part, as well as a faster healing. The treatment based on the present invention is suitable for the children, youth and aged. Moreover, the type of the anastomat may be selected depending on the actual size of the glans.

Furthermore, when used, the anastomat for circumcision in the present invention will not influence normal working and studying, and it can be easily operated without special training, which allows the treatment based on the present invention even can be implemented in a mini clinic. The present invention is further advantageously in its low

price. The total cost for the whole period of treatment including the surgery, antiphlogosis and the same is only 160-200 yuan, which is publicly acceptable.

Industrial Applicability

The present invention provides an anastomat for circumcision. Since its configuration of only arranging an upper casing pipe and a lower casing pipe in the upper part and lower part of the inner cutting ring I and outer cutting ring III respectively which are connected through a connecting plate or connecting rod, the anastomat for circumcision has a reduced weight. Furthermore, the upper casing pipe of the inner cutting ring I has an upper end face formed into patterns, which significantly relieves the suffering, when compared with known annular knife edge. Moreover, the connecting plate of the inner cutting ring I is additionally provided with a anti-erection plate V for preventing the penis from erection, which effectively avoids the suffering due to wound produced by penile erection. Besides, the graduated rulergraduated ruler arranged on the external side of the connecting rod of the outer cutting ring III may facilitate adjusting the crimping force produced between the outer cutting ring III and connecting ring IV depending on the thickness of the foreskin, as well as facilitate adjusting the cut deepness of the foreskin when a elevating cutting knife II is arranged between the outer cutting ring III and the connecting ring IV. In addition, since either the upper casing pipe or the lower casing pipe of the inner cutting ring I may be designed into a splicing ring, the inner diameter of the inner cutting ring I may be adjusted according to the requirement of patients. Due to its moveable configuration, the elevating cutting knife may be lifted up and withdrawn

back as desired, which provides a flexible operation. Finally, the present anastomat for circumcision is a disposable product which prevents the disease spreading. Therefore, the present invention provides advantages such as small and exquisite, light weight, convenient to use, as well as low cost, and possesses the industrial applicability.

CLAIMS

1. An anastomat for circumcision, characterized in that, it comprises:
an inner cutting ring (I) comprising an upper casing pipe (1), a lower casing pipe (2) and a connecting plate (3) for connecting said upper casing pipe (1) and said lower casing pipe (2);

an outer cutting ring (III) comprising an upper sleeve (5), an upper circular blocking piece (6) arranged at the upper end of said upper sleeve (5), a lower sleeve (7), and a connecting rod (8) for connecting said upper sleeve (5) and said lower sleeve (7);

a connecting ring (IV) comprising a casing pipe (9) and a lower annular blocking piece (10) arranged at the lower end of said casing pipe (9);

said inner cutting ring (I) is sleeved into said outer cutting ring (III), said upper casing pipe (1) of the inner cutting ring (I) has an upper end connecting to the inner side of said upper circular blocking piece (6) of the outer cutting ring (III) in a crimped mode, and said lower casing pipe (2) of the inner cutting ring (I) has a lower end connecting to the inner side of said lower annular blocking piece (10) of the connecting ring (IV) in a crimped mode; said lower sleeve (7) of the outer cutting ring (III) is detachably connected with said casing pipe (9) of the connecting ring (IV);

clearance (23) is provided between said inner cutting ring (I) and said outer cutting ring (III) for accommodating the foreskin.

2. An anastomat for circumcision of claim 1, characterized in that, it further comprises:

an elevating tubular cutting knife (II) for cutting the foreskin comprising a cutting casing pipe (24), a helix groove (14) arranged on the

pipe wall of said cutting casing pipe (24), a pipe foot (25) arranged at the lower end of said cutting casing pipe (24), and a rotary buckle (26) connected with said pipe foot (25);

said elevating tubular cutting knife (II) is sleeved between said inner cutting ring (I) and said outer cutting ring (III), and said pipe foot (25) of said elevating tubular cutting knife (II) is inserted through an arc groove (16) on said lower circular blocking piece (10) in the connecting ring (IV) so as to be connected to said rotary buckle (26) on the tubular cutting knife (II).

3. An anastomat for circumcision of claim 1 or 2, characterized in that, a detachable anti-erection plate (V) arranged at the inner side of said connecting plate (3) of the inner cutting ring (I), wherein several projecting spots are evenly distributed on the surface of said anti-erection plate (V).

4. An anastomat for circumcision of claim 1 or 2, characterized in that, said upper circular blocking piece (6) is provided with several projecting spots (6-1) on its internal surface.

5. An anastomat for circumcision of claim 3, characterized in that, said connecting plate (3) of the inner cutting ring (I) is provided with a projecting snap (13) on its external surface which is fitted with said helix groove (14) on the pipe wall of the cutting casing pipe (24) of said elevating tubular cutting knife (II).

6. An anastomat for circumcision of claim 3, characterized in that, said cutting casing pipe (24) of the elevating cutting knife (II) has an end provided with an acute-angled cutting edge (21) or a zigzag cutting edge (21a) which is fitted with the inner side of said upper annular blocking piece (6) of the outer cutting ring (III), or with a rubber washer (4)

arranged in said upper annular blocking piece (6) of the outer cutting ring (III), in a pressing mode.

7. An anastomat for circumcision of claim 6, characterized in that, said cutting casing pipe (24) of the elevating tubular cutting knife (II) has an inner diameter equal to the outer diameters of said upper casing pipe (1) and said lower casing pipe (2) in the inner cutting ring (I).

8. An anastomat for circumcision of claim 3, characterized in that, said connecting rod (8) is provided with a graduated ruler (17), a digital ruler (17-1) and an alarm (17-2).

9. An anastomat for circumcision of claim 8, characterized in that, said lower sleeve (7) of the outer cutting ring (III) and said casing pipe (9) of the connecting ring (IV) are also provided with graduated rulers (15) on the external surfaces, respectively.

10. An anastomat for circumcision of claim 8, characterized in that, said digital ruler includes a raster digital ruler (17-1), an electromagnetic induced digital ruler, and an infrared digital ruler.

11. An anastomat for circumcision of claim 8, characterized in that, said alarm comprises a circuit board, on which a alarming or reminding memory chip, a speech chip are provided; said speech chip is provided for warning the situation that said lower sleeve (7) of the outer cutting ring (III) is connected with said casing pipe (9) of the connecting ring (IV) overly tightly, and/or reminding the information of wound healing.

12. An anastomat for circumcision of claim 3, characterized in that, face teeth (12) are evenly distributed on the end surface of said upper casing pipe (1) of the inner cutting ring (I), said face teeth (12) are formed into patterns (11) and fitted with the inner side of said upper circular blocking piece (6) of the outer cutting ring (III) or a rubber

washer (4) arranged in said upper circular blocking piece (6), in a pressing mode.

13. An anastomat for circumcision of claim 3, characterized in that, said upper casing pipe (1) of the inner cutting ring (I) has an upper end whose section is formed into Λ -type tooth (12a) or M-type tooth (12b) which is fitted with the inner side of said upper circular blocking piece (6) of the outer cutting ring (III) or a rubber washer (4) arranged in said upper circular blocking piece (6), in a pressing mode.

14. An anastomat for circumcision of claim 3, characterized in that, each of said upper casing pipe (1) and lower casing pipe (2) of the inner cutting ring (I) is a splicing casing pipe (18) formed into a circular spliced casing pipe (18) consisted of several segments of arc plates (19) spliced together by a snap fastener (20) in a snap-fit way; a lacerable strip (27) which is liable to be torn longitudinally is arranged on the pipe wall of each of said upper casing pipe (1) and lower casing pipe (2) of the inner cutting ring (I), respectively.

15. An anastomat for circumcision of claim 3, characterized in that, said outer cutting ring (III) and said connecting ring (IV) are connected with each other by a thread (22), or by clamping a snap arranged on the external wall of said outer cutting ring (III) into a slot arranged on said connecting ring (IV), or by engaging a ratchet with a screw thread arranged on said outer cutting ring (III) and said connecting ring (IV), respectively, wherein the ratchet arranged on said connecting ring (IV) is liable to be torn.

16. An anastomat for circumcision of claim 3, characterized in that, said upper circular blocking piece (6) is provided with several projecting spots (6-1) on its internal surface, a washer is arranged below said

projecting spots (6-1), while a rubber pad is arranged below said washer.

17. An anastomat for circumcision of claim 3, characterized in that, there are frosted patterns arranged on the surfaces of said inner cutting ring (I), outer cutting ring (III) and connecting ring (IV).

18. An anastomat for circumcision, comprising: a tubular inner ring (28), a tubular outer ring (29) sleeved onto the outer side of said tubular inner ring, and an empty cavity (30) for accommodating the foreskin arranged between said tubular inner ring and said tubular outer ring; said anastomat for circumcision is characterized in that, said outer ring is consisted of an outer ring A (29-1) and an outer ring B (29-2) connected with each other, and the end of each of the outer ring A and the outer ring B is provided with a stop collar (31) respectively; one end of said tubular inner ring is formed as a circumcision end (33) whose external side is provided with a projecting edge (34); the lower end of said projecting edge (34) is equipped with a binding strip (35) for fastening the foreskin; while the other end of said tubular inner ring is fitted with the inner side of said stop collar arranged at the end of the outer ring B (29-2) so as to axially compress against the tubular inner ring.

19. An anastomat for circumcision of claim 18, characterized in that, said stop collar (31) is provided with a washer (32) at its inner side; said circumcision end (33) is fitted with said washer arranged at the inner side of the stop collar at the end of the outer ring A (29-1), so as to extrude the foreskin.

20. An anastomat for circumcision of claim 19, characterized in that, there are through holes (36) for injecting medicine or cleaner fluid arranged on the side wall of said tubular outer ring (29) or the end surface of said stop collar; several dismounting holes (37) for dismounting the

connection between said outer ring A (29-1) and said outer ring B (29-2) are arranged on the side wall of the tubular outer ring (29).

21. An anastomat for circumcision of claim 20, characterized in that, the external wall of said tubular outer ring is provided with bumps (38) or grooves or patterns used for slip-resistance.

22. An anastomat for circumcision of claim 19, characterized in that, said circumcision end (33) is provided with several projecting spots (39) at its end.

23. An anastomat for circumcision of claim 19, characterized in that, said circumcision end (33) is provided with several saw teeth (40) at its end.

24. An anastomat for circumcision of claim 22 or 23, characterized in that, the other end of said tubular inner ring (28) is connected with said stop collar arranged on the outer ring B (29-2) to form a whole.

25. An anastomat for circumcision of claim 22 or 23, characterized in that, the projecting edge on the external side of said circumcision end (33) has a surface formed into a taper face (41) whose lower end forms a right angle (42) with the external wall of said tubular inner ring (28), through which the foreskin can be fastened on the external wall of the tubular inner ring (28) by a binding strip; wherein said taper face is fitted with positioning bumps (43) on a taper face or arc face between the internal surface of the outer ring A (29-1) and the internal surface of the stop collar.

26. An anastomat for circumcision of claim 25, characterized in that, said projecting edge (34) is formed into several bumps segments.

27. An anastomat for circumcision of claim 26, characterized in that, said tubular inner ring (28) is a splicing ring consisted of at least two

semicircles which are spliced together.

28. An anastomat for circumcision of claim 21, characterized in that, said tubular outer ring (29) is consisted of two semicircles whose ends are connected with each other through a snap fastener or a screw thread.