

INTERCHANGEABLE GRIPS FOR POWER HAND TOOLS**Background of the Invention**

The invention relates to ergonomic tool grips and, in particular, to grips for power hand tools.

5 Many power hand tools, such as power ratchets, impact wrenches, drills, air hammers and the like, have handles which can become uncomfortable to the user, particularly after extended use. User discomfort could be caused, for example, by heat, vibration or the like. It is known to
10 provide handle grips for tools which are designed to improve user comfort by affording cushioning, vibration damping, thermal insulation or other properties. However, such grips are typically permanently installed on the tool during manufacture. However, different users have different-size
15 hands and, therefore, a permanently installed grip of a specific size, shape and material, will typically not be comfortable for all users.

It is known to provide removable covers for tool housings, including tool handles, but heretofore, such
20 covers have been of relatively complex, plural-part construction.

Summary of the Invention

It is a general object of the invention to provide an improved grip for a power tool handle which avoids the
25 disadvantages of prior grips while affording additional structural and operating advantages.

An important feature of the invention is the provision of a grip of the type set forth, which is of one-piece

construction and can be removably mounted on a tool handle.

In connection with the foregoing feature, another feature of the invention is the provision of a grip of the type set forth which is generally tubular in shape and can
5 be slid over a generally cylindrical handle.

Still another feature of the invention is the provision of a grip of the type set forth which can be securely retained in place on the tool handle.

Yet another feature of the invention is the provision
10 of a grip of the type set forth which provides inlet and exhaust air passages for pneumatic tools.

Certain ones of these and other features of the invention may be attained by providing a replaceable grip for a generally cylindrical handle portion of a power hand
15 tool housing which includes attachment structure, the grip comprising: a tubular body formed of a flexible and resilient material and shaped and dimensioned to be slidably received over and cover the handle portion of the tool housing, and a retention portion on the body engageable with
20 the attachment structure of the tool housing for retaining the grip in place on the handle portion.

Other features of the invention may be provided by providing the grip with an attachment portion which is adapted to be clamped between parts of a two-part tool
25 housing.

Still other features of the invention may be attained by providing a grip which defines an exhaust air passage running alongside the handle covered by the grip.

The invention consists of certain novel features and a combination of parts hereinafter fully described, illustrated in the accompanying drawings, and particularly pointed out in the appended claims, it being understood that
5 various changes in the details may be made without departing from the spirit, or sacrificing any of the advantages of the present invention.

Brief Description of the Drawings

For the purpose of facilitating an understanding of the
10 invention, there is illustrated in the accompanying drawings a preferred embodiment thereof, from an inspection of which, when considered in connection with the following description, the invention, its construction and operation, and many of its advantages should be readily understood and
15 appreciated.

FIG. 1 is an exploded perspective view of a power tool housing and grip in accordance with a first embodiment of the invention;

FIG. 2 is a fragmentary, side elevational view of the
20 tool of FIG. 1 with the grip installed thereon, with portions broken away to show internal construction;

FIG. 3 is a fragmentary sectional view taken generally along the line 3-3 of FIG. 2;

FIG. 4 is a view similar to FIG. 2 with the grip
25 removed and with the portion of the handle broken away;

FIG. 5 is a fragmentary rear elevational view of the tool of FIG. 2 with portions of the grip broken away;

FIG. 6 is a front perspective view of a handle grip in

accordance with a second embodiment of the invention, along with a retaining plate therefor;

FIG. 7 is an enlarged view in vertical section through the grip of FIG. 6;

5 FIG. 8 is a view in vertical section of a power tool housing of the type with which the grip of FIGS. 6 and 7 is to be used; and

FIG. 9 is a fragmentary, sectional view of the grip of FIG. 6 installed on the handle of the tool of FIG. 8.

10 Description of the Preferred Embodiment

Referring to FIGS. 1-5, there is illustrated a tool housing 10 for a power hand tool. While, for purposes of illustration, the housing 10 is for an air impact wrench, it will be appreciated that the principles of the present invention are applicable to other types of hand tools, using other types of power sources. The tool housing 10 is generally of "pistol grip" shape, and includes an elongated barrel 11 terminating in a rear end face 12 having an enlarged, circular opening 13 therethrough communicating with an internal cavity 14, which houses the motor mechanism (not shown). Also formed through the end face 12 is a smaller circular hole 15, as well as a plurality of screw holes 16 spaced about the periphery of the end face 12. Formed in the end face 12 adjacent to the lower end thereof are a pair of cylindrical recesses 17.

15 20 25

The housing 10 also includes an end cap 20 having a front face 21 with a hole 22 and four screw holes 23 therethrough, as well as a pair of cylindrical recesses 24

formed therein. In use, the end cap 20 is fitted over the rear end of the barrel 11, preferably with a gasket (not shown) interposed therebetween, for closing the rear end of the cavity 14, being secured in place by screws 25, respectively received through the aligned screw holes 23 and 16, and screwed into internally threaded lugs (not shown) inside the barrel 11, with the screw heads 26 being received in recesses in the end cap 20. Hole 22 aligns with the hole 15 for receiving therethrough a suitable mechanism, such as a direction-control mechanism (not shown), in a known manner.

The housing 10 also includes a handle 30 which extends downwardly at an angle from the rear end of the barrel 11, having a generally cylindrical outer surface 31 of generally oval cross section. Preferably, elongated tapered ribs 32 respectively project laterally from the opposite sides of the outer surface 31 adjacent to the distal end thereof. Formed longitudinally through the handle 30 is a tubular inlet passage 33, having an internally threaded portion 34 adjacent at its distal end, and an elongated outlet passage 35, the passages 33 and 35 respectively communicating with ports in the barrel 11, for respectively passing inlet air to the motor and exhaust air from the motor, all in a well-known manner. In this regard, a suitable pneumatic fitting is fixed to the handle 30 at the threaded portion 34 for coupling the inlet passage 33 to an associated source of compressed air. Formed through the front end of the handle 30 adjacent to its upper end is a generally rectangular

opening 36 for accommodating a trigger mechanism (not shown), the opening 36 preferably being flanked along its lower and upper edges by forwardly projecting flanges 37 and 38, respectively. A groove 39 is formed at the junction
5 between the handle 30 and the barrel 11 and extends along the front and sides of the handle 30.

In accordance with the present invention a grip 40 is provided for the handle 30, the grip 40 preferably being formed of a flexible and resilient material, such as
10 thermoplastic material, and being of unitary, one-piece construction. The grip 40 has a generally tubular main body 41 defining a central opening 42 extending longitudinally therethrough and having a generally annular flange 43 projecting laterally therefrom at one end thereof. Formed
15 in the inner surface of the main body 41 along opposite sides thereof are two elongated, tapered grooves 44 extending longitudinally from the end having the flange 43 and terminating about midway between the ends of the main body 41. Formed in the front of the main body 41 adjacent
20 to the upper end thereof is a generally rectangular trigger opening 45. Longitudinally spaced grooves 46 extending part way around the periphery of the main body 41 may be provided along the rear end thereof to provide an improved frictional gripping surface.

25 The lower and upper ends of the trigger opening 45 are, respectively, bounded by forwardly projecting straps 47 and 48, which respectively define partial loops. The upper end of the main body 41 is shaped and dimensioned to be

complementary with the upper end of the handle 30 and is provided with a laterally inwardly extending peripheral bead or short flange 49, which extends around the sides and front end thereof. Integral with the rear end of the main body 41 at its upper edge are attachment flanges 50 and 51 which extend generally longitudinally of the grip 40 and are, respectively, provided with generally cylindrical lugs 52 and 53, which respectively project both forwardly and rearwardly approximately equidistantly from the corresponding flanges 50 and 51.

The central opening 42 is designed to be complementary to the outer surface 31 of the handle 30, so that the grip 40 can be longitudinally slid over the handle 30 by fitting the distal end of the handle 30 into the upper end of the grip 40, as illustrated in FIG. 1. In this regard, the handle ribs 32 will respectively engage in the grip grooves 44 to guide the mounting of the grip 40 and to prevent rotational movement thereof relative to the handle 30. The grip 40 is pushed onto the handle 30 to a mounted position, illustrated in FIGS. 2, 3 and 5, wherein the upper end of the grip 40 engages the barrel 11, with the peripheral bead 49 seated in the groove 39. In this mounted position, the straps 47 and 48 respectively cover the handle flanges 37 and 38, it being appreciated that the material of the grip 40 is sufficiently flexible and resilient to permit the different portions of the grip 40 to be moved to this fully mounted position.

Preferably, the grip 40 is installed on the handle 30

when the end cap 20 is removed. When the grip 40 is in its mounted position, the attachment flanges 50 and 51 will lie along the end face 12 of the barrel 11, with the forwardly projecting portions of the lugs 52 and 53 being respectively seated in the recesses 17, the grip material being sufficiently flexible to permit this insertion. Then, the end cap 20 is installed in place, the rearwardly projecting portions of the lugs 52 and 53 being respectively received in the end cap recesses 24 and the flanges 50 and 51 being clamped between the barrel 11 and the end cap 20. Thus, the grip 40 is securely retained in place on the handle 30.

The material of the grip 40 is preferably designed to provide both cushioning of the user's hand and shock and vibration absorption properties, as well as providing thermal insulation. Because the grip 40 is readily mountable and demountable relative to the handle 30, it is easily replaceable and interchangeable with other similar grips, which have the same internal configuration but different external configurations. Thus, a variety of grips could be provided with different sizes, different durometers of plastic material, different colors, and the like. Grips may be provided in sufficient variety to comfortably fit most user's hands, to provide color coding, or to accommodate other variations in application situations.

Referring now to FIG. 8, there is illustrated a slightly different tool housing 60 which, again, may be for an air impact wrench. The housing 60 is of the pistol-grip type, having a barrel 61 with a trigger mount 62 depending

from the rear end thereof, and having extending at an angle therefrom an elongated handle 63 of generally cylindrical shape. The handle 63 defines a tubular air inlet passage 64 extending longitudinally therethrough and communicating
5 through valve structure (not shown) and associated passageways with an air motor (not shown) to be housed within the barrel 61, all in a well known-manner. In this particular embodiment, the tool housing 60 is provided with an air exhaust or outlet port 65 just forwardly of the upper
10 end of the handle 63. The inlet passage 64 may be internally threaded, as at 66, at the distal end thereof for accommodating attachment to the handle 63 of an exhaust plate 67 and associated air inlet bushing 68, which extends through a hole 69 in the plate 67, all in a well-known
15 manner. Preferably, the plate 67 also has a hole 69a therethrough forwardly of the hole 69.

Referring also to FIGS. 6, 7 and 9, there is illustrated a grip 70 in accordance with another embodiment of the invention, for use with the handle 63 of the tool
20 housing 60. The grip 70 is of unitary, one-piece construction, and may be formed of the same material as the grip 40, described above, being provided at the upper end thereof with an elongated, concave seat surface 72 adapted to matingly engage a complementary surface on the trigger
25 mount 62. Formed in the seat 72 is an elongated channel 73 to accommodate the lower end of the trigger mount 62. Extending longitudinally of the body 71 is a septum wall 74, which extends between the opposite sides of the body 71 and

includes an elongated, longitudinally extending portion 75, integral at its upper end with a forwardly extending portion 76. The longitudinally extending portion 75 divides the interior of the body 71 into longitudinally extending inlet and outlet passages 77 and 78, the outlet passage 78
5 communicating with a port 79 through the forwardly extending portion 76 of the septum wall 74 (FIG. 7). The opposite end of the body 71 terminates in an end surface 80.

The inlet passage 77 and the channel 73 are,
10 respectively, shaped and dimensioned to be complementary to the handle 63 and the trigger mount 62 of the tool housing 60, so that the grip 70 can be slid onto the handle 63, with the distal end of the handle 63 being fitted in the upper end of the inlet passage 77. In assembly, the grip 70 is
15 pushed onto the handle 63 to a fully-mounted position, illustrated in FIG. 9, with the seat 72 engaged against a complementary surface on the trigger mount 62. In this mounted configuration, the outlet passage 78 communicates with the outlet port 65 in the tool housing 60. The exhaust
20 plate 67 and inlet bushing 68 are then installed in place, the exhaust plate 67 being shaped and dimensioned to engage the end surface 80 of the grip 70 around its entire periphery, with the hole 69a communicating with the outlet passage 78, thereby securely to retain the grip 70 in place
25 on the handle 63. While the grip 70 could be formed of the same material as the grip 40, it also could be formed of a somewhat stiffer material, since it does not require the same flexibility in mounting and a somewhat stiffer material

would inhibit deformation of the outlet passage 78 in use.

While, in the illustrated embodiments, the grips have been shown adapted for use with pistol grip tool housings, it will be appreciated that the principles of the invention
5 are also applicable to power hand tools with in-line housings, such as power ratchets, for example.

From the foregoing, it can be seen that there has been provided an improved ergonomic grip for the handle of a power hand tool, which can be easily replaceably mounted on
10 the handle, while being securely retained in place.

While particular embodiments of the present invention have been shown and described, it will be obvious to those skilled in the art that changes and modifications may be made without departing from the invention in its broader
15 aspects. Therefore, the aim in the appended claims is to cover all such changes and modifications as fall within the true spirit and scope of the invention. The matter set forth in the foregoing description and accompanying drawings is offered by way of illustration only and not as a
20 limitation. The actual scope of the invention is intended to be defined in the following claims when viewed in their proper perspective based on the prior art.

**We Claim:**

1. A replaceable grip for a generally cylindrical handle portion of a power hand tool housing which includes attachment structure, the grip comprising:

5 a tubular body formed of a flexible and resilient material and shaped and dimensioned to be slidably received over and cover the handle portion of the tool housing, and a retention portion on said body engageable with the attachment structure of the tool housing for retaining the
10 grip in place on the handle portion.

2. The grip of claim 1, wherein said attachment structure is disposed adjacent to a junction between the handle portion and the remainder of the tool housing.

3. The grip of claim 1, wherein said retention
15 portion is at an end of the tubular body disposed in use adjacent to a distal end of the handle portion, the attachment structure including a plate connectable the handle portion.

4. The grip of claim 1, wherein the attachment
20 structure includes a groove formed at a junction between the handle portion and the remainder of the tool housing, said retention portion including a flange receivable in said groove.

5. The grip of claim 1, wherein the tool includes a
25 trigger mechanism projectable from the handle portion, said retention portion including a band of material engageable with the handle portion between the trigger assembly and the remainder of the tool housing.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN REPLACED



6. The grip of claim 1, wherein the handle portion has a rib extending longitudinally thereof and projecting laterally therefrom, said tubular body having an internal groove which receives said rib to guide the sliding of said body onto the handle portion.

7. The grip of claim 1, wherein the hand tool is a pneumatic tool having an air inlet passage extending through the handle portion.

8. The grip of claim 7, wherein the tool has an exhaust passage extending through the handle portion alongside the inlet passage.

9. The grip of claim 1, wherein the body is formed of a plastic material.

10. The grip of claim 1, wherein said body has an aperture therein accommodating a trigger assembly of the tool.

11. A replaceable grip for a generally cylindrical handle portion of a tool housing having two separable housing parts adapted to be secured together, the grip comprising:

a tubular body formed of a flexible and resilient material and shaped and dimensioned to be slidably received over and cover the handle portion of the tool housing, and

an attachment portion on said body disposable in use between the parts of the tool housing for retaining the grip in place on the handle portion.

12. The grip of claim 11, wherein the tool housing has a pistol grip configuration, the housing parts including a

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



14

barrel, from a rear end of which the handle portion projects, and a rear end cap, said attachment portion being disposable between the barrel and the end cap.

13. The grip of claim 11, wherein the attachment
5 portion includes a flange adapted to be clamped in use between the parts of the tool housing.

14. The grip of claim 13, wherein said flange includes a lug projecting therefrom and receivable in an aperture in at least one of the housing parts.

10 15. The grip of claim 14, wherein said lug projects in opposite directions from said flange and is receivable in apertures in both of the housing parts.

16. The grip of claim 11, wherein the attachment
15 portion includes a rib receivable in a groove in the tool housing.

17. The grip of claim 11, wherein the attachment
structure includes a groove formed at a junction between the handle portion and the remainder of the tool housing, said retention portion including a flange receivable in said
20 groove.

18. A replaceable grip for a generally cylindrical handle portion of a fluid-operated power hand tool housing which has a fluid exhaust port adjacent to the handle portion, the grip comprising:

25 a body formed of a flexible and resilient material and defining two substantially parallel tubular passages therethrough,

one of said passages being shaped and dimensioned to be

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



15

slidably received over and cover the handle portion of the tool in a mounted position,

the other tubular passage communicating with the fluid exhaust port in the mounted position for defining an exhaust
5 passage.

19. The grip of claim 18, and further comprising a retention plate attachable to a distal end of the handle portion and engageable with an adjacent end of the body for retaining it in place on the handle portion.

10 20. The grip of claim 18, wherein said body has an aperture therein for accommodating a trigger assembly of the tool.



THIS SHEET HAS BEEN
REPLACED