

TRAINING METHOD AND SYSTEM FOR PASSENGER DISTRIBUTION PREDICTION MODEL, AND PASSENGER GUIDING METHOD AND SYSTEM

FIELD OF THE INVENTION

5 The present invention belongs to the technical field of urban rail transit operation, and particularly relates to a training method and system for a distribution prediction model of passengers in a subway car, and a method and a system for guiding passengers in a subway car based on environmental monitoring and lighting guidance.

BACKGROUND OF THE INVENTION

With the continuous development of China's rail transit system, the improvement on the operational service level of the rail transit system has become an important force to promote the development of urban rail transit. When taking subway, passengers lack objective perception of the congestion condition in different areas of cars, resulting in some overcrowded areas and some empty
15 areas, which seriously affects the space utilization of subway cars and the passenger experience. Therefore, it is necessary to detect the degree of passenger gathering in the cars and on the platforms in real time and guide passengers to flow to places not crowded, so as to improve the utilization of subway space.

A system and a method for guiding subway passengers include two key technologies: passenger density information acquisition and guidance information release. Currently, the passenger density information acquisition is mainly based on an image detection or pressure sensor detection method. With regard to the image detection method, the passenger density detection ability cannot be guaranteed in cases of crowd flow, obscuration, etc. With regard to the pressure sensor detection method, the installation of pressure sensors requires invasive reconstruction of the entire ground of
20 the subway, for example, the patent application with the publication No. CN110281979A proposed a method of detecting the density of passengers in a subway car by installing piezoelectric sensors on the floor of a subway car.

Currently, the passenger guidance system and method mainly use voice prompts or display prompts, for example, the patent with the Announcement No. CN107244330B proposed a method of guiding
30 passengers to flow in order by installing isolation fences in subway cars and providing voice prompt information. However, the voice prompts are difficult to be heard in a noisy travel condition, and the display prompts are difficult to get the attention of passengers.

SUMMARY OF THE INVENTION

35 The objective of the present invention is to provide a training method and system for a passenger

distribution prediction model, and a method and a system for guiding passengers, so as to solve the problem that the passenger density detection ability cannot be guaranteed in cases of crowd flow and obscuration, the problem that the detection of passenger density with piezoelectric sensors requires invasive reconstruction, and the problem that the voice prompts are poorly targeted and the display prompts are difficult to get the attention of passengers.

In the first aspect, the present invention provides a training method for a distribution prediction model of passengers in a subway car, including:

establishing a spatial coordinate system of each car, installing collection devices constituted by temperature and humidity sensors and a CO₂ concentration sensor in each car, each collection device serving as a sample collection point, and obtaining installation coordinates of each sample collection point in the corresponding spatial coordinate system, wherein the spatial coordinate system is a two-dimensional rectangular coordinate system parallel to the roof or the ground of the car, or the spatial coordinate system is a two-dimensional rectangular coordinate system coincident with the roof or the ground;

obtaining a temperature time series, a humidity time series, and a CO₂ concentration time series at each sample collection point of each car during a sampling period, and obtaining an average temperature value and an average humidity value locally of the day, wherein the installation coordinates of each sample collection point, the temperature time series, the humidity time series, and the CO₂ concentration time series corresponding to the sample collection point, and the average temperature value and the average humidity value constitute an environmental data sample at each sample collection point of each car during the sampling period;

recording passenger positions in each car at an end time of the sampling period, and obtaining coordinates of passengers in the corresponding spatial coordinate system, i.e. obtaining a passenger distribution for each car during the sampling period;

converting the passenger distribution for each car during the sampling period into a binary image, and calculating a mean value, a variance, a maximum value and a minimum value of pixels in the binary image;

calculating an amplitude and a gradient direction of each pixel in the binary image, and establishing a frequency distribution histogram with the gradient direction of all pixels as the abscissa axis and the pixel value corresponding to each pixel as the ordinate axis; extracting a frequency distribution feature of the frequency distribution histogram, the frequency distribution feature referring to a feature vector constituted by pixel values corresponding to each interval among R intervals equally divided from the abscissa axis of the frequency distribution histogram;

combining the mean value, the maximum value, the minimum value, the variance and frequency distribution feature of the pixels to form an original feature vector, and clustering the binary images

with the original feature vector as an input of a clustering algorithm to obtain image clustering results;

coding the passenger distribution mode according to the image clustering results to obtain a passenger distribution code, and each category of image clustering result corresponding to a passenger distribution mode, and each passenger distribution mode corresponding to a passenger distribution code; and

establishing a distribution prediction model for each car, and training the distribution prediction model with training samples to obtain a trained distribution prediction model, the training sample taking the environmental data sample at each sample collection point of each car during the sampling period as input and the corresponding passenger distribution code as output.

In the present invention, the passenger distribution is intelligently sensed by means of the temperature, humidity and CO₂ concentration distribution changes in cars caused by passenger density changes, which avoids the problems of crowd flow and obscuration faced by passenger distribution detection method conducted with images, and avoids the shortcoming in floor intrusive reconstruction faced by passenger distribution detection method conducted with pressure sensors; the passenger distribution data in each car is mapped to the spatial coordinate system, and the passenger distribution is described in pixels, which realizes intelligent classification of passenger distribution modes by image clustering, and solves the problems of inaccurate description of passenger distribution modes in cars and inaccurate description of typical distribution modes in cars.

Further, the spatial coordinate system is a two-dimensional rectangular coordinate system with the horizontal centerline of the roof as the x -axis and the longitudinal centerline of the roof as the y -axis, or the spatial coordinate system is a two-dimensional rectangular coordinate system with the horizontal centerline of the ground as the x -axis and the longitudinal centerline of the ground as the y -axis.

Further, 15 collection devices are installed on the roof of each car, and the 15 collection devices are arranged in an array.

Further, the specific process of converting the passenger distribution for each car during the sampling period into a binary image is as follows:

dividing the car into W equal parts along the x -axis of the spatial coordinate system of each car, and dividing the car into L equal parts along the y -axis of the spatial coordinate system of each car, to convert the space of each car into $W \times L$ independent units;

setting each independent unit as a pixel, the number of passengers in each independent unit being a pixel value of the pixel; and

obtaining pixel values of all pixels, and converting the passenger distribution into the binary image

composed of $W \times L$ pixels.

Preferably, L is 3 and W is 10.

Further, formulas for calculating the amplitude and the gradient direction of the pixel are respectively:

$$G(l, w) = \sqrt{G_x(l, w)^2 + G_y(l, w)^2}, \quad \theta(l, w) = \arctan \frac{G_y(l, w)}{G_x(l, w)}$$

$$G_x(l, w) = I(l+1, w) - I(l-1, w), \quad G_y(l, w) = I(l, w+1) - I(l, w-1)$$

Where, $G(l, w)$ is the amplitude of the pixel, $\theta(l, w)$ is the gradient direction of the pixel, $G_x(l, w)$ is the gradient amplitude of the pixel along the x -axis of the spatial coordinate system, $G_y(l, w)$ is the gradient amplitude of the pixel along the y -axis of the spatial coordinate system, $I(l+1, w)$ is the pixel value of the pixel in row $l+1$ and column w , $I(l-1, w)$ is the pixel value of the pixel in row $l-1$ and column w , $l=1, 2, 3 \dots L$, $w=1, 2, 3 \dots W$, and W is a number of equal parts divided from the car along the x -axis of the spatial coordinate system of each car, and L is a number of equal parts divided from the car along the y -axis of the spatial coordinate system of each car.

Further, the clustering algorithm is an OPTICS algorithm, the initial neighborhood distance parameter ε of the OPTICS algorithm is 0.2, and the initial neighborhood sample parameter $MinPts$ is 3.

The OPTICS algorithm is not sensitive to input parameters, which improves the accuracy of clustering results.

Preferably, the distribution prediction model is any one of a support vector machine model, a relevance vector machine model or a neural network model.

Further, the temperature time series, the humidity time series, and the CO₂ concentration time series in the training samples are replaced with a temperature time series feature vector, a humidity time series feature vector, and a CO₂ concentration time series feature vector, respectively, wherein the temperature time series feature vector, the humidity time series feature vector, and the CO₂ concentration time series feature vector are obtained as follows:

establishing a temperature time series LSTM (Long Short-Term Memory) neural network model, and randomly dividing the temperature time series in the training samples into two temperature training sets, wherein one of the temperature training sets and the passenger distribution code corresponding to the temperature training set constitute a first training set, and the other temperature training set is a second training set; training the temperature time series LSTM neural network model with the first training set to obtain a trained temperature time series LSTM neural network model; removing a classification layer of the trained temperature time series LSTM neural network model, and obtaining the temperature time series feature vector with the second training set as input

and a vector outputted by a fully connected layer as output;
establishing a humidity time series LSTM neural network model, and randomly dividing the humidity time series in the training sample into two humidity training sets, wherein one humidity training set and the passenger distribution code corresponding to the humidity training set constitute
5 a third training set, and the other humidity training set is a fourth training set; training the humidity time series LSTM neural network model with the third training set to obtain a trained humidity time series LSTM neural network model; removing a classification layer of the trained humidity time series LSTM neural network model, and obtaining the humidity time series feature vector with the fourth training set as input and a vector outputted by a fully connected layer as output; and
10 establishing a CO₂ concentration time series LSTM neural network model, and randomly dividing the CO₂ concentration time series in the training sample into two CO₂ concentration training sets, wherein one CO₂ concentration training set and the passenger distribution code corresponding to the CO₂ concentration training set constitute a fifth training set, and the other CO₂ concentration training set is a sixth training set; training the CO₂ concentration time series LSTM neural network
15 model with the fifth training set to obtain a trained CO₂ concentration time series LSTM neural network model; removing a classification layer of the trained CO₂ concentration time series LSTM neural network model, and obtaining the CO₂ concentration time series feature vector with the sixth training set as input and a vector outputted by a fully connected layer as output.

The original temperature time series, humidity time series, and CO₂ concentration time series have
20 high dimensionality. The corresponding feature vectors are extracted through the LSTM neural network models, which reduces the dimensionality of the feature vectors and reduces the complexity of training and testing.

In a second aspect, the present invention further provides a training system for a distribution prediction model of passengers in a subway car, including a plurality of training subsystems, each
25 car corresponding to a training subsystem, wherein each training subsystem includes a plurality of collection devices arranged on the roof of the car and a control device; the collection device includes temperature and humidity sensors and a CO₂ concentration sensor;

the control device includes:

a coordinate system establishment unit, configured to establish a spatial coordinate system of each
30 car, and obtain installation coordinates of each sample collection point in the corresponding spatial coordinate system, each collection device serving as a sample collection point;

an environmental data obtaining unit, configured to obtain a temperature time series, a humidity time series, and a CO₂ concentration time series at each sample collection point of each carduring a sampling period, and obtain an average temperature value and an average humidity value locally of
35 the day, wherein the installation coordinates of each sample collection point, the temperature time

series, the humidity time series, and the CO₂ concentration time series corresponding to the sample collection point, and the average temperature value and the average humidity value constitute an environmental data sample at each sample collection point of each carduring the sampling period;

a passenger distribution obtaining unit, configured to obtain coordinates of passengers in the corresponding spatial coordinate system according to the recorded passenger positions in each car at the end timeof the sampling period, i.e. obtain a passenger distribution for each carduring the sampling period;

an image conversion and feature extraction unit, configured to convert the passenger distribution for each carduring the sampling period into a binary image, and calculate a mean value, a variance, a maximum value and a minimum value of pixels in the binary image; calculate an amplitude and a gradient direction of each pixel in the binary image, and establish a frequency distribution histogram with the gradient direction of all pixels as the abscissa axis and the pixel value corresponding to each pixel as the ordinate axis; and extract a frequency distribution feature of the frequency distribution histogram, the frequency distribution feature referring to a feature vector constituted by pixel values corresponding to each interval among R intervals equally divided from the abscissa axis of the frequency distribution histogram;

a clustering classification unit, configured to combine the mean value, the maximum value, the minimum value, the variance and the frequency distribution feature of the pixels to form an original feature vector, and cluster the binary images with the original feature vectoras input of a clustering algorithm to obtain image clustering results;

a coding unit, configured to code the passenger distribution mode according to the image clustering results to obtain a passenger distribution code, each category of image clustering result corresponding to a passenger distribution mode, and each passenger distribution mode corresponding to a passenger distribution code; and

a model training unit, configured to establish a distribution prediction model for each car, and train the distribution prediction model with a training sample to obtain a trained distribution prediction model, the training sample taking the environmental data sampleof each sample collection point of each carduring the sampling period as input and the corresponding passenger distribution code as output.

In the third aspect, the present invention further provides a method for guiding passengers in a subway car based on environmental monitoring and lighting guidance, including:

obtaining an environmental data sample at each sample collection point of each carduringeach sampling period in real time, the environmental data sample being constituted by installation coordinates of each sample collection point, a temperature time series, a humidity time series, and a CO₂ concentration time series corresponding to the sample collection point, and an average

temperature value and an average humidity value;

inputting the environmental data sample into the distribution prediction model for the corresponding car which is trained by the training method in the first aspect, to obtain a predicted passenger distribution code for each car during the corresponding sampling period; and

5 adjusting the brightness of lighting tubes in the corresponding car according to the predicted passenger distribution code for the car during the corresponding sampling period to guide passenger flow.

The passenger flow is guided by adjusting the brightness of the lighting tubes in the car. For example, the lighting tubes in areas with high passenger density are dimmed, and the lighting tubes
10 in areas with low passenger density are brightened, to guide ordered flow of passengers toward areas with low passenger density (i.e. empty areas), which avoids the noisy environment of the car, and the lighting guidance method has the advantages of simplicity, directness and has high level of public acceptance.

Further, the temperature time series, the humidity time series, and the CO₂ concentration time series
15 in the environmental data samples are replaced with a temperature time series feature vector, a humidity time series feature vector, and a CO₂ concentration time series feature vector, respectively, wherein the temperature time series feature vector, the humidity time series feature vector, and the CO₂ concentration time series feature vector are obtained as follows:

inputting the temperature time series into the trained temperature time series LSTM neural network
20 model with the classification layer removed in the first aspect, the vector outputted by the fully connected layer being the corresponding temperature time series feature vector;

inputting the humidity time series into the trained humidity time series LSTM neural network model with the classification layer removed in the first aspect, the vector outputted by the fully connected layer being the corresponding humidity time series feature vector; and

25 inputting the CO₂ concentration time series into the trained CO₂ concentration time series LSTM neural network model with the classification layer removed in the first aspect, the vector outputted by the fully connected layer being the corresponding CO₂ concentration time series feature vector.

Further, the specific process of controlling the brightness of lighting tubes in the corresponding car according to the predicted passenger distribution code for the car during the corresponding sampling
30 period is as follows:

obtaining a current image clustering result according to the predicted passenger distribution code for the car during the corresponding sampling period, and determining a clustering center corresponding to the current image according to the current image clustering result;

defining S binary images closest to the clustering center as typical clustering images of a
35 corresponding category, and calculating an average pixel value of each pixel position in the S

typical clustering images, to obtain an average pixel image under the category;

assigning each lighting tube to a lighting area according to the layout of lighting tubes in the corresponding car, and calculating an average value of pixel values for pixels in the lighting area corresponding to each lighting tube;

5 if the maximum pixel value in the average pixel image is greater than a pixel threshold, starting lighting guidance and performing the next step, otherwise skipping lighting guidance;

extracting pixels in the average pixel image whose average pixel values are greater than the pixel threshold, the pixels greater than the pixel threshold constituting a set of pixels to be guided;

calculating a lighting guidance coefficient according to the coordinates of the lighting tubes in the spatial coordinate system, the coordinates of pixels in the set of pixels to be guided in the spatial coordinate system, and the average value of pixel values for the pixels in the lighting area, wherein the specific calculation expression is:

$$\beta_n = A_n \left(\sqrt{(x_0^n - x_1^l)^2 + (y_0^n - y_1^w)^2} + \sqrt{(x_0^n - x_2^l)^2 + (y_0^n - y_2^w)^2} + \dots \right. \\ \left. \dots + \sqrt{(x_0^n - x_H^l)^2 + (y_0^n - y_H^w)^2} \right)$$

where, β_n is the lighting guidance coefficient, A_n is the average value of pixel values for pixels in the

15 lighting area corresponding to the n^{th} lighting tube, (x_0^n, y_0^n) is the coordinates of the n^{th} lighting tube in the spatial coordinate system, (x_1^l, y_1^w) is the coordinates of the first pixel in the set of

pixels to be guided in the spatial coordinate system, (x_2^l, y_2^w) is the coordinates of the second pixel

in the set of pixels to be guided in the spatial coordinate system, (x_H^l, y_H^w) is the coordinates of the

20 H^{th} pixel in the set of pixels to be guided in the spatial coordinate system, and H is the number of pixels in the set of pixels to be guided;

adjusting the brightness of the lighting tubes in the lighting areas corresponding to the β_n values according to the order of the β_n values, and guiding passengers to flow toward the lighting area with a smaller β_n value.

Preferably, the pixel threshold is 15.

25 In a fourth aspect, the present invention further provides a system for guiding passengers in a subway car based on environmental monitoring and lighting guidance, including:

a real-time data obtaining unit, configured to obtain an environmental data sample at each sample collection point of each car during each sampling period in real time, the environmental data sample being constituted by installation coordinates of each sample collection point, a temperature time series, a humidity time series, and a CO₂ concentration time series corresponding to the sample collection point, an average temperature value and an average humidity value;

a prediction unit, configured to input the environmental data sample into the distribution prediction model for the corresponding car which is trained by the training method of the first aspect, to obtain a predicted passenger distribution code for each car during the corresponding sampling period; and an adjustment and guidance unit, configured to adjust the brightness of lighting tubes in the corresponding car according to the predicted passenger distribution code for the car during the corresponding sampling period to guide passenger flow.

Further, the adjustment and guidance unit is specifically configured to:

Obtain a current image clustering result according to the predicted passenger distribution code for the car during the corresponding sampling period, and determine a clustering center corresponding to the current image according to the current image clustering result;

Define S binary images closest to the clustering center as typical clustering images of a corresponding category, and calculate an average pixel value of each pixel position in the S typical clustering images, to obtain an average pixel image under the category;

assign each lighting tube to a lighting area according to the layout of lighting tubes in the corresponding car, and calculate an average value of pixel values for pixels in the lighting area corresponding to each lighting tube;

if the maximum pixel value in the average pixel image is greater than a pixel threshold, start lighting guidance and perform next step, otherwise skip lighting guidance;

extract pixels in the average pixel image whose average pixel values are greater than the pixel threshold, the pixels greater than the pixel threshold constituting a set of pixels to be guided;

calculate a lighting guidance coefficient according to the coordinates of the lighting tubes in the spatial coordinate system, the coordinates of pixels in the set of pixels to be guided in the spatial coordinate system, and the average value of pixel values for the pixels in the lighting area, wherein the specific calculation expression is:

$$\beta_n = A_n \left(\sqrt{(x_0^n - x_1^l)^2 + (y_0^n - y_1^w)^2} + \sqrt{(x_0^n - x_2^l)^2 + (y_0^n - y_2^w)^2} + \dots \right. \\ \left. \dots + \sqrt{(x_0^n - x_H^l)^2 + (y_0^n - y_H^w)^2} \right)$$

where, β_n is the lighting guidance coefficient, A_n is the average value of pixel values for pixels in the lighting area corresponding to the n^{th} lighting tube, (x_0^n, y_0^n) is the coordinates of the n^{th} lighting tube in the spatial coordinate system, (x_1^l, y_1^w) is the coordinates of the first pixel in the set of pixels to be guided in the spatial coordinate system, (x_2^l, y_2^w) is the coordinates of the second pixel in the set of pixels to be guided in the spatial coordinate system, (x_H^l, y_H^w) is the coordinates of the H^{th} pixel in the set of pixels to be guided in the spatial coordinate system, and H is the number of

pixels in the set of pixels to be guided;

adjust the brightness of the lighting tubes in the lighting areas corresponding to the β_n values according to the order of the β_n values, and guide passengers to flow toward the lighting area with a smaller β_n value.

5 Beneficial effects

Compared with the prior art, the present invention provides training method and system for a passenger distribution prediction model, and the passenger guiding method and system. In the present invention, the passenger distribution is intelligently sensed by means of the characteristics that passenger density changes causes temperature, humidity and CO₂ concentration distribution to change in cars, which avoids the problems of crowd flow and obscuration faced by passenger distribution detection method conducted with images, and avoids the shortcoming in invasive reconstruction of floor faced by passenger distribution detection method conducted with pressure sensors; the passenger distribution data in each car is mapped to the spatial coordinate system, and the passenger distribution is described in pixels, which realizes intelligent classification of passenger distribution modes by image clustering, and solves the problems of inaccurate description of passenger distribution modes in cars and inaccurate description of typical distribution modes in cars; the passenger flow is guided by adjusting the brightness of the lighting tubes in the car, for example, the lighting tubes in areas with high passenger density are dimmed, and the lighting tubes in areas with low passenger density are brightened, to guide ordered flow of passengers toward areas with low passenger density (i.e. empty areas), which avoids the noisy environment of the car, and the lighting guidance method has the advantages of simplicity, directness and has high level of public acceptance.

Brief Description of the Drawings

25 In order to more clearly illustrate the technical solutions of the present invention, the drawings used in the description of the embodiments will be briefly described below. Obviously, the drawings in the following description are only some embodiments of the present invention, and those of ordinary skill in the art can also obtain other drawings according to the drawings without any creative effort.

30 FIG. 1 is a flowchart of a training method for a distribution prediction model of passengers in a subway car in an embodiment of the present invention;

FIG. 2 is a flowchart of a passenger guiding method for a subway car based on environmental monitoring and lighting guidance in an embodiment of the present invention;

FIG. 3 is a schematic diagram of the layout of lighting tubes and lighting areas in an embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

A clear and complete description will be made to the technical solutions in the present invention below with reference to the accompanying drawings in the embodiments of the present invention.

Apparently, the embodiments described are only part of the embodiments of the present invention, not all of them. All other embodiments obtained by those of ordinary skill in the art based on the embodiments of the present invention without any creative effort shall fall within the protection scope of the present invention.

As shown in FIG. 1, a training method for a distribution prediction model of passengers in a subway car provided by this embodiment includes:

1. Obtaining of training samples

1.1 Establishment of a coordinate system and setting of collection devices

A spatial coordinate system of each car is established, a collection device constituted by temperature and humidity sensors and a CO₂ concentration sensor is installed in each car, each collection device serves as a sample collection point, and installation coordinates of each sample collection point in the corresponding spatial coordinate system are obtained. The spatial coordinate system is a two-dimensional rectangular coordinate system parallel to the roof or the ground, or the spatial coordinate system is a two-dimensional rectangular coordinate system coincident with the roof or the ground. The spatial coordinate system facilitates the mapping of sample collection points and passengers (or independent units constituted by passengers) into the spatial coordinate system.

In this embodiment, the spatial coordinate system is a two-dimensional rectangular coordinate system with the horizontal centerline of the roof as the x -axis and the longitudinal centerline of the roof as the y -axis, or the spatial coordinate system is a two-dimensional rectangular coordinate system with the horizontal centerline of the ground as the x -axis and the longitudinal centerline of the ground as the y -axis.

In order to obtain the mapping relationship between the distribution of passengers in the subway car and environmental parameters, original environmental data is collected first by the collection device. 15 collection devices are installed on the roof of each car, and the 15 collection devices are arranged in a 3×5 array. It is assumed that the installation coordinates of the i^{th} sample collection point in the corresponding spatial coordinate system are $P_i = (x_i, y_i)$, $i = 1, 2, \dots, o$, and o is 15 in this embodiment.

1.2 Obtaining of training input samples (i.e. original environmental data samples)

A temperature time series, a humidity time series, and a CO₂ concentration time series at each sample collection point of each car during a sampling period are obtained, an average temperature value and an average humidity value locally of the day are obtained; and the installation coordinates

of each sample collection point, the temperature time series, the humidity time series, and the CO₂ concentration time series corresponding to the sample collection point, and the average temperature value and the average humidity value constitute an environmental data sample at each sample collection point of each carduring the sampling period.

5 The time when screen doors of the subway is opened after the arrival of the subway is defined as a time start 0 of the sampling period, the time when positions of passengers are basically stable after completion of passengerboarding (i.e. no crowd flow) is defined as an end T of the sampling period, and the collection device obtains a temperature time series $Temp^i = \{temp_t^i, t=1, 2, \dots, \frac{T}{t_0}\}$, a humidity time series $RH^i = \{Rh_t^i, t=1, 2, \dots, \frac{T}{t_0}\}$ and a CO₂ concentration time series

10 $C_{co2}^i = \{c_t^i, t=1, 2, \dots, \frac{T}{t_0}\}$ of the i^{th} sample collection point during a sampling period, where t_0 is a sampling interval, T is a duration of the sampling period, $temp_t^i$ is a temperature value of the i^{th} sample collection point at time t , Rh_t^i is a humidity value of the i^{th} sample collection point at time t , and c_t^i is a CO₂ concentration value of the i^{th} sample collection point at time t . An average temperature value $temp_0$ and an average humidity value Rh_0 locally of the day are obtained, then

15 the environmental data sample obtained during a sampling period (time 0 to time T) is $E = [x_i, y_i, temp_t^i, Rh_t^i, c_t^i, temp_0, Rh_0]$.

1.3 Obtaining of training output samples (i.e. coding of passenger distribution)

1.31 Obtaining of passenger distribution

In order to avoid the problem of low accuracy of passenger distribution detection due to obscuration and the like in other existing passenger distribution collection modes, passenger positions in each car at an end time T of the sampling period are recorded by artificial statistics, and coordinates of passengers in the corresponding spatial coordinate system are obtained, i.e. a passenger distribution for each carduring the sampling period is obtained, specifically denoted as

20 $D = \{x_j, y_j, j=1, 2, \dots, N\}$, where j is the j^{th} passenger, N is the number of passengers in the car, and (x_j, y_j) is the coordinates of the j^{th} passenger in the corresponding spatial coordinate system.

1.32 Coding of a passenger distribution mode of each car

In order to quantitatively describe the passenger distribution, the passenger distribution mode is coded. The specific coding steps are as follows:

30 *a.* The passenger distribution for each carduring the sampling period (time 0 to time T) is converted into a binary image, specifically:

a1. Each car is divided into W equal parts along the x -axis of the spatial coordinate system of the car, and each car is divided into L equal parts along the y -axis of the spatial coordinate system of the car, to convert the space of each car into $W \times L$ independent units. In this embodiment, $L=3$ and $W=10$.

a2. Each independent unit is set as a pixel, and the number of passengers in each independent unit is a pixel value of the pixel, that is, the number of passengers $I(l, w)$ in the independent unit of row l and column w is the pixel value of the pixel in row l and column w , $l=1, 2, 3, \dots, L$, $w=1, 2, 3, \dots, W$.

a3. The pixel values of all pixels are obtained, and the passenger distribution is converted into a binary image constituted by $W \times L$ pixels.

10 b. A mean value, a variance, a maximum value $I_{\max}$ and a minimum value $I_{\min}$ of pixels in the binary image are calculated.

The mean value $\bar{I}$ of pixels in the binary image is $\bar{I} = \frac{1}{L \times W} \sum_{l=1, w=1}^{l=L, w=W} I(l, w)$ (1)

The variance I_{SDE} of pixels in the binary image is $I_{SDE} = \sqrt{\sum_{l=1, w=1}^{l=L, w=W} (I(l, w) - \bar{I})^2 / (L \times W)}$ (2)

15 c. In order to obtain a feature of change in the pixel values of the binary image in different directions, an amplitude and a gradient direction of each pixel in the binary image are calculated, and a frequency distribution histogram is established with the gradient direction of all pixels as the abscissa axis and the pixel value corresponding to each pixel as the ordinate axis; and a frequency distribution feature of the frequency distribution histogram is extracted, the frequency distribution feature referring to a feature vector constituted by pixel values corresponding to each interval among R intervals equally divided from the abscissa axis of the frequency distribution histogram.

20 Formulas for calculating the amplitude and the gradient direction of each pixel in the binary image are respectively:

$$G(l, w) = \sqrt{G_x(l, w)^2 + G_y(l, w)^2} \quad (3)$$

$$\theta(l, w) = \arctan \frac{G_y(l, w)}{G_x(l, w)} \quad (4)$$

$$25 \quad G_x(l, w) = I(l+1, w) - I(l-1, w) \quad (5)$$

$$G_y(l, w) = I(l, w+1) - I(l, w-1) \quad (6)$$

Where, $G(l, w)$ is the amplitude of the pixel, $\theta(l, w)$ is the gradient direction of the pixel, $G_x(l, w)$ is the gradient amplitude of the pixel along the x -axis of the spatial coordinate system, $G_y(l, w)$ is the gradient amplitude of the pixel along the y -axis of the spatial coordinate system, $I(l+1, w)$ is the

pixel value of the pixel in row $l+1$ and column w , and $I(l-1, w)$ is the pixel value of the pixel in row $l-1$ and column w .

In this embodiment, $R=9$, that is, the gradient direction is divided into 9 equal parts within $[0, 180^\circ]$, to construct 9 gradient direction intervals $[0, 20^\circ)$, $[20, 40^\circ)$, $[40, 60^\circ)$, $[60, 80^\circ)$, $[80, 100^\circ)$, $[100, 120^\circ)$, $[120, 140^\circ)$, $[140, 160^\circ)$, and $[160, 180^\circ]$. At the time start of each sampling period, the initial frequency value of each interval is 0, that is, the cumulative pixel value of the gradient direction in this interval is 0, then the initial gradient direction frequency vector is $F_0 = \{0, 0, 0, 0, 0, 0, 0, 0, 0\}$, where F_0 indicates that the initial frequency values of the 9 intervals are all 0. The gradient direction frequency vector is set to be $F_{l \times w} = \{f_1, \dots, f_r, \dots, f_9\}$, and if the gradient direction of the $(l \times w)^{\text{th}}$ pixel falls within the r^{th} interval, the updated gradient direction frequency vector is $F_{l \times w} = \{f_1, \dots, f_r + G(l, w), \dots, f_9\}$, where $l \times w = 1, 2, \dots, L \times W$, $r = 1, 2, \dots, 9$. The final gradient direction frequency vector $F_{L \times W}$ obtained after all pixels are traversed is the frequency distribution feature of the binary image.

d. The mean value, the maximum value, the minimum value, the variance and the frequency distribution feature of the pixels are combined to form an original feature vector $P = [\bar{I}, I_{\max}, I_{\min}, I_{SDE}, F_{L \times W}]$, and the binary images are clustered with the original feature vector P as input of a clustering algorithm to obtain image clustering results.

The clustering algorithm for classification is the prior art. In this embodiment, the clustering algorithm is an OPTICS algorithm for clustering the binary images to obtain image clustering results.

The initial neighborhood distance parameter ε of the OPTICS algorithm is set to 0.2, and the initial neighborhood sample parameter $MinPts$ is set to 3. The OPTICS algorithm is the prior art, and the OPTICS algorithm is not sensitive to input parameters, which improves the accuracy of clustering results.

e. The passenger distribution mode is coded according to the image clustering results to obtain a passenger distribution code. Each category of image clustering result corresponds to a passenger distribution mode, and each passenger distribution mode corresponds to a passenger distribution code.

The clustering results show that the same category of images are the same category of image samples, the passenger distribution mode corresponding to the same category of image samples is the same type of distribution mode, and each type of passenger distribution mode corresponds to a passenger distribution code. For example, the image clustering results show that the images are divided into 5 categories, then 5 passenger distribution codes $[1, 0, 0, 0, 0]^T$, $[0, 1, 0, 0, 0]^T$, $[0, 0, 1, 0, 0]^T$, $[0, 0, 0, 1, 0]^T$ and $[0, 0, 0, 0, 1]^T$ can be obtained according to binary codes. The passenger distribution codes

are sorted in descending order according to the number of image samples in the category it belongs to, the first passenger distribution code is $[1, 0, 0, 0, 0]^T$, the second passenger distribution code is $[0, 1, 0, 0, 0]^T$, the third passenger distribution code is $[0, 0, 1, 0, 0]^T$, the fourth passenger distribution code is $[0, 0, 0, 1, 0]^T$, and the fifth type of passenger distribution code is $[0, 0, 0, 0, 1]^T$.

5 1.4 Processing of the original environmental data samples

The temperature time series, the humidity time series, and the CO₂ concentration time series in the original environmental data samples have high dimensionality. In order to reduce the dimensionality of input training samples and reduce the complexity of subsequent model training and testing, a LSTM neural network model is established to extract feature vectors. The specific process is:

A temperature time series LSTM neural network model is established, and the temperature time series LSTM neural network model is trained with a first training set to obtain a trained temperature time series LSTM neural network model; a classification layer of the trained temperature time series LSTM neural network model is removed, and a temperature time series feature vector is obtained with a second training set as input and a vector outputted by a fully connected layer as output; the temperature time series during a sampling period in step 1.21 is randomly divided into two temperature training sets, one of the temperature training sets and the passenger distribution code corresponding to the temperature training set (step *e*) constitute the first training set, and the other temperature training set is the second training set. For example, the temperature time series

20 $Temp^i = \{temp_t^i, t = 1, 2, \dots, \frac{T}{t_0}\}$ during a sampling period is divided into two temperature training sets according to a proportion of 5:3, the time series has a length of $\frac{T}{t_0}$, and the feature dimension is the number of the sample collection points. The humidity time series and the CO₂ concentration time series are processed in similar ways as that of the temperature time series.

A humidity time series LSTM neural network model is established, and the humidity time series LSTM neural network model is trained with a third training set to obtain a trained humidity time series LSTM neural network model; a classification layer of the trained humidity time series LSTM neural network model is removed, and a humidity time series feature vector is obtained with a fourth training set as input and a vector outputted by a fully connected layer as output; the humidity time series during a sampling period in step 1.21 is randomly divided into two humidity training sets, one of the humidity training sets and the passenger distribution code corresponding to the humidity training set constitute the third training set, and the other humidity training set is the fourth training set.

A CO₂ concentration time series LSTM neural network model is established, and the CO₂ concentration time series LSTM neural network model is trained with a fifth training set to

obtain a trained CO₂ concentration time series LSTM neural network model; a classification layer of the trained CO₂ concentration time series LSTM neural network model is removed, and a CO₂ concentration time series feature vector is obtained with a sixth training set as input and a vector outputted by a fully connected layer as output; the CO₂ concentration time series during a sampling period in step 1.21 is randomly divided into two CO₂ concentration training sets, one of the CO₂ concentration training sets and the passenger distribution code corresponding to the CO₂ concentration training set constitute the fifth training set, and the other CO₂ concentration training set is the sixth training set.

The temperature time series, the humidity time series, and the CO₂ concentration time series in the training input samples are replaced with the temperature time series feature vector, the humidity time series feature vector, and the CO₂ concentration time series feature vector respectively, to obtain new environmental data samples E' in the training input samples.

The establishment of the LSTM neural network model is the prior art. In this embodiment, the number of neurons in a hidden layer of the LSTM neural network model is 100, and the number of training iterations is 2000.

2. Establishment of a distribution prediction model for each car, and training of the distribution prediction model (i.e. obtaining of a mapping relationship between environmental data and passenger distribution)

A distribution prediction model for each car is established, and the distribution prediction model is trained with training samples to obtain a trained distribution prediction model, the training sample taking the new environmental data sample E' at each sample collection point of the car during a sampling period in step 1 as input and the corresponding passenger distribution code as output.

The distribution prediction model may be any of a support vector machine model, a relevance vector machine model or a neural network model, and the establishment of the distribution prediction model is the prior art.

A training system for a distribution prediction model of passengers in a subway car provided by this embodiment includes a plurality of training subsystems, each car corresponds to a training subsystem, and each training subsystem includes a plurality of collection devices arranged on the roof of the car and a control device; and the collection device includes temperature and humidity sensors and a CO₂ concentration sensor. The setting of the collection device is recorded in step 1.1. The control device may be shared by the entire train, or each car corresponds to a control device. Corresponding to the training method for a distribution prediction model of passengers in a subway car, the control device includes:

a coordinate system establishment unit, configured to establish a spatial coordinate system of each car, and obtain installation coordinates of each sample collection point in the corresponding spatial

coordinate system, each collection device serving as a sample collection point;
an environmental data obtaining unit, configured to obtain a temperature time series, a humidity time series, and a CO₂ concentration time series of each sample collection point of each car during a sampling period, and obtain an average temperature value and an average humidity value locally of the day, wherein the installation coordinates of each sample collection point, the temperature time series, the humidity time series, and the CO₂ concentration time series corresponding to the sample collection point, and the average temperature value and average humidity value constitute an environmental data sample of each sample collection point of each car during the sampling period;
a passenger distribution obtaining unit, configured to obtain coordinates of passengers in the corresponding spatial coordinate system according to the recorded passenger positions in each car at an end time of the sampling period, i.e. obtain a passenger distribution for each car during the sampling period;
an image conversion and feature extraction unit, configured to convert the passenger distribution for each car during the sampling period into a binary image, and calculate a mean value, a variance, a maximum value and a minimum value of pixels in the binary image according to formulas (1) and (2); calculate an amplitude and a gradient direction of each pixel in the binary image according to formulas (3) to (6), and establish a frequency distribution histogram with the gradient direction of all pixels as the abscissa axis and the pixel value corresponding to each pixel as the ordinate axis; and extract a frequency distribution feature of the frequency distribution histogram, the frequency distribution feature referring to a feature vector constituted by pixel values corresponding to each interval among R intervals equally divided from the abscissa axis of the frequency distribution histogram;
a clustering classification unit, configured to combine the mean value, the maximum value, the minimum value, the variance and the frequency distribution feature of the pixels to form an original feature vector, and cluster the binary images with the original feature vector as input of a clustering algorithm to obtain image clustering results;
a coding unit, configured to code the passenger distribution mode according to the image clustering results to obtain a passenger distribution code, each type of image clustering result corresponding to a passenger distribution mode, and each passenger distribution mode corresponding to a passenger distribution code; and
a model training unit, configured to establish a distribution prediction model for each car, and train the distribution prediction model with training samples to obtain a trained distribution prediction model, the training sample taking the environmental data sample at each sample collection point of each car during the sampling period as input and the corresponding passenger distribution code as output.

As shown in FIG. 2, a method for guiding passengers in a subway car based on environmental monitoring and lighting guidance provided by this embodiment includes:

3.1 obtaining of prediction samples

3.11 During the prediction, the collection device in step 1.1 obtains an environmental data sample of each sample collection point of each car during each sampling period in real time. The environmental data sample is constituted by installation coordinates of each sample collection point, a temperature time series, a humidity time series, and a CO₂ concentration time series corresponding to the sample collection point, and an average temperature value and an average humidity value.

3.12 The temperature time series in the environmental data samples of step 3.11 is inputted into the trained temperature time series LSTM neural network model with the classification layer removed in step 1.4, the vector outputted by the fully connected layer being a corresponding temperature time series feature vector;

The humidity time series in the environmental data samples of step 3.11 is inputted into the trained humidity time series LSTM neural network model with the classification layer removed in step 1.4, the vector outputted by the fully connected layer being a corresponding humidity time series feature vector;

The CO₂ concentration time series in the environmental data samples of step 3.11 is inputted into the trained CO₂ concentration time series LSTM neural network model with the classification layer removed in step 1.4, the vector outputted by the fully connected layer being a corresponding CO₂ concentration time series feature vector.

3.13 The temperature time series, the humidity time series, and the CO₂ concentration time series in the environmental data samples obtained in real time are replaced with the temperature time series feature vector, the humidity time series feature vector, and the CO₂ concentration time series feature vector respectively, to obtain new environmental data samples obtained in real time.

3.2 Obtaining of prediction results

The new environmental data samples obtained in real time are inputted into the distribution prediction model for the corresponding car which is trained by the training method for the distribution prediction model of passengers in the subway car, to obtain a predicted passenger distribution code for each car during the corresponding sampling period.

3.3 Lighting guidance

Taking the end time of the sampling period as a time start, the brightness of lighting tubes in the corresponding car is adjusted according to the predicted passenger distribution code for the car during the corresponding sampling period to guide passenger flow. The specific process is:

3.31 A current image clustering result (i.e. a category of current passenger distribution) is obtained

according to the predicted passenger distribution code for the car during the corresponding sampling period, and a clustering center corresponding to the current image is determined according to the current image clustering result. The image clustering result includes the clustering center and samples around the clustering center.

3.32 Binary images closest to the clustering center are defined as typical clustering images of a corresponding category, and an average pixel value of each pixel position in the S typical clustering images is calculated, to obtain an average pixel image under the category.

In this embodiment, $S=10$, and an average pixel value of the pixel position (l, w) in the 10 typical

clustering images is $\bar{I}(l, w) = \frac{1}{10} \sum_{k=1}^{10} I(l, w)_k$, where $I(l, w)_k$ is the pixel value of the k^{th} typical

clustering image at the position (l, w) . An average pixel value of each pixel position in the 10 typical clustering images is calculated, that is, an average pixel value of the pixels at the same position (or corresponding position) in the 10 typical clustering images is solved, and the number of average pixel values corresponds to the number of pixels on the typical clustering image.

3.33 According to the layout of lighting tubes of each car, each lighting tube is assigned to a lighting area in accordance with the principle of proximity. As shown in FIG. 3, dual-line parallel layout and lighting with 8 strip LED lamp panels are the typical lighting mode of the subway train. The brightness of 8 strip LED tubes is controlled to change the brightness distribution of the passenger compartment, so as to guide passenger flow.

An average value of pixel values for pixels in the lighting area corresponding to each lighting tube is calculated. The line connecting the points, located about the same distance from the centers of the lighting tubes respectively in two adjacent lighting areas, constitutes a dividing line of the two adjacent lighting areas.

3.34 If the maximum pixel value $\bar{I}_{\max}$ in the average pixel image is greater than a pixel threshold δ , lighting guidance is started and next step 3.35 is performed (i.e. as long as the average value for a pixel position is greater than the pixel threshold δ , the lighting guidance is started), otherwise, no lighting guidance is required. In this embodiment, $\delta=15$, and the average value for the pixel position which is greater than δ indicates a crowded state.

3.35 Pixels in the average pixel image whose average pixel values are greater than the pixel threshold δ are extracted, and the pixels whose average pixel values are greater than the pixel threshold constitute a set of pixels to be guided $\bar{I}_A = \{\bar{I}(l_1, w_1), \bar{I}(l_2, w_2), \dots, \bar{I}(l_H, w_H)\}$, where $\bar{I}(l_1, w_1)$ is an average pixel value of the first pixel in the pixels to be guided, $\bar{I}(l_2, w_2)$ is an average pixel value of the second pixel in the pixels to be guided, $\bar{I}(l_H, w_H)$ is an average

pixel value of the H^{th} pixel in the pixels to be guided, H is the number of pixels in the set of pixels to be guided, (l_1, w_1) indicates that the first pixel in the pixels to be guided is a pixel corresponding to the independent unit with the row of l_1 and the column of w_1 , i.e. pixel coordinates of the pixel, and other pixels can be analogized using the above method.

- 5 3.36 A lighting guidance coefficient is calculated according to the coordinates of the lighting tubes in the spatial coordinate system, the coordinates of pixels in the set of pixels to be guided in the spatial coordinate system, and the average value of pixel values for the pixels in the lighting area. The specific calculation expression is:

$$\beta_n = A_n \left(\sqrt{(x_0^n - x_1^l)^2 + (y_0^n - y_1^w)^2} + \sqrt{(x_0^n - x_2^l)^2 + (y_0^n - y_2^w)^2} + \dots \right. \\ \left. \dots + \sqrt{(x_0^n - x_H^l)^2 + (y_0^n - y_H^w)^2} \right) \quad (7)$$

- 10 Where, β_n is the lighting guidance coefficient, A_n is the average value of pixel values for pixels in the lighting area corresponding to the n^{th} lighting tube, (x_0^n, y_0^n) is the coordinates of the n^{th} lighting tube in the spatial coordinate system, (x_1^l, y_1^w) is the coordinates of the first pixel in the set of pixels to be guided in the spatial coordinate system, (x_2^l, y_2^w) is the coordinates of the second pixel in the set of pixels to be guided in the spatial coordinate system, and (x_H^l, y_H^w) is the coordinates of the H^{th} pixel in the set of pixels to be guided in the spatial coordinate system.

- 15 3.37 The brightness of the lighting tubes in the lighting areas corresponding to the β_n values are adjusted according to the order of the β_n values, and the passengers are guided to flow toward the lighting area with a smaller β_n value.

- For example, the β_n values are sorted from large to small, the lighting tubes in the lighting area corresponding to the maximum β_n value are adjusted to the darkest, the lighting tubes in the lighting area corresponding to the minimum β_n value are adjusted to the brightest, and the lighting tubes in the lighting area with smaller β_n value are adjusted to be brighter than the lighting tubes in the lighting area with larger β_n value. The passenger flow is guided by changing the brightness distribution in the car. This guidance method has the advantages of simplicity, directness, and has high level of public acceptance.

- 25 This embodiment further provides a system for guiding passengers in a subway car based on environmental monitoring and lighting guidance, including:

- a real-time data obtaining unit, configured to obtain an environmental data sample at each sample collection point of each car during each sampling period in real time; the environmental data sample being constituted by installation coordinates of each sample collection point, a temperature time

series, a humidity time series, and a CO₂ concentration time series corresponding to the sample collection point, and an average temperature value and an average humidity value;

a prediction unit, configured to input the environmental data samples into the distribution prediction model for the corresponding car which is trained by the training method for the distribution prediction model of passengers in the subway car, to obtain a predicted passenger distribution code for each car during the corresponding sampling period; and

an adjustment and guidance unit, configured to adjust the brightness of lighting tubes in the corresponding car according to the predicted passenger distribution code for the car during the corresponding sampling period to guide passenger flow.

Disclosed above are only the specific embodiments of the present invention, but the protection scope of the present invention is not limited thereto. Any person skilled in the art can easily conceive of changes or modifications within the technical scope disclosed in the present invention, and these changes and modifications shall fall within the protection scope of the present invention.

Claims

1. A method for guiding passengers in a subway car based on environmental monitoring and lighting guidance, comprising: establishing a spatial coordinate system of each car, installing a collection device constituted by temperature and humidity sensors and a CO₂ concentration sensor in each car, each collection device serving as a sample collection point,
5 and obtaining installation coordinates of each sample collection point in the corresponding spatial coordinate system; wherein the spatial coordinate system is a two-dimensional rectangular coordinate system parallel to the roof or the ground of the car, or the spatial coordinate system is a two-dimensional rectangular coordinate system coincident with the
10 roof or the ground;
obtaining a temperature time series, a humidity time series, and a CO₂ concentration time series at each sample collection point of each car during a sampling period, and obtaining an average temperature value and an average humidity value locally of the day, wherein the installation coordinates of each sample collection point, the temperature time series, the
15 humidity time series, and the CO₂ concentration time series corresponding to the sample collection point, and the average temperature value and the average humidity value constitute an environmental data sample at each sample collection point of each car during the sampling period;
recording passenger positions in each car at an end time of the sampling period, and
20 obtaining coordinates of passengers in the corresponding spatial coordinate system, i.e. obtaining a passenger distribution for each car during the sampling period;
converting the passenger distribution for each car during the sampling period into a binary image, and calculating a mean value, a variance, a maximum value and a minimum value of pixels in the binary image;
25 calculating an amplitude and a gradient direction of each pixel in the binary image, and

establishing a frequency distribution histogram with the gradient direction of all pixels as the abscissa axis and the pixel value corresponding to each pixel as the ordinate axis; extracting a frequency distribution feature of the frequency distribution histogram, the frequency distribution feature referring to a feature vector constituted by pixel values
 5 corresponding to each interval among R intervals equally divided from the abscissa axis of the frequency distribution histogram;

combining the mean value, the maximum value, the minimum value, the variance and the frequency distribution feature of the pixels to form an original feature vector, and clustering the binary images with the original feature vector as input of a clustering algorithm to obtain
 10 image clustering results;

coding the passenger distribution mode according to the image clustering results to obtain a passenger distribution code, each category of image clustering result corresponding to a passenger distribution mode, and each passenger distribution mode corresponding to a passenger distribution code; and

15 establishing a distribution prediction model for each car, and training the distribution prediction model with training samples to obtain a trained distribution prediction model, the training sample taking the environmental data sample at each sample collection point of each car during the sampling period as input and the corresponding passenger distribution code as output;

20 inputting the environmental data sample at each sample collection point of each car during each sampling period in real time into the trained distribution prediction model for the corresponding car to obtain a predicted passenger distribution code for each car during the corresponding sampling period

adjusting the brightness of lighting tubes in the corresponding car according to the predicted
 25 passenger distribution code for the car during the corresponding sampling period to guide

passenger flow; where the specific process is as follows:

obtaining a current image clustering result according to the predicted passenger distribution code for the car during the corresponding sampling period, and determining a clustering center corresponding to the current image according to the current image clustering result;

5 defining S binary images closest to the clustering center as typical clustering images of a corresponding category, and calculating an average pixel value of each pixel position in the S typical clustering images, to obtain an average pixel image under the category;

assigning each lighting tube to a lighting area according to the layout of lighting tubes in the corresponding car, and calculating an average value of pixel values for pixels in the

10 lighting area corresponding to each lighting tube;

if the maximum pixel value in the average pixel image is greater than a pixel threshold, starting lighting guidance and performing next step, otherwise skipping lighting guidance;

extracting pixels in the average pixel image whose average pixel values are greater than the pixel threshold, the pixels greater than the pixel threshold constituting a set of pixels to be

15 guided;

calculating a lighting guidance coefficient according to the coordinates of the lighting tubes in the spatial coordinate system, the coordinates of pixels in the set of pixels to be guided in the spatial coordinate system, and the average value of pixel values for the pixels in the lighting area, wherein the specific calculation expression is:

$$20 \quad \beta_n = A_n \left(\sqrt{(x_0^n - x_1^l)^2 + (y_0^n - y_1^w)^2} + \sqrt{(x_0^n - x_2^l)^2 + (y_0^n - y_2^w)^2} + \dots \right. \\ \left. \dots + \sqrt{(x_0^n - x_H^l)^2 + (y_0^n - y_H^w)^2} \right)$$

where, β_n is the lighting guidance coefficient, A_n is the average value of pixel values for pixels in the lighting area corresponding to the n^{th} lighting tube, (x_0^n, y_0^n) is the

coordinates of the n^{th} lighting tube in the spatial coordinate system, (x_1^l, y_1^w) is the

coordinates of the first pixel in the set of pixels to be guided in the spatial coordinate system,
 (x_2^l, y_2^w) is the coordinates of the second pixel in the set of pixels to be guided in the
spatial coordinate system, (x_H^l, y_H^w) is the coordinates of the H^{th} pixel in the set of pixels
to be guided in the spatial coordinate system, and H is the number of pixels in the set of
5 pixels to be guided;

adjusting the brightness of the lighting tubes in the lighting areas corresponding to the β_n
values according to the order of the β_n values, and guiding passengers to flow toward the
lighting area with a smaller β_n value.

2. The method for guiding passengers in a subway car according to claim 1, wherein the
10 spatial coordinate system is a two-dimensional rectangular coordinate system with a
horizontal centerline of the roof of the car as the x -axis and a longitudinal centerline of the
roof as the y -axis, or the spatial coordinate system is a two-dimensional rectangular
coordinate system with a horizontal centerline of the ground of the car as the x -axis and a
longitudinal centerline of the ground as the y -axis.

15 3. The method for guiding passengers in a subway car according to claim 1, wherein 15
collection devices are installed on the roof of each car, and the 15 collection devices are
arranged in a array.

4. The method for guiding passengers in a subway car according to claim 1, wherein the
specific process of converting the passenger distribution for each car during the sampling
20 period into a binary image is as follows:

dividing each car into W equal parts along the x -axis of the spatial coordinate system of the
car, and dividing each car into L equal parts along the y -axis of the spatial coordinate system
of the car, to convert the space of each car into $W \times L$ independent units;
setting each independent unit as a pixel, the number of passengers in each independent unit

being a pixel value of the pixel; and

obtaining pixel values of all pixels, and converting the passenger distribution into the binary image composed of $W \times L$ pixels.

5 5. The method for guiding passengers in a subway car according to claim 4, wherein L is 3, W is 10.

6. The method for guiding passengers in a subway car according to claim 1, wherein formulas for calculating the amplitude and the gradient direction of the pixel are respectively:

$$G(l, w) = \sqrt{G_x(l, w)^2 + G_y(l, w)^2}, \quad \theta(l, w) = \arctan \frac{G_y(l, w)}{G_x(l, w)}$$

10 $G_x(l, w) = I(l+1, w) - I(l-1, w), \quad G_y(l, w) = I(l, w+1) - I(l, w-1)$

where, $G(l, w)$ is the amplitude of the pixel, $\theta(l, w)$ is the gradient direction of the pixel, $G_x(l, w)$ is the gradient amplitude of the pixel along the x -axis of the spatial coordinate system, $G_y(l, w)$ is the gradient amplitude of the pixel along the y -axis of the spatial coordinate system, $I(l+1, w)$ is the pixel value of the pixel in row $l+1$ and column w , $I(l-1, w)$ is the pixel value of the pixel in row $l-1$ and column w , $l=1, 2, 3 \dots L$, $w=1, 2, 3 \dots W$, W is a number of equal parts divided from the car along the x -axis of the spatial coordinate system of each car, and L is a number of equal parts divided from the car along the y -axis of the spatial coordinate system of each car.

20 7. The method for guiding passengers in a subway car according to claim 1, wherein the clustering algorithm is an OPTICS algorithm, the initial neighborhood distance parameter ε of the OPTICS algorithm is 0.2, and the initial neighborhood sample parameter $MinPts$ is 3.

8. The method for guiding passengers in a subway car according to claim 1, wherein the distribution prediction model is any one of a support vector machine model, a relevance

vector machine model or a neural network model.

9. The method for guiding passengers in a subway car according to claim 1, wherein the temperature time series, the humidity time series, and the CO₂ concentration time series in the training samples are replaced with a temperature time series feature vector, a humidity
5 time series feature vector, and a CO₂ concentration time series feature vector, respectively, wherein the temperature time series feature vector, the humidity time series feature vector, and the CO₂ concentration time series feature vector are obtained as follows:

establishing a temperature time series LSTM neural network model, and randomly dividing the temperature time series in the training samples into two temperature training sets,
10 wherein one of the temperature training sets and the passenger distribution code corresponding to the temperature training set constitute a first training set, and the other temperature training set is a second training set; training the temperature time series LSTM neural network model with the first training set to obtain a trained temperature time series LSTM neural network model; removing a classification layer of the trained temperature
15 time series LSTM neural network model, and obtaining the temperature time series feature vector with the second training set as input and a vector outputted by a fully connected layer as output;

establishing a humidity time series LSTM neural network model, and randomly dividing the humidity time series in the training samples into two humidity training sets, wherein
20 one of the humidity training sets and the passenger distribution code corresponding to the humidity training set constitute a third training set, and the other humidity training set is a fourth training set; training the humidity time series LSTM neural network model with the third training set to obtain a trained humidity time series LSTM neural network model; removing a classification layer of the trained humidity time series LSTM neural network
25 model, and obtaining the humidity time series feature vector with the fourth training set as

input and a vector outputted by a fully connected layer as output; and
establishing a CO₂ concentration time series LSTM neural network model, and randomly
dividing the CO₂ concentration time series in the training samples into two CO₂
concentration training sets, wherein one of the CO₂ concentration training sets and the
5 passenger distribution code corresponding to the CO₂ concentration training set constitute
a fifth training set, and the other CO₂ concentration training set is a sixth training set;
training the CO₂ concentration time series LSTM neural network model with the fifth
training set to obtain a trained CO₂ concentration time series LSTM neural network model;
removing a classification layer of the trained CO₂ concentration time series LSTM neural
10 network model, and obtaining the CO₂ concentration time series feature vector with the
sixth training set as input and a vector outputted by a fully connected layer as output.

10. The method for guiding passengers in the subway car according to claim 9, wherein the
temperature time series, the humidity time series, and the CO₂ concentration time series in
the environmental data samples are replaced with a temperature time series feature vector,
15 a humidity time series feature vector, and a CO₂ concentration time series feature vector,
respectively, wherein the temperature time series feature vector, the humidity time series
feature vector, and the CO₂ concentration time series feature vector are obtained as follows:
inputting the temperature time series into the trained temperature time series LSTM neural
network model with the classification layer removed, the vector outputted by the fully
20 connected layer being the corresponding temperature time series feature vector;
inputting the humidity time series into the trained humidity time series LSTM neural
network model with the classification layer removed, the vector outputted by the fully
connected layer being the corresponding humidity time series feature vector; and
inputting the CO₂ concentration time series into the trained CO₂ concentration time series
25 LSTM neural network model with the classification layer removed, the vector outputted by

the fully connected layer being the corresponding CO₂ concentration time series feature vector.

11. The method for guiding passengers in the subway car according to claim 1, wherein the pixel threshold is 15.

5 12. The method for guiding passengers in the subway car based on environmental monitoring and lighting guidance, comprising a plurality of guiding subsystems, each car corresponding to a guiding subsystem, wherein each guiding subsystem comprises a plurality of collection devices arranged on the roof of the car, a plurality of lighting tubes and a control device; the collection device comprises temperature sensors and a CO₂
10 concentration sensor;

the control device comprises:

a coordinate system establishment unit, configured to establish a spatial coordinate system of each car, and obtain installation coordinates of each sample collection point in the corresponding spatial coordinate system, each collection device serving as a sample
15 collection point; The spatial coordinate system is a two-dimensional rectangular coordinate system parallel to the roof or the ground, or the spatial coordinate system is a two-dimensional rectangular coordinate system coincident with the roof or the ground.

an environmental data obtaining unit, configured to obtain a temperature time series, a humidity time series, and a CO₂ concentration time series at each sample collection point
20 of each car during a sampling period, and obtain an average temperature value and an average humidity value locally of the day, wherein the installation coordinates of each sample collection point, the temperature time series, the humidity time series, and the CO₂ concentration time series corresponding to the sample collection point, and the average temperature value and the average humidity value constitute an environmental data sample
25 at each sample collection point of each car during the sampling period;

a passenger distribution obtaining unit, configured to obtain coordinates of passengers in the corresponding spatial coordinate system according to a recorded passenger positions in each car at the end time of the sampling period, i.e. obtain a passenger distribution for each car during the sampling period;

5 an image conversion and feature extraction unit, configured to convert the passenger distribution for each car during the sampling period into a binary image, and calculate a mean value, a variance, a maximum value and a minimum value of pixels in the binary image; calculate an amplitude and a gradient direction of each pixel in the binary image, and establish a frequency distribution histogram with the gradient direction of all pixels as

10 the abscissa axis and the pixel value corresponding to each pixel as the ordinate axis; and extract a frequency distribution feature of the frequency distribution histogram, the frequency distribution feature referring to a feature vector constituted by pixel values corresponding to each interval among R intervals equally divided from the abscissa axis of the frequency distribution histogram;

15 a clustering classification unit, configured to combine the mean value, the maximum value, the minimum value, the variance and the frequency distribution feature of the pixels to form an original feature vector, and cluster the binary images with the original feature vector as input of a clustering algorithm to obtain image clustering results;

a coding unit, configured to code the passenger distribution mode according to the image

20 clustering results to obtain a passenger distribution code, each category of image clustering result corresponding to a passenger distribution mode, and each passenger distribution mode corresponding to a passenger distribution code; and

a model training unit, configured to establish a distribution prediction model for each car, and train the distribution prediction model with training samples to obtain a trained

25 distribution prediction model, the training sample taking the environmental data sample of

each sample collection point of the car during the sampling period as input and the corresponding passenger distribution code as output.

a prediction unit, the new environmental data samples obtained in real time at each sample collection point of each car during each sampling period are inputted into the trained
5 distribution prediction model for the corresponding car to obtain a predicted passenger distribution code for each car during the corresponding sampling period; and

an adjustment and guidance unit, configured to adjust the brightness of lighting tubes in the corresponding car according to the predicted passenger distribution code for the car during the corresponding sampling period to guide passenger flow. The specific process is as

10 follows:

obtaining a current image clustering result according to the predicted passenger distribution code for the car during the corresponding sampling period, and determining a clustering center corresponding to the current image according to the current image clustering result; defining S binary images closest to the clustering center as typical clustering images of a
15 corresponding category, and calculating an average pixel value of each pixel position in the S typical clustering images, to obtain an average pixel image under the category;

assigning each lighting tube to a lighting area according to the layout of lighting tubes in the corresponding car, and calculating an average value of pixel values for pixels in the lighting area corresponding to each lighting tube;

20 if the maximum pixel value in the average pixel image is greater than a pixel threshold, starting lighting guidance and performing next step, otherwise skipping lighting guidance; extracting pixels in the average pixel image whose average pixel values are greater than the pixel threshold, the pixels greater than the pixel threshold constituting a set of pixels to be guided;

25 calculating a lighting guidance coefficient according to the coordinates of the lighting tubes

in the spatial coordinate system, the coordinates of pixels in the set of pixels to be guided in the spatial coordinate system, and the average value of pixel values for the pixels in the lighting area, wherein the specific calculation expression is:

$$\beta_n = A_n \left(\sqrt{(x_0^n - x_1^l)^2 + (y_0^n - y_1^w)^2} + \sqrt{(x_0^n - x_2^l)^2 + (y_0^n - y_2^w)^2} + \dots \right. \\ \left. \dots + \sqrt{(x_0^n - x_H^l)^2 + (y_0^n - y_H^w)^2} \right)$$

- 5 where, β_n is the lighting guidance coefficient, A_n is the average value of pixel values for pixels in the lighting area corresponding to the n^{th} lighting tube, (x_0^n, y_0^n) is the coordinates of the n^{th} lighting tube in the spatial coordinate system, (x_1^l, y_1^w) is the coordinates of the first pixel in the set of pixels to be guided in the spatial coordinate system, (x_2^l, y_2^w) is the coordinates of the second pixel in the set of pixels to be guided in the
- 10 spatial coordinate system, (x_H^l, y_H^w) is the coordinates of the H^{th} pixel in the set of pixels to be guided in the spatial coordinate system, and H is the number of pixels in the set of pixels to be guided;
- adjusting the brightness of the lighting tubes in the lighting areas corresponding to the β_n values according to the order of the β_n values, and guiding passengers to flow toward the
- 15 lighting area with a smaller β_n value.