

PATENT SPECIFICATION

(11)

1 500 834

1 500 834

- (21) Application No. 1564/76 (22) Filed 15 Jan. 1976
(31) Convention Application No.
7 502 075 (32) Filed 23 Jan. 1975 in
(33) France (FR)
(44) Complete Specification published 15 Feb. 1978
(51) INT. CL.² F04B 47/02
(52) Index at acceptance
F1A 1A4 1B5 1C2 4H

(19)



19

(54) PUMPING DEVICE FOR WELLS

(71) We, CENTRE D'ETUDES ET DE REALISATIONS INDUSTRIELLES DE L'ATLANTIQUE (CERIA) of 1 and 3 rue Marcel Sembat, 44049 Nantes Loire Atlantique, France, a body corporate organized under the laws of France, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

The invention concerns a pumping device for wells, e.g. oil wells, comprising a framework or rig and machinery capable of imparting, by the intermediation of a flexible connection, a reciprocating rising and falling movement to a set of rods or links whereby to actuate a force pump immersed in the well.

Pumping devices of this kind are known, e.g. from German Patent Specification No. 814 432 and U.S. Patent Specification No. 1 839 355, wherein the framework has, for the connection to the set of rods, at least one guide pulley with a horizontal axis of rotation carried on an arm for pivoting on the framework about a vertical axis.

However, these devices consist of lattice frameworks. In order to give the necessary strength to such frameworks, they must be fairly large and they thus occupy a relatively large surface area. Moreover, they are expensive to maintain, especially in a marine environment, and in use it is difficult to release the head of the well for servicing work. In addition, lattice frameworks do not permit a large pivotal angle to be achieved by the pivoting arm.

An aim of the invention is to propose a new type of pumping device of minimum ground or marine platform space requirement and which permits the complete disengagement in height of the servicing shaft of the well without complicated or costly operations and without displacement

of material on the ground or on the platform.

According to the present invention, there is provided pumping apparatus for a well, comprising a framework, a driving plant, a rod linkage connectable to a force pump immersed in the well, a flexible connection between the said plant and the said rod linkage for transmitting and imparting a reciprocating lifting and lowering movement to the rod linkage to actuate the force pump, wherein the framework supports for the flexible connection to the rod linkage, at least one guide pulley having a horizontal axis of rotation as well as an arm for carrying said at least one guide pulley and which arm is mounted for pivoting on the framework about a vertical axis, the framework being constituted by a tubular mast.

According to a preferred feature, the arm mounted on the framework for pivoting about a vertical axis is pivotable between at least two positions angularly spaced by about 90° from each other.

Preferably, for counterbalancing the forces exerted on the flexible connection, two wells are coupled or twinned and each is served by a respective tubular mast so that counterbalancing is achieved by the coupling or twinning of the two pumps each immersed in its own well. It is then advantageous for the two tubular masts to be integrally joined together by a connecting means on the same base.

According to a variant, counterbalancing is achieved by a counterweight device accommodated in the tubular mast which serves as a guide therefor and which at its head carries a second guide pulley and a second flexible connection being guided by said second guide pulley and carrying the counterweight.

Expediently, the tubular mast includes a central guide rod fixed at the top and at 90

20

the bottom of the mast and the counterweight device includes a safety device.

According to one embodiment, the horizontal axes of the guide pulleys carried by the pivotally mounted arms are carried on vertical axes and are adjustable in angular position on the pivoting arms.

Other characteristics and advantages will become clear from the description of preferred embodiments given hereafter, merely by way of example, with reference to the attached drawings.

Figures 1 and 2 show in vertical elevation, partially broken away, two mutually orthogonal views from the front and from the left of the pumping apparatus according to the invention with counterweight counterbalancing means.

Figure 3 shows in plan the apparatus of Figures 1 and 2, the respective viewing directions of Figures 1 and 2 being shown at I and II.

Figures 4 and 5 respectively show on a larger scale the main parts of Figures 1 and 3, respectively as a rear view and a plan view after removal of the upper part of the mast.

Figures 6 and 7 show, analogously to Figures 1 and 3, a variant including a counterbalancing arrangement by coupling two pumps immersed in two wells; and

Figure 8 is a side view of a variant of the device of Figures 4 and 5.

The first preferred embodiment of the apparatus according to the invention is shown in Figures 1 to 5. It consists of machinery or a plant 10 for actuating a winch 11 and a tubular mast 20 preferably connected to the machinery on the same pedestal or base 1. The tubular mast 20 carries two pairs of guide pulleys with horizontal axes of rotation, namely a lateral pair 21 for guiding a double cable 22 between the winch 11 and the non-illustrated set of rods or linkage, and an upper pair 23 for the guidance of a double cable 24 between the winch 11 and a counterweight 25 accommodated in the tubular mast 20.

The counterweight 25 includes interchangeable weights 26 to allow its weight to be adjusted, e.g. to the sum of the weight of the linkage and of one-half of the column of the liquid pumped.

The plant 10 actuating the winch 11 includes the following components which are not shown in detail: a hydraulic motor for actuating the winch, a variable-output pump for feeding this motor with hydraulic liquid (oil) and delivering an output of oil proportional to the opening angle of its control lever, in one direction or in the opposite direction according to whether this lever is to the one or to the other side of its zero position of no output; an electric

motor for driving this pump, as well as a regulating flywheel for smoothing the peaks of intensity at the reversals of the direction of movement; a mechanism for reversing the direction of movement adapted to rock the control lever of the pump from one position to another symmetrically in relation to the zero point; an oil tank and an oil cooler; all the ancillary devices that are indispensable to the satisfactory operation and to the reliability of the installation, and a casing 12 enclosing all the components in a compact fashion.

The drum of the winch 11 carries the two cables 22 for the rod linkage and the two cables 24 for the counterweight 25. The doubling-up of the cables has the aim of ensuring their maximum service life. The drum of the winch 11 also allows the links of the linkage to be removed from the well.

The tubular mast 20 includes a central guide rod 27 fixed to the mast at the top and on the pedestal or base 1. The counterweight includes, in addition to the interchangeable weights 26, resilient suspension studs 18 for demounting.

The guide pulleys 23 for the suspension cables of the counterweight 25 are so mounted at the top of the mast that the strands 24 of these cables descend parallel to the guide rod 27.

As to the pulleys 21, they are carried at the end of a support arm or jib 28 pivotally mounted on the mast 20 at its upper part. The jib 28 includes an arm 29 and a bracket 30.

It is mounted for pivoting about a vertical axle 31 of a support 32 fixed to the mast 20. The arm 29 includes a crank 29' having a vertical slot 29'' serving to immobilize the arm in two places determined by vertical slots 32' and 32'' of the support 32. The two strands 22 are connected to the linkage by way of a rocking lever, as known per se.

According to a variant shown in Figure 8, the arm 29 and the bracket 30 are not connected to the axle of the pulleys 21 but are interconnected by a vertical spindle 33 around which the horizontal axle 21' of the pulleys 21 can swivel about a vertical axis in such a manner as to ensure a finer centering of the cables 22 on the axis of the linkage, i.e. to ensure that the cables pull more closely along this axis. The attachment points of the vertical spindle 33 to the arm and the bracket are then transferred to the outside of the height of the pulleys to permit optimal positioning of the latter.

In the embodiment described hitherto, it will be appreciated that the assembly constituted by the jib 28 and the pulleys 21 carried thereby may be locked either in its

pumping position represented in full lines in Figure 5, wherein the cables 22 fall appreciably to the right of the centre of the shaft 2 of the well to be cleared, or in its retracted position represented in broken lines in Figure 5, wherein the shaft 2 is wholly cleared in a vertical direction of all obstruction.

All the mechanical parts may be at ground level or at the level of the work floor where there is easy and complete access to the controls or dials. The circular shape and small diameter of the mast permits the pivoting assembly constituted by the jib, the pulleys and the crank of the jib to have a large angle of rotation, which facilitates servicing and maintenance of the well since a large zone thereof can be freed.

In addition it will be seen that the total ground space requirement is much reduced, the strength of a tubular structure allowing its size to be greatly decreased in comparison with lattice structures. This advantage is very important for marine production platforms where provision of the floor area is costly.

Of course, the height of the mast 20 and the length of the cable made fast on the winch are such as to ensure the required vertical stroke for the pump and that the linkage can be raised by the winch, at least link by link.

According to the variant shown in Figures 6 and 7 two pumps are each actuated, one in a respective well, by means of a respective linkage.

A sole base or pedestal 1 carries a single plant 10 and a single winch, the cables 22 being made fast on this winch and being directed to each of the linkages by means of pulleys 21 carried on two tubular masts 20 fixedly mounted on the base 1 and connected by a cross-bar 20'. This arrangement is favourable where the delivery and load of the two wells are generally balanced. The construction of the masts is the same as in the first embodiment described above except that these masts do not have counterweight balancing devices.

WHAT WE CLAIM IS:—

1. Pumping apparatus for a well comprising a framework, a driving plant, a rod linkage connectable to a force pump immersed in the well, a flexible connection between the said plant and the said rod linkage for transmitting and imparting a reciprocating lifting and lowering movement to the rod linkage to actuate the force pump, wherein the framework supports, for

the flexible connection to the rod linkage, at least one guide pulley having a horizontal axis of rotation as well as an arm for carrying said at least one guide pulley and which arm is mounted for pivoting on the framework about a vertical axis, the framework being constituted by a tubular mast.

2. Pumping apparatus according to claim 1 wherein locking means are provided for locking the said arm in either of at least two angularly spaced apart positions.

3. Pumping apparatus according to claim 1 or claim 2 wherein there are means for counterbalancing the forces exerted on the flexible connection constituted by the coupling together of two wells, each served by a respective tubular mast.

4. Pumping apparatus according to claim 3, wherein a connecting member integrally connects the two tubular masts on the same base.

5. Pumping apparatus according to claim 1 or claim 2, further including means for counterbalancing the forces exerted on the flexible connection, the counterbalancing means being in the form of a counterweight device accommodated in the tubular mast which latter serves to guide it and which has at its top a second guide pulley, and a second flexible connection being guided by said second guide pulley and carrying the counterweight device.

6. Pumping apparatus according to claim 5, wherein the tubular mast includes a central guide rod fixed at the top and bottom of the mast and the counterweight device includes a safety device.

7. Pumping apparatus according to any preceding claim, wherein means are provided for adjusting the angular position of the said at least one guide pulley carried by the pivotable arm, the horizontal axle of the said at least one pulley being mounted on a vertical spindle.

8. Pumping apparatus substantially as herein described with reference to and as shown in Figures 1 to 5, 6 and 7, or 8 of the accompanying drawings.

T. Z. GOLD & COMPANY,
Agents for the Applicants,
Chartered Patent Agents,
Staple Inn Buildings North,
High Holborn,
London WC1V 7QB.
— and —
2 Fawley Road,
London NW6 1SH.



21
3

1 500 834

3
pumping position represented in full lines in Figure 5, wherein the cables 22 fall appreciably to the right of the centre of the shaft 2 of the well to be cleared, or in its retracted position represented in broken lines in Figure 5, wherein the shaft 2 is wholly cleared in a vertical direction of all obstruction.

10 All the mechanical parts may be at ground level or at the level of the work floor where there is easy and complete access to the controls or dials. The circular shape and small diameter of the mast permits the pivoting assembly constituted by the jib, the pulleys and the crank of the jib to have a large angle of rotation, which facilitates servicing and maintenance of the well since a large zone thereof can be freed.

20 In addition it will be seen that the total ground space requirement is much reduced, the strength of a tubular structure allowing its size to be greatly decreased in comparison with lattice structures. This advantage is very important for marine production platforms where provision of the floor area is costly.

Of course, the height of the mast 20 and the length of the cable made fast on the winch are such as to ensure the required vertical stroke for the pump and that the linkage can be raised by the winch, at least link by link.

According to the variant shown in Figures 6 and 7 two pumps are each actuated, one in a respective well, by means of a respective linkage.

A sole base or pedestal 1 carries a single plant 10 and a single winch, the cables 22 being made fast on this winch and being directed to each of the linkages by means of pulleys 21 carried on two tubular masts 20 fixedly mounted on the base 1 and connected by a cross-bar 20'. This arrangement is favourable where the delivery and load of the two wells are generally balanced. The construction of the masts is the same as in the first embodiment described above except that these masts do not have counterweight balancing devices.

WHAT WE CLAIM IS:—

1. Pumping apparatus for a well comprising a framework, a driving plant, a rod linkage connectable to a force pump immersed in the well, a flexible connection between the said plant and the said rod linkage for transmitting and imparting a reciprocating lifting and lowering movement to the rod linkage to actuate the force pump, wherein the framework supports, for

the flexible connection to the rod linkage, at least one guide pulley having a horizontal axis of rotation as well as an arm for carrying said at least one guide pulley and which arm is mounted for pivoting on the framework about a vertical axis, the framework being constituted by a tubular mast.

2. Pumping apparatus according to claim 1 wherein locking means are provided for locking the said arm in either of at least two angularly spaced apart positions.

3. Pumping apparatus according to claim 1 or claim 2 wherein there are means for counterbalancing the forces exerted on the flexible connection constituted by the coupling together of two wells, each served by a respective tubular mast.

4. Pumping apparatus according to claim 3, wherein a connecting member integrally connects the two tubular masts on the same base.

5. Pumping apparatus according to claim 1 or claim 2, further including means for counterbalancing the forces exerted on the flexible connection, the counterbalancing means being in the form of a counterweight device accommodated in the tubular mast which latter serves to guide it and which has at its top a second guide pulley, and a second flexible connection being guided by said second guide pulley and carrying the counterweight device.

6. Pumping apparatus according to claim 5, wherein the tubular mast includes a central guide rod fixed at the top and bottom of the mast and the counterweight device includes a safety device.

7. Pumping apparatus according to any preceding claim, wherein means are provided for adjusting the angular position of the said at least one guide pulley carried by the pivotable arm, the horizontal axle of the said at least one pulley being mounted on a vertical spindle.

8. Pumping apparatus substantially as herein described with reference to and as shown in Figures 1 to 5, 6 and 7, or 8 of the accompanying drawings.

T. Z. GOLD & COMPANY,
Agents for the Applicants,
Chartered Patent Agents,
Staple Inn Buildings North,
High Holborn,
London WC1V 7QB.
— and —
2 Fawley Road,
London NW6 1SH.