

AN ANTI-ROTATION STRUCTURE, A TUBE STRUCTURE AND A PHOTOGRAPHIC SUPPORT

TECHNICAL FIELD

[0001] The present invention may generally relate to photographic support field, and may more specifically relate to an anti-rotation structure, tube structure, and photographic support.

BACKGROUND

[0002] Tripods are essential for taking photographs, especially in the process of taking long exposure shots, such as sky-gazing, water falls or streams, night shots, close-ups, etc. The need for tripods therefore is not confined just to professionals; amateurs or novices would appreciate the benefit of tripods. One of the main functions of a tripod is to secure a still-image camera, a video camera, or an imaging capturing device to produce images with desirable effects on the resulting image.

[0003] A typical tripod includes a central platform rotatably connected to three legs or supports peripherally connected to the platform. The image capturing device is connected to the central platform and with varying heights permitted in the legs or supports, a user may raise or lower the height of the image capturing device. In existing tripods, each of the legs or supports includes a set of tubes arranged in a telescopic fashion to increase or decrease the length of the legs or supports. For example, each leg or support includes a first tube connecting to the platform on one end and connecting with a second tube on the other end. The second tube would connect with a third tube and so on. A knob is typically placed

about the connection between the first tube and the second tube (or the second tube and the third tube, and so on) so that a user may tighten or loosen to enable the second tube to extend or retract from the other end of the first tube. A user may similar tighten or loosen another nob to extend or retract the third tube from the other end of the second tube. As the tubes are arranged in a nested arrangement, the diameter of the first tube is slightly larger than that of the second tube while the diameter of the second tube is slightly larger than that of the third tube, and so on.

[0004] Due to this arrangement, it is known that, in the process of loosening one of the nobs and in extending the length of a leg or support, the user may apply too much force in the process (either to the nob or on the tube or leg), resulting in separating the second tube from the first tube. This separation causes the end of the second tube being exposed. This significantly and negatively affect the use of the tripod, especially when the user has positioned the image capturing device to capture images and missing a leg stably supporting the image capturing device

SUMMARY

[0005] Embodiments of the invention resolve and overcome the shortcomings of the prior technology by provide a cap to the inner tube, such as the second tube, such that the cap may enable easy re-insertion of the second tube into the first tube.

[0006] In one embodiment, a first tube with its distal end may include in its interior surface at least one rib or slot axially or longitudinally disposed thereon. A second tube, fitted to the first tube, may include on its exterior surface a

corresponding groove or notch to receive or accommodate the at least one rib or slot of the first tube. When the first tube and the second tube are moving with respect to each other, the at least one rib or slot of the first tube moves along the corresponding groove or notch of the second tube.

[0007] In one embodiment, the second tube includes a cap where the cap may prevent or avoid rotation (e.g., anti-rotation). In this example, the cap may include the corresponding groove or notch.

[0008] In one embodiment, the cap structure may be disposed on the distal end of the second tube.

[0009] In one embodiment, a part or portion of the second tube may match to a portion or part of the cap structure via a set of an opening on the second tube and a protrusion on the cap structure.

[0010] In one embodiment, a part or portion of the second tube may match to a portion or part of the cap structure via a set of a protrusion on the second tube and an opening on the cap structure.

[0011] In one embodiment, the first tube may include a tightening element. The tightening element may tighten the first tube to the second tube.

[0012] In another embodiment, the tightening element may include an inner adapter having a cone shape. The inner adapter may be fitted onto the exterior surface of the first tube. In another embodiment, the inner adapter includes threads on its exterior surface. In this example, the tightening element may also include an outer adapter. The outer adapter with threads on its interior surface and may connect to the inner adapter through the threads.

[0013] In another embodiment, the tightening element may include a locking ring disposed on the outer adapter. In one example, the locking ring may halt or stop movement of the cap away from or out of the second tube when the cap moves to the locking ring.

[0014] Another embodiment of the invention may provide a tube structure having at least two sets of caps arranged therewith. In this example of the at least two sets of caps, one set of the caps may include its second tube to be fitted or sleeved to a first tube of another set of the caps.

[0015] Aspects of the invention also provide a photographic support with at least one tube having the tub structure as described above.

[0016] Moreover, embodiments of the invention provide one or more following advantages:

[0017] 1. The cap structure provided in one embodiment of the invention include: a first tube with its distal end may include in its interior surface at least one rib or slot axially or longitudinally disposed thereon. A second tube, fitted to the first tube, may include on its exterior surface a corresponding groove or notch to receive or accommodate the at least one rib or slot of the first tube. When the first tube and the second tube are moving with respect to each other, the at least one rib or slot of the first tube moves along the corresponding groove or notch of the second tube. In existing approach, when the first tube and the second tube are moving against each other, due to the forces that are applied, the tubes tend to rotate in directions that are opposite to one another.

[0018] According to aspects of the invention, when the first tube is moving relative to the second tube, the groove or notch limits or defines movement of the rib or slot therewithin. By defining or limiting the movement, the movements between the first tube and the second tube may be more defined or limited to a linear movement.

[0019] 2. Aspects of the invention provide the cap disposed in the distal end of the first tube, and the cap may include rib or slot disposed thereon. When the rib or slot may be damaged from use, a user may quickly and conveniently replace the cap such that the first tube and the second tube may resume operation without issues.

[0020] 3. In one embodiment, a part or portion of the first tube may match a part or portion of the cap structure via a set of an opening on the first tube and a protrusion on the cap structure. Through the opening/hole and the corresponding protrusion, embodiments of the invention may maintain stability of the connection.

[0021] 4. In another embodiment, a tightening element may include an inner adapter having a substantially cone shape, with a narrower circumference facing toward the first tube. The inner adapter may be fitted onto the exterior surface of the first tube. In another embodiment, the inner adapter includes threads on its exterior surface. In this example, the tightening element may also include an outer adapter. The outer adapter with threads on its interior surface and may connect to the inner adapter through the threads.

[0022] In one operation, when a user wishes loosen the connection between the first tube and the second tube, the user may rotate the outer adapter. Due to the substantially cone shape of the inner adapter, when the outer adapter may move away from the inner adapter along the threads, the tightening force applied on the inner adapter decreases as the outer adapter moves away from the narrower circumference end of the inner adapter for easier loosening.

[0023] 5. In another embodiment, the tightening element may include a locking ring disposed on the outer adapter. In one example, the locking ring may halt or stop movement of the cap away from or out of the second tube when the cap moves to the locking ring.

[0024] In one example, when the first tube and the second tube may be separating completely away from one another in a situation where the cap may be moving to a position of the locking ring, as the locking ring may be stationary or fixed on the second tube, the locking ring may block or inhibit that separation of the cap.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] In order to more clearly illustrate embodiments of the invention, the following figures provide exemplary but simplified illustrations. The following figures further illustrate exemplary embodiments, so to those skilled in the art without undue experimentation may appreciate other figures of aspects of the invention based on these figures.

[0026] FIG. 1 is a perspective view of an embodiment of a cap of a tripod leg or support as used with the tripod leg or support according to one embodiment of the invention.

[0027] FIG. 2 is a perspective view an embodiment of a cap of a tripod leg or support as used with a second tube of the tripod leg or support according to one embodiment of the invention.

[0028] FIG. 3 is a perspective view another embodiment of a cap of a tripod leg or support as used with a second tube of the tripod leg or support according to one embodiment of the invention.

[0029] Identification of the reference numbers in the figures:

[0030] 1 – a first tube; 11 – a first rib; 2 – a second tube; 21 – a second groove; 5 – a cap structure; 6 – an opening; 7 – a protrusion; 8 – a tightening element; 81 – an inner adapter; 82 – an outer adapter; 83 – a locking ring; 84 – an outer sleeve.

DETAILED DESCRIPTION

[0031] A clear and complete description of the technical schemes of the present application is given below, in conjunction with the accompanying drawings.

Apparently, the described embodiments are a part, but not all, of the embodiments of the present application. All the other embodiments, derived by a person skilled in the art on the basis of the embodiments described in the present application without undue experimentation or labor, are included in the protection scope of the present application.

[0032] In the description of the present application, it needs to be noted that, unless specifically defined or restricted otherwise, terms such as “center,” “up,”

“down,” “left,” right,” “vertical,” “horizontal,” “inner,” “outer,” etc., that denote directional or positional relationship may be directional or positional relationship as referenced in the figures. They are merely used for description and illustration purposes and do not instruct or imply that a device or element must possess the specific direction or a specific directional structure and operation. As such, they are not meant to be limiting. Moreover, terms such as “first,” “second,” or “third,” are merely for description purposes and should not be interpreted to instruct or imply a degree of importance.

[0033] In the description of the present application, it is to be noted that, unless specifically defined or restricted otherwise, terms such as “mount”, “interconnect”, “connect” should be broadly construed, for example, they may be fixed connection or detachable connection or integral connection; they may be mechanical connection or electrical connection; they may be direct connection, or indirect connection via an intermediate medium, or internal communication between two units; they may be wireless connection, or wired connection. For a person skilled in the art, the specific meaning of the aforementioned terms in the present application can be understood according to specific situations thereof.

[0034] Furthermore, the technical features involved in the various embodiments of the present application described below can be combined with one another as long as they do not conflict with one another.

[0035] Embodiment 1

[0036] According to an anti-rotation structure, as shown in FIG. 1, a first tube 1, with its distal end may include in its interior surface at least one rib 11 axially or

longitudinally disposed thereon. A second tube 2 may be fitted to or sleeved over the first tube 1. The second tube 2 may, on its exterior or outer tube surface, form a corresponding groove 21 to the at least one rib 11. As the first tube 1 correspondingly move with respect to the second tube 2, the at least one rib 1 may define a movement along the groove 21.

[0037] In another embodiment, the use of the at least one rib 1 and the groove 21 may be exchanged. For example, in one embodiment, the first tube 1 may, instead of the at least one rib 1, include a groove whereas the second tube 2 may include a corresponding at least one rib for the groove.

[0038] In existing art, when the first tube and the second tube are moving against one another, due to the forces applied, the first tube and the second tube may be rotated.

[0039] In the present embodiment, when the first tube 1 is moving relative to the second tube 2, the groove 21 may limit or define movement of the rib 1. By defining or limiting the movement, the movements between the first tube 1 and the second tube 2 may be more defined or limited to a linear movement.

[0040] In embodiments as illustrated in FIG. 2, the second tube 2 includes a cap structure 5 on a distal end of the second tube 2. The rib or the groove is disposed on the cap structure 5.

[0041] Through the cap structure 5, when the rib or the groove may be damaged from use, the cap structure 5 may quickly and conveniently replaced without interfering the use of the tubes, which may be part of a photographic support, such as a tripod or monopod.

[0042] In a further embodiment, the cap structure 5 may be sleeved or fitted to the second tube 2. A portion or part of the first tube 1 may match to a portion or part of the cap structure 5 by a set of an opening 6 on the first tube 1 and a protrusion 7 on the cap structure 5. This may ensure the stability of connection between the first tube 1 and the cap structure 5.

[0043] In another embodiment, a portion or part of the second tube 2 may match to a portion or part of the cap structure 5 by a set of a protrusion 7 on the first tube 2 and an opening 6 on the cap structure 5.

[0044] According to an embodiment as shown in FIG. 3, the first tube 1 may be mounted or fitted with a tightening element 8. The use may use tightening element 8 to tighten or decrease movement when the first tube 1 is connected to the second tube 2.

[0045] In a further embodiment, the tightening element 8 may include an inner adapter 81 having a substantially cone shape disposed on the exterior or outer surface of the first tube 1. The inner adapter 81 may include threads on its outer or exterior surface. The tightening element 8 may also include an outer adapter 82 and the outer adapter 82 may be connected to the inner adapter 81 via the threads. An outer sleeve 84 disposed on the exterior of the outer adapter 82 may enhance comfort in its use.

[0046] When loosening the connection between the first tube 1 and the second tube 2, a user may rotate or turn the outer adapter 82. Due to the substantially cone shape of the inner adapter 81, as the outer adapter 82 moves away or

separates from the inner adapter 81, forces applied on the inner adapter 81 decreases, which may be beneficial for separating.

[0047] Similarly, the tightening element 8 further includes a locking ring 83 mounted or disposed on the outer adapter 82. When the cap structure 5 moves to a position of the locking ring 83, the locking ring 83 may prevent or inhibit the cap structure 5 separate from the second tube 2. When the first tube 1 and the second tube 2 appear to be separated from one another, the cap structure 5 disposed on the first tube 1 may move to the position of the locking ring 83. As the locking ring 83 may be affixed securely or be stationary on the second tube 2, the locking ring 83 may prevent or block the movement of the cap structure 5 to be separated.

[0048] In a further embodiment, the inner adapter 81 may be affixed to a bottom end of the second tube via adhesives, and the locking ring 83 may be secured on the inner adapter 81.

[0049] Embodiment 2

[0050] Another embodiment of the invention provides a tube structure, where the tube structure may provide at least two sets of the cap structure 5 as described in Embodiment 1. The second tube of one set may connect on the exterior to the first tube of another set.

[0051] Embodiment 3

[0052] Embodiment of the invention provide a photographic support with at least one leg of the support include the tube structure of Embodiment 2.

[0053] Apparently, the aforementioned embodiments are merely examples illustrated for clearly describing the present application, rather than limiting the implementation ways thereof. For a person skilled in the art, various changes and modifications in other different forms can be made on the basis of the aforementioned description. It is unnecessary and impossible to exhaustively list all the implementation ways herein. However, any obvious changes or modifications derived from the aforementioned description are intended to be embraced within the protection scope of the present application.

CLAIMS

What is claimed is:

1. An anti-rotation structure, characterized

a first tube (1) including a first groove or a first rib (11) axially thereof;

a second tube (2) fitting to the first tube (1), wherein an exterior of the second tube (2) comprises a corresponding second rib or second groove (21) to the first groove or the first rib (11), when said first tube (1) moving relative to the second tube (2), the first rib (11) or the second rib moves along the corresponding second groove (21) or the first groove.

2. The anti-rotation structure of claim 1, characterized in that, a distal end of the second tube (2) includes an anti-rotation cap structure (5), wherein said first groove (21) or said second rib may be disposed on the anti-rotation cap structure (5).

3. The anti-rotation structure of claim 2, characterized in that, said anti-rotation cap structure (5) is disposed on the second tube (2).

4. The anti-rotation structure of claim 3, characterized in that, said second tube (2) matches to a part of the anti-rotation cap structure (5) with an opening (6) on the second tube (2), wherein the anti-rotation cap structure (5) includes a protrusion (7) matching the opening (6).

5. The anti-rotation structure of claim 3, characterized in that, said second tube (2) matches to a part of the anti-rotation cap structure (5) with a protrusion (7) on the second tube (2), wherein the anti-rotation cap structure (5) includes an opening matching the protrusion (7).

6. The anti-rotation structure of any one of the claims 2-5, characterized in that, said first tube (1) comprising a tightening element (8), said first tube (8) connecting to the second tube (2) via the tightening element (8).

7. The anti-rotation structure of claim 6, characterized in that, said tightening element (8) includes: an inner adapter (81), having a substantially cone shape and threads on its exterior surface, disposed on an exterior surface of the first tube (1); and an outer adapter (82) connecting to the inner adapter (81) via the threads of the inner adapter (81).

8. The anti-rotation structure of claim 7, characterized in that, said tightening element (8) includes a locking ring (83) disposed on the outer adapter (82), wherein the locking ring (83) prevents the anti-rotation cap structure (5) separating from the second tube (2) the anti-rotation cap structure (5) moves to the locking ring (83).

9. A support tube structure, characterized in that at least two sets of the anti-rotation structure of any one of the claims 1-8, the second tube (2) of one set connects to an exterior surface of the first tube (1) of the other set.

10. A photographic support, characterized in that, at least one supporting tube structure of claim 9.