WELLBORE APPARATUS AND METHODS FOR MULTI-ZONE WELL COMPLETION, PRODUCTION AND INJECTION

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 61/424,427, filed 17 December 2010 and U.S. Provisional Application No. 61/549,056, filed 19 October 2011.

BACKGROUND OF THE INVENTION

[0002] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

Field of the Invention

[0003] The present disclosure relates to the field of well completions. More specifically, the present invention relates to the isolation of formations in connection with wellbores that have been completed using gravel-packing. The application also relates to a downhole packer that may be set within either a cased hole or an open-hole wellbore and which incorporates alternate flow channel technology.

Discussion of Technology

[0004] In the drilling of oil and gas wells, a wellbore is formed using a drill bit that is urged downwardly at a lower end of a drill string. After drilling to a predetermined depth, the drill string and bit are removed and the wellbore is lined with a string of casing. An annular area is thus formed between the string of casing and the formation. A cementing operation is typically conducted in order to fill or "squeeze" the annular area with cement. The combination of cement and casing strengthens the wellbore and facilitates the isolation of the formation behind the casing.

[0005] It is common to place several strings of casing having progressively smaller outer diameters into the wellbore. The process of drilling and then cementing progressively smaller strings of casing is repeated several times until the well has reached total depth. The final string of casing, referred to as a production casing, is cemented in place and perforated. In some instances, the final string of casing is a liner, that is, a string of casing that is not tied back to the surface.

[0006] As part of the completion process, a wellhead is installed at the surface. The wellhead controls the flow of production fluids to the surface, or the injection of fluids into the wellbore. Fluid gathering and processing equipment such as pipes, valves and separators are also provided. Production operations may then commence.

[0007] It is sometimes desirable to leave the bottom portion of a wellbore open. In open-hole completions, a production casing is not extended through the producing zones and perforated; rather, the producing zones are left uncased, or "open." A production string or "tubing" is then positioned inside the wellbore extending down below the last string of casing and across a subsurface formation.

[0008] There are certain advantages to open-hole completions versus cased-hole completions. First, because open-hole completions have no perforation tunnels, formation fluids can converge on the wellbore radially 360 degrees. This has the benefit of eliminating the additional pressure drop associated with converging radial flow and then linear flow through particle-filled perforation tunnels. The reduced pressure drop associated with an open-hole completion virtually guarantees that it will be more productive than an unstimulated, cased hole in the same formation.

[0009] Second, open-hole techniques are oftentimes less expensive than cased hole completions. For example, the use of gravel packs eliminates the need for cementing, perforating, and post-perforation clean-up operations.

[0010] A common problem in open-hole completions is the immediate exposure of the wellbore to the surrounding formation. If the formation is unconsolidated or heavily sandy, the flow of production fluids into the wellbore may carry with it formation particles, e.g., sand and fines. Such particles can be erosive to production equipment downhole and to pipes, valves and separation equipment at the surface.

[0011] To control the invasion of sand and other particles, sand control devices may be employed. Sand control devices are usually installed downhole across formations to retain solid materials larger than a certain diameter while allowing fluids to be produced. A sand control device typically includes an elongated tubular body, known as a base pipe, having numerous slotted openings. The base pipe is then typically wrapped with a filtration medium such as a screen or wire mesh.

[0012] To augment sand control devices, particularly in open-hole completions, it is common to install a gravel pack. Gravel packing a well involves placing gravel or other particulate matter around the sand control device after the sand control device is hung or

otherwise placed in the wellbore. To install a gravel pack, a particulate material is delivered downhole by means of a carrier fluid. The carrier fluid with the gravel together forms a gravel slurry. The slurry dries in place, leaving a circumferential packing of gravel. The gravel not only aids in particle filtration but also helps maintain formation integrity.

[0013] In an open-hole gravel pack completion, the gravel is positioned between a sand screen that surrounds a perforated base pipe and a surrounding wall of the wellbore. During production, formation fluids flow from the subterranean formation, through the gravel, through the screen, and into the inner base pipe. The base pipe thus serves as a part of the production string.

[0014] A problem historically encountered with gravel-packing is that an inadvertent loss of carrier fluid from the slurry during the delivery process can result in premature sand or gravel bridges being formed at various locations along open-hole intervals. For example, in an inclined production interval or an interval having an enlarged or irregular borehole, a poor distribution of gravel may occur due to a premature loss of carrier fluid from the gravel slurry into the formation. Premature sand bridging can block the flow of gravel slurry, causing voids to form along the completion interval. Thus, a complete gravel-pack from bottom to top is not achieved, leaving the wellbore exposed to sand and fines infiltration.

[0015] The problems of sand bridging and of bypassing zonal isolation have been addressed through the use of Alternate Path® Technology, or "APT." Alternate Path® Technology employs shunt tubes (or shunts) that allow the gravel slurry to bypass selected areas along a wellbore. Such fluid bypass technology is described, for example, in U.S. Pat. No. 5,588,487 entitled "Tool for Blocking Axial Flow in Gravel-Packed Well Annulus," and PCT Publication No. WO2008/060479 entitled "Wellbore Method and Apparatus for Completion, Production, and Injection," each of which is incorporated herein by reference in its entirety. Additional references which discuss alternate flow channel technology include U.S. Pat. No. 4,945,991; U.S. Pat. No. 5,113,935; U.S. Pat. No. 7,661,476; and M.D. Barry, *et al.*, "Open-hole Gravel Packing with Zonal Isolation," SPE Paper No. 110,460 (November 2007).

[0016] The efficacy of a gravel pack in controlling the influx of sand and fines into a wellbore is well-known. However, it is also sometimes desirable with open-hole completions to isolate selected intervals along the open-hole portion of a wellbore in order to control the inflow of fluids. For example, in connection with the production of condensable hydrocarbons, water may sometimes invade an interval. This may be due to the presence of native water zones, coning (rise of near-well hydrocarbon-water contact), high permeability

streaks, natural fractures, or fingering from injection wells. Depending on the mechanism or cause of the water production, the water may be produced at different locations and times during a well's lifetime. Similarly, a gas cap above an oil reservoir may expand and break through, causing gas production with oil. The gas breakthrough reduces gas cap drive and suppresses oil production.

[0017] In these and other instances, it is desirable to isolate an interval from the production of formation fluids into the wellbore. Annular zonal isolation may also be desired for production allocation, production/injection fluid profile control, selective stimulation, or water or gas control. However, the design and installation of open-hole packers is highly problematic due to under-reamed areas, areas of washout, higher pressure differentials, frequent pressure cycling, and irregular borehole sizes. In addition, the longevity of zonal isolation is a consideration as the water/gas coning potential often increases later in the life of a field due to pressure drawdown and depletion.

[0018] Therefore, a need exists for an improved sand control system that provides fluid bypass technology for the placement of gravel that bypasses a packer. A need further exists for a packer assembly that provides isolation of selected subsurface intervals along an open-hole wellbore. Further, a need exists for a packer that utilizes alternate flow channels, and that provides a hydraulic seal to an open-hole wellbore before any gravel is placed around the sealing element.

SUMMARY OF THE INVENTION

[0019] An gravel pack zonal isolation apparatus for a wellbore is first provided herein. The zonal isolation apparatus has particular utility in connection with the placement of a gravel pack within an open-hole portion of the wellbore. The open-hole portion extends through one, two, or more subsurface intervals.

[0020] In one embodiment, the zonal isolation apparatus first includes a sand control device. The sand control device includes a base pipe. The base pipe defines a tubular member having a first end and a second end. Preferably, the zonal isolation apparatus further comprises a filter medium surrounding the base pipe along a substantial portion of the base pipe. Together, the base pipe and the filter medium form a sand screen.

[0021] The sand screen is arranged to have alternate flow path technology. In this respect, the sand screen includes at least one alternate flow channel to bypass the base pipe. The channels extend from the first end to the second end.

[0022] The zonal isolation apparatus also includes at least one and, optionally, at least two packer assemblies. Each packer assembly comprises at least two mechanically-set packers. These represent an upper packer element and a lower packer element. The upper and lower packer elements may be about 6 inches (15.2 cm) to 24 inches (61.0 cm) in length.

[0023] Intermediate the at least two mechanically set packers is at least one swellable packer element. The swellable packer element is preferably about 3 feet (0.91 meters) to 40 feet (12.2 meters) in length. In one aspect, the swellable packer element is fabricated from an elastomeric material. The swellable packer element is actuated over time in the presence of a fluid such as water, gas, oil, or a chemical. Swelling may take place, for example, should one of the mechanically set packer elements fails. Alternatively, swelling may take place over time as fluids in the formation surrounding the swellable packer element contact the swellable packer element.

[0024] The swellable packer element preferably swells in the presence of an aqueous fluid. In one aspect, the swellable packer element may include an elastomeric material that swells in the presence of hydrocarbon liquids or an actuating chemical. This may be in lieu of or in addition to an elastomeric material that swells in the presence of an aqueous fluid.

[0025] The zonal isolation apparatus also includes one or more alternate flow channels. The alternate flow channels are disposed outside of the base pipe and along the various packer elements within each packer assembly. The alternate flow channels serve to divert gravel pack slurry from an upper interval to one or more lower intervals during a gravel packing operation.

[0026] In one embodiment, the elongated base pipe comprises multiple joints of pipe connected end-to-end to form the first end of the sand control device and a second end of the sand control device. The zonal isolation apparatus may then comprise an upper packer assembly placed at the first end of the sand control device, and a lower packer assembly placed at the second end of the sand control device. The upper packer assembly and the lower packer assembly are spaced apart along the joints of pipe so as to straddle a selected subsurface interval within a wellbore.

[0027] The first and second mechanically-set packers are uniquely designed to be set within the open-hole portion of the wellbore before a gravel packing operation begins. To this end, a specially-designed downhole packer is offered herein, which may be used with the packer assembly and the methods herein. The downhole packer seals an annular region between a tubular body and a surrounding wellbore. The wellbore may be a cased hole,

meaning that a string of production casing has been perforated. Alternatively, the wellbore may be completed as an open hole.

[0028] In one embodiment, each downhole packer comprises an inner mandrel, at least one alternate flow channel along the inner mandrel, and a sealing element external to the inner mandrel. The sealing element resides circumferentially around the inner mandrel.

[0029] Each downhole packer may further include a movable piston housing. The piston housing is initially fixed around the inner mandrel. The piston housing has a pressure-bearing surface at a first end, and is operatively connected to the sealing element. The piston housing may be released and caused to move along the inner mandrel. Movement of the piston housing actuates the sealing element into engagement with the surrounding open-hole wellbore.

[0030] Preferably, each packer further includes a piston mandrel. The piston mandrel is disposed between the inner mandrel and the surrounding piston housing. An annulus is preserved between the inner mandrel and the piston mandrel. The annulus beneficially serves as the at least one alternate flow channel.

[0031] Each packer may also include one or more flow ports. The flow ports provide fluid communication between the alternate flow channel and the pressure-bearing surface of the piston housing. The flow ports are sensitive to hydrostatic pressure within the wellbore.

[0032] In one embodiment, each downhole packer also includes a release sleeve. The release sleeve resides along an inner surface of the inner mandrel. Further, each packer includes a release key. The release key is connected to the release sleeve. The release key is movable between a retaining position wherein the release key engages and retains the moveable piston housing in place, to a releasing position wherein the release key disengages the piston housing. When disengaged, hydrostatic pressure acts against the pressure-bearing surface of the piston housing and moves the piston housing along the inner mandrel to actuate the sealing element.

[0033] In one aspect, each packer also has at least one shear pin. The at least one shear pin may be one or more set screws. The shear pin or pins releasably connects the release sleeve to the release key. The shear pin or pins is sheared when a setting tool is pulled up the inner mandrel and slides the release sleeve. Thus, each packer is a mechanically-set packer.

[0034] In one embodiment, each downhole packer also has a centralizer. The centralizer has extendable fingers. The fingers extend radially in response to movement of

the piston housing. The centralizer is disposed around the inner mandrel between the piston housing and the sealing element. The downhole packer is preferably configured so that force applied by the piston housing against the centralizer also actuates the sealing element against the surrounding wellbore.

[0035] A method for completing a wellbore in a subsurface formation is also provided herein. The wellbore preferably includes a lower portion completed as an open-hole. In one aspect, the method includes providing a packer. The packer may be in accordance with the mechanically-set packer described above. For example, the packer will have an inner mandrel, alternate flow channels around the inner mandrel, and a sealing element external to the inner mandrel. The sealing element is preferably an elastomeric cup-type element.

[0036] The method also includes connecting the packer to a sand screen, and then running the packer and connected sand screen into the wellbore. The packer and connected sand screen are placed along the open-hole portion (or other production interval) of the wellbore.

[0037] The sand screen comprises a base pipe and a surrounding filter medium. The base pipe may be made up of a plurality of joints. The packer may be connected between two of the plurality of joints of the base pipe. Alternatively, the packer may be placed between a sand screen joint and a swellable packer element.

[0038] The method also includes setting the packer. This is done by actuating the sealing element of the packer into engagement with the surrounding open-hole portion of the wellbore. Thereafter, the method includes injecting a gravel slurry into an annular region formed between the sand screen and the surrounding open-hole portion of the wellbore, and then further injecting the gravel slurry through the alternate flow channels to allow the gravel slurry to bypass the packer. In this way, the open-hole portion of the wellbore is gravel-packed above and below the packer after the packer has been set in the wellbore.

[0039] In the method, it is preferred that the packer is a first mechanically-set packer that is part of a packer assembly. In this instance, the first mechanically-set packer is a first zonal isolation tool, and is part of a packer assembly that includes a second zonal isolation tool. The second zonal isolation tool may be a second mechanically-set packer that is constructed in accordance with the first mechanically-set packer. Alternatively, the second zonal isolation tool may be a gravel-based zonal isolation tool. Alternatively or in addition, the second zonal isolation tool may comprise a swellable packer intermediate the first and a second mechanically-set packer. The swellable packer has alternate flow channels aligned with the alternate flow channels of the first and second mechanically-set packers.

[0040] The step of further injecting the gravel slurry through the alternate flow channels allows the gravel slurry to bypass the packer assembly so that the open-hole portion of the wellbore is gravel-packed above and below the packer assembly after the first and second mechanically-set packers have been set in the wellbore.

[0041] The method may further include running a setting tool into the inner mandrel of the packers, and releasing the movable piston housing in each packer from its fixed position. The method then includes applying hydrostatic pressure to the piston housing through the one or more flow ports. Applying hydrostatic pressure moves the released piston housing and actuates the sealing element against the surrounding wellbore.

[0042] It is preferred that the setting tool is part of a washpipe used for gravel packing. In this instance, running the setting tool comprises running a washpipe into a bore within the inner mandrel of the packer, with the washpipe having a setting tool thereon. The step of releasing the movable piston housing from its fixed position then comprises pulling the washpipe with the setting tool along the inner mandrel of each packer. This serves to shear the at least one shear pin and shift the release sleeves in the respective packers.

[0043] The method may also include producing hydrocarbon fluids from at least one interval along the open-hole portion of the wellbore.

[0044] An alternate method for completing a wellbore is also provided herein. The wellbore again has a lower end defining an open-hole portion. In one aspect, the method includes running a gravel pack zonal isolation apparatus into the wellbore. The zonal isolation apparatus is generally in accordance with the zonal isolation apparatus described above, in its various embodiments. The zonal isolation apparatus will include the intermediate swellable packer element.

[0045] Next, the zonal isolation apparatus is hung in the wellbore. The apparatus is positioned such that one of the at least one packer assembly is positioned above or proximate the top of a selected subsurface interval. Alternatively, the at least one packer assembly is positioned proximate the interface of two adjacent subsurface intervals. Then, the mechanically set packers in each of the at least one packer assembly are set. This means that sealing elements in the mechanically-set packer elements are actuated into engagement with the surrounding open-hole portion of the wellbore .

[0046] The method also includes injecting a particulate slurry into an annular region formed between the sand screen and the surrounding subsurface formation. The particulate slurry is commonly made up of a carrier fluid and sand (and/or other) particles. The one or

more alternate flow channels of the zonal isolation apparatus allow the particulate slurry to travel through or around the mechanically set packer elements and the intermediate swellable packer element. In this way, the open-hole portion of the wellbore is gravel packed above and below (but not between) the mechanically set packer elements. Further, the gravel may be placed along the open-hole portion of the wellbore after the mechanically-set packers have been set.

[0047] In one embodiment, the method includes running a setting tool into the inner mandrel of the first and second mechanically-set packers, and moving the setting tool along the inner mandrels. This releases the movable piston housing on each of the first and second mechanically-set packers. The method then includes applying hydrostatic pressure to the piston housing through the one or more flow ports. This serves to move the respective piston housings and to actuate the respective upper and lower sealing elements into engagement against the surrounding wellbore.

[0048] The method also includes producing production fluids from one or more production intervals along the open-hole portion of the wellbore. Production takes place for a period of time. Over the period of time, the upper packer, the lower packer, or both, may fail, permitting the inflow of fluids into an intermediate portion of the packer along the swellable packer element. Alternatively, the intermediate swellable packer may come into contact with formation fluids or an actuating chemical. In either instance, contact with fluids will cause the swellable packer element to swell, thereby providing a long term seal beyond the life of the mechanically set packers.

[0049] Additional steps may be taken to isolate subsurface intervals along the open-hole portion of the wellbore. For example, a straddle packer may be placed within the base pipe of the sand screen joints along an intermediate interval. The straddle packer straddles packer assemblies placed near upper and lower formation interfaces for the intermediate interval. In this way, formation fluids in the intermediate interval are sealed from entering the wellbore.

[0050] Alternatively, a plug may be placed within the base pipe of the sand screen joints above a lower interval. The plug is placed at the same depth as a packer assembly proximate the top of the lower interval. In this way, formation fluids in the lower interval are sealed from entering the wellbore.

BRIEF DESCRIPTION OF THE DRAWINGS

[0051] So that the manner in which the present inventions can be better understood, certain illustrations, charts and/or flow charts are appended hereto. It is to be noted, however, that the drawings illustrate only selected embodiments of the inventions and are therefore not to be considered limiting of scope, for the inventions may admit to other equally effective embodiments and applications.

[0052] Figure 1 is a cross-sectional view of an illustrative wellbore. The wellbore has been drilled through three different subsurface intervals, each interval being under formation pressure and containing fluids.

[0053] Figure 2 is an enlarged cross-sectional view of an open-hole completion of the wellbore of Figure 1. The open-hole completion at the depth of the three illustrative intervals is more clearly seen.

[0054] Figure 3A is a cross-sectional side view of a packer assembly, in one embodiment. Here, a base pipe is shown, with surrounding packer elements. Two mechanically set packers are shown, along with an intermediate swellable packer element.

[0055] Figure 3B is a cross-sectional view of the packer assembly of Figure 3A, taken across lines 3B-3B of Figure 3A. Shunt tubes are seen within the swellable packer element.

[0056] Figure 3C is a cross-sectional view of the packer assembly of Figure 3A, in an alternate embodiment. In lieu of shunt tubes, transport tubes are seen manifolded around the base pipe.

[0057] Figure 4A is a cross-sectional side view of the packer assembly of Figure 3A. Here, sand control devices, or sand screens, have been placed at opposing ends of the packer assembly. The sand control devices utilize external shunt tubes.

[0058] Figure 4B provides a cross-sectional view of the packer assembly of Figure 4A, taken across lines 4B-4B of Figure 4A. Shunt tubes are seen outside of the sand screen to provide an alternative flowpath for a particulate slurry.

[0059] Figure 5A is another cross-sectional side view of the packer assembly of Figure 3A. Here, sand control devices, or sand screens, have again been placed at opposing ends of the packer assembly. However, the sand control devices utilize internal shunt tubes.

[0060] Figure 5B provides a cross-sectional view of the packer assembly of Figure 5A, taken across lines 5B-5B of Figure 5A. Shunt tubes are seen within the sand screen to provide an alternative flowpath for a particulate slurry.

[0061] Figure 6A is a cross-sectional side view of one of the mechanically-set packer of Figure 3A. The mechanically-set packer is in its run-in position.

[0062] Figure 6B is a cross-sectional side view of the mechanically-set packer of Figure 3A. Here, the mechanically-set packer element is in its set position.

[0063] Figure 6C is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6C-6C of Figure 6A.

[0064] Figure 6D is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6D-6D of Figure 6B.

[0065] Figure 6E is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6E-6E of Figure 6A.

[0066] Figure 6F is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6F-6F of Figure 6B.

[0067] Figure 7A is an enlarged view of the release key of Figure 6A. The release key is in its run-in position along the inner mandrel. The shear pin has not yet been sheared.

[0068] Figure 7B is an enlarged view of the release key of Figure 6B. The shear pin has been sheared, and the release key has dropped away from the inner mandrel.

[0069] Figure 7C is a perspective view of a setting tool as may be used to latch onto a release sleeve, and thereby shear a shear pin within the release key.

[0070] Figures 8A through 8N present stages of a gravel packing procedure using one of the packer assemblies of the present invention, in one embodiment. Alternate flowpath channels are provided through the packer elements of the packer assembly and through the sand control devices.

[0071] Figure 8O shows the packer assembly and gravel pack having been set in an open-hole wellbore following completion of the gravel packing procedure from Figures 8A through 8N.

[0072] Figure 9A is a cross-sectional view of a middle interval of the open-hole completion of Figure 2. Here, a straddle packer has been placed within a sand control device across the middle interval to prevent the inflow of formation fluids.

[0073] Figure 9B is a cross-sectional view of middle and lower intervals of the open-hole completion of Figure 2. Here, a plug has been placed within a packer assembly between the middle and lower intervals to prevent the flow of formation fluids up the wellbore from the lower interval.

[0074] Figures 10A through 10D present a sand screen that may be used as part of a wellbore completion system having alternate flow channels. This screen utilizes the MazeFlo™ technology.

[0075] Figure 10A provides a side view of a portion of a sand screen disposed along an open hole portion of a wellbore.

[0076] Figure 10B is a cross-sectional view of the sand screen of Figure 10A, taken across line 10B-10B of Figure 10A. Alternate flow channels are seen internal to the screen.

[0077] Figure 10C is another cross-sectional view of the sand screen of Figure 10A. This view is taken across line 10C-10C of Figure 10A.

[0078] Figure 10D is a third cross-sectional view of the sand screen of Figure 10A. This view is taken across line 10D-10D of Figure 10A.

[0079] Figures 11A through 11G present a sand control device that may be used as part of a wellbore completion system having alternate flow channels. This device utilizes a screen with an inflow control device.

[0080] Figure 11A provides a side view of a portion of the sand control device as may be placed along an open hole portion of a wellbore. The illustrative inflow control device is a choke at one end of the screen. A swellable packer is provided at the other end of the screen for fluid control.

[0081] Figure 11B is a cross-sectional view of the sand control device of Figure 11A, taken across line B-B of Figure 11A. Alternate flow channels are seen internal to the screen.

[0082] Figure 11C is another cross-sectional view of the sand control device of Figure 11A, taken across line C-C.

[0083] Figure 11D is a third cross-sectional view of the sand control device, taken across line D-D of Figure 11A.

[0084] Figure 11E is still another cross-sectional view of the sand control device of Figure 11A, taken across line E-E of Figure 11A.

[0085] Figure 11F is another side view of the sand control device of Figure 11A. Here, the swellable packer has been actuated and blocks annular flow at one end of the sand screen.

[0086] Figure 11G is a cross-sectional view of the sand control device of Figure 11F, taken across line G-G of Figure 11F. The swellable packer is seen filling an annular region between the base pipe and the surrounding screen.

[0087] Figure 12 is a flowchart for a method of completing a wellbore, in one embodiment. The method involves setting a packer and installing a gravel pack in the wellbore.

[0088] Figure 13 is a flowchart showing steps that may be performed in connection with a method for completing an open-hole wellbore, in an alternate embodiment. The method involves the installation of a zonal isolation apparatus.

[0089] Figure 14A is a side view of a gravel-packing assembly for providing back-up zonal isolation. The assembly defines a base pipe having shunt tubes there around.

[0090] Figure 14B is a cross-sectional view of the gravel-packing assembly of Figure 14A, taken across line B-B of Figure 14A.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Definitions

[0091] As used herein, the term "hydrocarbon" refers to an organic compound that includes primarily, if not exclusively, the elements hydrogen and carbon. Hydrocarbons generally fall into two classes: aliphatic, or straight chain hydrocarbons, and cyclic, or closed ring hydrocarbons, including cyclic terpenes. Examples of hydrocarbon-containing materials include any form of natural gas, oil, coal, and bitumen that can be used as a fuel or upgraded into a fuel.

[0092] As used herein, the term “hydrocarbon fluids” refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a

hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at processing conditions or at ambient conditions (15° C and 1 atm pressure). Hydrocarbon fluids may include, for example, oil, natural gas, coal bed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

[0093] As used herein, the term "fluid" refers to gases, liquids, and combinations of gases and liquids, as well as to combinations of gases and solids, and combinations of liquids and solids.

[0094] As used herein, the term "subsurface" refers to geologic strata occurring below the earth's surface.

[0095] The term "subsurface interval" refers to a formation or a portion of a formation wherein formation fluids may reside. The fluids may be, for example, hydrocarbon liquids, hydrocarbon gases, aqueous fluids, or combinations thereof.

[0096] As used herein, the term "wellbore" refers to a hole in the subsurface made by drilling or insertion of a conduit into the subsurface. A wellbore may have a substantially circular cross section, or other cross-sectional shape. As used herein, the term "well", when referring to an opening in the formation, may be used interchangeably with the term "wellbore."

[0097] The term "tubular member" refers to any pipe, such as a joint of casing, a portion of a liner, or a pup joint.

[0098] The term "sand control device" means any elongated tubular body that permits an inflow of fluid into an inner bore or a base pipe while filtering out predetermined sizes of sand, fines and granular debris from a surrounding formation. A sand screen is an example of a sand control device.

[0099] The term "alternate flow channels" means any collection of manifolds and/or shunt tubes that provide fluid communication through or around a tubular wellbore tool to allow a gravel slurry to by-pass the wellbore tool or any premature sand bridge in the annular region and continue gravel packing further downstream. Examples of such wellbore tools include (i) a packer having a sealing element, (ii) a sand screen or slotted pipe, and (iii) a blank pipe, with or without an outer protective shroud.

Description of Specific Embodiments

[0100] The inventions are described herein in connection with certain specific embodiments. However, to the extent that the following detailed description is specific to a particular embodiment or a particular use, such is intended to be illustrative only and is not to be construed as limiting the scope of the inventions.

[0101] Certain aspects of the inventions are also described in connection with various figures. In certain of the figures, the top of the drawing page is intended to be toward the surface, and the bottom of the drawing page toward the well bottom. While wells commonly are completed in substantially vertical orientation, it is understood that wells may also be inclined and or even horizontally completed. When the descriptive terms "up and down" or "upper" and "lower" or similar terms are used in reference to a drawing or in the claims, they are intended to indicate relative location on the drawing page or with respect to claim terms, and not necessarily orientation in the ground, as the present inventions have utility no matter how the wellbore is orientated.

[0102] **Figure 1** is a cross-sectional view of an illustrative wellbore **100**. The wellbore **100** defines a bore **105** that extends from a surface **101**, and into the earth's subsurface **110**. The wellbore **100** is completed to have an open-hole portion **120** at a lower end of the wellbore **100**. The wellbore **100** has been formed for the purpose of producing hydrocarbons for commercial sale. A string of production tubing **130** is provided in the bore **105** to transport production fluids from the open-hole portion **120** up to the surface **101**.

[0103] The wellbore **100** includes a well tree, shown schematically at **124**. The well tree **124** includes a shut-in valve **126**. The shut-in valve **126** controls the flow of production fluids from the wellbore **100**. In addition, a subsurface safety valve **132** is provided to block the flow of fluids from the production tubing **130** in the event of a rupture or catastrophic event above the subsurface safety valve **132**. The wellbore **100** may optionally have a pump (not shown) within or just above the open-hole portion **120** to artificially lift production fluids from the open-hole portion **120** up to the well tree **124**.

[0104] The wellbore **100** has been completed by setting a series of pipes into the subsurface **110**. These pipes include a first string of casing **102**, sometimes known as surface casing or a conductor. These pipes also include at least a second **104** and a third **106** string of casing. These casing strings **104**, **106** are intermediate casing strings that provide support for walls of the wellbore **100**. Intermediate casing strings **104**, **106** may be hung from the surface, or they may be hung from a next higher casing string using an

expandable liner or liner hanger. It is understood that a pipe string that does not extend back to the surface (such as casing string **106**) is normally referred to as a "liner."

[0105] In the illustrative wellbore arrangement of **Figure 1**, intermediate casing string **104** is hung from the surface **101**, while casing string **106** is hung from a lower end of casing string **104**. Additional intermediate casing strings (not shown) may be employed. The present inventions are not limited to the type of casing arrangement used.

[0106] Each string of casing **102**, **104**, **106** is set in place through cement **108**. The cement **108** isolates the various formations of the subsurface **110** from the wellbore **100** and each other. The cement **108** extends from the surface **101** to a depth "**L**" at a lower end of the casing string **106**. It is understood that some intermediate casing strings may not be fully cemented.

[0107] An annular region **204** is formed between the production tubing **130** and the casing string **106**. A production packer **206** seals the annular region **204** near the lower end "**L**" of the casing string **106**.

[0108] In many wellbores, a final casing string known as production casing is cemented into place at a depth where subsurface production intervals reside. However, the illustrative wellbore **100** is completed as an open-hole wellbore. Accordingly, the wellbore **100** does not include a final casing string along the open-hole portion **120**.

[0109] In the illustrative wellbore **100**, the open-hole portion **120** traverses three different subsurface intervals. These are indicated as upper interval **112**, intermediate interval **114**, and lower interval **116**. Upper interval **112** and lower interval **116** may, for example, contain valuable oil deposits sought to be produced, while intermediate interval **114** may contain primarily water or other aqueous fluid within its pore volume. This may be due to the presence of native water zones, high permeability streaks or natural fractures in the aquifer, or fingering from injection wells. In this instance, there is a probability that water will invade the wellbore **100**.

[0110] Alternatively, upper **112** and intermediate **114** intervals may contain hydrocarbon fluids sought to be produced, processed and sold, while lower interval **116** may contain some oil along with ever-increasing amounts of water. This may be due to coning, which is a rise of near-well hydrocarbon-water contact. In this instance, there is again the possibility that water will invade the wellbore **100**.

[0111] Alternatively still, upper **112** and lower **116** intervals may be producing hydrocarbon fluids from a sand or other permeable rock matrix, while intermediate interval

114 may represent a non-permeable shale or otherwise be substantially impermeable to fluids.

[0112] In any of these events, it is desirable for the operator to isolate selected intervals. In the first instance, the operator will want to isolate the intermediate interval **114** from the production string **130** and from the upper **112** and lower **116** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the second instance, the operator will eventually want to isolate the lower interval **116** from the production string **130** and the upper **112** and intermediate **114** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the third instance, the operator will want to isolate the upper interval **112** from the lower interval **116**, but need not isolate the intermediate interval **114**. Solutions to these needs in the context of an open-hole completion are provided herein, and are demonstrated more fully in connection with the proceeding drawings.

[0113] In connection with the production of hydrocarbon fluids from a wellbore having an open-hole completion, it is not only desirable to isolate selected intervals, but also to limit the influx of sand particles and other fines. In order to prevent the migration of formation particles into the production string **130** during operation, sand control devices **200** have been run into the wellbore **100**. These are described more fully below in connection with **Figure 2** and with **Figures 8A** through **8N**.

[0114] Referring now to **Figure 2**, the sand control devices **200** contain an elongated tubular body referred to as a base pipe **205**. The base pipe **205** typically is made up of a plurality of pipe joints. The base pipe **205** (or each pipe joint making up the base pipe **205**) typically has small perforations or slots to permit the inflow of production fluids.

[0115] The sand control devices **200** also contain a filter medium **207** wound or otherwise placed radially around the base pipes **205**. The filter medium **207** may be a wire mesh screen or wire wrap fitted around the base pipe **205**. Alternatively, the filtering medium of the sand screen comprises a membrane screen, an expandable screen, a sintered metal screen, a porous media made of shape memory polymer (such as that described in U.S. Pat. No. 7,926,565), a porous media packed with fibrous material, or a pre-packed solid particle bed. The filter medium **207** prevents the inflow of sand or other particles above a pre-determined size into the base pipe **205** and the production tubing **130**.

[0116] In addition to the sand control devices **200**, the wellbore **100** includes one or more packer assemblies **210**. In the illustrative arrangement of **Figures 1** and **2**, the wellbore **100** has an upper packer assembly **210'** and a lower packer assembly **210"**.

However, additional packer assemblies **210** or just one packer assembly **210** may be used. The packer assemblies **210'**, **210''** are uniquely configured to seal an annular region (seen at **202** of **Figure 2**) between the various sand control devices **200** and a surrounding wall **201** of the open-hole portion **120** of the wellbore **100**.

[0117] **Figure 2** is an enlarged cross-sectional view of the open-hole portion **120** of the wellbore **100** of **Figure 1**. The open-hole portion **120** and the three intervals **112**, **114**, **116** are more clearly seen. The upper **210'** and lower **210''** packer assemblies are also more clearly visible proximate upper and lower boundaries of the intermediate interval **114**, respectively. Finally, the sand control devices **200** along each of the intervals **112**, **114**, **116** are shown.

[0118] Concerning the packer assemblies themselves, each packer assembly **210'**, **210''** may have at least two packers. The packers are preferably set through a combination of mechanical manipulation and hydraulic forces. The packer assemblies **210** represent an upper packer **212** and a lower packer **214**. Each packer **212**, **214** has an expandable portion or element fabricated from an elastomeric or a thermoplastic material capable of providing at least a temporary fluid seal against the surrounding wellbore wall **201**.

[0119] The elements for the upper **212** and lower **214** packers should be able to withstand the pressures and loads associated with a gravel packing process. Typically, such pressures are from about 2,000 psi to 3,000 psi. The elements for the packers **212**, **214** should also withstand pressure load due to differential wellbore and/or reservoir pressures caused by natural faults, depletion, production, or injection. Production operations may involve selective production or production allocation to meet regulatory requirements. Injection operations may involve selective fluid injection for strategic reservoir pressure maintenance. Injection operations may also involve selective stimulation in acid fracturing, matrix acidizing, or formation damage removal.

[0120] The sealing surface or elements for the mechanically set packers **212**, **214** need only be on the order of inches in order to affect a suitable hydraulic seal. In one aspect, the elements are each about 6 inches (15.2 cm) to about 24 inches (61.0 cm) in length.

[0121] The elements for the packers **212**, **214** are preferably cup-type elements. Cup--type elements are known for use in cased-hole completions. However, they generally are not known for use in open-hole completions as they are not engineered to expand into engagement with an open-hole diameter. Moreover, such expandable cup-type elements may not maintain the required pressure differential encountered over the life of production operations, resulting in decreased functionality.

[0122] It is preferred for the packer elements **212**, **214** to be able to expand to at least an 11-inch (about 28 cm) outer diameter surface, with no more than a 1.1 ovality ratio. The elements **212**, **214** should preferably be able to handle washouts in an 8-1/2 inch (about 21.6 cm) or 9-7/8 inch (about 25.1 cm) open-hole section **120**. The preferred cup-type nature of the expandable portions of the packer elements **212**, **214** will assist in maintaining at least a temporary seal against the wall **201** of the intermediate interval **114** (or other interval) as pressure increases during the gravel packing operation.

[0123] In one embodiment, the cup-type elements need not be liquid tight, nor must they be rated to handle multiple pressure and temperature cycles. The cup-type elements need only be designed for one-time use, to wit, during the gravel packing process of an open-hole wellbore completion. This is because an intermediate swellable packer element **216** is also preferably provided for long term sealing.

[0124] The upper **212** and lower **214** packers are set prior to a gravel pack installation process. As described more fully below, the packers **212**, **214** are preferably set by mechanically shearing a shear pin and sliding a release sleeve. This, in turn, releases a release key, which then allows hydrostatic pressure to act downwardly against a piston housing. The piston housing travels downward along an inner mandrel (not shown). The piston housing then acts upon a centralizer and/or a cup-type packing element. The centralizer and the expandable portion of the packers **212**, **214** expand against the wellbore wall **201**. The elements of the upper **212** and lower **214** packers are expanded into contact with the surrounding wall **201** so as to straddle the annular region **202** at a selected depth along the open-hole completion **120**.

[0125] **Figure 2** shows a mandrel at **215**. This may be representative of the piston mandrel, and other mandrels used in the packers **212**, **214** as described more fully below.

[0126] As a "back-up" to the cup-type packer elements within the upper **212** and lower **214** packer elements, the packer assemblies **210'**, **210''** also each include an intermediate packer element **216**. The intermediate packer element **216** defines a swelling elastomeric material fabricated from synthetic rubber compounds. Suitable examples of swellable materials may be found in Easy Well Solutions' Constrictor™ or SwellPacker™, and SwellFix's E-ZIP™. The swellable packer **216** may include a swellable polymer or swellable polymer material, which is known by those skilled in the art and which may be set by one of a conditioned drilling fluid, a completion fluid, a production fluid, an injection fluid, a stimulation fluid, or any combination thereof.

[0127] The swellable packer element **216** is preferably bonded to the outer surface of the mandrel **215**. The swellable packer element **216** is allowed to expand over time when contacted by hydrocarbon fluids, formation water, or any chemical described above which may be used as an actuating fluid. As the packer element **216** expands, it forms a fluid seal with the surrounding zone, e.g., interval **114**. In one aspect, a sealing surface of the swellable packet element **216** is from about 5 feet (1.5 meters) to 50 feet (15.2 meters) in length; and more preferably, about 3 feet (0.9 meters) to 40 feet (12.2 meters) in length.

[0128] The swellable packer element **216** must be able to expand to the wellbore wall **201** and provide the required pressure integrity at that expansion ratio. Since swellable packers are typically set in a shale section that may not produce hydrocarbon fluids, it is preferable to have a swelling elastomer or other material that can swell in the presence of formation water or an aqueous-based fluid. Examples of materials that will swell in the presence of an aqueous-based fluid are bentonite clay and a nitrile-based polymer with incorporated water absorbing particles.

[0129] Alternatively, the swellable packer element **216** may be fabricated from a combination of materials that swell in the presence of water and oil, respectively. Stated another way, the swellable packer element **216** may include two types of swelling elastomers -- one for water and one for oil. In this situation, the water-swellable element will swell when exposed to the water-based gravel pack fluid or in contact with formation water, and the oil-based element will expand when exposed to hydrocarbon production. An example of an elastomeric material that will swell in the presence of a hydrocarbon liquid is oleophilic polymer that absorbs hydrocarbons into its matrix. The swelling occurs from the absorption of the hydrocarbons which also lubricates and decreases the mechanical strength of the polymer chain as it expands. Ethylene propylene diene monomer (M-class) rubber, or EPDM, is one example of such a material.

[0130] The swellable packer **216** may be fabricated from other expandable material. An example is a shape-memory polymer. U.S. Pat. No. 7,243,732 and U.S. Pat. No. 7,392,852 disclose the use of such a material for zonal isolation.

[0131] The mechanically set packer elements **212**, **214** are preferably set in a water-based gravel pack fluid that would be diverted around the swellable packer element **216**, such as through shunt tubes (not shown in **Figure 2**). If only a hydrocarbon swelling elastomer is used, expansion of the element may not occur until after the failure of either of the mechanically set packer elements **212**, **214**.

[0132] The upper **212** and lower **214** packers may generally be mirror images of each other, except for the release sleeves that shear the respective shear pins or other engagement mechanisms. Unilateral movement of a shifting tool (shown in and discussed in connection with **Figures 7A** and **7B**) will allow the packers **212**, **214** to be activated in sequence or simultaneously. The lower packer **214** is activated first, followed by the upper packer **212** as the shifting tool is pulled upward through an inner mandrel (shown in and discussed in connection with **Figures 6A** and **6B**). A short spacing is preferably provided between the upper **212** and lower **214** packers.

[0133] The packer assemblies **210'**, **210''** help control and manage fluids produced from different zones. In this respect, the packer assemblies **210'**, **210''** allow the operator to seal off an interval from either production or injection, depending on well function. Installation of the packer assemblies **210'**, **210''** in the initial completion allows an operator to shut-off the production from one or more zones during the well lifetime to limit the production of water or, in some instances, an undesirable non-condensable fluid such as hydrogen sulfide.

[0134] Packers historically have not been installed when an open-hole gravel pack is utilized because of the difficulty in forming a complete gravel pack above and below the packer. Related patent applications, U.S. Publication Nos. 2009/0294128 and 2010/0032158 disclose apparatus' and methods for gravel-packing an open-hole wellbore after a packer has been set at a completion interval.

[0135] Certain technical challenges have remained with respect to the methods disclosed in U.S. Pub Nos. 2009/0294128 and 2010/0032158, particularly in connection with the packer. The applications state that the packer may be a hydraulically actuated inflatable element. Such an inflatable element may be fabricated from an elastomeric material or a thermoplastic material. However, designing a packer element from such materials requires the packer element to meet a particularly high performance level. In this respect, the packer element needs to be able to maintain zonal isolation for a period of years in the presence of high pressures and/or high temperatures and/or acidic fluids. As an alternative, the applications state that the packer may be a swelling rubber element that expands in the presence of hydrocarbons, water, or other stimulus. However, known swelling elastomers typically require about 30 days or longer to fully expand into sealed fluid engagement with the surrounding rock formation. Therefore, improved packers and zonal isolation apparatus' are offered herein.

[0136] **Figure 3A** presents an illustrative packer assembly **300** providing an alternate flowpath for a gravel slurry. The packer assembly **300** is seen in cross-sectional side view.

The packer assembly **300** includes various components that may be utilized to seal an annulus along the open-hole portion **120**.

[0137] The packer assembly **300** first includes a main body section **302**. The main body section **302** is preferably fabricated from steel or from steel alloys. The main body section **302** is configured to be a specific length **316**, such as about 40 feet (12.2 meters). The main body section **302** comprises individual pipe joints that will have a length that is between about 10 feet (3.0 meters) and 50 feet (15.2 meters). The pipe joints are typically threadedly connected end-to-end to form the main body section **302** according to length **316**.

[0138] The packer assembly **300** also includes opposing mechanically-set packers **304**. The mechanically-set packers **304** are shown schematically, and are generally in accordance with mechanically-set packer elements **212** and **214** of **Figure 2**. The packers **304** preferably include cup-type elastomeric elements that are less than 1 foot (0.3 meters) in length. As described further below, the packers **304** have alternate flow channels that uniquely allow the packers **304** to be set before a gravel slurry is circulated into the wellbore.

[0139] The packer assembly **300** also optionally includes a swellable packer **308**. The swellable packer **308** is in accordance with swellable packer element **216** of **Figure 2**. The swellable packer **308** is preferably about 3 feet (0.9 meters) to 40 feet (12.2 meters) in length. Together, the mechanically-set packers **304** and the intermediate swellable packer **308** surround the main body section **302**. Alternatively, a short spacing may be provided between the mechanically-set packers **304** in lieu of the swellable packer **308**.

[0140] The packer assembly **300** also includes a plurality of shunt tubes. The shunt tubes are seen in phantom at **318**. The shunt tubes **318** may also be referred to as transport tubes or jumper tubes. The shunt tubes **318** are blank sections of pipe having a length that extends along the length **316** of the mechanically-set packers **304** and the swellable packer **308**. The shunt tubes **318** on the packer assembly **300** are configured to couple to and form a seal with shunt tubes on connected sand screens as discussed further below.

[0141] The shunt tubes **318** provide an alternate flowpath through the mechanically-set packers **304** and the intermediate swellable packer **308** (or spacing). This enables the shunt tubes **318** to transport a carrier fluid along with gravel to different intervals **112**, **114** and **116** of the open-hole portion **120** of the wellbore **100**.

[0142] The packer assembly **300** also includes connection members. These may represent traditional threaded couplings. First, a neck section **306** is provided at a first end of the packer assembly **300**. The neck section **306** has external threads for connecting with

a threaded coupling box of a sand screen or other pipe. Then, a notched or externally threaded section **310** is provided at an opposing second end. The threaded section **310** serves as a coupling box for receiving an external threaded end of a sand screen or other tubular member.

[0143] The neck section **306** and the threaded section **310** may be made of steel or steel alloys. The neck section **306** and the threaded section **310** are each configured to be a specific length **314**, such as 4 inches (10.2 cm) to 4 feet (1.2 meters) (or other suitable distance). The neck section **306** and the threaded section **310** also have specific inner and outer diameters. The neck section **306** has external threads **307**, while the threaded section **310** has internal threads **311**. These threads **307** and **311** may be utilized to form a seal between the packer assembly **300** and sand control devices or other pipe segments.

[0144] A cross-sectional view of the packer assembly **300** is shown in **Figure 3B**. **Figure 3B** is taken along the line **3B-3B** of **Figure 3A**. In **Figure 3B**, the swellable packer **308** is seen circumferentially disposed around the base pipe **302**. Various shunt tubes **318** are placed radially and equidistantly around the base pipe **302**. A central bore **305** is shown within the base pipe **302**. The central bore **305** receives production fluids during production operations and conveys them to the production tubing **130**.

[0145] **Figure 4A** presents a cross-sectional side view of a zonal isolation apparatus **400**, in one embodiment. The zonal isolation apparatus **400** includes the packer assembly **300** from **Figure 3A**. In addition, sand control devices **200** have been connected at opposing ends to the neck section **306** and the notched section **310**, respectively. Shunt tubes **318** from the packer assembly **300** are seen connected to shunt tubes **218** on the sand control devices **200**. The shunt tubes **218** represent packing tubes that allow the flow of gravel slurry between a wellbore annulus and the tubes **218**. The shunt tubes **218** on the sand control devices **200** optionally include valves **209** to control the flow of gravel slurry such as to packing tubes (not shown).

[0146] **Figure 4B** provides a cross-sectional side view of the zonal isolation apparatus **400**. **Figure 4B** is taken along the line **4B-4B** of **Figure 4A**. This is cut through one of the sand screens **200**. In **Figure 4B**, the slotted or perforated base pipe **205** is seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0147] An outer mesh **220** is disposed immediately around the base pipe **205**. The outer mesh **220** preferably comprises a wire mesh or wires helically wrapped around the base pipe **205**, and serves as a screen. In addition, shunt tubes **218** are placed radially and

equidistantly around the outer mesh **205**. This means that the sand control devices **200** provide an external embodiment for the shunt tubes **218** (or alternate flow channels).

[0148] The configuration of the shunt tubes **218** is preferably concentric. This is seen in the cross-sectional view of Figure 3B. However, the shunt tubes **218** may be eccentrically designed. For example, Figure 2B in U.S. Pat. No. 7,661,476 presents a "Prior Art" arrangement for a sand control device wherein packing tubes 208a and transport tubes 208b are placed external to the base pipe 202 and surrounding filter medium 204.

[0149] In the arrangement of **Figures 4A** and **4B**, the shunt tubes **218** are external to the filter medium, or outer mesh **220**. However, the configuration of the sand control device **200** may be modified. In this respect, the shunt tubes **218** may be moved internal to the filter medium **220**.

[0150] **Figure 5A** presents a cross-sectional side view of a zonal isolation apparatus **500**, in an alternate embodiment. In this embodiment, sand control devices **200** are again connected at opposing ends to the neck section **306** and the notched section **310**, respectively, of the packer assembly **300**. In addition, shunt tubes **318** on the packer assembly **300** are seen connected to shunt tubes **218** on the sand control assembly **200**. However, in **Figure 5A**, the sand control assembly **200** utilizes internal shunt tubes **218**, meaning that the shunt tubes **218** are disposed between the base pipe **205** and the surrounding filter medium **220**.

[0151] **Figure 5B** provides a cross-sectional side view of the zonal isolation apparatus **500**. **Figure 5B** is taken along the line **B-B** of **Figure 5A**. This is cut through one of the sand screens **200**. In **Figure 5B**, the slotted or perforated base pipe **205** is again seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0152] Shunt tubes **218** are placed radially and equidistantly around the base pipe **205**. The shunt tubes **218** reside immediately around the base pipe **205**, and within a surrounding filter medium **220**. This means that the sand control devices **200** of **Figures 5A** and **5B** provide an internal embodiment for the shunt tubes **218**.

[0153] An annular region **225** is created between the base pipe **205** and the surrounding outer mesh or filter medium **220**. The annular region **225** accommodates the inflow of production fluids in a wellbore. The outer wire wrap **220** is supported by a plurality of radially extending support ribs **222**. The ribs **222** extend through the annular region **225**.

[0154] **Figures 4A** and **5A** present arrangements for connecting sand control joints to a packer assembly. Shunt tubes **318** (or alternate flow channels) within the packers fluidly connect to shunt tubes **218** along the sand screens **200**. However, the zonal isolation apparatus arrangements **400**, **500** of **Figures 4A-4B** and **5A-5B** are merely illustrative. In an alternative arrangement, a manifolding system may be used for providing fluid communication between the shunt tubes **218** and the shunt tubes **318**.

[0155] **Figure 3C** is a cross-sectional view of the packer assembly **300** of **Figure 3A**, in an alternate embodiment. In this arrangement, the shunt tubes **218** are manifolded around the base pipe **302**. A support ring **315** is provided around the shunt tubes **318**. It is again understood that the present apparatus and methods are not confined by the particular design and arrangement of shunt tubes **318** so long as slurry bypass is provided for the packer assembly **210**. However, it is preferred that a concentric arrangement be employed.

[0156] It should also be noted that the coupling mechanism for the sand control devices **200** with the packer assembly **300** may include a sealing mechanism (not shown). The sealing mechanism prevents leaking of the slurry that is in the alternate flowpath formed by the shunt tubes. Examples of such sealing mechanisms are described in U.S. Patent No. 6,464,261; Intl. Pat. Application No. WO 2004/094769; Intl. Pat. Application No. WO 2005/031105; U.S. Pat. Publ. No. 2004/0140089; U.S. Pat. Publ. No. 2005/0028977; U.S. Pat. Publ. No. 2005/0061501; and U.S. Pat. Publ. No. 2005/0082060.

[0157] Coupling sand control devices **200** with a packer assembly **300** requires alignment of the shunt tubes **318** in the packer assembly **300** with the shunt tubes **218** along the sand control devices **200**. In this respect, the flow path of the shunt tubes **218** in the sand control devices should be un-interrupted when engaging a packer. **Figure 4A** (described above) shows sand control devices **200** connected to an intermediate packer assembly **300**, with the shunt tubes **218**, **318** in alignment. However, making this connection typically requires a special sub or jumper with a union-type connection, a timed connection to align the multiple tubes, or a cylindrical cover plate over the connecting tubes. These connections are expensive, time-consuming, and/or difficult to handle on the rig floor.

[0158] U.S. Patent No. 7,661,476, entitled "Gravel Packing Methods," discloses a production string (referred to as a joint assembly) that employs one or more sand screen joints. The sand screen joints are placed between a "load sleeve assembly" and a "torque sleeve assembly." The load sleeve assembly defines an elongated body comprising an outer wall (serving as an outer diameter) and an inner wall (providing an inner diameter). The inner wall forms a bore through the load sleeve assembly. Similarly, the torque sleeve

assembly defines an elongated body comprising an outer wall (serving as an outer diameter) and an inner wall (providing an inner diameter). The inner wall also forms a bore through the torque sleeve assembly.

[0159] The load sleeve assembly includes at least one transport conduit and at least one packing conduit. The at least one transport conduit and the at least one packing conduit are disposed exterior to the inner diameter and interior to the outer diameter. Similarly, torque sleeve assembly includes at least one conduit. The at least one conduit is also disposed exterior to the inner diameter and interior to the outer diameter.

[0160] The production string includes a "main body portion." This is essentially a base pipe that runs through the sand screen. A coupling assembly having a manifold region may also be provided. The manifold region is configured to be in fluid flow communication with the at least one transport conduit and at least one packing conduit of the load sleeve assembly during at least a portion of gravel packing operations. The coupling assembly is operably attached to at least a portion of the at least one joint assembly at or near the load sleeve assembly. The load sleeve assembly and the torque sleeve assembly are made up or coupled with the base pipe in such a manner that the transport and packing conduits are in fluid communication, thereby providing alternate flow channels for gravel slurry. The benefit of the load sleeve assembly, the torque sleeve assembly, and a coupling assembly is that they enable a series of sand screen joints to be connected and run into the wellbore in a faster and less expensive manner.

[0161] As noted, the packer assembly **300** includes a pair of mechanically-set packers **304**. When using the packer assembly **300**, the packers **304** are beneficially set before the slurry is injected and the gravel pack is formed. This requires a unique packer arrangement wherein shunt tubes are provided for an alternate flow channel.

[0162] The packers **304** of **Figure 3A** are shown schematically. However, **Figures 6A** and **6B** provide more detailed views of a mechanically-set packer **600** that may be used in the packer assembly of **Figure 3A**, in one embodiment. The views of **Figures 6A** and **6B** provide cross-sectional side views. In **Figure 6A**, the packer **600** is in its run-in position, while in **Figure 6B** the packer **600** is in its set position.

[0163] Other embodiments of sand control devices **200** may be used with the apparatuses and methods herein. For example, the sand control devices may include stand-alone screens (SAS), pre-packed screens, or membrane screens. The joints may be any combination of screen, blank pipe, or zonal isolation apparatus.

[0164] The packer **600** first includes an inner mandrel **610**. The inner mandrel **610** defines an elongated tubular body forming a central bore **605**. The central bore **605** provides a primary flow path of production fluids through the packer **600**. After installation and commencement of production, the central bore **605** transports production fluids to the bore **105** of the sand screens **200** (seen in **Figures 4A** and **4B**) and the production tubing **130** (seen in **Figures 1** and **2**).

[0165] The packer **600** also includes a first end **602**. Threads **604** are placed along the inner mandrel **610** at the first end **602**. The illustrative threads **604** are external threads. A box connector **614** having internal threads at both ends is connected or threaded on threads **604** at the first end **602**. The first end **602** of inner mandrel **610** with the box connector **614** is called the box end. The second end (not shown) of the inner mandrel **610** has external threads and is called the pin end. The pin end (not shown) of the inner mandrel **610** allows the packer **600** to be connected to the box end of a sand screen or other tubular body such as a stand-alone screen, a sensing module, a production tubing, or a blank pipe.

[0166] The box connector **614** at the box end **602** allows the packer **600** to be connected to the pin end of a sand screen or other tubular body such as a stand-alone screen, a sensing module, a production tubing, or a blank pipe.

[0167] The inner mandrel **610** extends along the length of the packer **600**. The inner mandrel **610** may be composed of multiple connected segments, or joints. The inner mandrel **610** has a slightly smaller inner diameter near the first end **602**. This is due to a setting shoulder **606** machined into the inner mandrel. As will be explained more fully below, the setting shoulder **606** catches a release sleeve **710** in response to mechanical force applied by a setting tool.

[0168] The packer **600** also includes a piston mandrel **620**. The piston mandrel **620** extends generally from the first end **602** of the packer **600**. The piston mandrel **620** may be composed of multiple connected segments, or joints. The piston mandrel **620** defines an elongated tubular body that resides circumferentially around and substantially concentric to the inner mandrel **610**. An annulus **625** is formed between the inner mandrel **610** and the surrounding piston mandrel **620**. The annulus **625** beneficially provides a secondary flow path or alternate flow channels for fluids.

[0169] In the arrangement of **Figures 6A** and **6B**, the alternate flow channels defined by the annulus **625** are external to the inner mandrel **610**. However, the packer could be reconfigured such that the alternate flow channels are within the bore **605** of the inner

mandrel **610**. In either instance, the alternate flow channels are "along" the inner mandrel **610**.

[0170] The annulus **625** is in fluid communication with the secondary flow path of another downhole tool (not shown in **Figures 6A** and **6B**). Such a separate tool may be, for example, the sand screens **200** of **Figures 4A** and **5A**, or a blank pipe, a swellable zonal isolation packer such as packer **308** of **Figure 3A**, or other tubular body. The tubular body may or may not have alternate flow channels.

[0171] The packer **600** also includes a coupling **630**. The coupling **630** is connected and sealed (e.g., via elastomeric "o" rings) to the piston mandrel **620** at the first end **602**. The coupling **630** is then threaded and pinned to the box connector **614**, which is threadedly connected to the inner mandrel **610** to prevent relative rotational movement between the inner mandrel **610** and the coupling **630**. A first torque bolt is shown at **632** for pinning the coupling to the box connector **614**.

[0172] In one aspect, a NACA (National Advisory Committee for Aeronautics) key **634** is also employed. The NACA key **634** is placed internal to the coupling **630**, and external to a threaded box connector **614**. A first torque bolt is provided at **632**, connecting the coupling **630** to the NACA key **634** and then to the box connector **614**. A second torque bolt is provided at **636** connecting the coupling **630** to the NACA key **634**. NACA-shaped keys can (a) fasten the coupling **630** to the inner mandrel **610** via box connector **614**, (b) prevent the coupling **630** from rotating around the inner mandrel **610**, and (c) streamline the flow of slurry along the annulus **612** to reduce friction.

[0173] Within the packer **600**, the annulus **625** around the inner mandrel **610** is isolated from the main bore **605**. In addition, the annulus **625** is isolated from a surrounding wellbore annulus (not shown). The annulus **625** enables the transfer of gravel slurry from alternative flow channels (such as shunt tubes **218**) through the packer **600**. Thus, the annulus **625** becomes the alternative flow channel(s) for the packer **600**.

[0174] In operation, an annular space **612** resides at the first end **602** of the packer **600**. The annular space **612** is disposed between the box connector **614** and the coupling **630**. The annular space **612** receives slurry from alternate flow channels of a connected tubular body, and delivers the slurry to the annulus **625**. The tubular body may be, for example, an adjacent sand screen, a blank pipe, or a zonal isolation device.

[0175] The packer **600** also includes a load shoulder **626**. The load shoulder **626** is placed near the end of the piston mandrel **620** where the coupling **630** is connected and

sealed. A solid section at the end of the piston mandrel **620** has an inner diameter and an outer diameter. The load shoulder **626** is placed along the outer diameter. The inner diameter has threads and is threadedly connected to the inner mandrel **610**. At least one alternate flow channel is formed between the inner and outer diameters to connect flow between the annular space **612** and the annulus **625**.

[0176] The load shoulder **626** provides a load-bearing point. During rig operations, a load collar or harness (not shown) is placed around the load shoulder **626** to allow the packer **600** to be picked up and supported with conventional elevators. The load shoulder **626** is then temporarily used to support the weight of the packer **600** (and any connected completion devices such as sand screen joints already run into the well) when placed in the rotary floor of a rig. The load may then be transferred from the load shoulder **626** to a pipe thread connector such as box connector **614**, then to the inner mandrel **610** or base pipe **205**, which is pipe threaded to the box connector **614**.

[0177] The packer **600** also includes a piston housing **640**. The piston housing **640** resides around and is substantially concentric to the piston mandrel **620**. The packer **600** is configured to cause the piston housing **640** to move axially along and relative to the piston mandrel **620**. Specifically, the piston housing **640** is driven by the downhole hydrostatic pressure. The piston housing **640** may be composed of multiple connected segments, or joints.

[0178] The piston housing **640** is held in place along the piston mandrel **620** during run-in. The piston housing **640** is secured using a release sleeve **710** and release key **715**. The release sleeve **710** and release key **715** prevent relative translational movement between the piston housing **640** and the piston mandrel **620**. The release key **715** penetrates through both the piston mandrel **620** and the inner mandrel **610**.

[0179] **Figures 7A** and **7B** provide enlarged views of the release sleeve **710** and the release key **715** for the packer **600**. The release sleeve **710** and the release key **715** are held in place by a shear pin **720**. In **Figure 7A**, the shear pin **720** has not been sheared, and the release sleeve **710** and the release key **715** are held in place along the inner mandrel **610**. However, in **Figure 7B** the shear pin **720** has been sheared, and the release sleeve **710** has been translated along an inner surface **608** of the inner mandrel **610**.

[0180] In each of **Figures 7A** and **7B**, the inner mandrel **610** and the surrounding piston mandrel **620** are seen. In addition, the piston housing **640** is seen outside of the piston mandrel **620**. The three tubular bodies representing the inner mandrel **610**, the piston mandrel **620**, and the piston housing **640** are secured together against relative translational

or rotational movement by four release keys **715**. Only one of the release keys **715** is seen in **Figure 7A**; however, four separate keys **715** are radially visible in the cross-sectional view of **Figure 6E**, described below.

[0181] The release key **715** resides within a keyhole **615**. The keyhole **615** extends through the inner mandrel **610** and the piston mandrel **620**. The release key **715** includes a shoulder **734**. The shoulder **734** resides within a shoulder recess **624** in the piston mandrel **620**. The shoulder recess **624** is large enough to permit the shoulder **734** to move radially inwardly. However, such play is restricted in **Figure 7A** by the presence of the release sleeve **710**.

[0182] It is noted that the annulus **625** between the inner mandrel **610** and the piston mandrel **620** is not seen in **Figure 7A** or **7B**. This is because the annulus **625** does not extend through this cross-section, or is very small. Instead, the annulus **625** employs separate radially-spaced channels that preserve the support for the release keys **715**, as seen best in **Figure 6E**. Stated another way, the large channels making up the annulus **625** are located away from the material of the inner mandrel **610** that surrounds the keyholes **615**.

[0183] At each release key location, a keyhole **615** is machined through the inner mandrel **610**. The keyholes **615** are drilled to accommodate the respective release keys **715**. If there are four release keys **715**, there will be four discrete bumps spaced circumferentially to significantly reduce the annulus **625**. The remaining area of the annulus **625** between adjacent bumps allows flow in the alternate flow channel **625** to by-pass the release key **715**.

[0184] Bumps may be machined as part of the body of the inner mandrel **610**. More specifically, material making up the inner mandrel **610** may be machined to form the bumps. Alternatively, bumps may be machined as a separate, short release mandrel (not shown), which is then threaded to the inner mandrel **610**. Alternatively still, the bumps may be a separate spacer secured between the inner mandrel **610** and the piston mandrel **620** by welding or other means.

[0185] It is also noted here that in **Figure 6A**, the piston mandrel **620** is shown as an integral body. However, the portion of the piston mandrel **620** where the keyholes **615** are located may be a separate, short release housing. This separate housing is then connected to the main piston mandrel **620**.

[0186] Each release key **715** has an opening **732**. Similarly, the release sleeve **710** has an opening **722**. The opening **732** in the release key **715** and the opening **722** in the release sleeve **710** are sized and configured to receive a shear pin. The shear pin is seen at **720**. In **Figure 7A**, the shear pin **720** is held within the openings **732**, **722** by the release sleeve **710**. However, in **Figure 7B** the shear pin **720** has been sheared, and only a small portion of the pin **720** remains visible.

[0187] An outer edge of the release key **715** has a ruggled surface, or teeth. The teeth for the release key **715** are shown at **736**. The teeth **736** of the release key **715** are angled and configured to mate with a reciprocal ruggled surface within the piston housing **640**. The mating ruggled surface (or teeth) for the piston housing **640** are shown at **646**. The teeth **646** reside on an inner face of the piston housing **640**. When engaged, the teeth **736**, **646** prevent movement of the piston housing **640** relative to the piston mandrel **620** or the inner mandrel **610**. Preferably, the mating ruggled surface or teeth **646** reside on the inner face of a separate, short outer release sleeve, which is then threaded to the piston housing **640**.

[0188] Returning now to **Figures 6A** and **6B**, the packer **600** includes a centralizing member **650**. The centralizing member **650** is actuated by the movement of the piston housing **640**. The centralizing member **650** may be, for example, as described in WO 2009/071874, entitled "Improved Centraliser," which an international filing date of November 28, 2008.

[0189] The packer **600** further includes a sealing element **655**. As the centralizing member **650** is actuated and centralizes the packer 600 within the surrounding wellbore, the piston housing **640** continues to actuate the sealing element **655** as described in WO 2007/107773, entitled "Improved Packer," which has an international filing date of March 22, 2007.

[0190] In **Figure 6A**, the centralizing member **650** and sealing element **655** are in their run-in position. In **Figure 6B**, the centralizing member **650** and connected sealing element **655** have been actuated. This means the piston housing **640** has moved along the piston mandrel **620**, causing both the centralizing member **650** and the sealing element **655** to engage the surrounding wellbore wall.

[0191] An anchor system as described in WO 2010/084353 may be used to prevent the piston housing **640** from going backward. This prevents contraction of the cup-type element **655**.

[0192] As noted, movement of the piston housing **640** takes place in response to hydrostatic pressure from wellbore fluids, including the gravel slurry. In the run-in position of the packer **600** (shown in **Figure 6A**), the piston housing **640** is held in place by the release sleeve **710** and associated piston key **715**. This position is shown in **Figure 7A**. In order to set the packer **600** (in accordance with **Figure 6B**), the release sleeve **710** must be moved out of the way of the release key **715** so that the teeth **736** of the release key **715** are no longer engaged with the teeth **646** of the piston housing **640**. This position is shown in **Figure 7B**.

[0193] To move the release the release sleeve **710**, a setting tool is used. An illustrative setting tool is shown at **750** in **Figure 7C**. The setting tool **750** defines a short cylindrical body **755**. Preferably, the setting tool **750** is run into the wellbore with a washpipe string (not shown). Movement of the washpipe string along the wellbore can be controlled at the surface.

[0194] An upper end **752** of the setting tool **750** is made up of several radial collet fingers **760**. The collet fingers **760** collapse when subjected to sufficient inward force. In operation, the collet fingers **760** latch into a profile **724** formed along the release sleeve **710**. The collet fingers **760** include raised surfaces **762** that mate with or latch into the profile **724** of the release key **710**. Upon latching, the setting tool **750** is pulled or raised within the wellbore. The setting tool **750** then pulls the release sleeve **710** with sufficient force to cause the shear pins **720** to shear. Once the shear pins **720** are sheared, the release sleeve **710** is free to translate upward along the inner surface **608** of the inner mandrel **610**.

[0195] As noted, the setting tool **750** may be run into the wellbore with a washpipe. The setting tool **750** may simply be a profiled portion of the washpipe body. Preferably, however, the setting tool **750** is a separate tubular body **755** that is threadedly connected to the washpipe. In **Figure 7C**, a connection tool is provided at **770**. The connection tool **770** includes external threads **775** for connecting to a drill string or other run-in tubular. The connection tool **770** extends into the body **755** of the setting tool **750**. The connection tool **770** may extend all the way through the body **755** to connect to the washpipe or other device, or it may connect to internal threads (not seen) within the body **755** of the setting tool **750**.

[0196] Returning to **Figures 7A** and **7B**, the travel of the release sleeve **710** is limited. In this respect, a first or top end **726** of the release sleeve **710** stops against the shoulder **606** along the inner surface **608** of the inner mandrel **610**. The length of the release sleeve **710** is short enough to allow the release sleeve **710** to clear the opening **732** in the release

key **715**. When fully shifted, the release key **715** moves radially inward, pushed by the ruggled profile in the piston housing **640** when hydrostatic pressure is present.

[0197] Shearing of the pin **720** and movement of the release sleeve **710** also allows the release key **715** to disengage from the piston housing **640**. The shoulder recess **624** is dimensioned to allow the shoulder **734** of the release key **715** to drop or to disengage from the teeth **646** of the piston housing **640** once the release sleeve **710** is cleared. Hydrostatic pressure then acts upon the piston housing **640** to translate it downward relative to the piston mandrel **620**.

[0198] After the shear pins **720** have been sheared, the piston housing **640** is free to slide along an outer surface of the piston mandrel **620**. To accomplish this, hydrostatic pressure from the annulus **625** acts upon a shoulder **642** in the piston housing **640**. This is seen best in **Figure 6B**. The shoulder **642** serves as a pressure-bearing surface. A fluid port **628** is provided through the piston mandrel **620** to allow fluid to access the shoulder **642**. Beneficially, the fluid port **628** allows a pressure higher than hydrostatic pressure to be applied during gravel packing operations. The pressure is applied to the piston housing **640** to ensure that the packer elements **655** engage against the surrounding wellbore.

[0199] The packer **600** also includes a metering device. As the piston housing **640** translates along the piston mandrel **620**, a metering orifice **664** regulates the rate the piston housing translates along the piston mandrel therefore slowing the movement of the piston housing and regulating the setting speed for the packer **600**.

[0200] To further understand features of the illustrative mechanically-set packer **600**, several additional cross-sectional views are provided. These are seen at **Figures 6C**, **6D**, **6E**, and **6F**.

[0201] First, **Figure 6C** is a cross-sectional view of the mechanically-set packer of **Figure 6A**. The view is taken across line **6C-6C** of **Figure 6A**. Line **6C-6C** is taken through one of the torque bolts **636**. The torque bolt **636** connects the coupling **630** to the NACA key **634**.

[0202] **Figure 6D** is a cross-sectional view of the mechanically-set packer of **Figure 6A**. The view is taken across line **6D-6D** of **Figure 6B**. Line **6D-6D** is taken through another of the torque bolts **632**. The torque bolt **632** connects the coupling **630** to the box connector **614**, which is threaded to the inner mandrel **610**.

[0203] **Figure 6E** is a cross-sectional view of the mechanically-set packer **600** of **Figure 6A**. The view is taken across line **6E-6E** of **Figure 6A**. Line **6E-E** is taken through the

release key **715**. It can be seen that the release key **715** passes through the piston mandrel **620** and into the inner mandrel **610**. It is also seen that the alternate flow channel **625** resides between the release keys **715**.

[0204] **Figure 6F** is a cross-sectional view of the mechanically-set packer **600** of **Figure 6A**. The view is taken across line **6F-6F** of **Figure 6B**. Line **6F-6F** is taken through the fluid ports **628** within the piston mandrel **620**. As the fluid moves through the fluid ports **628** and pushes the shoulder **642** of the piston housing **640** away from the ports **628**, an annular gap **672** is created and elongated between the piston mandrel **620** and the piston housing **640**.

[0205] Once the fluid bypass packer **600** is set, gravel packing operations may commence. **Figures 8A** through **8N** present stages of a gravel packing procedure, in one embodiment. The gravel packing procedure uses a packer assembly having alternate flow channels. The packer assembly may be in accordance with packer assembly **300** of **Figure 3A**. The packer assembly **300** will have mechanically-set packers **304**. These mechanically-set packers may be in accordance with packer **600** of **Figures 6A** and **6B**.

[0206] In **Figures 8A** through **8N**, sand control devices are utilized with an illustrative gravel packing procedure in a conditioned drilling mud. The conditioned drilling mud may be a non-aqueous fluid (NAF) such as a solids-laden oil-based fluid. Optionally, a solids-laden water-based fluid is also used. This process, which is a two-fluid process, may include techniques similar to the process discussed in International Pat. Appl. No. WO/2004/079145 and related U.S. Pat. No. 7,373,978, each of which is hereby incorporated by reference. However, it should be noted that this example is simply for illustrative purposes, as other suitable processes and fluids may be utilized.

[0207] In **Figure 8A**, a wellbore **800** is shown. The illustrative wellbore **800** is a horizontal, open-hole wellbore. The wellbore 800 includes a wall **805**. Two different production intervals are indicated along the horizontal wellbore **800**. These are shown at **810** and **820**. Two sand control devices **850** have been run into the wellbore **800**. Separate sand control devices **850** are provided in each production interval **810**, **820**.

[0208] Each of the sand control devices **850** is comprised of a base pipe **854** and a surrounding sand screen **856**. The base pipes **854** have slots or perforations to allow fluid to flow into the base pipe **854**. The sand control devices **850** also each include alternate flow paths. These may be in accordance with shunt tubes **218** from either **Figure 4B** or **Figure 5B**. Preferably, the shunt tubes are internal shunt tubes disposed between the base pipes **854** and the sand screens **856** in the annular region shown at **852**.

[0209] The sand control devices **850** are connected via an intermediate packer assembly **300**. In the arrangement of **Figure 8A**, the packer assembly **300** is installed at the interface between production intervals **810** and **820**. More than one packer assembly **300** can be incorporated. The connection between the sand control devices **850** and a packer assembly **300** may be in accordance with U.S. Patent No. 7,661,476, discussed above.

[0210] In addition to the sand control devices **850**, a washpipe **840** has been lowered into the wellbore **800**. The washpipe **840** is run into the wellbore **800** below a crossover tool or a gravel pack service tool (not shown) which is attached to the end of a drill pipe **835** or other working string. The washpipe **840** is an elongated tubular member that extends into the sand screens **850**. The washpipe **840** aids in the circulation of the gravel slurry during a gravel packing operation, and is subsequently removed. Attached to the washpipe **840** is a shifting tool, such as the shifting tool **750** presented in **Figure 7C**. The shifting tool **750** is positioned below the packer **300**.

[0211] In **Figure 8A**, a crossover tool **845** is placed at the end of the drill pipe **835**. The crossover tool **845** is used to direct the injection and circulation of the gravel slurry, as discussed in further detail below.

[0212] A separate packer **815** is connected to the crossover tool **845**. The packer **815** and connected crossover tool **845** are temporarily positioned within a string of production casing **830**. Together, the packer **815**, the crossover tool **845**, the elongated washpipe **840**, the shifting tool **750**, and the gravel pack screens **850** are run into the lower end of the wellbore **800**. The packer **815** is then set in the production casing **830**. The crossover tool **845** is then released from the packer **815** and is free to move as shown in **Figure 8B**.

[0213] Returning to **Figure 8A**, a conditioned NAF (or other drilling mud) **814** is placed in the wellbore **800**. Preferably, the drilling mud **814** is deposited into the wellbore **800** and delivered to the open-hole portion before the drill string **835** and attached sand screens **850** and washpipe **840** are run into the wellbore **800**. The drilling mud **814** may be conditioned over mesh shakers (not shown) before the sand control devices **850** are run into the wellbore **800** to reduce any potential plugging of the sand control devices **850**.

[0214] In **Figure 8B**, the packer **815** is set in the production casing string **830**. This means that the packer **815** is actuated to extend slips and an elastomeric sealing element against the surrounding casing string **830**. The packer **815** is set above the intervals **810** and **820**, which are to be gravel packed. The packer **815** seals the intervals **810** and **820** from the portions of the wellbore **800** above the packer **815**.

[0215] After the packer **815** is set, as shown in **Figure 8C**, the crossover tool **845** is shifted up into a reverse position. Circulation pressures can be taken in this position. In most embodiments, a carrier fluid **812** is pumped down the drill pipe **835** and placed into an annulus between the drill pipe **835** and the surrounding production casing **830** above the packer **815**. The carrier fluid is a gravel carrier fluid, which is the liquid component of the gravel packing slurry. (Those skilled in the art will recognize that in some embodiments a displacing fluid that is distinct from the carrier fluid may be used to displace or assist in displacing the drilling fluid, prior to the carrier fluid being introduced into the wellbore which then in turn displaces the displacement fluid. The displacement fluid may comprise the carrier fluid and/or another fluid composition. Such methods and embodiments are also within the scope of this invention.) The displacing or carrier fluid **812** displaces the conditioned drilling fluid **814** above the packer **815**, which again may be an oil-based fluid such as the conditioned NAF. The carrier fluid **812** displaces the drilling fluid **814** in the direction indicated by arrows "**C**."

[0216] Next, in **Figure 8D**, the crossover tool **845** is shifted back into a circulating position. This is the position used for circulating gravel pack slurry, and is sometimes referred to as the gravel pack position. The earlier placed carrier fluid **812** is pumped down the annulus between the drill pipe **835** and the production casing **830**. The carrier fluid **812** is further pumped down the washpipe **840**. This pushes the conditioned NAF **814** down the washpipe **840**, out the sand screens **856**, sweeping the open-hole annulus between the sand screens **856** and the surrounding wall **805** of the open-hole portion of the wellbore **800**, through the crossover tool **845**, and into the drill pipe **835**. The flow path of the carrier fluid **812** is again indicated by the arrows "**C**."

[0217] In **Figures 8E** through **8G**, the production intervals **810**, **820** are prepared for gravel packing.

[0218] In **Figure 8E**, once the open-hole annulus between the sand screens **856** and the surrounding wall **805** has been swept with carrier fluid **812**, the crossover tool **845** is shifted back to the reverse position. Conditioned drilling fluid **814** is pumped down the annulus between the drill pipe **835** and the production casing **830** to force the carrier fluid **812** out of the drill pipe **835**, as shown by the arrows "**D**." These fluids may be removed from the drill pipe **835**.

[0219] Next, the packers **304** are set, as shown in **Figure 8F** by pulling the shifting tool located below the packer assembly **300** on the washpipe **840** and up past the packer assembly **300**. More specifically, the mechanically-set packers **304** of the packer assembly

300 are set. The packers **304** may be, for example, packer **600** of **Figures 6A** and **6B**. The packer **600** is used to isolate the annulus formed between the sand screens **856** and the surrounding wall **805** of the wellbore **800**. The washpipe **840** is lowered to a reverse position.

[0220] While in the reverse position, as shown in **Figure 8G**, the carrier fluid with gravel **816** may be placed within the drill pipe **835** and utilized to force the carrier fluid **812** up the annulus formed between the drill pipe **835** and production casing **830** above the packer **815**, as shown by the arrows "**C**."

[0221] In **Figures 8H** through **8J**, the crossover tool **845** may be shifted into the circulating position to gravel pack the first subsurface interval **810**.

[0222] In **Figure 8H**, the carrier fluid with gravel **816** begins to create a gravel pack within the production interval **810** above the packer **300** in the annulus between the sand screen **856** and the wall **805** of the open-hole wellbore **800**. The fluid flows outside the sand screen **856** and returns through the washpipe **840** as indicated by the arrows "**D**." The carrier fluid **812** in the wellbore annulus is forced into screen, through the washpipe **840**, and up the annulus formed between the drill pipe **835** and production casing **830** above the packer **815**.

[0223] In **Figure 8I**, a first gravel pack **860** begins to form above the packer **300**. The gravel pack **860** is forming around the sand screen **856** and towards the packer **815**. Carrier fluid **812** is circulated below the packer **300** and to the bottom of the wellbore **800**. The carrier fluid **812** without gravel flows up the washpipe **840** as indicated by arrows "**C**."

[0224] In **Figure 8J**, the gravel packing process continues to form the gravel pack **860** toward the packer **815**. The sand screen **856** is now being fully covered by the gravel pack **860** above the packer **300**. Carrier fluid **812** continues to be circulated below the packer **300** and to the bottom of the wellbore **800**. The carrier fluid **812** *sans* gravel flows up the washpipe **840** as again indicated by arrows "**C**."

[0225] Once the gravel pack **860** is formed in the first interval **810** and the sand screens above the packer **300** are covered with gravel, the carrier fluid with gravel **816** is forced through the shunt tubes (shown at **318** in **Figure 3B**). The carrier fluid with gravel **816** forms the gravel pack **860** in **Figures 8K** through **8N**.

[0226] In **Figure 8K**, the carrier fluid with gravel **816** now flows within the production interval **820** below the packer **300**. The carrier fluid **816** flows through the shunt tubes and packer **300**, and then outside the sand screen **856**. The carrier fluid **816** then flows in the

annulus between the sand screen **856** and the wall **805** of the wellbore **800**, and returns through the washpipe **840**. The flow of carrier fluid with gravel **816** is indicated by arrows "**D**," while the flow of carrier fluid in the washpipe **840** without the gravel is indicated at **812**, shown by arrows "**C**."

[0227] It is noted here that slurry only flows through the bypass channels along the packer sections. After that, slurry will go into the alternate flow channels in the next, adjacent screen joint. Alternate flow channels have both transport and packing tubes manifolded together at each end of a screen joint. Packing tubes are provided along the sand screen joints. The packing tubes represent side nozzles that allow slurry to fill any voids in the annulus. Transport tubes will take the slurry further downstream.

[0228] In **Figure 8L**, the gravel pack **860** is beginning to form below the packer **300** and around the sand screen **856**. In **Figure 8M**, the gravel packing continues to grow the gravel pack **860** from the bottom of the wellbore **800** up toward the packer **300**. In **Figure 8N**, the gravel pack **860** has been formed from the bottom of the wellbore **800** up to the packer **300**. The sand screen **856** below the packer **300** has been covered by gravel pack **860**. The surface treating pressure increases to indicate that the annular space between the sand screens **856** and the wall **805** of the wellbore **800** is fully gravel packed.

[0229] **Figure 8O** shows the drill string **835** and the washpipe **840** from **Figures 8A** through **8N** having been removed from the wellbore **800**. The casing **830**, the base pipes **854**, and the sand screens **856** remain in the wellbore **800** along the upper **810** and lower **820** production intervals. Packer **300** and the gravel packs **860** remain set in the open hole wellbore **800** following completion of the gravel packing procedure from **Figures 8A** through **8N**. The wellbore **800** is now ready for production operations.

[0230] As mentioned above, once a wellbore has undergone gravel packing, the operator may choose to isolate a selected interval in the wellbore, and discontinue production from that interval. To demonstrate how a wellbore interval may be isolated, **Figures 9A** and **9B** are provided.

[0231] First, **Figure 9A** is a cross-sectional view of a wellbore **900A**. The wellbore **900A** is generally constructed in accordance with wellbore **100** of **Figure 2**. In **Figure 9A**, the wellbore **900A** is shown intersecting through a subsurface interval **114**. Interval **114** represents an intermediate interval. This means that there is also an upper interval **112** and a lower interval **116** (seen in **Figure 2**, but not shown in **Figure 9A**).

[0232] The subsurface interval **114** may be a portion of a subsurface formation that once produced hydrocarbons in commercially viable quantities but has now suffered significant water or hydrocarbon gas encroachment. Alternatively, the subsurface interval **114** may be a formation that was originally a water zone or aquitard or is otherwise substantially saturated with aqueous fluid. In either instance, the operator has decided to seal off the influx of formation fluids from interval **114** into the wellbore **900A**.

[0233] A sand control device **200** has been placed in the wellbore **900A**. Sand control device **200** is in accordance with the sand control device **200** of **Figure 2**. In addition, a base pipe **205** is seen extending through the intermediate interval **114**. The base pipe **205** is part of the sand control device **200**. The sand control device **200** also includes a mesh screen, a wire-wrapped screen, or other radial filter medium **207**. The base pipe **205** and surrounding filter medium **207** preferably comprise a series of joints connected end-to-end. The joints are ideally about 5 to 45 feet in length.

[0234] It is noted here that the sand control device **200** in **Figures 9A** and **9B** may be in various forms. In some embodiments, the sand control device **200** is a sand screen such as described in U.S. Patent No. 7,464,752.

[0235] **Figure 10A** illustrates a MazeFlo™ screen **1000**, in one embodiment. The illustrative screen **1000** utilizes three concentric conduits to enable the flow of hydrocarbons while filtering out formation fines. In the arrangement of **Figure 10A**, the first conduit is a base pipe **1010**; the second conduit is a wire mesh or screen **1020**; and the third conduit is a surrounding outer wire mesh or screen **1030**.

[0236] Each conduit **1010**, **1020**, **1030** includes both permeable and impermeable sections. The permeable sections contain a filtering medium designed to retain particles larger than a predetermined size, while allowing fluids to pass through. For the first conduit **1010**, the permeable sections are represented by slots **1012**, while the impermeable section is represented by blank pipe **1014**. For the second conduit **1020**, the permeable sections are represented by wire screen or mesh **1022**, while the impermeable section is represented by blank pipe **1024**. For the third conduit **1030**, the permeable sections are represented by wire screen or mesh **1032**, while the impermeable section is represented by blank pipe **1034**. The permeable sections **1022**, **1032** are preferably a wire-wrapped screen wherein the gap between two wires is sufficient to retain most formation sand produced into wellbore **1050**. The impermeable sections **1024**, **1034** may also be wire-wrapped screens, but with the pitch of the wires so small as to effectively close off the flow of any fluids there through.

[0237] Cross-sectional views of the sand screen **1000** are provided in **Figures 10B**, **10C**, and **10D**. **Figure 10B** is a cross-sectional view taken across line **10B-10B** of **Figure 10A**; **Figure 10C** is a cross-sectional view taken across line **10C-10C** of **Figure 10A**; and **Figure 10D** is a cross-sectional view taken across line **10D-10D** of **Figure 10A**.

[0238] It can be seen in the cross-sectional views of **Figures 10B**, **10C**, and **10D** that a series of small pipes are disposed radially around the sand screen **1000**. These are shunt tubes **1040**. The shunt tubes **1040** connect with alternate flow channels to carry gravel slurry along a portion of the wellbore undergoing a gravel packing operation. Nozzles **1042** serve as outlets for gravel slurry so as to bypass any sand bridges (not shown) or packer in the wellbore annulus.

[0239] It can also be seen in the cross-sectional views of **Figures 10B**, **10C**, and **10D** that a series of optional walls **1059** is provided. The walls **1059** are substantially impermeable and serve to create compartments or flow joints **1051**, **1053** within the conduits **1020**. **1030**. . In a three-dimensional perspective, the compartments or flow joints **1051**, **1053** can be longitudinally bounded by either permeable, impermeable, partially permeable, or partially impermeable section dividers **1069**, as shown in **Figure 10A**.

[0240] Each of the compartments **1051**, **1053** (or flow joints) has at least one inlet and at least one outlet. Compartments **1051** reside around the second conduit **1020**, while compartments **1053** reside around the first conduit **1010**. The compartments **1051**, **1053** are adapted to accumulate particles to progressively increase resistance to fluid flow through the compartments **1051**, **1053** in the event a permeable section of a conduit is compromised and permits formation particles to invade.

[0241] In the arrangement of **Figure 10A**, the primary means of flow for hydrocarbons is the first conduit **1010**. A central bore **1005** is formed within the first conduit **1010** to transport hydrocarbon fluids to a surface. The central bore **1005** may be considered an additional compartment. In operation, if the outermost conduit **1030** (e.g., filter medium **1032**) fails and particulates enter the compartments **1051**, the impermeable section **1024** and the permeable section **1022** along the second conduit **1020** will nevertheless prevent sand infiltration while still allowing fluids to pass through. Continuous sand invasion increases the sand concentration in the compartments **1051** around the second conduit **1020** and subsequently increases the frictional pressure loss, resulting in gradually diminished fluid/sand flow through the permeable sections **1022** of the second conduit **1020**. Fluid production is then diverted to other permeable sections **1032** without filter media failure.

[0242] This same "backup system" also works with respect to the first conduit **1010**. If a failure occurs in the second conduit **1020** such that formation particles pass through the second conduit **1020**, then the slots in the permeable section **1012** of the first conduit **1010** will at least partially filter out formation particles.

[0243] The number of compartments **1053**, **1051** along the respective circumferences of the second **1020** and third **1030** conduits may depend on borehole size for the wellbore **1000** and the type of permeable media used. Fewer compartments would enable larger compartment size and result in fewer redundant flow paths if sand infiltrates an outermost compartment **1051**. A larger number of compartments **1053**, **1051** would decrease the compartment sizes, increase frictional pressure losses, and reduce well productivity. The operator may choose to adjust the relative sizes of the compartments **1053**, **1051**.

[0244] As shown in **Figure 10A**, preferably at least one impermeable and permeable section of the flow joints are adjacent. More preferably, at any cross-section location of the MazeFlo™ screen, at least one wall of the flow joint should be impermeable. Therefore, there is in this preferred embodiment, at least one flow joint that is impermeable is adjacent to at least one flow joint that is permeable at any cross-section location of the MazeFlo™ screen. This preferred embodiment is illustrated in Figures 10B, 10C and 10D whereby there are at any given cross-section location, at least one wall that is impermeable and at least one wall that is permeable.

[0245] Additional details concerning the sand screen **1000** is provided in U.S. Patent No. 7,464,752 cited above. Figures 4A through 4D and Figures 5A through 5D, and accompanying descriptive text found in columns 7 through 9, are incorporated herein by reference.

[0246] As an alternative to the MazeFlo™ sand screen **1000** of **Figures 10A** through **10D**, a separate sand screen design may be employed that utilizes inflow control devices, or "ICD's." ICD's are sometimes used with sand control devices to regulate flow from different production intervals downhole. Examples of known ICD's include Reslink's RESFLOW™, Baker Hughes' EQUALIZER™, and Weatherford's FLOREG™. These devices are typically used in long, horizontal, open-hole completions to balance inflow into the completion across production intervals or zones. The balanced inflow enhances reservoir management and reduces the risk of early water or gas breakthrough from a high permeability reservoir streak or from the heel of a well. Additionally, more hydrocarbons may be captured from the toe of a horizontally completed well through the application of the inflow control technology.

[0247] Because gravel packing operations generally involve passing large quantities of fluid, such as carrier fluid, through a sand screen, gravel packing with typical ICD's is not feasible because the ICD's represent a substantial restriction in fluid flow for the carrier fluid. In this respect, the gravel slurry and the production fluids use the same flow paths. Localized and reduced inflow of the carrier fluid due to ICD's may cause early bridging, loose packs, voids, and/or increased pressure requirements during gravel pack pumping. U.S. Patent No. 7,984,760 discloses three different methods for employing inflow control technology with a gravel packing operation.

[0248] **Figures 11A** through **11G** present a sand control device **1100** that may be used as part of a wellbore completion system having alternate flow channels. The sand control device **1100** is designed to be coupled to a crossover tool (not shown), and provides one or more flow paths **1114** for a carrier fluid through a sand screen **1104** and into a base pipe **1102** during gravel packing operations. The carrier or gravel pack fluid may include XC gel (xanthomonas campestris or xanthan gum), visco-elastic fluids having non-Newtonian rheology properties, a fluid viscosified with hydroxyethylcellulose (HEC) polymer, a fluid viscosified with refined xanthan polymer (e.g. Kelco's XANVIS®), a fluid viscosified with visco-elastic surfactant, and/or a fluid having a favorable rheology and sand carrying capacity for gravel packing a wellbore.

[0249] The sand screen **1104** utilizes an inflow control device as disclosed in the '092 publication. The illustrative inflow control device is a choke **1108** at one end of the screen **1100**. A swellable packer **1112** is provided at the other end of the screen **1100** to contain production fluids after gravel packing and during production.

[0250] **Figure 11A** provides a side view of the illustrative sand control device **1100**. The sand control device **1100** includes a tubular member or base pipe **1102**. The base pipe **1102** includes openings **1110** for receiving carrier fluid during a gravel packing operation, and for receiving production fluids during later production. The base pipe **1102** is surrounded by a sand screen **1104** having ribs **1105**. The sand screen **1104** includes a permeable section, such as a wire-wrapped screen or filter medium, and a non-permeable section, such as a section of blank pipe. The ribs **1105**, which are not shown in **Figure 11A** for simplicity but are seen in **Figure 11C**, are utilized to keep the sand screen **1104** a specific distance from the base pipe **1102**. The space between the base pipe **1102** and the sand screen **1104** forms an annular chamber that is accessible from the fluids external to the sand control device **1100** via the permeable section.

[0251] The sand control device **1100** has a sealing element **1112**. The sealing element **1112** is configured to provide one or more flow paths to the openings **1110** and/or inflow control device **1108** during gravel packing operations, and to block the flow path to the openings **1110** prior to or during production operations. As such, the sand control device **1100** may be utilized to enhance operations within a well.

[0252] In **Figure 11A**, the sand control device **1100** includes various components utilized to manage the flow of fluids and solids into a well. For instance, the sand control device **1100** includes a main body section **1120**, an inflow control section **1122**, a first connection section **1124**, a perforated section **1126** and a second connection section **1128**, which may be made of steel, metal alloys, or other suitable materials. The main body section **1120** may be a portion of the base pipe **1102** surrounded by a portion of the sand screen **1104**. The main body section **1120** may be configured to be a specific length, such as between 10 and 50 feet, and having specific internal and outer diameters. The inflow control section **1122** and perforated section **1126** may be other portions of the base pipe **1102** surrounded by other portions of the sand screen **1104**. The inflow control section **1122** and perforated section **1126** may be configured to be between 0.5 feet and 4 feet in length.

[0253] The first **1124** and second **1128** connection sections may be utilized to couple the sand control device **1100** to other sand control devices or piping, and may be the location of the chamber formed by the base pipe **1102** and sand screen **1104** ends. The first **1124** and second **1128** connection sections may be configured to be a specific length, such as 2 inches to 4 feet or other suitable distance, having specific internal and outer diameters.

[0254] In some embodiments, coupling mechanisms may be utilized within the first **1124** and second **1128** connection sections to form the secure and sealed connections. For instance, a first connection **1130** may be positioned within the first connection section **1124**, and a second connection **1132** may be positioned within the second connection section **1128**. These connections **1130** and **1132** may include various methods for forming connections with other devices. For example, the first connection **1130** may have internal threads and the second connection **1132** may have external threads that form a seal with other sand control devices or another pipe segment. It should also be noted that in other embodiments, the coupling mechanism for the sand control device **1100** may include connecting mechanisms as described in U.S. Pat. No. 6,464,261 and U.S. Patent No. 7,661,476, for example.

[0255] As noted, the sand control device **1100** also includes an inflow control device **1108**. The inflow control device **1108** may include one or more nozzles, orifices, tubes,

valves, tortuous paths, shaped objects or other suitable mechanisms known in the art to create a pressure drop. The inflow control device **1108** chokes flow through form pressure loss (e.g. a shaped object, nozzle) or frictional pressure loss (e.g. helical geometry/tubes).

[0256] Form pressure loss, which is based on the shape and alignment of an object relative to fluid flow, is caused by separation of fluid that is flowing over an object. This results in turbulent pockets at different pressure behind the object. The openings **1110** may be utilized to provide additional flow paths for the fluids, such as carrier fluids, during gravel packing operations because the inflow control device **1108** may restrict the placement of gravel by hindering the flow of carrier fluid into the base pipe **1102** during gravel packing operations. The number of openings **1110** in the base pipe **1102** may be selected to provide adequate inflow during the gravel packing operations to achieve partial or substantially complete gravel packing. That is, the number and size of the openings **1110** in the base pipe **1102** may be selected to provide sufficient fluid flow from the wellbore through the sand screen **1104**, which is utilized to deposit gravel in the wellbore and to form the gravel pack (not shown).

[0257] The sealing or expansion element **1112** surrounds the base pipe **1102**. The expansion element **1112** constitutes a swellable material, that is, a swelling rubber element or a swellable polymer. The swellable material may expand in the presence of a stimulus, such as water, conditioned drilling fluid, a completion fluid, a production fluid (i.e. hydrocarbons), other chemical, or any combination thereof. As an example, a swellable material may be placed in the sand control device **1100**, which expands in the presence of hydrocarbons to form a seal between the walls of the base pipe **1102** and the non-permeable section of the sand screen **1104**. Examples of swellable materials include Easy Well Solutions' Constrictor™ and SwellFix's E-ZIP™ or P-ZIP™. Other expandable materials that are sensitive to temperature and fluid chemistry may also be used. These include a shape-memory polymer such as the Baker Hughes GeoFORM™.

[0258] Alternatively, the sealing element **1112** may be activated chemically, mechanically by the removal of a washpipe, and/or via a signal, electrical or hydraulic, to isolate the openings **1110** from the fluid flow during some or all of the production operations.

[0259] The sand control device **1100** of **Figure 11A** also includes shunt tubes **1106**. The shunt tubes **1106** provide alternate flow paths for gravel slurry. Alternate flow channels gravel packing techniques with proper fluid leak-off through the sand screen **1104** have been demonstrated in the field to achieve a complete gravel pack.

[0260] **Figure 11B** is a cross-sectional view of the sand control **1100**, taken across line **11B-11B** of **Figure 11A**. Alternate flow channels or shunt tubes **1106** are seen internal to the screen **1104**. The ICD **1108** representing small flow-openings is also seen.

[0261] **Figure 11C** is a cross-sectional view of the sand control device **1100** taken across line **11C-11C** of **Figure 11A**. Ribs **1105** are shown between the shunt tubes **1106**.

[0262] **Figure 11D** is a cross-sectional view of the sand control device **1100** taken across line **11D-11D** of **Figure 11A**. The sealing element **1112** is seen around the base pipe **1102** in an un-actuated state. In this respect, during the gravel packing operations the sealing element **1112** does not block the flow path **1114** and provides an alternative flow path for carrier fluid in addition to the inflow control device **1108**. Beneficially, by utilizing the shunt tubes **1106**, longer portions of intervals may be packed without leaking off into the formation. Accordingly, the shunt tubes **1106** provide a mechanism for forming a substantially complete gravel pack along the sand screen **1104** that bypasses sand and/or gravel bridges.

[0263] **Figure 11E** is a cross-sectional view of the sand control device **1100** taken across line **11E-11E** of **Figure 11A**. The shunt tubes **1106** are shown around the permeable section of the base pipe **1102**. The shunt tubes **1106** may include packing tubes and/or transport tubes. The packing tubes may have one or more valves or nozzles (not shown) that provide a flow path for the gravel pack slurry, which includes a carrier fluid and gravel, to the annulus formed between the sand screen **1104** and the walls of a wellbore (not shown). The valves may prevent fluids from an isolated interval from flowing through the at least one shunt tubes to another interval. These shunt tubes are known in the art as further described in U.S. Patent Nos. 5,515,915, 5,890,533, 6,220,345 and 6,227,303. One of the openings **1110** is also visible in **Figure 11E**.

[0264] **Figure 11F** is another side view of the sand control device **1100** of **Figure 11A**. Production operations have begun and production fluids are flowing into the base pipe **1102** as indicated by arrow **1116**. It is seen in **Figure 11F** that the swellable packer **1112** has been actuated and blocks annular flow at one end of the sand screen **1104**. Specifically, the sealing element **1112** is blocking fluid flow through the openings **1110**. In this embodiment, the sealing element **1112** includes either multiple individual portions positioned between adjacent shunt tubes **1106**, or a single sealing element with openings for the shunt tubes **1106**.

[0265] In operation, the sand control device **1100** may be run in a water-based mud with a hydrocarbon-swellable material used for the sealing element **1112**. During screen running

and gravel packing operations, the chamber between the base pipe **1102** and the sand screen **1104** is open for fluid flow through the inflow control device **1108** and/or openings **1110**. However, during production operations, such as post-well testing operations, the sealing element **1112** comprising a hydrocarbon-swellable material (or, optionally, individual sections of swellable material) expands to close off the chamber within the perforated section **1126**. As a result, the fluid flow is limited to the inflow control device **1108** once the sealing element **1112** comprising a hydrocarbon-swellable material isolates the openings **1110**. As a result, the sand control device **1100**, which may be coupled to a production tubing string **130** or other piping, provides a specific flow path **1116** for formation fluids through the sand screen **1104** and inflow control device **1108** and into the base pipe **1102**. Thus, the openings **1110** are isolated to limit fluid flow to only the inflow control device **1108**, which is designed to manage the flow of fluids from a surrounding interval (such as interval **112** seen in **Figure 1**).

[0266] **Figure 11G** is a cross-sectional view of the sand control device **1100**, taken across line **11G-11G** of **Figure 11F**. The swellable packer **1112** is seen filling an annular region between the base pipe **1102** and the surrounding screen **1104**.

[0267] Additional details concerning the sand control device **1100** are described in U.S. Patent Publ. No. 2009/0008092. Specifically, paragraphs 0054 through 0057 are incorporated herein by reference.

[0268] Other arrangements for a swellable inflow control device are also provided in U.S. Patent Publ. No. 2009/0008092. Paragraph 0058 and accompanying Figures 5A through 5F describe an embodiment for a swellable packer wherein the sealing element and the shunt tubes are configured to engage ribs radially spaced around the base pipe. Paragraphs 0059 through 0061 and accompanying Figures 6A through 6G describe an embodiment for a swellable packer wherein the shunt tubes are external to the sand screen, providing an eccentric configuration. These portions of U.S. Patent Publ. No. 2009/0008092 are likewise incorporated herein by reference.

[0269] U.S. Patent Publ. No. 2009/0008092 discloses two other ways of providing ICD's for a gravel pack for use in an open hole completion. Once such way involves the use of a flow-through conduit. The conduit runs along and internal to the sand screen. Paragraphs 0072 and accompanying Figures 9A through 9E describe such an embodiment using internal shunt tubes. Paragraphs 0073 and 0074 and accompanying Figures 10A through 10C describe such an embodiment using internal shunt tubes. These portions of U.S. Patent Publ. No. 2009/0008092 are likewise incorporated herein by reference.

[0270] Another such way involves the use of a sleeve. The sleeve may slide or it may rotate to selectively cover all or a portion of openings **1110**. In this manner, inflow control is provided. Paragraphs 0075 through 0080 and accompanying Figures 11A through 11F describe the use of a sleeve. These portions of U.S. Patent Publ. No. 2009/0008092 are likewise incorporated herein by reference.

[0271] Returning now to **Figure 9A**, the wellbore **900A** has an upper packer assembly **210'** and a lower packer assembly **210''**. The upper packer assembly **210'** is disposed near the interface of the upper interval **112** and the intermediate interval **114**, while the lower packer assembly **210''** is disposed near the interface of the intermediate interval **114** and the lower interval **116**. Each packer assembly **210'**, **210''** is preferably in accordance with packer assembly **300** of **Figures 3A** and **3B**. In this respect, the packer assemblies **210'**, **210''** will each have opposing mechanically-set packers **304**. Optionally, the packer assemblies **210'**, **210''** will also each have an intermediate swellable packer **308**. The mechanically-set packers are shown in **Figure 9A** at **212** and **214**, while the intermediate swellable packer is shown at **216**. The mechanically-set packers **212**, **214** may be in accordance with packer **600** of **Figures 6A** and **6B**.

[0272] The dual packers **212**, **214** are mirror images of each other, except for the release sleeves (e.g., release sleeve **710** and associated shear pin **720**). As noted above, unilateral movement of a shifting tool (such as shifting tool **750**) shears the shear pins **720** and moves the release sleeves **710**. This allows the packer elements **655** to be activated in sequence, the lower one first, and then the upper one.

[0273] The wellbore **900A** is completed as an open-hole completion. A gravel pack has been placed in the wellbore **900A** to help guard against the inflow of granular particles. Gravel packing is indicated as spackles in the annulus **202** between the filter media **207** of the sand screen **200** and the surrounding wall **201** of the wellbore **900A**.

[0274] In the arrangement of **Figure 9A**, the operator desires to continue producing formation fluids from upper **112** and lower **116** intervals while sealing off intermediate interval **114**. The upper **112** and lower **116** intervals are formed from sand or other rock matrix that is permeable to fluid flow. To accomplish this, a straddle packer **905** has been placed within the sand screen **200**. The straddle packer **905** is placed substantially across the intermediate interval **114** to prevent the inflow of formation fluids from the intermediate interval **114**.

[0275] The straddle packer **905** comprises a mandrel **910**. The mandrel **910** is an elongated tubular body having an upper end adjacent the upper packer assembly **210'**, and

a lower end adjacent the lower packer assembly **210''**. The straddle packer **905** also comprises a pair of annular packers. These represent an upper packer **912** adjacent the upper packer assembly **210'**, and a lower packer **914** adjacent the lower packer assembly **210''**. The novel combination of the upper packer assembly **210'** with the upper packer **912** and the lower packer assembly **210''** with the lower packer **914** allows the operator to successfully isolate a subsurface interval such as intermediate interval **114** in an open-hole completion.

[0276] Another technique for isolating an interval along an open-hole formation is shown in **Figure 9B**. **Figure 9B** is a side view of a wellbore **900B**. Wellbore **900B** may again be in accordance with wellbore **100** of **Figure 2**. Here, the lower interval **116** of the open-hole completion is shown. The lower interval **116** extends essentially to the bottom **136** of the wellbore **900B** and is the lowermost zone of interest.

[0277] In this instance, the subsurface interval **116** may be a portion of a subsurface formation that once produced hydrocarbons in commercially viable quantities but has now suffered significant water or hydrocarbon gas encroachment. Alternatively, the subsurface interval **116** may be a formation that was originally a water zone or aquitard or is otherwise substantially saturated with aqueous fluid. In either instance, the operator has decided to seal off the influx of formation fluids from the lower interval **116** into the wellbore **100**.

[0278] To accomplish this, a plug **920** has been placed within the wellbore **100**. Specifically, the plug **920** has been set in the mandrel **215** supporting the lower packer assembly **210''**. Of the two packer assemblies **210'**, **210''**, only the lower packer assembly **210''** is seen. By positioning the plug **920** in the lower packer assembly **210''**, the plug **920** is able to prevent the flow of formation fluids up the wellbore **200** from the lower interval **116**.

[0279] It is noted that in connection with the arrangement of **Figure 9B**, the intermediate interval **114** may comprise a shale or other rock matrix that is substantially impermeable to fluid flow. In this situation, the plug **920** need not be placed adjacent the lower packer assembly **210''**; instead, the plug **920** may be placed anywhere above the lower interval **116** and along the intermediate interval **114**. Further, in this instance the upper packer assembly **210'** need not be positioned at the top of the intermediate interval **114**; instead, the upper packer assembly **210'** may also be placed anywhere along the intermediate interval **114**. If the intermediate interval **114** is comprised of unproductive shale, the operator may choose to place blank pipe across this region, with alternate flow channels, i.e. transport tubes, along the intermediate interval **114**.

[0280] A method for completing an open-hole wellbore is also provided herein. The method is presented in **Figure 12**. **Figure 12** provides a flow chart presenting steps for a method **1200** of completing an open-hole wellbore, in various embodiments.

[0281] The method **1200** first includes providing a packer. This is shown at Box **1210**. The packer may be in accordance with packer **600** of **Figures 6A** and **6B**. Thus, the packer is a mechanically-set packer that is set against an open-hole wellbore to seal an annulus.

[0282] Fundamentally, the packer will have an inner mandrel, and alternate flow channels around the inner mandrel. The packer may further have a movable piston housing and an elastomeric sealing element. The sealing element is operatively connected to the piston housing. This means that sliding the movable piston housing along the packer (relative to the inner mandrel) will actuate the sealing element into engagement with the surrounding wellbore.

[0283] The packer may also have a port. The port is in fluid communication with the piston housing. Hydrostatic pressure within the wellbore communicates with the port. This, in turn, applies fluid pressure to the piston housing. Movement of the piston housing along the packer in response to hydrostatic pressure causes the elastomeric sealing element to be expanded into engagement with the surrounding wellbore.

[0284] It is preferred that the packer also have a centralizing system. An example is the centralizer **650** of **Figures 6A** and **6B**. It is also preferred that mechanical force used to actuate the sealing element be applied by the piston housing through the centralizing system. In this way, both the centralizers and the sealing element are set through the same hydrostatic force.

[0285] The method **1200** also includes connecting the packer to a sand screen. This is provided at Box **1220**. The sand screen comprises a base pipe and a surrounding filter medium. The sand screen is equipped with alternate flow channels.

[0286] Preferably, the packer is one of two mechanically-set packers having cup-type sealing elements. The two packers form a packer assembly. The packer assembly is placed within a string of sand screens or blanks equipped with alternate flow channels. Preferably, a swellable packer is placed between the two mechanically-set packers.

[0287] As an alternative, the packer is a first zonal isolation tool, and is connected to a sand screen. A second zonal isolation tool is used as a back-up, and is a gravel-based zonal isolation tool. The use of a gravel-based zonal isolation tool is described below in connection with **Figures 14A** and **14B**.

[0288] Regardless of the arrangement, the method **1200** also includes running the packer and the connected sand screen into a wellbore. This is shown at Box **1230**. In addition, the method **1200** includes running a setting tool into the wellbore. This is provided at Box **1240**. Preferably, the packer and connected sand screen are run first, followed by the setting tool. The setting tool may be in accordance with exemplary setting tool **750** of **Figure 7C**. Preferably, the setting tool is part of or is run in with a washpipe.

[0289] The method **1200** next includes moving the setting tool through the inner mandrel of the packer. This is shown at Box **1250**. The setting tool is translated within the wellbore through mechanical force. Preferably, the setting tool is at the end of a working string such as coiled tubing.

[0290] Movement of the setting tool through the inner mandrel causes the setting tool to shift a sleeve along the inner mandrel. In one aspect, shifting the sleeve will shear one or more shear pins. In any aspect, shifting the sleeve releases the piston housing, permitting the piston housing to shift or to slide along the packer relative to the inner mandrel. As noted above, this movement of the piston housing permits the sealing element to be actuated against the wall of the surrounding open-hole wellbore.

[0291] In connection with the moving step of Box **1250**, the method **1200** also includes communicating hydrostatic pressure to the port. This is seen in Box **1260**. Communicating hydrostatic pressure means that the wellbore has sufficient energy stored in a column of fluid to create a hydrostatic head, wherein the hydrostatic head acts against a surface or shoulder on the piston housing. The hydrostatic pressure includes pressure from fluids in the wellbore, whether such fluids are completion fluids or reservoir fluids, and may also include pressure contributed downhole by a reservoir. Because the shear pins (including set screws) have been sheared, the piston housing is free to move.

[0292] The method **1200** also includes injecting a gravel slurry into an annular region formed between the sand screen and the surrounding formation. This is provided at Box **1270** of **Figure 12**. In addition, the method **1200** includes injecting the gravel slurry through the alternate flow channels. This allows the gravel slurry to at least partially bypass the sealing element so that the wellbore is gravel-packed within the annular region below the packer. This is shown at Box **1280**.

[0293] A separate method is provided herein for completing a wellbore. This method is shown in **Figure 13** as method **1300**. **Figure 13** is also a flowchart showing steps for the method **1300**.

[0294] The method **1300** first includes providing a zonal isolation apparatus. This is shown at Box **1310**. The zonal isolation apparatus is preferably in accordance with the components described above in connection with **Figure 2**. In this respect, the zonal isolation apparatus may first include a sand screen. The sand screen will represent a base pipe and a surrounding mesh or wound wire. The zonal isolation apparatus will also have at least one packer assembly. The packer assembly will have at least one mechanically-set packer, with the mechanically-set packer having alternate flow channels.

[0295] Preferably, the packer assembly will have at least two mechanically set packers and an intermediate elongated swellable packer. Alternate flow channels will travel through each of the mechanically-set packers and the intermediate swellable packer element. Preferably, the zonal isolation apparatus will comprise at least two packer assemblies separated by sand screen joints.

[0296] The method **1300** also includes running the zonal isolation apparatus into the wellbore. The step of running the zonal isolation apparatus into the wellbore is shown at Box **1320**. The zonal isolation apparatus is run into a lower portion of the wellbore, which is preferably completed as an open-hole.

[0297] The open-hole portion of the wellbore may be completed substantially vertically. Alternatively, the open-hole portion may be deviated, or even horizontal.

[0298] The method **1300** also includes positioning the zonal isolation apparatus in the wellbore. This is shown in **Figure 13** at Box **1330**. The step **1330** of positioning the zonal isolation apparatus is preferably done by hanging the zonal isolation apparatus from a lower portion of a string of production casing. The apparatus is positioned such that the sand screen is adjacent one or more selected production intervals along the open-hole portion of the wellbore. Further, a first of the at least one packer assembly is positioned above or proximate the top of a selected subsurface interval.

[0299] In one embodiment, the open-hole wellbore traverses through three separate intervals. These include an upper interval from which hydrocarbons are produced, and a lower interval from which hydrocarbons are no longer being produced in economically viable volumes. Such intervals may be formed of sand or other permeable rock matrix. The intervals may also include an intermediate interval from which hydrocarbons are not produced. The formation along the intermediate interval may be formed of shale or other substantially impermeable material. The operator may choose to position the first of the at least one packer assembly near the top of the lower interval or anywhere along the non-permeable intermediate interval.

[0300] In one aspect, the at least one packer assembly is placed proximate a top of an intermediate interval. Optionally, a second packer assembly is positioned proximate the bottom of a selected interval such as the intermediate interval. This is shown in Box **1335**.

[0301] The method **1300** next includes setting the mechanically set packer elements in each of the at least one packer assembly. This is provided in Box **1340**. Mechanically setting the upper and lower packer elements means that an elastomeric (or other) sealing member engages the surrounding wellbore wall. The packer elements isolate an annular region formed between the sand screens and the surrounding subsurface formation above and below the packer assemblies.

[0302] Beneficially, the step of setting the packer of Box **1340** is provided before slurry is injected into the annular region. Setting the packer provides a hydraulic and mechanical seal to the wellbore before any gravel is placed around the elastomeric element. This provides a better seal during the gravel packing operation.

[0303] The step of Box **1340** may be accomplished by using the packer **600** of **Figures 6A** and **6B**. The open-hole, mechanically-set packer **600** enables gravel pack completions to gain the current flexibility of standalone screen (SAS) applications by providing future zonal isolation of unwanted fluids while enjoying the benefits of an alternate flow channel gravel pack completion.

[0304] The method **1300** for completing an open-hole wellbore also includes injecting a particulate slurry into the annular region. This is demonstrated in Box **1350**. The particulate slurry is made up of a carrier fluid and sand (and/or other) particles. One or more alternate flow channels allow the particulate slurry to bypass the sealing elements of the mechanically-set packers. In this way, the open-hole portion of the wellbore is gravel-packed below, or above and below (but not between), the mechanically-set packer elements.

[0305] For the method **1300**, the sequence for annulus pack-off may vary. For example, if a premature sand bridge is formed during gravel packing, the annulus above the bridge will continue to be gravel packed via fluid leak-off through the sand screen due to the alternate flow channels. In this respect, some slurry will flow into and through the alternate flow channels to bypass the premature sand bridge and deposit a gravel pack. As the annulus above the premature sand bridge is nearly completely packed, slurry is increasingly diverted into and through the alternate flow channels. Here, both the premature sand bridge and the packer will be bypassed so that the annulus is gravel packed below the packer.

[0306] It is also possible that a premature sand bridge may form below the packer. Any voids above or below the packer will eventually be packed by the alternate flow channels until the entire annulus is fully gravel packed.

[0307] During pumping operations, once gravel covers the screens above the packer, slurry is diverted into the shunt tubes, then passes through the packer, and continues to pack below the packer via the shunt tubes (or alternate flow channels) with side ports allowing slurry to exit into the wellbore annulus. The hardware provides the ability to seal off bottom water, selectively complete or gravel pack targeted intervals, perform a stacked open-hole completion, or isolate a gas/water-bearing sand following production. The hardware further allows for selective stimulation, selective water or gas injection, or selective chemical treatment for damage removal or sand consolidation.

[0308] The method **1300** further includes producing production fluids from intervals along the open-hole portion of the wellbore. This is provided at Box **1360**. Production takes place for a period of time.

[0309] In one embodiment of the method **1300**, flow from a selected interval may be sealed from flowing into the wellbore. For example, a plug may be installed in the base pipe of the sand screen above or near the top of a selected subsurface interval. This is shown at Box **1070**. Such a plug may be used at or below the lowest packer assembly, such as the second packer assembly from step **1335**.

[0310] In another example, a straddle packer is placed along the base pipe along a selected subsurface interval to be sealed. This is shown at Box **1375**. Such a straddle may involve placement of sealing elements adjacent upper and lower packer assemblies (such as packer assemblies **210'**, **210''** of **Figure 2** or **Figure 9A**) along a mandrel.

[0311] It is noted that the mechanically-set packers used in connection with the methods **1200** and **1300** above are complex downhole tools. The tools must be designed not only to withstand the high temperatures and pressures of a downhole environment, but must be reliable enough to provide at least a temporary wellbore seal while a gravel packing procedure is being undertaken at high fluid velocities. As such, the mechanically-set packer is an expensive device. This expense is increased when a packer assembly is employed that includes two mechanically-set packers plus an intermediate swellable packer.

[0312] Because of the cost, in some instances the operator may wish to utilize a less-expensive, gravel-based zonal isolation system in lieu of a second mechanically-set packer. Such a system relies upon a long blank pipe surrounded by densely packed sand. Such a

system is described in WO Pat. Publ. No. 2010/120419 entitled "Systems and Methods for Providing Zonal Isolation in Wells."

[0313] **Figure 14A** and **14B** present side and cross-sectional views of a gravel-packing assembly **1400** for providing back-up zonal isolation. The assembly defines a tubular body having an upstream manifold **1402** at a first end, and a downstream manifold **1410** at a second end. Intermediate the upstream manifold **1402** and the downstream manifold **1410** is an elongated base pipe **1430**.

[0314] In operation, gravel slurry is pumped downhole until it reaches the upstream manifold **1402**. The gravel slurry is then distributed through both a gravel packing conduit **1404** and a transport conduit **1408**. The gravel packing conduit **1404** serves to deliver slurry into an annular region between the gravel-packing assembly **1400** and the surrounding wellbore (not shown), while the transport conduit **1408** delivers a portion of the gravel slurry further downhole. Thus, the gravel packing conduit **1404** and the transport conduit **1408** serve as classic shunt tubes.

[0315] The gravel packing conduit **1404** contains a number of leak-off ports **1412**. As gravel slurry enters the gravel packing conduit, the slurry exits the ports **1412** and fills the annular space, typically from the bottom (or toe) of the well to the top (or heel) of the well. A plug **1414** prevents gravel slurry from bypassing the ports **1412**.

[0316] The transport conduit **1408** moves slurry from the upstream manifold **1402** to the downstream manifold **1410**. In this way, any sand bridges along the blank pipe **1430** are bypassed in a downstream flow path. Preferably, the transport conduit **1408** and the adjacent blank pipe **1430** run together in 40 foot sections.

[0317] The gravel-packing assembly **1400** also includes a leak-off conduit **1406**. The leak-off conduit **1406** represents a wire-wrapped screen or other filtering arrangement. A restriction **1416** between the leak-off conduit **1406** and the upstream manifold **1402** minimizes the gravel slurry entering the leak-off conduit **1406** from the upstream manifold **1402**. The leak-off conduit **1406** receives water (or carrier fluid) during the gravel-packing operation, and merges the water (or carrier fluid) with the gravel slurry in the downstream manifold **1410**. Alternatively, the leak-off conduit **1406** may be in direct fluid communication with the transport conduit **1408** above the downstream manifold **1410**. At the same time, the leak-off conduit **1406** filters out sand particles, leaving the gravel-pack in place around the blank pipe **1430**.

[0318] The gravel-packing assembly **1400** is designed to threadedly connect to the base pipe of a section of sand screen at one end. At another end, the gravel-packing assembly **1400** is connected to a mechanically-set packer **600**. The gravel-packing assembly **1400** at least partially restricts the flow of production fluids between production zones or geologic intervals in an open-hole wellbore. The gravel-based isolation system of the assembly **1400** may not be a primary isolation tool, but it does substantially restrict the flow in the event of failure of a cup-type element **655**. Ideally, the gravel-packing assembly **1400** is at least 40 feet, and more preferably at least 80 feet, in order to provide optimum fluid isolation.

[0319] Additional details concerning the design and operation of gravel-based zonal isolation systems are found in WO Pat. Publ. No. 2010/120419. This application is incorporated herein by reference in its entirety.

[0320] While it will be apparent that the inventions herein described are well calculated to achieve the benefits and advantages set forth above, it will be appreciated that the inventions are susceptible to modification, variation and change without departing from the spirit thereof. Improved methods for completing an open-hole wellbore are provided so as to seal off one or more selected subsurface intervals. An improved zonal isolation apparatus is also provided. The inventions permit an operator to produce fluids from or to inject fluids into a selected subsurface interval.

CLAIMS

1. A method for completing a wellbore in a subsurface formation, the method comprising:

providing a packer assembly having a first mechanically-set packer as a first zonal isolation tool, and a second zonal isolation tool, wherein each of the first and second zonal isolation tools comprises an internal bore for receiving production fluids, and alternate flow channels, and the first mechanically-set packer comprises:

an inner mandrel as the internal bore,

alternate flow channels along the inner mandrel,

a movable piston housing around the inner mandrel,

one or more flow ports providing fluid communication between the alternate flow channels and pressure-bearing surface of the piston housing; and

a sealing element external to the inner mandrel;

connecting the packer assembly to a sand screen, the sand screen comprising a base pipe, a surrounding filter medium, and alternate flow channels, wherein:

the base pipe has an inner bore in fluid communication with the internal bore of the first and second zonal isolation tools, and

the alternate flow channels of the sand screen are in fluid communication with alternate flow channels of the first and second zonal isolation tools;

running the packer assembly and connected sand screen into the wellbore;

running a setting tool into the inner mandrel of the first mechanically-set packer;

moving the setting tool along the inner mandrels, thereby releasing the movable piston housing on the first mechanically-set packer; and

communicating hydrostatic pressure to the piston housings through the one or more flow ports, thereby allowing the piston housings to slide, and thereby actuating the sealing element against the surrounding wellbore; and

injecting a gravel slurry into the wellbore; and

injecting the gravel slurry at least partially through the alternate flow channels to allow the gravel slurry to bypass the sealing element so that the

wellbore is gravel-packed within an annular region between the sand screen and the surrounding formation below the packer assembly.

2. The method of claim 1, wherein the filtering medium of the sand screen comprises a wire-wrapped screen, a membrane screen, an expandable screen, a sintered metal screen, a wire-mesh screen, a shape memory polymer, or a pre-packed solid particle bed.

3. The method of claim 1 or 2, wherein the second zonal isolation tool is a gravel-based zonal isolation tool comprising:

an upstream manifold configured to receive the gravel slurry;

a gravel-packing conduit in fluid communication with the upstream manifold and extending longitudinally away from the upstream manifold, the gravel-packing conduit having a plurality of ports to place the gravel-packing conduit in fluid communication with an annulus between the second zonal isolation tool and the surrounding wellbore, and having a plug proximate a lower end of the gravel-packing conduit to isolate the gravel-packing conduit from a downstream flow path;

a transport conduit in fluid communication with the upstream manifold and in fluid communication with the downstream flow path, the transport conduit serving as the alternate flow channels for the second zonal isolation tool; and

a leak-off conduit comprising permeable media in order to place the leak-off conduit in fluid communication with the annulus but filtering gravel-packing particles during a gravel-packing procedure, the leak-off conduit comprising a longitudinal tubular body in fluid communication with the downstream flow path.

4. The method of claim 3, wherein the gravel-based zonal isolation tool is at least 40 feet in length.

5. The method of claim 1 or 2, wherein the second zonal isolation tool comprises a second mechanically-set packer constructed in accordance with the first mechanically-set packer, and being arranged within the packer assembly as substantially a mirror image of the first mechanically-set packer.

6. The method of claim 1 or 2, wherein the second zonal isolation tool comprises a swellable packer adjacent the first mechanically-set packer.

7. The method of claim 1 or 2, wherein:

the second zonal isolation tool comprises a second mechanically-set packer constructed in accordance with the first mechanically-set packer; and

the packer assembly further comprises a swellable packer intermediate the first and second mechanically-set packers, the swellable packer having alternate flow channels fluidly connected with the alternate flow channels of the first and second mechanically-set packers.

8. The method of claim 7, wherein the second mechanically-set packer is arranged within the packer assembly as substantially a mirror image of the first mechanically-set packer.

9. The method of any one of claims 1 to 8, wherein the step of further injecting the gravel slurry through the alternate flow channels comprises bypassing the packer assembly so that the wellbore is gravel-packed above and below the packer assembly after the first and second mechanically-set packers have been set in the wellbore.

10. The method of claim 1, wherein the sand screen comprises:

a) a first conduit forming a primary flow path in fluid communication with the inner mandrel of the first mechanically-set packer, the first conduit having at least one section along its length that is permeable and at least one section along its length that is impermeable;

b) at least one shunt tube along the length of the first conduit, the at least one shunt tube being in fluid communication with one of the alternate flow channels of the first mechanically-set packer to transport gravel slurry;

c) a second conduit comprising a secondary flow joint, wherein the second conduit also has at least one section along its length that is permeable and at least one section along its length that is impermeable, and where one of the at least one permeable sections of the second conduit is in fluid communication with one of the at least one permeable sections of the first

conduit, thereby providing fluid communication between the first and second conduits; and

d) the filtering medium, the filtering medium being designed to retain particles larger than a predetermined size while allowing fluids to pass into the permeable sections of the first and second conduits.

11. The method of claim 10, wherein:

the filtering medium comprises a first filtering screen placed along the permeable sections of the first conduit, and a second filtering medium placed along the permeable sections of the second conduit; and

the first conduit and the second conduit each comprises a tubular body having a cylindrical wall, with the first conduit and the second conduit running substantially parallel to one another within the wellbore.

12. The method of any one of claims 1 to 11, wherein:

the wellbore has a lower end defining an open-hole portion;

running the packer assembly and sand screen into the wellbore along the open-hole portion; and

setting the packer within the open-hole portion of the wellbore.

13. A method for completing a wellbore, the wellbore having a lower end defining an open-hole portion, and the method comprising:

running a gravel pack zonal isolation apparatus into the wellbore, the zonal isolation apparatus comprising:

a sand control device having:

an elongated base pipe,

a filter medium circumferentially surrounding at least a portion of the base pipe, and

at least one alternate flow channel along the base pipe; and

at least one packer assembly, each of the at least one packer assembly comprising:

a first mechanically set packer having an upper sealing element,

a second mechanically set packer having a lower sealing element,

a swellable packer element between the upper sealing element and

the lower sealing element that swells over time in the presence of a fluid, and

one or more alternate flow channels along the first mechanically-set packer, the swellable packer element, and the second mechanically-set packer to permit a gravel pack slurry to by-pass the at least one packer assembly and

the first mechanically-set packer further comprising

an inner mandrel;

a movable piston housing around the inner mandrel; and

one or more flow ports providing fluid communication between the alternate flow channels and a pressure-bearing surface of the piston housing;

positioning the zonal isolation apparatus in the open-hole portion of the wellbore;

running a setting tool into the inner mandrel of the first mechanically-set packer;

moving the setting tool along the inner mandrels, thereby releasing the movable piston housing on the first mechanically-set packer; and

communicating hydrostatic pressure to the piston housings throughthe one or more flow ports, thereby allowing the respective piston housings to slide, and thereby actuating the respective upper and lower sealing elements against the surrounding wellbore;

injecting a gravel slurry into an annular region formed between the sand control device and the surrounding open-hole portion of the wellbore;

further injecting the gravel slurry through the alternate flow channels to allow the gravel slurry to bypass the at least one packer assembly so that the open-hole portion of the wellbore is gravel-packed above and below the at least one packer assembly after the packer has been set in the wellbore.

14. The method of claim 13, wherein positioning the zonal isolation apparatus comprises positioning the zonal isolation apparatus such that a first of the at least one packer assembly is above or proximate the top of a selected subsurface interval.

15. The method of claim 13 or 14, wherein releasing the movable piston housings comprises shifting respective release sleeves in the first and second mechanically-set packers by pulling the setting tools along the inner mandrels.

16. The method of claim 15, wherein:

each of the first and second mechanically-set packers further comprises a centralizer; and

moving the respective piston housings further actuates the respective centralizers into engagement with the surrounding open-hole portion of the wellbore.

17. The method of claim 16, further comprising:

actuating the respective centralizers in the mechanically-set packers into engagement with the surrounding wellbore by applying hydrostatic pressure to the respective piston housings.

18. The method of clam 17, wherein applying hydrostatic pressure to the piston housings moves the respective piston housings to act on the respective centralizers, which in turn actuates the upper and lower sealing elements against the surrounding wellbore.

19. The method of any one of claims 13 to 18, further comprising:

producing hydrocarbon fluids from the open-hole portion of the wellbore.

20. A gravel pack zonal isolation apparatus, comprising:

a sand control device having:

an elongated base pipe extending from a first end to a second end,

at least one alternate flow channel along the base pipe extending from the first to the second end, and

a filter medium radially surrounding the base pipe along a substantial portion of the base pipe so as to form a sand screen; and

at least one packer assembly, each of the at least one packer assembly comprising:

an upper mechanically-set packer having a sealing element, and

a lower mechanically-set packer having a sealing element, wherein:

the upper packer and the lower packer each comprises at least one alternate flow channel in fluid communication with the at least one alternate flow channel in the sand control device to divert gravel pack slurry past the upper mechanically set packer and the lower mechanically set packer during a gravel-packing operation; and

each of the upper packer and lower packer comprises:

an inner mandrel,

a movable piston housing retained around the inner mandrel,

one or more flow ports providing fluid communication between the alternate flow channels and a pressure-bearing surface of the piston housing,

a release sleeve along an inner surface of the inner mandrel, the release sleeve being configured to move in response to movement of a setting tool within the inner mandrel and thereby expose the one or more flow ports to hydrostatic pressure during the gravel-packing operation.

21. The apparatus of claim 20, wherein the filter medium for the sand screen comprises wound wires, a wire mesh, or combinations thereof.

22. The apparatus of claim 21, further comprising:

a swellable packer intermediate the upper mechanically-set packer and the lower mechanically-set packer, the swellable packer having an element that swells over time in the presence of a fluid; and

wherein the swellable packer comprises at least one alternate flow channel in fluid communication with the at least one alternate flow channel in the upper mechanically set packer and the lower mechanically set packer to divert gravel

pack slurry past the upper mechanically set packer and the lower mechanically set packer during a gravel-packing operation.

23. The apparatus of claim 20, wherein at least one of the at least one packer assembly is placed at the first end of the sand control device.

24. The apparatus of claim 20, wherein at least one of the at least one packer assembly is placed between two joints of the elongated base pipe intermediate the first and second ends.

25. The apparatus of claim 20, wherein:

the elongated base pipe comprises multiple joints of pipe connected end-to-end forming the first end of the sand control device and a second end of the sand control device; and

the gravel pack zonal isolation apparatus comprises an upper packer assembly placed at the first end of the sand control device, and a lower packer assembly placed at the second end of the sand control device.

26. The apparatus of claim 25, wherein the upper packer assembly and the lower packer assembly are spaced apart along the joints of pipe so as to straddle a selected subsurface interval within a wellbore.

27. The apparatus of claim 21, wherein the elements for the first and second mechanically set packer elements are elastomeric cup-type elements.

28. The apparatus of claim 23, wherein the sand screen comprises:

a) a first conduit forming a primary flow path in fluid communication with the inner mandrels of the upper and lower packers, the first conduit having at least one section along its length that is permeable and at least one section along its length that is impermeable;

b) at least one shunt tube along the length of the first conduit, the at least one shunt tube being in fluid communication with one of the alternate flow channels of the upper and lower packers to transport gravel slurry;

c) a second conduit comprising a secondary flow joint, wherein the second conduit also has at least one section along its length that is permeable and at least one section along its length that is impermeable, and wherein one of the at least one permeable sections of the second conduit is in fluid communication with one of the at least one permeable sections of the first conduit, thereby providing fluid communication between the first and second conduits; and

d) the filter medium, the filter medium being designed to retain particles larger than a predetermined size while allowing fluids to pass into the permeable sections of the first and second conduits.