

OPHTHALMIC LENSES FOR PREVENTION OF MYOPIA PROGRESSION

Cross Reference to Related Application

5 This application is a continuation in part application of U.S. Application No. 11/751,205 filed on May 21, 2007 and claims priority thereto under 35 U.S.C. 121.

Field of the Invention

10 The invention relates to ophthalmic lenses. In particular, the invention provides ophthalmic lenses useful for the prevention or retardation of myopia progression.

Background of the Invention

15 Myopia, or near-sightedness, affects up to 25% of the United States population and, in some parts of the world, up to 75% of the population. In the myopic eye, the shape of the eyeball is elongated and light rays entering the eye are focused in front of the retina. The conventional treatment for myopia is prescribing corrective lenses. However, the typical corrective lens does not prevent the progression of myopia.

20

 A number of methods to retard myopia progression, especially in children, have been proposed. These methods include using multifocal lenses, using lenses into which aberration is introduced or which control aberrations, using off-axis power lenses, reshaping the cornea, exercising the eye, and using pharmacological
25 therapies.

 The use of multifocal lenses and those having aberrations have proved to be disadvantageous in that the lenses compromise the wearer's distance vision. The other methods too suffer from disadvantages including discomfort, as with the
30 corneal reshaping, and undesirable side effects, as with the drug therapies.

Brief Description of the Drawings

Figure 1 depicts a front surface of a lens of the invention.

5

Figure 2 is a graph depicting the power profiles of the lenses of the examples.

Figure 3 is a graph depicting the power profiles of the lenses of the invention.

10

Figure 4 is a graph depicting the power profiles of the lenses of the invention.

15

Detailed Description of the Invention and Preferred Embodiments

The invention provides ophthalmic lenses, and methods for their design and production, which lenses substantially prevent myopia progression. It is a discovery of the invention that myopia progression can be substantially prevented by providing a multifocal lens having an area of distance vision power in the center of the optic zone surrounded by at least one region that provides positive longitudinal spherical aberration.

By "ophthalmic lens" is meant a contact, intraocular, onlay lens or the like. Preferably, the lenses of the invention are contact lenses. By "distance optical power," "distance vision power" and "distance power" is meant the amount of refractive power required to correct the wearer's distance vision acuity to the desired degree. By "longitudinal spherical aberration" is meant the dioptric difference in focus between the center and the periphery of the lens calculated as the dioptric value of the peripheral ray's focus minus the dioptric value of the paraxial ray's

30

focus. By “positive longitudinal spherical aberration” is meant that the dioptric difference between the peripheral and paraxial rays is a positive value.

In a first embodiment of the invention, ophthalmic lenses are provided which
5 lenses have an optic zone comprising, consisting essentially of, and consisting of a central zone having substantially constant distance vision power and at least a first annular zone concentric with the central zone and having positive longitudinal spherical aberration. In an alternative embodiment, a second annular zone concentric with the first annular zone may be provided, which second zone can
10 provide one of constant power or progressively decreasing power. In yet another embodiment, lenses are provided having an optic zone comprising, consisting essentially of, and consisting of a substantially constant distance vision power at the centermost portion of the optic zone and at least a one region peripheral to the distance vision power having positive longitudinal spherical aberration.

15

As seen in Figure 1, lens 10 has optic zone 11 and non-optical, lenticular zone 14. Optic zone 11 is composed of central zone 12 and peripheral zone 13. Central zone 12 is centered at the optical axis of the lens and has a radius of about 0.5 to 2 mm and preferably about 1 to 1.5 mm measured from the optical center of
20 the lens. The power within central zone 12 is substantially constant distance vision power and will be about +12.00 diopters to about -12.00 diopters. Due to the addition of the positive power in the peripheral zone, it may be desirable to provide overcorrection for the distance vision power in the central zone, meaning power in addition to that required to correct the wearer's distance vision acuity. The amount
25 of overcorrection will depend upon the diameter of the central zone 12 and the magnitude of the positive spherical aberration provided. However, typically, the overcorrection will be about 0.25 to about 1.00 diopters.

Peripheral zone 13 provides positive longitudinal spherical aberration that continuously and progressively increases as one moves from the innermost boundary defining the lenticular zone 14, (or boundary closest to the optical center of the lens), to the outermost boundary 15 of periphery of zone 13.

The increase in longitudinal spherical aberration in peripheral zone 13 may be about 0.25 to about 2 diopters, and preferably is about 0.5 to about 1.50 diopters, at a radius of about 2.5 mm from the optical center of the lens. Peripheral zone 13 may have a width of about 0.5 to about 3.5 mm, preferably about 1 to about 2 mm.

As shown in Figure 1, central zone 12 and peripheral zone 13 are zones with discrete junctions therebetween. In an alternative embodiment, no discrete junction exists between the substantially constant distant vision power and the positive longitudinal spherical aberration, both the substantially constant distant vision power and the positive longitudinal spherical aberration forming one zone.

In designing the lenses of the invention, the positive longitudinal spherical aberration is provided net of the wearer's ocular aberrations. Thus, for purposes of the invention, preferably the spherical aberration of the lens wearer is first determined and then the spherical aberration necessary to correct that aberration is provided.

Alternatively, a population average, such as 0.1 D/mm² may be used for the spherical aberration. Spherical aberration may be measured by any known and convenient method including, without limitation, by use of a commercially available aberrometer.

Any of a number of mathematical functions may be used to design the optic zone of the lenses of the invention including, without limitation, spheres, aspheres, splines, conics, polynomials and the like. In a preferred embodiment, the central zone preferably is spherical and there is a smooth transition between the central and

peripheral zone. Such a smooth transition may be ensured by use of mathematical functions that are continuous in magnitude and first and second derivatives.

One suitable equation for use in designing the optic zone of the lenses of the invention is:

$$y = \frac{x^2}{r + \sqrt{r^2 - (1+k)x^2}} \quad (I)$$

wherein y is the distance from the lens' center;
 x is the sag value;
 r is radius of curvature; and
 k is the conic constant and is 0 for a sphere, $-1 < k < 0$ for an ellipse and $k < -1$ for a hyperbola.

A conic of the following equation type may be used for an optic zone of a diameter D with a central spherical zone of diameter d for $-d/2 < x < d/2$

$$y = \frac{x^2}{r + \sqrt{r^2 - x^2}} \quad (II)$$

and for $d/2 < x < D/2$

$$y = \frac{(x-d/2)^2}{\left\{ r + \sqrt{r^2 - (x-d/2)^2} \right\} - (x-d/2)^2} - \frac{(x-d/2)^2}{\left\{ r + \sqrt{r^2 - (1+k)(x-d/2)^2} \right\}}$$

(III)

The sag values at any point may be converted to radii and the power of the lens at
 5 that point may be calculated using the following formula:

$$P = (n-1) \left[\frac{1}{r_1^2} - \frac{1}{r_2^2} \right]$$

(IV)

10 wherein P is the power; and
 n is the refractive index of the lens material.

The distance power and positive longitudinal spherical aberration may both
 be, and preferably are, on either the front or back surface of the lens or each on one
 15 of the front or back lens surfaces. One surface of the lens may provide the distance
 power and positive longitudinal spherical aberration and the other surface may be
 spherical, aspheric or incorporate cylinder power in order to correct the wearer's
 astigmatism. One ordinarily skilled in the art will recognize that for contact lens

20

embodiments in which cylinder power is present, a stabilization means will need to
 be incorporated in the lens. Suitable stabilization means are any of the static and
 dynamic stabilization means known in the art including, without limitation, prism
 25 ballast, thin and thick zones, bosses and the like and combinations thereof.

In embodiments with a central zone and at least one concentric zone, a second zone concentric about the first such zone may be provided. The second zone may provide substantially constant power or preferably power that progressively decreases as one moves to the periphery of the zone. The second concentric zone
5 may find utility in those lens wearers with large pupils, such as a young person in low illumination. The second zone preferably begins at a radius of about 3.5 mm and extends to a radius of about 4.5 mm. In embodiments in which the power progressively decreases across the zone, preferably the decrease reaches about half of the power found at the innermost portion of the zone. For example, if the lens has
10 a 1.0 diopter positive longitudinal spherical aberration in the first concentric zone at a radius of about 2.5 mm, the power at the outermost portion of the second zone will be have decreased to about 0.5 diopters. In embodiments in which there is no discrete junction between the constant distant power and positive longitudinal spherical aberration, a second region that provides this constant power or
15 progressively decreasing power may be provided at the periphery of the region of positive longitudinal spherical aberration. The inclusion of the second peripheral zone may be advantageous because it can be used to reduce the positive power in the periphery thereby reducing the visual compromise resulting from the positive power under low luminance conditions.

20

The lenses of the invention preferably are soft contact lenses, made of any material suitable for producing such lenses. Illustrative materials for formation of soft contact lenses include, without limitation silicone elastomers, silicone-containing macromers including, without limitation, those disclosed in United States

25

Patent Nos. 5,371,147, 5,314,960, and 5,057,578 incorporated in their entireties herein by reference, hydrogels, silicone-containing hydrogels, and the like and combinations thereof. More preferably, the surface is a siloxane, or contains a

siloxane functionality, including, without limitation, polydimethyl siloxane macromers, methacryloxypropyl polyalkyl siloxanes, and mixtures thereof, silicone hydrogel or a hydrogel, such as etafilcon A.

5 A preferred lens-forming material is a poly 2-hydroxyethyl methacrylate polymers, meaning, having a peak molecular weight between about 25,000 and about 80,000 and a polydispersity of less than about 1.5 to less than about 3.5 respectively and covalently bonded thereon, at least one cross-linkable functional group. This material is described in United States Patent No. 6,846,892
10 incorporated herein in its entirety by reference. Suitable materials for forming intraocular lenses include, without limitation, polymethyl methacrylate, hydroxyethyl methacrylate, inert clear plastics, silicone-based polymers, and the like and combinations thereof.

15 Curing of the lens forming material may be carried out by any means known including, without limitation, thermal, irradiation, chemical, electromagnetic radiation curing and the like and combinations thereof. Preferably, the lens is molded which is carried out using ultraviolet light or using the full spectrum of visible light. More specifically, the precise conditions suitable for curing the lens
20 material will depend on the material selected and the lens to be formed. Polymerization processes for ophthalmic lenses including, without limitation, contact lenses are well known. Suitable processes are disclosed in U.S. Patent No. 5,540,410 incorporated herein in its entirety by reference.

25 The contact lenses of the invention may be formed by any conventional method. For example, the optic zone may be produced by diamond-turning or

diamond-turned into the molds that are used to form the lens of the invention. Subsequently, a suitable liquid resin is placed between the molds followed by compression and curing of the resin to form the lenses of the invention. Alternatively, the zone may be diamond-turned into lens buttons.

5

The invention may be further clarified by a consideration of the following examples:

Examples

10

Example 1

A lens of the invention is provided with a back surface of 8.8 mm radius of curvature and a front surface calculated in accordance with Equation II wherein $k + 10^{-5}$, $r = 1.1$ and $d = 0.75$ mm. The central zone power is -3.00 diopters and positive longitudinal spherical aberration of $+1$ diopters at 5 mm is provided. The lens is made using single point, diamond-turning into a brass insert followed by injection molding of a lens molds from the insert and casting of the lens using etafilcon A according to conventional lens manufacturing processes. The solid line in the graph of Figure 2 depicts the power profile for the optic zone of the lens. Figures 3 and 4 depict power profiles of alternative embodiments.

20

Comparative Example 1

A prior art lens designed made in accordance with the disclosure in U.S. Patent No. 6,045,578 is provided with a back surface of 8.8 mm radius of curvature and a front surface calculated using Equation I with $k + 3.5$. The central zone of the optic zone has a power of 3.00 diopters and positive longitudinal spherical aberration of $+1$ diopters at 5 mm is provided. The lens is made using single point, diamond-turning into a brass insert followed by injection molding of a lens molds from the insert and casting of the lens using etafilcon A according to conventional

25

lens manufacturing processes. The dotted line in the graph of Figure 2 depicts the power profile for the optic zone of the lens.

Claims

1 An ophthalmic lens, comprising an optic zone including a central zone having substantially constant distance vision power and at least a first annular zone concentric with the central zone and having positive longitudinal spherical aberration in an amount sufficient to prevent or retard myopia progression, and a second portion having a progressively decreasing power in the direction towards the periphery of the lens, wherein said power of said additional portion decreases to no more than half of the maximum power of the first annular zone, and wherein said central zone includes a hyperopic defocus of up to -0.25 Diopters.

2 The lens of claim 1, wherein the lens is a contact lens wherein the power profile in the first annular zone is described by a 4th order polynomial.

3 The lens of claim 1, wherein the optic zone further includes a second annular zone concentric with the first annular zone.

4 An ophthalmic lens, comprising an optic zone including a central zone having substantially constant distance vision power and a first annular zone concentric with the central zone and having a positive longitudinal spherical aberration in an amount sufficient to prevent or retard myopia progression, the arrangement being such that there is no discrete junction between the central zone and the first annular zone, and an additional portion distinct from the first annular zone, wherein the additional portion includes a progressively decreasing power in the direction towards the periphery of the lens, wherein said power of said additional portion decreases to no more than half of the maximum power of the first annular zone, and wherein said central zone includes a hyperopic defocus of up to -0.25 Diopters.

5 The lens of claim 4, wherein the power profile in the first annular zone is described by a 4th order polynomial

6 The lens of claim 4 or claim 5, wherein the lens is a contact lens and wherein distance vision power is overcorrected by 0.25 to 1.00 diopters.

7 The lens of any one of claims 4 to 6, wherein the additional portion is concentric with said first annular zone.