

REACTOR FOR GENERATING MOISTURE AND MOISTURE GENERATING AND FEEDING APPARATUS FOR WHICH THE REACTOR IS EMPLOYED

Field of the Invention

[0001] The present invention is concerned with a reactor for generating moisture mainly used for semiconductor manufacturing facilities, and a moisture generating and feeding apparatus for which the radiator is employed. The present invention is used for generating and feeding moisture needed for oxide coatings of silicon, treatments to remove hydrogen discharged from a process chamber and the like.

Background of the Invention

[0002] In semiconductor manufacturing facilities, a reactor for generating moisture with a structure as shown in Figure 15 has been widely used. Namely, in Figure 15,

A Reactor

B Temperature regulator

H₂ Hydrogen gas

O₂ Oxygen gas

G Mixed gas

W Moisture gas

L Gap

V Interior space

- α Inclination angle of the peripheral edge of a reflector
- 1 Reactor structural component on the inlet side
 - 1a Gas feed port
- 2 Reactor structural component on the outlet side
 - 2a Moisture gas take-out port
- 3a, 3b Reflectors
- 4 Reflector fixing bolt
- 5 Spacer
- 6 Platinum coating catalyst layer comprising a barrier coat 7 and a platinum coat 8 mounted on its outer surface
- 9 Barrier coat mounted on the inner surface of the reactor structural component on the inlet side
- 10 Barrier coat mounted on the outer surface of the reflector
- 11 Welded portion
- 12 Fixing hole for the sheath-type thermometer
- 13 Heater
- 14 Heater press
- 15 Cooler
 - 15a Heat dissipation fin
 - 15b Substrate

[0003] A mixed gas G produced by mixing hydrogen gas H₂ and oxygen gas O₂

is fed from the gas feed port 1a to the interior space V, and when the gases contact with a platinum coating catalyst layer 6 mounted on the inner surface of the reactor structural component on the outlet side 2, the reactivity of the hydrogen and oxygen is activated by catalytic action. The activated hydrogen and oxygen react at the appropriate speed without causing an explosive combustion reaction within the atmosphere, below the combustion temperature of hydrogen, and the high purity moisture gas V produced flows out from the moisture take-out port 2a.

[0004] It may be necessary to raise the temperature of the interior space V of the reactor A higher than at least 200°C in order that the afore-mentioned reactivity of the hydrogen and oxygen is activated and to maintain the stable reaction of both hydrogen and oxygen. To achieve this end, a plane-shaped heater 13 is provided on the outer side of the reactor structural component on the outlet side 2, and the reactor A is heated by the plane-shaped heater when the reactor A starts up. Figure 16 shows the relationship between the temperature of the reactor A and the reaction rate of the hydrogen · oxygen. When the temperature of the reactor exceeds approximately 200°C, the reaction rate of the hydrogen · oxygen becomes the value of approximately 98% or more regardless of the mixture ratio of both hydrogen and oxygen.

[0005] While the reaction of the afore-mentioned hydrogen and oxygen proceeds, the reactor A is heated by the reaction heat, and then the reactor's temperature goes up. In order to restrain the afore-mentioned explosive combustion reaction of the hydrogen and oxygen, it is necessary that the temperature of the interior space V is held at a temperature lower (for example,

400~450°C) than the lowest limit ignition temperature (approximately 560°C, and the limit ignition temperature goes up higher than 560°C depending on the mixing ratio of hydrogen and oxygen) of the hydrogen gas (or hydrogen containing gas).

[0006] Accordingly, with this kind of conventional reactor for generating moisture, such measures as limiting the flow rate (namely, the volume of moisture gas W generated), improving the cooling performance of a cooler 15, or increasing the heat capacity of a reactor A, are implemented. When such measures as these are employed, it becomes possible to produce high purity moisture gas at the low cost, and stably and continuously with this kind of reactor for generating moisture. Thus, such reactors are widely and practically used.

[0007] However, in recent years there is seen a trend to downsize the apparatus for generating moisture while providing a bigger volume of moisture generation, which has been demanded in the field of semiconductor manufacturing facilities. For example, when the bore of a wafer becomes larger, the volume of moisture required for each treatment process increases. Accordingly, there has been a strong demand for more volume of moisture generation than that presently obtained by a conventional moisture generating apparatus having a dimensional volume similar to that of the conventional ones that are produced.

[0008] However, when downsizing of semiconductor manufacturing facilities is required, the moisture generating apparatus has to meet a severe restriction placed upon its volume/dimension. Because of this reason, it is nearly impossible for the cooling performance of the reactor A to be improved by means

of upgrading the cooling fan though improvements such as making the heat dissipation fin 15a of the cooler 15 higher and increasing the number of heat dissipation fins slightly. Similarly, it is very difficult to upgrade a reactor A in view of the afore-mentioned restrictions on its volume. For example, the structurally allowable dimensions of a reactor A for generating moisture having a large flow rate of more than 10SLM are similar to the values of dimensions (outer diameter 228mm, thickness 37mm and height of a heat dissipation fin 25mm) of the conventional reactor for generating moisture which has a maximum volume of moisture generation of 5SLM.

[0009] Therefore, for a conventional reactor equipped with a cooler 15 provided with the structure shown in Figure 15, there is no way at all to meet the requirement of increasing the volume of moisture generated in view of the restrictions in its volume/dimension including that volume/dimension of the cooler 15. Thus, a conventional reactor equipped with a cooler 15 fails to increase the volume of moisture that may be generated safely and easily.

[0010] Patent Document 1: TOKU-KAI No. 2001-48501

Patent Document: 2: INTERNATIONAL DISCLOSURE WO-01/94254A

Disclosure of the Invention

Object of the Invention

[0011] It is an object of the present invention to solve the above-stated problems of the conventional reactor for generating moisture, namely, that the reactor cannot be upsized, and cooling performance cannot be enhanced significantly with the cooling fan 15, due to restrictions in the volume/dimension

of the moisture generating apparatus, thus resulting in there being no way to increase the volume of moisture to be generated by the conventional reactor. It is another object of the present invention to provide a reactor for generating moisture that has made it possible to increase the volume of moisture to be generated using a reactor A, and having a similar volume, by making improvements in both the shape of the cooler 15 and the fixing structure of the cooler 15 to the reactor A so that heat dissipation from the reactor A is enhanced without increasing the volume/dimension of the cooler 15 significantly.

Means of the Invention

[0012] Inventors of the present invention have come to the idea of meeting the requirements to increase the volume of moisture to be generated by employing a reactor (outer diameter 228mm, thickness 37mm and height of a heat dissipation fin 25mm) with a conventional structure, as shown in Figure 15, to enhance cooling performance. Namely, only with some allowable structural modifications on the heat dissipation fin 15a without upsizing the cooling fan 18, structural modifications of the cooler 15 of the reactor A were tried, and tests were conducted principally aimed at suppressing the temperature of reactor A below about 450°C during halts of the operation of the cooling fan 18.

[0013] Firstly, as shown in Figure 17 to Figure 20, one reactor A having a cooler 15 equipped with a 25mm high heat dissipation fin 15a, and another reactor A having a cooler 15 equipped with a 60mm high heat dissipation fin 15a, were manufactured, and cooling performance of coolers 15 equipped with the heat dissipation fins 15a with different heights was studied.

In this case, the outer diameter and thickness of the reactor A were 228mm ϕ and 37mm, respectively. The total volume and total surface area of the heat dissipation fin 15a, as shown in Figure 17, were 268cm and 0.1984c m^2 respectively, and the total volume and total surface area of the heat dissipation fin 15a shown in Figure 19 were 548cm and 0.4430c m^2 , respectively. Furthermore, slight improvements were made on a cooling fan 18 so that the air volume of 2.7m³/min in Figure 17 was made to be 6.0 m³/min in Figure 19.

[0014] The height, 60mm (in Figure 19 and Figure 20) of the afore-mentioned heat dissipation fin 15a has a value determined by the restrictions of the volume/dimension of the afore-mentioned reactor A. If the height of the heat dissipation fin 15a is made to be higher than 60mm, the volume/dimension of the reactor A exceeds the limit value, and the more wattage that is required by the heater at the time moisture generation starts. Similarly, with regard to cooling fan 18, it is difficult to use a fan with a wind volume of 6.0m³/min or more because of the restrictions on displacement of the case body. Therefore, a fan with a wind volume of 6.0m³/min or less has been employed in the present invention.

[0015] Figure 21 and Figure 22 show the schematic outline of one example of the afore-mentioned moisture generating apparatus equipped with a reactor A of Figure 19 and Figure 20. Outer dimensions (the volume) have been set to be width 380mm x depth 380mm x height 533mm. Also, as shown in Figure 21 and Figure 22, A designates a reactor, 15a designates a heat dissipation fin, 18 designates a cooling fan, and 17 designates a H₂ sensor. The fixing position of the cooling fan can be appropriately altered depending on the structure of the

case body. For example, in the case shown in Figure 21, it is placed on the front side.

[0016] Figure 23 is a diagram showing the relationship between volume of the afore-mentioned moisture generated in the reactor A and the temperature of the reactor shown in Figure 17 to Figure 20. When the cooling fan 18 is set to off, the temperature of the reactor reaches 430°C with the volume of moisture generated at 7SLM (in case of a 25mm high fin), and the temperature of the reactor reaches 420°C with the volume of moisture generated of 8SLM (in case of a 60mm high fin). Even when the height of the cooling fin 15a is made to be the height of the allowable dimension limit (approx 60mm), it was difficult at the time the fan halts to achieve a highest temperature of 450°C or less and a volume of moisture generated of 10SLM.

[0017] Inventors of the present invention have found, through analysis of the afore-mentioned test results in Figure 23, that the reduction in the highest temperature of the reactor, due to the increase in the height of the heat dissipation fin 15a, is extremely low. In view of the above results, it has been learned that heat transfer characteristics from the reactor A to the heat dissipation fin 15a need to be improved in order to enhance natural heat dissipation from the heat dissipation fin 15a. Specifically, as shown in Figure 15, when the reactor A is constituted so that a plane-shaped heater 13 is installed nearly over the front part of the outer surface of the reactor structural component on the outlet side 2, and a cooler 15 is fixed to its outside through the mediation of a heater press 14, the heat transfer from the reactor A to the cooler 15 is suppressed because of hard mica used to cover the plane-shaped heater 13 for

its protection. Thus, it has become evident that the cooler 15 has not achieved its function sufficiently.

[0018] The present invention has been created with the knowledge as explained above. The plane-shaped heater 13 is inserted to the heat dissipation body substrate 15b of the cooler 15, and installed only on the center part of the reactor structural component on the outlet side 2, and the cooler 15 equipped with the heat dissipation fin is adhered only to the peripheral edge of the reactor A so that heat dissipation from the reactor A becomes possible efficiently.

[0019] The present invention as claimed in Claim 1 is fundamentally constituted so that it comprises a reactor having an interior space formed by combining a reactor structural component on the inlet side having a gas feed port and a reactor structural component on the outlet side having a moisture gas take-out port positioned against each other, a reflector placed oppositely to the gas feed port and moisture gas take-out port in the interior space of the afore-mentioned reactor, a platinum coating catalyst layer formed on the inner wall face of the afore-mentioned reactor structural component on the outlet side, a heater to heat the reactor, and a cooler fixed to the outer surface of the reactor to cool the reactor; and with the reactor for generating moisture to make hydrogen and oxygen react under conditions of non-combustion by allowing hydrogen and oxygen fed from the gas feed port into the interior space of the reactor to contact with the afore-mentioned platinum coating catalyst layer to activate the reactivity, the afore-mentioned cooler is made to be a cooler on the outlet side comprising a heat dissipation body substrate having a heater

insertion hole in the center to fix to the outer surface of the reactor structural component on the outlet side, and a plural number of heat dissipation bodies installed vertically in parallel on the area excluding the part where the afore-mentioned heater insertion hole on the heat dissipation body substrate exists, and one part of the heater to heat the afore-mentioned reactor is inserted in the cooler on the outlet side, to fix the cooler to the outer surface of the reactor structural component on the outlet side.

[0020] The present invention as claimed in Claim 2 is fundamentally constituted so that it comprises a reactor having an interior space formed by combining a reactor structural component on the inlet side having a gas feed port and a reactor structural component on the outlet side having a moisture gas take-out port positioned against each other, a reflector placed oppositely to the gas feed port and moisture gas take-out port in the interior space of the afore-mentioned reactor, a platinum coating catalyst layer formed on the inner wall face of the afore-mentioned reactor structural component on the outlet side, a heater to heat the reactor, and a cooler fixed to the outer surface of the reactor to cool the reactor; and with the reactor for generating moisture to make hydrogen and oxygen react under conditions of non-combustion by allowing hydrogen and oxygen fed from the gas feed port into the interior space of the reactor to contact with the afore-mentioned platinum coating catalyst layer to activate the reactivity, the afore-mentioned cooler comprises a cooler on the outlet side and a cooler on the inlet side, and the afore-mentioned cooler on the outlet side comprises a heat dissipation body substrate having a heater insertion hole in the center to fix to the outer surface of the reactor structural component

on the outlet side, and a plural number of heat dissipation bodies installed vertically in parallel on the area excluding the part where the afore-mentioned heater insertion hole on the heat dissipation body substrate exists, and the afore-mentioned cooler on the inlet side comprises a heat dissipation body substrate fixed to the outer surface of the reactor structural component on the inlet side and a plural number of heat dissipation bodies installed on the heat dissipation body substrate vertically in parallel.

[0021] The present invention as claimed in Claim 3, according to Claim 1 or Claim 2, is made so that a reactor structural component on the inlet side is provided with a heater.

[0022] The present invention as claimed in Claim 4, according to Claim 2, is made so that the height of the heat dissipation body of a cooler on the inlet side and the height of the heat dissipation body of a cooler on the outlet side are made to be the same or the height of the heat dissipation body of the cooler on the outlet side is made higher.

[0023] The present invention as claimed in Claim 5, according to Claim 2, is constituted so that a plane-shaped heater is provided between the heat dissipation body substrate of a cooler on the inlet side and the outer surface of the reactor structural component on the inlet side.

[0024] The present invention as claimed in Claim 6, according to Claim 2, is made so that the heat dissipation body substrate of the cooler on the inlet side is directly fixed to the outer surface of the inner part of the reactor structural component on the inlet side, and a brim-shaped heater is directly fixed to the outer surface of the outer part of the reactor structural component on the inlet

side.

[0025] The present invention as claimed in Claim 7, according to Claim 2 or Claim 3, is made so that the heat dissipation body substrate of the cooler on the inlet side is fixed to the outer surface of the reactor structural component on the inlet side positioned at the inner side part of the heater press fixed to the outer surface of the reactor structural component on the inlet side, and a heater is fixed between the outer surface of the outside part of the reactor structural component on the inlet side and the heater press.

[0026] The present invention as claimed in Claim 8, according to Claim 1 to Claim 7, is so made that the heat dissipation body substrate of the cooler on the outlet side is directly fixed to the outer surface of the outside part of the reactor structural component on the outlet side, and the heater is directly fixed to the reactor structural component on the outlet side by making the heater inserted into the heater insertion hole made on the cooler on the outlet side.

[0027] The present invention as claimed in Claim 9, according to Claim 1 to Claim 8, is made so that a heat dissipation body is made to be a thin-plate-shaped heat dissipation fin or a rod-shaped heat dissipation pin.

[0028] The present invention as claimed in Claim 10, according to Claim 1 to Claim 8, is made so that the outer surfaces of the reactor structural component on the inlet side and the reactor structural component on the outlet side are made to be round-shaped, and the heat dissipation body substrates of both coolers are made to be either round-shaped or square-shaped, and the heater insertion hole installed on the heat dissipation body substrate of the cooler on the outlet side is made to be round-shaped.

[0029] The present invention as claimed in Claim 11, according to Claim 1 or Claim 2, is made so that the heater to heat a reactor is provided on the cylindrical face of the reactor.

[0030] The present invention as claimed in Claim 12, according to Claim 1 or Claim 2, is made so that a heater is made to be brim-shaped. The present invention, as claimed in Claim 13, is fundamentally constituted so that a moisture generating and feeding apparatus is constituted by using a reactor for generating moisture stipulated in Claim 1.

Effects of the Invention

[0031] The present invention is constituted so that a plate-shaped heater is directly fixed to the outer surface of the reactor structural component on the outlet side through the heater insertion hole made on the heat dissipation body substrate of the cooler on the outlet side, and a heat dissipation fin is installed only on the part excluding the afore-mentioned heater insertion hole of the heat dissipation body substrate of the cooler on the outlet side for cooling the reactor structural component on the outlet side. Accordingly, heat from the reactor structural component on the outlet side is directly transferred to the heat dissipation body substrate without passing through the plane-shaped heater, thus achieving substantial improvements in heat dissipation characteristics (cooling characteristics) compared to the case wherein the plane-shaped heater is installed between the heat dissipation body substrate and the reactor structural component on the outlet side. As a result, the present invention can generate moisture at approximately 2 times the amount of moisture generated

conventionally and safely without reaching the temperature higher than about 400~450°C while employing the small-sized reactor for generating moisture.

[0032] The start-up performance and ascending velocity of the moisture generating apparatus is improved because the plane-shaped heater of the reactor structural component on the outlet side is made in a manner such that the heat dissipation body substrate of the cooler on the outlet side does not contact with the outer surface side of the plane-shaped heater so that heat dissipation is reduced at the time of heating, thus efficiently making the reactor go up to the temperature of the start of reaction.

Brief Description of Drawings

[0033] Figure 1 is a front view of a reactor for generating moisture with regard to a first embodiment of the present invention.

Figure 2 is a side view of the inlet side, for raw material gas, of the reactor shown in Figure 1.

Figure 3 is a side view of the outlet side, for the moisture gas, of the reactor shown in Figure 1.

Figure 4 is a longitudinal cross sectional view of the reactor shown in Figure 1.

Figure 5 shows another example of a cooler on the outlet side, for the moisture gas, of the reactor shown in Figure 1.

Figure 6 shows the temperature distribution (radial) in close proximity to the inner wall of the reactor structural component on the outlet side 2 of a reactor for generating moisture with regard to Example 1 in Figure 1 to Figure 4.

Figure 7 is a longitudinal cross sectional view of a reactor for generating moisture with respect to an other embodiment of the present invention.

Figure 8 is a plan view of the reactor shown in Figure 7.

Figure 9 is a side view of the right side of the reactor shown in Figure 8.

Figure 10 is a longitudinal cross sectional view illustrating another embodiment of a reactor for generating moisture of the present invention.

Figure 11 is a diagram illustrating the temperature distribution (radial) in close proximity to the inner wall of the reactor structural component on the outlet side 2 with a reactor for generating moisture in Example 2 as shown in Figure 7 to Figure 9.

Figure 12 is a diagram illustrating the afore-mentioned temperature distribution (radial) at the same position as that in Figure 11 with the reactor for generating moisture in Example 3.

Figure 13 is a diagram illustrating the afore-mentioned temperature distribution (radial) at the same position as that in Figure 5 under conditions when a cooling fan is in operation with a reactor for generating moisture in Example 3.

Figure 14 is a diagram showing the relationship between the volume of moisture generated and the temperature, and the like, of a reactor when the height of the heat dissipation fin of a cooler is varied.

Figure 15 is a longitudinal cross sectional view of a conventional reactor for generating moisture.

Figure 16 is a diagram to show the relationship between the

temperature of a reactor and the reaction rate of hydrogen + oxygen.

Figure 17 is a schematic view of the reactor for testing.

Figure 18 is a side view of the outlet side of the reactor shown in Figure 17.

Figure 19 is a schematic view of another reactor for testing.

Figure 20 is a side view of the outlet side of the reactor shown in Figure 19.

Figure 21 is a longitudinal cross sectional schematic view of the moisture generating apparatus in which a reactor is incorporated.

Figure 22 is a plan view of the moisture generating apparatus of Figure 21.

Figure 23 is a diagram showing the relationship between the volume of moisture generated by using the reactor shown in Figure 17 to Figure 20 and the temperature of the reactor.

Figure 24 is a flow diagram of a moisture generating and feeding apparatus in which a reactor A for generating moisture in the present invention is employed.

Figure 25 is a plan schematic view of a moisture generating and feeding apparatus.

Figure 26 is a longitudinal schematic view of a moisture generating and feeding apparatus.

List of Reference Characters and Numerals

[0034] A Reactor

- B Temperature Regulator
- H₂ Hydrogen gas
- O₂ Oxygen gas
- G Mixed gas
- W Moisture gas
- L Gap
- V Interior space
- α Inclination angle of the peripheral edge of a reactor
- 1 Reactor structural component on the inlet side
- 1a Gas feed port
- 2 Reactor structural component on the outlet side
- 2a Moisture gas take-out port
- 3a, 3b Reflectors
- 4 Reflector fixing bolt
- 5 Spacer
- 6 Platinum coating catalyst layer
- 7 Barrier coat
- 8 Platinum coat
- 9 Barrier coat mounted on the reactor structural component on the inlet side
- 10 Barrier coat mounted on the reflector
- 11 Welded portion
- 12 Fixing hole for the sheath-type thermometer
- 13 Plane-shaped heater

- 14 Heater press
- 15 Cooler
 - 15₁ Cooler on the inlet side
 - 15₂ Cooler on the outlet side
- 15a Heat dissipation fin
- 15b Heat dissipation body substrate (fin substrate)
- 23 Heater insertion hole
- 17 Hz sensor
- 18 Cooling fan
- 19 Bolt (heater press bolt)
- 20 Bolt (bolt for the cooler fixing)
- 21 Fixing hole for the heater control thermometer
- 22 Fixing hole for the thermometer to monitor reactor's temperature
- 24 Mixer
- 25 Gas filter
- 26 Heater
- 27 Filter
- 28 Mixture gas take-out port
- 29 Lead wire for the heater
- 30 Case body

Best Mode for Carrying Out the Present Invention

[0035] [The First Embodiment] Embodiments of the present invention are described with reference to the drawings hereunder. Figure 1 to Figure 4

illustrate the first embodiment of the present invention. Figure 1 is a front view of a reactor for generating moisture. Figure 2 is a side view of the inlet side of the raw material gas. Figure 3 is a side view of the outlet side of the moisture gas. Figure 4 is a longitudinal cross sectional view of the reactor for generating moisture.

[0036] Referring to Figure 1 to Figure 4, a reactor for generating moisture A is formed in a round and hollow disc shape by combining a stainless steel (SUS316L) made reactor structural component on the inlet side 1 and reactor structural component on the outlet side 2 positioned against each other, and welding them hermetically. The afore-mentioned reactor structural component on the inlet side 1 is equipped with a round-shaped recess with a flat-shaped bottom therein, and a gas feed port 1a communicates with the inside of the recess. The reactor structural component on the outlet side 2 is equipped with a round-shaped recess with a flat-shaped bottom therein, and a moisture gas take-out port 2a communicates with the inside of the recess. Furthermore, flanges are formed inwardly on the peripheral edges of both reactor structural components 1, 2, and both flanges are positioned against each other and hermetically welded 11.

[0037] The centers of the round disc-shaped reflectors 3a, 3b are positioned against the gas feed port 1a and the moisture gas take-out port 2a of both reactor structural components 1, 2 respectively, and are fixed to both reactor structural components 1, 2 by using the fixing bolt 4 with a gap L located between the bottom faces of both reactor structural components. The stainless steel (SUS316L) made reflectors 3a, 3b are made so that their diameters are

slightly smaller than the inner diameters of the round recesses.

[0038] As shown in Figure 4, the peripheral edges of the reflectors 3a, 3b, positioned against both reactor structural components 1, 2, are finished to be tapered with an inclination angle α . The mixed gas G flowed in from the gas feed port 1a can flow out smoothly into the interior space V due to the inclination angle α ; thus, flow in the gap between the reflector 3b and the reactor structural component on the outlet side 2 can prevent local and intensive heat liberation of the platinum coating catalyst layer 6 positioned against the peripheral edge of the reflector 3b.

[0039] The afore-mentioned platinum coating catalyst layer 6 is formed on the entire area of the inner surface of the SUS316 made reactor structural component on the outlet side 2. The platinum coating catalyst layer 6 is made up of a TIN-made barrier coat 7 and the platinum coat 8 formed thereon.

[0040] A TIN-made barrier coat 9 and barrier coat 10 are formed on the inner surface of the reactor structural component on the inlet side 1 and the outer surfaces the afore-mentioned reflectors 3a, 3b. The barrier coats 9, 10 are for preventing local heat liberation by means of the metal catalytic action on the surfaces of the reactor structural component on the inlet side 1 and on reflectors 3a, 3b.

[0041] The temperature regulator B of reactor A comprises a temperature regulator on the outlet side B₁ and a temperature regulator on the inlet side B₂. The afore-mentioned temperature regulator on the outlet side B₁ is made up of a brim-shaped heater 13b to heat the outer face side of the reactor structural component on the outlet side 2, a regulator (not illustrated) for the on-off control

of the heater 13b, and a cooler on the outlet side 15₂ to cool the reactor on the outlet side 2.

[0042] The temperature regulator on the inlet side B₂ is made up of a brim-shaped heater 13a, a regulator (not illustrated) for the on-off control of the heater 13a, and a cooler on the inlet side 15₁ to cool the reactor on the inlet side 1.

[0043] The afore-mentioned brim-shaped heaters 13a, 13b, which are so-called thin-plate- and plane-shaped heaters, are attached to and fixed to the reactor structural components 1, 2 by means of the round-plate-shaped heater presses 14a, 14b. Specifically, as shown in Figure 4, the brim-shaped heater on the outlet side 13b is shaped like a brim with a smaller outer diameter (180mm ϕ with the present invention) than the outer diameter (228mm ϕ) of the reactor structural component on the outlet side 2, and is directly fixed to the reactor structural component on the outlet side by a bolt 19 through the mediation of the round-shaped heater press 14b having the same diameter as that of the brim-shaped heater 13b. The brim-shaped heater on the outlet side 13b is installed only at the intermediate part of the reactor structural component on the outlet side 2, thus making it different from the afore-mentioned conventional example in Figure 15.

[0044] On the other hand, the brim-shaped heater on the inlet side 13a is formed in a brim shape having nearly same outer diameter as that of the reactor structural component on the inlet side 1, and fixed to the reactor structural component on the inlet side 1 by a bolt 19 through the mediation of the round-shaped heater press 14a.

[0045] The afore-mentioned cooler 15 comprises a cooler 15₁ on the inlet side adhered to the outer surface of the reactor structural component on the inlet side 1 and a cooler 15₂ on the outlet side adhered to the outer surface of the reactor structural component on the outlet side 2. The cooler 15₁ on the inlet side is formed to be a square-shaped cooler as an integral unit with a 25mm high heat dissipation fin 15a and an approximately 5mm thick fin substrate (heat dissipation body substrate) 15b as shown in Figure 15, and is fixed to the position corresponding inwardly to the brim-shaped heater 13a by a bolt 20.

[0046] As shown in Figure 3 and Figure 4, the cooler 15₂ on the outlet side, provided on the side of the reactor structural component on the outlet side 2, is made up of a heat dissipation body substrate 15b on which a heater insertion hole 23 having an inner diameter of 190mm is made in the center of the square-shaped heat dissipation body substrate, and a plural number of the 60mm high thin-plate-shaped heat dissipation fins 15a, made like the teeth of a comb, are disposed on the heat dissipation body substrate 15b. In this embodiment, the cooler 15₂ is made as an integral unit fabricated with an aluminum alloy made heat dissipation body substrate 15b (approx 10mm thick) and heat dissipation fins 15a (approx 2mm thick, 60mm high) are employed.

[0047] In Figure 1 to Figure 4, a thin-plate-shaped heat dissipation fin 15a is utilized as the heat dissipation body. However, it goes without saying that a heat dissipation body of any shape can be used. For example, a rod-shaped heat dissipation pin can be used. Also, it goes without saying that although a square-shaped heat dissipation body substrate 15b is employed in the present embodiment for the cooler 15₂ on the outlet side and the cooler 15₁ on the inlet

side, the shape employed could be a round one or the like.

[0048] Furthermore, as shown in Figure 5, it is desirable that the afore-mentioned cooler 15₂ on the outlet side is provided with a plural number (78pcs.x 2=156pcs.) of through holes 15c, having a diameter of approximately 6mm ϕ on the area where the heat dissipation fin 15a of the afore-mentioned heat dissipation body substrate 15b is not installed, to improve the permeability performance at the time when the cooling fan 18 is operated as well as to increase the cooling area so that the cooling performance of the cooler 15₂ is enhanced.

[0049] With respect to Figure 2 and Figure 3, 19 designates a fixing bolt of the heater press 14 and 20 designates a fixing bolt of the cooler 15. According to the present embodiment, though the height of the heat dissipation fins 15a of the cooler 15₁ on the inlet side is made to be 25mm, it can be made to be 60mm, which is the same as that of the cooler 15₂ on the outlet side. Furthermore, according to the present embodiment, though it is constituted so that a brim-shaped heater 13a is installed on the reactor structural component on the inlet side 1, it can be constituted so that a brim-shaped heater 13a is not installed on the reactor structural component on the inlet side 1.

[0050] Before the moisture gas is generated, it is normal that the N₂ gas is fed into the reactor A and a purge treatment is conducted in the reactor A. At this time, the peripheral part of the reactor A is cooled with the afore-mentioned purge gas. Therefore, the reaction rate of moisture generation when moisture starts being generated is lowered, thus increasing the amount of non-reacted gas unless the peripheral part of the reactor A is heated to raise the temperature.

The afore-mentioned brim-shaped heater 13a is utilized to prevent cooling due to purge gas and those associated problems. Heater 13a is, therefore, operated when the peripheral part of the reactor A needs mainly to be heated to raise the temperature. According to the present embodiment, though it is constituted so that a brim-shaped heater 13a is installed on the reactor structural component on the inlet side 1, it is also possible that a plane-shaped heater 13 is installed on the cylindrical face (cylinder-shaped peripheral face side) of the reactor A.

Example 1

[0051] According to Figure 1 to Figure 4, the reactor A has an outer diameter and thickness of 228mm ϕ and 37mm, respectively; the interior space V has the thickness and inner diameter of 17mm and 216mm ϕ , respectively; the reflectors 3a, 3b have a thickness and outer form of 3mm and 204mm ϕ , respectively; the gap L with the reactor structural component on the outlet side 2 is 1mm and the gap L with the reactor structural component on the inlet side 1 is 1mm; the length of the tapered face is approximately 21mm (inclination angle $\alpha = 8^\circ$); a platinum coating catalyst layer 6 is 0.8 μm (TiN barrier coat 7 = 5 μm + pt coat 8 = 0.3 μm); and the barrier coats 9, 10 of the inner wall face of the reactor structural component on the inlet side 1 and of the outer surface of the reflectors 3a, 3b are TiN (5 μm), respectively.

[0052] Also, reactor A is made so that the heat dissipation body substrate 15b of the cooler 15 has the external dimensions and thickness of 235mm x235mm and 10mm, respectively; the inner diameter of the heater insertion hole 23 of the

cooler on the outlet side 15₂ is 190mm ϕ ; the height of the heat dissipation fin 15a is 60mm; the height of the heat dissipation fin 15a of the cooler on the inlet side 15₁ is 25mm; and the thickness of the fin is 1.8mm. Furthermore, the outer diameter of the brim-shaped heater 13b is made to be 180mm ϕ (the thin plate- and plane-shaped heater 1mm thick).

[0053] After reactor A was heated to approximately 300~350°C by the plane-shaped heater 13, the mixed gas including O₂ and H₂ (O₂=10l/min and H₂=10l/min) was fed into the interior space V from the gas feed port 1a to generate moisture, and the temperature distribution, in a radial direction of the reactor structural component 2 at the position of 1.5mm inwardly from the platinum coating catalyst layer 6 of the reactor structural component on the outlet side 2, was measured using a temperature detector inserted into, and fixed to, the reactor structural component on the outlet side 2.

[0054] At the time of measurement, the cooling fan 18 of the temperature regulator B was brought to a halt, and the temperature of the brim-shaped heater 13a was set at 350°C. Figure 6 illustrates the results of the measurement. The test results reveal that the temperature (maximum temperature part) of the reactor structural component on the downstream side 2, in the vicinity of the periphery of the reflector 3b under conditions that the volume of moisture generated is 10SLM, can be suppressed approximately to 440°C.

[0055] [The Second Embodiment]

Figure 7 is a longitudinal cross sectional view of the reactor for generating moisture with regard to a second embodiment of the present

invention. Figure 8 is its plan view, and Figure 9 is a side view of the right side of the second embodiment.

[0056] Referring to Figure 7 to Figure 9, a reactor A for generating moisture is formed in a round and hollow disc shape by combining a stainless steel (SUS316L) made reactor structural component on the inlet side 1 and reactor structural component on the outlet side 2 positioned against each other and welding them hermetically. The afore-mentioned reactor structural component on the inlet side 1 is equipped with a round-shaped recess with a flat-shaped bottom therein, and a gas feed port 1a communicates with the inside of the recess. The reactor structural component on the outlet side 2 is equipped with a round-shaped recess with a flat-shaped bottom therein, and a moisture gas take-out port 2a communicates with the inside of the recess. Furthermore, flanges are formed inwardly on the peripheral edges of both reactor structural components 1 and 2, and both flanges are positioned against each other and hermetically welded 11.

[0057] The centers of the round-shaped reflectors 3a, 3b are positioned against the gas feed port 1a and the moisture gas take-out port 2a of both reactor structural components 1 and 2, respectively, and are fixed to both reactor structural components 1 and 2 using a fixing bolt 4 with a gap L located between the bottom faces of both reactor structural components by means of a spacer 5. The stainless steel (SUS316L) made reflectors 3a, 3b are made so that their diameters are slightly smaller than the inner diameters of the round recesses. As shown in Figure 7, the peripheral edges, positioned against both reactor structural components 1, 2, of the reflectors 3a, 3b are finished to have a taper

with an inclination angle α . The mixed gas G flowing in from the gas feed port 1a can flow out smoothly into the interior space V due to the inclination angle α , and flow in the gap between the reflector 3b and the reactor structural component on the outlet side 2 occurs such that local and intensive heat liberation of the platinum coating catalyst layer 6 positioned against the peripheral edge of the reflector 3b can be prevented.

[0058] The afore-mentioned platinum coating catalyst layer 6 is formed on the entire area of the inner surface of the SUS316L made reactor structural component on the outlet side 2 (excluding the area in the vicinity of the part which the spacer 6 makes a contact with the inner surface). The platinum coating catalyst layer 6 is made up of the TiN-made barrier coat 7 formed on the inner surface of the reactor 2 and the platinum coat 8 formed thereon.

[0059] The TiN-made barrier coat 9 and barrier coat 10 are formed on the inner surface of the reactor structural component on the inlet side 1 and on the outer surfaces of the afore-mentioned reflectors 3a, 3b. The barrier coats 9, 10 are for preventing local heat liberation by means of the metal catalytic action on the surfaces of the reactor structural component on the inlet side 1 and on reflectors 3a, 3b.

[0060] The temperature regulator B of reactor A comprises a plane-shaped heater 13 disposed to heat the outer side of the reactor structural component on the outlet side 2, a regulator (not illustrated) for on-off control of the plane-shaped heater 13, and a cooler 15 to cool the reactor A. The afore-mentioned plane-shaped heater 13 is a so-called thin-plate- and plane-shaped heater, and in this example, formed in the shape of a brim. The

plane-shaped heater 13 is attached to, and fixed to, the reactor structural component on the outlet side 2 by means of the round-shaped heater press 14. Specifically, as shown in Figure 9, the plane-shaped heater 13 is formed in a round shape having an outer diameter (180mm ϕ with the present embodiment) that is smaller than the outer diameter (228mm ϕ) of the reactor structural component on the outlet side 2, and the heater 13 is fixed directly to the reactor structural component on the outlet side by a bolt 19 through the mediation of the round-shaped heater press 14 that is provided with the same diameter as that of the plane-shaped heater 13. The plane-shaped heater 13 is installed only on the center part of the reactor structural component on the outlet side 2. Therefore, the present embodiment is different from the afore-mentioned conventional example shown in Figure 15.

[0061] The afore-mentioned cooler 15 comprises a cooler 15₁ on the inlet side adhered to the outer surface of the reactor structural component on the inlet side 1 and a cooler 15₂ on the outlet side adhered to the outer surface of the reactor structural component on the outlet side 2. The cooler 15₁ on the inlet side is formed to be a square-shaped integral unit with a 25mm high heat dissipation fin 15a and an approximately 5mm thick fin substrate 15b as shown in Figure 15.

[0062] As shown in Figure 8 and Figure 9, the cooler 15₂ on the outlet side is provided on the side of the reactor structural component on the outlet side 2 and is made up of a heat dissipation body substrate 15b, on which a heater insertion hole 23 having an inner diameter of 190mm is made in the center of the square-shaped heat dissipation body substrate, and a plural number of 60mm high thin-plate-shaped heat dissipation fins 15a. The 60mm high

thin-plate-shaped heat dissipation fins 15a are made like the teeth of a comb on the heat dissipation body substrate 15b except for the round-shaped hole. According to the present embodiment, a cooler 15 is employed that is made as an integral unit fabricated with an aluminum alloy made heat dissipation body substrate 15b (approx 10mm thick) and heat dissipation fins 15a (approx 2mm thick and 60mm high). According to Figure 7 to Figure 9, a thin-plate-shaped heat dissipation fin 15a is utilized as a heat dissipation body. However, it goes without saying that heat dissipation device of any shape can be used. For example, a rod-shaped heat dissipation pin can be used. Also, it goes without saying that although a square-shaped heat dissipation body substrate is employed in this embodiment for the second cooler 15₂ and the cooler 15₁ on the inlet side, the shape could be a round one or the like.

[0063] In Figure 9, 20 designates a fixing bolt for the cooler 15, 21 designates a fixing hole for the heater control thermometer and 22 designates a fixing hole for the thermometer to monitor the reactor's temperature. According to the present embodiment, although the height of the heat dissipation fin of the cooler 15₁ on the inlet side is made to be 25mm, it can be made to be 60mm in height, which is the same as that of the cooler 15₂ on the outlet side. Furthermore, according to the present embodiment, although the reactor A is constituted so that a heater is not installed on the side of the reactor structural component on the inlet side 1, the reactor can be so constituted such that a heater can be installed also on the reactor structural component on the inlet side 1.

[0064] According to the afore-mentioned embodiment shown in Figure 7 to Figure 9, the area of the heat dissipation body substrate 15b of the cooler 15₁ on

the inlet side is made to be about the same as that of the outer surface of the reactor structural component on the inlet side 1. However, it is possible that the reactor A is constituted so that the area of the heat dissipation body substrate 15b of the cooler 15₁ on the inlet side is made smaller, and the heat dissipation body substrate 15b is fixed to the inside part (specifically, the center part) of the reactor structural component on the inlet side 1 so that the inside part of the reactor structural component on the inlet side 1 is mainly cooled, and the brim-shaped heater is directly fixed to the outside of the outer surface of the reactor structural component on the inlet side 1 so that only the peripheral edge of the reactor structural component on the inlet side is heated by the brim-shaped heater.

[0065] Furthermore, according to the afore-mentioned embodiment in Figure 7 to Figure 9, 2 pieces of reflector 3a, 3b are installed inside the reactor A. However, it is possible that reactor A may be constituted so that one reflector 3 is installed to make the gas feed port 1a and moisture gas take-out port 2a positioned against each other as shown in Figure 10. In Figure 10, the constitution of reactor A is the same as that in Figure 7 except for the part corresponding to the reflector 3.

Example 2

[0066] In Figure 7 to Figure 9, the outer diameter of the reactor A was made to be 228mm ϕ ; its thickness is 37mm; the thickness of an interior space V is 17mm; the inner diameter is 216mm ϕ ; the thickness of reflectors 3a, 3b is 3mm; the outer form is 204mm ϕ ; the gap L with the reactor structural component on

the outlet side 2 is 1mm; the gap with the reactor structural component on the inlet side 1 is 1mm; the length of the tapered face approx 21mm (inclination angle = 8°); a platinum coating catalyst layer 6 is $5.3\text{ }\mu\text{m}$ (TiN barrier coat 7 = $5\text{ }\mu\text{m}$ + pt coat 8 = $0.3\text{ }\mu\text{m}$), and the barrier coats 9, 10 of the inner wall face of the reactor structural component on the inlet side 1 and the outer surface of reflectors 3a, 3b are TiN of $5\text{ }\mu\text{m}$, respectively.

[0067] External dimensions of the heat dissipation body substrate 15b of the cooler 15₁ on the inlet side and the cooler 15₂ on the outlet side were made to be $235\text{mm} \times 234\text{mm}$; its thickness is 10mm; the inner diameter of the heater insertion hole 23 of the cooler on the outlet side 15₂ is $190\text{mm } \phi$; the height of the heat dissipation fins 15a are 60mm; the height of the heat dissipation fins 15a of the cooler 15₁ on the inlet side are 25mm; and the thickness of the fin is 1.8mm. Furthermore, the outer diameter of the plane-shaped heater was made to be $180\text{mm } \phi$ (thin-plate- and plane-shaped heater, 1mm thick). The fixing hole 22 for the thermometer used to monitor the temperature of the reactor was installed in a position of 1.5mm inwardly from the inner surface of the reactor structural component on the outlet side 2.

[0068] After reactor A was heated to approximately $300\sim 350^\circ\text{C}$ with a plane-shaped heater 13, the gas mixed including O_2 and H_2 ($\text{O}_2 = 101/\text{min}$ (fixed), $\text{H}_2 = 101/\text{min}$ (variable)) was fed into the interior space V from the gas feed port 1a with free adjustment of the flow rate to generate moisture, and the temperature distribution in a radial direction of the reactor structural component 2, at the position of 1.5mm inwardly from the platinum coating catalyst layer 6 of the reactor structural component on the outlet side 2, was measured using a

temperature detector inserted into, and fixed to, the reactor structural component on the outlet side 2 making volume of moisture generated (specifically, the feeding volume of the mixed gas G) as a parameter.

[0069] Figure 11 shows the measurement results. Curve A₁ shows the case when the volume of moisture generated is 10SLM, Curve A₂ shows the case when the volume of moisture generate is 9SLM, and Curve A₃ shows the case when only the N₂ gas is fed to the reactor A. At the time these measurements were collected, the cooling fan 18 of the temperature regulator B was brought to a halt, and the temperature of the plane-shaped heater 13 was set at 350°C.

[0070] The testing results shown in Figure 11 reveal that the temperature (max temperature part) of the reactor structural component on the downstream side 2, at the position in the vicinity of the peripheral edge of the reflector 3b under conditions that the volume of moisture generated was 10SLM, could be suppressed to approx 450°C.

Example 3

[0071] Figure 12 shows, for the reactor A for generating moisture illustrated in Figure 7 to Figure 9, the results of measurements of the temperature distribution in a radial direction of the position in the vicinity of the inner surface of the reactor structural component on the outlet side 2 by making the volume of moisture generated a parameter. In accordance with the case in the afore-mentioned Example 2 in Figure 11, under conditions wherein the cooler 15₁ on the inlet side was removed, and the reactor A for generating moisture, which was constituted so that a round plane-shaped heater 13 having the outer

diameter of 228mm ϕ and the cooler 15 were employed and provided on the outer surface of the reactor structural component on the inlet side 1 as shown in Figure 15. Also, the conditions of the afore-mentioned Example 2 in 11 included setting the temperature of both plane-shaped heaters 13 of the upstream side and downstream side at 350°C, and to halt the cooling fan 18.

[0072] As apparent from Figure 12, the highest temperature observed with the volume of moisture generated of 10SLM was approx 470°C, which is slightly higher than the case of Example 2.

Example 4

[0073] Figure 13 shows the temperature distribution in a radial direction in the vicinity of the inner surface of the reactor structural component on the outlet side 2 at the time when the cooling fan 18 is operated when using the same reactor for generating moisture as that of the afore-mentioned Example 3. The cooling fan 18 used in this embodiment has the same cooling capacity as that of the conventional reactor of 5SLM shown in Figure 15.

[0074] Figure 14 shows, with the cooler 15₁ on the inlet side and the cooler 15₂ on the outlet side, as shown in Figure 7 to Figure 9, the relationship between the volume of moisture generated and the highest temperature in case where the height of the heat dissipation fin 15a was varied. Curve E₁ and Curve E₂ show the relationship between the volume of moisture generated and the temperature of the reactor structural component 2 (E₁ is the value measured by the thermometer for monitoring the temperature of the reactor and E₂ is the value detected by the thermometer for controlling a heater) when the height of heat

dissipation fins 15a of the cooler 15₁ on the inlet side and the cooler 15₂ on the outlet side was 25mm, respectively, and the cooling fan 18 was brought to a halt.

[0075] Curves F₁ and F₂ show the value measured by the thermometer for monitoring the temperature of the reactor in fixing hole 22 and the value measured by the thermometer for controlling a heater in fixing hole 21 in the case where the capacity of the cooling fan 18 is improved and the exhaust pressure inside the case constituting a reactor A for generating moisture is made -22PaG (diameter of the exhaust duct is 76mm ϕ and the displacement is 2.7m/min). Furthermore, Curves J₁ and J₂ show the value measured by the thermometer for monitoring the temperature of the reactor in fixing hole 22 and the value measured by the thermometer for controlling a heater in fixing hole 21, respectively, in the afore-shown Figure 9.

[0076] In accordance with the afore-mentioned embodiment in Figure 7 to Figure 9, a heater is made to be a disc- and plane-shaped heater. However, the shape of the heater can be triangular-shaped. In such a case, a triangular-shaped heater fixing hole 23 is to be made in the center of the heat dissipation body substrate 15b on the side of the cooler 15₂ on the outlet side. In accordance with the present embodiment, the reactor A is constituted so that a plane-shaped heater 13 is attached to the outer surface of the reactor structural component on the outlet side 2 (or to the outer surfaces of both reactor structural components 1 and 2) from the outside. However, it is also possible that a plane-shaped heater 13 is imbedded in (or fitted into) the outermost layer part of the reactor structural component on the outlet side 2 (or the outermost layer parts of both reactor structural components 1 and 2).

[0077] Furthermore, it is also possible that a heat dissipation body substrate 15b of the cooler 15₁ on the inlet side is made smaller in size so that it can be directly fixed to the outer surface of the inner side (center part) and a brim-shaped heater is fixed to the outside (peripheral edge) of the reactor structural component on the inlet side 1.

[0078] Figure 24 is a flow diagram of the moisture generating and feeding apparatus for which the reactor A, in accordance with the present invention, is employed. Figure 25 is a plan schematic view of the moisture generating and feeding apparatus, and Figure 26 is a longitudinal cross sectional schematic diagram of the moisture generating and feeding apparatus. In Figure 24 to Figure 26, A designates a reactor for generating moisture, 15₁ designates a cooler on the inlet side, 17 designates a H₂ sensor, 18 designates a cooling fan, 24 designates a mixer, 25 designates a gas filter, 26 designates a heater in the pipe passage, 27 designates a filter, 28 designates a gas take-out port, 29 designates a lead wire for a heater, and 30 designates a case body. The flow diagram of the moisture generating and feeding apparatus is generally the same as the flow diagram of a conventional one. Therefore, the explanation is omitted herewith.

[0079] With the moisture generating and feeding apparatus in accordance with the present invention, the external dimensions of the case body are set to be 380mm wide, 380mm deep and 465mm high. The width 380mm and depth 380mm are generally the same as those of a conventional moisture generating and feeding apparatus, but in the apparatus shown in Figure 21 and Figure 22 the height is approx 60mm shorter. As stated before, the reactor A can

generate the volume of moisture of 10SLM under conditions of the highest temperature of 450°C or less, and feed the volume of moisture approx 10 times the conventional one.

Feasibility of Industrial Use

[0080] The present invention is mainly utilized as a moisture feeding apparatus for semiconductor manufacturing facilities, an apparatus to remove the hydrogen gas out of the hydrogen containing gas or a moisture feeding apparatus for chemical agent manufacturing facilities, and the like.

Scope of Claim

What is claimed is:

[1] A reactor for generating moisture characterized by that it is so constituted that it comprises a reactor having an interior space formed by combining a reactor structural component on the inlet side having a gas feed port and a reactor structural component on the outlet side having a moisture gas stake-out port positioned against each other, one or more reflectors with centre of each reflector being positioned against the gas feed port and moisture gas take-out port in the interior space of the afore-mentioned reactor, a platinum coating catalyst layer formed on the inner wall face of the afore-mentioned reactor structural component on the outlet side, a heater to heat the reactor, and a cooler fixed to the outer surface of the reactor to cool the reactor; and with the reactor for generating moisture to make hydrogen and oxygen react under conditions of non-combustion by allowing hydrogen and oxygen fed from the gas feed port into the interior space of the reactor to contact with the afore-mentioned platinum coating catalyst layer to make the reactivity activated, the afore-mentioned cooler is made to be a cooler on the outlet side comprising a heat dissipation body substrate having a heater insertion hole in the center to fix to the outer surface of the reactor structural component on the outlet side, and a plural number of heat dissipation bodies installed perpendicularly on the area of the heat dissipation body substrate and one part of the heater to heat the afore-mentioned reactor is inserted in the cooler on the outlet side, to fix it to the outer surface of the reactor structural component on the outlet side.

[2] A reactor for generating moisture as claimed in claim 1, wherein it is so constituted that the cooler on the inlet side comprises a heat dissipation body substrate fixed to the outer surface of the reactor structural component on the inlet side and a plural number of heat dissipation bodies installed perpendicularly on the area of the heat dissipation body substrate.

[3] A reactor for generating moisture as claimed in Claim 1 or Claim 2, wherein said reactor structural component on the inlet side is provided with a heater.

[4] A reactor for generating moisture as claimed in Claim 2, wherein it is so made that the height of the heat dissipation body of a cooler on the inlet side and the height of the heat dissipation body of a cooler on the outlet side are made same or the height of the heat dissipation body of a cooler on the outlet side is made higher.

[5] A reactor for generating moisture as claimed in Claim 2, wherein it is so constituted that a plane-shaped heater is provided between the heat dissipation body substrate of a cooler on the inlet side and the outer surface of the reactor structural component on the inlet side.

[6] A reactor for generating moisture as claimed in Claim 2, wherein it is so constituted that the heat dissipation body substrate of the cooler on the inlet side is directly fixed to the outer surface of the inner part of the reactor structural component on the inlet side, and a brim-shaped heater is directly fixed to the outer surface of the outer part of the reactor structural component on the inlet side.

[7] A reactor for generating moisture as claimed in Claim 2 or Claim 3, wherein it is so constituted that the heat dissipation body substrate of the cooler on the inlet side is fixed to the outer surface of the reactor structural component on the inlet side positioned at the inner side part of a heater press fixed to the outer surface of the reactor structural component on the inlet side, and a heater is fixed between the outer surface of the outside part of the reactor structural component on the inlet side and the heater press.

[8] A reactor for generating moisture as claimed in Claim 1 to Claim 7, wherein it is so constituted that the heat dissipation body substrate of the cooler on the outlet side is directly fixed to the outer surface of the outside part of the reactor structural component on the outlet side, and the heater is directly fixed to the reactor structural component on the outlet side by making the heater inserted into the heater insertion hole made on the cooler on the outlet side.

[9] A reactor for generating moisture as claimed in Claim 1 to Claim 8, wherein it is so made that a heat dissipation body is made to be a thin-plate-shaped heat dissipation fin or a rod-shaped heat dissipation pin.

[10] A reactor for generating moisture as claimed in Claim 1 to Claim 8, wherein it is so made that the outer surfaces of the reactor structural component on the inlet side and the reactor structural component on the outlet side are made to be round-shaped, and the heat dissipation body substrates of both coolers are made to be either round-shaped or square-shaped, and the heater insertion hole installed on the heat dissipation body substrate of the cooler on the outlet side is made to be round-shaped.

[11] A reactor for generating moisture as claimed in Claim 1 or Claim 2, wherein the heater to heat a reactor is provided on a cylindrical face of the reactor.

[12] A reactor for generating moisture as claimed in Claim 1 or Claim 2, wherein a heater is made to be brim-shaped.

[13] A moisture generating and feeding apparatus as claimed in Claim 1 or Claim 2, wherein a reactor for generating moisture is employed.