ARTICLE COMPRISING A DIFFUSER WITH FLOW CONTROL FEATURES

Statement of Related Applications

The present invention is related to International Application No. PCT/US99/12772 filed June 8, 1999 entitled "Pharmaceutical Product and Methods and Apparatus for Making Same."

Field of the Invention

The present invention relates to improvements in an apparatus for the manufacture of pharmaceutical products.

Background of the Invention

In the pharmaceutical industry, pharmaceutical products are typically embodied as tablets, caplets, test strips, capsules and the like. Such products, which include diagnostic products, include one or more "unit dosage forms" or "unit diagnostic forms" (collectively "unit forms").

Each of the unit forms typically contains at least one pharmaceutically- or biologically-active ingredient (collectively "active ingredient") and, also, inert/inactive ingredients. Such active and inactive ingredients, typically available as powders, are suitably processed to create the unit forms.

In the above-referenced International Patent Application, which is incorporated herein by reference, applicant discloses an apparatus for manufacturing such unit forms. The apparatus utilizes an electrostatic deposition process whereby powder(s) containing active and/or inactive ingredients are deposited on a substrate at discrete locations thereby producing the unit forms. To provide context for the present invention, the deposition apparatus, its operation, and illustrative unit forms produced thereby are described below.

FIGS. 1-4 depict one embodiment of a unit form **6** produced by the electrostatic deposition apparatus. FIG. 1 depicts a plurality of such unit forms **6** arrayed on a strip **4**. In the illustrated embodiment, strip **4** comprises a substrate **8** and a cover layer **10**, each of

which comprise a substantially planar, flexible film or sheet. In some embodiments, one of either substrate **8** or cover layer **10** include an array of semi-spherical bubbles, concavities or depressions (hereinafter "bubbles") **12** that are advantageously uniformly arranged in columns and rows.

Unit form **6** comprises active ingredient **14**, a portion of cover layer **10** defining bubble **12**, and a region of substrate **8** within bonds **7**. FIG. 2 (showing cover layer **10** partially "peeled" back from substrate **8**) and FIG. 3 (showing a cross section of a portion of strip 4) depict a deposit of dry active ingredient **14**, in the form of a powder, disposed between substrate **8** and cover layer **10** within bubble **12**. FIG. 3 and FIG. 4 (showing a top view of a unit form **6**) depict substrate **8** and cover layer **10** attached to one another via bonds **7** that are near to and encircle bubble **12**.

Deposition Apparatus

FIG. 5 depicts, via a high-level block diagram, deposition apparatus **1** suitable for making unit form **6**. Apparatus **1** comprises platform **102** wherein unit forms **6** are produced. Platform **102** performs a variety of operations including the electrostatic deposition of dry powder on defined discrete regions of a substrate, materials handling, alignment operations, measurement operations and bonding operations.

Electrostatically-charged powder is delivered to platform **102** for deposition via powder feed apparatus **402**. In some embodiments, platform **102** and/or powder feed apparatus **402** are isolated from the ambient environment by an environmental enclosure. In such environments, environmental controller **EC** provides temperature, pressure and humidity control for platform **102** and powder feed apparatus **402**. Further description of platform **102** and powder feed apparatus **402** is provided later in this section.

Processor **P** and controller **C** control various electronic functions of apparatus **1**, such as, for example, the application of voltage for the electrostatic deposition operation, the operation of powder feed apparatus **402**, the operation of robots that are advantageously used in conjunction with platform **102**, and dose measurement operations. To facilitate such control functions, memory **M** is accessible to processor **P** and controller **C**.

FIGS. 6 and 7 depict a top view and a front elevational view, respectively, of illustrative platform **102**. In some embodiments, platform **102** comprises bench **214** that incorporates five processing stations that perform various operations used to produce the present product. Briefly, those processing stations include: storage station **220**, which advantageously comprises three substations **220A**, **220B** and **220C** for storing substrates and cover layers; alignment station **230** for assuring that the substrate and cover layer are properly adhered to a transport mechanism (*e.g.*, robotic elements) that delivers them to other processing stations; deposition station **250** where powder is deposited on the substrate; dose measurement station **240** for measuring the amount of powder that is deposited on the substrate; and lamination station **260** where the cover layer is laminated to the substrate.

As depicted in FIG. 7, four supports **216** elevate bench **214** above a table or like surface. Additionally, supports **216** advantageously provide a frame or superstructure for optional side-mounted barriers **218**, depicted in FIG. 6. The side-mounted barriers, in conjunction with a top barrier (not shown) and bench **214** define an environmental enclosure or chamber that isolates the region therein from the ambient environment under air or inert gas.

To facilitate the various processing operations, as well as materials handling between the processing stations, platform **102** advantageously includes a transport means. In the embodiment illustrated in FIG. 7, the transport means is a robotic system that includes first robotic transport element **270** and second robotic transport element **280** that are movable along first rail **290**. First rail **290** functions as a guide/support for movement in one direction (*e.g.*, along the x-axis). An additional rail (not shown) movably mounted on first rail **290** functions as a guide/support for movement in a direction orthogonal to but in the same plane (*e.g.*, the y-axis) as first rail **290**. Such rails collectively provide x-y motion. Drive means (not shown), such as x-y stepper motors, move robotic transport elements **270** and **280** along the rails.

Receiver **272** is attached to first robotic transport element **270** and "bonding" head **282** is attached to second robotic transport element **280**. Receiver **272** is operable to retrieve at least the substrate from the substation where it is stored (*i.e.*, **220A** or **220B** or **220C**) and to move it to at least some of the various operational stations **230-260** for processing.

Bonding head **282** is operable to join/seal the substrate and cover layer to one another to create the unit forms **6**.

First and second robotic transport elements **270** and **280** have telescoping components under servo control (not shown) that provide movement along the z axis (*i.e.*, normal to the x-y plane). Such z-axis movement allows receiver **272** and bonding head **282** to move "downwardly" toward a processing station to facilitate an operation, and "upwardly" away from a processing station after the operation is completed.

Moreover, robotic transport elements **270** and **280** advantageously include θ control components under servo control (not shown) that allow receiver **272** and bonding head **282** to be rotated in the x-y plane as may facilitate operations at a processing station. Compressed dry air or other gas is suitably provided to operate the robotic transport elements. Robotic transport elements **270** and **280** can be based, for example, on a Yaskawa Robot World Linear Motor Robot available from Yaskawa Electric Company of Japan.

As previously indicated, powder comprising an active ingredient is electrostatically deposited at discrete locations on substrate **8** at deposition station **250**. In the illustrated embodiments, accomplishing such deposition requires that, among other things, substrate **8** is transported to deposition station **250** from some other location, and that an electrostatic charge is developed that causes the powder to electrostatically deposit on substrate **80**. Such transport and charging operations are facilitated, at least in part, via receiver **272** and electrostatic chuck **302**.

FIG. 8 depicts a view of first surface **304** of electrostatic chuck **302**. Electrostatic chuck **302** comprises a layer **303** of dielectric material. The electrostatic chuck has a thickness of about 0.01 inches (0.25 mm), and, as such, is relatively flexible. Illustrative electrostatic chuck **302** has "through holes" **ECH** implemented as slots that are disposed at its periphery. First surface **304** further includes a plurality of powder collection zones **CZ**. In illustrative electrostatic chuck **302**, collection zones **CZ** are advantageously organized in eight columns $\mathbf{306}_{C1-C8}$ of twelve collection zones each for a total of ninety-six collection zones **CZ**. As will be described in further detail later in this specification, each collection zone **CZ** corresponds to a powder deposition location on the substrate (*see* substrate **8** in FIG. 1). Collection zones **CZ** are formed within electrostatic chuck **302** by an arrangement of

dielectric and conductive regions, several embodiments of which are described later in this section in conjunction with FIGS. 10a - 10c.

FIG. 9 depicts a view of second surface **308** of electrostatic chuck **302**. As depicted in more detail in FIGS. 10a - 10c, collection zones **CZ** are formed via electrical contact pads **310**. Such electrical contact pads **310** provide contact points for connection to a controlled voltage source.

Electrical contact pads **310** are electrically connected to selected other electrical contact pads via address electrodes **312**. By virtue of such groups of selected electrical connections (*e.g.*, the pads **310** within a given column $\mathbf{306}_{C1-C8}$ of illustrative chuck **302** of FIG. 9 define an illustrative grouping), a first voltage can be applied to contact pads **310** in column $\mathbf{306}_{C1}$, while a second voltage different from the first voltage can be applied to contact pads **310** in second column $\mathbf{306}_{C2}$, and so forth varying the voltage applied to contact pads **310** on a column-by-column basis as desired. It will be understood that the application of such different voltages to such different columns facilitates control of the powder deposition rate at collection zones **CZ** in each of such columns. In other embodiments, address electrodes are arranged differently thereby creating electrical interconnects between differently-arranged groupings of contact pads **310**. For the layout of contact pads **310** and address electrodes **312** depicted in FIG. 9, voltage need only be applied to a single contact pad **310** within a given column **306** to develop substantially the same electrostatic charge at each contact pad **310** within that column.

FIGS. 10a -10c depict several illustrative embodiments of structural arrangements suitable for forming collection zones **CZ** within an electrostatic chuck, such as electrostatic chuck **302**. For clarity of illustration, the structure associated with only a single collection zone **CZ** of an electrostatic chuck is depicted in FIGS. 10a - 10c.

In a first embodiment depicted in FIG. 10a, a conductive material **314** is disposed through layer **303** of dielectric at each region designated to be a collection zone **CZ**. The conductive material overlays a portion of first surface **304** and second surface **308** of the electrostatic chuck. The portion of conductive material **314** overlying first surface **304** comprises a powder-attracting electrode **316A**, while the portion of conductive material **314** overlying the second surface **308** comprises electrical contact pad **310A** (which is one

embodiment of electrical contact pad **310** previously mentioned). A shield electrode **318** (also termed a "ground electrode" based on a preferred bias) is disposed within layer **303**.

Applying a voltage to electrical contact pad **310A** generates an electrostatic field at powder-attracting electrode **316A** at collection zone **CZ**. As described later in this section, the electrostatic field attracts charged powder to the substrate **8** that engages first surface **304** of the electrostatic chuck. Additionally, the electrostatic field aids in holding substrate **8** flat against first surface **304**. Tight adherence of the substrate **8** to the electrostatic chuck increases the reliability, consistency, *etc.*, of powder deposition at the collection zones. A reduced pressure that is developed in receiver **272** to which the substrate **8** is exposed also assists in adhering the substrate to the electrostatic chuck.

FIG. 10b depicts a second illustrative embodiment where via hole **V** is formed at electrical contact pad **310B** and powder-attracting electrode **316B**. FIG. 10c depicts a third illustrative embodiment wherein an additional layer **305** of dielectric material separates powder-attracting electrode **316C** from substrate **8**. Electrical contact-pad **310C** overlays second surface **308**.

The electrostatic chuck provided by the configuration depicted in FIG. 10c can be termed a "Pad Indent Chuck" which is useful, for example for powder depositions of less than about 2 mg, preferably less than about 100 μg, per collection zone **CZ** (assuming, for example, a collection zone having a diameter within the range of 3-6 mm diameter). The electrostatic chuck provided by the configuration depicted in FIG. 10a can be termed a "Pad Forward Chuck" which is useful, for example, for powder depositions of more than about 20 μg per collection zone **CZ** (again assuming a collection zone of about 3-6 mm diameter). The Pad Forward Chuck is more useful than the Pad Indent Chuck for higher dose depositions.

As described further below, electrostatic chuck **302** is engaged to receiver **272** during at least some deposition-apparatus operations (*e.g.*, during electrostatic deposition of powder on the substrate **8**). FIG. 11 depicts underside **274** of receiver **272** with electrostatic chuck **302** adhered thereto. Electrostatic chuck **302** has alignment features **320**, such as pins or holes, by which it is aligned to complementary holes or pins (not shown) in the receiver. Also depicted are alignment pins **276** that are received by complementary holes in bench **214** for aligning receiver **272** to various processing stations (*e.g.*, deposition station **250**). Height-

adjustable vacuum cups **278** are advantageously used to attach an alignment frame (not shown), which can be used in conjunction with the substrate, to the receiver.

The powder deposition process proceeds via electronic control of electrostatic chuck **302**. As previously described, the deposition apparatus **1** advantageously includes central processor **P** and controller **C** for performing calculations, control functions, *etc.* (*see* FIG. 5). Processor **P** receives performance input from multiple sources, including, for example, on-board sensors and historical data from dose measurement station **240**, and uses such information to determine if operating parameters should be adjusted to keep powder deposition within specification. Such input includes, for example, data pertaining to the rate of powder flux into and through the deposition engine (made up of powder feed apparatus **402** and deposition station **250**) and the degree to which powder is being evenly deposited at electrostatic chuck **302**. The "on-receiver" electronics described below, either alone or in conjunction with processor **401** and controller **403**, provide a means for adjusting apparatus **1** during operation.

In embodiments in which processor **P** has primary responsibility for processing functions, a secondary processor (not shown) located in receiver **272** functions as a communications board that receives commands from processor **P** and relays such commands to an addressing board (not shown), also located in receiver **272**. The addressing board then sends bias control signals (DC or AC signals) for controlling the voltage applied to electrical-contact pads **310**. Depending upon the addressing scheme (*e.g.*, the arrangement, if any, by which individual electrical-contact pads **310** are electrically interconnected via address electrodes **312**), voltage is either regionally (*e.g.*, by columns, rows, *etc.*) or individually applied.

The addressing board preferably has multiple channels of synchronized output (e.g., square wave or DC). The signals sent to the addressing board can be encoded, for example, with a pattern of square wave voltage pulses of varying magnitudes to identify a particular electrical-contact pad/powder-attracting electrode, or a group of such electrodes, together with the appropriate voltage to be applied thereto.

The bias control signals are sent via a high voltage board (not shown), which advantageously has multiple channels of high-voltage converters (transformers or HV DC-to-

DC converters) for generating the voltages, such as 200 V or 2,500 V or 3,000 V (of either polarity), that energizes powder-attracting electrodes **310**. The high voltage board is advantageously located in receiver **272** so that other systems are isolated therefrom.

In some embodiments, the "secondary" on-receiver processor receives data directly from "charge" sensors (not shown) that are positioned on or adjacent to electrostatic chuck **302**. Such sensors monitor the amount of powder being deposited. The on-receiver processor locally interprets and responds to data from such sensors by suitably adjusting the voltage applied to the electrical contact pads/powder-attracting electrodes.

***Operation of the Deposition Apparatus* (Refer to FIGS. 6-7)**

In operation, first robotic transport element **270** moves receiver **272** and electrostatic chuck **302** adhered thereto (*see* FIG. 11) to storage station **220**. At station **220a**, electrostatic chuck **302** engages a "virgin" substrate and, in some embodiments, also engages an alignment frame (not shown) that is joined to the substrate.

In one embodiment, after engagement, robotic transport element **270** moves receiver **272**, electrostatic chuck **302**, the substrate and frame to alignment station **230**. At the alignment station, the substrate is brought into contact with a pad (*e.g.*, urethane foam, *etc.*). Such contact advantageously smoothes the substrate against electrostatic chuck **302**. After the substrate is smoothed against the substrate, a suction force is applied that holds the substrate against electrostatic chuck **302**. Flattening and smoothing the deposition surface (*i.e.*, the substrate) in such manner improves the consistency of the powder deposits thereon. In another embodiment, alignment station **230** is not used. Rather, shot pins (not shown) and compliance in the robotic transport element provide such functionality.

Robotic transport element **270** then moves engaged receiver **272**, electrostatic chuck **302**, the substrate and frame to dose measurement station **240**. After aligning with a measurement apparatus **242** at station **240**, the substrate is scanned via a measurement device and distances from a reference point to the substrate at each collection zone **CZ** (*see* FIGS. 8, 10a-10c and 11) are calculated and recorded to provide baseline data.

Robotic transport element **270** then moves engaged receiver **272**, electrostatic chuck **302**, the frame and virgin substrate to deposition station **250**. At deposition station **250**, the

substrate abuts gasket **259** that frames deposition opening **258** (*see* FIG. 6). The powder deposition engine (*see* FIG. 13) is turned on and powder is electro-deposited through deposition opening **258** on the substrate at regions overlying the electrostatic chuck's collection zones **CZ**.

At the completion of the powder-deposition operation, robotic transport element **270** returns the substrate, with its complement of discreetly deposited powder, to dose measurement station **240**. At that station, the measurement device again scans the substrate to determine the distance between the reference point to the surface of each "deposit" of powder. From such distances, and the previously obtained baseline data, the amount (*e.g.*, volume) of powder in each deposition is calculated. If the calculated amount is outside a desired range of a predetermined target amount, such information is displayed. An operator can then suitably adjust operating parameters to bring the process back into specification. In another embodiment, automatic feed back is provided to automatically adjust the process, as required. The "out-of-spec" unit forms may be discarded.

Regarding dose measurement, either one or both of two optical measurement methods may be used: diffuse reflection and optical profilometry, both of which methods are known in the art.

The diffuse reflection method is based on reflecting or scattering a probe light beam, such as a laser beam, off of the powder in directions that are not parallel to the specular reflection direction. Applicants have discovered that measurements obtained based on diffuse reflection using non-absorbing radiation provide a strong correlation with the deposited amount of powder in a unit form, at least up to a certain amount. The limiting amount varies with the character of the powder and is believed to correspond to an amount of powder that prevents light penetration into lower layers.

Diffuse reflection in a non-absorbing region provides good accuracy in measuring dose deposition amounts ranging from 50-400μg, or even as high as 750 μg to 1 mg, for a 3 or 7 mm deposition "dot," depending on the characteristics of the powder. The diffuse reflection method can detect substantially less than a mono-layer of powder. If the deposit is more than a mono-layer, the probe light beam must partially penetrate the upper layers so that it can be affected by the reflection off of the lower layers to provide an accurate

measurement. There tends, however, to be a practical limit (dependent upon the powder) to deposition thickness for it to exhibit "Lambertian" characteristics required for measurement via diffuse reflection. Diffuse reflection is also a measure of the physical uniformity of the dose deposits at the above-listed ranges.

Optical profilometry is useful for obtaining dose measurements that are above the ranges that can be accurately measured by the diffuse reflection method. In optical profilometry, light is directed to the deposit and scattered therefrom at an angle that is indicative of the height of the deposit. That height is readily calculated by triangulation. The profilometer can be, for example, a confocal profilometer. A confocal profilometer suitable for use in conjunction with the present invention is available from Keyence (Keyence Corp., Japan, or Keyence Corporation of America, Woodcliff Lake, NJ) as Model LT8105.

Continuing, second robotic transport element **280** picks up a cover layer and, advantageously, an alignment frame from storage station **220** and delivers them to lamination support block **502** (*see* FIG. 12) at lamination station **260**. After measurements are completed at dose measurement station **240**, first robotic transport element **270** delivers the substrate with the deposited powder to lamination station **260**. First robotic transport element **270** places substrate **8** on cover layer **10** such that the deposits of powder **14** are properly aligned within the perimeter of the bubbles **12** in the cover layer **10** (*see* FIG. 12).

After first robotic transport element **270** moves away, second robotic transport element **280** returns and, by the operation of bonding head **282**, attaches the substrate and cover layer together, forming a plurality of unit forms on a strip (*see* FIG. 1). In an automated system, the unit forms may be automatically transferred to a packaging station wherein out-of-specification unit forms are screened out and in-spec unit forms are appropriately packaged.

Apparatus **1** for electrostatic deposition provides a product containing a plurality of pharmaceutical or diagnostic unit forms, each comprising at least one pharmaceutically or diagnostic active ingredient that advantageously does not vary from a predetermined target amount by more than about 5%.

The deposition "engine," which comprises deposition station **250** on platform **102** and powder feed apparatus **402**, can be a source of a variety of operational problems. Such problems include, for example, powder compaction, non-uniform powder flux, powder loading difficulties, operating instabilities and powder size limitations, among others. While the powder feed apparatus that is disclosed in International Application No. PCT/US99/12772 (and described briefly below) has been designed to avoid many of such problems, room for improvement in that apparatus exists. Such improvement is a goal of the present invention. Before addressing such improvements, which are described later in this Specification in the "Summary" and "Detailed Description" sections, an embodiment of the existing powder feed apparatus is described.

The Deposition Engine

Illustrative powder feed apparatus **402** includes powder-delivery system **403**, which charges the powder via a powder-charging system **416** and delivers it to powder distributor **418.** The powder distributor delivers the charged powder to deposition station **250** for deposition on the substrate **8** (electrostatic chuck and receiver not shown for clarity of illustration) that abuts gasket **259** framing deposition opening **258**. Powder that is not deposited on the substrate is drawn back by a pressure differential through powder-evacuation tubes **426** to powder trap **428**. Gas exiting powder trap **428** is delivered to HEPA filter **430**.

In the illustrated embodiment, powder-delivery system **403** comprises auger rotation motor **404**, hopper **406**, vibrator **408**, auger **410**, clean gas source **414** feeding modified venturi feeder valve **412**, and powder-charging system **416**, interrelated as shown. In some embodiments, feeder valve **412** feeds powder-charging system **416**. With the exception of powder-charging system **416,** illustrative powder delivery system **403** is disposed substantially within enclosure **432**, which is depicted in phantom for clarity of illustration.

In the illustrated embodiment, the powder-charging system is realized as a tube, referred to hereinafter as powder-charging feed tube **416**. It will be understood, however, that in other embodiments, arrangements for powder charging other than the illustrated tube may suitably be used.

In place of venturi **412**, a gas source can be provided to propel powder through powder charging feed tube **416**. In one embodiment, gas source **414** directs gas pressure towards the outlet of a mechanical device that feeds powder. The gas jet can be directed and adjusted to act to de-agglomerate powder at that outlet.

In an alternate embodiment (not depicted), the hopper and auger arrangement depicted in FIG. 13 can be replaced with a rotating drum that temporarily stores powder and delivers it to a movable belt. The movable belt then transports the powder to a means for removing the powder from the belt. An example of such a means is a thin, high velocity jet of gas that blows the powder into powder charging feed tube **416** or a conduit in communication therewith.

For electrostatic deposition, the powder must be charged. This function is accomplished, as described above, by the powder-charging system (*e.g.*, powder-charging feed tube **416**). Some further details concerning powder charging is now provided.

In one embodiment, powder charging feed tube **416** is made of a material that imparts, by triboelectric charging, the appropriate charge to the powder as it transits the tube making periodic collisions with the sides thereof. As is known in the art, TEFLON®, a perfluorinated polymer, can be used to impart a positive charge to the powder (where appropriate for the powder material) and Nylon (amide-based polymer) can be used to impart a negative charge.

In so charging the powder, the tube builds up charge which can, if not accommodated, discharge by arcing. Accordingly, a conductive wrap or coating is applied to the exterior of powder charging feed tube **416** and grounded. Tube **416** can be wrapped, for example, with aluminum or copper foil, or coated with a colloidal graphite product such as Aquadag®, available from Acheson Colloids Co. of Port Huron, MI. Alternatively, powder charging feed tube **416** can be coated with a composition comprising graphite or another conductive particle such as copper or aluminum, an adhesive polymer, and a carrier solvent, mixed in amounts that suitably preserves the "tackiness" of the adhesive polymer. An example of such a composition is 246 g trichloroethylene, 30 g polyisobutylene and 22.5 g of graphite powder.

The charge relieved by the grounding procedures outlined above can be monitored to provide a measure of powder flux through powder charging feed tube **416**. This data is advantageously sent to processor **P** for analysis. As a result of such analysis, deposition operating parameters can be modified, as appropriate, to maintain an on-specification operation.

Another way to impart charge to the powder is by "induction" charging. One way to implement induction charging is to incorporate an induction-charging region in powder charging feed tube **416**. More particularly, at least a portion of powder charging feed tube **416** comprises a material such as a stainless steel, which is biased by one pole from a power supply, with the opposite pole attached to a nearby metallic structure that the powder is made to contact. Consequently, a high field region is created at the point of contact. The point of contact can be changed, as required, to impart the desired amount of charge to the powder. In one embodiment, induction charging is used in conjunction with the tribocharging features described above.

In yet another embodiment, powder is charged by "corona charging," familiar to those skilled in the art. *See*, for example, J.A. Cross, "Electrostatics: Principles, Problems and Applications," IOP Publishing Limited (1987), pp. 46-49.

As previously indicated, powder charging feed tube **416** feeds charged powder via powder distributor **418** into deposition station **250**, which is enclosed by enclosure **252**. In the illustrated embodiment, powder distributor **418** comprises rotating baffle **424** that depends from nozzle **422**. Nozzle motor **420** drives the rotating baffle.

Powder moving towards substrate **8** passes through control grid **254**. Control grid **254** is advantageously disposed a distance of about one-half to about 1.0 inch below collection zones CZ of the electrostatic chuck (not shown in FIG. 12), and is biased at about 500V per one-half inch of such distance at the polarity intended for the powder. Control grid **254** thus regulates the field near the chuck from variations in the field produced by the charged powder cloud lower in the deposition station **250**.

Control grid **254** can be, for example, a series of parallel electrical wires, such as can be formed from "switchbacks" of one wire, or, alternatively, a grid of wires. Spacing

between parallel sections of wire is advantageously within the range of about 5 to about 15 mm. The rate of powder cloud flux can be monitored by measuring light attenuation between light emitter **256** (*e.g.*, a laser emitter) and light detector **257**. This value can be transmitted to processor **P**.

It has been found that fluctuations occur in the gas/powder flow through the deposition engine described above. Such fluctuations negatively impact deposition performance. The fluctuations are due, at least in part, to:

(1) the non-axisymmetric geometry of some embodiments of rotating baffle **424** and deposition station **250**;
(2) the pulsing manner in which powder is delivered by some embodiments of powder delivery system **403**; and
(3) flow instabilities due to boundary layer separation and vortex shedding.

It will be appreciated that it is desirable to reduce such gas/powder flow fluctuations to improve the performance of the deposition apparatus.

Summary of the Invention

In accordance with the illustrative embodiment of the present invention, flow fluctuations observed in the existing deposition apparatus are reduced using a flow diffuser. The flow diffuser, which replaces the powder distributor of the existing deposition apparatus, comprises a conduit having a cross-sectional area that increases in the direction of powder flow. The increase in cross section controllably slows the gas flow to a velocity wherein electrostatic forces dominate the motion of the powder transported via the gas.

In some embodiments, the diffuser includes one or more flow control features. A first flow-control feature comprises one or more appropriately-shaped annular slits through which gas is injected into a "boundary layer" near the wall of the diffuser. The injected gas has a greater momentum than the gas in the boundary layer. Such injected gas serves several purposes, as itemized below.

1. Reducing the tendency for boundary-layer separation.

2. Directing/shaping the "powder cloud" (*i.e.*, the powder-transporting gas) towards a central axis of the diffuser. Such shaping counteracts an existing tendency for charged particles to repel one another, which tendency would otherwise cause the powder to migrate away from the central axis of the diffuser.
3. Providing a "gas-curtain" effect that reduces the tendency for powder contained in the powder cloud to get stuck against the diffuser wall.

A second flow control feature comprises one or more annular slits, or a multiplicity of slots/holes that are disposed at appropriate locations around the circumference of the diffuser. Such openings are in fluid communication with a pressure-differential generating means. The pressure-differential generating means generates a pressure differential across the openings in the diffuser such that pressure on the exterior of the diffuser is less than the pressure in the interior of the diffuser. As such, a portion of the powder-transporting gas in the slow-moving boundary layer is removed. Removing such slower-moving gas contributes to a flattening of the velocity profile of the powder-laden gas in the diffuser. And, such velocity-profile flattening tends to stabilize the powder-laden gas flow by preventing flow separation or at least delaying its onset.

Thus, the diffuser, the flow control features, and other elements related to powder delivery to the deposition station advantageously reduce spatial and temporal variations in the velocity of the powder-laden gas. The resulting increase in the uniformity of the flow-field improves control over the deposition operation. Such improved control results in an improvement in the uniformity and precision (*i.e.*, the variation in the amount of active ingredient from a target amount) of depositions.

Brief Description of the Drawings

FIG. 1 depicts an isometric view of a strip containing a plurality of unit forms.

FIG. 2 depicts a cover layer of a strip package partially separated from a substrate.

FIG. 3 depicts a side view of an illustrative unit form.

FIG. 4 depicts a top view of the illustrative unit form of FIG. 3.

FIG. 5 depicts a high-level block diagram of an apparatus suitable for producing the unit forms of FIGS. 1-4.

FIG. 6 depicts a top view of a platform wherein processing operations occur.

FIG. 7 depicts a side elevation of the platform of FIG. 7.

FIG. 8 depicts a plan view of a first surface of an illustrative electrostatic chuck.

FIG. 9 depicts a plan view of a second surface of an illustrative electrostatic chuck.

FIGS. 10a - 10c depict side cross-sectional views of embodiments of the electrostatic chuck of FIGS. 8 and 9 near a collection zone.

FIG. 11 depicts the underside of the illustrative receiver with the electrostatic chuck adhered thereto.

FIG. 12 depicts a lamination support block for laminating the substrate and cover layer together.

FIG. 13 depicts a deposition engine for electrostatically depositing powder on a substrate.

FIG. 14 depicts a portion of an improved deposition apparatus in accordance with the present teachings, the depicted portion including a diffuser.

FIG. 15 depicts an illustrative boundary-layer gas injector.

FIG. 16 depicts a top cross-sectional view of a first illustrative embodiment of an annular channel in a boundary-layer gas injector and four injection nozzles.

FIG. 17 depicts a top cross-sectional view of a second illustrative embodiment of an annular channel in a boundary-layer gas injector and four injection nozzles.

FIG. 18 depicts an illustrative embodiment of a manual control system for adjusting boundary-layer gas injection responsive to the powder deposition data.

FIG. 19 depicts an illustrative embodiment of an automatic control system for adjusting boundary-layer gas injection responsive to the powder deposition data.

FIG. 20 depicts a characteristic angle used to describe the diffuser configuration.

FIG. 21 depicts a further embodiment of a diffuser in accordance with the present teachings.

FIG. 22 depicts an illustrative flow straightener for use in conjunction with the present diffuser.

FIG. 23 depicts a cross-sectional end-view depicts tubes within a flow straightener.

FIG. 24 depicts a side view of a focusing electrode for use in conjunction with electrostatic deposition.

FIG. 25 depicts the focusing electrode as viewed from the bottom of the electrostatic chuck.

Detailed Description of the Invention

In this Detailed Description, reference is made to well-understood fluid dynamics concepts, including, for example, "boundary layer" and "flow separation" theory. Since such concepts are well-known to those skilled in the art, they will not be defined or discussed herein.

FIG. 14 depicts a portion of deposition apparatus **1A** in accordance with the present teachings. The portion of apparatus **1A** depicted in FIG. 14 includes a region of powder-charging feed tube **416**, flow straightener **517**, diffuser **518**, and deposition station **550**. FIG. 14 also shows substrate **8**, electrostatic chuck **302** and receiver **272** all engaged to deposition station **550**.

Powder-laden gas leaves powder-charging feed tube **416** and enters flow straightener **517**, wherein turbulence in the powder-laden gas is reduced. As described in further detail later in this Specification, the flow straightener can be used to tailor the flow profile within the diffuser. From the flow straightener **517**, the powder-laden gas enters diffuser **518**. The cross-sectional area of diffuser **518** increases in the direction of flow. As such, average fluid velocity decreases as the powder-laden gas **540** moves through diffuser **518**. As the powder-laden gas flows through the diffuser, it eventually encounters a region wherein the gas

velocity slows to the extent that electrostatic forces generated by the spacecharge of the powder, electrostatic chuck **302** and optional focusing electrode (*see* FIGS. 16 and 17) dominate the motion of the powder. This region is referred to herein as "particle drift zone **534**." The specific location of particle drift zone **534** is dictated by flow parameters and electrostatic-field strength. By way of illustration, in some embodiments, the particle drift zone may occupy as much or more than the latter one-half of the diffuser.

Diffuser **518** is formed from a material that is compatible with the deposition process being used. For example, in the illustrated embodiments, the diffuser is used in conjunction with an electrostatic deposition process. As such, the interior surface of wall **521** of diffuser **518** must be capable of accepting an electrical charge and maintaining it. Moreover, the material must be compatible with the charging characteristic of the powder and the charging method (*e.g.*, if the powder is positively charged, the material comprising wall **521** must not change the positive charge to a negative charge). Furthermore, to the extent that the diffuser is used in conjunction with a process that is producing pharmaceuticals, the material must satisfy pertinent FDA regulations.

As will be apparent to those skilled in the art, when the present diffuser is used in conjunction with an electrostatic deposition process, the diffuser should be formed from a dielectric material, such as any one of a variety of plastics, including, without limitation, acrylic and polycarbonate plastics. To the extent that the present diffuser is used in conjunction with other types of powder deposition processes, or more generally, in other types of powder-delivery systems, other materials requirements may be controlling.

Charged powder **544** is moved through the diffuser under the control of aerodynamic forces of the flowing fluid until it enters particle drift zone **534**. In the particle drift zone, electrostatic forces control powder movement, since, in this region of the diffuser, such forces dominate aerodynamic forces. In other words, in particle drift zone **534**, the powder does not follow the flow streamlines of the gas.

Gas **542**, substantially sans powder, is withdrawn from diffuser **518** at annular slit **530**. The gas is ultimately withdrawn via several circumferentially-located outlets **526**. The annular slit **530** is advantageously well rounded, as depicted at region **532**, to avoid introducing turbulence into the uniform flow profile established by diffuser **518.** Powder

544 is deposited on substrate **8** at regions overlying the collection zones (not shown) of electrostatic chuck **302**.

In some embodiments, one or more flow-control features are advantageously used in conjunction with diffuser **518**. A first flow control feature is the injection of gas **548** into the "boundary layer" flow within the diffuser. The injected gas, which can be, for example, nitrogen, should have a greater momentum than the powder-laden gas flowing in the boundary layer (such momentum calculations are readily performed by those skilled in the art). The injected gas is introduced through a boundary-layer gas injector, which comprises one or more annular slits in diffuser **518**. In the embodiment depicted in FIG. 14, gas is injected into the boundary-layer at two locations: a first injection slit **520** disposed near the inlet of diffuser **518** and a second injection slit **522** disposed near the mid-point of the diffuser.

The boundary-layer injection gas is injected into the diffuser in the form of a thin stream, and is "directed" to flow along wall **521**. In one embodiment, the gas is directed toward wall **521** by having the injection slits (*e.g.*, **520** and **522**) inject the gas *towards* wall **521**. In another embodiment, the injection slits inject the gas *along* wall **521**. And, in a further embodiment, the injection slit is substantially perpendicular to wall **521** of the diffuser (*i.e.*, nominally directing injected gas *away from* nearby wall **521** and towards the central flow region). In this latter embodiment, the "upstream" wall of the slit (*i.e.*, the slit wall nearest the diffuser inlet) is provided with a sharp edge, and the "downstream" wall of the slit is provided with a well-rounded edge. As a result of this arrangement, the injected gas turns the rounded edge to remain near wall **521**. This effect, known as the Coanda effect, is known to those skilled in the art.

The boundary-layer gas injection improves flow uniformity. In particular, such injection reduces or prevents flow separation at the interior surface of wall **521** of diffuser **518**. Moreover, gas injection effects a "shaping" or "steering" of powder-laden gas **540** toward central axis **519** (*see* FIG. 15) of diffuser **518**. Such steering counteracts the tendency of the charged particles to move away from the central axis due to the mutual repulsion of such similarly-charged particles. Additionally, such gas injection provides a "gas curtain" effect, wherein powder contained in the gas **540** is kept away from the interior

surface of diffuser wall **521**, thereby reducing the tendency for powder to accumulate thereon.

Further embodiments of illustrative boundary-layer gas injectors are described in conjunction with FIGS. 15-19. FIG. 15 depicts an "enlargement" of the region near injection slit **520** of diffuser **518** depicted in FIG. 14. In the embodiment depicted in FIG. 15, the boundary-layer gas injector further comprises two nozzles **660A** and **660B**, annular channel **662**, and fasteners (received by bores **664A** and). The gas that is to be injected into the boundary layer is delivered to annular channel **662** from nozzles **660A** and **660B**. Fasteners, such as screws or the like (not shown) that are received by bores **664A** and **664B** control the size of slit **520**. In particular, tightening one of the fasteners (*e.g.*, the fastener in bore **664A**) more than the other fastener (*e.g.*, the fastener in bore **664B**) causes the slit to be slightly larger at one region (*e.g.*, near bore **664B**) than at another region (*e.g.*, near bore **664A**).

When the flow rate of injection gas into nozzles **660A** and **660B** is equal, the flow of injection gas through injection slit **520** will be relatively greater at a region at which the injection slit is relatively larger. It has been found that such a variation in the boundary layer gas injection will affect flow distribution near the outlet of diffuser **518** and can ultimately affect the powder distribution on substrate **8**.

In a further embodiment of a diffuser in accordance with the present teachings, boundary layer gas injection is regionally varied by introducing additional injection nozzles, as is depicted in FIG. 16. FIG. 16 depicts a top-cross sectional view of the annular channel **662**. As shown in FIG. 16, four nozzles **660A – 660D** deliver injection gas to annular channel **662**. By individually varying the flow of injection gas through nozzles **660A – 660D**, the flow distribution near the outlet of diffuser **518** can be affected (*e.g.*, a greater amount of powder can be directed to a particular region of the substrate). While four nozzles are depicted in FIG. 16, a greater number of nozzles can be used, thereby providing an even greater measure of control over the downstream powder distribution.

FIG. 17 depicts yet a further embodiment wherein annular channel **762** is segmented into regions via dividers **766**. The flow of injection gas within a particular region of the channel is thus dictated via the nozzle feeding that region. Such an arrangement is expected

to provide a greater measure of control over downstream powder distribution than continuous annular channel **662** depicted in FIG. 16.

As described earlier in this Specification, "charge" sensors (which actually measure current) disposed on or near electrostatic chuck **302** can be used to determine the amount of powder being deposited on a regional basis on the substrate. In some embodiments, sensors are provided at each collection zone **CZ** such that the powder distribution is known at each point across substrate **8**. Such information can be used as the basis for a closed-loop control system (feedback or feedforward) wherein the boundary-layer gas injection flow is adjusted to correct any deviations in the powder distribution.

FIG. 18 depicts a manual control scheme wherein the output from the charge sensors **CS** is delivered to processing electronics **PE**, and an indication of the powder distribution is provided to an operator (*e.g.*, displayed on a display device **DD**). The operator can then manually adjust the boundary-layer gas injection via flow-control means, such as mass-flow controllers **MFC**, that individually control the flow of injection gas through each nozzle **660**.

FIG. 19 depicts an automatic control loop wherein the output of the charge sensors **CS** is delivered to appropriate processing electronics **PE** including a suitably-programmed processor **PP** that determines how the boundary layer flow should be adjusted to correct deficiencies in the powder distribution. One or more signals **RS** are generated that reset the set-point of a controller **FC** that controls the operation of a flow-control valve **CV** feeding each nozzle **660**. Controllers **FC** generate a control signal **CS** that causes the controlled valve to incrementally open or close thereby increasing or decreasing flow therethrough.

A second flow control feature that is used in conjunction with some embodiments of the present diffuser comprises a "boundary layer" gas *suction*, wherein gas is withdrawn from the slowly-moving boundary layer (not depicted) adjacent interior surface of wall **521** through a boundary-layer gas aspirator. The boundary-layer gas aspirator comprises one or more openings in wall **521** for withdrawing gas **546**, and a pressure-differential-generating means that creates a pressure differential across such openings to draw gas **546** therethrough. In the embodiment depicted in FIG. 14, the boundary-layer gas aspirator comprises multiple rows of slots **524** disposed in wall **521**. As depicted in FIG. 14, slots **524** are advantageously offset, on a row-by-row basis, from slots **524** in an adjacent row. In other embodiments, an

annular slit configured in the manner of injection slits **520** and **522** can be used for the boundary layer gas suction.

In the illustrated embodiment, the pressure-differential-generating means includes a pressure-tight shell/enclosure **528** and a suction flow generating means (not shown) that is in fluid communication with shell **528**. The suction flow generating means creates a flow **550** out of said enclosure **528**. Flow **550** establishes the pressure differential across holes **524** that withdraws gas **546** from the boundary layer. Flow **550** can be generated in a variety of well-known ways, such as, for example, by using a piston or diaphragm-type vacuum pump or a jet ejector.

In some embodiments of the present invention, "vanes" (not shown) are disposed within the diffuser. In one of such embodiments, the vanes are arranged radially about central longitudinal axis **519**. In another of such embodiments, the vanes are configured as a multiplicity of concentric rings that are centered about longitudinal axis **519**. The vanes flatten the velocity profile of powder-laden gas **540**, forestalling flow separation. Such vanes may, however, have a tendency to collect powder from powder-laden gas **540**.

It should be understood that the aforementioned flow-control features (*i.e.*, boundary-layer gas injection, boundary-layer gas suction and vanes) are used individually in some embodiments, and in various combinations in other embodiments.

The "cone angle" of the diffuser, which is expressed as 2θ (*see* FIG. 20), affects diffuser performance. While well-known equations express relationships between cone angle and performance parameters, suitable cone angles for the diffuser are best determined by fabricating sample diffusers and then evaluating their performance.

The flow-control features described herein facilitate use of greater cone angles, which results in relatively "shorter" diffusers. A cone angle of about 15° has been found to be suitable for a diffuser that does not rely on the additional flow-control features described above. More generally, it is expected that a cone angle within the range of about 10° to about 17° is suitable for such an application. Using such flow-control features, and ensuring smooth, well rounded surfaces in transition regions (*e.g.*, the axial slits, the boundary between the flow straightener and the diffuser, *etc.*) allows for a significantly greater cone angle.

Specifically, in such circumstances, it is expected that satisfactory performance can be obtained with a diffuser cone angle as great as about 25° to about 30°.

Illustrative diffuser **518** has a constant cone angle (*e.g.*, 15 degrees). In a further embodiment depicted in FIG. 21, first portion **870** of diffuser **818** has a constant cone angle and second portion **876** of the diffuser **818** has an increasing cone angle. Compare cone half-angle θ_1 at location **882** on the surface of the diffuser nearer beginning **878** of second portion **876** with cone half-angle θ_2 at location **884** on the surface of the diffuser nearer outlet **880** of second portion **876**.

In first portion **870**, a relatively moderate cone angle (*e.g.*, 10° - 17°) aids in establishing the desired flow profile in diffuser **818**. Once established, the cone angle can be progressively increased while maintaining the desired flow profile. Increasing the cone angle reduces the length of the diffuser (given a target diameter near the outlet of the diffuser). Since abrupt transitions at the wall of the diffuser will disrupt the flow profile, the cone angle at beginning **878** of second portion **876** is advantageously equal to the cone angle at end **874** of first portion **870**.

Selecting cone angles for the first and second portion of the diffuser is an application specific task. More particularly, the cone angle is dependent on the gas feed rate, the powder feed rate and the electric charge. By way of illustration, not limitation, the cone angle for first portion **870** is typically in the range of about 10° to about 17°. The cone angle at beginning **878** of second portion **876** is typically in the range of about 10° to about 17° and the cone angle near end **880** of second portion **876** is typically in the range of about 25° to about 35°.

It was previously stated that in some embodiments of the present invention, a flow straightener is used in conjunction with the diffuser to "tailor" or adjust the flow profile within the diffuser. FIGS. 22 and 23 depict embodiments of a flow straightener suitable for tailoring the flow profile of powder-laden gas **540** in the diffuser.

FIG. 22 depicts flow straightener **917** engaged to diffuser **518**. Transitional region **920** between the flow straightener and the diffuser reduces the likelihood of flow instabilities (*e.g.*, powder settling out of powder-laden gas **540**, *etc.*). Flow straightener **917** comprises a plurality of tubes **922**. Tubes **922** have a length-to-diameter ratio (L/D) in the range of about

10/1 to 60/1. Passing powder-laden gas **540** through such tubes results in a relatively flat flow profile as the powder-laden gas **540** enters diffuser **518**.

It has been discovered that the flow profile of the powder-laden gas near the outlet of the diffuser is dependent, to some extent, on the flow profile of the powder-laden gas before such gas enters the diffuser. Therefore, in some embodiments, flow straightener **917** is advantageously used to tailor the flow profile of the powder-laden gas **540**, as desired.

In one embodiment, the flow profile of powder-laden gas **540** is tailored by providing a variation in the diameter of tubes **922** within flow straightener **917**. FIG. 23, which shows a cross-sectional end view of a flow straightener **1017**, depicts an embodiment wherein the diameter of tubes **922** increase with increasing radial distance from the central axis of the flow straightener. Thus, tube **922D**, aligned with the central axis, has the smallest diameter, six tubes **922C** have a somewhat larger diameter than tube **922D**, six tubes **922B** have a larger diameter than tubes **922C**, and six tubes **922A** near wall **924** of the flow straightener have the largest diameter.

The arrangement depicted in FIG. 23 generally increases the velocity of the gas near wall **521** as compared to a flow straightener having tubes of equal diameter. Thus, such an approach can be used to flatten the flow profile across the diffuser if a particular diffuser design exhibits an unacceptable radial velocity gradient. In other embodiments, other arrangements of tubes of unequal diameter are used to cause other changes in the flow profile in the diffuser as desired.

It was previously indicated that a "focusing electrode" is advantageously used in conjunction with the electrostatic chuck to deposit powder on substrate **8**. An embodiment of such a focusing electrode **1152** is depicted in FIG. 24 (side view) and FIG. 25 (bottom view of electrostatic chuck).

In the embodiment depicted in FIG. 24, focusing electrode **1152** is located near substrate **8**. The focusing electrode is configured for easy removal, such as for cleaning, *etc.*

In the embodiment shown in FIG. 25, focusing electrode **1152** comprises a dielectric material coated with a conductor, such as copper. Electrode **1152** includes a plurality of openings **1154** aligned with the collection zones (not shown) of electrostatic chuck **302**.

Electrode **1152** is in contact with a controlled voltage source (not shown) operable to place a charge on the conductor that has the same polarity as the charge on the powder. Powder is thus "steered" away from the conductor and through holes **1154** to substrate **8**.

It is to be understood that the above-described embodiments are merely illustrative of the invention and that many variations may be devised by those skilled in the art without departing from the scope of the invention. It is therefore intended that such variations be included within the scope of the following claims and their equivalents.

I claim:

1. An apparatus for electrostatically depositing powder on a substrate, comprising:

a powder-feed apparatus for directing the powder to said substrate, said powder-feed apparatus comprising:

a diffuser; and

a powder-delivery system that delivers said powder, carried in a first gas, to said diffuser, the powder-delivery system including a powder-charging system that imparts electrical charge to said powder, wherein:

said diffuser is operable to:

receive the electrically-charged powder from said powder-delivery system;

and reduce a velocity of said first gas and said electrically-charged powder to an extent that electrostatic forces control motion of said electrically-charged powder, drawing said electrically-charged powder to said substrate.

2. The apparatus of claim 1 wherein a cone angle of said diffuser is about 10 to about 17 degrees.

3. The apparatus of claim 1 further comprising at least one flow-control feature that improves uniformity of flow of said first gas and said electrically-charged powder through said diffuser.

4. The apparatus of claim 3 wherein said one flow-control feature comprises a boundary- layer gas injector.

5. The apparatus of claim 4 wherein said boundary-layer gas injector comprises at least a first annular slit in a wall of said diffuser through which a second gas is injected into said boundary layer.

6. The apparatus of claim 5 wherein said second gas has a second momentum that is greater than a first momentum of a portion of said first gas that flows in said boundary layer.

7. The apparatus of claim 5 wherein said boundary-layer gas injector further comprises an annular channel that is in fluid communication with said annular slit, wherein said second gas is injected into said annular channel.

8. The apparatus of claim 7 wherein said boundary-layer gas injector further comprises at least two nozzles that inject said second gas into said annular channel.

9. The apparatus of claim 8 wherein said boundary-layer gas injector further comprises flow control means for independently controlling flow of said second gas through said two nozzles.

10. The apparatus of claim 1 wherein said one flow-control feature comprises a boundary-layer gas aspirator.

11. The apparatus of claim 10 wherein said boundary-layer gas aspirator comprises:

at least a first annular slit in a wall of said diffuser; and

a pressure-differential generating means that creates a pressure differential across said first annular slit so that at least some of said first gas in said boundary layer is removed through said first annular slit.

12. The apparatus of claim 11 wherein said pressure-differential generating means comprises:

a pressure-tight enclosure that isolates said first annular slit from an ambient environment;

a suction-flow-generating means in fluid communication with said pressure-tight enclosure.

13. The apparatus of claim 3 wherein a cone angle of said diffuser is in a range of about 15 to about 30 degrees.

14. The apparatus of claim 1 wherein said diffuser comprises:

a first section having an inlet and an outlet and characterized by a constant cone angle; and

a second section having an inlet adjacent to said outlet of said first section, the second section extending to an outlet of said diffuser, said second section characterized by a variable cone angle that increases from a minimum at said inlet of said second section to a maximum at said outlet of the diffuser.

15. The apparatus of claim 14 wherein:

said constant cone angle is in a range of about 10 to about 17 degrees;

said variable cone angle is in a range of about 10 to about 17 degrees at said inlet of said second section; and

said variable cone angle is in a range of about 25 to about 30 degrees at said outlet of the diffuser.

16. The apparatus of claim 1 further comprising a flow straightener that receives said electrically-charged powder carried in said first gas and delivers it to said diffuser, wherein said flow straightener is operable to flatten a velocity profile of said first gas.

17. The apparatus of claim 16 wherein said flow straighener comprises a plurality of tubes through which said first gas and said electrically-charged powder flows.

18. The apparatus of claim 17 wherein said tubes have a length-to-diameter ratio in a range of about 10:1 to about 60:1.

19. The apparatus of claim 17 wherein at least some of said tubes have a different diameter than other of said tubes.

20. The apparatus of claim 19 wherein a tube aligned with a central longitudinal axis of said straightener has a smaller diameter than a tube located off of said central longitudinal axis.

21. The apparatus of claim 1 further comprising an electrostatic chuck having one or more collection zones, each of which collection zones is operable, in conjunction with a bias source, to generate said electrostatic forces, and further wherein:

said substrate is detachably engaged to said electrostatic chuck and overlies said collection zones.

22. The apparatus of claim 21 further comprising:

sensors that are operable to obtain data indicative of a quantity of powder that is deposited at each collection zone; and

a boundary-layer gas injector comprising:

at least one annular slit in a wall of said diffuser through which a second gas is injected into said boundary layer;

at least two nozzles that inject said second gas through said annular channel; and means for adjusting said injection of said second gas responsive to said data obtained by said sensors.

23. The apparatus of claim 21 further comprising:

an optical detection device for obtaining data indicative of an amount of said powder deposited on said substrate on regions overlying each collection zone.

24. The apparatus of claim 23 further comprising a transport element operable to move said electrostatic chuck:

to a first location to engage said substrate;

to a second location wherein said powder is deposited on said substrate; and

to a third location for acquisition of measurement data by said optical detection device.

25. The apparatus of claim 1 wherein said powder delivery system comprises:

a drum for temporary storage of said powder;

a movable belt that receives said powder from said drum;

means for removing said powder off said movable belt; and

means for receiving said removed powder and directing it towards said powder-charging feed tube.

26. The apparatus of claim 1 wherein said powder-charge system comprises a powder charging feed tube.

27. An article comprising a diffuser, said diffuser comprising:

a conduit having a cross-sectional area that increases in a direction of flow of a first fluid; and

a first annular slit in a wall of said conduit through which a second fluid having a second momentum is injected, wherein said second momentum is greater than a first momentum of a minor portion of said first fluid, which minor portion flows in a boundary layer.

28. The article of claim 27, said diffuser further comprising a second annular slit in said wall through which a part of said minor portion of said first gas is removed.

29. The article of claim 28 further comprising a pressure-differential-generating means that creates a pressure differential across said second annular slit so that said part of said minor portion of said first gas is removed through said second annular slit.

30. The article of claim 29 further comprising a third annular slit in said wall through which a major portion of said first gas is removed.

31. The article of claim 27, wherein:

said article produces a pharmaceutical product or a medical diagnostic product; and

said first fluid comprises a powder including an active ingredient.

32. A powder-feed apparatus comprising:

a conduit in which a first fluid comprising a powder that is entrained in a gas flows from a first end to a second end, wherein a cross-sectional area of said conduit increases from said first end to said second end; and

a first flow-control feature for flattening a velocity profile of said first fluid as it flows through said conduit.

33. The apparatus of claim 32, wherein said first flow control feature comprises: an arrangement for injecting a second fluid into a boundary-layer flow of said first fluid.

34. The apparatus of claim 33 wherein said arrangement comprises at least two nozzles that inject said second gas into said boundary-layer flow.

35. The apparatus of claim 34 wherein said arrangement further comprises flow control means for independently controlling flow of said second gas through said two nozzles.

36. The apparatus of claim 32, wherein said first flow control feature comprises an arrangement for removing a portion of said boundary layer flow from said conduit.

37. A method for improving uniformity of flow of a first fluid through a diffuser comprising injecting a second fluid into a boundary layer flow of said first fluid.

38. The method of claim 37 further comprising withdrawing a portion of a boundary-layer flow of said first fluid.