

Conveyor Apparatus for Loading and Unloading an Aircraft

This invention relates to a conveyor apparatus for loading and unloading an aircraft.

5 A critical process in the operation of aircraft is the loading and unloading of passengers' luggage from the cargo hold of the aircraft. Tight operating schedules place great demands on the efficient and rapid loading and unloading of luggage into and from the cargo hold. It is common to utilise height adjustable and tiltable endless belt conveyors to convey luggage between a ground level and the entrance to a cargo hold of an aircraft, which may be positioned at a considerable height above
10 the ground. However, once the luggage is delivered into the cargo hold by such conveyors it is normally necessary for the luggage to be manually handled within the luggage compartment, requiring baggage handlers to enter the cargo hold and carry out manual lifting and moving of the luggage delivered from the conveyor, often in confined spaces. This requires the person to lift luggage from the conveyor at the opening of the cargo hold, leading to a risk of injury should the
15 person accidentally fall from the opening.

The conveyor apparatus disclosed in EP 1 248 726 attempts to address this problem by providing a second conveyor extendable from the end of the main conveyor to enter into the cargo hold of the aircraft, the second conveyor comprising a succession of individual conveyor units, each comprising
20 a short endless belt conveyor with its own drive system, the conveyor units being coupled together by coupling members permitting sideways pivotal movement of the second conveyor so that it can extend into the cargo hold in an arcuate manner whereby the end of the conveyor can be located at any desired position within the cargo hold, obviating the need to manually lift and carry luggage around within the cargo hold.

25

However, the use of a succession of individual conveyor units, each requiring its own drive means and power coupling, creates a complex and costly arrangement. Moreover, the failure of just one of the several individual conveyor units will disable the entire conveyor apparatus.

30 The present invention provides an improved conveyor apparatus that overcomes the problems with the prior art.

According to the present invention there is provided a conveyor apparatus for loading and unloading aircraft as claimed in claim 1. Said drive means may be provided on at least one end of said second
35 conveyor. Preferably said drive means is provided at least on said head end of the second conveyor. In one embodiment a first drive means may be provided on said head end of the second conveyor for driving the conveyor in a first direction, a further drive means being provided at a tail end of said second conveyor for driving the conveyor in a second direction, opposite said first direction.

40

Said coupling means is preferably adapted to enable the articulation of adjacent conveyor segments in both a horizontal and a vertical plane to permit sideways and upwards and downwards mutual articulation between adjacent conveyor segments.

- 5 In one embodiment said endless member comprises a drive chain, belt or band extending between sprockets or pulleys mounted on the respective head and tail ends of the second conveyor. Preferably said endless member extends along a central axis of the second conveyor coincident with the coupling means of each of the conveyor segments. Guide means may be provided on each segment of the second conveyor for guiding the path of the chain.

10

Preferably each conveyor flight comprising a central portion coupled to the endless member and pair of opposing side wings extending transversely from the endless member to define a respective portion of a conveying surface. Preferably said side wings taper from the central portion to a respective distal end thereof to permit mutual sideways pivotal movement of the conveyor segments.

- 15 Preferably the central portion is guided for movement within a channel or slot provided in each conveyor segment.

Each conveyor segment includes a driven member, such as a sprocket, engaging the endless member, at least one roller or wheel being driven by the driven member for rotation about an axis
20 extending transverse to the second conveyor for conveying articles along the second conveyor.

Preferably each conveyor segment is provided with at least one ground engaging support wheel or roller on a lower side thereof.

- 25 In one embodiment said coupling means comprises a ball and socket joint provided between mutually interconnected conveyor segments. Alternatively said coupling means may comprise a universal joint, such as a cardan joint. A central channel may be provided through each conveyor segment and through the coupling means through which may extend cables or wires. Said channel may be defined by a flexible tubular member in the region of said coupling means, for example in the
30 form of a coil spring.

Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which :-

- 35 Figure 1 is a side view of a conveyor apparatus according to a first embodiment of the present invention;

Figure 2 is a detailed perspective view of a head end of the conveyor apparatus of Figure 1;

40

Figure 3 is a longitudinal sectional view through a portion of the conveyor apparatus of Figure 1;

Figure 4 is a longitudinal sectional view through the head section of the conveyor apparatus of Figure 1.

5

Figure 5 is a transverse sectional view through the second conveyor of the conveyor apparatus of Figure 1;

Figure 6 is a longitudinal sectional view through the second conveyor of a conveyor apparatus
10 according to a second embodiment of the present invention; and

Figure 7 is a transverse sectional view through the second conveyor of the conveyor apparatus of Figure 6.

15 As shown in Figure 1, a conveyor apparatus according to an embodiment of the present invention comprises a vehicle 10 having a forward operator cab 12, a first endless belt conveyor 14 being mounted on the vehicle 10 for conveying luggage from a lower position A at the rear end of the vehicle 10 to a raised position B at forward end of the vehicle 10 for conveying luggage into and out of the opening of a cargo hold 2 of an aircraft 1. As is conventional in the art, the first conveyor 14 is
20 mounted on the vehicle 10 such that the angle of inclination of the conveyor 14 and the height of the upper or head end of the conveyor 14 can be adjusted to suit the height of the opening of the cargo hold 2 of the aircraft 1. Hand rails 18 are provided on either side of the first conveyor 14.

A second conveyor 16 is telescopically extendable from below the first conveyor 14 to extend into the cargo hold 2 of the aircraft 1 from the head end of the first conveyor 14, such that the first and second conveyors 14,16 form an uninterrupted conveyor path between the tail end of the first conveyor and a head end of the second conveyor 16.

5

A further belt conveyor 20 is pivotally mounted on a tail end of the first conveyor 14, said further conveyor 20 being generally arranged substantially horizontally for loading and unloading luggage on and off the conveyor apparatus at ground level.

10 The second conveyor 16 comprises a plurality of mutually interconnected conveyor segments 22 connected together by means of ball and socket or knuckle joints 24 whereby the conveyor segments 22 of the second conveyor 16 may be pivotally displaced sideways and upwards and downwards with respect to each other to adjust the conveyor path of the second conveyor 16 as required such that the head end of the second conveyor 16 is located at a position wherein the
15 luggage conveyed therein is desired to be placed. Each conveyor segment 16 is provided with support rollers 26 on the base thereof to allow the segments 22 of the second conveyor 16 to be rolled out along the floor of the cargo hold 2 of the aircraft and moved around therein as required to locate the head end of the second conveyor 16 at a desired location in the cargo hold. The second conveyor 16 is of sufficient length to reach into the furthest point away from the opening of the cargo
20 hold when fully extended from the first conveyor 14. The length of the conveyor 16 may be selected to suit the size of the cargo hold of the largest aircraft with which the conveyor apparatus is to be used.

An intermediate conveyor section 28 is journaled on the head end of the first conveyor 14 to be
25 pivotable about a horizontal axis extending transverse to the first conveyor 16, the intermediate conveyor section 28 bridging the gap between the first and second conveyors 14,16 for smoothly transferring articles between the second conveyor and first conveyor 14,16. The intermediate conveyor section 28 may comprise a belt conveyor or may comprise a simple ramp or may comprise a series of parallel rollers.

30

The second conveyor 16 comprises an endless drive chain 30 extending around said plurality of conveyor segments 18 between a first sprocket 32 mounted on a head section 34 of the second conveyor 16 and a second sprocket (not shown) mounted at a tail end of the second conveyor 16. A first drive motor may be mounted within a head section 34 of the second conveyor 16 for driving the
35 chain 30 in a first direction. The drive motor is preferably an electric motor, although other types of drive motor may be used, such as a hydraulic motor. A second drive motor may be provided at a tail end of the second conveyor for driving the chain in a second direction, opposite said first direction. For example, the first drive motor may be used to drive the second conveyor in a loading direction for delivering luggage into a luggage hold of an aircraft and the second drive motor may be used to drive
40 the second conveyor in an unloading direction for unloading luggage from the luggage hold.

A plurality of transversely extending conveyor flights 36 are mounted on the chain 30 to define a moveable conveying surface. Each flight 36 comprises a central portion and a pair of opposing wing portions. The sides of said wing portions are tapered from the central portion to the respective distal end thereof to provide sufficient clearance between adjacent conveyor flights to permit sideways displacement of the segments 22 of the second conveyor 16, as will be described below in more detail. The chain 30, or at least the central portion of each conveyor flight mounted on the chain, is guided through channels 31 formed in each segment 22 of the second conveyor 16. Such channels 31 may be formed from or lined with a hard wearing low friction material, such as a polymeric material, such as polyethylene. As shown in Figure 5, a channel is defined in each conveyor segment 22 above the support rollers 26 through which the lower run of the conveyor surface defined by the conveyor flights 36 may pass.

A further belt conveyor section 38 may be mounted on the head section 34 of the second conveyor 16 for delivering luggage onto and off the head section 34 of the second conveyor 16.

As shown in Figures 2 and 4, the head section 34 of the second conveyor may be provided with freely rotating idler rollers 48 on either side of the conveyor flights 36.

Handles may be provided on the head end of the second conveyor 16 to enable it to be moved into position within the cargo hold of an aircraft. In the embodiment shown, handles 46 are provided on either side of the conveyor section 38 mounted on the head section 34 of the second conveyor 16.

In the embodiment shown in Figures 5 and 6, each segment 22 of the second conveyor 16 includes a sprocket 40 mounted on a shaft 42 journaled in the respective segment 22 to extend transversely across the width of the segment 22, the sprocket 40 engaging the chain 30 such that the shaft is rotated by movement of the chain, a roller 44 being provided on each end of the shaft 42, the roller 44 being exposed on either side of the conveyor flights 36 to engage luggage located on the second conveyor, said rollers 44 being rotated by the drive chain 30 to move luggage along the second conveyor 16 when the chain 30 is driven by the drive motor of the second conveyor 16.

In use, the vehicle 10 is driven up to the side of an aircraft and the first conveyor 14 is raised to bring the head end of the first conveyor adjacent the opening of the cargo hold 2 of an aircraft 1. A baggage handler may then climb up the first conveyor 14 and enter the cargo hold 2. The head section 38 of the second conveyor 16 can then be manually extended into the cargo hold 2.

Luggage can then be placed onto the belt conveyor section 38 on the head section 34 of the second conveyor and the conveyor apparatus activated to convey luggage out of the aircraft and down to the ground, where it can be removed from the belt conveyor 20 at the tail end of the first conveyor and placed into luggage carts to be transported to the terminal.

Subsequently the luggage hold 2 can be loaded by activating the first and second conveyors 14,16 and placing luggage onto the belt conveyor 20 at the tail end of the first conveyor 14 from where it is conveyed onto the first conveyor 14 and subsequently onto the second conveyor 16 via the intermediate conveyor section 28 and into the cargo hold 2 via the second conveyor 16.

5

The articulation of the conveyor segments 28 of the second conveyor 16 by virtue of the joints 24 enables the path of the second conveyor 16 to be adjusted to deliver the luggage where required within the luggage hold 2. As loading progresses, the position of the head end of the second conveyor 16 can be moved and the second conveyor retracted into its housing beneath the first conveyor 14 as the hold is filled. When loading is finished the second conveyor 16 can be fully retracted out of the luggage hold and the vehicle 10 can be moved away from the aircraft 1. The conveyor apparatus can be used in a similar way to unload a cargo hold 2, the second conveyor 16 being extended to a desired loading location within the hold and activated to convey luggage out of the hold 2 onto the first conveyor 14. The second motor mounted in a tail end of the second conveyor 16 may be powered to move the conveyor flights in an unloading direction.

Figures 7 and 8 show a modified second conveyor 16 in accordance with a further embodiment of the present invention. In such embodiment the second conveyor 16 comprises a plurality of mutually interconnected conveyor segments 122 connected together by means of respective universal joints, such as Cardan joints 124, whereby the conveyor segments 122 of the second conveyor 16 may be pivotally displaced sideways and upwardly and downwardly with respect to each other to adjust the conveyor path of the second conveyor 16 as required such that the head end of the second conveyor 16 is located at a position wherein the luggage conveyed therein is desired to be placed. Each segment incorporates a central bore 123, the bore of adjacent segments being linked by hollow springs 125 whereby an elongate channel is defined through the segments. Such channel may be utilised to house wiring for the transmission of power and/or for control signals.

As with the first embodiment, each conveyor segment 16 is provided with support rollers 126 on the base thereof to allow the segments 122 of the second conveyor 16 to be rolled out along the floor of the cargo hold 2 of the aircraft and moved around therein as required to locate the head end of the second conveyor 16 at a desired location in the cargo hold. In such embodiment the sprockets 40 are omitted and the luggage carrying rollers 144 are not driven by the endless drive chain 130, but rather and freely rotating, in a similar manner to the lower support rollers 126.

A plurality of transversely extending conveyor flights 136 are mounted on an endless chain 130 to define a moveable conveying surface. Each flight 136 comprises a central portion and a pair of opposing wing portions. The sides of said wing portions are tapered from the central portion to the respective distal end thereof to provide sufficient clearance between adjacent conveyor flights to permit sideways displacement of the segments 122 of the second conveyor 16. The chain 130 and associated portions of the conveyor flights 136 are guided through channels 131 formed in each segment 122 of the second conveyor 16. The conveyor flights 136 are guided over hard wearing low

friction plates 135 mounted on the segments 122, said plates being formed from a suitable hard wearing material, such as a polymeric material, such as polyethylene or nylon. Similar plates 139 may be provided for guiding lower portions 150 of the conveyor flights. 136, such that the conveyor flights 136 define slots within which the sides of the channels 131 are received to retain the conveyor flights on the conveyor segments 122.

The invention is not limited to the embodiment(s) described herein but can be amended or modified without departing from the scope of the present invention. It is envisaged that the upper rollers 44,144 may be omitted and the width of the conveyor flights may be increased to extend over the entire width of the second conveyor 16. Flexible and/or elastic webs or membranes may extend between the conveyor flights to link the conveyor flights into a continuous conveying surface. Alternatively the conveyor flights may overlap to prevent items from passing between the conveyor flights.

Claims

1. A conveyor apparatus for loading and unloading aircraft, said apparatus comprising a first
5 conveyor (14) for conveying articles from an area outside of an aircraft to an entrance to a cargo
compartment of the aircraft and a second conveyor (16) for conveying articles from an end of said
first conveyor (14) into said cargo compartment, said second conveyor (16) being telescopically
extendable from said first conveyor (14), characterised in that said second conveyor (16) comprises
a plurality of conveyor segments (22) mutually interconnected by coupling means (24) permitting
10 mutual sideways pivotal movement of the conveyor segments (22) defining an adjustable conveyor
path, wherein said second conveyor is provided with an endless flexible member (30) extending
between a tail end of the second conveyor (16) adjacent the first conveyor (14) and a head end (34)
of the second conveyor (16) at a distal end of said second conveyor (16), drive means driving said
endless member (16) to convey articles along said second conveyor (16), wherein a plurality of
15 conveyor flights (36) are mounted on said endless flexible member (30) to define a conveying
surface, characterised in that each conveyor segment (22) includes a driven member (40) engaging
the endless member (30), at least one roller or wheel (44) being driven by the driven member (40) for
rotation about an axis extending transverse to the second conveyor (16) for conveying articles along
the second conveyor (16).
20
2. A conveyor as claimed in claim 1, wherein said drive means is provided on at least one end of
said second conveyor.
3. A conveyor as claimed in claim 2, wherein said drive means is provided at at least the head end
25 (34) of the second conveyor (16).
4. A conveyor as claimed in any preceding claim, wherein a first drive means is provided on said
head end (34) of the second conveyor (16) for driving the second conveyor (16) in a first direction, a
further drive means being provided at a tail end of said second conveyor (16) for driving the second
30 conveyer (16) in a second direction, opposite said first direction.
5. A conveyor as claimed in any preceding claim, wherein said endless member (30) comprises a
drive chain, belt or band extending between sprockets (32) or pulleys mounted on the respective
head and tail ends of the second conveyor (16), the driven member of each conveyor segment (22)
35 comprising a sprocket (40) engaging said endless member (30).
6. A conveyor as claimed in claim 5, wherein said endless member (30) extends along a central axis
of the second conveyor (16) coincident with the coupling means (24) of each of the conveyor
segments (22).

7. A conveyor as claimed in claim 5 or claim 6, wherein guide means may be provided on each segment (22) of the second conveyor (16) for guiding the path of the endless member (30).

5 8. A conveyor as claimed in any preceding claim, wherein each conveyor flight (36) comprising a central portion coupled to the endless member (30) and pair of opposing side wings extending transversely from the endless member (30) to define a respective portion of a conveying surface.

9. A conveyor as claimed in claim 8, wherein said side wings (36) taper from the central portion to a respective distal end thereof to permit mutual sideways pivotal movement of the conveyor segments.
10

10. A conveyor as claimed in any preceding claim, wherein each conveyor segment (22) is provided with at least one ground engaging support wheel or roller (26) on a lower side thereof.