

TANK ARRANGEMENT ADAPTED FOR A SUBMERSIBLE PUMP

TECHNICAL FIELD

The present invention relates to a tank arrangement for a marine structure. The tank
5 arrangement is adapted for a submersible pump, the tank arrangement comprises a
circulation conduit for circulating liquid to enable the submersible pump to operate in an
advantageous condition substantially at all time. The present invention also relates to an
assembly of a submersible pump and a tank arrangement.

10 BACKGROUND OF THE INVENTION

A marine structure, such as a ship or a semi-submersible unit, is often provided with one
or more ballast systems in order to control the draught and/or the inclination of the marine
structure. Generally, a ballast system comprises a ballast tank, and in fact often a plurality
of tanks, which is adapted to be filled with sea water - i.e. water ambient of the marine
15 structure – through a water filling assembly.

In order to be able to empty or to transfer water between tanks, the ballast system further
generally comprises a pump assembly which in turn comprises a pump and means for
fluidly connecting the tank and the pump as well as means for connecting the pump and
20 the environment ambient of the marine structure such that water may be pumped from the
tank to the ambient environment. Generally, at least a portion of the pump assembly is in
fluid communication with the aforesaid water filling assembly.

However, in some operations, intrusion of air cannot be avoided. For example, when a
25 ballast tank is drained of water, there is a risk that air, at low tank level in the ballast tank,
will be mixed with ballast water and guided towards to, and later introduced into the
pumps such that air will be entrained in the water filling assembly and – at a later stage -
in at least a portion of the pump assembly. As such, when a ballast tank is to be emptied
of water, there is a risk that the air in the pump assembly will be guided towards the pump
30 and hence introduced in the pump. Since air generally adversely affects a pump, the
presence of air is undesired. Moreover, at the completion of a ballast tank emptying
operation, i.e. when a ballast tank is almost completely emptied of water, the water flow
from the ballast tank to the pump is generally lower than in the beginning of the ballast

tank emptying operation. Since a pump generally has an optimum operating condition at a specific combination of the flow rate and pressure, the aforesaid change in the water flow is generally undesired.

- 5 Additionally, during load altering operations of the marine structure, such as multiple ballast operations and/or oil refueling, which occur simultaneously as a ballast tank emptying operation, there may be a need for controlling the rate at which the ballast tank is emptied in order to maintain a balance in the marine structure. Moreover, when a ballast tank is almost emptied of water, it may be desirable to have a low flow rate of the
- 10 water leaving the ballast tank in order to at least limit the amount of air in the water entering the pump.

- Pumping ballast water usually requires relatively high capacity pumps while when pumping bilge water, generally low capacity pumps are required. The difference in
- 15 requirements of the pumps tends to be burdensome for the manufacturer of the marine structure as it demands two different pumps, each specifically adapted for the operating condition required for the specific purpose of the pump. Further, if the marine structure is damaged, it remains vital that the ballast pumps and bilge water pumps are operational, even if the hull is breached or the space at which the pumps are positioned is flooded.
- 20 Today, this is often solved by having a plurality of pump rooms at different locations; this ensures that always one ballast pump or bilge water pump remains operational.

- In view, of the above, it may be realized that there is a need for improvements in the field of moving fluids.
- 25

SUMMARY OF THE INVENTION

- The above mentioned drawbacks are at least partly solved or at least partly reduced by a tank arrangement according to the present invention and more specifically, a tank arrangement for temporarily hold bilge fluid and/or ballast fluid in a marine structure. The
- 30 tank arrangement comprises a storage space defined by at least one tank wall, at least one fluid inlet for introducing the bilge fluid and/or ballast fluid in the storage space, and at least one fluid outlet for permitting removal of at least parts of the bilge fluid and/or ballast fluid from the storage space. The at least one fluid outlet is at least partly formed by a caisson adapted for receiving a submersible pump at a submersible pump position in the
- 35 storage space. The submersible pump comprises a high side and a low side. The caisson

comprises at least one circulation conduit having an inlet and an outlet, adapted to enable circulation of at least parts of the bilge fluid and/or ballast fluid in the caisson from the high side of the submersible pump to the low side of the submersible pump, when the submersible pump is in the submersible pump position.

5

The present invention provides for a tank arrangement which can be utilized with a submersible pump. The tank arrangement enables a submersible pump for pumping e.g. bilge water or ballast water while being constantly submerged in water, thereby removing the risk of failure during start up due to air in the pump, or insufficient pump fluid. By

- 10 having a tank arrangement which is adapted for a submersible pump, and by using a submersible pump, the tank arrangement is less susceptible for the risks involved when pump rooms are flooded, e.g. during a hull breach. Thus, bilge water and/or ballast water pumping becomes less exposed for failure due to flooding of the pump. The tank arrangement can be operated to separate air entering the storage space together with the
- 15 incoming liquid, to be a temporarily storage chamber for circulation liquid and to maintain the a predetermined minimum level of liquid in the storage space, enabling the submersible pump to be substantially constantly submerged.

- According to an aspect of the present invention, the at least one circulation conduit
- 20 comprises at least one circulation flow valve for regulating the flow at the outlet of the circulation conduit. The circulation flow valve enables a controlled flow which in turn enables different operating conditions for the submersible pump so that the operating conditions can be adapted for a specific purpose, e.g. for pumping bilge water or ballast water. The outlet of the circulation conduit can advantageously be arranged in the
- 25 proximity of the submersible pump position. Optionally, the outlet of the circulation conduit can be arranged at the low side of the submersible pump, when the submersible pump is arranged in the submersible pump position. The circulated water can thereby be directly propelled onto the low side of the submersible pump.

- 30 According to an embodiment of the present invention, the circulation conduit extends through the at least one tank wall into the storage space. As such the inlet of the circulation conduit is arranged to the caisson outside of the storage space, defined by the tank walls, and thereafter extends into the storage space. This enables e.g. a circulation flow valve to be positioned outside of the storage space while still permitting the
- 35 advantages of the circulation conduit as mentioned above. In an embodiment according to

the present invention, the inlet of the circulation conduit can be arranged within the tank wall defining the storage space, the circulation conduit can thereafter be arranged to extend outside of the storage space, to thereafter return into the storage space. There are several advantages with this which will be explained in greater detail below.

5

The caisson can be a long caisson, e.g. extending between the tank arrangement and the deck of the marine structure, or e.g. an intermediate caisson extending to a level substantially in the plane of the centre of balance of the marine structure, or optionally a short caisson, extending just past the tank wall defining the storage space. The caisson
10 generally comprises a first and a second end. According to an embodiment of the present invention, the second end of the caisson is arranged to form the submersible pump position. The submersible pump position is adapted to receive the submersible pump enabling the submersible pump to operate with at least a first and a second operating condition. The submersible pump position can be adapted to seal around the submersible
15 pump, preventing liquid or air leakage between the submersible pump and the caisson. Optionally the submersible pump itself can be equipped with means for sealing around the submersible pump, or a combination thereof is of course possible.

A closeable lid can advantageously be arranged at the first end of the caisson, this is
20 especially advantageous when the caisson is a short caisson or not more than a recess in the into the storage space. The closeable lid can be arranged with means for permitting power and/or control cables to extend through the lid or to permit cables to be connected to the lid for power and/or control management of the submersible pump. Optionally the submersible pump itself can be provided with means of sealing the first end of the
25 caisson. Advantageously this can be a circumferential seal flange extending around the periphery of the submersible pump. The submersible pump can thus be fixed to the caisson preventing the submersible pump from torque imparted by the flow of liquid or via e.g. rotating blades of the submersible pump, during operation. Additionally, any cables can be attached to the submersible pump at the dry side of the submersible pump, while
30 permitting the wet side of the submersible pump extend down into the storage space of the tank arrangement. Thus the power cord/cables does not need to be constantly submerged, however, the benefits of a submerged pump, as described above and below are still achieved.

In an embodiment of the present invention, the caisson extends through the at least one tank wall into the storage space. The caisson can be arranged to extend in a substantially vertical direction, thereby permitting the submersible pump to be introduced into the storage space in a vertical direction. Optionally, the caisson can be arranged to extend in
5 a substantially horizontal direction, thereby permitting the submersible pump to be introduced into the storage space in a horizontal direction. A combination of the above is possible, e.g. in a diagonal direction.

The caisson can be arranged to extend a distance D at least past the at least one tank
10 wall, and away from the storage space of the tank arrangement. The distance D is about the range of 0,1-50 meters. For a short caisson the distance D is about 0,1- 8 meters, preferably about 0,1-5 meters, more preferably about 0,2-2, even more preferably 0,2-1 meters. This permits a tank arrangement to which a submersible pump can be easily replaced, removed or serviced.

15

In an embodiment of the present invention, the tank arrangement comprises means for removing air, or excess air, from the storage space. This will prevent air from entering the submersible pump in an undesired manner. It may however permit air to be circulated back to the submersible pump and especially to the low side of the submersible pump.
20 The means for removing the air from the storage space is advantageously arranged to the circulation conduit. In such an embodiment, the means for removing the air from the storage space comprises a priming ejector. The storage space can be adapted to enable air to raise to the top of the storage space, e.g. by having a dome or spherical formed structure of parts of a tank wall or arranged to the tank wall.

25

The priming ejector is advantageously promoting the air to be removed by means of the circulated liquid as motive power. This reduces the need for separate power sources for the individual functions. The priming ejector can be in fluid communication with an air discharge conduit, which in turn is arranged to discharge the air outside of the storage
30 space, e.g. outside of the marine structure. This embodiment is a simple yet effective way of discharging the air.

However, optionally or even additionally, the priming ejector can be in fluid communication with an air discharge conduit which is arranged to discharge air inside the storage space.
35 This solution enables the submersible pump to finally discharge the air from the storage

space out through the outlet of the tank arrangement. Nevertheless, the priming ejector can be arranged with an ejector outlet for ejecting at least air. The ejector outlet of the priming ejector is in an embodiment arranged in the storage space and in the proximity of the submersible pump position to enable the submersible pump to remove the air. The
5 means for removing the air is arranged to operate by means of the circulating flow in the circulation conduit as motive power.

The present invention further relates to a tank arrangement and submersible pump assembly. The assembly comprises a tank arrangement according to the accompanying
10 claims, or optionally as described above, and a submersible pump. The submersible pump can advantageously be arranged with means for sealing the caisson. This submersible pump can be connected with cables at a dry side of the submersible pump, as this side is outside of the storage space. The cable and the connection still needs to be adapted for withstanding water, as this part of the marine structure could be flooded in
15 case of an accident. Optionally, if the caisson comprises a lid, the submersible pump comprises a power and/or control cable with a sufficient length for removing the submersible pump from the submersible pump position without disconnecting the power and/or control cable.

20 The present invention provides for a tank arrangement which can be integrated in a conduit system of e.g. a ballast system, generally because it can be made within a generally confined space. It further has a high reliability of operation and service and can keep the submersible pump submerged at all times. The present invention can further provide a one-way flow into the tank arrangement, circulating parts of the water, and
25 provide a one way out from the tank arrangement for the water.

DEFINITIONS

As used herein, the expression "pump" relates to any type of device being adapted to move a fluid (i.e. liquid and/or gas) such that a higher pressure of the fluid is obtained.
30 Moreover, the position of the pump wherein the fluid enters the pump is herein referred to as the "low side" whereas the position of the pump wherein the higher pressure fluid leaves the pump is herein referred to as the "high side".

As used herein, the expression "priming" relates to the removal of air from the low side of a pump, to enable a substantially normal water level in the pump, which in turn enables a substantially normal operation of the pump.

5 BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in greater detail with reference to the accompanying figures, in which;

figure 1 shows a schematic illustration of a ballast system and tank arrangement according to the present invention;

- 10 figure 2 shows one embodiment of a tank arrangement, according to the present invention, comprising a long caisson;

figure 3 shows one embodiment of a tank arrangement, according to the present invention, comprising a short caisson equipped with a recloseable lid;

- 15 figure 4 shows one embodiment of a tank arrangement, according to the present invention, comprising a short caisson equipped with a recloseable lid;
- figure 5 shows one embodiment of a tank arrangement, according to the present invention, comprising a short caisson having an air discharge outlet outside of the storage space and;
- figure 6 shows one embodiment of a tank arrangement, according to the present invention, comprising a short caisson and adapted for a submersible pump having a lid function.
- 20

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

- Fig. 1 shows a schematic view of a ballast system 10 for de-ballasting water from the ballast tanks, to which a tank arrangement 100, according to the present invention, can be used. The ballast system 10 is preferably used in a marine structure (not shown), such as a ship, facility, semi submersible unit, or any other marine or floating unit, arranged in a body of water with a sea level. Purely by way of example, the ballast system 10 may preferably be used in a semi-submersible unit, i.e. a vessel having a deck and a float and
- 25
- 30 one or more supporting columns connecting the deck and the float to one another. It should be noted that a marine structure may be provided with a plurality of ballast systems 10 and, in particular, a semi-submersible unit may be provided with one ballast system 10 per supporting column (not shown). The ballast system 10 of the present

invention comprises at least one ballast tank 12. Generally, a ballast system 10 comprises a plurality of ballast tanks as indicated by the dotted lines in Fig. 1.

The ballast system 10 also comprises a first inlet conduit 20, also referred to with
5 reference 110 below, adapted to provide a fluid communication between at least the ballast tank 12 and a tank arrangement 100, according to one embodiment of the present invention. In Fig. 1, the first inlet conduit 20 includes a plurality of pipe sections 22, 24, 26 which are connected to one another so as to form the first inlet conduit 20 although one continuous pipe may be used. Moreover, the first inlet conduit 20 preferably comprises a
10 valve 28 for controlling the liquid flow in and/or out of the ballast tank 12.

The ballast system 10 further comprises a bilge water supply conduit 30 and a liquid discharge assembly 32 wherein the bilge water supply conduit 30 may be connected to the first inlet conduit assembly 20, preferably through a valve 34, whereas the liquid
15 discharge assembly 32 generally is in fluid communication with the outlet of the tank arrangement 100, as will be described in greater detail below. Generally, the liquid used in the ballast system 10 is sea water but in some specific applications, other liquids may be used such as oil, diesel, liquid fossil fuel or the like. For the purpose of illustrating the present invention in a non limiting way, sea water is used as liquid. The first inlet conduit
20 20, 110, can be at least one inlet or a plurality of inlets.

Figure 2 shows a tank arrangement 100, according to one embodiment of the present invention, in greater detail and partly with a cross section. More specifically, figure 2 shows a storage space 101 formed by a tank wall 102 and parts of adjacent ballast tanks
25 103 and parts of the hull 105. A water level 104 is also shown. The tank arrangement 100 comprises a liquid inlet 110, in fluid communication with the first inlet conduit 20 mentioned above, in the shown embodiment, a bilge water and ballast water inlet for introducing at least bilge water and/or ballast water into the storage space 101. The tank arrangement 100 is further adapted to at least partly receive a submersible pump 130 for
30 removing at least parts of the water in the storage space 101 and/or for pumping ballast water from e.g. at least one ballast tank, bilge water or the like for temporarily containment in the storage space. The water is thus only passing through the tank arrangement, i.e. it is temporarily contained in the tank arrangement. The tank arrangement 100 is adapted to receive the submersible pump 130 at a submersible pump position 131, which is arranged
35 inside the storage space 101 of the tank arrangement 100 in the shown embodiment. The

tank arrangement 100 can be filled by means of gravity or by pumping ballast and/or bilge water to the tank arrangement by the submersible pump.

As is noted, the tank arrangement 100 can be adapted to draw liquid from a plurality of
5 tanks, such as the ballast tank 12 via the first inlet conduit assembly 20, but also from emergency bilge water tanks 30' or other bilge water conduits 30'', each conduit can of course be arranged with a flow regulation valve 34', 34''.

The tank arrangement 100, according to the present invention, and especially the storage
10 space 101, is significantly smaller than the storage space of a ballast tank, such as ballast tank 12, for example. As can be mentioned, the storage space 101 is about 10, 15, 20, 25, 30, 35 m³. The storage space 101 can typically be about 10-35 m³. The ballast tank 12 is in the order of about 100-1500 m³. The tank arrangement 100 is exerted for a variety of different pressures during normal operation, and it should be noted that the tank
15 arrangement 100 comprises a confined storage space 101, and not an open space to the ambient environment. Thus it may be regarded as a part of a ballast conduit, more than a ballast tank.

A caisson 140 forms parts of an outlet 139 through which the water be conducted during
20 removal from the storage space 101. The caisson 140, of which only parts are shown, comprises a first and a second end 141, 142. The submersible pump position 131 is arranged at the second end 142 of the caisson 140, in the storage space 101, i.e. inside the defined space by the tank wall 102, ballast tanks 103 and the hull 105. The second end 142 of the caisson 140 is thus adapted to seal around the submersible pump 130,
25 when positioned in the submersible pump position 131. The caisson 140 can either be adapted to provide a conduit for the water during removal from the storage space 101, i.e. the caisson 140 itself functions as a conduit as shown in figure 2, or it can be in fluid communication with a water conduit 145 for removal of the water from the storage space 101, as shown in figure 3.

30

The submersible pump 130 may be any means for moving a liquid but preferably a rotodynamic pump, such as an electrical centrifugal pump, with a capacity of e.g. about 500 m³/h. The submersible pump 130 should however be adapted to operate submerged in water and to be adapted to be able to be on stand by in a submerged condition for a

longer period of time. A submersible pump generally has a hermetically sealed motor close-coupled to the pump body to withstand the liquid it is submerged in.

The submersible pump 130 comprises a high side 132 and a low side 133. A circulation
5 conduit 150 is arranged to circulate fluid from the high side 132 of the submersible pump 130, when the submersible pump 130 is in the submersible pump position 131, to the low side 133 of the submersible pump 130 or at least back into the storage space 101.

Preferably the circulation conduit 150 is returned directly to the proximity of the low side
133 of the submersible pump 130 or at least directly back into the storage space 101. The
10 circulation conduit 150 enables the submersible pump 130 to be operated in at least a first and a second operating condition. It should be noted that the submersible pump 130 can be considered to be submerged in a conduit system, when submerged in the tank arrangement.

15 A first operating condition can be a selected volumetric flow rate at the high side 132 of the submersible pump 130 for example, while the second operating condition can be a different volumetric flow rate at the high side 132 of the submersible pump 130. Generally pumps have preferred operating conditions in which they have a beneficial volumetric flow rate. Centrifugal pumps with a volumetric flow which severely deviates from the nominal
20 volumetric flow, for which the pumps are designed, may cause vibrations, mechanical damage due to e.g. cavitation, or bad pump performance. If the volumetric flow rate of the water entering the low side 133 of the submersible pump 130 is below a predetermined desired value, water may be circulated through the circulation conduit 150 in order to increase the volumetric flow rate to thereby obtain a more preferred volumetric flow rate
25 for the submersible pump 130.

For example, if it is realized that the volumetric flow rate of water is too high, the water which is circulated through the circulation conduit 150 can be reduced or the circulation conduit 150 can be closed to completely stop the circulation of water through the
30 circulation conduit 150, in order to decrease the volumetric flow rate and to thereby obtain a more preferred volumetric flow rate for the submersible pump 130.

The circulation conduit 150 is in the shown embodiment provided with a circulation flow valve 151 and comprises an inlet opening 152 and an outlet 153. The circulation flow
35 valve 151 is not necessary, although very advantageous. As an option, the flow can be

adjusted by means of changing the diameter of the circulation conduit 150. By means of the circulation flow valve 151, which can be connected directly or indirectly with an electronic control unit (ECU) to operate the circulation flow valve 151 from a remote location, the flow through the circulation conduit 150 can be controlled in a precise way.

- 5 Thereby an advantageous volumetric flow rate can be provided; enabling very good operating conditions for the submersible pump 130, independently on which operation the submersible pump 130 is intended to be used for.

For example, if the submersible pump 130 is used as bilge pump, relatively low nominal
10 volumetric flow rates are desired, e.g. about 50-110 m³/h. However, if the submersible pump is used as ballast pump relatively high nominal volumetric flow rates are desired, e.g. about 100-500 m³/h, or at least > 110 m³/h. The operating conditions, by the means of the circulation conduit 151 and optionally the circulation flow valve 151, can be controlled to provide advantageous operating conditions.

15

As mentioned, an objective with the present invention is to at least partly to enable advantageous operating conditions for the submersible pump 130. One advantageous operating condition can be to enable a low amount of air, or to enable a reduced amount of air, entering the low side 133 of the submersible pump 130. In an embodiment

- 20 according to the present invention, the submersible pump 130 is arranged in working cooperation with a priming arrangement 160. In figure 2, a priming ejector 161 is arranged in fluid communication with the circulation conduit 150 and the low side 133 of the submersible pump 130, i.e. when the submersible pump 130 is positioned at the submersible pump position 131.

25

The priming arrangement 160 comprises a priming circulation conduit 162 which extends from the circulation conduit 150 at a first point 163 outside of the storage space 101, and circulates parts of the circulation flow of the circulation conduit 150 to a second point 164 inside of the storage space 101 and down stream of the first point 163, to an ejector outlet
30 163b at a mixing point 165. As is noticed, the mixing point 165 is arranged substantially at the bottom of the storage space, near the hull 105. The circulation conduit 150 and the priming circulation conduit 162 are connected at the mixing point 165 and thereby permits the mixing of the flow from the circulation conduit 150 and the priming circulation conduit 162 before the flow is discharged at the low side 133 of the submersible pump 130, when

- 35 the submersible pump 130 is positioned at the submersible pump position 131. A priming

conduit valve 167 is arranged to enable regulation the flow in the priming circulation conduit 162. The priming conduit valve 167 can of course be connected to the ECU, mentioned above, or any other control unit.

- 5 The mixing point 165 is advantageously arranged as shown in figure 2-4 in which the mixing point 165 is illustrated as a cross section of mixing point 165, or coupling arrangement 165, the mixing point 165 comprises an inner conduit 168, partly defined by the priming circulation conduit 162 and the ejector outlet 163b, and an outer conduit 169, partly defined by parts of the circulation conduit 150, wherein both the inner conduit 168
10 and the outer conduit 169 are in fluid communication with the low side 133 of the submersible pump 130. Moreover, Figures 2-4 illustrates that the outer conduit 169 substantially encloses the inner conduit 168. The outer conduit 169 comprises a tapered portion at the location of the ejector outlet 163b. The tapered portion of the outer conduit 169 will ensure that liquid transported through the inner conduit 168 and/or the outer
15 conduit 169 will assume a preferred direction of flow - i.e. a substantially in a direction towards the low side 133 of the submersible pump 130, and to deviate by turbulent flow.

An air removal conduit 166 is arranged to the priming ejector 161 and permits surplus air, which have been introduced to the storage space 101 from the inlet 110, to be removed
20 from the storage space 101. The air removal conduit 166 comprises a plurality of openings arranged along the removal conduit 166 which, as the water level 104 is lowered, permits a larger amount of air into the air removal conduit 166 by providing a larger inlet opening i.e. a larger area through which air may pass into the air removal conduit 166. The priming ejector 161 pulls the surplus air from the storage space 101 by
25 means of motive power from the water flowing in the priming circulation conduit 162 and introduces the air at the mixing point 165 and thereafter at the low side 133 of the submersible pump 130. The air is thus mixed with an appropriate amount of circulated water to provide an amount of air at the low side 133 of the submersible pump 130 which is adapted not interfere, thereby still providing advantageous operating conditions for the
30 submersible pump 130.

The mixing point 165 can further break air bubbles to smaller air bubbles and/or mix the air bubbles with the water flow of the circulation conduit 150, thereby enabling advantageous operating conditions for the submersible pump 130 for both priming
35 purposes and for the purpose of air removal from the storage space. As is noticed in

figure 2, the air removal conduit 166 extends from the storage space 101, through the tank wall 102 to the outside, and into the priming circulation conduit 162 at the priming ejector 161.

- 5 The recirculation conduit 150 preferably comprises nozzles (not shown) in the proximity of the low side 133 of the submersible pump 130, which nozzles are adapted to disintegrate the air into the liquid. Optionally, as indicated in figure 2, 3 and 4, a mesh or grid can be provided at that part which is equivalent with the submersible pump position 131 and the low side 133 of the submersible pump 130 when the submersible pump 130 is in the
- 10 submersible pump position 131, to prevent unwanted objects or particles to enter the submersible pump 130. Such a mesh or grid reduces the cost as grids at the inlet 110 of the tank arrangement 100 are not needed.

Figure 3 shows a second embodiment of a tank arrangement 100 according to the present invention. Similar features will be referred to with similar reference numbers. As is noticed, the opening adapted to receive the submersible pump 130 is not more than a recess 170 having a circular collar 171. The circular collar 171 is adapted to enable a seal between a recloseable lid 172 or optionally parts of the submersible pump 130. The recloseable lid 172 is resting on the circular collar 171.

- 20 The recloseable lid 172 enables an operator of a derrick 173 to remove or insert a submersible pump 130 through the outlet 139, into the recess 170 and thereby also into the storage space 101. A short caisson 140, as shown in figure 3, enables an operator to move the submersible pump 130 to an alternative or a second tank arrangement similar or
- 25 different to the tank arrangement 100, according to the present invention, to a service station (not shown), or the like.

A water conduit 145 is arranged to the collar 171 of the recess 170 for removal of the water from the storage space 101 by means of the submersible pump 130. The water

30 conduit can advantageously be extended to the deck of the marine structure, or at least above the sea level enabling emergency bilge water removal, bilge water removal or ballast water removal. As mentioned above, part of the recess 170, and especially the bottom 174, is further adapted to seal around the submersible pump 130, when positioned in the submersible pump position 131.

Figure 4 shows a tank arrangement 100 according to a third embodiment of the present invention. The tank arrangement 100 comprises as mentioned with reference to figure 2 and 3, a storage space 101, at least one tank wall 102, at least one inlet for introducing bilge water, emergency bilge water or ballast water, a recess 170 for receiving a
5 submersible pump 130 at a submersible pump position 131 and a recloseable lid 172.

The recloseable lid 172 is adapted to permit power and/or control cables 176 to the submersible pump 130 to extend there through or optionally via a cable connection on each side of the recloseable lid 172. The power and/or control cable 176 can however
10 extend through any other wall of the tank arrangement 100. As is noticed in figure 4, the power and/or control cable 176 has a designated length, indicated by that the power and/or control cable 176 is illustrated in a serpentine like manner. By having a designated length of the power and/or control cable 176, the submersible pump 130 can be removed
15 submersible pump 130 from the storage space 101, e.g. by means of the derrick 173, without disconnecting the submersible pump 130 from the power and/or control cable 176, thereby simplifying pump removal or pump service, and reducing the risk of short-circuiting the electrical system.

Optionally, the submersible pump 130 can be arranged with a recloseable lid function, e.g. by a circumferential flange which is adapted to seal around the circular collar 171 of
20 the recess 170. This embodiment is shown in figure 6. In this embodiment, the submersible pump 130 is adapted to seal the recess 170 or the caisson 140 after being inserted into the storage space 101. This can be beneficial as the submersible pump 130 during start up and operation is subjected to a torque imparted by the flowing water and e.g. the rotation of the blades of the submersible pump 130, if such are present. In this
25 case, the submersible pump 130 would be fixed to the circular collar 171, or generally fixed with respect to the recess 170. An additional advantage is that the fittings for the cable and/or control cable 176 can be arranged outside the lid 172, i.e. the dry side, while the remaining submersible pump 130 is arranged on the opposite side of the lid 172, i.e. the wet side.

30

As an option, the recloseable lid 172 can be adapted to receive a drive shaft for the submersible pump.

In the shown figures 2-4, the submersible pump 130 is introduced vertically from the
35 upper side with respect to the water level 104 of the tank arrangement 100 into the

storage space 101, however, the submersible pump 130 can be introduced horizontally or diagonally or in any other direction at a recess similar to the recess 170 of figure 3 and 4.

It should be noted that the at least one inlet 110 for introducing bilge water, emergency
5 bilge water or ballast water can be one single inlet pipe or a plurality of pipes. The plurality of pipes is preferably adapted so that only one pipe, or flow, for the bilge water, emergency bilge water or ballast water respectively can be open. This will prevent the water from flowing between the three different systems. Further visible is a circulation conduit 150 for circulating at least parts of the water back to the storage space 101, after
10 leaving the high side 132 of the submersible pump 130, and the recess 170. Generally the water is circulated from the high side 132 to the low side 133 of the submersible pump 130. A circulation flow valve 151 is arranged to control the flow of the water through the circulation conduit 150.

15 As is noticed in figure 4, the circulation conduit 150 has an inlet opening 152 arranged substantially in the proximity of the bottom 174 of the recess 170. Optionally substantially between the high side 132 and the low side 133 of the submersible pump 130, when the submersible pump 130 is positioned at the submersible pump position 131. The submersible pump position 131 is, as shown figure 4 at the bottom 174 of the recess 170.

20

The circulation conduit 150 thereafter extends through the tank wall 102 out from the storage space 101 of the tank arrangement 100. The reason for this is that this simplifies the operations and service of the circulation flow valve 151 and other valves arranged to, or in working cooperation with, the circulation conduit 150. As is noticed, the circulation
25 conduit 150 thereafter returns through the tank wall 102 and extends a distance into the storage space 101, preferably back to a position in the proximity of the submersible pump position 131, and preferably the low side 133 of the submersible pump 130 when the submersible pump 130 is in the submersible pump position 131.

30 The submersible pump 130 is arranged with a water guide collar 134 arranged at the high side 132 of the submersible pump 130, the purpose of the water guide collar 134 is to provide a water pillar for the water which is to be circulated in the circulation conduit 150 to remove access air before the water enters the inlet opening 152 of the circulation conduit 150 and also, or optionally to, provide an appropriate distance for the water to
35 travel, to reduce interference from turbulence from the high side 132 of the submersible

pump 130. As such, the recess 170 with the recloseable lid 172 can be operated as a pressure chamber with the function of a separator for removing air from the water which is intended to be circulated to the circulation conduit 150 and the priming ejector 161 of the priming arrangement 160.

5

As is shown in figure 4, the diameter of the recess 170 is somewhat larger than the diameter of the submersible pump 130. This is to enable the water to reach the inlet opening 152 of the circulation conduit 150 with minimum content of air.

- 10 The submersible pump 130 can further be arranged with a lifting device 175, such as a steel ring or the like. The submersible pump 130 can optionally be arranged to a guide rail, a hose or the like to enable the submersible pump 130 to be introduced into the storage space 101 of the tank arrangement 100. The tank arrangement 100 can thus be provided with means for removing the submersible pump 130 from the tank arrangement
- 15 100.

The tank arrangement 100, as described above, can be provided with a water level indicator (not shown) which can be used together with an ECU, programme logic controller, computer or the like, e.g. as mentioned above, to regulate and control the

20 different flows in the tank arrangement 100, and the operating conditions of the submersible pump 130, as well as the submersible pump 130 itself. As a non limiting example, the water level indicator can be operated in conjunction with the circulation flow valve 151 of the circulation conduit 150, the priming conduit valve 167 and e.g. the submersible pump 130 and a regulating valve 180. This operation should preferably be

25 automatically controlled, e.g. by the ECU or any other computerized device communicating with the ECU, and with such performance that the water level inside the storage space will not go below the minimum water level, indicated min. in figure 5. By this arrangement the impeller of the submersible pump will be water filled and ready for operation at all time.

30

If the submersible pump 130 is to be used as a regular bilge water pump, both the circulation flow valve 151 of the circulation conduit 150, the priming conduit valve 167 are fully opened. Further flow control is performed by throttling the regulating valve 180. This will provide an operating condition for the submersible pump 130 which is very

35 advantageous.

As is further noticed figure 4 also shows a regulation valve 180 and a check valve 181 (a non return valve) in the proximity of the recess 170 and the water conduit 145 for removal of the water from the storage space 101, also referred to as the liquid discharge assembly 5 32 above. In the embodiment shown in figure 2, with a long caisson 140, the regulation valve 180 and a check valve 181 is advantageously arranged between the upper end of the caisson 140 and the overboard conduit, arranged to discharge the water overboard somewhere above the sea level. A cut off valve should also be arranged at the proximity of the outside planking of the marine structure.

10

According to one aspect of the invention, a minimum level of water, indicated as "min." in figure 5, is retained in the storage space 101 as this will make certain that the submersible pump 130 always is drenched before start up. The minimum level of water is preferably set to be above the submersible pump position 131 to thereby always keep at least parts 15 of the submersible pump 130 submerged, or advantageously the whole of the submersible pump 130 submerged. This will be discussed in greater detail below.

Figure 5 shows an alternative embodiment of the present invention in which an air separator is arranged to remove air collected at the top of the storage space 101 of the 20 tank arrangement 100. However, the separated air is not returned the storage space 101 or the low side 132 of the submersible pump 130. The separated air is instead directed out and away from the tank arrangement 100 and the preferably away from the marine structure, into the ambient air outside the marine structure.

25 When liquid flows in the priming circulation conduit 162, so as to feed the priming ejector in figure 5 referred to as the priming ejector 200, to thereby impart a motive power to the air in the storage space 101 via the air outlet conduit assembly 220. The air outlet conduit assembly 220 is arranged to the tank wall 102 and a dome to promote air to be sucked out from the storage space 101. A mixture of air and liquid will leave the priming ejector 30 200 through a priming ejector outlet 201 which in turn is in fluid communication with a restoring conduit assembly 202 which in the figure 5 embodiment comprises a restoring separator 203 and a liquid seal 204. The priming ejector outlet 201 may preferably discharge into the restoring separator 203. The restoring separator 203 further comprises an air discharge conduit 205 such that air in the restoring separator 203 may leave the

tank arrangement 100 of the present invention and is preferably directed into the ambient air of the marine structure.

The liquid seal 204 preferably comprises a conduit – or a plurality of conduits joined
5 together so as to form a continuous conduit arrangement – which in turn comprises a lower bend 210 and an upper bend 211, wherein the lower and upper bends 210, 211 are distanced from one another by a vertical distance V , which vertical distance preferably is more than 10 meters, more preferably > 11 meters, optionally in the range of 10-15 meters.

10

Furthermore, the priming circulation conduit 162, the restoring conduit assembly 202, the conduit 212 from the upper bend 211 and portions of the first inlet conduit assembly 20 together form a motive fluid recirculation conduit assembly for the tank arrangement 100, which motive fluid recirculation conduit assembly provides a fluid communication between
15 the high side 132 and the low side 132 of the submersible pump 130, when the submersible pump 130 is in the submersible pump position 131, to thereby enable liquid transport from the high side 132 to the low side 132 of the submersible pump 130. The motive fluid recirculation conduit assembly just described may in some embodiments of the present invention be the only recirculation conduit 150 of the tank arrangement 100
20 adapted to provide a fluid passage from the high side 132 to the low side 133 of the submersible pump 130.

It should be noted that the figure 5 tank arrangement 100 also comprises a cut-off conduit assembly 215 providing a fluid communication between the liquid seal 204 – preferably at
25 the location of the upper bend 211 - and an air outlet conduit assembly 220 which is in fluid communication with the storage space 101 of the tank arrangement 100 in order to reduce the risk of having the liquid seal 204 emptied of liquid due to *inter alia* a siphon action.

30 Figure 6 shows an additional embodiment in which the tank arrangement according to the present invention is adapted to a submersible pump 130 which has a recloseable lid function. The submersible pump 130 comprises sealing and connection means 190 for providing a connection and a liquid and pressure tight seal to the caisson 170. As is noticed the power and/or control cables are arranged directly to the submersible pump,
35 and especially to that part of the submersible pump representing the electric motor M.

- The tank arrangement 100 can be used for separating air which during certain circumstances travels with the flow in the at least one fluid inlet 110. It should be noted that the term separate air does not mean that the tank arrangement 100 can separate air dissolved in the water but air which travels with the water as bubbles or distinct air pockets. The separated air can be removed by the means for removing air 160, which is described above. The removal of air keeps the storage space 101 filled with a normal water level. In cases of exceptional amounts of air entering the storage space 101 and the water level is decreased, the regulating system can be engaged to start;
- 5 a) the priming;
 - b) additional circulation
 - c) if the water level in the storage space 101 is still decreasing, the regulating valve 180, i.e. a valve regulating the out flow from the storage space 101, can be closed, or at least reduced, to prevent water from escaping the storage space 101.
- 15 When the regulating valve 180 is reduced or closed, the flow through the at least one fluid inlet 110 is reduced or stopped, which also has the advantage of preventing or reducing the amount of air entering the storage space 101, until balance is restored in the storage space 101, i.e. at least the minimum level of water is maintained or reached. The
- 20 minimum level of water, indicated min. in figure 5, is surpassed if the flow of air if without restrain, e.g. if the storage space 101 is completely emptied of water and the operator is still pumping using the submersible pump 130. The regulation system has automatically, or via an operator, at that stage initiated both priming and recirculation and further closed the regulating valve 180. No water leaves the storage space 101 but the priming and
- 25 circulation is still in operation. The water level in the storage space 101 can thus be maintained at a reasonable level and not go below the minimum water level, indicated min. in figure 5. By this, the submersible pump 130 can still be operable but without pumping water e.g. overboard, via the at least one fluid outlet 145.
- 30 The advantages are that the submersible pump 130 always can be kept submerged in water, permitting the submersible pump 130 to always be ready for start. At start up, the priming and the circulation is started until the storage space 101 is filled and normal pumping out through the fluid outlet 145 can be performed.

CLAIMS

1. A ballast system (10) for a marine structure, said ballast system (10) comprising a ballast tank (12) which is in fluid communication with a tank arrangement (100) for temporarily holding bilge fluid and/or ballast fluid in a marine structure, characterized in that said tank arrangement (100) comprises:
5 a closed storage space (101) defined by at least one tank wall (102);
at least one fluid inlet (110) for introducing said bilge fluid and/or ballast fluid in said storage space (101);
10 and at least one fluid outlet (145) permitting removal of at least parts of said bilge fluid and/or ballast fluid from said storage space (101);
wherein said at least one fluid outlet (145) is at least partly formed by a caisson (140, 170) adapted for receiving a submersible pump (130) at a submersible pump position (131) in said storage space (101), said submersible pump (130) comprising a high side (132) and a low side (133),
15 said caisson (140, 170) comprises at least one circulation conduit (150) having an inlet (152) and an outlet (153), adapted to enable circulation of at least parts of said bilge fluid and/or ballast fluid from said high side (132) of said submersible pump (130) to said low side (133) of said submersible pump (130), when said submersible pump (130) is in said submersible pump position (131).
20
2. The ballast system (10) according to claim 1, characterized in that said at least one circulation conduit (150) comprises at least one circulation flow valve (151)
25 for regulating the flow at said outlet (153) of said circulation conduit (150).
3. The ballast system (10) according to claim 1 or 2, characterized in that said outlet (153) of said circulation conduit (150) is arranged in the proximity of said submersible pump position (131).
30
4. The ballast system (10) according to claim 3, characterized in that said outlet (153) of said circulation conduit (150) is arranged at said low side (133) of said submersible pump (130), when said submersible pump (130) is arranged in said submersible pump position (131).
35

5. The ballast system (10) according to any preceding claims, characterized in that said circulation conduit (150) extends through said at least one tank wall (102) into said storage space (101).
- 5 6. The ballast system (10) according to any preceding claims, characterized in that said caisson (140, 170) comprises a first and a second end (141, 142, 171, 174), and in that said second end (142, 174) of said caisson (140, 170) is forming said submersible pump position (131).
- 10 7. The ballast system (10) according to any preceding claims, characterized in that said caisson (170) comprises a first and a second end (171, 174), and in that said first end (171) comprises a closable lid (172).
- 15 8. The ballast system (10) according to any preceding claims, characterized in that said caisson (140, 170) extends through said at least one tank wall (102) into said storage space (101).
- 20 9. The ballast system (10) according to claim 8, characterized in that said caisson (140, 170) extends a distance (D) at least past said at least one tank wall (102) and away from said storage space (101) of said tank arrangement (100).
- 25 10. The ballast system (10) according to any preceding claims, characterized in that said tank arrangement (100) comprises means for removing air (160, 200) from said storage space (101).
- 30 11. The ballast system (10) according to any preceding claims, characterized in that said means for removing air (160, 200) from said storage space (101) is arranged to said circulation conduit (150).
- 35 12. The ballast system (10) according to claim 11, characterized in that said means for removing air (160, 200) from said storage space (101) comprises a priming ejector (161, 200).
13. The ballast system (10) according to claim 12, characterized in that said priming ejector (200) is in fluid communication with an air discharge conduit

(205), and in that said air discharge conduit (205) is arranged to discharge said air outside of said storage space (101).

5 14. The ballast system (10) according to claim 13, characterized in that said air discharge conduit (205) is arranged to discharge said air outside of said marine structure.

10 15. The ballast system (10) according to claim 12, characterized in that said priming ejector (161) is in fluid communication with an air discharge conduit (162), and in that said air discharge conduit (162) is arranged to discharge said air inside said storage space (101).

15 16. The ballast system (10) according to claim 15, characterized in that said priming ejector (161) comprises an ejector outlet (163b) for ejecting at least air, said ejector outlet (163b) of said priming ejector (161) is arranged inside of said storage space (101) and in the proximity of said submersible pump position (131) to enable said submersible pump (130) to remove said air.

20 17. The ballast system (10) according to any of claims 10-16, characterized in that said means for removing said air is arranged to operate by means of at least a part of said circulating flow in said circulation conduit (150) as motive power.

25 18. The ballast system (10) according to any preceding claim, characterized in that said tank arrangement (100) is adapted to separate air entering said storage space (101) together with said fluid, from said at least one fluid inlet (110).

30 19. The ballast system (10) according to any preceding claim, characterized in that said tank arrangement (100) is adapted to maintain, or to be operated to maintain, a minimum level of fluid (min.) in said storage space, to maintain said submersible pump (130) at least partly submerged when said submersible pump (130) is in said submersible pump position (131).

35 20. The ballast system (10) according to any one of the preceding claims, wherein said ballast system (10) further comprises a submersible pump (130).

21. The ballast system (10) according to claim 20, characterized in that said submersible pump (130) comprises a power and/or control cable (176).
- 5 22. The ballast system (10) according to claim 20 or 21, characterized in that said submersible pump (130) is arranged with sealing means adapted to seal against said caisson (170) when said submersible pump (130) is in said submersible pump position (131).
- 10 23. The ballast system (10) according to claim 22, characterized in that said sealing means enables a lid function to said caisson (170).
24. The ballast system (10) according to any of claims 20-23, characterized in said power and/or control cable (176) is of sufficient length for removing said submersible pump (130) from said submersible pump position (131) without
15 disconnecting said power and/or control cable (176).
25. A marine structure having a ballast system (10) according to any one of the preceding claims.
- 20 26. A method for pumping ballast and/or bilge fluid using a ballast system (10) according to any of claims 20-24,
characterized in
that said method comprises the steps of circulating at least a part of said ballast and/or bilge fluid back from said high side (132) of said submersible
25 pump (130) to said storage space (101); thereby maintaining a minimum level (min.) of fluid in said storage space (101).
27. The method according to claim 26, characterized in that said ballast and/or bilge fluid circulated to a position in the proximity of said low side (133) of said
30 submersible pump (130).
28. The method according to claim 26 or 27, characterized in that said circulated ballast and/or bilge fluid is regulated by a circulation flow valve (151).