

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E21B 37/06, 41/02	A1	(11) International Publication Number: WO 96/22451 (43) International Publication Date: 25 July 1996 (25.07.96)
(21) International Application Number: PCT/GB96/00045 (22) International Filing Date: 11 January 1996 (11.01.96) (30) Priority Data: 9501021.1 19 January 1995 (19.01.95) GB 9511487.2 7 June 1995 (07.06.95) GB (71) Applicant (for all designated States except US): BP CHEMICALS LIMITED [GB/GB]; Britannic House, 1 Finsbury Circus, London EC2M 7BA (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): CHAPMAN, Richard, George [GB/GB]; 15 Willerton Lodge, Bridgewater Road, Weybridge, Surrey KT13 0ED (GB). COLLINS, Ian, Ralph [GB/GB]; 39 Percy Road, Hampton, Middlesex TW12 2LD (GB). GOODWIN, Stephen, Paul [GB/GB]; 61 Disraeli Road, London SW15 2DR (GB). LUCY, Andrew, Richard [GB/GB]; 35 Main Street, Hotham, York YO4 3UD (GB). STEWART, Nevin, John [GB/GB]; 16 Scillonian Road, Guildford, Surrey GU2 5PS (GB). (74) Agent: KRISHNAN, Suryanarayana, Kalyana; BP International Limited, Group Patents & Agreements, Chertsey Road, Sunbury-on-Thames, Middlesex TW16 7LN (GB).	(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	
(54) Title: OIL AND GAS FIELD CHEMICALS (57) Abstract This invention relates to a process for increasing the effectiveness of production chemicals by reducing the number of squeezing and shut-in operations needed to increase the production rate from an oil well. The process comprises injecting into an oil-bearing rock formation a water-miscible formulation comprising as components: (a) a water-miscible surfactant which is an alkyltriglycol ether and (b) at least one water-miscible oil field or gas field production chemical, said components of the formulation being introduced either as a pre-formed single composition, or simultaneously in parallel or sequentially in either order into the rock formation via the production well.		