

## DESCRIPTION



\*166166\*

IMAGE FORMING CHARACTERISTICS MEASURING METHOD,  
IMAGE FORMING CHARACTERISTICS ADJUSTING METHOD,  
5 EXPOSURE METHOD AND APPARATUS, PROGRAM AND  
STORAGE MEDIUM, AND DEVICE MANUFACTURING METHOD

**TECHNICAL FIELD**

The present invention relates to image forming  
10 characteristics measuring methods, image forming  
characteristics adjusting methods, exposure methods and  
apparatus, programs and storage mediums, and device  
manufacturing methods, and more particularly to an image  
forming characteristics measuring method in which a  
15 targeted image forming characteristic of a projection  
optical system is measured, an image forming  
characteristics adjusting method in which the image  
forming characteristic is adjusted, an exposure method in  
which exposure is performed using a projection optical  
20 system whose image forming characteristic has been  
adjusted according to the image forming characteristics  
adjusting method and an exposure apparatus suitable for  
performing the image forming characteristics adjusting  
method, a program which makes a control computer of the  
25 exposure apparatus execute processes of calculating and  
adjusting a targeted image forming characteristic of a  
projection optical system and an information storage  
medium in which such a program is stored and is readable



\*G00002\*

by the computer, and a device manufacturing method using the exposure apparatus.

### **BACKGROUND ART**

5 Conventionally, when manufacturing devices such as semiconductors, liquid crystal displays, or the like in a photolithographic process, projection exposure apparatus have been used, such as a reduction projection exposure apparatus based on a step-and-repeat method (a so-called  
10 stepper) and a scanning projection exposure apparatus based on a step-and-scan method (a so-called scanning stepper). With such projection exposure apparatus, a pattern formed on a photo-mask or reticle (generally referred to as "reticle" hereinafter) is transferred onto  
15 a substrate such as a wafer or a glass plate coated with a photosensitive material such as a photo-resist, via a projection optical system.

When manufacturing semiconductor devices, because different circuit patterns need to be formed in multiple  
20 layers on a substrate, it is important to accurately overlay the reticle on which a circuit pattern is formed onto the pattern formed in prior on each shot area on the substrate. In order to have good overlay accuracy, image forming characteristics of the projection optical system  
25 need to be adjusted to a desired state (for example, a state where magnification error of the transferred image of a reticle pattern relative to each shot area (pattern) on the substrate is corrected). Even when transferring a

reticle pattern of a first layer onto each shot area of the substrate, the image forming characteristics of the projection optical system is preferably adjusted so that reticle patterns of a second layer and the layers onward  
5 are accurately transferred onto each shot area.

As a premise for adjusting the image forming characteristics (a type of optical characteristic) of the projection optical system, the image forming characteristics need to be accurately measured (or  
10 detected). As the measuring method of the image forming characteristics, a method in which the image forming characteristics are calculated (hereinafter referred to as "exposing method") is mainly used. In this method, exposure is performed using a measurement mask on which a  
15 predetermined measurement pattern is formed, and a transferred image such as a resist image obtained by developing the substrate on which the projected image of the measurement pattern is transferred and formed, is measured. Then, based on the measurement results, the  
20 image forming characteristics, specifically Seidel's five aberrations (distortion, spherical aberration, astigmatism, field curvature and coma) are calculated. Besides such a method, a method in which the above-mentioned five aberrations are calculated without  
25 actually performing exposure (hereinafter referred to as "aerial image measurement method") is also used. In this method, a measurement mask is illuminated with an illumination light, and aerial images (projected images)

of measurement patterns formed via the projection optical system are measured, and then the above five aberrations calculated based on the measurement results.

However, with the exposing method or aerial image measurement method described above, in order to obtain all five aberrations, the measurement has to be repeated separately, using the appropriate pattern for each measurement. Furthermore, the order to perform the measurement has to be considered, depending on the type and amount of the aberration to be measured, in order to accurately adjust the projection optical system. For example, when coma is large, the image of the pattern is not resolved, therefore, when aberration such as distortion, spherical aberration, astigmatism are measured in this state, accurate data cannot be obtained. Accordingly, in such a case, the coma needs to be reduced to a certain level before measurement on distortion or the like is performed.

In addition, due to higher integration of semiconductor devices or the like in recent years, circuit patterns are becoming finer. Thus, correcting only the Seidel's five aberrations is not sufficient enough, and requirements are pressing for an overall adjustment of the image forming characteristics of the projection optical system, including the higher order of aberrations. In order to perform such overall adjustment on the image forming characteristics, lens elements that require adjustment and their adjustment amount need to be

calculated, by performing a light-ray-trace computation using data (such as curvature, refractive index, and thickness) of individual lens elements composing the projection optical system.

5           However, because data of individual lens elements are confidential for the exposure apparatus maker, it is usually difficult for a service technician repairing or adjusting the exposure apparatus or a user to obtain such data. In addition, since the light-ray-trace computation  
10 requires an enormous amount of time, it is not realistic for the service technician to perform the computation on site.

          In addition, the effect of aberrations of the projection optical system on the image forming  
15 characteristics of various patterns are different, which also makes a user of an exposure apparatus have different requirements depending on the type of pattern to be projected. For example, a contact-hole pattern is affected particularly by astigmatism. A line-and-space  
20 pattern with a thin line-width is greatly affected by coma, and for example, best focus position is different between an isolated line pattern and a line-and-space pattern.

          Under such circumstances, new technologies are  
25 expected, such as a new technology to enable an operator in a semiconductor factory to perform a simple and accurate measurement of the image forming characteristics (a type of optical characteristic) of a projection

optical system, especially the image forming characteristics (aberrations) predicted to have a great influence on the accuracy when transferring a subject pattern onto a substrate, or a new technology that can  
5 enable a service technician or the like in a semiconductor factory to perform a relatively simple and highly accurate adjustment on the image forming characteristics of the projection optical system.

The present invention was made under such  
10 circumstances, and has as its first purpose to provide an image forming characteristics measuring method in which a targeted image forming characteristic of a projection optical system can be measured easily and accurately.

The second purpose of the present invention is to  
15 provide an image forming characteristics adjusting method in which an image forming characteristic of a projection optical system can be adjusted easily and accurately.

The third purpose of the present invention is to  
20 provide an exposure method in which fine patterns can be formed with good precision on a substrate.

The fourth purpose of the present invention is to  
provide an exposure apparatus that can transfer a pattern of a mask onto a substrate with good precision.

The fifth purpose of the present invention is to  
25 provide a device manufacturing method that contributes to improving productivity of the devices.

The sixth purpose of the present invention is to  
provide a program suitable for use in each of the

exposure apparatus, and an information storage medium where such a program is stored and is readable by a computer.

## 5 ***DISCLOSURE of INVENTION***

According to a first aspect of the present invention, there is provided an image forming characteristics measuring method in which at least one image forming characteristic of a projection optical  
10 system is measured, the method comprising: a measuring process in which wavefront aberration of the projection optical system is measured at one measurement point at the least in a field of the projection optical system; and a calculating process in which at least one targeted  
15 image forming characteristic is calculated, based on the measuring of wavefront aberration and a Zernike variation table of the targeted image forming characteristic that is prepared in advance.

The "targeted image forming characteristic" in this  
20 case, is a concept that includes both a targeted image forming characteristic and its index. In this description, the term "targeted image forming characteristic" is used in such meaning.

In this method, after the wavefront aberration of  
25 the projection optical system is measured in at least one measurement point in the field of the projection optical system, the targeted image forming characteristic is calculated based on the measured aberration and the

Zernike variation table of the image forming characteristic that is prepared in advance. By preparing the Zernike variation table in advance in such manner, the targeted image forming characteristic can be  
5 calculated with only one measurement of the wavefront aberration. In this case, because the measurement is performed on wavefront aberration, which is the overall image forming characteristics of the projection optical system, the targeted image forming characteristic can be  
10 obtained with good accuracy.

In this case, in the calculating process, when the targeted image forming characteristic include image forming characteristics of a plurality of types, the image forming characteristics of a plurality of types  
15 included in the targeted image forming characteristic can each be calculated, based on the measuring of wavefront aberration and a Zernike variation table for each of the image forming characteristics of a plurality of types.

With the image forming characteristics measuring  
20 method in the present invention, the Zernike variation table of the image forming characteristic may be made separately for various image forming characteristics, taking into consideration various patterns, or the method may further comprise: a making process in which  
25 conditions are set in order to make a Zernike variation table, based on information on a pattern subject to projection by the projection optical system and the targeted image forming characteristic, and a Zernike

variation table of the targeted image forming characteristic that corresponds to information related to a given aberration is made, based on information related to the projection optical system and information related to the given aberration, prior to the measuring process. In the latter case, the information related to the projection optical system can include numerical aperture of the projection optical system, illumination condition, and wavelength of illumination light.

10           With the image forming characteristics measuring method in the present invention, when the Zernike variation table is made prior to the measuring process, in the making process, when the targeted image forming characteristic include image forming characteristics of a plurality of types, a Zernike variation table for each of the image forming characteristics of a plurality of types that correspond to the information related to aberration can be made.

20           With the image forming characteristics measuring method in the present invention, it can further comprise: a displaying process in which information related to the targeted image forming characteristic that has been calculated is displayed.

25           According to a second aspect of the present invention, there is provided a first image forming characteristics adjusting method in which at least one image forming characteristic of a projection optical system is adjusted, the method comprising: a measuring

process in which at least one targeted image forming characteristic is measured using the image forming characteristics measuring method according to Claim 1; and an adjusting process in which the projection optical system is adjusted based on results of the measuring of the targeted image forming characteristic.

In the adjusting method, because at least one targeted image forming characteristic is measured using the image forming characteristics measuring method according to the present invention, the targeted image forming characteristic can be obtained with good accuracy. And the projection optical system is adjusted based on the image forming characteristic that is obtained (the measurement results of the image forming characteristic). Therefore, the targeted image forming characteristic of the projection optical system can be adjusted with good accuracy. For example, by making the targeted image forming characteristic an image forming characteristic (aberration) that particularly influences the image forming of a subject pattern, the image forming characteristic of the projection optical system can be adjusted as much as possible according to the subject pattern.

In this case, the projection optical system can be structured comprising a plurality of optical elements that include a specific optical element used for adjustment, and adjustment of the projection optical system can be performed by deciding a targeted adjustment

amount of the specific optical element by computation using a relation expression between the image forming characteristic that has been measured, parameters, and a targeted adjustment amount of the specific optical element, and by adjusting the specific optical element for adjustment according to the decided targeted adjustment amount, the parameters denoting a relation between adjustment of the specific optical element and a change in image forming characteristics of the projection optical system.

According to a third aspect of the present invention, there is provided a second image forming characteristics adjusting method in which at least one image forming characteristic of a projection optical system comprising a plurality of optical elements that include a specific optical element used for adjustment is adjusted, the method comprising: an obtaining process in which at least one image forming characteristic of the projection optical system is obtained, by obtaining information on light via the projection optical system at one measurement point at the least in a field of the projection optical system; and a deciding process in which a targeted adjustment amount of the specific optical element is decided by computation using a relation expression between the image forming characteristic that has been obtained, parameters, and a targeted adjustment amount of the specific optical element, the parameters denoting a relation between

adjustment of the specific optical element and a change in image forming characteristics of the projection optical system.

"A specific optical element used for adjustment" in this case, refers to a specific optical element that is used for adjusting the image forming characteristic, and besides the case when the image forming characteristic of the projection optical system is adjusted by driving or changing the specific optical element, the case such as when the image forming characteristic is adjusted by reprocessing or exchanging the specific optical element is also included. That is, besides adjustment (correction) of the image forming characteristic at the adjustment stage, "adjustment" with the specific optical element also includes the making of the projection optical system itself whose image forming characteristic is adjusted. In addition, as a matter of course, the specific optical element for adjustment is not limited to one, and may be in plurals. In this description, the term "A specific optical element used for adjustment" is used in such a meaning.

In addition, when the specific optical element for adjustment is in plurals, the "targeted adjustment amount" includes the case when the adjustment amount is zero, that is, the case when no adjustment is made. In this description, the term "targeted adjustment amount" is used in such a meaning.

In this method, when adjusting the projection

optical system, information on light via the projection optical system is obtained at one measurement point in the least in the field of the projection optical system, and the image forming characteristic is obtained. And, by  
5 performing computation, using a relation expression between the image forming characteristic that has been obtained, parameters denoting the relation between the adjustment of the specific optical element and the change in the image forming characteristics of the projection  
10 optical system, and the targeted adjustment amount of the specific optical element, with the targeted adjustment amount as an unknown value, the unknown value, that is, the targeted adjustment amount of the specific optical element is decided by computation. In this manner, by  
15 using the relation expression between the actual measurement results of the image forming characteristic (aberration), parameters denoting the relation between the adjustment of the specific optical element and the change in the image forming characteristics of the  
20 projection optical system, and the targeted adjustment amount of the specific optical element, the targeted adjustment amount of the specific optical element for correcting the image forming characteristic can be calculated easily. This makes it possible to adjust the  
25 image forming characteristic of the projection optical system in a simple manner with high precision.

In this case, the method may further comprise an obtaining process in which the parameters are obtained,

prior to the obtaining process in which the image forming characteristic is obtained.

With the second image forming characteristics adjusting method in the present invention, the image forming characteristic subject to adjustment may be only one image forming characteristic, or the image forming characteristic may include a plurality of types of image forming characteristics. In the latter case, in the obtaining process in which the image forming characteristic is obtained, image forming characteristics of a plurality of types can be obtained, and in the deciding process, a target adjustment amount of the specific optical element can be decided by computation using a relation expression between the image forming characteristics of a plurality of types that have been obtained, parameters, and a targeted adjustment amount of the specific optical element, the parameters denoting a relation between adjustment of the specific optical element and a change in image forming characteristics of the projection optical system.

With the second image forming characteristics measuring method in the present invention, the image forming characteristic subject to adjustment can be image forming characteristics of various types, and corresponding to such image forming characteristics various relation expressions can be considered. For example, the image forming characteristic can be a wavefront aberration expressed in a Zernike polynomial.

In this case, the relation expression can be an equation that includes a weighting function that performs weighting on a coefficient of any term in coefficients of each term of the Zernike polynomial.

5        According to a fourth aspect of the present invention, there is provided an exposure method in which a pattern formed on a mask is transferred onto a substrate via a projection optical system, the exposure method comprising: an adjusting process in which at least  
10 one image forming characteristic of the projection optical system is adjusted using the image forming characteristics adjusting method according to any one of the first and second image forming characteristics adjusting methods; and a transferring process in which  
15 the pattern is transferred onto the substrate using the projection optical system whose image forming characteristic is adjusted.

      In the method, the image forming characteristic of the projection optical system is adjusted using either  
20 the first or the second image forming characteristics adjusting method of the present invention, and the pattern of the mask is transferred onto the substrate via the projection optical system whose image forming characteristic is adjusted. Therefore, because the  
25 pattern of the mask is transferred onto the substrate via the projection optical system whose image forming characteristic is adjusted with high precision, it allows fine patterns to be formed on the substrate with good

precision.

Especially when the projection optical system is adjusted using the first image forming characteristics adjusting method of the present invention, the targeted  
5 image forming characteristic, for example, the image forming characteristic (aberration) that particularly influences the image forming of the subject pattern, is adjusted as much as possible. Accordingly, even when exposure is performed using a mask on which a fine  
10 pattern is formed as the subject pattern, the pattern is transferred on the substrate via a projection system whose image forming characteristic (aberration) that particularly influences the image forming of the fine pattern is adjusted as much as possible.

15 According to a fifth aspect of the present invention, there is provided a first exposure apparatus that transfers a pattern formed on a mask onto a substrate via a projection optical system, the exposure apparatus comprising: a measuring unit that measures  
20 wavefront aberration of the projection optical system, the measuring unit being at least partly attachable to an exposure apparatus main body including the projection optical system; and a first computing unit that calculates at least one targeted image forming  
25 characteristic based on wavefront aberration of the projection optical system measured by the measuring unit and a Zernike variation table of the targeted image forming characteristic.

In this apparatus, when the measuring unit measures the wavefront aberration of the projection optical system, the first computing unit calculates the targeted image forming characteristic based on the calculated wavefront  
5 aberration of the projection optical system and the Zernike variation table of the targeted image forming characteristic. In this manner, by using the Zernike variation table, the targeted image forming characteristic can be calculated with only one  
10 measurement of the wavefront aberration. In this case, because the measurement is performed on wavefront aberration, which is the overall image forming characteristics of the projection optical system, the targeted image forming characteristic can be obtained  
15 with good accuracy. And, by performing exposure in a state where the targeted image forming characteristic obtained with good accuracy becomes optimum (for example, the difference between the target value is minimal), the mask pattern can be transferred onto the substrate with  
20 good accuracy.

In this case, the first exposure apparatus can further comprise a storage unit that stores the Zernike variation table in advance.

With the first exposure apparatus according to the  
25 present invention, the Zernike variation table can be a Zernike variation table of the targeted image forming characteristic that corresponds to information on a given aberration on exposure of a subject pattern.

The first exposure apparatus according to the present invention can further comprise: an input unit used to input information of various types including information on the subject pattern, information on the targeted image forming characteristic, information related to the projection optical system, and information on the given aberration; and a second computing unit that set conditions in order to make a Zernike variation table based on the information on the subject pattern and the targeted image forming characteristic input via the input unit, and based on information related to the projection optical system and information related to the given aberration input via the input unit, the second computing unit makes a Zernike variation table of the targeted image forming characteristic that corresponds to information on the given aberration on exposure of the subject pattern.

In this case, the information related to the projection optical system can include numerical aperture of the projection optical system, illumination condition, and wavelength of illumination light.

The first exposure apparatus according to the present invention can further comprise a display unit which displays information on the targeted image forming characteristic calculated by the first computing unit on screen.

The first exposure apparatus according to the present invention can further comprise an image forming

characteristics correcting unit that corrects at least one image forming characteristic of the projection optical system based on calculation results of the targeted image forming characteristic by the first  
5 computing unit.

In this case, the projection optical system can be structured comprising a plurality of optical elements that include a specific optical element used for adjustment, and the image forming characteristics  
10 correcting unit can have a storage unit in which parameters are stored in advance that denotes a relation between adjustment of the specific optical element and a change in image forming characteristics of the projection optical system, and a calculation unit that calculates a  
15 targeted adjustment amount of the specific optical element using a relation expression between information on the image forming characteristic that has been calculated, the parameters, and a targeted adjustment amount of the specific optical element.

20 According to a sixth aspect of the present invention, there is provided a second exposure apparatus that transfers a pattern formed on a mask onto a substrate via a projection optical system, the exposure apparatus comprising: the projection optical system that  
25 comprises a plurality of optical elements including a specific optical element used for adjustment; a storage unit in which parameters are stored in advance that denotes a relation between adjustment of the specific

optical element and a change in image forming characteristics of the projection optical system, a measuring unit that measures at least one image forming characteristic of the projection optical system, the  
5 measuring unit being at least partly attachable to an exposure apparatus main body including the projection optical system; and a computing unit that calculates a targeted adjustment amount of the specific optical element using a relation expression between an actual  
10 measurement data measured by the measuring unit, the parameters, and a targeted adjustment amount of the specific optical element.

In this apparatus, parameters are obtained in advance that denote the relation between the adjustment  
15 of an adjustable specific optical element and the change in image forming characteristics of the projection optical system, and are stored in the storage unit. And, when the measuring unit actually measures the image forming characteristic of the projection optical system,  
20 the computing unit then calculates the targeted adjustment amount of the specific optical element using the relation expression between the actual measurement data of the image forming characteristic, the above parameters, and the targeted adjustment amount of the  
25 specific optical element. As is described, because the above parameters are obtained in advance and stored in the storage unit, when the image forming characteristic (aberration) is actually measured the targeted adjustment

amount of the specific optical element for correcting the image forming characteristic can be calculated easily, and by adjusting the specific optical element based on the calculation results, the image forming characteristic of the projection optical system can be adjusted simply but with high precision. Accordingly, by performing exposure using such projection optical system whose image forming characteristic is adjusted with high precision, the pattern of the mask can be transferred onto the substrate with good accuracy via the projection optical system.

In this case, the adjustment based on the above calculated targeted adjustment amount of the specific optical element can be performed manually via an operator, or, for example, the second exposure apparatus can further comprise an image forming characteristics adjusting unit that adjusts at least one image forming characteristic of the projection optical system by adjusting the specific optical element according to the calculated targeted adjustment amount.

With the second exposure apparatus according to the present invention, the image forming characteristic subject to adjustment can be one image forming characteristic, however, the image forming characteristic can include image forming characteristics of a plurality of types. In the latter case, the measuring unit can measure image forming characteristics of a plurality of types of the projection optical system, and the computing

unit can calculate a targeted adjustment amount of the specific optical element using a relation expression between an actual measurement data of the image forming characteristics of a plurality of types measured by the measuring unit, the parameters, and a targeted adjustment amount of the specific optical element.

With the second exposure apparatus according to the present invention, the image forming characteristic subject to adjustment can be image forming characteristics of various types, and corresponding to such image forming characteristics various relation expressions can be considered. For example, the image forming characteristic can be a wavefront aberration expressed in a Zernike polynomial.

In this case, the relation expression can be an equation that includes a weighting function that performs weighting on a coefficient of any term in coefficients of each term of the Zernike polynomial.

According to a seventh aspect of the present invention, there is provided a first program that makes a control computer of an exposure apparatus that transfers a pattern of a mask onto a substrate via a projection optical system execute a predetermined process, the program making the control computer execute: a condition setting procedure in which conditions are set for making a Zernike variation table in response to an input of information related to information on a subject pattern and information on a targeted image forming

characteristic; and a making procedure in which a Zernike variation table of the targeted image forming characteristic corresponding to information on given aberration on exposure of the subject pattern is made, in response to an input of information related to the projection optical system and information on the given aberration.

When the program is installed in the control computer of the exposure apparatus, by inputting information on the subject pattern and information related to the targeted image forming characteristic in the computer, condition setting for making a Zernike variation table is performed by the computer in response to the input. Next, by inputting information related to the projection optical system and information on a given aberration into the computer that has completed such condition setting, the computer makes a Zernike variation table of the targeted image forming characteristic that corresponds to the information on the given aberration on exposure of the subject pattern in response to the input. That is, by only inputting minimal information necessary for making the Zernike variation table into the computer, such as information on the subject pattern, information related to the targeted image forming characteristic, information related to the projection optical system, and information on the given aberration, a Zernike variation table of the targeted image forming characteristic that corresponds to the given aberration on exposure of a

subject pattern can be easily made. The Zernike variation table, which is made, can also be used in other exposure apparatus that comprises the same type of projection optical system.

5        After creating the Zernike variation table in the manner described above, the program can further make the control computer execute a calculating procedure in which the targeted image forming characteristic of the projection optical system is calculated in response to an  
10    input of actual measurement data of wavefront aberration of the projection optical system, based on the actual measurement data and the Zernike variation table. In such a case, by further inputting the actual measurement data of wavefront aberration of the projection optical system,  
15    the computer calculates the targeted image forming characteristic of the projection optical system based on the actual data and the Zernike variation table in response to the input. Accordingly, only by inputting the actual measurement data of the wavefront aberration  
20    obtained in at least one measurement, the targeted image forming characteristic can be calculated by the computer accurately in a short period of time.

      With the first program according to the present invention, the program can further make the control  
25    computer execute a displaying procedure in which information on the targeted image forming characteristic that has been calculated is displayed on a display unit.

      With the first program according to the present

invention, the program can further make the control computer execute an adjusting procedure in which the projection optical system is adjusted so that the targeted image forming characteristic that has been  
5 calculated becomes optimal (for example, the difference between the target value is minimal).

With the first program according to the present invention, when the targeted image forming characteristic is calculated in addition to the making of the Zernike  
10 variation table described above, the program can further make the control computer execute: a making procedure in which the Zernike variation table is made in response to input of different information related to the projection optical system and input of information on the given  
15 aberration, by each different information related to the projection optical system; a calculating procedure in which the targeted image forming characteristic of the projection optical system is calculated by each different information related to the projection optical system in  
20 response to input of actual measurement data of wavefront aberration of the projection optical system, based on the actual measurement data and the Zernike variation table; and a deciding procedure in which an optimum exposure condition is decided by finding information related to  
25 the projection optical system that makes the targeted image forming characteristic that has been calculated become optimal (for example, the difference between the target value is minimal).

In this case, the program can further make the control computer execute a setting procedure in which the optimum exposure condition that has been decided is set.

According to an eighth aspect of the present invention, there is provided a second program that makes a control computer execute a process, the program making the control computer execute: a procedure of calculating a targeted image forming characteristic of a projection optical system in response to an input of information related to the targeted image forming characteristic and an input of actual measurement data of wavefront aberration of the projection optical system, based on the actual measurement data and a Zernike variation table of the targeted image forming characteristic that is prepared in advance.

When the program is installed in the control computer of the exposure apparatus, by inputting information related to the targeted image forming characteristic and the actual measurement data of wavefront aberration of the projection optical system into the computer, the computer calculates the targeted image forming characteristic of the projection optical system based on the actual measurement data and the Zernike variation table of the targeted image forming characteristic prepared in advance in response to the input. In such a case, control computers of other exposure apparatus that comprise the same type of projection optical system can use the Zernike variation

table, which is a Zernike variation table of the targeted image forming characteristic that is made using the first program of the present invention. Accordingly, only by inputting information related to the targeted image forming characteristic and the actual measurement data of the wavefront aberration obtained in at least one measurement, the targeted image forming characteristic can be calculated by the computer accurately in a short period of time. In this case, for example, the image forming characteristic that greatly affects the image forming of the subject pattern is preferably chosen as the targeted image forming characteristic.

With the second program according to the present invention, the program can further make the control computer execute a displaying procedure in which information on the targeted image forming characteristic that has been calculated is displayed on a display unit.

With the second program according to the present invention, the program can further make the control computer execute an adjusting procedure in which the projection optical system is adjusted so that the targeted image forming characteristic that has been calculated becomes optimal.

According to a ninth aspect of the present invention, there is provided a third program that makes a control computer of an exposure apparatus that transfers a pattern of a mask onto a substrate via a projection optical system execute a predetermined process, the

program making the control computer execute: a  
calculating procedure in which a targeted adjustment  
amount of the projection optical system is calculated in  
response to an input of actual measurement data of image  
5 forming characteristic of the projection optical system,  
using a relation expression between the actual  
measurement data of image forming characteristic that has  
been input, parameters, and a targeted adjustment amount  
of the projection optical system, the parameters denoting  
10 a relation between adjustment of the projection optical  
system and a change in image forming characteristics of  
the projection optical system.

With this program, the program is installed in the  
control computer of the exposure apparatus in advance.  
15 And, when the actual measurement data of the image  
forming characteristic of the projection optical system  
is input, the control computer of the exposure apparatus  
calculates the targeted adjustment amount using the  
relation expression between the actual measurement data  
20 that has been input, the parameters denoting the relation  
between the adjustment of the projection optical system  
and the change in the image forming characteristics of  
the projection optical system, and the targeted  
adjustment amount of the projection optical system. That  
25 is, the operator or the like only has to actually measure  
the image forming characteristic (aberration) and input  
the actual measurement values of the image forming  
characteristic, to calculate the targeted adjustment

amount of the projection optical system in order to correct the image forming characteristic. Accordingly, for example, by adjusting the projection optical system based on the calculated targeted adjustment amount, the  
5 image forming characteristic of the projection optical system can be easily adjusted, with high precision.

In this case, the program can further make the control computer execute a displaying procedure in which information on the targeted adjustment amount that has  
10 been calculated is displayed on a display unit.

With the third program according to the present invention, the program can further make the control computer execute an adjusting procedure in which the projection optical system is adjusted based on the target  
15 adjustment amount that has been calculated.

With the third program according to the present invention, the parameters can be parameters denoting a relation between adjustment of a specific optical element used for adjustment that structures the projection  
20 optical system and a change in the image forming characteristics, and the targeted adjustment amount can be an amount of the specific optical element that needs to be adjusted.

With the third program according to the present  
25 invention, the image forming characteristic can be a wavefront aberration expressed in a Zernike polynomial.

In this case, the relation expression can be an equation that includes a weighting function that performs

weighting on a coefficient of any term in coefficients of each term of the Zernike polynomial.

With the third program according to the present invention, the program can further make the control  
5 computer execute: a condition setting procedure in which conditions are set for making a Zernike variation table in response to an input of information related to information on a subject pattern and an input of information on a targeted image forming characteristic; a  
10 making procedure in which a Zernike variation table of the targeted image forming characteristic corresponding to information on aberration is made, in response to an input of information related to the projection optical system and information on a given aberration; and a  
15 calculating procedure in which the targeted image forming characteristic is calculated in response to an input of actual measurement data of wavefront aberration of the projection optical system, based on the measurement data and the Zernike variation table.

20 With the third program according to the present invention, the program can further make the control computer execute a displaying procedure in which information on the targeted image forming characteristic that has been calculated is displayed on a display unit.

25 With the third program according to the present invention, the program can further make the control computer execute a converting procedure in which information obtained on light via the projection optical

system at one measurement point at the least in a field of the projection optical system is converted into actual measurement data of the wavefront aberration of the projection optical system.

5        According to a tenth aspect of the present invention, there is provided a third image forming characteristics adjusting method in which at least one image forming characteristic of a projection optical system is adjusted, the method including: a measuring process in which  
10   information related to wavefront aberration of the projection optical system is measured; and the image forming characteristic is adjusted by driving an optical element of the projection optical system, based on data of a relation between an adjustment amount of the optical  
15   element and a change in coefficients of each term in a Zernike polynomial, and the information related to wavefront aberration.

With this method, when adjusting at least one image forming characteristic of the projection optical system,  
20   information related to the wavefront aberration of the projection optical system is measured, and based on the information related to the wavefront aberration that is measured and data on the relation between the adjustment amount of the optical element of the projection optical  
25   system and the change in coefficients of each term in the Zernike polynomial, the image forming characteristic is adjusted by driving the optical element. In this case, the targeted adjustment amount of the optical element for

correcting the image forming characteristic of the projection optical system can be calculated easily, based on the adjustment amount of the optical element of the projection optical system and the change in coefficients  
5 of each term in the Zernike polynomial and the information related to the wavefront aberration that has been measured. As a consequence, the image forming characteristic of the projection optical system can be adjusted easily with high precision.

10       According to an eleventh aspect of the present invention, there is provided an exposure method in which a pattern is transferred onto an object via a projection optical system, the method including a measuring process in which information related to wavefront aberration of  
15 the projection optical system is measured; a calculating process in which a targeted image forming characteristic is calculated for each of a plurality of exposure conditions settable when the pattern is projected by the projection optical system, based on the information  
20 related to wavefront aberration and a Zernike variation table that is obtained by giving a predetermined value of aberration to each term in a Zernike polynomial and calculating a targeted image forming characteristic of the projection optical system in each of a plurality of  
25 terms in the Zernike polynomial; and a transferring process in which the pattern is transferred onto the object with an optimum exposure condition set with respect to the pattern, based on the targeted image

forming characteristic that has been calculated for each of the exposure conditions.

With this method, the information related to the wavefront aberration of the projection optical system is measured prior to exposure, and based on the information related to the aberration and the Zernike variation table that is obtained by calculating the targeted image forming characteristic of the projection optical system in each of a plurality of terms in the Zernike polynomial and by giving a predetermined value of aberration to each term in a Zernike polynomial, the targeted image forming characteristics are calculated for each of a plurality of exposure conditions settable when the pattern is projected by the projection optical system. And, when exposure is performed, the optimum condition is set for the pattern based on targeted mage forming characteristic calculated for each of the exposure conditions, and the pattern is transferred onto the object. Therefore, because exposure is performed under the optimum condition according to the pattern, the pattern can be transferred onto the object with good accuracy, even when it is fine pattern.

According to a twelfth aspect of the present invention, there is provided a third exposure apparatus that transfers a pattern onto an object via a projection optical system, the exposure apparatus comprising: a computing unit that obtains a targeted image forming characteristic, based on information related to wavefront

aberration of the projection optical system and a Zernike variation table that is obtained by giving a predetermined value of aberration to each term in a Zernike polynomial and calculating the targeted image forming characteristic of the projection optical system in each of a plurality of terms in the Zernike polynomial; and an adjusting unit that adjusts at least one image forming characteristic of the projection optical system based on one of the information related to wavefront aberration and the targeted image forming characteristic that has been calculated.

With this apparatus, the computing unit obtains the targeted image forming characteristic, based on the information related to the wavefront aberration of the projection optical system and the Zernike variation table obtained by calculating the targeted image forming characteristic of the projection optical system in each of a plurality of terms in the Zernike polynomial, by giving a predetermined value of aberration to each term in the Zernike polynomial. And, the adjusting unit adjust the image forming characteristic of the projection optical system based on the information related to the wavefront aberration or the image forming characteristic that has been calculated. Accordingly, the image forming characteristic of the projection optical system is adjusted with good accuracy including the high order component based on the information related to the wavefront aberration, or adjustment to correct the

targeted image forming characteristic with good accuracy is performed. In any case, by using the projection optical system that has been adjusted to transfer the pattern onto the object, fine patterns can be transferred  
5 onto the object with good accuracy.

According to a thirteenth aspect of the present invention, there is provided a fourth exposure apparatus that transfers a pattern onto an object via a projection optical system, the exposure apparatus comprising: a  
10 storage unit that stores data related to a relation between an adjustment amount of an optical element of the projection optical system and a change in coefficients of each term in a Zernike polynomial; and an adjusting unit that adjusts at least one image forming characteristic of  
15 the projection optical system based on information related to wavefront aberration of the projection optical system and the data.

With this apparatus, the adjusting unit adjusts the image forming characteristic of the projection optical  
20 system based on the data on the relation between the adjustment amount of the optical element of the projection optical system and the change in coefficients of each term in the Zernike polynomial and the information related to the wavefront aberration of the  
25 projection optical system that are stored in the storage unit. In this case, because the targeted adjustment amount of the optical element for correcting the image forming characteristic of the projection optical system

can be easily calculated, based on the data on the relation between the adjustment amount of the optical element of the projection optical system and the change in coefficients of each term in the Zernike polynomial and the information related to the wavefront aberration (such as the measurement values of the wavefront aberration), the image forming characteristic of the projection optical system can be adjusted easily with high precision. And, by performing exposure using the projection optical system that has been adjusted, the pattern can be transferred onto the object with good accuracy.

According to a fourteenth aspect of the present invention, there is provided a fifth exposure apparatus that transfers a pattern onto an object via a projection optical system, the exposure apparatus comprising: a computing unit that obtains a targeted image forming characteristic when a plurality of exposure conditions are settable on projecting the pattern by the projection optical system, based on information related to wavefront aberration of the projection optical system and a Zernike variation table that is obtained by giving a predetermined value of aberration to each term in a Zernike polynomial and calculating the targeted image forming characteristic of the projection optical system in each of a plurality of terms in the Zernike polynomial; and an exposure control unit that sets an optimum exposure condition for the pattern, based on the

targeted image forming characteristic that has been calculated for each of the exposure conditions.

With this apparatus, the computing unit calculates the targeted image forming characteristic for a plurality of exposure conditions that are settable when projecting the pattern with the projection optical system, based on the information related to the wavefront aberration of the projection optical system and the Zernike variation table obtained by calculating the targeted image forming characteristic of the projection optical system in each of a plurality of terms in the Zernike polynomial, by giving a predetermined value of aberration to each term in the Zernike polynomial. And, the exposure control unit sets the optimum exposure condition for the pattern based on the targeted image forming characteristic that has been calculated for each of the exposure conditions. In this manner, exposure is performed under the optimum condition corresponding to the pattern, therefore, even if the pattern is a fine pattern, it can be transferred with good accuracy on the object.

According to a fifteenth aspect of the present invention, there is provided a fourth program that makes a control computer of an exposure apparatus that transfers a pattern of a mask onto an object via a projection optical system execute a predetermined process, the program making the control computer execute: a measuring procedure in which information related to wavefront aberration of the projection optical system is

measured; and an adjusting procedure in which at least one image forming characteristic is adjusted by driving an optical element of the projection optical system, based on data of a relation between an adjustment amount  
5 of the optical element and a change in coefficients of each term in a Zernike polynomial, and information related to the wavefront aberration.

According to a sixteenth aspect of the present invention, there is provided a fifth program that makes a  
10 control computer of an exposure apparatus that transfers a pattern of a mask onto an object via a projection optical system execute a predetermined process, the program making the control computer execute: a measuring procedure in which information related to wavefront  
15 aberration of the projection optical system is measured; a calculating procedure in which a targeted image forming characteristic is calculated in a plurality of exposure conditions settable when projecting the pattern by the projection optical system, based on information related  
20 to wavefront aberration of the projection optical system and a Zernike variation table that is obtained by giving a predetermined value of aberration to each term in a Zernike polynomial and calculating the targeted image forming characteristic of the projection optical system  
25 in each of a plurality of terms in the Zernike polynomial; and a transferring procedure in which the pattern is transferred onto the object with an optimum exposure condition set with respect to the pattern, based

on the targeted image forming characteristic that has been calculated for each of the exposure conditions.

According to a seventeenth aspect of the present invention, there is provided a sixth program that makes a control computer of an exposure apparatus that transfers a pattern of a mask onto an object via a projection optical system execute a predetermined process, the program making the control computer execute: an obtaining procedure in which a targeted image forming characteristic is obtained, based on information related to wavefront aberration of the projection optical system and a Zernike variation table that is obtained by giving a predetermined value of aberration to each term in a Zernike polynomial and calculating the targeted image forming characteristic of the projection optical system in each of a plurality of terms in the Zernike polynomial; and an adjusting procedure in which at least one image forming characteristic of the projection optical system is adjusted, based on the information related to wavefront aberration and the image forming characteristic that has been calculated.

The first to sixth programs of the present invention can be stored in a storage medium. Therefore, according to an eighteenth aspect of the present invention, there is provided an information storage medium that can be read by a computer in which any one of the first to sixth programs is recorded.

In addition, in a lithographic process, by

performing exposure using one of the first to fifth exposure apparatus according to the present invention, patterns can be formed with good precision on a substrate, which allows production of highly integrated microdevices  
5 with good yield. Accordingly, further from another aspect of the present invention, there is provided a device manufacturing method that uses one of the first to fifth exposure apparatus of the present invention (that is, a device manufacturing method that includes the process of  
10 transferring a pattern onto a photosensitive object using one of the first to fifth exposure apparatus).

In addition, when making the exposure apparatus, by adjusting the projection optical system using one of the first to third image forming characteristics adjusting  
15 method after the projection optical system has been incorporated into the main body of the exposure apparatus,

the image forming characteristics of the projection optical system can be adjusted with good accuracy. Accordingly, yet further from another aspect of the present invention, there is provided a making method of an exposure apparatus that includes the process of adjusting the projection optical system using one of the first to third image forming characteristics adjusting methods.

#### 10 **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a schematic view showing a configuration of an exposure apparatus according to an embodiment of the present invention;

15 Figs. 2A to 2F are views for explaining a definition of drive directions of movable lenses or the like that are driven on the making of a data base;

Fig. 3 is a schematic perspective view of a measurement reticle;

20 Fig. 4 is a view showing a schematic view of an XZ cross section in the vicinity of an optical axis in a state where a measurement reticle is mounted on a reticle stage, along with a diagram of a projection optical system;

25 Fig. 5 is a view showing a schematic view of an XZ cross section in the vicinity of a -Y side end portion in a state where a measurement reticle is mounted on a reticle stage, along with a diagram of a projection optical system;

Figs. 6A and 6B are views showing a measurement pattern and a reference pattern formed on the measurement reticle in this embodiment, respectively;

Fig. 7 is a flow chart schematically showing a control algorithm of a CPU of a main controller for measurement of an image forming characteristic and display (simulation);

Fig. 8 is a flow chart showing a processing in subroutine 126 of Fig. 7;

Fig. 9A is a view showing a reduced image (latent image) of the measurement pattern formed at a predetermined spacing on the resist layer of a wafer, and Fig. 9B is a view showing a positional relation between the latent image of the measurement pattern in Fig. 9A and a latent image of a reference pattern;

Fig. 10 is a sectional view showing an example of a portable wavefront-aberration measuring unit; and

Figs. 11A and 11B are views showing beams outgoing from a microlens array, in cases where there is no aberration in the optical system and where there is aberration in the optical system, respectively.

### ***Best Mode for Carrying out the Invention***

An embodiment of the present invention will be described below with reference to Figs. 1 to 9B.

Fig. 1 shows an entire structure of an exposure apparatus 10 according to an embodiment of the present invention. Exposure apparatus 10 is a reduction

projection exposure apparatus based on a step-and-repeat method, or a so-called stepper, which uses a pulse-laser light source as an exposure light source (hereinafter, called a "light source").

5           Exposure apparatus 10 comprises: an illumination system made up of a light source 16 and an illumination optical system 12; a reticle stage RST which serves as a mask stage holding a reticle R serving as a mask, which is illuminated with exposure illumination light EL  
10   serving as an energy beam from the illumination system; a projection optical system PL which projects exposure illumination light EL emitted from reticle R onto a wafer W (on the image plane) serving as a substrate; a wafer stage WST serving as a substrate stage on which a Z-tilt  
15   stage 58 for holding wafer W is mounted; and a control system for controlling the above parts.

          Light source 16 is a pulse-ultraviolet light source that emits pulse light having a wavelength in the vacuum-ultraviolet range, such as an F<sub>2</sub> laser (a wavelength of  
20   157nm) or an ArF laser (a wavelength of 193nm).

Alternatively, light source 16 may be a light source that emits pulse light having a wavelength in the far-ultraviolet or ultraviolet range such as a KrF excimer laser (a wavelength of 248nm).

25           In actual, light source 16 is arranged in a service room that has a low degree of cleanliness, different from a clean room where a chamber 11 is arranged. In chamber 11, an exposure apparatus main body is housed that is

made up of parts such as various elements of illumination optical system 12, reticle stage RST, projection optical system PL, and wafer stage WST, and light source 16 is connected to chamber 11 via a light-transmitting optical system (not shown). The light transmitting optical system includes at least an optical axis adjusting optical system called a beam-matching unit as a part of its system. An internal controller of the apparatus controls the on/off of the output of laser beam LB, the energy of laser beam LB per pulse, oscillation frequency (repetition frequency), the center wavelength and half band width in spectrum (width of the wavelength range) and the like of light source 16, according to control information TS from a main controller 50.

15           Illumination optical system 12 comprises: a beam-shaping illuminance uniformity optical system 20 which includes parts such as a cylinder lens, a beam expander (none are shown), an optical integrator (homogenizer) 22; an illumination system aperture stop plate 24; a first relay lens 28A; a second relay lens 28B; a reticle blind 30; a mirror M for deflecting the optical path; a condenser lens 32, and the like. As the optical integrator a fly-eye lens, a rod integrator (internal reflection type integrator) or a diffracting optical element can be used. In this embodiment, since a fly-eye lens is used as optical integrator 22, it will be referred to as fly-eye lens 22 hereinafter.

Beam shaping illuminance uniformity optical system

20 is connected to the light transmitting optical system (not shown), via a light transmission window 17 provided on the chamber 11. It shapes the cross section of laser beam LB, which is emitted from light source 16 and enters beam shaping illuminance uniformity optical system 20 via light transmission window 17, using parts such as the cylinder lens and beam expander. Fly-eye lens 22 in the exit side of beam shaping illuminance uniformity optical system 20 forms a surface light source (a secondary light source), which is made up of a large number of point light sources on the focal plane on the exit side arranged so that it substantially coincides with the pupil plane of illumination optical system 12, with the laser beam that has its cross section shaped, in order to illuminate reticle R with uniform illuminance distribution. The laser beam emitted from the secondary light source is hereinafter referred to as "illumination light EL".

In the vicinity of the focal plane on the exit side of fly-eye lens 22, illumination system aperture stop plate 24 constituted by a disk-like member is disposed. And, on illumination system aperture stop plate 24, for example, an aperture stop (conventional stop) constituted by a circular opening, an aperture stop (a small  $\sigma$  stop) for making coherence factor  $\sigma$  small which is constituted by a small, circular opening, a ring-like aperture stop (annular stop) for forming a ring of illumination light, and a modified aperture stop for modified illumination

composed of a plurality of openings disposed in an eccentric arrangement are arranged at a substantially equal angle (only two types of aperture stops are shown in Fig. 1). Illumination system aperture stop plate 24 is  
5 constructed and arranged to be rotated by a driving unit 40, for example a motor, controlled by main controller 50, and one of the aperture stops is selectively set to be on the optical path of the illumination light EL, so that the shape of the illuminant surface in Koehler  
10 illumination described later is limited to a ring, a small circle, a large circle, four eyes or the like.

Instead of, or in combination with aperture stop plate 24, for example, an optical unit comprising at least one of a plurality of diffracting optical elements,  
15 a movable prism (conical prism, polyhedron prism, etc.) which moves along the optical axis of the illumination optical system, and a zoom optical system can be arranged in between light source 16 and optical integrator 22. And by changing the intensity distribution of the  
20 illumination light on the incident surface when the optical integrator 22 is a fly-eye lens, or the range of incident angle of the illumination light to the incident surface when the optical integrator 22 is an internal surface reflection type integrator, light amount  
25 distribution (the size and shape of the secondary illuminant) of the illumination light on the pupil plane of the illumination optical system, or in other words, the loss of light due to the change of conditions for

illuminating reticle R, is preferably suppressed. In addition, in the embodiment, a plurality of light source images (virtual images) formed by the internal surface reflection type integrator is also referred to as the  
5 secondary light source.

On the optical path of illumination light EL emitted from illumination system aperture stop plate 24, a relay optical system is arranged that is made up of the first relay lens 28A and the second relay lens 28B, with  
10 reticle blind 30 disposed in between. Reticle blind 30 is disposed on a plane conjugate to the pattern surface of reticle R, and forms a rectangular opening to set a rectangular illumination area IAR on reticle R. In this case, a movable blind that has a variable opening shape  
15 is used as reticle blind 30, and the opening is set by main controller 50 based on blind setting information, which is also called masking information.

On the optical path of the illumination light EL after the second relay lens 28B making up the relay  
20 optical system, deflecting mirror M is disposed for reflecting illumination light EL having passed through the second relay lens 28B toward reticle R. And, on the optical path of illumination light EL after mirror M, condenser lens 32 is disposed.

25 In the structure described above, the incident surface of fly-eye lens 22, the plane on which the reticle blind 30 is disposed, and the pattern surface of reticle R are set optically conjugate to one another,

whereas the light source surface formed on the focal plane on the exit side of fly-eye lens 22 (the pupil plane of the illumination optical system) and the Fourier transform plane of projection optical system PL (the exit pupil plane) are set optically conjugate to each other, so as to form a Koehler illumination system.

The operation of illumination optical system 12 that has the structure described above will be briefly described below. Laser beam LB emitted in pulse from light source 16 enters beam shaping illuminance uniformity optical system 20, which shapes the cross section of the beam. The beam then enters fly-eye lens 22, and the secondary light source is formed on the focal plane on the exit side of fly-eye lens 22.

When illumination light EL emitted from the secondary light source passes through one of the aperture stops on illumination system aperture stop plate 24, it then passes through the rectangular aperture of the reticle blind 30 via the first relay lens 28A, and then passes through second relay lens 28B and is deflected vertically downward by mirror M. Then, after passing through condenser lens 32, illumination light EL illuminates the rectangular illumination area IAR on reticle R held on reticle stage RST with uniform illuminance.

On reticle stage RST, reticle R is mounted and held by electrostatic chucking (or by vacuum chucking) or the like (not shown). Reticle stage RST is structured so that

it can be finely driven (and rotated) on a horizontal plane (an XY plane) by a driving system (not shown). In addition, reticle stage RST can be moved in the Y-axis direction within a predetermined stroke range (of around  
5 the length of reticle R). The position of reticle stage RST is measured by a position detector, such as a reticle laser interferometer, at a resolution of, for example, 0.5 to 1nm, and the measurement results are supplied to main controller 50.

10           Material used for reticle R depends on the light source used. More particularly, when an ArF excimer laser or KrF excimer laser is used as the light source, synthetic quartz, fluoride crystal such as fluorite, fluorine-doped quartz or the like can be used, whereas,  
15 when an F<sub>2</sub> laser is used as the light source, the material used for reticle R needs to be fluoride crystal such as fluorite, fluorine-doped quartz or the like.

          Projection optical system PL is, for example, a reducing system that is double telecentric, and the  
20 projection magnification of projection optical system PL is, e.g., 1/4, 1/5 or 1/6. Therefore, when illumination area IAR on reticle R is illuminated with illumination light EL in the manner described above, the image of the pattern formed on reticle R is reduced by the above  
25 projection magnification via projection optical system PL, and then is projected and transferred onto a rectangular area IA (normally coincides with the shot area) on wafer W coated with a resist (photosensitive material).

Projection optical system PL is a dioptric system composed only of a plurality of refracting optical elements (lenses) 13, such as around 10 to 20, as is shown in Fig. 2. Of the plurality of lenses 13 making up  
5 projection optical system PL, a plurality of lenses 13<sub>1</sub>, 13<sub>2</sub>, 13<sub>3</sub>, 13<sub>4</sub> (in this case, for the sake of simplicity, there are four lens devices) in the object-plane side (reticle R side) are movable lenses, which can be driven externally by an image forming characteristics correction  
10 controller 48. Lens holders (not shown) hold lenses 13<sub>1</sub>, 13<sub>2</sub>, 13<sub>4</sub>, respectively, and these lens holders are supported in the gravitational direction at three points by driving devices such as piezo elements (not shown). And, by independently adjusting the applied voltage to  
15 the driving devices, the lenses 13<sub>1</sub>, 13<sub>2</sub>, 13<sub>4</sub> can be shifted in a Z-axis direction, which is the optical axis direction of projection optical system PL, and can be driven (tilted) in a direction of inclination relative to the XY plane (that is, a rotational direction around the  
20 X-axis and a rotational direction around the Y-axis). In addition, a lens holder (not shown) holds lens 13<sub>3</sub>, and on the periphery of the lens holder, driving devices such as piezo elements are disposed at a substantially equal angle of, for example, 90 degrees. The opposing driving  
25 devices are paired, and the applied voltage to each pair is adjusted so that lens 13<sub>3</sub> can be shifted two-dimensionally in the XY plane. In this embodiment, lenses 13<sub>1</sub>, 13<sub>2</sub>, 13<sub>3</sub>, and 13<sub>4</sub> each structure a specific optical

element for adjustment. Specific optical elements are not limited to lenses 13<sub>1</sub>, 13<sub>2</sub>, 13<sub>3</sub>, 13<sub>4</sub>, and may include lenses disposed near the pupil plane or the image plane of projection optical system PL, or an aberration  
5 correcting plate (optical plate) for correcting the aberration of projection optical system PL, especially the non-rotational symmetric component. Furthermore, the degree of freedom (the number of movable directions) of the specific optical elements is not limited to two or  
10 three, but may be one or four and over.

In addition, an aperture stop 15 is provided near the pupil plane of projection optical system PL, and the numerical aperture (N.A.) of aperture stop 15 is variable continuously in a predetermined range. As aperture stop  
15 15, for example, a so-called iris aperture stop is used, and main controller 50 controls aperture stop 15.

When an ArF excimer laser or KrF excimer laser is used as the illumination light EL, the material for each of the lens elements used in the projection optical  
20 system PL can be synthetic quartz, however, when an F<sub>2</sub> laser is used, the material of the lenses used all has to be fluoride crystal such as fluorite, or fluorine-doped quartz referred to earlier.

Wafer stage WST is structured freely drivable on  
25 the XY two-dimensional plane by a wafer-stage driving portion 56. And wafer W is held on a Z-tilt stage 58 mounted on wafer stage WST by electrostatic chucking, vacuum chucking or the like, via a wafer holder (not

shown). Z-tilt stage 58 adjusts the position of wafer W in the Z-direction (focus position) and the angle of inclination of wafer W with respect to the XY plane. In addition, the X- and Y-positions and rotation (including yawing, pitching and rolling) of wafer stage WST is measured with a wafer laser interferometer 54W externally disposed via a movable mirror 52W, which is fixed on Z-tilt stage 58. The measurement values of wafer laser interferometer 54W are supplied to main controller 50.

10 In addition, a reference mark plate FM on which reference marks such as those for base-line measurement are formed is fixed on Z-tilt stage 58 so that the surface of reference mark plate FM is substantially the same height as the surface of wafer W.

15 In the exposure apparatus 10 in the embodiment, although it is omitted in the drawings, a pair of reticle alignment microscopes is provided above reticle R, each constituted by a TTR (Through The Reticle) alignment optical system. With this system, the exposure wavelength is used to observe a reticle mark 2 on reticle R and a reference mark on the reference mark plate at the same time, via projection optical system PL. As such reticle alignment microscopes, microscopes that have a similar structure to the ones disclosed in, for example, Japanese Patent Application Laid-Open No. 07-176468 and the corresponding U.S. Patent No. 5,646,413, are used. As long as the national laws in designated states or elected states, to which this international application is

applied, permit, the above disclosures are incorporated herein by reference.

In addition, in the embodiment, although it is omitted in the drawings, the position of wafer W in the Z-direction is measured with a focus detection sensor constituted by a multiple focal point position detection system, which details are disclosed in, for example, Japanese Patent Application Laid-Open No. 06-283403 and its corresponding U.S. Patent No. 5,448,332. The output of this focus sensor is supplied to main controller 50, which performs so-called focus-leveling by controlling Z-tilt stage 58. As long as the national laws in designated states or elected states, to which this international application is applied, permit, the above disclosures are incorporated herein by reference.

Furthermore, an alignment system based on an off-axis method is provided (not shown) on the side surface of projection optical system PL. As such a system, for example, a microscope of an FIA (Field Image Alignment) system based on an image-processing method is used. In this system, for example, a broadband detection beam that does not expose the resist on the wafer is irradiated on a target mark, an image of the target mark formed on the photodetection surface by the reflection light from the target mark and an index image are picked up with a pick-up device (such as a CCD), and the imaging signals are output. And, based on the output of the alignment system, the position of the reference marks on reference mark

plate FM and alignment marks on the wafer can be measured in the XY two-dimensional directions.

In the control system in Fig. 1, main controller 50 plays the main role. Main controller 50 is made up of a so-called workstation (or microcomputer) comprising a CPU (Central Processing Unit), ROM (Read Only Memory), RAM (Random Access Memory), or the like, and controls overall operations such as the stepping of wafer stage WST in between shots and the exposure timing so that exposure operations are appropriately performed.

In addition, in the embodiment, for example, a storage unit 42 made up of hard disks, an input unit 45 comprising a key board and a pointing-device such as a mouse, a display unit 44 such as a CRT display or liquid-crystal display, and a drive unit 46 which is an information recording medium such as CD-ROM, DVD-ROM, MO, or FD are externally connected to main controller 50. In the information recording medium (hereinafter described as CD-ROM for the sake of convenience) set in drive unit 46, a conversion program (a first program), a second program, a third program, and data associated with the second program are stored. In this case, the first program is a conversion program for converting positional deviations measured using a measurement reticle  $R_T$ , which will be described later, into coefficients of each term of the Zernike polynomial, the second program is a program for computing the adjustment amount of the image forming characteristic based on the obtained coefficients

of each term of the Zernike polynomial, and the third program is a program for converting the obtained coefficients of each term of the Zernike polynomial into various image forming characteristics (including index  
5 values of the image forming characteristics).

Next, the above database will be described. The database contains numerical data of parameters for calculating an image forming characteristic, in this case, a targeted drive amount (targeted adjustment amount) of  
10 movable lenses  $13_1$ ,  $13_2$ ,  $13_3$ , and  $13_4$  referred to earlier, so that the image forming characteristic is adjusted according to the input of measurement results of the wavefront aberration. The database consists of a group of data on a variation amount of the image forming  
15 characteristic, which are obtained as simulation results, arranged in a predetermined order. The simulation performed uses a model substantially equivalent to projection optical system PL, and obtains data on how the image forming characteristic corresponding to a plurality  
20 of measurement points within the field of projection optical system PL change when movable lenses  $13_1$ ,  $13_2$ ,  $13_3$ , and  $13_4$  are driven by a unit adjustment quantity in directions of each degree of freedom (movable directions), or more specifically, obtains wavefront data, that is,  
25 data on how the coefficients of the second term through the 37<sup>th</sup> term of the Zernike polynomial change.

Next, the procedure of generating the database will be briefly described. First of all, design values of

projection optical system PL (numerical aperture N.A., coherence factor  $\sigma$ , wavelength, data of each lenses or the like) are input into a computer used for the simulation where specific optical software is installed.

5 Then, data on a first measurement point (in this case, a position corresponding to an arbitrary pinhole position of measurement reticle  $R_T$ , which will be described later) within the field of projection optical system PL are input in the simulation computer.

10 Next, data on unit quantity of the movable lenses in directions of each degree of freedom (movable directions) is input. However, before the input, conditions that are a prerequisite for the input will be described below.

15 More particularly, for movable lenses  $13_1$ ,  $13_2$ , and  $13_4$ , directions in which each of the movable lenses 13 are rotated around the X-axis and Y-axis are to be the positive directions of a Y-direction tilt and an X-direction tilt, as is shown by the arrows in Figs. 2A and 2B, and the unit tilt amount is to be 0.1 degrees. In  
20 addition, when each of the movable lenses 13 are shifted in the +Z direction as is shown in Fig. 2C, the +Z direction is to be the positive direction of the Z-direction shift, and the unit shift amount is to be 100  
25  $\mu\text{m}$ .

In addition, for movable lens  $13_3$ , when it is shifted in the +X direction as is shown in Figs. 2D and 2E, this direction is to be the + (positive) direction of

the X-direction shift, whereas when it is shifted in the +Y direction, this direction is to be the + (positive) direction of the Y-direction shift, and the unit shift amount is to be 100  $\mu\text{m}$

5           And, for example, when instructions to tilt movable lens 13<sub>1</sub> in the positive direction of the Y-direction tilt by the unit quantity is input, the simulation computer calculates the amount of deviation of a first wavefront from an ideal wavefront at a first measurement point set  
10 in advance within the field of projection optical system PL; for example, variation of the coefficients of each term (e.g. the second term through the 37<sup>th</sup> term) of the Zernike polynomial. The data of the variation is shown on the display, while also being stored in memory as  
15 parameter PARA1P1.

          Next, when instructions to tilt movable lens 13<sub>1</sub> in the positive direction of the X-direction tilt by the unit quantity is input, the simulation computer calculates the amount of deviation of a second wavefront  
20 from the ideal wavefront at the first measurement point, for example, variation of the coefficients of the above terms of the Zernike polynomial, and data on the variation are shown on the display, while also being stored in memory as parameter PARA2P1.

25           Next, when instructions to shift movable lens 13<sub>1</sub> in the positive direction of the Z-direction shift by the unit quantity is input, the simulation computer calculates the deviation of a third wavefront from the

ideal wavefront at the first measurement point, for example, variation of the coefficients of the above terms of the Zernike polynomial, and data on the variation are shown on the display, while also being stored in memory  
5 as parameter PARA3P1.

Then, input for each measurement point from the second measurement point to the  $n^{\text{th}}$  measurement point is performed in the same procedure as is described above, and each time instructions are input for the Y-direction  
10 tilt, the X-direction tilt, and the Z-direction shift of movable lens 13<sub>1</sub>, the simulation computer calculates the data of the first, second, and third wavefront in each measurement point, such as variation of the coefficients of the above terms of the Zernike polynomial, and data on  
15 each variation are shown on the display, while also being stored in memory as parameters PARA1P2, PARA2P2, PARA3P2, through PARA1Pn, PARA2Pn, PARA3Pn.

Also for the other movable lenses 13<sub>2</sub>, 13<sub>3</sub>, and 13<sub>4</sub>, in the same procedure as is described above, input for  
20 each measurement point is performed and instructions are input for driving movable lenses 13<sub>2</sub>, 13<sub>3</sub>, and 13<sub>4</sub> in the + direction only by the unit quantity in directions of each degree of freedom. And in response, the simulation computer calculates the wavefront data for each of the  
25 first through  $n^{\text{th}}$  measurement points when movable lenses 13<sub>2</sub>, 13<sub>3</sub>, and 13<sub>4</sub> are driven only by the unit quantity in directions of each degree of freedom, such as variation of the coefficients of the above terms of the Zernike

polynomial, and parameter (PARA4P1, PARA5P1, PARA6P1, ...  
 PARAMp1), parameter (PARA4P2, PARA5P2, PARA6P2, ...  
 PARAMp2), ..... up to parameter (PARA4Pn, PARA5Pn, PARA6Pn,  
 ... PARAMpn) are stored in memory. Then, data of a matrix O  
 5 given the following expression (1) is stored in the CD-  
 ROM as the above database. The data of matrix O is  
 composed of column matrices (vectors) PARA1P1 up to  
 PARAMpn, which consists of variations of the coefficients  
 of the above terms of the Zernike polynomial. In the  
 10 embodiment, because there are three movable lenses that  
 can be moved in directions of three degrees of freedom  
 and one movable lens that can be moved in directions of  
 two degrees of freedom,  $m = 3 \times 3 + 2 \times 1 = 11$ .

$$O = \begin{bmatrix} \text{PARA1P1} & \text{PARA2P1} & \Lambda & \Lambda & \text{PARAMp1} \\ \text{PARA1P2} & \text{PARA2P2} & \Lambda & \Lambda & \text{PARAMp2} \\ M & M & & & M \\ M & M & & & M \\ \text{PARA1Pn} & \text{PARA2Pn} & \Lambda & \Lambda & \text{PARAMpn} \end{bmatrix} \Lambda (1)$$

Next, the method of measuring and displaying  
 15 (simulating) the image forming characteristic will be  
 described so that an operator of exposure apparatus 10  
 can easily understand the state of aberrations of  
 projection optical system PL. The simulation in the  
 embodiment requires the actual measurement data of the  
 20 wavefront aberration of projection optical system PL, and  
 when the wavefront aberration is measured, a measurement  
 reticle  $R_T$  (hereinafter, also called "reticle  $R_T$ " as  
 appropriate) is used. Therefore, first of all,

measurement reticle  $R_T$  will be described.

Fig. 3 shows a schematic oblique view of measurement reticle  $R_T$ . In addition, Fig. 4 shows a schematic view of reticle  $R_T$  mounted on the reticle stage RST sectioned along a X-Z plane in the vicinity of optical axis AX, along with a diagram of projection optical system PL. Also, Fig. 5 shows a schematic view of reticle  $R_T$  mounted on the reticle stage RST sectioned along a X-Z plane in the vicinity of the -Y side end, along with a diagram of projection optical system PL.

As is obvious in Fig. 3, the shape of measurement reticle  $R_T$  is almost the same as an ordinary reticle with a pellicle. Measurement reticle  $R_T$  comprises a glass substrate 60, a lens-attached member 62 which has a rectangular plate-like shape and is fixed on the upper surface of glass substrate 60 in Fig. 3 at the center in the X-axis direction, a spacer member 64 made up of a frame member that has the same shape as an ordinary pellicle frame, being fixed on the bottom surface of the glass substrate 60 in Fig. 3, and an aperture plate 66 fixed on the bottom surface of spacer member 64.

In the lens-attached member 62,  $n$  circular apertures  $63_{i,j}$  ( $i=1$  through  $p$ ,  $j=1$  through  $q$ ,  $p \times q = n$ ) are formed in a matrix arrangement, covering the entire surface excluding both ends in the Y-direction. Inside the circular apertures  $63_{i,j}$ , condenser lenses  $65_{i,j}$  are provided that are each made of a convex lens having an optical axis in the Z-axis direction (refer to Fig. 4).

In addition, inside the space enclosed by glass substrate 60, spacer member 64, and aperture plate 66, reinforcing members 69 are provided as is shown in Fig. 4, spaced a predetermined distance apart.

5 Furthermore, on the lower surface of the glass substrate 60, facing condenser lenses  $65_{i,j}$ , measurement patterns  $67_{i,j}$  are formed as is shown in Fig. 4. In addition, in aperture plate 66, pinhole-shaped openings  $70_{i,j}$  are formed, each facing measurement patterns  $67_{i,j}$  as  
10 is shown in Fig. 4. The diameter of pinhole-shaped openings  $70_{i,j}$  is, for example, around 100 to 150  $\mu\text{m}$ .

Referring back to Fig. 3, in lens-attached member 62, openings  $72_1$ ,  $72_2$  are formed, respectively, in the center of strip shaped areas on both ends of lens-  
15 attached member 62 in the Y-axis direction. As is shown in Fig. 5, on the bottom surface (pattern surface) of glass substrate 60, a reference pattern  $74_1$  is formed opposing opening  $72_1$ . Also, although it is omitted in the drawing, a reference pattern  $74_2$  identical to reference  
20 pattern  $74_1$  is formed opposing the other opening  $72_2$  on the bottom surface (pattern surface) of glass substrate 60.

Moreover, as is shown in Fig. 3, on the X-axis that passes through the center of reticle R, a pair of reticle  
25 alignment marks RM1 and RM2 is formed symmetrically with respect to the center of the reticle, on the glass substrate 60 outside lens-attached member 62.

In the embodiment, as measurement patterns  $67_{i,j}$ , a

mesh (street-line shaped) pattern is used, as is shown in Fig. 6A. And, corresponding to the pattern, reference patterns 74<sub>1</sub> and 74<sub>2</sub> are a two-dimensional grid pattern that has square patterns arranged at the same pitch as measurement pattern 67<sub>i,j</sub> in Fig. 6B. As reference patterns 74<sub>1</sub> and 74<sub>2</sub>, the pattern shown in Fig. 6A can be used, and the pattern shown in Fig. 6B can be used as the measurement pattern. Furthermore, patterns that have other shapes may be used as the measurement pattern 67<sub>i,j</sub>, and in such a case, as the corresponding reference pattern, a pattern having a predetermined positional relation with the measurement pattern has to be used. That is, the reference pattern only needs to be a pattern, which is a reference for positional deviation of the measurement pattern, regardless of the shape. However, in order to measure the image forming characteristic of projection optical system PL, a pattern that covers the entire image field of projection optical system PL or the entire exposure area is preferred.

Next, the method of measuring and displaying (simulating) image forming characteristics will be described so that an operator of exposure apparatus 10 can easily understand the state of aberrations of projection optical system PL, following a flow chart in Fig. 7, which schematically shows the control algorithm of the CPU in main controller 50, and referring to other figures when necessary.

As a premise, the CD-ROM containing the first

through third programs and the database is set in drive unit 46, and from the CD-ROM, the first through third programs are to be installed in storage unit 42.

The process in the flow chart starts when the  
5 operator inputs the instructions to start the simulation via the input unit 45.

First, in step 101, the third program is loaded into the main memory. Then, steps 102 through 122 are executed, according to the third program.

10 First, in step 102, when the screen for setting conditions is displayed on the display unit 44, the process then goes to step 104 and waits for the conditions to be input. The operator then inputs information on a pattern subject to simulation (for  
15 example, in the case of a line-and-space pattern, the pitch, the line width, and duty ratio or the like) and information on a targeted image forming characteristic (including an index value of the image forming  
characteristic; the targeted image forming characteristic  
20 also hereinafter referred to as "targeted aberration" as appropriate) such as information on a line width abnormal value, via input unit 45. Then, when instructions are given that the input is complete, the process proceeds to step 106, where conditions are set for creating a Zernike  
25 variation table of the targeted aberration input in step 104, and the step then proceeds to step 108. The information on targeted aberration entered in step 104 is not limited to one kind. That is, various kinds of image

forming characteristics of projection optical system PL can be designated as the targeted aberration at the same time.

In step 108, when the screen for inputting  
5 information on the projection optical system is displayed on display unit 44, the process then goes to step 110 and waits for the information to be input. And after the operator inputs information on projection optical system PL, specifically information on the numerical aperture  
10 (N.A.), illumination conditions (such as setting of the illumination system aperture stop or coherence factor  $\sigma$ ), wavelength or the like via input unit 45, the process goes to step 112, where the input information is stored in the RAM and when the screen for inputting information  
15 on the aberration is displayed on display unit 44, the procedure moves on to step 114 and waits for the information to be input.

The operator then individually inputs information on a given aberration, or to be more specific,  
20 individually inputs the same value, such as  $0.05\lambda$ , into the input screen for aberration information for the coefficient values of each term of the Zernike polynomial when they are, for example, coefficient  $Z_2$  of the second term up to coefficient  $Z_{37}$  of the 37<sup>th</sup> term.

25 When input of the above aberration is complete, the process proceeds to step 116, where a graph is made (for example, a Zernike variation table on a line width abnormal value), based on the information of aberration

that has been input. For example, the vertical axis of the map can be a targeted aberration corresponding to the  $0.05\lambda$  or its index value (such as the line width abnormal value, which is the index value of coma), and the  
5 horizontal axis can be the coefficients of each term of the Zernike polynomial. The process then proceeds to step 118, where the screen for confirming the completion of the above graph is displayed on display unit 44.

In the next step, step 120, operation is suspended  
10 until the operator inputs the confirmation. When the operator inputs the confirmation via input unit 45 such as the mouse, the process then proceeds to step 122, where the variation table made in the above step 116 is stored in the RAM, and the decision is made whether or  
15 not the Zernike variation table is made for all the targeted aberrations input in step 104. When the decision in step 122 is negative, the process then returns to step 116 to make a Zernike variation table and for the next targeted aberration. In the embodiment, one variation  
20 table is made for one targeted aberration without changing any conditions such as the numerical aperture of projection optical system PL or the illumination conditions, however, for example, a plurality of variation tables may be made for one targeted aberration  
25 changing at least either the numerical aperture of projection optical system PL or the illumination conditions. In addition, the pattern subject to simulation may be in plurals, and the variation table for

the target aberration may be made per pattern.

When the Zernike variation table has been made for all the targeted aberrations and the confirmation has been input in step 120, the decision turns positive in  
5 step 122 and the process proceeds to the next step, step 124.

In step 124, the decision is made whether a flag F is "1" or not. Flag F indicates whether data of positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ), which will be described  
10 later, has been input. In this case, because data of the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) has not been input, the decision is negative, which takes the process to a measuring subroutine 126, where wavefront aberration is measured using measurement reticle  $R_T$  at a plurality of  
15 measurement points (hereinafter,  $n$ ) in the field of projection optical system PL in the following manner.

That is, in subroutine 126, first of all, in step 202 in Fig. 8, measurement reticle  $R_T$  is loaded onto reticle stage RST via a reticle loader (not shown).

20 In the next step, step 204, wafer stage WST is moved via the wafer-stage driving portion 56 while the output of laser interferometer 54W is being monitored, and a pair of reticle alignment reference marks formed on reference mark plate FM is positioned at a predetermined  
25 reference position. The reference position, in this case, is set so that, for example, the center of the pair of reference marks coincides with the origin of the stage coordinate system set by laser interferometer 54W.

In step 206, the pair of reticle alignment marks RM1 and RM2 formed on measurement reticle  $R_T$  and the corresponding reticle alignment reference marks are observed with the reticle alignment microscopes at the same time, and reticle stage RST is finely driven in the XY two-dimensional plane via a driving system (not shown) so as to make positional deviations minimal between projected images of reticle alignment marks RM1 and RM2 on reference plate FM and the reticle alignment reference marks. With this operation, reticle alignment is completed, and the center of the reticle substantially coincides with the optical axis of projection optical system PL.

In the next step, step 208, wafer W is loaded onto Z-tilt stage 58 via a wafer loader (not shown). The surface of wafer W is coated with a resist (photosensitive material).

In the next step, step 210, the aperture size of reticle blind 30 is set so that a rectangular shaped illumination area is formed to cover the entire surface of measurement reticle  $R_T$  including all the condenser lenses  $65_{i,j}$ , with the exception of openings  $72_1$ ,  $72_2$ , and the length of the illumination area in the X-axis direction length is within the maximum width of the X-axis direction of lens-attached member 62. In addition, at the same time, illumination system aperture stop plate 24 is rotated via driving unit 40 to set a predetermined aperture stop, such as the small  $\sigma$  stop, to the optical

path of illumination light EL. With this operation, the preparatory operations for exposure are completed.

In the next step, step 212, control information TS is given to light source 16 so that laser beam LB is generated, and exposure is performed by irradiating reticle  $R_T$  with illumination light EL. With this operation, measurement patterns  $67_{i,j}$  are each simultaneously transferred via pinhole-like openings  $70_{i,j}$  and projection optical system PL, as is shown in Fig. 4. As a result, reduced images  $67'_{i,j}$  (latent images) of measurement patterns  $67_{i,j}$  as is shown in Fig. 9A are formed two-dimensionally on the resist layer of wafer W, spaced apart at a predetermined distance.

In the next step, step 214, the reference pattern is sequentially overlaid and transferred onto the images of the measurement patterns already formed on wafer W by a step-and-repeat method. Following are the details of the sequence, from a. through g.

a. First, reticle stage RST is driven in the Y-axis direction by a predetermined distance via a driving system (not shown), so that the center of reference pattern  $74_1$  coincides with optical axis AX, based on the measurement values of a reticle laser interferometer (not shown) and the designed positional relation between the center of the reticle and reference pattern  $74_1$ .

b. Next, when the above movement is completed, the aperture of reticle blind 30 is set via a driving system (not shown) so that the illumination area of illumination

light EL is set limited to a rectangular area having a predetermined size, on the lens-holding member 62 including opening 72<sub>1</sub> (but does not include any condenser lenses).

5           c. Next, wafer stage WST is moved so that the center of the area where latent image 67'<sub>1,1</sub> of the first measurement pattern 67<sub>1,1</sub> is formed on wafer W is positioned substantially on optical axis AX, while the measurement values of laser interferometer 54W are  
10       monitored.

          d. Then, main controller 50 gives control information TS to light source 16 for generating laser beam LB, and performs exposure by irradiating illumination light EL on reticle R<sub>T</sub>. With this operation,  
15       reference pattern 74<sub>1</sub> is overlaid and transferred onto the area where the latent image of measurement pattern 67<sub>1,1</sub> is already formed (referred to as area S<sub>1,1</sub>) on the resist layer of wafer W. As a result, the latent image 67'<sub>1,1</sub> of the first measurement pattern 67<sub>1,1</sub> and the latent image  
20       74'<sub>1</sub> of the reference pattern 74<sub>1</sub> are formed on area S<sub>1,1</sub> in a positional relation shown in Fig. 9B.

          e. Next, a designed arrangement pitch p of measurement patterns 67<sub>i,j</sub> on wafer W is calculated, based on an arrangement pitch of measurement patterns 67<sub>i,j</sub> on  
25       reticle R<sub>T</sub> and the projection magnification of projection optical system PL. Then, wafer stage WST is moved in the X-axis direction by pitch p so that the center of an area S<sub>1,2</sub> where the latent image of the second measurement

pattern 67<sub>1,2</sub> is formed substantially coincides with optical axis AX.

f. Then, control information TS is given to light source 16 so that laser beam LB is emitted and exposure  
5 is performed by irradiating illumination light EL on reticle R<sub>T</sub>. With this operation, reference pattern 74<sub>1</sub> is overlaid and transferred onto area S<sub>1,2</sub> on wafer W.

g. Hereinafter, stepping operations between areas and exposure operation are repeated in the manner  
10 described above, and latent images of the measurement patterns and the reference pattern are formed in areas S<sub>i,j</sub> on wafer W, as shown is in Fig. 9B.

When exposure is completed in this manner, the process goes to step 216, where wafer W is unloaded from  
15 Z-tilt stage 58 via the wafer loader (not shown) and is transferred to a coater-developer (not shown; hereinafter, "C/D" for short), which is connected in line with chamber 11. The process then proceeds to step 218, where data of positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ), which will be described  
20 later, will be input.

Then, in the C/D, wafer W is developed, and the resist images of the measurement pattern and the reference pattern are formed on wafer W in the same arrangement as shown in Fig. 9B, in each of the areas S<sub>i,j</sub>  
25 arranged in a matrix.

Then, wafer W that has been developed is removed from the C/D, and overlay errors are measured in each of the areas S<sub>i,j</sub> by an external overlay measuring unit

(registration measuring unit). And, based on the results, positional errors (positional deviations) of the resist images of measurement patterns  $67_{i,j}$  with respect to the corresponding images of reference pattern  $74_1$  are  
5 calculated.

Various methods of calculating the positional deviations can be considered, however, from the viewpoint of improving accuracy, performing statistical computation based on measured raw data is preferred.

10 In this manner, the XY two-dimensional positional deviations  $(\Delta\xi, \Delta\eta)$  of the measurement patterns from the respective reference patterns are obtained for the areas  $S_{i,j}$ . Then the data on positional deviations  $(\Delta\xi, \Delta\eta)$  for the areas  $S_{i,j}$  is input by an operator via input unit 45.  
15 And, when the decision in step 218 is positive, the process then returns to step 128 in the main routine of Fig. 7.

Incidentally, data on positional deviations  $(\Delta\xi, \Delta\eta)$  in the areas  $S_{i,j}$  can be input online from the external  
20 overlay measuring. And, also in this case, the process returns to step 128 in the main routine responding to the input.

In step 128 in the main routine, the first program is loaded into the main memory, and then the process goes  
25 to step 130, where wavefronts (wavefront aberrations) corresponding to each of the areas  $S_{i,j}$ , or in other words, the first measurement point through the  $n^{\text{th}}$  measurement point within the field of projection optical system PL,

which in this case are the coefficients of each of the terms in the Zernike polynomial such as the coefficient  $Z_2$  of the second term through the coefficient  $Z_{37}$  of the 37<sup>th</sup> term, are calculated according to the first program, based on the principle described below. When the main memory has enough empty area, the third program, which is loaded in advance, can be stored in the main memory, however, in this case the main memory does not have enough empty area, therefore, the third program is temporarily unloaded from the main memory to its original area in storage unit 42, and then the first program is loaded in the main memory.

In the embodiment, the wavefront of projection optical system PL is obtained by calculation according to the first program, based on the above positional deviations  $(\Delta\xi, \Delta\eta)$ . Before describing this process, as a premise, the physical relation between the positional deviations  $(\Delta\xi, \Delta\eta)$  and the wavefront will be briefly described, referring to Figs. 4 and 5.

As is representatively shown by a measurement pattern  $67_{k,1}$  in Fig. 4, of the diffraction light generated from measurement pattern  $67_{i,j}$ , the light having passed through pinhole-shaped opening  $70_{i,j}$  passes through the pupil plane of projection optical system PL at different positions, depending on where in measurement pattern  $67_{k,1}$  the light comes from. That is, the wavefront at each position on the pupil plane corresponds to the optical wavefront via position, in the corresponding

positions in measurement pattern  $67_{k,1}$ . And, when there is no aberration at all in projection optical system PL, such wavefront on the pupil plane of projection optical system PL is supposed to be an ideal wavefront (in this case, a flat plane) as in shown by a reference  $F_1$ . However, because there are no such projection optical systems that are free of aberration, the wavefront on the pupil plane becomes a curved surface such as wavefront  $F_2$ , which is indicated by a dotted curve. Therefore, the image of measurement pattern  $67_{i,j}$  is formed at a deviated position on wafer W, according to the angle that the curved surface  $F_2$  makes with respect to the ideal wavefront.

Meanwhile, as shown in Fig. 5, light diffracted by the reference pattern  $74_1$  (or  $74_2$ ) enters projection optical system PL directly, without being restricted by the pinhole-shaped aperture and is imaged on wafer W via projection optical system PL. Moreover, because exposure of the reference pattern  $74_1$  is performed in a state where the center of reference pattern  $74_1$  is positioned on the optical axis of projection optical system PL, the imaging beam generated from reference pattern  $74_1$  is substantially free from aberration caused by projection optical system PL, so that the image is formed without positional deviation in an extremely small area that includes the optical axis.

Therefore, the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) directly reflect the gradients of the wavefront to an

ideal wavefront, and based on such positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) the wavefront can be reproduced. As is obvious from the above physical relation between the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) and the wavefront, the principle of this embodiment for calculating the wavefront is the known Shack-Hartmann wavefront calculation principle.

Next, the method of calculating the wavefront based on the above positional deviations will be described briefly.

As is described above, positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) correspond to values of the gradient of the wavefront, and by integrating the positional deviations the shape of the wavefront (or to be more precise, deviations from the reference plane (the ideal plane)) is obtained. When the wavefront (deviations from the reference plane) is expressed as  $W(XY)$  and the proportional coefficient is expressed as  $k$ , then the relation in the following equations (2) and (3) exist.

$$\Delta\xi = k \frac{\partial W}{\partial x} \quad (2)$$

$$\Delta\eta = k \frac{\partial W}{\partial y} \quad (3)$$

Because it is not easy to integrate the gradient of the wavefront given only as positional deviations, the surface shape is expanded in series so that it fits the wavefront. In this case, an orthogonal system is chosen for the series. The Zernike polynomial is a series suitable to expand a surface symmetrical with respect to an axis in, whose component in the

circumferential direction is a trigonometric series. That is, when wavefront  $W$  is expressed using a polar coordinate system  $(\rho, \theta)$ , the Zernike polynomial is expressed as  $R_n^m(\rho)$  and is expanded as the equation (4):

$$W(\rho, \theta) = \sum_n A_n^0 R_n^0(\rho) + \sum_n \sum_m (A_n^m \cos m\theta + B_n^m \sin m\theta) R_n^m(\rho) \quad (4)$$

5           Because the Zernike radial polynomials  $R_n^m(\rho)$  are known, the description thereof is omitted. Because the terms are orthogonal, coefficients  $A_n^m$ ,  $B_n^m$  of the terms can be determined independently. Using only finite terms provides a sort of filtering.

10           Because the differentials are detected as the above positional deviations in actual, the fitting needs to be performed on the differential coefficients. In the polar coordinate system  $(x=\rho\cos\theta, y=\rho\sin\theta)$ , the partial differentials are represented by the equations (5), (6):

$$\frac{\partial W}{\partial x} = \frac{\partial W}{\partial \rho} \cos\theta - \frac{1}{\rho} \frac{\partial W}{\partial \theta} \sin\theta \quad (5)$$

$$\frac{\partial W}{\partial y} = \frac{\partial W}{\partial \rho} \sin\theta + \frac{1}{\rho} \frac{\partial W}{\partial \theta} \cos\theta \quad (6)$$

15           Because the differentials of Zernike polynomials are not orthogonal, the fitting needs to be performed in the least-squares method. Because the information (amount of positional deviation) is given in the X and Y directions for each measurement pattern, when the number of measurement patterns (for example,  $n$ = around 81 to  
20           400) is expressed as  $n$ , then the number of observation equations derived from the above equations (2) through

(6) is  $2n$  (= around 162 to 800).

Each term of the Zernike polynomial corresponds to an optical aberration. Furthermore, lower-order terms substantially correspond to Seidel's aberrations.

5 Therefore, by using the Zernike polynomial, the wavefront aberration of projection optical system PL can be obtained.

Incidentally, an invention related to a technology in calculating wavefront aberration is disclosed in the  
10 U.S. Patent No. 5,978,085. In this disclosure, a mask that has the same structure as the measurement reticle  $R_T$  is used, and a plurality of measurement patterns formed on the mask are sequentially exposed on a substrate via separately provided pinholes and a projection optical  
15 system, while a reference pattern on the mask is exposed on the substrate via the projection optical system without passing through condenser lens and pinholes. Then, positional deviations of the resist images of the plurality of measurement patterns from the respective  
20 resist images of the reference pattern are measured, and by predetermined computation, the wavefront aberration is calculated.

The computation procedure of the first program is determined according to the above principle, and by  
25 executing the first program the wavefront (wave-front aberration) for the first up to the  $n^{\text{th}}$  measurement point within the field of projection optical system PL, or in this case, the coefficients of terms of the Zernike

polynomial, such as the coefficient  $Z_2$  of the second term up to the coefficient  $Z_{37}$  of the 37<sup>th</sup> term, can be obtained.

After the data of the wavefront (the coefficients of terms of the Zernike polynomial, such as the  
 5 coefficient  $Z_2$  of the second term through the coefficient  $Z_{37}$  of the 37<sup>th</sup> term) is obtained, the process proceeds to step 132, which sets the flag F to one and stores the data of the wavefront in a temporary storage area in the RAM.

10 In step 134, the third program is reloaded into the main memory. In this case, as a matter of course, the third program is loaded after the first program is unloaded into the original area in storage unit 42.

In the next step, step 136, according to the third  
 15 program, one of the targeted aberrations input in step 104 is calculated for each measurement point by the following equation (7), using the Zernike variation table created earlier.

$$20 \quad A = K \times \{Z_2 \times (\text{the table's value}) + Z_3 \times (\text{the table's value}) + \dots + Z_{37} \times (\text{the table's value})\}. \quad \dots(7)$$

A, in this case, is a targeted aberration in the projection optical system PL such as astigmatism or field  
 25 curvature, or an index value of the targeted aberration such as a line-width abnormal value, which is an index value of coma.

K is a proportional constant which is set according

to the sensitivity of the resist and so forth.

In the next step 138, the targeted aberration or its index value calculated for each measurement point in the manner above is shown on display unit 44. And, by  
5 this display, the operator can easily recognize the aberration of the projection optical system PL in question.

In the next step, step 140, the decision is made whether or not all the targeted aberrations (aberrations  
10 (image forming characteristics) for which conditions have been set) have been calculated. If the decision is negative, the process returns to step 136, and the next targeted aberration is calculated and displayed.

When all the targeted aberrations have been  
15 calculated in the manner above, the process proceeds to step 142 where a screen for verifying whether the simulation is to continue is displayed on display unit 44, and then the process proceeds to step 144 and stays there until a predetermined time has passed.

20 When the predetermined time has passed, the step moves onto step 146, where decision is made on whether or not instructions to continue the simulation has been input. When the simulation is to be continued, instructions for continuance should be given during the  
25 predetermined time, therefore, if the answer in step 146 is negative, the process of this routine ends based on the decision that the simulation does not have to continue.

Meanwhile, when instructions to continue the simulation have been input during the predetermined time, the process returns to step 102, and hereinafter repeatedly performs the process and decision-making, according to the next conditions specified in the simulation. However, in this case, because the flag F is set, the decision in step 124 is positive so the process goes from step 124 to step 136.

That is, when the wavefront aberration of projection optical system PL is measured, the simulation is continued without re-measuring the wave-front aberration.

As is described above, in the embodiment, the operator only has to sequentially input necessary items via input unit 45 according to the screen, as well as input instructions to measure the wavefront aberration, or in addition, also input data of the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) in the each of the areas  $S_{i,j}$  measured by the overlay measuring unit. And, with this operation, because the targeted aberration specific to the measurement pattern of projection optical system PL (including lower-order and higher-order components of coma, astigmatism, and spherical aberration) is automatically and accurately calculated and displayed on display unit 44, the aberration can be easily and accurately recognized. Furthermore, even when the targeted aberration are in plurals, the aberration can be accurately recognized, by measuring the wavefront

aberration of projection optical system PL only once. In this case, while there are various forms for displaying the targeted aberration, the form is preferred where the results are expressed numerically in a way that is easy  
5 for anyone to understand. In such a case, analysis of the coefficients of terms of the Zernike polynomial is not required.

Moreover, as is obvious from the flow chart in Fig. 7, the exposure apparatus in the embodiment can easily  
10 set the optimum exposure condition corresponding to the subject patterns. That is, the optimum exposure condition can be easily set when repeating the steps 102 and onward, by inputting the same subject pattern and the same targeted aberration (which may be a plurality of types)  
15 to the condition setting screen in step 102, and by sequentially inputting different illumination conditions, numerical apertures, wavelengths, and the like to the input screen in step 108 where information related to projection optical system PL is input. As a consequence,  
20 in step 138, the condition is defined in which the target aberration value shown in step 138 is minimal. Needless to say, the software can be modified so that main controller 50 automatically defines and sets the optimum exposure condition based on the definition. This is  
25 because, for example, the illumination condition can be changed respectively by selecting a different aperture stop of the illumination system aperture stop plate 24, the numerical aperture of the projection optical system

PL can be set freely within a certain range by adjusting aperture stop 15 in Fig. 1 of projection optical system PL, and the wavelength of the illumination light EL can be changed by giving such control information TS to light source 16.

Needless to say, information on the defined exposure condition may be used when the operator creates a process program file (data file for setting exposure conditions).

Next, the method of adjusting the image forming characteristic of projection optical system PL will be described which is performed by a service technician of the exposure apparatus maker or the like, in a semiconductor manufacturing factory.

As a premise, the CD-ROM containing the first through third programs and the database created in the manner above is set in drive unit 46, and the first through third programs are installed in storage unit 42, along with the database associated with the second program.

When instructions for measuring the wavefront aberration is input by the service technician or the like, main controller 50 (CPU) transfers the pattern of measurement reticle  $R_T$  onto wafer W for measuring the wavefront aberration at a plurality of (in this case, n) measurement points in the field of projection optical system PL in the same procedure as is previously described (refer to Fig. 8). Wafer W is then developed in

the C/D, and when wafer W has been developed, the resist images of the measurement pattern and the reference pattern are formed in each of the areas  $S_{i,j}$  arranged in a matrix on wafer W, in the same arrangement as is shown in Fig. 9B.

After that, wafer W that has been developed is removed from the C/D, and overlay errors are measured with an external overlay measuring unit (registration measuring unit) in the areas  $S_{i,j}$ . And, based on the results, position errors (positional deviations) of the resist images of measurement patterns 67<sub>i,j</sub> from the corresponding images of the reference pattern 74<sub>1</sub> are calculated.

Then, the data on the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) in the areas  $S_{i,j}$  is input into main controller 50 by the service technician or the like via input unit 45. Incidentally, the data on the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) in the areas  $S_{i,j}$  may be input into main controller 50 online from the external overlay measuring unit.

In any case, responding to the above input, the CPU of main controller 50 loads the first program in the main memory, and based on the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ), the wavefront (wavefront aberration) for the areas  $S_{i,j}$  corresponding to the first through  $n^{\text{th}}$  measurement point within the field of projection optical system PL, in this case, the coefficients for each of the terms in the Zernike polynomial, such as the coefficient  $Z_2$  of the second term up to the coefficient  $Z_{37}$  of the 37<sup>th</sup> term of

the Zernike polynomial, are computed according to the first program.

In the description below, data of the wavefront (wavefront aberration) for the first to the  $n^{\text{th}}$  measurement point within the field of projection optical system PL is expressed by a column matrix  $Q$ , as in equation (8):

$$Q = \begin{bmatrix} P_1 \\ P_2 \\ M \\ M \\ P_n \end{bmatrix} \quad \Lambda \quad (8)$$

In equation (8), the elements  $P_1$  to  $P_n$  of matrix  $Q$  are each a column matrix (vector) made up of the coefficients of the second to the 37<sup>th</sup> terms ( $Z_2$  to  $Z_{37}$ ) of the Zernike polynomial.

When matrix  $Q$  is calculated in the manner above, main controller 50 then stores the values in the temporary storing area in the RAM.

Next, the CPU in main controller 50 loads the second program into the main memory from storage unit 42, and computes the adjustment amount of the movable lenses 13<sub>1</sub> through 13<sub>4</sub> previously described in directions of each degree of freedom, according to the second program.

Between data  $Q$  of the wavefront (wavefront aberration) for the first to  $n^{\text{th}}$  measurement points, the matrix  $Q$  stored in the CD-ROM as the database, and an adjustment amounts vector  $P$  of the movable lenses 13<sub>1</sub>

through 13<sub>4</sub> in directions of each degree of freedom, a relation as in the following equation (9) exists:

$$Q = O \times P \quad (9)$$

In equation (9), P is a column matrix (vector) having m elements as in equation (10):

$$P = \begin{bmatrix} ADJ1 \\ ADJ2 \\ M \\ M \\ ADJm \end{bmatrix} \quad (10)$$

Therefore, from the above equation (9), by computing the following equation (11) using the least-squares method, each of the elements ADJ1 to ADJm of P, or in other words, adjustment amount (target adjustment amount) of movable lenses 13<sub>1</sub> through 13<sub>4</sub> in directions of each degree of freedom can be obtained.

$$P = (O^T \times O)^{-1} \times O^T \times Q. \quad (11)$$

In equation (11),  $O^T$  is the transposed matrix of matrix O and  $(O^T \times O)^{-1}$  is the inverse matrix of  $(O^T \times O)$ .

That is, the second program is a program for performing a least-squares method computation by the above equation (11) using the database. Therefore, the CPU calculates the adjustment amount ADJ1 to ADJm according to the second program while sequentially reading the database from the CD-ROM into the RAM, and then shows the adjustment amounts on the screen of display unit 44 as well as stores the values in storage

unit 42.

Next, main controller 50 gives instruction values to image forming characteristics correction controller 48 according to the adjustment amounts ADJ1 through ADJm stored in storage unit 42 on the drive amounts of the movable lenses 13<sub>1</sub> through 13<sub>4</sub> in directions of each degree of freedom. With this operation, image forming characteristics correction controller 48 controls the applied voltage to each of the driving devices that drives movable lenses 13<sub>1</sub> through 13<sub>4</sub> in directions of each degree of freedom, and at least one of a position and posture of movable lenses 13<sub>1</sub> through 13<sub>4</sub> is adjusted substantially at the same time, correcting the image forming characteristic of projection optical system PL such as distortion, field curvature, coma, spherical aberration, and astigmatism. As for coma, spherical aberration and astigmatism, not only the lower orders but also the higher orders of the aberration can be corrected.

As is described above, in the embodiment, when adjusting the image forming characteristic of projection optical system PL, the service technician or the like only has to input measurement instructions of the wavefront aberration via input unit 45, or in addition, input the positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) for the areas  $S_{i,j}$  measured by the overlay measuring unit. With this operation, the image forming characteristic of projection optical system PL is adjusted almost automatically, with high accuracy.

Instead of the above equation (11), the following equation, equation (12), which is a computation program for performing a least-squares computation, may be used as the second program.

$$5 \quad P = (O^T \times G \times O)^{-1} \times O^T \times G \times Q. \quad (12)$$

In equation (12), G is a diagonal matrix with n rows and n columns as in the following equation, equation (13):

$$G = \begin{bmatrix} A_{1,1} & & & & \\ & A_{2,2} & & & \\ & & \cdot & & \\ & & & \cdot & \\ 0 & & & & \cdot \\ & & & & & A_{n,n} \end{bmatrix} \quad \Lambda (13)$$

In addition, elements  $A_{i,i}$  ( $i=1$  through  $n$ ) of matrix  
 10 G each are a diagonal matrix with weight parameters  $\delta$  as the elements. In this case,  $A_{i,i}$  is a diagonal matrix with 36 rows and 36 columns expressed as in equation (14):

$$A_{i,i} = \begin{bmatrix} \delta_{1,1} & & & & \\ & \delta_{2,2} & & & \\ & & \cdot & & \\ & & & \cdot & \\ 0 & & & & \cdot \\ & & & & & \delta_{36,36} \end{bmatrix} \quad \Lambda (14)$$

Therefore, each of elements  $\delta_{j,j}$  ( $j=1$  through 36) of

diagonal matrix  $A_{i,i}$  represents the weight parameter corresponding to the coefficients  $Z_2$  through  $Z_{37}$  of the second term to the 37<sup>th</sup> term of the Zernike polynomial measured at each measurement point. So, for example, when  
5 low order distortion obtained from the measurement results of one or a plurality of measurement points is to be corrected in particular, the values of the weight parameters such as  $\delta_{1,1}$  and  $\delta_{2,2}$  at the corresponding measurement points only have to be made heavier than the  
10 rest of the weight parameters. In addition, for example, when spherical aberration (00 component) obtained from the measurement results of one or a plurality of measurement points is to be corrected in particular including the high order component, the mean of weight parameters  $\delta_{8,8}$ ,  
15  $\delta_{15,15}$ ,  $\delta_{24,24}$ ,  $\delta_{35,35}$ ,  $\delta_{36,36}$  at the corresponding measurement points only has to be made heavier than the mean of the remaining weight parameters.

In this case, another program that works with the second program is preferably provided, and the screens  
20 for specifying a measurement point and inputting the weight for each of the terms of the Zernike polynomial are to be sequentially displayed by the program. With such an arrangement, the service technician can easily set the weight parameters described above using input  
25 unit 45, by inputting the measurement point when the screen for specifying the measurement point is displayed and by inputting the weight of the term of the Zernike polynomial corresponding to the aberration to be

corrected in particular heavier than the other terms when the screen for inputting the weight is displayed. Especially, on the input screen for inputting the weight, a plurality of types of input referred to above is preferred, more specifically, other than being able to input the weight of each term, input of the weight divided into four groups such as 0 $\theta$ , 1 $\theta$ , 3 $\theta$ , and 4 $\theta$  is preferred. In the latter case, a desired set value can be input by each  $\theta$  group. 0 $\theta$  generically refers to coefficients of the terms of the Zernike polynomial (in this case, the first and fourth terms are excluded) that do not include sin or cos ( $Z_9$ ,  $Z_{16}$ ,  $Z_{25}$ ,  $Z_{36}$ , and  $Z_{37}$ ); 1 $\theta$  generically refers to coefficients of terms (in this case, the second and third terms are excluded) with sin $\theta$  or cos $\theta$  ( $Z_7$ ,  $Z_8$ ,  $Z_{14}$ ,  $Z_{15}$ ,  $Z_{23}$ ,  $Z_{24}$ ,  $Z_{34}$ , and  $Z_{35}$ ); 2 $\theta$  generically refers to coefficients of terms with sin2 $\theta$  or cos3 $\theta$  ( $Z_5$ ,  $Z_6$ ,  $Z_{12}$ ,  $Z_{13}$ ,  $Z_{21}$ ,  $Z_{22}$ ,  $Z_{32}$ , and  $Z_{33}$ ); 3 $\theta$  generically refers to coefficients of terms with sin3 $\theta$  or cos3 $\theta$  ( $Z_{19}$ ,  $Z_{20}$ ,  $Z_{30}$ , and  $Z_{31}$ ), and 4 $\theta$  generically refers to coefficients of terms with sin4 $\theta$  or cos4 $\theta$  ( $Z_{28}$  and  $Z_{29}$ ).

In the embodiment, as is previously described, main controller 50 executes the third program and the first program so that the image forming characteristic (aberration) of projection optical system PL to be known can be recognized almost automatically, when the operator or the like sequentially inputs necessary issues via input unit 45 according to the display on the screen and inputs instructions to measure the wavefront aberration,

or in addition, inputs the data on positional deviations ( $\Delta\xi$ ,  $\Delta\eta$ ) for the areas  $S_{i,j}$  measured by the overlay measuring unit. Therefore, after the image forming characteristic of projection optical system PL is  
5 adjusted in the manner previously described by making use of such arrangement, the service technician or the like performs the simulation previously described so that the state of whether the image forming characteristic is adjusted as planned can be confirmed on the display  
10 screen. When the adjustment is not proceeding as planned, by inputting a plurality of image forming characteristics as information related to the targeted image forming characteristic, the image forming characteristic that is not adjusted as planned can be recognized, therefore,  
15 necessary countermeasures can be taken without further delay.

In this embodiment, other than the maintenance operation, the operator or the like may also give instructions to adjust the image forming characteristic  
20 of projection optical system PL even during normal operation. After the operator or the like gives the predetermined instructions described earlier (including input of condition setting and input of information related to the projection optical system), a process  
25 similar to the above simulation is performed in the same manner by the CPU of main controller 50 to create a similar Zernike variation chart. Then, when the wavefront aberration is measured and the positional deviation data

input, the CPU of main controller 50 sequentially calculates the targeted image forming characteristic in the manner described above. In this case, instead of displaying information related to the targeted image forming characteristic on display unit 44, or with the display, the CPU may calculate the drive amount of the movable lenses 13<sub>1</sub> to 13<sub>4</sub> in directions of each degree of freedom so that the targeted aberration is optimal (such as zero or minimal) according to, for example, the second program by the least squares method in the same manner as before. This can be achieved by a simple modification of the software.

Then, the CPU in main controller 50 provides the instruction values of the calculated drive amount to image forming characteristics correction controller 48. With this operation, image forming characteristics correction controller 48 controls the applied pressure to each of the driving devices that drives movable lenses 13<sub>1</sub> through 13<sub>4</sub> in directions of each degree of freedom, and at least one of a position and posture of movable lenses 13<sub>1</sub> through 13<sub>4</sub> is adjusted, correcting the image forming characteristic of projection optical system PL such as distortion, field curvature, coma, spherical aberration, and astigmatism. As for coma, spherical aberration and astigmatism, not only the lower orders but also the higher orders of the aberration can be corrected.

With exposure apparatus 10 in the embodiment, when semiconductor devices are manufactured, reticle R for

manufacturing the devices is loaded onto reticle stage  
RST as the reticle, and then preparatory operations such  
as the reticle alignment, the so-called baseline  
measurement, and the wafer alignment such as the EGA  
5 (Enhanced Global Alignment) are performed.

Details on the above preparatory operations such as  
the reticle alignment and the baseline measurement are  
disclosed in, for example, Japanese Patent Application  
Laid-open Application No.04-324923 and the corresponding  
10 U.S. Patent No. 5,243,195. Furthermore, details on EGA  
that follows are disclosed in, for example, Japanese  
Patent Application Laid-open No. 61-44429 and the  
corresponding U.S. Patent No. 4,780,617. As long as the  
national laws in designated states or elected states, to  
15 which this international application is applied, permit,  
the above disclosures are incorporated herein by  
reference.

When the preparatory operations are completed,  
exposure based on the step-and-repeat method is performed,  
20 similar to the measurement of the wavefront aberration.  
However, in this case, the stepping operation is  
performed based on the results of wafer alignment with  
the stepping in between shots serving as a unit.  
Incidentally, because the operation during exposure is  
25 not any different from an ordinary stepper, a detailed  
description is omitted.

Next, the method of making exposure apparatus 10  
will be described.

When making exposure apparatus 10, first of all, illumination optical system 12 comprising optical elements such as a plurality of lenses and mirrors, projection optical system PL, and the reticle stage system and the wafer stage system made up of many mechanical components, are each assembled as units, while adjustment such as optical adjustment, mechanical adjustment, and electric adjustment are performed on each of the units so that a desirable performance can be secured in each unit.

Next, illumination optical system 12 and projection optical system PL are incorporated into the exposure apparatus main body, as well as the reticle stage system and the wafer stage system, and then the wiring and piping are connected.

Then, optical adjustment is performed on illumination optical system 12 and projection optical system PL. This is because such optical systems, especially the image forming characteristic of projection optical system PL, slightly change after being incorporated into the exposure apparatus main body. In the embodiment, the first, second, and third programs and the database previously described can also be used in the optical adjustment of projection optical system PL which is performed after projection optical system PL is installed in the exposure apparatus main body.

As a first method of optically adjusting projection optical system PL, a worker performing the adjustment

operation measures the wavefront aberration of projection optical system PL using measurement reticle  $R_T$  described earlier in the manner already described. Then, by inputting the measurement results to main controller 50, main controller 50 then performs the processes according to the first and second program, so that the image forming characteristic of projection optical system PL is adjusted as accurately as possible.

Then, for the purpose of confirming the adjustment results, the wavefront aberration of projection optical system PL is re-measured using measurement reticle  $R_T$  described earlier in the manner and procedure previously described. Then, by inputting the measurement results of the wavefront aberration to main controller 50, main controller 50 then performs the processes according to the first and third program, and shows the astigmatism, field curvature, and/or a line-width abnormal value corresponding to coma of projection optical system PL after the adjustment on the screen. Aberrations that have not been corrected at this stage, mainly the high order aberrations, can be determined as aberrations that are difficult to adjust automatically, therefore, attachment of lenses or the like may be re-adjusted, if necessary.

As a second method of optically adjusting projection optical system PL, when a worker who performs adjustment in the manufacturing stage inputs instructions (including input of condition setting and input of information related to the projection optical system)

like the adjustment described earlier, the CPU in main controller 50 performs processes according to the third program and a similar Zernike variation chart is created. Then, the wavefront aberration of projection optical system PL is measured in the procedure previously described using measurement reticle  $R_T$  also described earlier. And, by inputting the measurement results of wavefront aberration to main controller 50, the CPU in main controller 50 performs processing according to the first and third programs previously described, and the targeted aberration is sequentially calculated. Then, instruction values on drive amount of movable lenses 13<sub>1</sub> to 13<sub>4</sub> in directions of each degree of freedom are given to image forming characteristics correction controller 48 that optimizes (zero or minimal) such targeted aberration. With this operation, image forming characteristics correction controller 48 adjusts the targeted image forming characteristic of projection optical system PL such as distortion, field curvature, coma, spherical aberration, and astigmatism, with as much precision as possible.

Then, for the purpose of confirming the adjustment results, the simulation referred to earlier is performed again and astigmatism, field curvature, a line-width abnormal value corresponding to coma, and the like of projection optical system PL that has been adjusted is displayed on screen. The aberrations that are not corrected at this point, mainly high order aberration,

can be judged as aberration difficult to adjust automatically, therefore, the lens assembly can be re-adjusted if necessary.

When a desired performance cannot be obtained even  
5 when the above re-adjustment has been performed, the lenses may have to be reprocessed or replaced. In order to simplify the reprocessing of the optical elements of projection optical system PL, the wavefront aberration referred to earlier may be measured using a wavefront  
10 measurement unit or the like specified for wavefront measurement before incorporating projection optical system PL into the exposure apparatus main body, and based on the measurement results, whether or not there are optical elements that require reprocessing and its  
15 position can be identified. Then, the reprocessing of the identified optical element and the readjustment of the other optical elements may be performed in parallel.

In addition, the optical elements of projection optical system PL may be replaced per unit, or when the  
20 projection optical system has a plurality of lens barrels, they may be replaced per barrel. Furthermore, when reprocessing the optical device, its surface may be processed non-spherically, if necessary. In addition, when adjusting projection optical system PL the position  
25 (including the spacing between other optical elements) or inclination may simply be changed, or especially when the optical element is a lens element, its eccentricity may be changed or it may be rotated around optical axis AX.

Then, overall adjustment (such as electrical adjustment and operation verification) is further performed. By such operations, exposure apparatus 10 in the embodiment that can transfer a pattern of reticle R on wafer W with good precision using projection optical system PL whose optical properties have been adjusted with high precision can be made. The exposure apparatus is preferably built in a clean room where the temperature and the degree of cleanliness are controlled.

10        As is obvious from the description so far, in the embodiment, main controller 50 constitutes a computing unit; the first computing unit and the second computing unit, and main controller 50 and image forming characteristics correction controller 48 constitutes an

15        image forming characteristics adjusting unit. Furthermore, the measurement reticle  $R_T$ , the external overlay measuring unit, and main controller 50 make up a measuring unit for measuring the wavefront aberration of projection optical system PL.

20        As has been described in detail, according to the exposure apparatus in the embodiment, when the measuring unit (such as  $R_T$  and 50) measures the wavefront aberration of projection optical system PL according to instructions from the operator, and main controller 50 calculates the

25        targeted image forming characteristic of projection optical system PL, based on the wavefront aberration of projection optical system PL which has been measured and the Zernike variation table of the targeted image forming

characteristic corresponding to the aberration information given when the subject pattern was exposed. By using the Zernike variation table in the manner described above, the targeted image forming  
5 characteristic can be calculated with only one measuring of the wavefront aberration. In this case, in the measuring, as for spherical aberration, astigmatism, and coma, not only the low order aberration, but also a total aberration including the high order aberration can be  
10 calculated.

In addition, since the targeted image forming characteristic is corrected as much as possible by image forming characteristics adjusting unit (48 and 50) based on the calculation results of the targeted aberration  
15 (image forming characteristic), the image forming characteristic of projection optical system PL is consequently adjusted according to the subject pattern.

In addition, according to exposure apparatus 10 in the embodiment, parameters that denote a relationship  
20 between the adjustment of specific optical elements for adjustment (movable lenses 13<sub>1</sub> through 13<sub>4</sub>) and the variation of the image forming characteristic of projection optical system PL are obtained in advance, and the parameters are stored as a database in storage unit  
25 42. And, based on instructions from the service technician or the like on adjustment, the wavefront aberration of projection optical system PL is actually measured, and then when the measurement data (actual

measurement data) is input via input unit 45, main computer 50 calculates the target adjustment amount of movable lenses 13<sub>1</sub> through 13<sub>4</sub>, using the actual measurement data of the wavefront aberration input via input unit 45 and a relation expression between the parameters and the movable lenses 13<sub>1</sub> through 13<sub>4</sub> (equation(11) or equation(12)). Because the above parameters are obtained in advance and stored in storage unit 42, when the wavefront aberration is actually measured, the target adjustment amount of the movable lenses 13<sub>1</sub> through 13<sub>4</sub> for correcting the wavefront aberration can be easily calculated by simply inputting the actual measurement values of the wavefront aberration via input unit 45. In this case, data that are difficult to obtain, such as the design data of the lenses are not necessary, as well as a difficult ray-tracing calculation.

Then, the target adjustment amount is given as instruction values to image forming characteristics correction controller 48 from main controller 50, and image forming characteristics correction controller 48 adjusts movable lenses 13<sub>1</sub> through 13<sub>4</sub> according to the target adjustment amount, performing a simple but highly precise adjustment on the image forming characteristic of projection optical system PL.

In addition, according to exposure apparatus 10 in the embodiment, when exposure is preformed, because the pattern of reticle R is transferred onto wafer W via projection optical system PL whose image forming

characteristic is adjusted in the manner described above according to the subject pattern or whose image forming characteristic is adjusted with high precision based on the measurement results of wavefront aberration, fine  
5 patterns can transferred onto wafer W with good overlay accuracy.

In the above embodiment, the case has been described where on simulation, various types of information including information on the subject pattern,  
10 information on the targeted image forming characteristic, information on the projection optical system, and information on the aberration that is to be given is input to main controller 50 via input unit 45 such as a keyboard, and based on such information, main controller  
15 50 makes a Zernike variation table of the targeted image forming characteristic that corresponds to the aberration information given when main controller 50 exposed the subject pattern. However, the present invention is not limited to this. That is, the third program may be  
20 installed into a different computer for simulation other than main controller 50, and various assumptions may be made on information such as the object pattern and information on the projection optical system. And based on each assumption, input operation may be repeatedly  
25 performed to make the Zernike variation table of various types corresponding to the input information in advance, while sequentially changing the condition setting, as well as the information on the targeted aberration, the

information on the projection optical system, and the information on the aberration that is to be given, and from these variation tables a database may be made, which may be stored in the CD-ROM along with the first and  
5 second programs.

When the database made up of the Zernike variation table of various types described above is made in advance, a program (hereinafter called "the fourth program" for the sake of convenience) is to be prepared, which is a  
10 simplified program of the third program to make the CPU in main controller 50 perform the computation previously described using a corresponding Zernike variation table in response to the input of the measurement results of the wavefront aberration and setting conditions and to  
15 make the CPU immediately calculate and display the targeted aberration. The fourth program is to be stored in the above CD-ROM.

Then, on simulation, the first and fourth programs in the CD-ROM are installed on the storage unit 42, and  
20 at the same time the database consisting of the Zernike variation table is copied to the storage unit 42. Or, only the first and fourth programs in the CD-ROM may be installed on the storage unit 42 and the CD-ROM may be left in drive unit 46. In the latter case, on simulation,  
25 main controller 50 is to read the database of the Zernike variation table from the CD-ROM when necessary. In this case, the CD-ROM set inside drive unit 46 makes up the storage unit. This can be accomplished, by modifying the

software.

In the above embodiment, the case has been described where a wavefront aberration, which is an overall aberration, is measured as the image forming characteristics of the projection optical system, and the target adjustment amount of the movable lenses (specific optical elements for adjustment) for correcting the wavefront aberration is calculated, according to the measurement results. However, the present invention is not limited to this. For example, the image forming characteristics of the projection optical system subject to adjustment may be individual image forming characteristics, such as coma or distortion. In this case, for example, a relationship between the unit quantity adjustment amount of the specific optical elements for adjustment in directions of each degree of freedom and the variation amount of the individual image forming characteristics such as coma or distortion is obtained by simulation, and based on the results, parameters denoting the relationship between the adjustment of the specific optical element and the change in the image forming characteristics of the projection optical system is obtained, and then a database is made by the parameters. Then, when actually adjusting the image forming characteristics of the projection optical system, by obtaining coma (or a line-width abnormal value), distortion, or the like of the projection optical system using, for example, the exposing method or aerial image

measurement method, and inputting the measurement values to the main controller, the target adjustment amount of the specific optical element can be decided by calculation likewise the above embodiment, using a  
5 relation equation between the image forming characteristics that has been obtained, the parameters, and the target adjustment amount of the specific optical element (such relation expression is to be prepared in advance).

10 In addition, in the above embodiment, the case has been described where the wavefront aberration of projection optical system PL is measured using a measurement reticle. The present invention, however, is not limited to this, and the measurement of the wavefront  
15 aberration may be performed on body using a portable wavefront aberration measuring unit that is detachable to wafer stage WST. As such a wavefront aberration measuring unit, a wavefront aberration measuring unit 80 based on the Shack-Hartmann method that uses a microlens array in  
20 its photodetection optical system may be used, as is shown in Fig. 10.

Details such as the structure of wavefront aberration measuring unit 80 will now be briefly described. As is shown in Fig. 10, wavefront aberration  
25 measuring unit 80 comprises a housing 82 whose inner space has an L-shaped cross section in an YZ plane, a photodetection optical system 84, which is composed of a plurality of optical elements arranged in a predetermined

positional relationship in housing 82, and a photodetection portion 86, which is disposed on the +Y side end within housing 82.

Housing 82 is made from a member whose cross  
5 section in the YZ plane is shaped in the letter L, having a space formed therein, and at its topmost portion (the end portion in the +Z direction), an opening 82a that has a circular shape when in a planar view is formed so that the light from above housing 82 will be guided into the  
10 inner space of housing 82. In addition, a cover glass 88 is provided so as to cover opening 82a from the inside of housing 82. On the upper surface of cover glass 88, a light shielding membrane that has a circular opening in the center is formed by vapor deposition of metal such as  
15 chrome, which shields unnecessary light from entering photodetection optical system 84 when the wavefront aberration of projection optical system PL is measured.

Photodetection optical system 84 is made up of an objective lens 84a, a relay lens 84b, and a deflecting  
20 mirror 84c, which are sequentially arranged from under cover glass 88 inside housing 82 in a downward direction, and a collimator lens 84d and a microlens array 84e, which are sequentially arranged on the +Y side of deflecting mirror 84c. Deflecting mirror 84c is provided  
25 having an inclination of  $45^\circ$ , and by deflecting mirror 84c, the optical path of the light entering the objective lens 84a from above in a downward vertical direction is deflected toward the collimator lens 84d. Each of the

optical members that make up photodetection optical system 84 is fixed to the wall of housing 82 on the inner side, via holding members (not shown), respectively.

5      Microlens array 84e has a plurality of small convex lenses (lens elements) that are arranged in an array shape on a plane perpendicular to the optical path.

Photodetection portion 86 is made up of parts like a photodetection element such as a two-dimensional CCD, and an electric circuit such as a charge transport  
10      controlling circuit. The photodetection element has an area large enough to receive all the beams that have entered objective lens 84a and are outgoing microlens array 84e. The measurement data of photodetection portion 86 is output to main controller 50 via a signal line (not  
15      shown).

Next, the measuring method of wavefront aberration using wavefront aberration measuring unit 80 will be described. In the following description, for the sake of simplicity, the aberration of photodetection optical  
20      system 84 in wavefront aberration measuring unit 80 is to be small enough so that it can be ignored.

First of all, on normal exposure, because wavefront aberration measuring unit 80 is detached from Z tilt stage 58, the operator performs the operation of  
25      attaching wavefront aberration measuring unit 80 to the side surface of Z tilt stage 58 when wavefront measurement is performed. On such attachment operation, wavefront aberration measuring unit 80 is fixed to a

predetermined reference surface (in this case, the surface on the +Y side) via bolt or a magnet, so that wavefront aberration measuring unit 80 is within the movement strokes of wafer stage WST (Z tilt stage 58) during wavefront measurement.

After the above attachment has been completed, in response to the command input by the operator to start the measurement, main controller 50 moves wafer stage WST via wafer stage drive portion 56 so that wavefront aberration measuring unit 80 is positioned below the alignment system referred to earlier based on the off-axis method. Then, main controller 50 detects alignment marks (not shown) provided on wavefront aberration measuring unit 80 with the alignment system, and based on the detection results and the measurement values of laser interferometer 54W at that point, calculates the position coordinates of the alignment marks and obtains the accurate position of wavefront aberration measuring unit 80. Then, after the position of the wavefront aberration measuring unit 80 is measured, the wavefront aberration is measured in the following manner, with main controller 50 playing the main role.

First of all, main controller 50 loads a measurement reticle (not shown) on which pinhole patterns are formed (hereinafter referred to as a 'pinhole reticle' in order to distinguish it from measurement reticle  $R_T$  previously described) with a reticle loader (not shown) on reticle stage RST. This measurement

reticle has pinholes (which become ideal point light sources that generate spherical waves) formed on its pattern surface at a plurality of points in an area identical to illumination area IAR, and is used only for  
5 measurement.

In the pinhole reticle used in this case, for example, a diffusion plate is provided on its upper surface so that the wavefront of the beams passing through all the numerical apertures of projection optical  
10 system PL can be obtained, that is, the wavefront aberration covering all the numerical apertures of projection optical system PL are measured.

After the pinhole reticle is loaded, main controller 50 detects reticle alignment marks formed on  
15 the pinhole reticle using the reticle alignment microscope described earlier, and based on the detection results, aligns the pinhole reticle at a predetermined position. With this operation, the center of the pinhole reticle is substantially made to coincide with the  
20 optical axis of projection optical system PL.

Then, main controller 50 gives control information TS to light source 16 so as to make it start emitting the laser beam. With this operation, illumination light EL from illumination optical system 12 is irradiated on the  
25 pinhole reticle. Then, the beams outgoing from the plurality of pinholes on the pinhole reticle are condensed on the image plane via projection optical system PL, and the images of the pinholes are formed on

the image plane.

Next, main controller 50 moves wafer stage WST via wafer stage drive portion 56 so that the substantial center of opening 82a of wavefront aberration measuring unit 80 coincides with an image forming point where an image of a pinhole on the pinhole reticle (hereinafter referred to as 'focused pinhole') is formed, while monitoring the measurement values of wafer laser interferometer 54W. On such operation, based on the detection results of the focal point position detection system previously described, main controller 50 finely moves wafer stage WST in the Z-axis direction via wafer stage drive portion 56 so that the upper surface of cover glass 88 of wavefront-aberration measuring unit 80 coincides with the image plane on which the pinhole images are formed. When wafer stage WST is being finely moved, the angle of inclination is also adjusted if necessary. In this manner, the imaging beam of the focused pinhole enters photodetection optical system 84 via the opening in the center of cover glass 88, and is photodetected by the photodetection elements making up the photodetection portion 86.

More particularly, from the focused pinhole on the pinhole reticle, a spherical wave is generated which becomes parallel beams via projection optical system PL and objective lens 84a, relay lens 84b, mirror 84c, and collimator lens 84d that make up the photodetection optical system 84 and irradiate microlens array 84e. With

this operation, the pupil surface of projection optical system PL is relayed to microlens array 84e, and then divided thereby. And then, by each lens element of microlens array 84e, the respective beams are condensed  
5 on the photodetection surface of the photodetection element, and the images of the pinholes are respectively formed on the photodetection surface.

In this case, when projection optical system PL is an ideal optical system that does not have any wavefront  
10 aberration, the wavefront in the pupil plane of projection optical system PL becomes an ideal shape (in this case, a planar surface), and as a consequence, the parallel beams incident on microlens array 84e is supposed to be a plane wave that has an ideal wavefront.  
15 In this case, as is shown in Fig. 11A, a spot image (hereinafter also referred to as a 'spot') is formed at a position on the optical axis of each lens element that make up microlens array 84e.

However, in projection optical system PL, because  
20 there normally is wavefront aberration, the wavefront of the parallel beams incident on microlens array 84e shifts from the ideal wavefront, and corresponding to the shift, that is, the inclination of the wavefront with respect to the ideal wavefront, the image forming position of each  
25 spot shifts from the position on the optical axis of each lens element of microlens array 84e, as is shown in Fig. 11B. In this case, the positional deviation of each spot from its reference point (the position on the optical

axis of each lens element) corresponds to the inclination of the wavefront.

Then, the light incident on each condensing point on the photodetection element making up photodetection  
5 portion 86 (beams of the spot images) is photoelectrically converted at the photodetection elements, and the photoelectric conversion signals are sent to main controller 50 via the electric circuit. Based on the photodetection conversion signals, main  
10 controller 50 calculates the image forming position of each spot, and furthermore, calculates the positional deviation ( $\Delta\xi$ ,  $\Delta\eta$ ) using the calculation results and the positional data of the known reference points and stores it in the RAM. On such operation, the measurement values  
15 of laser interferometer 54W at that point ( $X_i$ ,  $Y_i$ ) are being sent to main controller 50.

When measurement of positional deviation of the spot images by wavefront aberration measuring unit 80 at the image forming point of the focused pinhole image is  
20 completed, main controller 50 moves wafer stage WST so that the substantial center of opening 82a of wavefront aberration measuring unit 80 coincides with the image forming point of the next pinhole image. When this movement is completed, main controller 50 makes light  
25 source 16 generate the laser beam as is described above, and similarly calculates the image forming position of each spot. Hereinafter, a similar measurement is sequentially performed at the image forming point of

other pinhole images.

When all the necessary measurement has been completed, in the RAM of main controller 50, data on the positional deviation ( $\Delta\xi$ ,  $\Delta\eta$ ) of each pinhole image at the image forming point previously described and the coordinate data of each image forming point (the measurement values of laser interferometer 54W ( $X_i$ ,  $Y_i$ ) when performing measurement the image forming point of each pinhole image) are stored.

Then, main controller 50 calculates the wavefront data (the coefficients of each term of the Zernike polynomial), based on the positional deviation ( $\Delta\xi$ ,  $\Delta\eta$ ) of the image forming points of the pinhole images stored in the RAM that corresponds to the inclination of the wavefront on the pupil surface of projection optical system PL, using a different conversion program similar to the first program, which was previously described. The reason for stating 'similar to the first program' is because, when wavefront aberration measuring unit 80 described earlier is used, a program different from the first program is normally prepared that converts the positional deviation amount of the image forming point of the spot images that are measured into coefficients of each term of the Zernike polynomial.

As is obvious from the description so far, when the wavefront aberration is measured using wavefront aberration measuring unit 80, wafer development or the like will not be required, therefore, reduction of the

measurement time can be expected. In addition, because wafer development or the like will not be required, there is also an advantage of exposure apparatus 10 being able to perform a so-called self-measurement in a state where  
5 wavefront aberration measuring unit 80 is attached to wafer stage WST. Then, by performing a process according to a procedure similar to the above embodiment, main controller 50 can calculate and display the targeted aberration (image forming characteristics), and  
10 furthermore, automatically perform adjustment of the image forming characteristic of projection optical system PL.

In the above embodiment, the case has been described where the first program, which converts the  
15 positional deviation amount measured using measurement reticle  $R_T$  into coefficients of each term of the Zernike polynomial, the second program, which computes the adjustment amount of the image forming characteristics based on the coefficients of each term of the Zernike  
20 polynomial that were converted in the first program, the third program, which converts the coefficients of each term of the Zernike polynomial converted in the first program into various aberrations (including index of such aberrations), and the database that goes with the second  
25 program, are all packaged in a single CD-ROM. Such a packaging, however, is not a mandatory. That is, the first program, the second program (and its database), and the third program are programs that have different

purposes, which means that they all have sufficient utility values independently.

Especially with the third program, a part of it that makes the Zernike variation table (corresponding to steps 101 through 122) can be used as a single program. By inputting various types of information including information on a subject pattern, information of the targeted image forming characteristic, information on the projection optical system, and information on a given aberration from an input unit such as a keyboard into a computer that has such a program installed, the Zernike variation table of the targeted image forming characteristic is made. Accordingly, the database consisting of the Zernike variation table made in the manner above can be suitably used in other exposure apparatus as is previously described.

For example, when the wavefront aberration measuring unit referred to earlier is used, a program different from the first program is normally prepared that converts the positional deviation amount of the image forming point of the spot images that are measured into coefficients of each term of the Zernike polynomial, and even when the second program and its database, and the third program are combined with such a conversion program, it is obvious that the second program and its database, and the third program can sufficiently show their capability.

In addition, especially with the second program and

the third program, they do not necessarily have to be combined because their purposes differ greatly. The purpose of the former is to make the operation efficient for a service technician or the like performing repair and adjustment on the exposure apparatus the image forming characteristics of the projection optical system need to be adjusted, whereas, the purpose of the latter is to perform a simulation to confirm whether the targeted image forming characteristic of the projection optical system is sufficient enough when the operator or the like of the exposure apparatus in a semiconductor manufacturing site exposes a subject pattern. When taking into consideration such differences in their purposes, in the case the second program and its database and the third program are in the same software package as in the above embodiment, for example, two types of passwords is settable. In such a case, the second and third program may be supplied as a different information storage medium such as a firmware, and only the database may be recorded in a storage medium such as the CD-ROM.

In addition, in the above embodiment, on the adjustment of the image forming characteristic of projection optical system PL, the first to third program was installed on storage unit 42 from the CD-ROM, and the database was copied to storage unit 42. The present invention, however, is not limited to this, and so long as only the first to third programs are installed on storage unit 42 from the CD-ROM, the database does not

have to be copied to storage unit 42. In this case, the CD-ROM set in the drive unit structures the storage unit.

In the above embodiment, the case has been described where the database is made up of parameters corresponding to the unit drive amount of movable lenses 13<sub>1</sub> to 13<sub>4</sub> in directions of each degree of freedom. However, the present invention is not limited to this, and in cases such as when a part of the lens making up projection optical system PL can be easily exchanged, parameters that show the change of the image forming characteristics corresponding to the thickness of the lens may be included. In such a case, the optimal lens thickness is to be calculated as the target adjustment amount. Besides such parameters, the database may include parameters that show the change of the image forming characteristics corresponding to the reticle rotation. In this case, for example, when reticle R rotates as is shown in Fig. 2F, such rotation may be in a + (positive) direction, and the unit rotation amount may be 0.1 degrees. In this case, according to the calculated reticle rotation, for example, only at least one of reticle stage RST and wafer stage WST has to be rotated. And, other than such parameters, details whose change affects the image forming characteristics of the projection optical system and is also adjustable can also be included in the database, such as center wavelength of the illumination light, or the position of the reticle or the like in the optical axis direction.

In addition, in the above embodiment, the case has been described where main controller 50 automatically adjusts the image forming characteristics of the projection optical system PL via image forming characteristics correction controller 48, based on the target adjustment amount of the specific optical elements computed according to the second program or the targeted aberration amounts computed according to the third program. However, the present invention is not limited to this, and the image forming characteristic of projection optical system PL may be adjusted manually by an operator or via an operation. In such a case, the second program or the third program can be effectively used not only in the adjustment stage, but also in the manufacturing stage, which allows production of a projection optical system whose image forming characteristics are adjusted.

In the above embodiment, the case has been described where reference patterns are provided on measurement reticle  $R_T$  along with measurement patterns, however, the reference patterns do not have to be provided on the measurement reticle masks (measurement reticle  $R_T$  in the case of the above embodiment) for measuring optical properties. That is, the reference patterns may be provided on a different mask, or the reference patterns may not be provided on the mask side but be provided on the substrate (wafer) side instead. More particularly, a reference wafer on which the reference patterns are formed in advance in a size

corresponding to the projection magnification can be used,  
and by coating a resist on the reference wafer,  
transferring the measurement patterns on the resist layer,  
and developing the patterns, and then by measuring the  
5 positional deviating between the resist image of the  
measurement pattern that can be obtained after  
development and the reference marks, substantially the  
same measurement as in the above embodiment can be  
performed.

10 In addition, in the above embodiment, after the  
measurement pattern and the reference pattern has been  
transferred onto wafer W, the wavefront aberration of  
projection optical system PL was calculated based on the  
measurement results of the resist image that was obtained  
15 by developing the wafer. The present invention, however,  
is not limited to this, and the projection image (aerial  
image) or the measurement pattern can be projected on the  
wafer and the projected image (aerial image) may be  
measured using an aerial image measuring unit, or the  
20 latent images of the measurement patterns and the  
reference patterns formed on the resist layer or images  
that are obtained by wafer etching may be measured. In  
such cases, as long as the positional deviation of the  
measurement patterns from the reference position (such as  
25 the designed projection position of the measurement  
pattern) are measured, the wavefront aberration of the  
projection optical system can be measured in the  
procedure similar to the above embodiment based on the

measurement results. Also, instead of transferring the measurement pattern onto the wafer, a reference wafer on which the reference pattern is already formed may be prepared in advance, and the reference pattern may be transferred onto its resist layer and the positional deviation measured, or an aerial image measuring unit that has a plurality of apertures corresponding to the measurement patterns may be used to measure the positional deviation between the apertures and the reference pattern. Furthermore, in the above embodiment, the positional deviation previously described was measured using an overlay measuring unit, however, other units may be used, such as for example, an alignment sensor provided in the exposure apparatus.

In addition, in the above embodiment, the coefficients of the terms of the Zernike polynomial were used up to the 37<sup>th</sup> term, however, the 38<sup>th</sup> term and higher terms may be used, such as using the terms up to the 81<sup>st</sup> term so that the high order component of each aberration of projection optical system PL may be calculated. That is, the number of terms or the numbers used in the Zernike polynomial may be any number. Furthermore, because the aberration of projection optical system PL may be positively generated depending on the illumination conditions or the like, in the above embodiment, the optical elements of projection optical system PL may be adjusted so that the targeted aberration becomes a predetermined value, in addition to the targeted

aberration being either zero or a minimal quantity at all times.

Furthermore, in the above embodiment, a service technician performed the installation of the programs previously described. However, for example, the programs may be installed in a server connected through the Internet or the like to a host computer that totally controls manufacturing equipment such as exposure apparatus or a manufacturing line including a large number of manufacturing equipment, or the programs may be installed in the exposure apparatus. In this case, the operator may enter the pattern information, or the exposure apparatus may be made to obtain the pattern information by reading a bar code or a two dimensional code of a reticle on which the pattern to be transferred onto a wafer is formed, so that the exposure apparatus or the server can automatically perform the making of the Zernike variation table described earlier, deciding the optimum exposure condition (conditions such as illumination condition and the numerical apertures of projection optical system PL), and adjusting the image forming characteristic of projection optical system PL, without any intervening by the operator or the service technician. On such automation, when, for example, the measurement reticle described earlier is used when measuring the wavefront aberration, the alignment system of the exposure apparatus may detect the positional deviation of the latent images of the measurement pattern

formed on a resist layer of a wafer from the latent images of the reference pattern. In addition, in the above embodiment, the operator or the like fixed wavefront aberration measuring unit 80 to wafer stage WST, however, for example, a carriage system (such as a wafer loader) that performs wafer or wafer holder exchange may be used to automatically carry wavefront aberration measuring unit 80.

In the above embodiment, the case has been described where the present invention has been applied to a stepper, however, the present invention is not limited to this, and the present invention can also be suitably applied to a scanning type exposure apparatus like the one disclosed in, for example, United States Patent No. 5,473,410 that transfers a pattern of a mask onto a substrate while synchronously moving the mask and the substrate.

The use of the exposure apparatus is not limited only to the exposure apparatus for manufacturing semiconductor devices, but the present invention can also be widely applied to an exposure apparatus for transferring a liquid crystal display device pattern onto a rectangular glass plate and an exposure apparatus for producing thin-film magnetic heads, micromachines, DNA chips, and the like. Furthermore, the present invention can be applied not only to an exposure apparatus for producing microdevices such as semiconductor devices, but can also be applied to an exposure apparatus that

transfers a circuit pattern onto a glass plate or silicon wafer to produce a mask or reticle used in a light exposure apparatus, an EUV exposure apparatus, an X-ray exposure apparatus, an electron-beam exposure apparatus,  
5 and the like.

In addition, the light source of the exposure apparatus in the above embodiment is not limited to an ultraviolet pulse light source such as an F<sub>2</sub> laser, an ArF excimer laser, or a KrF excimer laser, and an ultra-high  
10 pressure mercury lamp emitting an emission line such as g-line (a wavelength of 436nm) or i-line (a wavelength of 365nm) can also be used.

In addition, a harmonic wave may be used that is obtained by amplifying a single-wavelength laser beam in  
15 the infrared or visible range emitted by a DFB semiconductor laser or fiber laser, with a fiber amplifier doped with, for example, erbium (or both erbium and ytterbium), and by converting the wavelength into ultraviolet light using a nonlinear optical crystal. Also,  
20 the magnification of the projection optical system is not limited to a reduction system, and an equal magnification or a magnifying system may be used. Furthermore, the projection optical system is not limited to a refraction system, and a catadioptric system that has reflection  
25 optical elements and refraction optical elements may be used as well as a reflection system that uses only reflection optical elements. When the catadioptric system or the reflection system is used as projection optical

system PL, the image forming characteristics of the projection optical system are adjusted by changing the position or the like of the reflection optical elements (such as a concave mirror or a reflection mirror) that  
5 serve as the specific optical elements previously described. In addition, when the  $F_2$  laser beam, the  $Ar_2$  laser beam, the EUV light, or the like is used as illumination light EL, projection optical system PL can be a total reflection system that has only reflection  
10 optical elements. However, when the  $Ar_2$  laser beam, the EUV light, or the like is used, reticle R also needs to be a reflective type reticle.

Incidentally, semiconductor devices are made undergoing the following steps: a device  
15 function/performance designing step, a reticle making step where a reticle is made based on the designing step, a wafer making step where a wafer is made from silicon material, a transferring step where the pattern of the reticle is transferred onto the wafer by the exposure  
20 apparatus in the embodiment, a device assembly step (including the dicing process, bonding process, and packaging process), and an inspection step. According to the device manufacturing method, because exposure is performed in a lithographic process using the exposure  
25 apparatus in the above embodiment, the pattern of reticle R is transferred onto wafer W via projection optical system PL whose image forming characteristics are adjusted according to a subject pattern, or whose image

forming characteristics are adjusted with high precision based on the measurement results of the wavefront aberration, and therefore it is possible to transfer the detailed pattern onto wafer W with high overlay accuracy.

5 Accordingly, the yield of the devices as final products is improved, which makes it possible to improve its productivity.

### **INDUSTRIAL APPLICABILITY**

10 As is described above, the image forming characteristics measuring method of the present invention is suitable to measure the targeted image forming characteristic of a projection optical system. Also, the image forming characteristics adjusting method of the present invention is suitable to adjust the image forming characteristics of a projection optical system. Also, the exposure method of the present invention is suitable to form fine patterns on a substrate. Also, the exposure apparatus of the present invention is suitable to perform exposure with the image forming characteristics of its projection optical system adjusted accurately. Also, the programs and storage medium of the present invention are suitable for use in the above exposure apparatus.

20 Furthermore, the device manufacturing method of the present invention is suitable to manufacture microdevices.

**WHAT IS CLAIMED IS:**

1. An image forming characteristics measuring method in which at least one image forming characteristic  
5 of a projection optical system is measured, said method comprising:

a measuring process in which information related to wavefront aberration of said projection optical system is measured at one measurement point at the least in a field  
10 of said projection optical system; and

a calculating process in which at least one targeted image forming characteristic is calculated, based on said information related to wavefront aberration and a Zernike variation table of said targeted  
15 image forming characteristic that is prepared in advance, as a linear sum of coefficients of each term in a Zernike polynomial that are decided based on said information related to wavefront aberration and said Zernike variation table.

20

2. The image forming characteristics measuring method according to Claim 1 wherein

in said calculating process, when said targeted image forming characteristic include image forming  
25 characteristics of a plurality of types, said image forming characteristics of a plurality of types included in said targeted image forming characteristic are each calculated, based on said measuring of wavefront aberration and a Zernike variation table for each of said  
30 image forming characteristics of a plurality of types.

3. The image forming characteristics measuring method according to Claim 1, said method further

comprising:

a making process in which conditions are set in order to make a Zernike variation table, based on information on a pattern subject to projection by said  
5 projection optical system and said targeted image forming characteristic, and a Zernike variation table of said targeted image forming characteristic that corresponds to information related to a given aberration is made, based on information related to said projection optical system  
10 and information related to said given aberration, prior to said measuring process.

4. The image forming characteristics measuring method according to Claim 3 wherein  
15 said information related to said projection optical system includes numerical aperture of said projection optical system, illumination condition, and wavelength of illumination light.

20 5. The image forming characteristics measuring method according to Claim 3 wherein  
in said making process, when said targeted image forming characteristic include image forming characteristics of a plurality of types, a Zernike  
25 variation table for each of said image forming characteristics of a plurality of types that correspond to said information related to aberration is made.

6. The image forming characteristics measuring  
30 method according to Claim 1, further comprising:  
a displaying process in which information related to said targeted image forming characteristic that has been calculated is displayed.

7. An image forming characteristics adjusting method in which at least one image forming characteristic of a projection optical system comprising a plurality of optical elements that include a specific optical element used for adjustment is adjusted, said method comprising:

an obtaining process in which at least one image forming characteristic of said projection optical system is obtained, by obtaining information on light via said projection optical system at one measurement point at the least in a field of said projection optical system; and

a deciding process in which a targeted adjustment amount of said specific optical element is decided by computation using a relation expression between said image forming characteristic that has been obtained, parameters, and a targeted adjustment amount of said specific optical element, said parameters denoting a relation between adjustment of said specific optical element and a change in image forming characteristics of said projection optical system.

8. The image forming characteristics adjusting method according to Claim 7, said method further comprising:

an obtaining process in which said parameters are obtained, prior to said obtaining process in which said image forming characteristic is obtained.

9. The image forming characteristics adjusting method according to Claim 7 wherein

in said obtaining process in which said image forming characteristic is obtained, image forming characteristics of a plurality of types are obtained, and

in said deciding process, a target adjustment amount of said specific optical element is decided by computation using a relation expression between said image forming characteristics of a plurality of types  
5 that have been obtained, parameters, and a targeted adjustment amount of said specific optical element, said parameters denoting a relation between adjustment of said specific optical element and a change in image forming characteristics of said projection optical system.

10

10. The image forming characteristics adjusting method according to Claim 7 wherein said image forming characteristic is a wavefront aberration expressed in a Zernike polynomial.

15

11. The image forming characteristics adjusting method according to Claim 10 wherein

said relation expression is an equation that includes a weighting function that performs weighting on  
20 a coefficient of any term in coefficients of each term of said Zernike polynomial.

12. An exposure method in which a pattern is transferred onto an object via a projection optical  
25 system, said exposure method comprising:

an adjusting process in which at least one image forming characteristic of said projection optical system is adjusted using said image forming characteristics adjusting method according to any one of Claims 7 to 11;  
30 and

a transferring process in which said pattern is transferred onto said object using said projection optical system whose image forming characteristic is

adjusted.

13. An exposure apparatus that transfers a pattern onto an object via a projection optical system, said exposure apparatus comprising:

a measuring unit that measures wavefront aberration of said projection optical system, said measuring unit being at least partly attachable to an exposure apparatus main body including said projection optical system; and  
10 a first computing unit that calculates at least one targeted image forming characteristic based on measurement information measured by said measuring unit and a Zernike variation table of said targeted image forming characteristic, as a linear sum of coefficients  
15 of each term in a Zernike polynomial that are decided based on said measurement information and said Zernike variation table.

14. The exposure apparatus according to Claim 13, further comprising:

a storage unit that stores said Zernike variation table in advance.

15. The exposure apparatus according to Claim 13 wherein

said Zernike variation table is a Zernike variation table of said targeted image forming characteristic that corresponds to information on a given aberration on exposure of a subject pattern.

30

16. The exposure apparatus according to Claim 15, further comprising:

an input unit used to input information of various

types including information on said subject pattern,  
information on said targeted image forming  
characteristic, information related to said projection  
optical system, and information on said given aberration;  
5 and

a second computing unit that set conditions in  
order to make a Zernike variation table based on said  
information on said subject pattern and said targeted  
image forming characteristic input via said input unit,  
10 and based on information related to said projection  
optical system and information related to said given  
aberration input via said input unit, said second  
computing unit makes a Zernike variation table of said  
targeted image forming characteristic that corresponds to  
15 information on said given aberration on exposure of said  
subject pattern.

17. The exposure apparatus according to Claim 16  
wherein

20 said information related to said projection optical  
system includes numerical aperture of said projection  
optical system, illumination condition, and wavelength of  
illumination light.

25 18. The exposure apparatus according to Claim 13,  
further comprising:

a display unit which displays information on said  
targeted image forming characteristic calculated by said  
first computing unit on screen.

30

19. The exposure apparatus according to Claim 13,  
further comprising:

an image forming characteristics correcting unit

that corrects at least one image forming characteristic of said projection optical system based on calculation results of said targeted image forming characteristic by said first computing unit.

5

20. The exposure apparatus according to Claim 19 wherein

said projection optical system is structured comprising a plurality of optical elements that include a specific optical element used for adjustment, and

10 said image forming characteristics correcting unit has a storage unit in which parameters are stored in advance that denotes a relation between adjustment of said specific optical element and a change in image forming characteristics of said projection optical system, and a calculation unit that calculates a targeted adjustment amount of said specific optical element using a relation expression between information on said image forming characteristic that has been calculated, said parameters, and a targeted adjustment amount of said specific optical element.

21. An exposure apparatus that transfers a pattern onto an object via a projection optical system, said exposure apparatus comprising:

25 said projection optical system that comprises a plurality of optical elements including a specific optical element used for adjustment;

a storage unit in which parameters are stored in advance that denotes a relation between adjustment of said specific optical element and a change in image forming characteristics of said projection optical system,

30

a measuring unit that measures at least one image forming characteristic of said projection optical system, said measuring unit being at least partly attachable to an exposure apparatus main body including said projection  
5 optical system; and

a computing unit that calculates a targeted adjustment amount of said specific optical element using a relation expression between an actual measurement data measured by said measuring unit, said parameters, and a  
10 targeted adjustment amount of said specific optical element.

22. The exposure apparatus according to Claim 21, further comprising:

15 an image forming characteristics adjusting unit that adjusts at least one image forming characteristic of said projection optical system by adjusting said specific optical element according to said calculated targeted adjustment amount.

20

23. The exposure apparatus according to Claim 21 wherein

said measuring unit can measure image forming characteristics of a plurality of types of said  
25 projection optical system, and

said computing unit calculates a targeted adjustment amount of said specific optical element using a relation expression between an actual measurement data of said image forming characteristics of a plurality of  
30 types measured by said measuring unit, said parameters, and a targeted adjustment amount of said specific optical element.

24. The exposure apparatus according to Claim 21 wherein said image forming characteristic is a wavefront aberration expressed in a Zernike polynomial.

5           25. The exposure apparatus according to Claim 24 wherein said relation expression is an equation that includes a weighting function that performs weighting on a coefficient of any term in coefficients of each term of said Zernike polynomial.

10

26. A device manufacturing method including a lithographic process, wherein in said lithographic process exposure is performed using said exposure apparatus according to any one of Claims 13 to 25.

15

27. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an object via a projection optical system execute a predetermined process, said program making said control computer execute:

20           a condition setting procedure in which conditions are set for making a Zernike variation table in response to an input of information on a subject pattern and information on a targeted image forming characteristic; and

25

          a making procedure in which a Zernike variation table of said targeted image forming characteristic corresponding to information on given aberration on exposure of said subject pattern is made, in response to

30           an input of information related to said projection optical system and information on said given aberration.

28. The program according to Claim 27, said

program further making said control computer execute:

5 a calculating procedure in which said targeted image forming characteristic of said projection optical system is calculated in response to an input of actual measurement data of wavefront aberration of said projection optical system, based on said actual measurement data and said Zernike variation table.

10 29. The program according to Claim 28, said program further making said control computer execute:

a displaying procedure in which information on said targeted image forming characteristic that has been calculated is displayed on a display unit.

15 30. A program according to Claim 28, said program further making said control computer execute:

20 an adjusting procedure in which said projection optical system is adjusted so that said targeted image forming characteristic that has been calculated becomes optimal.

31. A program according to Claim 28, said program further making said control computer execute:

25 a making procedure in which said Zernike variation table is made in response to input of different information related to said projection optical system and input of information on said given aberration, by each different information related to said projection optical system;

30 a calculating procedure in which said targeted image forming characteristic of said projection optical system is calculated by each different information related to said projection optical system in response to

input of actual measurement data of wavefront aberration of said projection optical system, based on said actual measurement data and said Zernike variation table; and

5 a deciding procedure in which an optimum exposure condition is decided by finding information related to said projection optical system that makes said targeted image forming characteristic that has been calculated become optimal.

10 32. The program according to Claim 31, said program further making said control computer execute:

a setting procedure in which said optimum exposure condition that has been decided is set.

15 33. A program that makes a control computer execute a process, said program making said control computer execute:

a procedure of calculating a targeted image forming characteristic of a projection optical system in response  
20 to an input of information related to said targeted image forming characteristic and an input of actual measurement data of wavefront aberration of said projection optical system, based on said actual measurement data and a Zernike variation table of said targeted image forming  
25 characteristic that is prepared in advance, as a linear sum of coefficients of each term in a Zernike polynomial that are decided based on said actual measurement data and said Zernike variation table.

30 34. The program according to Claim 33, said program further making said control computer execute:

a displaying procedure in which information on said targeted image forming characteristic that has been

calculated is displayed on a display unit.

35. The program according to Claim 33, said program further making said control computer execute:

5        an adjusting procedure in which said projection optical system is adjusted so that said targeted image forming characteristic that has been calculated becomes optimal.

10        36. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an object via a projection optical system execute a predetermined process, said program making said control computer execute:

15        a calculating procedure in which a targeted adjustment amount of said projection optical system is calculated in response to an input of actual measurement data of image forming characteristics of said projection optical system, using a relation expression between said  
20        actual measurement data of image forming characteristics that has been input, parameters, and a targeted adjustment amount of said projection optical system, said parameters denoting a relation between adjustment of said projection optical system and a change in said image  
25        forming characteristics of said projection optical system.

37. The program according to Claim 36, said program further making said control computer execute:

30        a displaying procedure in which information on said targeted adjustment amount that has been calculated is displayed on a display unit.

38. The program according to Claim 36, said program further making said control computer execute:

an adjusting procedure in which said projection optical system is adjusted based on said target  
5 adjustment amount that has been calculated.

39. The program according to Claim 36 wherein said parameters are parameters denoting a relation between adjustment of a specific optical element used for  
10 adjustment that structures said projection optical system and a change in said image forming characteristics, and said targeted adjustment amount is an amount of said specific optical element that needs to be adjusted.

15 40. The program according to Claim 36 wherein said image forming characteristic is a wavefront aberration expressed in a Zernike polynomial.

41. The program according to Claim 40 wherein said  
20 relation expression is an equation that includes a weighting function that performs weighting on a coefficient of any term in coefficients of each term of said Zernike polynomial.

25 42. The program according to Claim 36, said program further making said control computer execute:  
a condition setting procedure in which conditions are set for making a Zernike variation table in response to an input of information related to information on a  
30 subject pattern and an input of information on a targeted image forming characteristic;

a making procedure in which a Zernike variation table of said targeted image forming characteristic

corresponding to information on aberration is made, in response to an input of information related to said projection optical system and information on a given aberration; and

- 5           a calculating procedure in which said targeted image forming characteristic is calculated in response to an input of actual measurement data of wavefront aberration of said projection optical system, based on said measurement data and said Zernike variation table.

10

43. A program according to Claim 42, said program further making said control computer execute:

- a displaying procedure in which information on said targeted image forming characteristic that has been  
15   calculated is displayed on a display unit.

44. A program according to Claim 42, said program further making said control computer execute:

- a converting procedure in which information  
20   obtained on light via said projection optical system at one measurement point at the least in a field of said projection optical system is converted into actual measurement data of said wavefront aberration of said projection optical system.

25

45. An information storage medium that can be read by a computer in which a program according to any one of claims 27 to 44 is recorded.

- 30           46. A making method of an exposure apparatus that transfers a pattern onto an object via a projection optical system, said making method comprising:

          an adjusting process in which said projection

optical system is adjusted using said image forming characteristics adjusting method according to any one of Claims 7 to 11.

5           47. The image forming characteristics measuring method according to Claim 1 wherein

          said Zernike variation table is a table in which a predetermined value of aberration is given to each term in a Zernike polynomial and said targeted image forming  
10   characteristic is calculated for a plurality of terms in said Zernike polynomial.

          48. The image forming characteristics measuring method according to Claim 47 wherein

15           a first information related to a pattern subject to projection by said projection optical system and a second information related to a projection condition of said pattern are used when making said Zernike variation  
table.

20

          49. The image forming characteristics measuring method according to Claim 48 wherein

          said second information includes numerical aperture of said projection optical system and an illumination  
25   condition of said pattern.

          50. The image forming characteristics measuring method according to Claim 47 wherein

          when different patterns are each projected by said  
30   projection optical system, said targeted image forming characteristic is calculated by making a Zernike variation table for each of said patterns.

51. The image forming characteristics measuring method according to Claim 47 wherein

when said targeted image forming characteristic includes an image forming characteristic of a plurality of types, a Zernike variation table is made for each of  
5 said image forming characteristics to perform said calculation.

52. The image forming characteristics measuring  
10 method according to Claim 47 wherein

when a plurality of projection conditions are settable on projection of a pattern by said projection optical system, said targeted image forming characteristic is calculated using the Zernike variation  
15 table for each of said projection conditions.

53. An adjusting method of an exposure apparatus that transfers a pattern onto an object via a projection optical system, said method including

20 a measuring process in which a targeted image forming characteristic of said projection optical system is measured using said image forming characteristics measuring method according to any one of Claims 1 to 6 and Claims 47 to 52.

25

54. An image forming characteristics adjusting method in which an image forming characteristic of a projection optical system is adjusted, said method including

30 a measuring process in which a targeted image forming characteristic is measured using said image forming characteristics measuring method according to any one of Claims 1 to 6 and Claims 47 to 52; and

an adjusting process in which said projection optical system is adjusted based on measurement results of said image forming characteristic.

5           55. The image forming characteristics adjusting method according to Claim 54 wherein

          said projection optical system comprises a plurality of optical elements that include a specific optical element for adjustment, and

10           adjustment of said projection optical system is performed by deciding a targeted adjustment amount of said specific optical element using a relation expression between said measured image forming characteristics, parameters that denote a relation between adjustment of  
15           said specific optical element and a change in image forming characteristics of said projection optical system, and said targeted adjustment amount of said specific optical element, and adjusting said specific optical element according to said targeted adjustment  
20           amount that has been decided.

          56. An exposure method in which a pattern is transferred onto an object via a projection optical system, said method including

25           an adjusting process in which an image forming characteristic of said projection optical system is adjusted using said image forming characteristics adjusting method according to Claim 54; and

          a transferring process in which said pattern is  
30           transferred onto said object using said projection optical system whose image forming characteristic is adjusted.

57. The exposure method according to Claim 56  
wherein

said image forming characteristic is adjusted by  
deciding an adjustment amount of an optical element of  
5 said projection optical system, based on data of a  
relation between an adjustment amount of said optical  
element and a change in its image forming  
characteristics, and said measured image forming  
characteristic, and by driving said optical element  
10 according to said adjustment amount that has been  
decided.

58. An image forming characteristics adjusting  
method in which an image forming characteristic of a  
15 projection optical system is adjusted, said method  
including:

a measuring process in which a targeted image  
forming characteristic is obtained using said image  
forming characteristics measuring method according to any  
20 one of Claims 1 to 6 and Claims 47 to 52; and

said image forming characteristic is adjusted by  
driving an optical element of said projection optical  
system, based on data of a relation between an adjustment  
amount of said optical element and a change in  
25 coefficients of each term in a Zernike polynomial, and  
said measured wavefront aberration.

59. An exposure method in which a pattern is  
transferred onto an object via a projection optical  
30 system, said method including

an adjusting process in which an image forming  
characteristic of said projection optical system is  
adjusted using said image forming characteristics

adjusting method according to Claim 58; and

a transferring process in which said pattern is transferred onto said object using said projection optical system whose image forming characteristic is  
5 adjusted.

60. An image forming characteristics adjusting method in which at least one image forming characteristic of a projection optical system is adjusted, said method  
10 including:

a measuring process in which information related to wavefront aberration of said projection optical system is measured; and

said image forming characteristic is adjusted by  
15 driving an optical element of said projection optical system, based on data of a relation between an adjustment amount of said optical element and a change in coefficients of each term in a Zernike polynomial, and said information related to wavefront aberration.

20

61. The image forming characteristics adjusting method according to Claim 60 wherein

said information related to wavefront aberration is expressed in a Zernike polynomial, and different  
25 weighting is performed on a plurality of terms in said Zernike polynomial to decide said adjustment amount of said optical element, in order to adjust an image forming characteristic of a plurality of types of said projection optical system.

30

62. An exposure method in which a pattern is transferred onto an object via a projection optical system, said method including

a calculating process in which a targeted image forming characteristic of said projection optical system is calculated for each of a plurality of exposure conditions settable when a pattern image is projected by  
5 said projection optical system, based on information related to wavefront aberration of said projection optical system and a Zernike variation table corresponding to each of said plurality of exposure conditions; and

10 a transferring process in which said pattern is transferred onto said object with an optimum exposure condition set with respect to said pattern, based on said targeted image forming characteristic that has been calculated for each of said exposure conditions.

15

63. The exposure method according to Claim 62 wherein

said exposure conditions include numerical aperture of said projection optical system and an illumination  
20 condition of said pattern.

64. The exposure method according to Claim 62 wherein

25 said targeted image forming characteristic is calculated, as a linear sum of coefficients of each term in a Zernike polynomial that are decided based on said information related to wavefront aberration and said Zernike variation table.

30 65. The exposure method according to Claim 62 wherein

when different patterns are each transferred via said projection optical system, by calculating said

targeted image forming characteristic using a Zernike variation table for each of said patterns, said optimum exposure condition is set for each said different pattern.

5

66. An exposure method in which a pattern is transferred onto an object via a projection optical system, said exposure method comprising:

an adjusting process in which at least one image  
10 forming characteristic of said projection optical system is adjusted using said image forming characteristics adjusting method according to one of Claims 60 and 61; and

a transferring process in which said pattern is  
15 transferred onto said object using said projection optical system whose image forming characteristic is adjusted.

67. The exposure apparatus according to any one of  
20 Claims 13 to 20 wherein

said Zernike variation table is a table in which a predetermined value of aberration is given to each term in a Zernike polynomial and said targeted image forming characteristic is calculated for a plurality of terms in  
25 said Zernike polynomial.

68. An exposure apparatus that transfers a pattern onto an object via a projection optical system, said exposure apparatus comprising:

30 a computing unit that obtains an image forming characteristic that becomes an evaluation item of said projection optical system, based on information related to wavefront aberration of said projection optical system

and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern , as a linear sum of coefficients of each term in a Zernike polynomial that  
5 are decided based on said information related to wavefront aberration and said Zernike variation table;  
and

an adjusting unit that adjusts at least one image forming characteristic of said projection optical system  
10 to transfer the pattern onto said object.

69. The exposure apparatus according to Claim 68 wherein

said Zernike variation table is obtained by giving  
15 a predetermined value of aberration to each term in said Zernike polynomial and calculating an image forming characteristic of said projection optical system in each of a plurality of terms in said Zernike polynomial.

20 70. The exposure apparatus according to Claim 68 wherein

said computing unit calculates, when said illumination condition is changed, an image forming characteristic that becomes said evaluation item using a  
25 Zernike variation table corresponding to said changed illumination condition.

71. The exposure apparatus according to Claim 68 wherein

30 said computing unit calculates an image forming characteristic that becomes said evaluation item using the Zernike variation table for each said pattern, when different patterns are each transferred via said

projection optical system.

72. An exposure apparatus that transfers a pattern onto an object via a projection optical system, said exposure apparatus comprising:

a storage unit that stores data related to a relation between an adjustment amount of an optical element of said projection optical system and a change in coefficients of each term in a Zernike polynomial; and  
an adjusting unit that adjusts at least one image forming characteristic of said projection optical system based on information related to wavefront aberration of said projection optical system and said data.

73. The exposure apparatus according to Claim 72 wherein

said information related to wavefront aberration is expressed in a Zernike polynomial, and said adjusting unit decides said adjustment amount of said optical element by performing different weighting on a plurality of terms in said Zernike polynomial to adjust said image forming characteristic of a plurality of types of said projection optical system.

74. An exposure apparatus that transfers a pattern onto an object via a projection optical system, said exposure apparatus comprising:

a computing unit that obtains a targeted image forming characteristic of said projection optical system for each of a plurality of exposure conditions settable on projecting a pattern image by said projection optical system, based on information related to wavefront aberration of said projection optical system and a

Zernike variation table corresponding to each of said plurality of exposure conditions ; and

an exposure control unit that sets an optimum exposure condition for said pattern, based on said  
5 targeted image forming characteristic that has been calculated for each of said exposure conditions.

75. The exposure apparatus according to Claim 74 wherein

10 said exposure conditions include numerical aperture of said projection optical system and an illumination condition of said pattern.

76. The exposure apparatus according to Claim 74  
15 wherein

said computing unit calculates said targeted image forming characteristic , as a linear sum of coefficients of each term in a Zernike polynomial that are decided based on said information related to wavefront aberration  
20 and said Zernike variation table.

77. The exposure apparatus according to Claim 74 wherein

said computing unit calculates said targeted image  
25 forming characteristic using the Zernike variation table for each of said patterns, when different patterns are transferred via said projection optical system, and

said exposure control unit sets an optimum exposure condition for each of said different patterns, based on  
30 said targeted image forming characteristic that has been calculated for each of said patterns.

78. A device manufacturing method including a lithographic process, wherein

in said lithographic process exposure is performed  
5 using said exposure apparatus according to any one of  
Claims 68 to 77.

79. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an  
10 object via a projection optical system execute a  
predetermined process, said program making said control  
computer execute:

a measuring procedure in which information related  
to wavefront aberration of said projection optical system  
15 is measured; and

an adjusting procedure in which at least one image  
forming characteristic is adjusted by driving an optical  
element of said projection optical system, based on data  
of a relation between an adjustment amount of said  
20 optical element and a change in coefficients of each term  
in a Zernike polynomial, and said information related to  
wavefront aberration.

80. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an  
25 object via a projection optical system execute a  
predetermined process, said program making said control  
computer execute:

a calculating procedure in which a targeted  
30 image forming characteristic of said projection optical  
system is calculated in each of a plurality of exposure  
conditions settable when projecting a pattern image by  
said projection optical system, based on information

related to wavefront aberration of said projection optical system and a Zernike variation table corresponding to each of said plurality of exposure conditions; and

5           a transferring procedure in which said pattern is transferred onto said object with an optimum exposure condition set with respect to said pattern, based on said targeted image forming characteristic that has been calculated for each of said exposure conditions.

10

81. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an object via a projection optical system execute a predetermined process, said program making said control  
15 computer execute:

an obtaining procedure in which an image forming characteristic that becomes an evaluation item of said projection optical system is obtained, based on information related to wavefront aberration of said  
20 projection optical system and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern, as a linear sum of coefficients of each term in a Zernike polynomial that are decided based on said information  
25 related to wavefront aberration and said Zernike variation table; and

an adjusting procedure in which at least one image forming characteristic of said projection optical system is adjusted to transfer the pattern onto said object.

30

82. An exposure method in which a pattern is transferred onto an object via a projection optical system, said method comprising:

deciding coefficients of each term in a Zernike polynomial based on information related to wavefront aberration of said projection optical system; and

calculating an image forming characteristic that  
5 becomes an evaluation item of said projection optical system, based on said decided coefficients of each term in a Zernike polynomial, and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern, as a  
10 linear sum of said decided coefficients of each term in a Zernike polynomial and said Zernike variation table.

83. The exposure method according to Claim 82 wherein

15 said Zernike variation table is obtained by giving a predetermined value of aberration to each term in said Zernike polynomial and calculating an image forming characteristic of said projection optical system in each of a plurality of terms in said Zernike polynomial.

20

84. An exposure method in which a pattern is transferred onto an object via a projection optical system, said method comprising:

optimizing a weighting function to compensate an  
25 error of a pattern image projected onto said object via said projection optical system, and calculating adjustment information in an adjusting unit that adjusts an image forming state of said pattern image, based on information related to wavefront aberration of said  
30 projection optical system and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern; and  
controlling said adjusting unit based on said

calculated adjustment information to transfer the pattern onto said object.

85. The exposure method according to Claim 84  
5 wherein  
for the calculation of said adjustment information,  
the least-squares method is used.

86. The exposure method according to Claim 85  
10 wherein  
coefficients of each term in a Zernike polynomial  
are decided based on said information related to  
wavefront aberration, and  
for the calculation of said adjustment information,  
15 the decided coefficients of each term in a Zernike  
polynomial are used.

87. The exposure method according to Claim 86  
wherein  
20 said weighting function is a function that performs  
weighting on said decided coefficients of each term of a  
Zernike polynomial.

88. The exposure method according to Claim 87  
25 wherein  
said Zernike variation table is obtained by giving  
a predetermined value of aberration to each term in a  
Zernike polynomial and calculating an image forming  
characteristic of said projection optical system in each  
30 of a plurality of terms in said Zernike polynomial.

89. The exposure method according to Claim 84  
wherein

for the calculation of said adjustment information, data related to a relation between an adjustment amount of said adjusting unit and a change in coefficients of each term in a Zernike polynomial is used.

5

90. The exposure method according to Claim 89 wherein

said data includes at least data related to a relation between an adjustment amount of an optical element of said projection optical system and a change in coefficients of each term in said Zernike polynomial.

10

91. The exposure method according to Claim 84 wherein

said adjustment information includes an adjustment amount related to at least one of movement of an optical element of said projection optical system and a characteristic of illumination light irradiated on said pattern.

15  
20

92. The exposure method according to Claim 84 wherein

by controlling said adjusting unit, at least one of movement of an optical element of said projection optical system and change of a characteristic of illumination light irradiated on said pattern is performed.

25

93. An exposure apparatus that transfers a pattern onto an object via a projection optical system, said exposure apparatus comprising:

30

an adjusting unit that adjusts an image forming state of a pattern image projected onto said object via said projection optical system; and

a computing unit that optimizes a weighting function to compensate an error of said pattern image, and calculates adjustment information in said adjusting unit, based on information related to wavefront aberration of said projection optical system and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern.

10           94. The exposure apparatus according to Claim 93 wherein

for the calculation of the adjustment information, the least-squares method is used.

15           95. The exposure apparatus according to Claim 94 wherein

coefficients of each term in a Zernike polynomial are decided based on said information related to wavefront aberration, and

20           for the calculation of said adjustment information, the decided coefficients of each term in a Zernike polynomial are used.

25           96. The exposure apparatus according to Claim 95 wherein

said weighting function is a function that performs weighting on said decided coefficients of each term of a Zernike polynomial.

30           97. The exposure apparatus according to Claim 96 wherein

said Zernike variation table is obtained by giving a predetermined value of aberration to each term in a

Zernike polynomial and calculating an image forming characteristic of said projection optical system in each of a plurality of terms in said Zernike polynomial.

5           98. The exposure apparatus according to Claim 93 wherein

          for the calculation of said adjustment information, data related to a relation between an adjustment amount of said adjusting unit and a change in coefficients of  
10 each term in a Zernike polynomial is used.

          99. The exposure apparatus according to Claim 98 wherein

          said data includes at least data related to a  
15 relation between an adjustment amount of an optical element of said projection optical system and a change in coefficients of each term in said Zernike polynomial.

          100. The exposure apparatus according to Claim 93  
20 wherein

          said adjustment information includes an adjustment amount related to at least one of movement of an optical element of said projection optical system and a characteristic of illumination light irradiated on said  
25 pattern.

          101. The exposure apparatus according to Claim 93 wherein

          said adjusting unit performs at least one of  
30 movement of an optical element of said projection optical system and change of a characteristic of illumination light irradiated on said pattern.

102. The exposure apparatus according to Claim 93, further comprising:

an illumination system that includes a shaping optical system that makes said illumination condition  
5 variable, wherein

said computing unit uses, when said illumination condition is changed, a Zernike variation table corresponding to the changed illumination condition for the calculation of said adjustment information.

10

103. A device manufacturing method including a lithographic process, wherein

in said lithographic process, exposure is performed using said exposure apparatus according to any one of  
15 Claims 93 to 102

104. A device manufacturing method including a lithographic process, wherein

in said lithographic process, exposure is performed  
20 using said exposure method according to any one of Claims 62 to 65 and 82 to 92.

105. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an  
25 object via a projection optical system execute a predetermined process, said program making said control computer execute:

a deciding procedure in which coefficients of each term in a Zernike polynomial are decided based on  
30 information related to wavefront aberration of said projection optical system; and

a calculating procedure in which an image forming characteristic that becomes an evaluation item of said

projection optical system is calculated, based on said decided coefficients of each term in a Zernike polynomial and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern, as a linear sum of said decided coefficients of each term in a Zernike polynomial and said Zernike variation table.

106. A program that makes a control computer of an exposure apparatus that transfers a pattern onto an object via a projection optical system execute a predetermined process, said program making said control computer execute:

a calculating procedure in which a weighting function to compensate an error of a pattern image projected onto said object is optimized, and adjustment information in an adjusting unit that adjusts an image forming state of said pattern image is calculated, based on information related to wavefront aberration of said projection optical system, and a Zernike variation table that corresponds to a pattern to be transferred onto said object and an illumination condition of the pattern; and

a controlling procedure in which said adjusting unit is controlled based on said calculated adjustment information to transfer the pattern onto said object.

107. An information storage medium in which the program according to any one of Claims 79 to 81, 105 and 106 is recorded that can be read by a computer.