



(51) International Patent Classification:

E21B 34/08 (2006.01) *E21B 43/10* (2006.01)
E21B 34/14 (2006.01) *E21B 47/12* (2012.01)

(21) International Application Number:

PCT/US2011/052383

(22) International Filing Date:

20 September 2011 (20.09.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/384,493 20 September 2010 (20.09.2010) US
13/227,847 8 September 2011 (08.09.2011) US

(71) Applicant (for all designated States except US):
WEATHERFORD/LAMB, INC. [US/US]; 515 Post Oak
Boulevard, Suite 600, Houston, Texas 77027 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NOSKE, Joe**
[US/US]; 408 Peden Street, Houston, Texas 77006 (US).
SMITH, Roddie R. [US/GB]; Parkhill House, Dyce, Ab-
erdeen Aberdeenshire AB21 7AL (GB). **SMITH, Paul L.**
[US/US]; 1226 Strawberry Park Lane, Katy, Texas 77450
(US). **BAILEY, Thomas F.** [US/US]; 13055 Pebblebrook,
Houston, Texas 77079 (US). **MCDOWELL, Christopher**
L. [US/US]; 2519 Roman Forest Blvd., New Caney, Texas
77357 (US). **TILTON, Frederick T.** [US/US]; 5807 Cim-
maron Creek Court, Spring, Texas 77379 (US).

(74) Agents: **PATTERSON, William B.** et al.; Patterson &
Sheridan, LLP, 3040 Post Oak Blvd., Suite 1500, Houston,
Texas 77056 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,

[Continued on next page]

(54) Title: SIGNAL OPERATED ISOLATION VALVE




FIG. 2A

(57) Abstract: A method of drilling a wellbore includes drilling the wellbore through a formation by injecting drilling fluid through a drill string and rotating a drill bit. The drill string includes a shifting tool, a receiver in communication with the shifting tool, and the drill bit. The method further includes retrieving the drill string from the wellbore through a casing string until the shifting tool reaches an actuator. The casing string includes an isolation valve in an open position and the actuator. The method further includes sending a wireless instruction signal to the receiver. The shifting tool engages the actuator in response to the receiver receiving the instruction signal. The method further includes operating the actuator using the engaged shifting tool, thereby closing the isolation valve and isolating the formation from an upper portion of the wellbore.



HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,

LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:

25 April 2013