[Name of Document] CLAIMS

1. A container for a refrigerating machine comprising:

a storeroom storing a stored objective;

a housing chamber housing an evaporator and an evaporator fan and guiding an inside air in the storeroom to flowing back to the storeroom after passing through the evaporator;

a first ventilation duct connected to the housing chamber, the first ventilation duct having a first blower fan and a first heat storage body that are disposed separately;

a second ventilation duct connected to the housing chamber, the second ventilation duct having a second blower fan and a second heat storage body that are disposed separately; and

a controller controlling the first blower fan and the second blower fan, wherein

the controller controls the first blower fan and the second blower fan and switches between (i) a mode in which an outside air inflows through the first ventilation duct, and the inside air outflows through the second ventilation duct and (ii) a mode in which an outside air inflows through the second ventilation duct, and the inside air outflows through the first ventilation duct, at a specified time interval,

the first ventilation duct and the second ventilation duct are located on a same level in a vertical direction,

the first ventilation duct has a first connecting port connected to the housing chamber,

the second ventilation duct has a second connecting port connected to the housing chamber, ~~and~~

the first connecting port and the second connecting port are arranged in parallel with respect to a flow direction of air flowing in the housing chamber,

the first blower fan is located on a side adjacent to the housing chamber with respect to the first heat storage body, and

the second blower fan is located on a side adjacent to the housing chamber with respect to the second heat storage body.

2. The container for a refrigerating machine according to claim 1, further comprising

a gas concentration detector detecting a gas concentration of the inside air, wherein

the controller regulates the gas concentration to be kept at an optimum gas concentration that is optimum for the stored objective by controlling the first blower fan and the second blower fan.

3. The container for a refrigerating machine according to claim 1 or 2, wherein

each of the first heat storage body and the second heat storage body has a length that is longer than or equal to 150 mm and shorter than or equal to 200 mm in a flow direction of the outside air or the inside air, and

each of the first heat storage body and the second heat storage body includes a latticed part having a hydraulic diameter that is longer than or

oxygen concentration detected by the gas concentration detector is higher than or equal to a second threshold value.

11. The container for a refrigerating machine according to any one of claims 1 to 10, wherein

a ventilator is provided that includes the first ventilation duct, the second ventilation duct, the first blower fan, the second blower fan, the first heat storage body, and the second heat storage body ~~are integrated with each other to provide a ventilator~~.

12. The container for a refrigerating machine according to any one of claims 1 to 11, wherein

the specified time interval is set to be longer than or equal to 10 seconds and to be shorter than or equal to 55 seconds.

13. The container for a refrigerating machine according to any one of claims 5, 8, 10, wherein

the door is provided to be rotatably,

at least one of the first ventilation duct or the second ventilation duct has a magnet made of a permanent magnet or an electromagnet,

the door is kept to be closed due to an attractive force of the magnet when the door closes the first ventilation duct and the second ventilation duct, and

the first ventilation duct and the second ventilation duct are open when the first blower fan and the second blower fan are operated.

14. The container for a refrigerating machine according to any one of claims 1 to 13, wherein

the first blower fan is located between the housing chamber and the first heat storage body, and

the second blower fan is located between the housing chamber and the second heat storage body.

15. The container for a refrigerating machine according to claim 1, wherein

the first blower fan is located in the first connecting port, and

the second blower fan is located in the second connecting port.